



RF EXPOSURE EVALUATION

Applicant Name:
 Samsung Electronics Co., Ltd.
 129, Samsung-ro, Maetan dong,
 Yeongtong-gu, Suwon-si
 Gyeonggi-do, 16677, Korea

Date of Evaluation:
 11/16/2021
Test Site/Location:
 PCTEST Lab, Columbia, MD, USA
Document Serial No.:
 1M2110180128-04.A3L

FCC ID: **A3LEJPS908**

APPLICANT: **SAMSUNG ELECTRONICS CO., LTD.**

DUT Type: Stylus
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: EJ-PS908

SAR Test Exclusion


This device contains a transmitter with Bluetooth LE that may be used in close proximity to the user's body. The maximum allowed output power of the 2.4 GHz Bluetooth LE module is 1.0 mW.

Per FCC KDB Publication 447498 D01v06, 1g SAR exclusion threshold for distance < 50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Distance (mm)}} \times \sqrt{\text{Frequency (GHz)}} \leq 3.0$$



Based on the maximum output power of Bluetooth LE (rounded to the nearest mW) and the antenna to user separation distance, Bluetooth LE SAR was not required: $[(1 / 5) * \sqrt{2.480}] = 0.31 \leq 3.0$. Per FCC KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation. Since the minimum separation distance is < 5mm, a distance of 5 mm is applied to determine SAR test exclusion.

Therefore, no SAR test is required to determine that this device will not exceed the FCC RF Exposure limit when being used at 0 mm from the human body.



Randy Ortanez
 President



FCC ID: A3LEJPS908	 RF EXPOSURE EVALUATION		Approved by: Quality Manager
Document S/N: 1M2110180128-04.A3L	Evaluation Date: 11/16/2021	DUT Type: Stylus	Page 1 of 1