

TEST REPORT

OF

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID : A3LEPNG930

Equipment Under Test : WIRELESS CHARGER
Model Name : EP-NG930
Applicant : Samsung Electronics Co., Ltd.
Manufacturer : Samsung Electronics Co., Ltd.
Date of Test(s) : 2016.02.05 ~ 2016.02.11
Date of Issue : 2016.02.15

In the configuration tested, the EUT complied with the standards specified above.

Tested By:




Youngmin Park

Date:

2016.02.15

Approved By:



Logan Lee

Date:

2016.02.15

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

<u>TABLE OF CONTENTS</u>	Page
1. General Information -----	3
2. Test Result -----	6

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General information

1.1. Testing laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of applicant

Applicant : Samsung Electronics Co., Ltd.

Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea

Contact Person : Kim, Kyung-Won

Phone No. : +82 31 301 0274

1.3. Description of EUT

Kind of Product	WIRELESS CHARGER
Model Name	EP-NG930
Power Supply	DC 5 V, DC 9 V (Used AC 100 V ~ 240 V adaptor)
Frequency Range	110 kHz ~ 148 kHz
Antenna Type	Inductive loop coil antenna

1.4. Declarations by the manufacturer

- Operation temperature: -20 °C ~ 70 °C
- The EUT has 2 loop coil antennas, and only one antenna can transmit at once.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.5. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Spectrum Analyzer	R&S	FSV30	100768	Mar. 24, 2015	Annual	Mar. 24, 2016
E-Field Probe	D.A.R.E!! Instruments	RadiSense 4	13I00444SNO04	Aug. 05, 2015	Annual	Aug. 05, 2016
Magnetic Field Sensor	HIOKI	0850-B1	3471	Jul. 16, 2015	Annual	Jul. 16, 2016
Magnetic Field Hitester	HIOKI	FT3470-50	140430999	Jul. 16, 2015	Annual	Jul. 16, 2016
DC Power Supply	Agilent	U8002A	MY50060028	Mar. 23, 2015	Annual	Mar. 23, 2016
Anechoic Chamber	SY Corporation	L x W x H (9.6 m x 6.4 m x 6.6 m)	N/A	N.C.R.	N/A	N.C.R.

1.6. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL009494	2016.02.15	Initial

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.7. Worst case of test configurations


In order to check all kinds of possible configurations, EUT was evaluated with appropriate client and under each charging condition as below table.

EUT configuration	Type	Description
Charging Mode with client device (Model : SM-G930V, FCC ID : A3LSMG930US)	DC 5.0 V	Less than 1 % of battery
		Less than 50 % of battery
		100 % full charging of battery
	DC 9.0 V	Less than 1 % of battery
		Less than 50 % of battery
		100 % full charging of battery

Operating configurations :

Client device (SM- G930V)

- While the client device was in airplane mode (Trace#1 “M1”)
- While the client device was connected to an active data connection (Trace#2 “M2”) The device was tested under all modes and bands like 2G and 3G. In the result, **PCS GSM / GPRS1900 / 1 TX** was found in **Middle channel**.
- While the wireless charger is charging with the client device turned off. (Trace#3 “M3”)




Plot – fundamental emission comparison

- The level of Trace#2 was more than Trace#1 and 3 so Trace#2 was selected.
- Trace#2 as **PCS GSM / GPRS1900 / 1 TX** which was found in **Middle channel** should be tested with the client device as a worst case.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. Test Result

2.1. Test Setup



2.2. Measurement procedure

- a) The RF exposure test was performed in anechoic chamber.
- b) The measurement probe was placed at test distance (10 cm) which is between the edge of the charger and the geometric center of probe.
- c) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- d) The EUT was measured according to the dictates of KDB 680106 D01v02.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.3. Equipment Approval Considerations item 5.2 of KDB 680106 D01v02.

a) Power transfer frequency is less than 1 MHz.

- The device operates at a frequency of 110 kHz to 148 kHz.

b) Output power from each primary coil is less than 5 watts.

- DC 5 V condition → Output power from each primary coil : 5 W (Max.)
- DC 9 V condition → Output power from each primary coil : 9 W (Max.)

c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

- The transfer system including a charging system with multiple primary coils is to detect and allow only between individual pairs of coils.

d) Client device is inserted in or placed directly in contact with the transmitter.

- Client device is placed directly in contact with the transmitter.

e) The maximum coupling surface area of the transmit (charging) device:

- The EUT coupling surface area : $11.3 \text{ cm (W)} \times 10.9 \text{ cm (H)} = 123.17 \text{ cm}^2$,
 $60 \text{ cm}^2 < 123.17 \text{ cm}^2 < 400 \text{ cm}^2$

f) Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30 % of the MPE limit.

- Refer to following test results.
The EUT field strength levels < MPE limit 1.63 A/m
 $1.461 \text{ A/m (Max.)} < 1.63 \text{ A/m}$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

§1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter

TABLE 1 - LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational /Control Exposures				
0.3 – 3.0	614	1.63	*(100)	6
3.0 – 30	1842/f	4.89/f	*(900/f ²)	6
30 – 300	61.4	0.163	1.0	6
300 – 1 500			f/300	6
1 500 – 100 000			5	6
(B) Limits for General Population / Uncontrol Exposures				
0.3 – 1.34	614	1.63	*(100)	30
1.34 – 30	824/f	2.19/f	*(180/f ²)	30
30 – 300	27.5	0.073	0.2	30
300 – 1 500			f/1 500	30
1 500 – 100 000			1.0	30

f = frequency in MHz

* = Plane wave equivalent power density

Note 1 to Table 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2 to Table 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.5. E and H field strength

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

2.5.1. E-Field Strength at 10 cm from the edges surrounding the EUT

Test Mode : Charging mode with client device (DC 5 V) _Coil#1

Test condition: Charging mode (less than 1 % battery status of client device)

Frequency Range (kHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
110 ~ 148	7.15	7.03	10.30	6.90	7.11	8.59	614.00

Test condition: Charging mode (less than 50 % battery status of client device)

Frequency Range (kHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
110 ~ 148	7.10	7.01	10.20	7.00	7.04	8.55	614.00

Test condition: Charging mode (100 % battery status of client device)

Frequency Range (kHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
110 ~ 148	7.11	7.02	10.10	6.98	7.01	8.54	614.00

Note.

1. All antennas of operation were investigated and the worst-case antenna was reported considered the highest exposure.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Test Mode : Charging mode with client device (DC 9 V) _Coil#1

Test condition: Charging mode (less than 1 % battery status of client device)

Frequency Range (kHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
110 ~ 148	7.18	8.05	12.08	7.10	7.06	8.81	614.00

Test condition: Charging mode (less than 50 % battery status of client device)

Frequency Range (kHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
110 ~ 148	7.64	7.56	11.70	7.06	7.08	8.87	614.00

Test condition: Charging mode (100 % battery status of client device)

Frequency Range (kHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
110 ~ 148	7.41	7.33	11.40	7.01	7.05	8.80	614.00

Note.

1. All antennas of operation were investigated and the worst-case antenna was reported considered the highest exposure.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.5.2. H-Field Strength at 10 cm from the edges surrounding the EUT

Test Mode : Charging mode with client device (DC 5 V) _Coil#1

Test condition: Charging mode (less than 1 % battery status of client device)

Frequency Range (kHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
110 ~ 148	0.474	0.479	1.448	0.580	0.543	0.735	1.630

Test condition: Charging mode (less than 50 % battery status of client device)

Frequency Range (kHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
110 ~ 148	0.409	0.424	1.291	0.496	0.530	0.680	1.630

Test condition: Charging mode (100 % battery status of client device)

Frequency Range (kHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
110 ~ 148	0.426	0.434	1.295	0.526	0.539	0.686	1.630

Note.

1. All antennas of operation were investigated and the worst-case antenna was reported considered the highest exposure.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Test Mode : Charging mode with client device (DC 9 V) _Coil#1

Test condition: Charging mode (less than 1 % battery status of client device)

Frequency Range (kHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
110 ~ 148	0.485	0.498	1.461	0.594	0.569	0.749	1.630

Test condition: Charging mode (less than 50 % battery status of client device)

Frequency Range (kHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
110 ~ 148	0.416	0.428	1.410	0.501	0.534	0.686	1.630

Test condition: Charging mode (100 % battery status of client device)

Frequency Range (kHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
110 ~ 148	0.448	0.455	1.409	0.565	0.541	0.731	1.630

Note.

1. All antennas of operation were investigated and the worst-case antenna was reported considered the highest exposure.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.