


	1	2	3	4	5	6	7	8
A			Rev. No					
B								
C								
D								
E								
F								
G								
H								
I								
J								
K								
L								

Technical Description

1. Use 'FILM' provided by 'SAMSUNG' for letter and contents
2. Background color is 'WHITE', letter color is 'BLACK' (reverse for SAMSUNG LOGO)
3. Put 'release paper' on the back side after the adhesive.
4. No blur and spread for letter
5. Proceed with manufacturing process after the approval of R&D Group
6. The spec. of product must be based on approved limit samples.
7. Stock on as a ROLL
8. Follow drawing instruction above for CE or WEEE mark
9. Unify material and color as one color (blue) for glassine paper

MAT.	White polypropylene 80μ	FIN.	Semitransparency OPP Lamination + UVP Coating		
TITLE	GT-I9100 LABEL (R)-MAIN-EU				
UNIT	mm	DESIGNED	CHECKED	APPROVED	PROJECTION
TOLERANCE	+0.0 -0.1	jukyun Kim	kyeonghwan jo	junesop kim	
SCALE	N/S				
Manufacture	HANSUNG P&I	10-10-08	10-10-08	10-10-08	SHEET NO 1/1
		Doc. CODE	GH68-00000A		



The label is placed inside the battery compartment