



MEASUREMENT REPORT
FCC PART 15.247 WLAN 802.11a/b/g/n/ac

Applicant Name:
Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:
02/02 - 02/15/2013, 03/14/2013
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0Y1307181296.A3L


FCC ID:	A3LGTI9507
APPLICANT:	Samsung Electronics, Co. Ltd.

Application Type: Certification
Model(s): GT-I9507
EUT Type: Portable Handset
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15.247
Test Procedure(s): ANSI C63.10-2009, KDB 558074 v02

Mode	Tx Frequency (MHz)	Avg Conducted		Peak Conducted	
		Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)
802.11b	2412 - 2462	48.865	16.89	90.573	19.57
802.11g	2412 - 2462	41.400	16.17	163.682	22.14
802.11n	2412 - 2462	20.989	13.22	122.180	20.87
802.11a	5745 - 5825	20.893	13.20	118.304	20.73
802.11n (20MHz)	5745 - 5825	19.011	12.79	116.413	20.66
802.11n (40MHz)	5755 - 5795	16.520	12.18	92.045	19.64
802.11ac (80MHz)	5775	13.213	11.21	68.549	18.36

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2009 and KDB 558074. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President







FCC ID: A3LGTI9507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 1 of 66	

TABLE OF CONTENTS

FCC PART 15.247 MEASUREMENT REPORT.....		3
1.0 INTRODUCTION.....		4
1.1 SCOPE.....		4
1.2 PCTEST TEST LOCATION.....		4
2.0 PRODUCT INFORMATION.....		5
2.1 EQUIPMENT DESCRIPTION.....		5
2.2 DEVICE CAPABILITIES.....		5
2.3 TEST CONFIGURATION.....		5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....		5
2.5 LABELING REQUIREMENTS.....		5
3.0 DESCRIPTION OF TEST.....		6
3.1 EVALUATION PROCEDURE.....		6
3.2 AC LINE CONDUCTED EMISSIONS.....		6
3.3 RADIATED EMISSIONS.....		7
4.0 ANTENNA REQUIREMENTS.....		8
5.0 TEST EQUIPMENT CALIBRATION DATA.....		9
6.0 TEST RESULTS.....		10
6.1 SUMMARY.....		10
6.2 6DB BANDWIDTH MEASUREMENT – 802.11A/B/G/N/AC.....		11
6.3 OUTPUT POWER MEASUREMENT – 802.11B/G/N (2.4GHZ).....		22
6.4 OUTPUT POWER MEASUREMENT – 802.11A/N/AC (5GHZ).....		24
6.5 POWER SPECTRAL DENSITY (802.11A/B/G/N/AC).....		25
6.6 CONDUCTED EMISSIONS AT THE BAND EDGE.....		36
6.7 CONDUCTED SPURIOUS EMISSIONS.....		44
6.8 RADIATED SPURIOUS EMISSION MEASUREMENTS.....		52
6.9 RADIATED RESTRICTED BAND EDGE MEASUREMENTS.....		58
6.10 LINE-CONDUCTED TEST DATA.....		62
7.0 CONCLUSION.....		66

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 2 of 66	



MEASUREMENT REPORT

FCC Part 15.247



§ 2.1033 General Information

APPLICANT: Samsung Electronics, Co. Ltd.

APPLICANT ADDRESS: 129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si, Gyeonggi-do 443-742, Korea

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): Part 15.247

IC SPECIFICATION(S): RSS-210 Issue 8

MODEL NAME: GT-I9507

FCC ID: A3LGTI9507

Test Device Serial No.: 044C4, 0445B Production Pre-Production Engineering



FCC CLASSIFICATION: Digital Transmission System (DTS)

DATE(S) OF TEST: 02/02 - 02/15/2013, 03/14/2013



TEST REPORT S/N: 0Y1307181296.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LGTI9507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 3 of 66

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 4 of 66

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LGTI9507**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Band 5 LTE (1.4,3,5,10MHz BW), 802.11a/b/g/n/ac WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

Notes:

- 1) 5GHz WLAN (DTS/NII) operation is possible in 20MHz, 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles are as follows:
 - 802.11b – 99.4%
 - 802.11a/g/n 20MHz Bandwidth – 98.9%
 - 802.11n 40MHz Bandwidth – 98.7%
 - 802.11ac 80MHz Bandwidth – 98.1%
- 2) The circuitry for this device is electrically identical to a previously certified device bearing the FCC ID: A3LGTI9505. Thus, the data found within this report was taken from the A3LGTI9505 device.

2.3 Test Configuration

The Samsung Portable Handset FCC ID: A3LGTI9507 was tested per the guidance of ANSI C63.10-2009 and KDB 558074. See Sections 3.2, 3.3, and 6.1 of this test report for a description of the AC line conducted emissions, radiated emissions, and antenna port conducted emissions test setups, respectively.



2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.5 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: A3LGTI9507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 5 of 66	

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009), and the guidance provided in KDB 558074 were used in the measurement of the **Samsung Portable Handset FCC ID: A3LGTI9507**.

Deviation from measurement procedure.....None



3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 8.51.0.



FCC ID: A3LGTI9507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 6 of 66

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by varying: the mode of operation or resolution, clock or data rate, scrolling H pattern to the EUT and/or support equipment, and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

FCC ID: A3LGT19507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 7 of 66	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:



The **Samsung Portable Handset FCC ID: A3LGTI9507** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Ch.	BW (MHz)	Frequency (MHz)
149	20	5745
151	20 / 40	5755
153	20	5765
155	20 / 80	5775
157	20	5785

Ch.	BW (MHz)	Frequency (MHz)
159	20 / 40	5795
161	20	5805
163	20	5815
165	20	5825

Table 4-1. Frequency/ Channel Operations

FCC ID: A3LGTI9507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 8 of 66

5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/10/2012	Annual	7/10/2013	N/A
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	2/13/2012	Annual	2/13/2013	N/A
-	WL25-1	Conducted Cable Set (25GHz)	1/16/2013	Annual	1/16/2014	N/A
-	WL40-1	Conducted Cable Set (40GHz)	1/29/2013	Annual	1/29/2014	N/A
Agilent	8447D	Broadband Amplifier	5/8/2012	Annual	5/8/2013	1937A03348
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Anritsu	MA2411B	Pulse Sensor	9/19/2012	Annual	9/19/2013	1027293
Anritsu	ML2495A	Power Meter	10/11/2012	Annual	10/11/2013	1039008
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	5/10/2012	Annual	5/10/2013	121034
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Biennial	7/22/2013	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/30/2012	Biennial	5/30/2014	135427
ETS Lindgren	3160-10	26.5-40 GHz Standard Gain Horn	6/6/2012	Biennial	6/6/2014	130993
Mini-Circuits	VHF-3100+	High Pass Filter	1/17/2013	Annual	1/17/2014	30841
Mini-Circuits	VHF-8400+	3.4GHz - 9.9GHz High Pass Filter	1/17/2013	Annual	1/17/2014	31048
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	6/26/2012	Annual	6/26/2013	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/30/2012	Annual	5/30/2013	100040
Rohde & Schwarz	TS-PR40	26.5-40 GHz Pre-Amplifier	6/6/2012	Annual	6/6/2013	100037
Rohde & Schwarz	ESU26	EMI Test Receiver	2/15/2012	Annual	2/15/2013	100342
Solar Electronics	8012-50-R-24-BNC	LISN	6/23/2011	Biennial	6/23/2013	310233
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 5-1. Annual Test Equipment Calibration Schedule

Note:

The "RE2" cable set listed above was not used for testing past its calibration due date.

FCC ID: A3LGT19507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 9 of 66

6.0 TEST RESULTS

6.1 Summary



Company Name: Samsung Electronics, Co. Ltd.
 FCC ID: A3LGTI9507
 FCC Classification: Digital Transmission System (DTS)
 Data Rate(s) Tested: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)
6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (a/g)
6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps,
52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n – 20MHz)
13.5/15Mbps, 27/30Mbps, 40.5/45Mbps, 54/60Mbps, 81/90Mbps, 108/120Mbps,
121.5/135Mbps, 135/150Mbps (n – 40MHz)
350/391Mbps, 391/433.3Mbps (ac – 80MHz)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
15.247(a)(2)	RSS-210 [A8.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 6.2
15.247(b)(3)	RSS-210 [A8.4]	Transmitter Output Power	< 1 Watt		PASS	Sections 6.3, 6.4
15.247(e)	RSS-210 [A8.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 6.5
15.247(d)	RSS-210 [A8.5]	Band Edge / Out-of-Band Emissions	Conducted ≥ 30dBc		PASS	Sections 6.6, 6.7
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Sections 6.8, 6.9
15.207	RSS-Gen [7.2.2]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 6.10

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “WLAN Automation”, Version 1.5.

FCC ID: A3LGTI9507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 10 of 66

6.2 6dB Bandwidth Measurement – 802.11a/b/g/n/ac

§15.247(a)(2); RSS-210 [A8.2]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

KDB 558074 v02 – Section 7.2 Option 2

Test Settings

1. RBW = 1 – 5% of DTS BW, not to exceed 100kHz
2. VBW \geq 3 x RBW
3. Detector = Peak
4. Trace mode = max hold
5. Sweep = auto couple
6. The trace was allowed to stabilize
7. The automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The “X” dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.



Figure 6-1. Test Instrument & Measurement Setup



Test Notes


None

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 11 of 66	


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2412	1	b	1	9.102	0.500	Pass
2437	6	b	1	9.550	0.500	Pass
2462	11	b	1	9.104	0.500	Pass
2412	1	g	6	16.36	0.500	Pass
2437	6	g	6	16.38	0.500	Pass
2462	11	g	6	16.37	0.500	Pass
2412	1	n	6.5/7.2 (MCS0)	17.61	0.500	Pass
2437	6	n	6.5/7.2 (MCS0)	17.64	0.500	Pass
2462	11	n	6.5/7.2 (MCS0)	17.62	0.500	Pass
5745	149	a	6	16.37	0.500	Pass
5785	157	a	6	16.37	0.500	Pass
5825	165	a	6	16.38	0.500	Pass
5745	149	n (20MHz)	6.5/7.2 (MCS0)	16.37	0.500	Pass
5785	157	n (20MHz)	6.5/7.2 (MCS0)	16.37	0.500	Pass
5825	165	n (20MHz)	6.5/7.2 (MCS0)	16.35	0.500	Pass
5755	151	n (40MHz)	13.5/15 (MCS0)	36.33	0.500	Pass
5795	159	n (40MHz)	13.5/15 (MCS0)	36.31	0.500	Pass
5775	155	n (80MHz)	350/391 (MCS8)	75.57	0.500	Pass

Table 6-2. Conducted Bandwidth Measurements

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 12 of 66




Plot 6-1. 6dB Bandwidth Plot (802.11b – Ch. 1)




Plot 6-2. 6dB Bandwidth Plot (802.11b – Ch. 6)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 13 of 66




Plot 6-3. 6dB Bandwidth Plot (802.11b – Ch. 11)




Plot 6-4. 6dB Bandwidth Plot (802.11g – Ch. 1)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 14 of 66




Plot 6-5. 6dB Bandwidth Plot (802.11g – Ch. 6)




Plot 6-6. 6dB Bandwidth Plot (802.11g – Ch. 11)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 15 of 66




Plot 6-7. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 1)




Plot 6-8. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 16 of 66




Plot 6-9. 6dB Bandwidth Plot (802.11n (2.4GHz) – Ch. 11)




Plot 6-10. 6dB Bandwidth Plot (802.11a – Ch. 149)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 17 of 66




Plot 6-11. 6dB Bandwidth Plot (802.11a – Ch. 157)




Plot 6-12. 6dB Bandwidth Plot (802.11a – Ch. 165)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 18 of 66




Plot 6-13. 6dB Bandwidth Plot (20MHz BW 802.11n (5.8GHz) – Ch. 149)




Plot 6-14. 6dB Bandwidth Plot (20MHz BW 802.11n (5.8GHz) – Ch. 157)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 19 of 66




Plot 6-15. 6dB Bandwidth Plot (20MHz BW 802.11n (5.8GHz) – Ch. 165)




Plot 6-16. 6dB Bandwidth Plot (40MHz BW 802.11n (5.8GHz) – Ch. 151)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 20 of 66



Plot 6-17. 6dB Bandwidth Plot (40MHz BW 802.11n (5.8GHz) – Ch. 159)



Plot 6-18. 6dB Bandwidth Plot (80MHz BW 802.11ac (5.8GHz) – Ch. 155)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 21 of 66

6.3 Output Power Measurement – 802.11b/g/n (2.4GHz)

§15.247(b)(3); RSS-210 [A8.4]

Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

KDB 558074 v02 – Section 8.1.3 Option 3 (peak power measurements)

KDB 558074 v02 – Section 8.2.3 Option 3 (average power measurements)

Test Settings

1. Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter and power sensor with a thermocouple detector. The EUT was operating with a duty cycle larger than 98% so triggering and gating functionalities were not necessary. The trace was averaged over 100 traces to obtain the final measured average power.
2. Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter and power sensor. The power sensor employs a VBW = 50MHz.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-2. Test Instrument & Measurement Setup

Test Notes

For 802.11ac (80MHz BW) conducted power measurements, the results obtained using the 50MHz VBW Anritsu power sensor were compared to the results obtained by using the channel integration method (Section 8.1.2 of KDB 558074) on a spectrum analyzer. The powers measured on the spectrum analyzer were found to match the powers from the power meter so it was determined that the limited VBW of the power sensor did not have an effect on the peak power measurements.

FCC ID: A3LGT19507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 22 of 66

Mode	Freq [MHz]	Channel	Detector	802.11b Conducted Power [dBm]			
				Data Rate [Mbps]			
				1	2	5.5	11
802.11b	2412	1	AVG	16.59	16.64	16.63	16.65
			PEAK	19.57	19.53	19.49	19.24
802.11b	2437	6	AVG	16.67	16.78	16.83	16.89
			PEAK	19.43	19.46	19.51	19.53
802.11b	2462	11	AVG	16.28	16.29	16.31	16.28
			PEAK	18.91	18.89	18.86	18.79



Table 6-3. 802.11b Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	802.11g Conducted Power [dBm]							
				Data Rate [Mbps]							
				6	9	12	18	24	36	48	54
802.11g	2412	1	AVG	15.69	15.56	15.57	15.71	15.74	15.61	16.17	13.61
			PEAK	21.31	21.48	21.47	21.48	21.68	22.13	22.04	19.99
802.11g	2437	6	AVG	15.77	15.89	15.91	15.62	15.68	15.82	16.09	13.69
			PEAK	21.58	21.64	21.69	21.33	21.52	22.02	22.14	20.04
802.11g	2462	11	AVG	15.33	15.42	15.41	15.36	15.20	15.22	15.64	13.41
			PEAK	20.91	21.03	21.20	20.89	20.86	21.42	21.52	19.72

Table 6-4. 802.11g Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	802.11n (2.4GHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2
802.11n	2412	1	AVG	12.99	12.69	12.74	12.88	12.76	12.83	12.89	12.76
			PEAK	19.22	18.84	19.12	18.94	18.87	18.84	19.19	18.91
802.11n	2437	6	AVG	13.01	12.96	13.06	12.96	13.02	13.14	13.17	13.22
			PEAK	19.26	19.26	19.34	19.28	20.84	20.55	20.83	20.87
802.11n	2462	11	AVG	12.46	12.44	12.39	12.47	12.51	12.56	12.52	12.48
			PEAK	19.95	20.08	20.03	20.26	20.23	20.27	20.13	20.04

Table 6-5. 20MHz BW 802.11n (2.4GHz) Conducted Output Power Measurements

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 23 of 66

6.4 Output Power Measurement – 802.11a/n/ac (5GHz) §15.247(b)(3); RSS-210 [A8.4]

Mode	Freq [MHz]	Channel	Detector	802.11a Conducted Power [dBm]							
				Data Rate [Mbps]							
				6	9	12	18	24	36	48	54
802.11a	5745	149	AVG	12.68	12.72	12.72	12.66	12.63	12.59	12.74	12.53
			PEAK	19.71	19.88	20.06	20.33	19.73	20.29	19.91	19.84
802.11a	5765	153	AVG	13.14	13.15	13.17	13.20	13.11	13.07	13.16	12.85
			PEAK	20.16	20.36	20.38	20.73	20.18	20.70	20.33	20.15
802.11a	5785	157	AVG	13.04	13.06	13.09	13.07	13.06	13.05	13.13	12.89
			PEAK	19.99	20.20	20.32	20.62	20.11	20.62	20.34	20.19
802.11a	5805	161	AVG	12.98	13.10	13.16	13.07	13.03	12.93	13.05	12.89
			PEAK	19.97	20.28	20.48	20.66	20.11	20.57	20.26	20.25
802.11a	5825	165	AVG	13.03	12.96	13.02	13.03	13.00	13.02	13.15	13.08
			PEAK	20.01	20.22	20.33	20.63	20.07	20.70	20.30	20.24

Table 6-6. 802.11a Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5/7.2	13/14.4	19.5/21.7	26/28.9	39/43.4	52/57.8	58.5/65	65/72.2
802.11n	5745	149	AVG	12.77	12.68	12.73	12.74	12.79	12.62	12.69	12.62
			PEAK	20.28	20.35	20.41	20.47	20.51	20.46	20.41	20.32
802.11n	5765	153	AVG	12.61	12.59	12.77	12.70	12.71	12.61	12.71	12.63
			PEAK	20.12	20.21	20.43	20.35	20.45	20.43	20.52	20.45
802.11n	5785	157	AVG	12.59	12.55	12.61	12.65	12.72	12.68	12.62	12.56
			PEAK	20.44	20.46	20.12	20.19	20.62	20.61	20.19	20.21
802.11n	5805	161	AVG	12.67	12.59	12.67	12.69	12.68	12.66	12.43	12.49
			PEAK	20.52	20.56	20.29	20.24	20.66	20.64	20.32	20.29
802.11n	5825	165	AVG	12.71	12.68	12.77	12.72	12.71	12.69	12.71	12.72
			PEAK	20.43	20.39	20.57	20.43	20.52	20.50	20.44	20.49



Table 6-7. 20MHz BW 802.11n (5GHz) Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				13.5/15	27/30	40.5/45	54/60	81/90	108/120	121.5/135	135/150
802.11n	5755	151	AVG	11.97	11.98	11.93	11.84	11.67	11.65	11.64	11.69
			PEAK	19.41	18.46	18.34	18.37	18.11	18.21	18.13	18.23
802.11n	5795	159	AVG	11.92	12.05	12.02	12.18	11.72	11.52	11.49	11.52
			PEAK	19.64	18.54	18.59	18.72	18.27	18.21	18.04	18.12

Table 6-8. 40MHz BW 802.11n (5GHz) Conducted Output Power Measurements

Mode	Freq [MHz]	Channel	Detector	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
				Data Rate [Mbps]									
				29.3/32.5	58.5/65	87.8/97.5	117/130	175.5/195	234/260	263.3/292.5	292.5/325	351/390	390/433.3
802.11ac	5775	155	AVG	11.11	11.07	11.21	11.10	11.08	11.01	11.15	11.04	11.08	11.09
			PEAK	18.30	18.36	18.08	17.96	18.05	17.75	17.98	17.76	17.87	17.95

Table 6-9. 40MHz BW 802.11ac (5GHz) Conducted Output Power Measurements

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 24 of 66

6.5 Power Spectral Density (802.11a/b/g/n/ac) §15.247(e); RSS-210 [A8.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

KDB 558074 v02 – Section 9.1 Option 1

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 10kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-3. Test Instrument & Measurement Setup



Test Notes


None

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 25 of 66	


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	1.42	8.00	-6.58	Pass
2437	6	b	1	1.24	8.00	-6.76	Pass
2462	11	b	1	-0.12	8.00	-8.12	Pass
2412	1	g	6	-3.85	8.00	-11.85	Pass
2437	6	g	6	-3.63	8.00	-11.63	Pass
2462	11	g	6	-4.14	8.00	-12.14	Pass
2412	1	n	6.5/7.2 (MCS0)	-6.24	8.00	-14.24	Pass
2437	6	n	6.5/7.2 (MCS0)	-5.63	8.00	-13.63	Pass
2462	11	n	6.5/7.2 (MCS0)	-6.09	8.00	-14.09	Pass
5745	149	a	6	-3.28	8.00	-11.28	Pass
5785	157	a	6	-3.83	8.00	-11.83	Pass
5825	165	a	6	-4.10	8.00	-12.10	Pass
5745	149	n (20MHz)	6.5/7.2 (MCS0)	-6.09	8.00	-14.09	Pass
5785	157	n (20MHz)	6.5/7.2 (MCS0)	-5.99	8.00	-13.99	Pass
5825	165	n (20MHz)	6.5/7.2 (MCS0)	-6.32	8.00	-14.32	Pass
5755	151	n (40MHz)	13.5/15 (MCS0)	-8.49	8.00	-16.49	Pass
5795	159	n (40MHz)	13.5/15 (MCS0)	-9.54	8.00	-17.54	Pass
5775	155	n (80MHz)	350/391 (MCS8)	-11.76	8.00	-19.76	Pass

Table 6-10. Conducted Power Density Measurements

FCC ID: A3LGT19507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 26 of 66




Plot 6-19. Power Spectral Density Plot (802.11b – Ch. 1)




Plot 6-20. Power Spectral Density Plot (802.11b – Ch. 6)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 27 of 66




Plot 6-21. Power Spectral Density Plot (802.11b – Ch. 11)




Plot 6-22. Power Spectral Density Plot (802.11g – Ch. 1)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 28 of 66




Plot 6-23. Power Spectral Density Plot (802.11g – Ch. 6)




Plot 6-24. Power Spectral Density Plot (802.11g – Ch. 11)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 29 of 66




Plot 6-27. Power Spectral Density Plot (802.11n (2.4GHz) – Ch. 11)




Plot 6-28. Power Spectral Density Plot (802.11a – Ch. 149)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 31 of 66




Plot 6-29. Power Spectral Density Plot (802.11a – Ch. 157)




Plot 6-30. Power Spectral Density Plot (802.11a – Ch. 165)



FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 32 of 66




Plot 6-31. Power Spectral Density Plot (20MHz BW 802.11n (5.8GHz) – Ch. 149)




Plot 6-32. Power Spectral Density Plot (20MHz BW 802.11n (5.8GHz) – Ch. 157)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 33 of 66




Plot 6-33. Power Spectral Density Plot (20MHz BW 802.11n (5.8GHz) – Ch. 165)




Plot 6-34. Power Spectral Density Plot (40MHz BW 802.11n (5.8GHz) – Ch. 151)



FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 34 of 66



Plot 6-35. Power Spectral Density Plot (40MHz BW 802.11n (5.8GHz) – Ch. 159)



Plot 6-36. Power Spectral Density Plot (80MHz BW 802.11ac (5.8GHz) – Ch. 155)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 35 of 66	

6.6 Conducted Emissions at the Band Edge

§15.247(d); RSS-210 [A8.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate of 1Mbps for “b” mode, 6 Mbps for “g” mode, 6 Mbps for “a” mode, 6.5/7.2Mbps for 20MHz BW “n” mode, 13.5/15Mbps for 40MHz “n” mode, and 351/390Mbps for 80MHz “ac” mode as these settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 9.1).

Test Procedure Used

KDB 558074 v02 – Section 10.1.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 1MHz
5. Detector = Peak
6. Trace mode = max hold
7. Sweep time = auto couple
8. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.







Figure 6-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 36 of 66	




Plot 6-37. Band Edge Plot (802.11b – Ch. 1)




Plot 6-38. Band Edge Plot (802.11b – Ch. 11)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 37 of 66




Plot 6-39. Band Edge Plot (802.11g– Ch. 1)




Plot 6-40. Band Edge Plot (802.11g – Ch. 11)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 38 of 66




Plot 6-41. Band Edge Plot (802.11n (2.4GHz) – Ch. 1)




Plot 6-42. Band Edge Plot (802.11n (2.4GHz) – Ch. 11)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 39 of 66




Plot 6-43. Band Edge Plot (802.11a – Ch. 149)




Plot 6-44. Band Edge Plot (802.11a – Ch. 165)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 40 of 66




Plot 6-45. Band Edge Plot (20MHz BW 802.11n (5.8GHz) – Ch. 149)




Plot 6-46. Band Edge Plot (20MHz BW 802.11n (5.8GHz) – Ch. 165)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 41 of 66




Plot 6-47. Band Edge Plot (40MHz BW 802.11n (5.8GHz) – Ch. 151)




Plot 6-48. Band Edge Plot (40MHz BW 802.11n (5.8GHz) – Ch. 159)



FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 42 of 66



Plot 6-49. Lower Band Edge Plot (80MHz BW 802.11ac (5.8GHz) – Ch. 155)



Plot 6-50. Upper Band Edge Plot (80MHz BW 802.11ac (5.8GHz) – Ch. 155)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 43 of 66

6.7 Conducted Spurious Emissions

§15.247(d); RSS-210 [A8.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots, the EUT was investigated in all available data rates for “b”, “g”, “a”, “n”, and “ac” modes. The worst case spurious emissions for the 2.4GHz band were found while transmitting in “b” mode at 1 Mbps and are shown in the plots below. The worst case spurious emissions for the 5.8GHz band were found while transmitting in “a” mode at 6 Mbps and are shown in the plots below.

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 9.1).

Test Procedure Used

KDB 558074 v02 – Section 10.1.2

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.









Figure 6-5. Test Instrument & Measurement Setup

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 44 of 66	


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 30dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 30dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

FCC ID: A3LGT19507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 45 of 66




Plot 6-51. Conducted Spurious Plot (802.11b – Ch. 1)




Plot 6-52. Conducted Spurious Plot (802.11b – Ch. 1)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 46 of 66




Plot 6-53. Conducted Spurious Plot (802.11b – Ch. 6)




Plot 6-54. Conducted Spurious Plot (802.11b – Ch. 6)



FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 47 of 66




Plot 6-55. Conducted Spurious Plot (802.11b – Ch. 11)




Plot 6-56. Conducted Spurious Plot (802.11b – Ch. 11)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 48 of 66




Plot 6-57. Conducted Spurious Plot (802.11a – Ch. 149)




Plot 6-58. Conducted Spurious Plot (802.11a – Ch. 149)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 49 of 66




Plot 6-59. Conducted Spurious Plot (802.11a – Ch. 157)




Plot 6-60. Conducted Spurious Plot (802.11a – Ch. 157)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 50 of 66



Plot 6-61. Conducted Spurious Plot (802.11a – Ch. 165)



Plot 6-62. Conducted Spurious Plot (802.11a – Ch. 165)

FCC ID: A3LGT19507	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 51 of 66

6.8 Radiated Spurious Emission Measurements

§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-11 per Section 15.209.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-11. Radiated Limits

Test Procedures Used

ANSI C63.10-2009 (Used for guidance on how to set up the EUT for radiated emissions)



KDB 558074 v02 – Section 10.2.3.3 (average power measurements)

KDB 558074 v02 – Section 10.2.3.2 (peak power measurements)

Test Settings

Average Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz (per KDB 558074 v02 Section 10.2.3.3)
3. RBW = 1MHz
4. VBW = 3MHz
5. Detector = power average (RMS)
6. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 52 of 66	

7. Sweep time = 1 second (Sweep time must be $\geq 10 \times$ (number of measurement points in sweep) \times (transmission symbol period), where the transmission symbol period (in seconds) is defined as the reciprocal of the symbol rate (in bauds or symbols per second). See “Sample Calculations” section below for sample calculations on determining the minimum sweep time based on the EUT transmission data rate)
8. Measurement was performed over a single sweep

Peak Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 1MHz (per KDB 558074 v02 Section 10.2.3.2)
4. VBW = 3MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-6. Test Instrument & Measurement Setup

FCC ID: A3LGT19507	 FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 53 of 66

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 v02 were not used to evaluate this device.
2. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-10.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery. The standard battery for this model is one that contains an embedded NFC antenna.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$



Determining Minimum Sweep Times

- “Transmission Symbol Period” is defined as the reciprocal of the symbol rate, R_s
- An 802.11b signal operating at 1Mbps uses BPSK modulation which uses 2 bits/symbol and, thus, has a symbol rate, R_s , of 0.5Msps
- $\text{Transmission Symbol Period} = 1/R_s = 2\mu s$
- $\text{Minimum sweep time} = 10 \times (\text{number of measurement points in sweep}) \times (\text{transmission symbol period}) = 10 \times 1001 \text{ points} \times 2\mu s = 20ms$

Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 6.8 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + 10 \text{ dB Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 54 of 66

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2412MHz
 Channel: 01



Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4824.00	-104.72	Avg	H	40.24	42.52	53.98	-11.46
4824.00	-97.11	Peak	H	40.24	50.13	73.98	-23.85
12060.00	-135.00	Avg	H	50.16	22.16	53.98	-31.82
12060.00	-125.00	Peak	H	50.16	32.16	73.98	-41.82

Table 6-12. Radiated Measurements

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2437MHz
 Channel: 06

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4874.00	-105.43	Avg	H	40.26	41.83	53.98	-12.15
4874.00	-99.03	Peak	H	40.26	48.23	73.98	-25.75
7311.00	-116.89	Avg	H	43.67	33.79	53.98	-20.19
7311.00	-105.43	Peak	H	43.67	45.25	73.98	-28.73
12185.00	-135.00	Avg	H	50.49	22.49	53.98	-31.49
12185.00	-125.00	Peak	H	50.49	32.49	73.98	-41.49

Table 6-13. Radiated Measurements

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 55 of 66

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]

Worst Case Mode: 802.11b
 Worst Case Transfer Rate: 1 Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11



Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
4924.00	-106.80	Avg	H	40.28	40.48	53.98	-13.50
4924.00	-100.47	Peak	H	40.28	46.81	73.98	-27.17
7386.00	-116.93	Avg	H	43.80	33.87	53.98	-20.10
7386.00	-104.52	Peak	H	43.80	46.28	73.98	-27.69
12310.00	-135.00	Avg	H	50.81	22.81	53.98	-31.17
12310.00	-125.00	Peak	H	50.81	32.81	73.98	-41.17

Table 6-14. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11490.00	-111.94	Avg	H	48.54	0.00	43.60	53.98	-10.38
11490.00	-98.52	Peak	H	48.54	0.00	57.02	73.98	-16.96
22980.00	-104.05	Avg	H	44.43	-9.54	37.84	53.98	-16.14
22980.00	-93.98	Peak	H	44.43	-9.54	47.91	73.98	-26.07

Table 6-15. Radiated Measurements

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 56 of 66

Radiated Spurious Emission Measurements (Cont'd)

§15.247(d) / §15.205 & §15.209; RSS-210 [A8.5]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157



Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11570.00	-115.33	Avg	H	48.53	40.20	53.98	-13.78
11570.00	-101.47	Peak	H	48.53	54.06	73.98	-19.92

Table 6-16. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
11650.00	-115.56	Avg	H	48.54	39.98	53.98	-14.00
11650.00	-100.99	Peak	H	48.54	54.55	73.98	-19.43

Table 6-17. Radiated Measurements

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 57 of 66

6.9 Radiated Restricted Band Edge Measurements

§15.205 / §15.209; RSS-210 [A8.5]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


Worst Case Mode: 802.11g

Worst Case Transfer Rate: 6Mbps



Distance of Measurements: 3 Meters

Operating Frequency: 2412MHz


Channel: 1





Plot 6-63. Radiated Restricted Lower Band Edge Measurement (Average)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 58 of 66

Radiated Restricted Band Edge Measurements (Cont'd)
§15.205 / §15.209; RSS-210 [A8.5]




Plot 6-64. Radiated Restricted Lower Band Edge Measurement (Peak)

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 59 of 66	

6.10 Line-Conducted Test Data

§15.207; RSS-Gen [7.2.2]



Plot 6-67. Line Conducted Plot with 802.11b (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.294	L1	0.1	45.60	60.40	14.80	40.00	50.40	10.40
0.498	L1	0.1	32.90	56.00	23.10	26.00	46.00	20.00
0.586	L1	0.1	38.80	56.00	17.20	29.90	46.00	16.10
0.974	L1	0.1	25.60	56.00	30.40	16.80	46.00	29.20
3.846	L1	0.2	23.10	56.00	32.90	15.30	46.00	30.70
29.238	L1	1.0	32.40	60.00	27.60	27.70	50.00	22.30

Table 6-18. Line Conducted Data with 802.11b (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11b mode using 1Mbps on Channel 6. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LGT19507			FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset			Page 62 of 66

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-68. Line Conducted Plot with 802.11b (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.294	N	0.2	45.30	60.40	15.10	40.10	50.40	10.30
0.586	N	0.1	38.40	56.00	17.60	29.90	46.00	16.10
0.978	N	0.2	29.90	56.00	26.10	15.90	46.00	30.10
1.606	N	0.2	29.90	56.00	26.10	14.90	46.00	31.10
1.754	N	0.2	32.40	56.00	23.60	21.50	46.00	24.50
3.846	N	0.2	30.50	56.00	25.50	16.70	46.00	29.30

Table 6-19. Line Conducted Data with 802.11b (N)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11b mode using 1Mbps on Channel 6. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
5. Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 63 of 66

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-69. Line Conducted Plot with 802.11a (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.294	L1	0.1	46.40	60.40	14.00	40.50	50.40	9.90
0.750	L1	0.1	42.10	56.00	13.90	26.00	46.00	20.00
0.874	L1	0.1	32.30	56.00	23.70	20.40	46.00	25.60
3.846	L1	0.2	30.90	56.00	25.10	24.40	46.00	21.60
3.906	L1	0.2	32.10	56.00	23.90	25.30	46.00	20.70
8.622	L1	0.3	45.00	60.00	15.00	38.40	50.00	11.60

Table 6-20. Line Conducted Data with 802.11a (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 157. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset			Page 64 of 66

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-70. Line Conducted Plot with 802.11a (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.786	N	0.1	37.50	56.00	18.50	24.20	46.00	21.80
0.826	N	0.1	45.40	56.00	10.60	24.90	46.00	21.10
1.814	N	0.2	40.00	56.00	16.00	27.60	46.00	18.40
1.858	N	0.2	40.40	56.00	15.60	27.20	46.00	18.80
2.310	N	0.2	38.90	56.00	17.10	26.20	46.00	19.80
8.038	N	0.3	42.60	60.00	17.40	35.50	50.00	14.50

Table 6-21. Line Conducted Data with 802.11a (N)



Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 157. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LGT19507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset		Page 65 of 66

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LGTI9507** is in compliance with Part 15C of the FCC Rules.

FCC ID: A3LGTI9507		FCC Pt. 15.247 802.11a/b/g/n/ac MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1307181296.A3L	Test Dates: 02/02 - 02/15/2013, 03/14/2013	EUT Type: Portable Handset	Page 66 of 66	