

FCC RF Test Report

APPLICANT : Samsung Electronics Co., Ltd.
EQUIPMENT : Mobile phone
BRAND NAME : Samsung
MODEL NAME : GT-S5310M, GT-S5312M
MARKETING NAME : Samsung GALAXY POCKET Neo
FCC ID : A3LGTS5310M
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 24, 2014 and testing was completed on May 06, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test 5

 1.5 Modification of EUT 6

 1.6 Testing Location 6

 1.7 Applicable Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1 Carrier Frequency Channel 7

 2.2 Pre-Scanned RF Power 8

 2.3 Test Mode 9

 2.4 Connection Diagram of Test System 10

 2.5 Support Unit used in test configuration and system 11

 2.6 EUT Operation Test Setup 11

 2.7 Measurement Results Explanation Example 11

3 TEST RESULT 12

 3.1 6dB Bandwidth Measurement 12

 3.2 Output Power Measurement 14

 3.3 Power Spectral Density Measurement 16

 3.4 Conducted Band Edges and Spurious Emission Measurement 18

 3.5 Radiated Band Edges and Spurious Emission Measurement 28

 3.6 AC Conducted Emission Measurement 46

 3.7 Antenna Requirements 51

4 LIST OF MEASURING EQUIPMENT 52

5 UNCERTAINTY OF EVALUATION 53

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.62 dB at 2390.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.30 dB at 1.726 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Samsung Electronics Co., Ltd.

129 Samsung-ro, Yeongtong-gu, Suwon City, Gyeonggi – Do, Korea 443-742

1.2 Manufacturer

Samsung Electronics Co., Ltd.

129 Samsung-ro, Yeongtong-gu, Suwon City, Gyeonggi – Do, Korea 443-742

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	Samsung
Model Name	GT-S5310M, GT-S5312M
Marketing Name	Samsung GALAXY POCKET Neo
FCC ID	A3LGTS5310M
IMEI Code	353676060005998 353676060006186
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA WLAN 11b/g/n (HT20) Bluetooth v4.0 EDR/LE
HW Version	REV1.0
SW Version	S5310M.001
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 19.11 dBm (0.0815 W) 802.11g : 23.59 dBm (0.2286 W) 802.11n HT20 : 22.86 dBm (0.1932 W)
Antenna Type	SUS Antenna type with gain -1.18 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		
	TH02-HY	CO05-HY	03CH07-HY

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
- ♦ ANSI C63.4-2003

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b mode				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	19.11	19.02	19.10	19.09

2.4GHz 802.11g mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	23.59	23.28	23.26	23.16	23.27	23.25	23.13	23.20

2.4GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	22.86	22.72	22.41	22.50	22.56	22.36	22.68	22.43


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
	Test Items	Mode	Data Rate	Test Channel
Conducted TCs	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + MP3 + Earphone			

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
5.	SD Card	San Disk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test Mode :	2.4GHz	Temperature :	21~26°C
Test Engineer :	Osolemio Chang and Alex Lee	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	18.65	30	-1.18	Pass
11b	1Mbps	1	6	2437	19.11	30	-1.18	Pass
11b	1Mbps	1	11	2462	18.45	30	-1.18	Pass
11g	6Mbps	1	1	2412	23.12	30	-1.18	Pass
11g	6Mbps	1	6	2437	23.59	30	-1.18	Pass
11g	6Mbps	1	11	2462	22.92	30	-1.18	Pass
HT20	MCS0	1	1	2412	22.60	30	-1.18	Pass
HT20	MCS0	1	6	2437	22.86	30	-1.18	Pass
HT20	MCS0	1	11	2462	22.43	30	-1.18	Pass

Note: Measured power (dBm) has offset with cable loss.

3.2.6 Test Result of Average output Power (Reporting Only)

Test Mode :	2.4GHz	Temperature :	21~26°C
Test Engineer :	Osolemio Chang and Alex Lee	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.04	15.97	30	-1.18	Pass
11b	1Mbps	1	6	2437	0.04	16.36	30	-1.18	Pass
11b	1Mbps	1	11	2462	0.04	15.75	30	-1.18	Pass
11g	6Mbps	1	1	2412	0.29	13.24	30	-1.18	Pass
11g	6Mbps	1	6	2437	0.29	13.48	30	-1.18	Pass
11g	6Mbps	1	11	2462	0.29	12.85	30	-1.18	Pass
HT20	MCS0	1	1	2412	0.33	12.17	30	-1.18	Pass
HT20	MCS0	1	6	2437	0.33	12.46	30	-1.18	Pass
HT20	MCS0	1	11	2462	0.33	11.74	30	-1.18	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Test Mode :	2.4GHz	Temperature :	21~26°C
Test Engineer :	Osolemio Chang and Alex Lee	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-4.84	8	-1.18	Pass
11b	1Mbps	1	6	2437	-5.47	8	-1.18	Pass
11b	1Mbps	1	11	2462	-6.55	8	-1.18	Pass
11g	6Mbps	1	1	2412	-11.72	8	-1.18	Pass
11g	6Mbps	1	6	2437	-10.84	8	-1.18	Pass
11g	6Mbps	1	11	2462	-12.34	8	-1.18	Pass
HT20	MCS0	1	1	2412	-12.39	8	-1.18	Pass
HT20	MCS0	1	6	2437	-12.32	8	-1.18	Pass
HT20	MCS0	1	11	2462	-13.25	8	-1.18	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission


Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Osolemio Chang and Alex Lee

WLAN 802.11b Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 6.MAY.2014 02:10:26

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:10:46

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:11:05



Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 6.MAY.2014 02:14:45

High Channel Plot




Date: 6.MAY.2014 02:14:58

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:15:18

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:15:36



Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 6.MAY.2014 02:19:17

Low Channel Plot




Date: 6.MAY.2014 02:19:31

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:19:50

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:20:09



Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 6.MAY.2014 02:23:55

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:24:15

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:24:34



Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 6.MAY.2014 02:27:54

High Channel Plot




Date: 6.MAY.2014 02:28:07

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:28:27

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:28:45



Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 6.MAY.2014 02:31:44

Low Channel Plot




Date: 6.MAY.2014 02:31:58

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:32:17

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:32:36



Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Osolemio Chang and Alex Lee


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 6.MAY.2014 02:35:40

Spurious Emission 30MHz~3GHz



Date: 6.MAY.2014 02:35:59

Spurious Emission 2GHz~25GHz




Date: 6.MAY.2014 02:36:18




Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Osolemio Chang and Alex Lee

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(μs)	1/T(kHz)	VBW Setting
802.11b	99.08	8640.00	0.12	10Hz
802.11g	93.46	1430.00	0.70	1kHz
2.4GHz 802.11n HT20	92.78	1336.00	0.75	1kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	Low	Relative Humidity :	49~54%
Test Channel :	01	Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2385.6	59.97	-14.03	74	55.03	32.3	6.91	34.27	123	340	Peak
2385.24	46.89	-7.11	54	41.97	32.28	6.91	34.27	123	340	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2384.88	57.92	-16.08	74	53	32.28	6.91	34.27	105	62	Peak
2373.99	44.8	-9.2	54	39.91	32.28	6.88	34.27	105	62	Average

Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	High	Relative Humidity :	49~54%
Test Channel :	11	Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2487.52	60.26	-13.74	74	55.23	32.4	7.06	34.43	120	342	Peak
2487.19	47.38	-6.62	54	42.37	32.38	7.06	34.43	120	342	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2486.98	58.18	-15.82	74	53.17	32.38	7.06	34.43	102	59	Peak
2487.4	44.71	-9.29	54	39.7	32.38	7.06	34.43	102	59	Average



Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	Low	Relative Humidity :	49~54%
Test Channel :	01	Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.83	65.71	-8.29	74	60.8	32.3	6.91	34.3	153	346	Peak
2390	50.38	-3.62	54	45.47	32.3	6.91	34.3	153	346	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.29	59.57	-14.43	74	54.63	32.3	6.91	34.27	106	60	Peak
2389.92	46.18	-7.82	54	41.27	32.3	6.91	34.3	106	60	Average

Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	High	Relative Humidity :	49~54%
Test Channel :	11	Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.62	65.33	-8.67	74	60.32	32.38	7.06	34.43	122	330	Peak
2483.71	49.39	-4.61	54	44.38	32.38	7.06	34.43	122	330	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.77	59.46	-14.54	74	54.45	32.38	7.06	34.43	102	43	Peak
2483.62	45.85	-8.15	54	40.84	32.38	7.06	34.43	102	43	Average



Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	Low	Relative Humidity :	49~54%
Test Channel :	01	Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.83	65.67	-8.33	74	60.76	32.3	6.91	34.3	102	334	Peak
2389.92	49.91	-4.09	54	45	32.3	6.91	34.3	102	334	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.29	61.55	-12.45	74	56.61	32.3	6.91	34.27	132	60	Peak
2389.47	47.22	-6.78	54	42.28	32.3	6.91	34.27	132	60	Average

Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	High	Relative Humidity :	49~54%
Test Channel :	11	Test Engineer :	Eric Shih

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	65.73	-8.27	74	60.72	32.38	7.06	34.43	120	337	Peak
2483.83	50.16	-3.84	54	45.15	32.38	7.06	34.43	120	337	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.79	61.48	-12.52	74	56.47	32.38	7.06	34.43	102	57	Peak
2483.86	46.49	-7.51	54	41.48	32.38	7.06	34.43	102	57	Average

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	802.11b	Temperature :	21~25°C
Test Channel :	01	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	104.54	-	-	99.58	32.31	6.95	34.3	123	340	Average
2412	108.99	-	-	104.03	32.31	6.95	34.3	123	340	Peak
4824	45.31	-28.69	74	61.5	33.97	8.77	58.93	100	0	Peak

Test Mode :	802.11b	Temperature :	21~25°C
Test Channel :	01	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	99.93	-	-	94.97	32.31	6.95	34.3	105	62	Average
2412	104.4	-	-	99.44	32.31	6.95	34.3	105	62	Peak
4824	47.28	-26.72	74	63.47	33.97	8.77	58.93	100	0	Peak



Test Mode :	802.11b	Temperature :	21~25°C
Test Channel :	06	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2438 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2438	104.61	-	-	99.62	32.35	6.99	34.35	121	337	Average
2438	109.01	-	-	104.02	32.35	6.99	34.35	121	337	Peak
4875	44.05	-29.95	74	60.11	33.95	8.82	58.83	100	0	Peak
7311	42.46	-31.54	74	53.74	35.54	10.91	57.73	100	0	Peak

Test Mode :	802.11b	Temperature :	21~25°C
Test Channel :	06	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2438 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2438	101.85	-	-	96.86	32.35	6.99	34.35	129	58	Average
2438	105.97	-	-	100.98	32.35	6.99	34.35	129	58	Peak
4875	45.44	-28.56	74	61.5	33.95	8.82	58.83	100	0	Peak
7311	42.83	-31.17	74	54.11	35.54	10.91	57.73	100	0	Peak



Test Mode :	802.11b	Temperature :	21~25°C
Test Channel :	11	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	104.22	-	-	99.22	32.37	7.02	34.39	120	342	Average
2462	108.73	-	-	103.73	32.37	7.02	34.39	120	342	Peak
4926	45.06	-28.94	74	60.96	33.93	8.9	58.73	100	0	Peak
7386	42.31	-31.69	74	53.6	35.52	10.99	57.8	100	0	Peak

Test Mode :	802.11b	Temperature :	21~25°C
Test Channel :	11	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	99.39	-	-	94.39	32.37	7.02	34.39	102	59	Average
2462	103.5	-	-	98.5	32.37	7.02	34.39	102	59	Peak
4926	44.77	-29.23	74	60.67	33.93	8.9	58.73	100	0	Peak
7386	42.9	-31.1	74	54.19	35.52	10.99	57.8	100	0	Peak



Test Mode :	802.11g	Temperature :	21~25°C
Test Channel :	01	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.35	20.13	-19.87	40	32.73	18.28	0.54	31.42	196	100	Peak
161.22	17.84	-25.66	43.5	37.44	10.36	1.22	31.18	-	-	Peak
281.91	16.86	-29.14	46	33.27	12.86	1.65	30.92	-	-	Peak
565.3	21.52	-24.48	46	29.83	19.84	2.59	30.74	-	-	Peak
873.3	26.02	-19.98	46	30.1	22.97	3.3	30.35	-	-	Peak
984.6	27.98	-26.02	54	29.84	24.91	3.49	30.26	-	-	Peak
2412	98.14	-	-	93.18	32.31	6.95	34.3	153	346	Average
2412	107.26	-	-	102.3	32.31	6.95	34.3	153	346	Peak
4824	41.93	-32.07	74	58.12	33.97	8.77	58.93	100	0	Peak



Test Mode :	802.11g	Temperature :	21~25°C
Test Channel :	01	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
33.24	19.86	-20.14	40	33.44	17.24	0.56	31.38	147	85	Peak
80.49	19.74	-20.26	40	43.04	7	0.88	31.18	-	-	Peak
288.66	18	-28	46	34.3	13.07	1.69	31.06	-	-	Peak
307	23.05	-22.95	46	38.99	13.27	1.79	31	-	-	Peak
746.6	24.46	-21.54	46	29.68	22.13	3.05	30.4	-	-	Peak
961.5	27.76	-26.24	54	29.93	24.71	3.47	30.35	-	-	Peak
2412	91.91	-	-	86.95	32.31	6.95	34.3	106	60	Average
2412	101.69	-	-	96.73	32.31	6.95	34.3	106	60	Peak
4824	43.8	-30.2	74	59.99	33.97	8.77	58.93	100	0	Peak



Test Mode :	802.11g	Temperature :	21~25°C
Test Channel :	06	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2438 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2438	97.84	-	-	92.85	32.35	6.99	34.35	121	339	Average
2438	106.75	-	-	101.76	32.35	6.99	34.35	121	339	Peak
4875	41.35	-32.65	74	57.41	33.95	8.82	58.83	100	0	Peak
7311	42.67	-31.33	74	53.95	35.54	10.91	57.73	100	0	Peak

Test Mode :	802.11g	Temperature :	21~25°C
Test Channel :	06	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	94.62	-	-	89.63	32.35	6.99	34.35	130	61	Average
2437	103.18	-	-	98.19	32.35	6.99	34.35	130	61	Peak
4875	42.02	-31.98	74	58.08	33.95	8.82	58.83	100	0	Peak
7311	43.33	-30.67	74	54.61	35.54	10.91	57.73	100	0	Peak



Test Mode :	802.11g	Temperature :	21~25°C
Test Channel :	11	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	96.19	-	-	91.19	32.37	7.02	34.39	122	330	Average
2462	105.22	-	-	100.22	32.37	7.02	34.39	122	330	Peak
4923	42.29	-31.71	74	58.22	33.93	8.87	58.73	100	0	Peak
7386	41.96	-32.04	74	53.25	35.52	10.99	57.8	100	0	Peak

Test Mode :	802.11g	Temperature :	21~25°C
Test Channel :	11	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2464 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2464	90.36	-	-	85.36	32.37	7.02	34.39	102	43	Average
2464	99.61	-	-	94.61	32.37	7.02	34.39	102	43	Peak
4923	41.67	-32.33	74	57.6	33.93	8.87	58.73	100	0	Peak
7386	42.34	-31.66	74	53.63	35.52	10.99	57.8	100	0	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	21~25°C
Test Channel :	01	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	96.02	-	-	91.06	32.31	6.95	34.3	102	334	Average
2412	105.33	-	-	100.37	32.31	6.95	34.3	102	334	Peak
4923	40.06	-33.94	74	55.99	33.93	8.87	58.73	100	0	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	21~25°C
Test Channel :	01	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	92.31	-	-	87.35	32.31	6.95	34.3	132	60	Average
2412	101.57	-	-	96.61	32.31	6.95	34.3	132	60	Peak
4923	39.68	-34.32	74	55.61	33.93	8.87	58.73	100	0	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	21~25°C
Test Channel :	06	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2438 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2438	97.36	-	-	92.37	32.35	6.99	34.35	123	340	Average
2438	106.72	-	-	101.73	32.35	6.99	34.35	123	340	Peak
4875	40.27	-33.73	74	56.33	33.95	8.82	58.83	100	0	Peak
7311	42.11	-31.89	74	53.39	35.54	10.91	57.73	100	0	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	21~25°C
Test Channel :	06	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2439	94.27	-	-	89.28	32.35	6.99	34.35	130	59	Average
2439	103.59	-	-	98.6	32.35	6.99	34.35	130	59	Peak
4875	41.14	-32.86	74	57.2	33.95	8.82	58.83	100	0	Peak
7311	42.15	-31.85	74	53.43	35.54	10.91	57.73	100	0	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	21~25°C
Test Channel :	11	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Horizontal
Remark :	1. 2464 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.53	23.68	-16.32	40	40.95	13.3	0.63	31.2	156	72	Peak
161.49	17.57	-25.93	43.5	37.31	10.22	1.22	31.18	-	-	Peak
256.53	25.35	-20.65	46	41.26	13.52	1.57	31	-	-	Peak
553.4	21.11	-24.89	46	29.45	19.88	2.56	30.78	-	-	Peak
708.8	23.55	-22.45	46	30.03	20.96	2.96	30.4	-	-	Peak
928.6	27.58	-18.42	46	30.29	24.24	3.41	30.36	-	-	Peak
2464	96.17	-	-	91.17	32.37	7.02	34.39	120	337	Average
2464	106.85	-	-	101.85	32.37	7.02	34.39	120	337	Peak
4923	41.59	-32.41	74	57.52	33.93	8.87	58.73	100	0	Peak
7386	42.08	-31.92	74	53.37	35.52	10.99	57.8	100	0	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	21~25°C
Test Channel :	11	Relative Humidity :	49~54%
Test Engineer :	Eric Shih	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
56.73	21.31	-18.69	40	45.57	6.24	0.74	31.24	190	110	Peak
81.57	19.29	-20.71	40	42.35	7.22	0.89	31.17	-	-	Peak
258.15	20.07	-25.93	46	35.81	13.68	1.58	31	-	-	Peak
307	23.52	-22.48	46	39.46	13.27	1.79	31	-	-	Peak
825.7	25.16	-20.84	46	29.64	22.66	3.21	30.35	-	-	Peak
964.3	27.96	-26.04	54	30.1	24.74	3.47	30.35	-	-	Peak
2462	91.74	-	-	86.74	32.37	7.02	34.39	102	57	Average
2462	101.03	-	-	96.03	32.37	7.02	34.39	102	57	Peak
4923	40.22	-33.78	74	56.15	33.93	8.87	58.73	100	0	Peak
7386	42.03	-31.97	74	53.32	35.52	10.99	57.8	100	0	Peak

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Cosmo Xu	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + MP3 + Earphone		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.478000	38.2	Off	L1	19.4	17.8	56.0
1.574000	39.8	Off	L1	19.5	16.2	56.0
1.630000	40.5	Off	L1	19.5	15.5	56.0
1.726000	42.1	Off	L1	19.5	13.9	56.0
1.862000	41.5	Off	L1	19.5	14.5	56.0
1.974000	39.0	Off	L1	19.5	17.0	56.0
2.062000	37.0	Off	L1	19.5	19.0	56.0
3.590000	37.2	Off	L1	19.6	18.8	56.0
3.966000	39.0	Off	L1	19.6	17.0	56.0
4.390000	41.9	Off	L1	19.6	14.1	56.0
4.838000	41.5	Off	L1	19.6	14.5	56.0



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Cosmo Xu	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + MP3 + Earphone		




Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.478000	26.6	Off	L1	19.4	19.4	46.0
1.574000	30.4	Off	L1	19.5	15.6	46.0
1.630000	32.4	Off	L1	19.5	13.6	46.0
1.726000	32.7	Off	L1	19.5	13.3	46.0
1.862000	31.8	Off	L1	19.5	14.2	46.0
1.974000	29.3	Off	L1	19.5	16.7	46.0
2.062000	27.5	Off	L1	19.5	18.5	46.0
3.590000	27.2	Off	L1	19.6	18.8	46.0
3.966000	29.7	Off	L1	19.6	16.3	46.0
4.390000	32.6	Off	L1	19.6	13.4	46.0
4.838000	32.4	Off	L1	19.6	13.6	46.0



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Cosmo Xu	Relative Humidity :	45~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + MP3 + Earphone		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.206000	39.1	Off	N	19.3	24.3	63.4
0.406000	32.0	Off	N	19.4	25.7	57.7
1.814000	38.5	Off	N	19.6	17.5	56.0
4.390000	38.4	Off	N	19.6	17.6	56.0
7.158000	32.0	Off	N	19.7	28.0	60.0
12.590000	31.0	Off	N	19.8	29.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.206000	22.2	Off	N	19.3	31.2	53.4
0.406000	20.0	Off	N	19.4	27.7	47.7
1.814000	31.1	Off	N	19.6	14.9	46.0
4.390000	32.2	Off	N	19.6	13.8	46.0
7.158000	25.2	Off	N	19.7	24.8	50.0
12.590000	23.6	Off	N	19.8	26.4	50.0



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Apr. 28, 2014 ~ May 06, 2014	Jun. 06, 2014	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 17, 2013	Apr. 28, 2014 ~ May 06, 2014	Aug. 16, 2014	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 17, 2013	Apr. 28, 2014 ~ May 06, 2014	Aug. 16, 2014	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9 kHz~7 GHz	Sep. 06, 2013	May 02, 2014	Sep. 05, 2014	Radiation (03CH07-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz ~ 30GHz	Feb. 10, 2014	May 02, 2014	Feb. 09, 2015	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	860004/0001	9 kHz~30 MHz	Jul. 03, 2012	May 02, 2014	Jul. 03, 2014	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30 MHz ~ 1 GHz	Oct. 10, 2013	May 02, 2014	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1 GHz~18 GHz	Aug. 22, 2013	May 02, 2014	Aug. 21, 2014	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15 GHz- 40 GHz	Oct. 03, 2013	May 02, 2014	Oct. 02, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10 MHz ~ 1000MHz 32dB GAIN	Mar. 17, 2014	May 02, 2014	Mar. 16, 2015	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Nov. 29, 2013	May 02, 2014	Nov. 28, 2014	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	DC~18 G High Gain	Jul. 09, 2013	May 02, 2014	Jul. 08, 2014	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	May 02, 2014	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	May 02, 2014	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	Apr. 28, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Apr. 28, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Apr. 28, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 28, 2014	N/A	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50
---	------