



SAMSUNG ELECTRONICS Co., Ltd.,
Regulatory Compliance Group
IT R&D Center
416 Maetan3-Dong,
Yeongtong-gu, Suwon city,
Gyeonggi-Do, Korea 443-742

FCC CFR47 PART 22 SUBPART CERTIFICATION REPORT

Model Tested: GT-S8300T
FCC ID (Requested): A3LGTS8300T
Report No: FG-040-R2
Job No: FG-040
Date issued: 2009-03-09

- Abstract -

All measurement reported here in accordance with FCC Rules, 47CFR
Part2, Part22

Prepared By

KJ KWON - Test Engineer

Authorized By

WT JANG - Technical Manager



TABLE OF CONTENT

MEASUREMENT REPORT	Page
1. FCC Certification Information.....	3
1.1 §2.1033 General Information	3
2. INTRODUCTION	4
2.1 General	4
3. MEASURING INSTRUMENT CALIBRATION	5
4. TEST EQUIPMENT LIST.....	6
5. FCC 3G MEASUREMENT PROCEDURES	7
5.1 Effective Radiated Power / Equivalent Isotropic Radiated Power	8
5.2 Radiated Spurious & Harmonic Emission	9
5.3 Occupied Bandwidth	11
5.4 Spurious and Harmonic Emissions at Antenna Terminal	11
5.4.1 Occupied Bandwidth Emission Limits	11
5.4.2 Conducted Spurious Emission	12
5.5 Frequency Stability / Temperature Variation	13
6. TEST DATA	14
6.1 Effective Radiated Power(E.R.P.)	14
6.2 Cellular WCDMA Radiated Spurious & Harmonic measurement	15
6.3 Cellular WCDMA Radiated Spurious & Harmonic Conversion Table	16
6.4 Frequency Stability	17
6.4.1 Cellular WCDMA Frequency Stability Table	17
6.4.2 Cellular WCDMA Frequency Stability Graph	18
7. SAMPLE CALCULATION	20
7.1 Emission Designator	20
8. CONCLUSION.....	21
9. TEST PLOT.....	22



MEASUREMENT REPORT

1. FCC Certification Information

The following information is in accordance with FCC Rules, 47CFR Part2, Subpart J, Sections 2.1033 – 2.1055.

1.1 §2.1033 General Information

- Applicant Name: SAMSUNG ELECTRONICS CO., LTD.
- Address: 416 Maetan3-Dong, Yeongtong-gu, Suwon City
Gyeonggi-Do, Korea 443-742
- Attention: SungJoo KIM, Engineering Manager (QA Lab)
- FCC ID: A3LGTS8300T
- Quantity: Quantity production is planned
- Emission Designators: 4M19F9W(Cellular WCDMA)
- Tx Freq. Range: 826.4 - 846.6 MHz (Cellular WCDMA)
- Rx Freq. Range: 826.4 - 846.6 MHz (Cellular WCDMA)
- Max. Power Rating: 0.181 W Cellular WCDMA (22.58dBm)
- FCC Classification(s): PCS Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: 850/1900 GSM/EDGE and 850 WCDMA Phone with Bluetooth.
- Modulation(s): WCDMA
- Frequency Tolerance: $\pm 0.00025\%$ (2.5ppm)
- FCC Rule Part(s): **§22(H), §2.**
- Dates of Test: February 26-27, 2009
- Place of Test: SAMSUNG Lab,
- Test Report S/N: FG-040-R2

2. INTRODUCTION

2.1 General

These measurement test were conducted at **SAMSUNG ELECTRONICS CO., LTD(SUWON)**. The site address is 416 Maetan3-Dong, Yeongtong-gu, Suwon City, Gyeonggi-Do, Korea 443-742 The site have 1 Fully-anechoic chamber and measurement facility.




Figure1. Map of the Suwon City area.

Measurement Procedure

The radiated and spurious measurements were made Fully-anechoic chamber at a 3-meter test range (see Figure2). The equipment under testing was placed on the rotating device at the same height and at a distance of 3-meters from the receive antenna. The rotating device which can rotate horizontal axis was mounted on the turn unit to facilitate rotation around a vertical axis. The measurement was made for each horizontal/vertical position combination with receive antenna horizontally polarized. This measurement was repeated with receive antenna vertically polarized. The substitution antenna will replace the EUT antenna it the same position and in vertical polarization. The frequency of the signal generator shall be set to the frequencies that were measured on the EUT. The signal generator, output level, shall be adjusted until an equal or a known related level to what was measured from the EUT is obtained in the spectrum analyzer. This level was recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure2. Photograph of 3m Fully-Anechoic Chamber



3. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

- End of page -

4. TEST EQUIPMENT LIST

Name Of Equipment	Model	Serial No.	Due Date
Spectrum Analyzer	ESI26	836119/010	2009-10-21
	E4440A(3Hz~26.5GHz)	MY46187454	2009-03-03
	E4440A(3Hz~26.5GHz)	MY41000236	2009-04-15
Signal Generator	SMR20	835197/030	2009-12-05
Network Analyzer	8753E	JP38160590	2009-06-20
Power Sensor	E9300H	MY41495838	2009-09-12
	8481B	3318A10325	2009-09-28
Power Meter	E4417A	MY45101042	2009-09-12
	E4419B	GB41293846	2009-09-12
Pre-Amplifier	8449B	3008A00691	2009-12-15
Communication test set	8960	MY47510060	2009-03-03
	8960	GB42230535	2009-12-18
Controller	CO2000	CO2000/424	Not Required
Turn Unit	CT0800	CT0800/057	Not Required
Rotating Device	DE3600-RH-PR	DE3600-RH-PR/050	Not Required
Antenna Master	MA4000	MA4000/204	Not Required
Horn Antenna	HF906	100134	2009-10-24
	HF906	360306/011	2010-06-13
	BBHA9120	9120D-637	2009-10-24
Dipole Antenna	UHA 9105	9105-2412	2009-11-07
	UHA 9105	9105-2413	2010-06-13
	3121C-DB4	9007-587	2009-04-16
Communication test set	CMU200	109162	2009-10-17
Receive Antenna	HL040	353255/019	2009-10-29
	HL040	353255/020	2010-06-13
Power Supply	E3640A	MY40003594	2009-06-20
	E3640A	MY40003595	2009-05-22
	E3632A	MY40022438	2009-03-03
Divider	11636B	51946	Not Required
	11636B	51942	Not Required
	11636B	56913	Not Required
	11636B	56918	Not Required
High Pass Filter	WHK1.0/15G-10SS	1	Not Required
	WHK/3.0/18G-10SS	492	Not Required
	WHK/3.5/18G-10SS	4	Not Required
Environmental Chamber	SH-241	92000549	2009-11-14
	SH-241	92000548	2009-11-14
Shielded Fully Anechoic Chamber	CHAMBER	ANT0001	Not Required

5. FCC 3G MEASUREMENT PROCEDURES

The maximum output power is a measure of the maximum power the UE can transmit (i.e. the actual power as would be measured assuming no measurement error) in a band width of at least $(1+\alpha)$ times the chip rate of the radio access mode

The default test configuration is configure an established radio link between the UE and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. Maximum output is verified according to 3GPP TS 34.121 Section 5.2

1. Configure TCP (Transmit Power Control) set to "All 1"s.
2. RMC and AMR connections at 12.2kbps are measured under 3.4kbps SRB (signaling radio bearer)
3. Measure the mean power of the UE in a bandwidth of at least $(1+\alpha)$ times the chip rate of the radio access mode. The mean power shall be averaged over at least one timeslot.

Table1
3GPP TS 34.121 Nominal Maximum Output Power

Operating Band	Power Class3		Power Class 4	
	Power (dBm)	Tol (dB)	Power (dBm)	Tol (dB)
Band V	+24	+1/-3	+21	+2/-2

Operating Band	Channel	HSDPA Inactive		HSDPA Active
		12.2 kbps RMC	12.2 kbps AMR	12.2 kbps RMC
Cellular WCDMA	4132	23.51	23.53	22.71
	4175	23.03	23.04	22.38
	4233	22.65	22.63	21.97

5.1 Effective Radiated Power / Equivalent Isotropic Radiated Power

Test Set-up for the ERP/EIRP TEST

Test Set-up for the ERP/EIRP TEST

Effective Radiated Power Output and Equivalent Isotropic Radiated Power output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004




Figure 3. Diagram of ERP/EIRP test Set-up

The EUT was placed on the rotating device at 3-meters from the receive antenna. The turn unit and rotating device was adjusted for the highest reading on the receive spectrum analyzer. For GSM signals, an average detector is used, with RBW=VBW=3MHz, SPAN=10MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of dipole is measured. The ERP and EIRP are recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

5.2 Radiated Spurious & Harmonic Emission

Test Set-up for the Radiated Emission TEST

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004




Figure 4. Diagram of Radiated Spurious & Harmonic test Set-up

The EUT was placed on the rotating device at 3-meters from the receive antenna. The turn unit and rotating device was adjusted for the highest reading on the receive spectrum analyzer. **The Spectrum was investigated from 30MHz to the 10th Harmonic of the fundamental. A peak detector is used, with RBW=VBW=1MHz. The value that we could measure was only reported.** A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



SAMPLE CALCULATION

Example: Channel 600 PCS Mode 2nd Harmonic(3760MHz)

The receive analyzer reading at 3meters with the EUT on the turntable was -81.0dBm . The gain of the substituted antenna is 8.1dBi . The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0dBm of the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0dB at 3760MHz . So 6.1dB is added to the signal generator reading of -30.9dBm yielding -24.8dBm . The fundamental EIRP was 25.5dBm so this harmonic was $25.5\text{dBm} - (-24.8) = 50.3\text{dBc}$.

- End of page -

5.3 Occupied Bandwidth

Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.

Plots of the EUT's occupied bandwidth are shown herein.

5.4 Spurious and Harmonic Emissions at Antenna Terminal

5.4.1 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

- End of page -

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A	1850 – 1865	1930 – 1945
B	1870 – 1885	1950 – 1965
C	1895 – 1910	1975 – 1990
D	1865 – 1870	1945 – 1950
E	1885 – 1890	1965 – 1970
F	1890 – 1895	1970 – 1975

Table 1. Broadband PCS Service Frequency Blocks

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A* Low + A	824 – 835	869 – 880
B	835 – 845	880 – 890
A* High	845 – 846.5	890 – 891.5
B*	846.5 – 849	891.5 – 894

Table 2. Cellular Service Frequency Blocks

5.4.2 Conducted Spurious Emission

Minimum standard:

On any frequency outside a license frequency block, the power of any emission shall be attenuated below the transmitter power(P) by at least $43+10\log(P)$ dB. Limit equivalent to -13 dBm, calculation shown below.

$$43 + 10\log(0.333 \text{ W}) = 38.22\text{dB}$$

$$25.22 \text{ dBm} - 38.22 \text{ dB} = -13 \text{ dBm}$$

Test Procedure:

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1% of the emission bandwidth to show compliance with the -13 dBm limit, in the 1MHz bands immediately outside and adjacent to the edge of the frequency block. The measurements are repeated for the EUT’s highest channel. For the Out-of-Band measurements a 1MHz RBW was used to scan from 10MHz to 10GHz. (PCS Mode : 10MHz to 20GHz). A display line was placed at -13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements. Plots are shown herein.

5.5 Frequency Stability / Temperature Variation

The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is carried from -30°C to +60°C using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification- The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (Usually 14~16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +60°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE : The EUT is tested down to the battery endpoint.

- End of page -

6. TEST DATA

6.1 Effective Radiated Power(E.R.P.)

Supply Voltage : 3.7VDC

Modulation : Cellular WCDMA

Reference level

Frequency (MHz)	Output (dBm)	Polarization	P/M (dBm)	Ant gain (dBd)	Ref level (dBm)
826.4	18.00	H	-19.29	-0.67	-18.62
		V	-19.50	-0.67	-18.83
836.6	23.00	H	-15.20	-0.73	-14.47
		V	-14.39	-0.73	-13.66
846.6	19.00	H	-21.36	-0.79	-20.57
		V	-19.58	-0.79	-18.79

Result

Frequency (MHz)	From EUT Tested level (dBm)	Polarization (H/V)	Azimuth (angle)	ERP (dBm)	ERP (W)	Battery
826.4	-18.15	H	79/90	18.47	0.070	Standard
836.6	-14.89	H	75/100	22.58	0.181	Standard
846.6	-20.93	H	74/70	18.64	0.073	Standard

NOTE : Standard batteries are the only battery options for this phone

- All modes of operation were investigated, and the worst-case results are reported.

-

Radiated measurements at 3 meters by Substitution Method

6.2 Cellular WCDMA Radiated Spurious & Harmonic measurement

Operating Frequency : 826.4 MHz(Low), 836.4 MHz(Middle), 846.6 MHz(High)

Measured Output Power : **22.58 dBm = 0.181 W**

Modulation Signal : CDMA

Limit : $43 + 10\log_{10}(P) = 35.58\text{dBc}$

Result

Channel	Harmonic	Frequency (MHz)	From EUT Tested level (dBm)	POL (H/V)	Result (dBc)
4132	2	1652.80	-59.29	H	70.33
	3	2479.20	-66.84	H	72.42
	4	3305.60	-67.47	H	69.79
	5	4132.00	-	-	-
	6	4958.40	-	-	-
	7	5784.80	-	-	-
4175	2	1672.80	-53.73	H	63.45
	3	2509.20	-66.64	V	72.72
	4	3345.60	-67.22	H	69.21
	5	4182.00	-	-	-
	6	5018.40	-	-	-
	7	5854.80	-	-	-
4233	2	1693.20	-53.52	H	62.41
	3	2539.80	-65.13	H	70.47
	4	3386.40	-67.59	V	69.85
	5	4233.00	-	-	-
	6	5079.60	-	-	-
	7	5926.20	-	-	-

NOTE :

1. "-" Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. The spectrum is measured from 30MHz to the 10th harmonic and All modes of operation were investigated, and the worst-case results are reported..

Radiated Spurious Emission measurements at 3 meters by Substitution Method



6.3 Cellular WCDMA Radiated Spurious & Harmonic Conversion Table

Date : February 27, 2009
 Test Engineer : KJ KWON

Tx Cable loss
 Tx Horn Ant Gain
 Tx Level to radiate -13dBm
 ESI Level received from Tx with -13dBm
 Tested Level from EUT
 = ERP+2.14 - (-13 + -)

CH	Har	Frequency (MHz)	Tx C/L dB	Tx Horn Gain dBi	Tx Level dBm	ESI Level : H dBm	ESI Level : V dBm	Test ed EUT Level : H dBm	Test ed EUT Level : H dBm	Result EUT : H (dBc)	Result EUT : V (dBc)
4357	2	1652.80	-9.02	-16.09	-26.68	-25.78	-25.24	-59.29	-60.21	70.33	70.83
	3	2479.20	-11.25	-18.38	-32.14	-30.65	-30.96	-66.84	-67.26	72.42	73.53
	4	3305.60	-13.26	-19.62	-35.31	-34.30	-34.88	-67.47	-67.50	69.88	69.79
	5	4132.00	-14.79	-21.54	-38.87	-37.37	-37.16	-	-	-	-
	6	4958.40	-16.60	-22.35	-40.93	-39.95	-40.17	-	-	-	-
	7	5784.80	-18.02	-23.73	-43.59	-42.25	-42.16	-	-	-	-
4408	2	1673.20	-9.05	-16.10	-28.00	-26.45	-26.15	-53.73	-54.56	63.45	63.65
	3	2509.80	-11.31	-18.32	-32.40	-30.90	-30.96	-67.52	-66.64	72.84	72.72
	4	3346.40	-13.33	-19.62	-35.73	-34.28	-34.36	-67.22	-67.32	69.21	69.44
	5	4183.00	-15.01	-21.73	-39.30	-36.90	-37.13	-	-	-	-
	6	5019.60	-16.84	-22.83	-41.59	-40.04	-40.64	-	-	-	-
	7	5856.20	-18.26	-23.94	-43.87	-42.75	-42.94	-	-	-	-
4458	2	1693.20	-9.07	-16.33	-28.83	-26.64	-26.78	-53.52	-54.85	62.41	64.82
	3	2539.80	-11.35	-18.41	-32.38	-30.32	-30.81	-65.13	-66.38	70.47	71.16
	4	3386.40	-13.26	-19.79	-35.94	-34.25	-34.55	-68.07	-67.59	69.85	69.85
	5	4233.00	-15.20	-21.86	-39.34	-37.07	-37.26	-	-	-	-
	6	5079.60	-16.99	-22.63	-41.96	-40.12	-40.75	-	-	-	-
	7	5926.20	-18.38	-23.97	-43.98	-43.10	-42.67	-	-	-	-



6.4 Frequency Stability

6.4.1 Cellular WCDMA Frequency Stability Table

Operating Frequency : 836,600,000 Hz

Channel : 4183

Reference Voltage : 3.7VDC


Deviation Limit : ± 0.00025 % or 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency Error (Hz)	Frequency (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	15.30	836,600,015	0.000002	0.018
100%		-30	39.70	836,600,040	0.000005	0.047
100%		-20	25.50	836,600,026	0.000003	0.030
100%		-10	-0.60	836,599,999	0.000000	-0.001
100%		0	27.60	836,600,028	0.000003	0.033
100%		+10	31.00	836,600,031	0.000004	0.037
100%		+20	15.30	836,600,015	0.000002	0.018
100%		+30	34.50	836,600,035	0.000004	0.041
100%		+40	-19.70	836,599,980	-0.000002	-0.024
100%		+50	13.80	836,600,014	0.000002	0.016
100%		+60	-37.30	836,599,963	-0.000004	-0.045
85%		3.25	+20	-1.00	836,599,999	0.000000
115%	4.26	+20	-4.80	836,599,995	-0.000001	-0.006
Batt. Endpoint	3.25	+20	-1.00	836,599,999	0.000000	-0.001


Note : The temperature is varied from -30 °C to +60 °C using an environmental chamber.

The EUT is tested down to the battery end point

6.4.2 Cellular WCDMA Frequency Stability Graph



Zoom In



- End of page -

7. SAMPLE CALCULATION

7.1 Emission Designator

Emission Designator = 4M19F9W

CDMA BW = 4.19MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination(Audio/Data)

(Measured at the 99.75% power bandwidth)

- End of page -



8. CONCLUSION

The data collected shows that the SAMSUNG 850/1900 GSM/EDGE and 850 WCDMA Phone with Bluetooth.

FCC ID : A3LGTS8300T complies with all the requirements of Parts 2, 22 of the FCC Rules.


- End of page -

9. TEST PLOT

Agilent

R T

Freq/Channel



Center Freq
852.000000 MHz

Start Freq
850.000000 MHz

Stop Freq
854.000000 MHz

CF Step
400.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
821.000000 MHz

Start Freq
819.000000 MHz

Stop Freq
823.000000 MHz

CF Step
400.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved


Agilent

R T

Freq/Channel

FCC ID:A3LGTS8300T Band Edge Ch.4458 Mkr1 849.00 MHz

Ref 24 dBm Atten 30 dB -33.367 dBm



Center 849.00 MHz Span 10 MHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.84 ms (601 pts)

Center Freq
849.000000 MHz

Start Freq
844.000000 MHz

Stop Freq
854.000000 MHz

CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved


Agilent

R T

Freq/Channel

FCC ID:A3LGTS8300T Band Edge Ch.4357 Mkr1 824.00 MHz

Ref 24 dBm Atten 30 dB -27.196 dBm



Center 824.00 MHz Span 10 MHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.84 ms (601 pts)

Center Freq
824.000000 MHz

Start Freq
819.000000 MHz

Stop Freq
829.000000 MHz

CF Step
1.00000000 MHz
Auto Man


Freq Offset
0.00000000 Hz

Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Base Ch Freq 826.4 MHz Trig Free
 Channel Power ***3GPP W-CDMA**

FCC ID:A3LGTS8300T Power Out Ch.4357
 Ref 24 dBm Atten 30 dB



Center 826.40 MHz Span 10 MHz
 #Res BW 62 kHz #VBW 620 kHz Sweep 7.6 ms (601 pts)


Channel Power	Power Spectral Density
24.00 dBm /4.0551 MHz	-42.01 dBm/Hz

Freq/Channel
Center Freq 826.400000 MHz
Start Freq 821.400000 MHz
Stop Freq 831.400000 MHz
CF Step 1.00000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

File Operation Status, C:\TEMP.GIF file saved

Base Ch Freq 836.6 MHz Trig Free
 Channel Power ***3GPP W-CDMA**

FCC ID:A3LGTS8300T Power Out Ch.4408
 Ref 24 dBm Atten 30 dB



Center 836.60 MHz Span 10 MHz
 #Res BW 62 kHz #VBW 620 kHz Sweep 7.6 ms (601 pts)


Channel Power	Power Spectral Density
23.76 dBm /4.1345 MHz	-42.40 dBm/Hz

Freq/Channel
Center Freq 836.600000 MHz
Start Freq 831.600000 MHz
Stop Freq 841.600000 MHz
CF Step 1.00000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

File Operation Status, C:\TEMP.GIF file saved

Base Ch Freq 846.6 MHz Trig Free
 Channel Power #3GPP W-CDMA

FCC ID:A3LGTS8300T Power Out Ch.4458
 Ref 24 dBm Atten 30 dB




Channel Power	Power Spectral Density
23.14 dBm /4.1900 MHz	-43.08 dBm/Hz

Freq/Channel
Center Freq 846.600000 MHz
Start Freq 841.600000 MHz
Stop Freq 851.600000 MHz
CF Step 1.00000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

File Operation Status, C:\TEMP.GIF file saved

FCC ID:A3LGTS8300T Cond Spur Ch.4357
 Ref 24 dBm Atten 30 dB



Center 1.255 GHz Span 2.49 GHz
 #Res BW 1 MHz #VBW 1 MHz Sweep 4.16 ms (601 pts)


Freq/Channel
Center Freq 1.25500000 GHz
Start Freq 10.0000000 MHz
Stop Freq 2.50000000 GHz
CF Step 249.000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
413.200000 MHz

Start Freq
10.0000000 MHz

Stop Freq
816.400000 MHz

CF Step
80.6400000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.66820000 GHz

Start Freq
836.400000 MHz

Stop Freq
2.50000000 GHz

CF Step
166.360000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
6.25000000 GHz

Start Freq
2.50000000 GHz

Stop Freq
10.00000000 GHz

CF Step
750.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.25500000 GHz

Start Freq
10.00000000 MHz

Stop Freq
2.50000000 GHz

CF Step
249.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
418.300000 MHz

Start Freq
10.0000000 MHz

Stop Freq
826.600000 MHz

CF Step
81.6600000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.67330000 GHz

Start Freq
846.600000 MHz

Stop Freq
2.50000000 GHz

CF Step
165.340000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
6.25000000 GHz

Start Freq
2.50000000 GHz

Stop Freq
10.00000000 GHz

CF Step
750.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.25500000 GHz

Start Freq
10.00000000 MHz

Stop Freq
2.50000000 GHz

CF Step
249.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
423.300000 MHz

Start Freq
10.0000000 MHz

Stop Freq
836.600000 MHz

CF Step
82.6600000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.67830000 GHz

Start Freq
856.600000 MHz

Stop Freq
2.50000000 GHz

CF Step
164.340000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
6.25000000 GHz

Start Freq
2.50000000 GHz

Stop Freq
10.00000000 GHz

CF Step
750.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
826.400000 MHz

Start Freq
821.400000 MHz

Stop Freq
831.400000 MHz

CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

Occupied Bandwidth	Occ BW % Pwr	99.00 %
4.0551 MHz	x dB	-26.00 dB
Transmit Freq Error		42.053 kHz
x dB Bandwidth		4.536 MHz*

File Operation Status, C:\TEMP.GIF file saved

Base Ch Freq 836.6 MHz Trig Free
 Occupied Bandwidth #3GPP W-CDMA

FCC ID:A3LGTS8300T 0BW Ch.4408
 Ref 24 dBm Atten 30 dB



Occupied Bandwidth	Occ BW % Pwr	99.00 %
4.1345 MHz	x dB	-26.00 dB
Transmit Freq Error	3.189 kHz	
x dB Bandwidth	4.590 MHz*	

File Operation Status, C:\TEMP.GIF file saved

Freq/Channel

Center Freq
836.600000 MHz

Start Freq
831.600000 MHz

Stop Freq
841.600000 MHz


CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

Base Ch Freq 846.6 MHz Trig Free
 Occupied Bandwidth #3GPP W-CDMA

FCC ID:A3LGTS8300T 0BW Ch.4458
 Ref 24 dBm Atten 30 dB



Occupied Bandwidth	Occ BW % Pwr	99.00 %
4.1900 MHz	x dB	-26.00 dB
Transmit Freq Error	-32.571 kHz	
x dB Bandwidth	4.585 MHz*	

File Operation Status, C:\TEMP.GIF file saved

Freq/Channel

Center Freq
846.600000 MHz

Start Freq
841.600000 MHz

Stop Freq
851.600000 MHz

CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

Measurement/Instrument Screen										
Control		Thermal Power						Call Parms		
Thermal Power Setup ▾		<p style="text-align: center;">Thermal Power 23.51 dBm</p> <p style="text-align: right;">Single</p>						Cell Power		
								-104.00		
								Channel Type		
								12.2k RNC		
								Paging Service		
								RB Test Mode		
								HSDPA Parameters		
								34.121 Preset Call Configs ▾		
								Channel (UARFCN) Parms		
				Active Cell Connected		Sys Type: UTRA FDD				
1 of 2					IntRef	Offset	R T			1 of 3

Measurement/Instrument Screen										
Control		Thermal Power						Call Parms		
Thermal Power Setup ▾		<p style="text-align: center;">Thermal Power 23.03 dBm</p> <p style="text-align: right;">Single</p>						Cell Power		
								-104.00		
								Channel Type		
								12.2k RNC		
								Paging Service		
								RB Test Mode		
								HSDPA Parameters		
								34.121 Preset Call Configs ▾		
								Channel (UARFCN) Parms		
				Active Cell Connected		Sys Type: UTRA FDD				
1 of 2					IntRef	Offset	R T			1 of 3

Measurement/Instrument Screen											
Control		Thermal Power						Call Parms			
Thermal Power Setup ▾		Thermal Power 22.65 dBm Single						Cell Power			
								-104.00			dBm/3.84 MHz
								Channel Type			
								12.2k RNC			
								Paging Service			
								RB Test Mode			
								HSDPA Parameters			
								34.121 Preset Call Configs ▾			
								Channel (UARFCN) Parms			
		Active Cell Connected				Sys Type: UTRA FDD					
1 of 2											1 of 3
				IntRef	Offset	R	T				