


# PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road • Columbia, MD 21045 • U.S.A.

TEL (410) 290-6652 • FAX (410) 290-6654

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE

SAMSUNG Electronics Co., Ltd.  
#271, Oseon-Dong, Gwangsan-Gu  
Gwangju-City, 506-723, KOREA  
Attention: Mr. Gi-Hyeong Lee

Dates of Tests: June 27, 2002  
Test Report S/N: 15.220620323.A3L  
Test Site: PCTEST Lab, Columbia MD

FCC ID

**A3LHP2777AT**

APPLICANT


**SAMSUNG Electronics Co., Ltd.**

FCC Rule Part(s): § 15.247; ANSI C-63.4 (1992)  
Classification: Digital Transmission System (DTS)  
Max Output Power: 0.063 W / 18.0 dBm Conducted (Refrigerator-Base)  
Method/System: Direct Sequence System (DSS)  
Equipment Type: HomePAD Refrigerator  
Frequency Range: 2412 – 2462 MHz  
Model No(s): HP2777AT



This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63-4.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*



  
Randy Ortanez  
President




PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report S/N: 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 1 of 31

## TABLE OF CONTENTS


<b>APPENDIX A -</b>	<b>COVER LETTER</b>	
<b>APPENDIX B -</b>	<b>ATTESTATION STATEMENT</b>	
<b>APPENDIX C -</b>	<b>TEST REPORT</b>	
<b>SCOPE</b>		<b>3</b>
<b>INTRODUCTION (SITE DESCRIPTION)</b>		<b>4</b>
<b>PRODUCT INFORMATION</b>		<b>5</b>
<b>DESCRIPTION OF TESTS</b>		
<b>A.</b>	<b>CONDUCTED EMISSIONS</b>	<b>6</b>
<b>B.</b>	<b>RADIATED EMISSIONS</b>	<b>7</b>
<b>C.</b>	<b>RESTRICTED BANDS</b>	<b>8</b>
<b>D.</b>	<b>ANTENNA REQUIREMENT</b>	<b>9</b>
<b>E.</b>	<b>DIRECT SEQUENCE BANDWIDTH</b>	<b>10</b>
<b>F.</b>	<b>MAXIMUM PEAK POWER OUTPUT</b>	<b>11</b>
<b>G.</b>	<b>POWER DENSITY</b>	<b>12 - 13</b>
<b>RADIATED MEASUREMENTS (FUNDAMENTAL &amp; HARMONICS)</b>		<b>17 - 25</b>
<b>RADIATED MEASUREMENTS (RESTRICTED BAND)</b>		<b>25 - 29</b>
<b>LIST OF TEST EQUIPMENT</b>		<b>30</b>
<b>CONCLUSION</b>		<b>31</b>
<b>APPENDIX D -</b>	<b>RECEIVER VERIFICATION REPORT</b>	
<b>APPENDIX E -</b>	<b>TEST PLOTS</b>	
<b>APPENDIX F -</b>	<b>FCC ID LABEL &amp; LOCATION</b>	
<b>APPENDIX G -</b>	<b>TEST SETUP PHOTOGRAPHS</b>	
<b>APPENDIX H -</b>	<b>EXTERNAL PHOTOGRAPHS</b>	
<b>APPENDIX I -</b>	<b>INTERNAL PHOTOGRAPHS</b>	
<b>APPENDIX J-</b>	<b>BLOCK DIAGRAM(S)</b>	
<b>APPENDIX K -</b>	<b>SCHEMATIC DIAGRAM(S)</b>	
<b>APPENDIX L -</b>	<b>OPERATIONAL DESCRIPTION</b>	
<b>APPENDIX M -</b>	<b>USER'S MANUAL</b>	
<b>APPENDIX N -</b>	<b>MPE REPORT</b>	

PCTEST™ PT. 15.247 REPORT	 <b>EVALUATION REPORT</b> 	Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator
		FCC ID: A3LHP2777A T
Page 2 of 31		

# MEASUREMENT REPORT



*Scope - Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.*





**§2983(a) General Information**

<b>Applicant Name:</b>	<b>SAMSUNG Electronics Co., Ltd.</b>
<b>Address:</b>	<b>#271, Oseon-Dong, Gwangsan-Gu Gwangju-City, 506-723, KOREA</b>
<b>Attention:</b>	<b>Mr. Gi-Hyeong Lee</b>

- FCC ID: **A3LHP2777AT**
- Class: Spread Spectrum Transceiver (DSS)
- Type: HomePAD Refrigerator
- Freq. Range: 2412 – 2462 MHz
- Method/System: Direct Sequence System (DSS)
- Model No(s): **HP2777AT**
- Max. RF Output Power: 0.063 W / 18.0 dBm Conducted
- Rule Part(s): § 15.247
- Dates of Tests: June 27, 2002
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 220620323.A3L

*NOTE: The receiver portion was tested and complies with Part 15B under the verification procedure.*

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 3 of 31

## INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-1992) and FCC Public Notice dated July 12, 1995 entitled "Guidance on Measurement for Direct Sequence Spread Spectrum Systems" were used in the measurement of **Samsung Spread Spectrum HomePAD Refrigerator**.

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

### PCTEST Location

The map at right shows the location of the PCTEST Lab, its proximity to the FCC Lab, the Columbia vicinity area, the Baltimore-Washington International (BWI) airport, and the city of Baltimore, and the Washington, D.C. area. (see Figure1).






Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T
			Page 4 of 31

## PRODUCT INFORMATION



---

### Equipment Description:

The Equipment under test (EUT) is the **Samsung Spread Spectrum HomePAD Refrigerator** using spread spectrum direct sequence and time division duplex techniques.

Frequency Range: 2412 – 2462 MHz  
 Channels: 1, 6, 11  
 Channel Separation: 5.0 MHz  
 Antenna: omni-directional antenna  
 Spread Spectrum Method: Direct Sequence (DBPSK modulation)  
 Max RF Output Power: 0.063 W / 18.0 dBm Conducted

CH	Rx/Tx Freq. (MHz)	CH	Rx/Tx Freq. (MHz)
1	2412.0	7	2442.0
2	2417.0	8	2447.0
3	2422.0	9	2452.0
4	2427.0	10	2457.0
5	2432.0	11	2462.0
6	2437.0		

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 5 of 31

## Description of Tests

### Conducted Emissions




Figure 4. Shielded Enclosure Line-Conducted Test Facility




Figure 2. Line Conducted Emission Test Set-Up




Figure 3. Wooden Table & Bonded LISNs




Figure 5. LISN Schematic Diagram

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure. It is manufactured by Ray Proof Series 81 (see Figure 2). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m. x 1.5m. wooden table 80cm. high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room (see Figure 3). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 4). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filters (100dB 14kHz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Solar LISN. LISN schematic diagram is shown in Figure 5. All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 450kHz to 30MHz with 20 msec. sweep time. The frequency producing the maximum level was reexamined using EMI/ Field Intensity Meter and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode. The bandwidth of the receiver was set to 10 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Appendix C. Each EME reported was calibrated using the HP8640B signal generator.

PCTEST™ PT. 15.247 REPORT		PCTEST EVALUATION REPORT		SAMSUNG	Reviewed By: Quality Manager
Test Report 15.220620323.A3L		Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 6 of 31

## Description of Tests (Continued)




Figure 6. 3-Meter Test Site




Figure 7. Dimensions of Outdoor Test Site




Figure 8. Turntable and System Setup




Figure 9. Normalized Site Attenuation Curves (H&V)

### Radiated Emissions

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using biconical antenna and from 200 to 1000 MHz using log-spiral antenna. Above 1 GHz, linearly polarized double horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antenna (see Figure 6). The test equipment was placed on a wooden and plastic bench situated on a 1.5 x 2 meter area adjacent to the measurement area (see Figure 7). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1 MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 8). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Appendix C. Each EME reported was calibrated using the HP8640B signal generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 9.

PCTEST™ PT. 15.247 REPORT	EVALUATION REPORT		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 7 of 31

## § 15.205 Restricted Bands



Special attention is made for the EUT's harmonic and spurious radiated emission in the restricted bands of operation. The EUT was tested from 9kHz and up to the tenth harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average measurements was used using RBW 1 MHz – VBW 10Hz and linearly polarized horn antennas. In addition, peak measurements were taken to ensure that the peak levels are not more than 20dB above the average limit. All out of band emissions, other than those created by the spreading sequence, data sequence, and the carrier modulation must not exceed the limits show in Table 2 per 15.209.

Frequency (MHz)	F/S (UV/m)	Meas. Dist. (Meters)
0.009-0.490	2400/F (kHz)	300
0.490-1.705	24000/F (kHz)	30
1.705-30.00	30	30
30.0-88.0	100	3
88.0-216.0	150	3
216.0-960.0	200	3
Above 960	500	3

Tab. 2. Radiated Emission Limits Per 15.209

### Test Equipment

HP 8566B	Spectrum Analyzer 100Hz-22HGhz
HP83017A	Microwave Analyzer 40dB Gain (0.5 – 26.5 GHz)
HP 3784A	Digital Transmission Analyzer
EMCO 3115	Horn Antenna (1 – 18GHz)
HP 8495A	20dB Attenuator (DC-40GHz) 0-70dB
HP 8493B	10dB Attenuator
MicroCoax Cables	Low Loss Microwave Cables (1-26.5 GHz)
CDI Dipoles	Dipole Antennas (30 – 1000 MHz)

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 8 of 31

## § 15.203 Antenna Requirement



---

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the applicant can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

The SAMSUNG **HP2777AT** unit complies with the requirement of §15.203. The antenna is a **permanently attached omni-directional antenna**.

### **CONCLUSION**

There are no provisions for connection to an external antenna. The unit meets the Antenna Requirements of §15.203.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 9 of 31

## §15.247(a)(2) – Direct Sequence Bandwidth (Refrigerator-Base Unit)

Res. Bandwidth = 100 kHz (5dB/div)  
 Vid. BW = 100 kHz  
 Span = 30 MHz  
 Ref. Level - 40 dBm  
 Sweep 10ms

(see attached spectrum plots)



FREQ (MHz)	Channel	6dB Bandwidth (MHz)
2412	1	9.95
2437	6	9.59
2462	11	10.37

Table 3. 6dB Bandwidth measurements

Minimum Standard – The transmitter shall have a minimum 6dB bandwidth of 500Hz (0.5 MHz).  
 These are conducted measurements.

**REMARKS:**

**PASS**

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 10 of 31

## §15.247(b) Maximum Peak Output Power (Refrigerator-Base Unit)

Minimum Standard – The maximum peak output power of the transmitter shall not exceed 1 watt. Radiated power measurements were taken at 3 meters with a power meter.

Max. Power Peak + Atten = dBm  $\Rightarrow$  Watts



FREQ (MHz)	Channel	Power Output (dBm)	Power Output (mW)
2412	1	18.0	63.0
2437	6	18.0	63.0
2462	11	18.0	63.0

Table 4. Output Power Measurements

**REMARKS:**

**PASS**

The table above was derived by taking EIRP reading with a peak power meter using the signal substitution method ensuring that the turn table azimuth and antenna height have been adjusted for the maximum power.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 11 of 31

## §15.247(c) Power Density (Refrigerator-Base Unit)

Minimum Standard – The transmitted power density averaged over any 1 second interval shall not be greater than 8dBm in any 3kHz bandwidth within these bands.

Res. Bandwidth = 3 kHz (7dB/div)  
 Vid. BW = 3 kHz  
 Span = 40 kHz  
 Ref. Level - 50dBm  
 Sweep 1000 sec

Peak + Atten = dBm ⇒ (Limit < 8dBm)

FREQ (MHz)	Channel	Power Density (dBm)
2412	1	- 10.5
2437	6	- 9.40
2462	11	- 9.22



Table 5. Output Power Density Data.

Minimum Standard – The transmitter power density average over and 1 second interval shall not be greater than 8dBm in any 3 kHz BW within these bands. These are conducted measurements.

**REMARKS:**

**PASS**



The table above was derived first by taking EIRP reading with a peak power meter using the signal substitution method ensuring that the turn table azimuth and antenna height have been adjusted for the maximum power. A spectrum analyzer with the RBW and VBW = 3 kHz is then used in place of the power meter to obtain a raw reading of the power density. A second signal substitution is done to obtain the Power Density level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 12 of 31

## 2.5G Power Density for Refrigerator-Base Unit

---

FREQ. (MHz)	Level* (dBm)	AFCL** (dB)	POL (H/V)	(dBμV/m)	F/S (μV/m)	(W)	(dBm)
2412	- 55.0	32.7	V	84.7	17179.1	8.85E^-05	- 10.529
2437	- 54.0	32.8	V	85.8	19498.4	0.000114	- 9.4288
2462	- 53.9	32.9	V	86.0	19952.6	0.000119	- 9.2288

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 13 of 31

## RADIATED Measurements (Fundamental & Harmonics)

### A. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2412 MHz (1 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 1

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S ( $\mu$ V/m)	F/S (dB $\mu$ V/m)	Margin (dB)
2412	- 26.5	32.70	V	Peak	457088	113.2	n/a
4824	- 102.5	40.39	V	Peak	175.59	44.89	9.11
7236	- 107.5	47.42	V	Peak	221.82	46.92	6.58
9648	< - 120						
12060	< - 120						






Figure 10. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

#### NOTES:

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 14 of 31

## RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

### B. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2437 MHz (1 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 6

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2437	- 26.55	32.8	V	Peak	459727	113.25	n/a
4874	- 102.1	40.5	V	Peak	186.209	45.40	8.6
7311	- 106.8	48.0	V	Peak	257.040	48.20	5.8
9748	< - 120						
12185	< - 120						






Figure 11. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 15 of 31

## RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

### C. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (1 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2462	- 26.7	32.9	V	Peak	457088	113.2	n/a
4924	- 101.8	40.7	V	Peak	197.242	45.90	8.1
7386	- 106.5	48.2	V	Peak	272.27	48.70	5.3
9848	< - 120						
12310	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

#### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 16 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2412 MHz (2 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 1

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2412	- 26.5	32.70	V	Peak	457088	113.2	n/a
4824	- 102.2	40.39	V	Peak	181.761	45.19	8.81
7236	- 107.2	47.42	V	Peak	229.615	47.22	6.58
9648	< - 120						
12060	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 17 of 31

## RADIATED Measurements (Fundamental & Harmonics) -(CONT.)

### D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2437 MHz (2 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 6

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2437	- 26.55	32.8	V	Peak	459727	113.25	n/a
4874	- 102.5	40.5	V	Peak	177.828	45.00	9.0
7311	- 106.5	48.0	V	Peak	266.073	48.50	5.5
9748	< - 120						
12185	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

#### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 18 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (2 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2462	- 26.7	32.9	V	Peak	457088	113.2	n/a
4924	- 102	40.7	V	Peak	192.752	45.70	8.3
7386	- 106.2	48.2	V	Peak	281.838	49.00	5.0
9848	< - 120						
12310	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 19 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2412 MHz (5.5 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 1

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2412	- 26.5	32.70	V	Peak	457088	113.2	n/a
4824	- 101.3	40.39	V	Peak	201.604	46.09	7.91
7236	- 107.0	47.42	V	Peak	234.963	47.42	6.58
9648	< - 120						
12060	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 20 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2437 MHz (5.5 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 6

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2437	- 25.55	32.8	V	Peak	515822	114.25	n/a
4874	- 102.2	40.5	V	Peak	184.077	45.30	8.7
7311	- 106.2	48.0	V	Peak	275.423	48.80	5.2
WE9748	< - 120						
12185	< - 120						




Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 21 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (5.5 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2462	- 26.70	32.9	V	Peak	457088	113.2	n/a
4924	- 101.5	40.7	V	Peak	204.174	46.20	7.8
7386	- 105.9	48.2	V	Peak	291.743	49.30	4.7
9848	< - 120						
12310	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 22 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2412 MHz (11 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 1

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2412	- 28.9	32.70	V	Peak	346737	110.8	n/a
4824	- 101.1	40.39	V	Peak	206.30	46.29	7.71
7236	- 106.2	47.42	V	Peak	257.632	48.22	6.58
9648	< - 120						
12060	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 23 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2437 MHz (11 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 6

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2437	- 29.1	32.8	V	Peak	342768	110.7	n/a
4874	- 102.0	40.5	V	Peak	188.365	45.50	8.5
7311	- 106.0	48.0	V	Peak	281.838	49.00	5.0
9748	< - 120						
12185	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 24 of 31

# RADIATED Measurements (Fundamental & Harmonics) - (CONT.)

## D. Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (11 Mbps)  
 Distance of Measurements: 3 meters  
 Channel: 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2462	- 28.10	32.9	V	Peak	389045	111.8	n/a
4924	- 101.0	40.7	V	Peak	211.349	46.50	7.5
7386	- 105.5	48.2	V	Peak	305.492	49.70	4.3
9848	< - 120						
12310	< - 120						






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 25 of 31

## RADIATED Measurements (Restricted Band)

### Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (11 Mbps)  
 Distance of Measurements: 3 meters  
 Channel(s): 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S ( $\mu$ V/m)	F/S (dB $\mu$ V/m)	Margin (dB)
2483.9	- 92.2	33.0	V	- 47.429	245.471	47.8	- 6.2
2484.4	- 93.5	33.0	V	- 48.729	211.349	46.5	- 7.5
2484.5	- 95.0	33.1	V	- 50.129	179.887	45.1	- 8.9
2486.1	- 90.6	33.1	V	- 45.729	298.538	49.5	- 4.5
2491.3	- 90.0	33.2	V	- 45.029	323.594	50.2	- 3.8
2495.0	- 91.3	33.2	V	- 46.329	278.612	48.9	- 5.1






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

#### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 26 of 31

## RADIATED Measurements (Restricted Band)

### Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (5.5 Mbps)  
 Distance of Measurements: 3 meters  
 Channel(s): 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S ( $\mu\text{V}/\text{m}$ )	F/S ( $\text{dB}\mu\text{V}/\text{m}$ )	Margin (dB)
2483.9	- 93.0	33.0	V	- 48.229	223.872	47.0	- 7.00
2448.3	- 94.5	33.0	V	- 49.729	188.365	45.5	- 8.50
2484.5	- 97.2	33.1	V	- 52.329	139.637	42.9	- 11.1
2486.1	- 93.1	33.1	V	- 48.229	223.872	47.0	- 7.00
2491.3	- 92.0	33.2	V	- 47.029	257.04	48.2	- 5.80
2491.0	- 99.0	33.2	V	- 54.029	114.815	41.2	- 12.8






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500  $\mu\text{V}/\text{m}$  (54dBu/m)

#### NOTES:

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 27 of 31

# RADIATED Measurements (Restricted Band)

## Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (2 Mbps)  
 Distance of Measurements: 3 meters  
 Channel(s): 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	F/S (dBμV/m)	Margin (dB)
2483.7	- 94.3	33.0	V	- 49.529	192.752	45.7	- 8.3
2484.3	- 93.0	33.0	V	- 48.229	223.872	47.0	- 7.0
2484.5	- 97.0	33.1	V	- 52.129	142.889	43.1	- 10.9
2486.2	- 92.2	33.1	V	- 47.329	248.313	47.9	- 6.1
2491.0	- 93.0	33.2	V	- 48.029	229.087	47.2	- 6.8
2492.0	- 100.0	33.2	V	- 55.029	102.329	40.2	- 13.8






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

### NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 28 of 31

## RADIATED Measurements (Restricted Band)

### Transmitter Portion (Refrigerator-Base Unit)

Operating Frequency: 2462 MHz (1 Mbps)  
 Distance of Measurements: 3 meters  
 Channel(s): 11

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S ( $\mu$ V/m)	F/S (dB $\mu$ V/m)	Margin (dB)
2483.6	- 93.0	33.0	V	- 48.229	223.872	47.0	- 7.0
2484.2	- 94.0	33.0	V	- 49.229	199.526	46.0	- 8.0
2484.5	- 94.9	33.1	V	- 50.029	181.97	45.2	- 8.8
2486.0	- 90.6	33.1	V	- 45.729	298.538	49.5	- 4.5
2491.3	- 94.4	33.2	V	- 49.429	194.984	45.8	- 8.2
2495.0	- 91.3	33.2	V	- 46.329	278.612	48.9	- 5.1






Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

#### NOTES:



1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: \* Restricted Band)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.
7. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
8. < - 120 are below the analyzer floor level.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 29 of 31

## TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	12/05/02	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/03	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (9kHz-1.8GHz)	06/02/03	3144A02458
Spectrum Analyzer	HP 8591A (9kHz-1.8GHz)	10/15/02	3108A02053
Spectrum Analyzer	HP 8594A (9kHz-2.9GHz)	11/02/02	3051A00187
Signal Generator*	HP 8640B (500Hz-1GHz)	06/02/03	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/02/03	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/02	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/03	0792-03271
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/03	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/02	0608-03241
Quasi-Peak Adapter	HP 85650A	08/09/02	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/03	0194-04082
RG58 Coax Test Cable	No. 167		n/a
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Transient Limiter	HP 11947A (9kHz-200MHz)		2820A00300
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance		Design 1295, 1332, 0355
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set) A100		5118
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (2)	3816/2		1077, 1079
EMCO LISN	3725/2		2009
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8591A		3034A01395
Modulation Analyzer	HP 8901A		2432A03467
NTSC Pattern Generator	Leader 408		0377433
Noise Figure Meter	HP 8970B		3106A02189
Noise Figure Meter	Ailtech 7510		TE31700
Noise Generator	Ailtech 7010		1473
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285



\* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT 		Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T Page 30 of 31

## Conclusion

---

The data collected shows that the **SAMSUNG HomePAD Refrigerator FCC ID: A3LHP2777AT** complies with Part 15C of the FCC Rules.

PCTEST™ PT. 15.247 REPORT	 EVALUATION REPORT			Reviewed By: Quality Manager
Test Report 15.220620323.A3L	Test Dates: June 27, 2002	EUT Type: HomePAD Refrigerator	FCC ID: A3LHP2777A T	Page 31 of 31