

# EMC TEST REPORT

Project No.	LBE20115122		Revision No.	NONE	
Applicant	Name of organization		Samsung Electronics Co., Ltd.		
	Address		18600 Broadwick St. Rancho Dominguez CA 90220		
	Date of application		October 20,2011		
EUT Equipment Under Test	Type of device		Class B personal computers and peripherals		
	Equipment authorization		<input type="checkbox"/> Declaration of Conformity <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Verification		
	Kind of product		LED Monitor		
	Model No.		LS19B150		
			Variant Model No.		None
	Manufacturer		Tianjin Samsung Electronics Co., LTD. Weisi Rd. Micro-Electronic Industrial Park, Jingang Rd. Xiqing Dist, Tianjin, 300385 China		
Applied Standards	FCC Part 15, Subpart B class B				
	ANSI C63.4-2009				
Test period	October 20,2011~ October 26, 2011				
Issue date	October 27, 2011				
<b>Test result : Complied</b>					
The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)					
Tested by : Yangjie	Reviewed by : Xiao Li				
					

The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CSQAL

Le



TSEC Wei 4 Road, Microelectronics Industrial Park, Jingang High way, Tianjin, China  
Tel: 86 22 23961234, Fax: 86 22 23961234-5214



According to Sec. 2.1077, 47 CFR of the FCC Rules.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

<b>Equipment EUT Type</b>	Class B personal computers and peripherals
<b>Kind of product</b>	LED Monitor
<b>Trade Name</b>	Samsung Electronics
<b>Model</b>	<b>LS19B150</b>
<b>Applied Rules</b>	FCC Part 15, Subpart B Class B
	ANSI C63.4-2009
<b>Manufacturer</b>	Tianjin Samsung Electronics Co., LTD. Weisi Rd. Micro-Electronic Industrial Park, Jingang Rd. Xiqing Dist, Tianjin, 300385 China

We hereby *declare that* the equipment bearing the trade name and model number specified above was tested conforming to the applicable FCC Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the Commission's requirements.

<b>U.S. RESPONSIBLE PARTY</b>	Samsung Electronics America QA Lab 18600 Broadwick St. Rancho Dominguez CA 90220
<b>CONTACT PERSON</b>	 <u>Mr. Peter Ra, Manager</u> E-Mail : <a href="mailto:raaaa@samsung.com">raaaa@samsung.com</a> Tel : 1-310-900-5250   Fax : 1-310-537-5500

---

# Table of contents

## **1. Summary of test results**

1.1 Emission

## **2. General Information**

2.1 Test facility

## **3. Test configuration**

3.1 Test Peripherals  
3.2 EUT operating mode  
3.3 Details of Sampling  
3.4 Used cable description  
3.5 EUT Description  
3.6 Description of the EUT exercising method  
3.7 Measurement uncertainty

## **4. Result of individual tests**

4.1 Conducted disturbance  
4.2 Radiated disturbance

## **Appendix – EUT photography**

## 1. Summary of test results

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result	Remarks
<input checked="" type="checkbox"/>	Conducted Disturbance	FCC Part 15 Subpart B	Complied	Meets Class B Limit
<input checked="" type="checkbox"/>	Radiated Disturbance	ANSI C63.4-2009	Complied	Meets Class B Limit

- Note : These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

## 2. General Information

### 2.1 Test facility

The following firm has submitted the information required by Section 2.948 of the FCC Rules for measuring devices subject to Certification under Parts 15 & 18. The FCC takes no responsibility regarding the capability of this firm for performing the required measurements. Accordingly, this firm should not advertise or otherwise imply FCC approval of CSQAL.

CHINA SAMSUNG QUALITY ASSURANCE LABORATORY is LOCATED ON Block D, 17 - 19, Wei 4 Road, Microelectronics Industrial Park, Jingang Highway, Tianjin China.

Registration Number: 745769

E-mail Address:xiaoli@samsung.com

Phone Number:86-22-2396-1234-5211

All testing are performed in Semi-anechoic chambers conforming to the site attenuation Characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2 and Shielded rooms.

CSQAL is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

### 3. Test Setup configuration

#### 3.1 Test Peripherals

The peripherals which were interconnected to the EUT during the test are as follows:

Item	Model No.	Serial No.	Manufacturer	Note
LED Monitor	LS19B150	-	Samsung	EUT
ADAPTER	AD-3014N	CN07BN4400394DSE38B8TD7VE	Samsung	FOR EUT
PC	DM-V200	ZLPZ9WAZ500828F	Samsung	-
Printer	CLP-315	Z0CEBAZZ500252J	Samsung	-
USB Keyboard	SK-8185	OY526K	Dell	-
USB Mouse	MOC5UO	J0G00G9L	Dell	-

#### 3.2 EUT operating mode(s)

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

<b>Operating Mode 1</b>	D-Sub (PC Video IN or Analog) IN Display
-------------------------	--

#### 3.3 Details of Sampling

Customer selected, single unit.

#### 3.4 Cable description

The type(s) of cables which were connected to the ports (of the EUT) are as follows:

No	Connect Cable	Length [m]	Ferrite core [Y/N]	Remark
1	VGA in	1.8	Y	To PC
2	POWER	1.5	N	FOR EUT

\*) One ferrite core was used.



### 3.5 EUT Description


The following features describe EUT represented by this report:

MODEL NAME		S19B150N
Panel	Size	18.5 inches (47 cm)
	Display area	409.8 mm(H) X 230.4 mm(V)
	Pixel Pitch	0.300 mm (H) x 0.300 mm (V)
Synchroniza-tion	Horizontal	30 ~ 81 kHz
	Vertical	56 ~ 75 Hz
Display Color		16.7M
Resolution	Optimum resolution	1366x768 @ 60Hz
	Maximum resolution	1366x768 @ 60Hz
Input Signal, Terminated		RGB Analog 0.7 Vp-p ± 5% separate H/V sync, Composite, SOG TTL level (V high ≥ 2.0V, V low ≤ 0.8V)
Maximum Pixel Clock		85.5MHz (Analog)
Power Supply		This product supports 100-240 V. Since the standard voltage may differ from country to country, please check the label on the back of the product.
Signal Cable		15pin-to-15pin D-sub cable, Detachable
Dimensions (WxHxD) / Weight		445 x 273 x 53 mm (17.5 x 10.7 x 2.1 inches) (Without Stand) 445 x 348 x 177 mm (17.5 x 13.7 x 7.0 inches) (With Stand) / TBD kg (TBD lbs)
Environmen-tal consider-ations	Operating	Operating Temperature : 50°F ~ 104°F (10°C ~ 40°C) Humidity : 10 % ~ 80 %, non-condensing
	Storage	Storage Temperature : -4°F ~ 113°F (-20°C ~ 45°C) Humidity : 5 % ~ 95 %, non-condensing
Tilt		-1.0°(±1.0°) ~ +21.0°(±1.0°)

### 3.6 Description of the EUT exercising method

The EUT exercise program used during EMI testing was CSQAL standardized test program for MS Windows. The program repetitively sends a screen of H – Character to the display. Connect video output of computer on EUT's PC IN (D-sub) port and scrolled H – character continuously on EUT's screen.

The EUT system includes a monitor, the operational conditions shown as follows, within the selected area.



**Notes:**

1. Set the brightness control to maximum
2. Set the contrast control to maximum
3. Display a pattern of a full screen of scrolling letter-H characters with a font size to get as close

as possible to three characters per linear cm and use single line spacing

### **3.7 Measurement uncertainty**

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

<b>Test type</b>		<b>Measurement uncertainty (C.L. 95 %, k = 2)</b>	
Disturbance voltage at the mains terminals		2. 9 dB	
Radiated Disturbance	Horizontal	30 MHz - 1 GHz	3. 86 dB
	Vertical	30 MHz - 1 GHz	4. 90 dB
	Horizontal	1GHz - 6 GHz	3. 964 dB
	Vertical	1GHz - 6 GHz	3. 964 dB

## 4. Results of individual test

### 4.1 Conducted disturbance

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.

The EUT measured in accordance with the methods described in standards. Including the worst-case data points for each tested configuration.

#### Limits for conducted disturbance at the mains ports of class B ITE

Frequency range Limits MHz	Limits dB(µV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Note 1: 1 µV is regarded as 0 dB.

Note 2: The limits shall decreases linearly with the logarithm of the frequency in the range 150 – 500 kHz.

Note 3: If the average limit is met in the measurement with quasi-peak detector, the measurement with average detector is unnecessary.

Note 4: The lower limit shall apply at the transition frequency.

If the reading on the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 seconds at each measurement frequency, the highest reading shall be recorded, with the exception of any brief isolated high reading (which shall be ignored). Including the worst-case data points for each tested configuration.

#### 4.1.1 Test instrumentation

Test instrumentation used in the Conducted disturbance test was as follows:


Test instrumentation	Model name	Manufacturer	Serial or Firmware (No./Ver.)	Calibration	
				Date	Interval (Month)
Test Software	EP5CE	TOYO	V 4.7.10	N/A	N/A
Measuring receiver	ESCI	R&S	101027	2011.03.26	12
Artificial mains network	ENV216	R&S	101122	2011.08.23	12
Artificial mains network	ENV216	R&S	101059	2011.08.23	12
ISN	ISN T800	TESEQ	28602	2011.03.02	12
ISN	ISN T8-CAT6	TESEQ	27286	2011.03.02	12

#### 4.1.2 Photograph of the test Configuration

**(Front)**



**(Rear)**



### 4.1.3 Test results

Test date	2011.10.20		Test engineer		Yangjie	
Climate condition	Ambient temperature	26°C	Relative humidity	36%	Atmospheric pressure	101.9 kPa
Test place	Shielded Room #2					


### 4.1.4 Test data

#### ■ Operating Mode: VGA IN

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (640\*480@60Hz, 1024\*768@60Hz, 1366\*768@60Hz) then choose the worst one (1366\*768@60Hz) for final evaluation.



## Final Result

## --- N Phase ---

No.	Frequency	Reading QP	Reading AV	c. f	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV	Remark
	[MHz]	[dB(μV)]	[dB(μV)]		[dB]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB]	[dB]	
1	0.19539	43.4	31.9	9.6	53.0	41.5	63.8	53.8	10.8	12.3	
2	0.26081	40.7	32.2	9.6	50.3	41.8	61.4	51.4	11.1	9.6	
3	0.45702	33.1	29.9	9.6	42.7	39.5	56.7	46.7	14.0	7.2	
4	0.52144	32.2	30.0	9.6	41.8	39.6	56.0	46.0	14.2	6.4	
5	10.69508	30.4	22.0	9.8	40.2	31.8	60.0	50.0	19.8	18.2	

## --- L1 Phase ---

No.	Frequency	Reading QP	Reading AV	c. f	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV	Remark
	[MHz]	[dB(μV)]	[dB(μV)]		[dB]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB]	[dB]	
1	0.19549	43.1	31.0	9.6	52.7	40.6	63.8	53.8	11.1	13.2	
2	0.26095	40.5	31.5	9.6	50.1	41.1	61.4	51.4	11.3	10.3	
3	0.3265	36.2	28.5	9.6	45.8	38.1	59.5	49.5	13.7	11.4	
4	0.45808	32.6	29.0	9.6	42.2	38.6	56.7	46.7	14.5	8.1	
5	0.39116	33.2	28.1	9.6	42.8	37.7	58.0	48.0	15.2	10.3	

Note) Level (Quasi-Peak and/or Average) = Meter Reading (Quasi-Peak and/or Average) + Factor (LISN Insertion Loss + Cable Loss)

Margin = Limit – Level (Quasi-Peak and/or Average)



## 4.2 Radiated disturbance

Of those disturbances above ( $L - 20\text{dB}$ ), where  $L$  is the limit level in logarithmic units, record at least the disturbance levels and the frequencies of the six highest disturbances.

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin. All measurements were taken utilizing quasi-peak detection unless stated otherwise.

Measurements were performed at an antenna to EUT distance of 3 meters and elevated between 1 and 4 meters. Both vertical and horizontal antenna polarizations were measured.

Above 1GHz, peak detector function mode was used with resolution bandwidth of 1 MHz and a video bandwidth of 1 MHz. If the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range Limits MHz	Quasi-peak Limits (microvolts/meter)
	Class B
<b>30 to 88</b>	<b>100</b>
<b>88 to 216</b>	<b>150</b>
<b>216 to 960</b>	<b>200</b>
<b>Above 960</b>	<b>500</b>

Note 1: The lower limit shall apply at the transition frequency.  
 Note 2: Additional provisions may be required for cases where interference occurs.  
 Note 3: 1  $\mu\text{V}/\text{m}$  is regarded as 0 dB.

Measurements above 1GHz were performed at an antenna to EUT distance of 3 meters and elevated 1 to 4 meters in FAC. Both vertical and horizontal antenna polarizations were measured.

### Limits for radiated disturbance of ITE at a measuring distance of 3 m

Frequency range Limits MHz	Class A		Class B	
	Peak dB( $\mu\text{V}/\text{m}$ )	Average dB( $\mu\text{V}/\text{m}$ )	Peak dB( $\mu\text{V}/\text{m}$ )	Average dB( $\mu\text{V}/\text{m}$ )
<b>1000 to 3000</b>	<b>76</b>	<b>56</b>	<b>70</b>	<b>50</b>
<b>3000 to 6000</b>	<b>80</b>	<b>60</b>	<b>74</b>	<b>54</b>

Note 1: The lower limit shall apply at the transition frequency.

Including the worst-case data points for each tested configuration.

o



#### 4.2.1 Test instrumentation

Test instrumentation used in the Radiated disturbance was as follows:

30MHz~1GHz

<b>Test instrumentation</b>	<b>Model name</b>	<b>Manufacturer</b>	<b>Serial or Firmware (No./Ver.)</b>	<b>Calibration</b>	
				<b>Date</b>	<b>Interval (Month)</b>
Test Software	EP5/RE	TOYO	V 4.7.10	N/A	N/A
Bi-con Antenna	CBL6112D	SCHAFFNER	29069	2011.04.04	24
EMI Receiver	ESCI	R&S	101026	2011.03.26	12
AMPLIFIER	310N	SONOMA	300911	2011.08.23	12
Ant Mast	MA4000	INN CO	-	N/A	N/A
Mast Controller	CO2000	INN CO	-	N/A	N/A
RF Selector	NS4900N	TOYO	-	N/A	N/A


#### 1GHz-2GHz

<b>Test instrumentation</b>	<b>Model name</b>	<b>Manufacturer</b>	<b>Serial or Firmware (No./Ver.)</b>	<b>Calibration</b>	
				<b>Date</b>	<b>Interval (Month)</b>
Test Software	EP5/RE	TOYO	V 4.7.10	N/A	N/A
Broad-Band Horn Antenna	BBHA9120B	Schwarzbeck	519	2011.04.05	24
EMI Receiver	ESU26	R&S	100243	2011.03.26	12
AMPLIFIER	TPA0108-40	TOYO	0934	2011.08.23	12
Ant Mast	MA4000	INN CO	-	N/A	N/A
Mast Controller	CO2000	INN CO	-	N/A	N/A
Table Controller	CO2000	INN CO	-	N/A	N/A


#### 4.2.2 Photograph of the test Configuration

30MHz~1GHz

**(Front)**



**(Rear)**



---

**1GHz-2GHz**

**(Front)**



**(Rear)**





#### 4.2.3 Test results

##### 30MHz~1GHz


Test date	2011.10.21		Test engineer		Yangjie	
Climate condition	Ambient temperature	24 °C	Relative humidity	38%	Atmospheric pressure	101.6 kPa
Test place	3m Semi-Anechoic Chamber					

##### ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (640\*480@60Hz, 1024\*768@60Hz, 1366\*768@60Hz) then choose the worst one (1366\*768@60Hz) for final evaluation.



## Final Result

No.	Frequency [MHz]	(P)	S.C	Reading QP [dB ( $\mu$ V)]	c. f [dB(1/m)]	Result QP [dB ( $\mu$ V/m)]	Limit QP [dB]	Margin QP [dB]	Height [cm]	Angle [°]	Remark
1	84.410	H	S	39.5	-16.3	23.2	40.0	16.8	226.0	247.7	
2	132.614	H	S	37.7	-11.4	26.3	43.5	17.2	224.0	284.1	
3	264.025	H	S	38.8	-9.1	29.7	46.0	16.3	102.0	207.8	
4	312.047	V	S	39.6	-8.3	31.3	46.0	14.7	173.0	189.9	
5	504.030	V	S	38.5	-3.3	35.2	46.0	10.8	100.0	162.4	
6	552.078	V	S	35.8	-1.6	34.2	46.0	11.8	101.0	176.4	
7	750.025	V	S	37.6	0.0	37.6	46.0	8.4	120.0	335.7	
8	36.404	V	S	44.7	-9.2	35.5	40.0	4.5	100.0	60.3	
9	48.245	H	S	46.4	-15.2	31.2	40.0	8.8	393.0	311.7	
10	78.376	H	S	40.4	-17.3	23.1	40.0	16.9	236.0	37.0	

Note) Receiving antenna polarization : Horizontal and/or Vertical

Test Distance : 3m, Antenna Height : 1 to 4 meters

Result (Quasi-Peak) = Reading QP + C.F (Antenna Factor + Cable Loss - Amp. Gain)

Margin QP (Quasi-Peak) = Limit – Level QP

## 1GHz-2GHz


<b>Test date</b>	2011.10.21		<b>Test engineer</b>		Yangjie	
<b>Climate condition</b>	<b>Ambient temperature</b>	24 °C	<b>Relative humidity</b>	38%	<b>Atmospheric pressure</b>	101.6 kPa
<b>Test place</b>	3m Semi-Anechoic Chamber					

### ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (640\*480@60Hz, 1024\*768@60Hz, 1366\*768@60Hz), then choose the worst one (1366\*768@60Hz) for final evaluation.



No.	Frequency [MHz]	(P)	S. C	Reading [dB(μV)]		Reading [dB(μV)]		c. f.		Result [dB(1/m)]		Result [dB(1/m)]		Limit [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]		Margin [cm]		Angle [°]		Remark
				AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	
1	1501.603	H	S	37.9	53.1	-15.0	22.9	38.1	50.0	70.0	27.1	31.9	198.0	206.7	27.1	31.9	198.0	206.7	27.1	31.9	198.0	206.7	206.7	
2	1602.564	H	S	39.8	62.8	-14.6	25.2	48.2	50.0	70.0	24.8	21.8	198.0	206.7	24.8	21.8	198.0	206.7	24.8	21.8	198.0	206.7	206.7	
3	1147.436	H	S	37.5	59.4	-15.9	21.6	43.5	50.0	70.0	28.4	26.5	198.0	27.6	28.4	26.5	198.0	27.6	28.4	26.5	198.0	27.6	27.6	
4	1485.577	H	S	37.8	62.4	-15.1	22.7	47.3	50.0	70.0	27.3	22.1	198.0	310.1	27.3	22.1	198.0	310.1	27.3	22.1	198.0	310.1	310.1	
5	1463.141	H	S	39.5	58.0	-15.2	24.3	42.8	50.0	70.0	25.7	27.2	198.0	310.1	25.7	27.2	198.0	310.1	25.7	27.2	198.0	310.1	310.1	
6	1539.103	H	S	36.0	49.6	-13.6	22.4	36.0	50.0	70.0	27.6	34.0	198.0	276.9	27.6	34.0	198.0	276.9	27.6	34.0	198.0	276.9	276.9	
7	1181.090	H	S	36.0	61.8	-15.7	20.3	46.1	50.0	70.0	29.7	23.9	198.0	353.1	29.7	23.9	198.0	353.1	29.7	23.9	198.0	353.1	353.1	
8	1790.064	H	S	35.5	54.2	-13.7	21.8	40.5	50.0	70.0	28.2	29.5	198.0	156.1	28.2	29.5	198.0	156.1	28.2	29.5	198.0	156.1	156.1	
9	1722.737	H	S	35.7	53.7	-13.6	22.1	40.1	50.0	70.0	27.9	29.9	198.0	277.3	27.9	29.9	198.0	277.3	27.9	29.9	198.0	277.3	277.3	
10	1980.769	H	S	35.1	49.3	-12.7	22.4	36.6	50.0	70.0	27.6	33.4	302.0	10.3	27.6	33.4	302.0	10.3	27.6	33.4	302.0	10.3	10.3	

Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3m, Antenna Height : 1 to 4 meters

Result (Average) = Reading AV + C.F (Antenna Factor + Cable Loss - Amp. Gain)

Margin AV (Average) = Limit – Result AV



---

## **Appendix A – EUT photography**

**(Front)**





**(Rear)**





**(Power Adapter)**





---

(Panel 1)





(Board 1)





(Board 2)



(Crystal)

