

# EMC TEST REPORT

Project No.	LBE20122289		Revision No.	NONE	
FCC ID	A3LLS24B150				
Applicant	Name of organization		Samsung Electronics Co., Ltd.		
	Address		18600 Broadwick St. Rancho Dominguez CA 90220		
	Date of application		April 13, 2012		
EUT Equipment Under Test	Type of device		Class B personal computers and peripherals		
	Equipment authorization		<input type="checkbox"/> Declaration of Conformity <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Verification		
	Kind of product		LCD MONITOR		
	Model No.		LS24B150		
			Variant Model No.	None	
	Manufacturer		Tianjin Samsung Electronics Co., LTD. Weisi Rd. Micro-Electronic Industrial Park, Jingang Rd. Xiqing Dist, Tianjin, 300385 China		
Applied Standards		FCC Part 15, Subpart B class B			
		ANSI C63.4-2009			
Test period		April 16, 2012 ~ April 19, 2012			
Issue date		April 21, 2012			
<b>Test result : Complied</b>					
The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)					
Tested by : Xinxing Fu		Reviewed by : Xiao Li			
					

The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CSQAL



TSEC Wei 4 Road, Microelectronics Industrial Park, Jingang High way, Tianjin, China  
Tel: 86 22 23961234, Fax: 86 22 23961234-5214



According to Sec. 2.1077, 47 CFR of the FCC Rules.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

<b>Equipment EUT Type</b>	Class B personal computers and peripherals
<b>Kind of product</b>	<b>LCD Monitor</b>
<b>Trade Name</b>	Samsung Electronics
<b>Model</b>	<b>LS24B150</b>
<b>Applied Rules</b>	FCC Part 15, Subpart B Class B
	ANSI C63.4-2009
<b>Manufacturer</b>	Tianjin Samsung Electronics Co., LTD. Weisi Rd. Micro-Electronic Industrial Park, Jingang Rd. Xiqing Dist, Tianjin,300385 China

We hereby *declare* that the equipment bearing the trade name and model number specified above was tested conforming to the applicable FCC Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the Commission's requirements.

U.S. RESPONSIBLE PARTY	Samsung Electronics America QA Lab 18600 Broadwick St. Rancho Dominguez CA 90220
CONTACT PERSON	 <u>Mr. Peter Ra, Manager</u> E-Mail : <a href="mailto:raaaa@samsung.com">raaaa@samsung.com</a> Tel : 1-310-900-5250   Fax : 1-310-537-5500

---

# Table of contents

## **1. Summary of test results**

1.1 Emission

## **2. General Information**

2.1 Test facility

## **3. Test configuration**

3.1 Test Peripherals

3.2 EUT operating mode

3.3 Details of Sampling

3.4 Used cable description

3.5 EUT Description

3.6 Description of the EUT exercising method

3.7 Measurement uncertainty

## **4. Result of individual tests**

4.1 Conducted disturbance

4.2 Radiated disturbance

## **Appendix – EUT photography**



## 1. Summary of test results

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result	Remarks
<input checked="" type="checkbox"/>	Conducted Disturbance	FCC Part 15 Subpart B  ANSI C63.4-2009	Complied	Meets Class B Limit
<input checked="" type="checkbox"/>	Radiated Disturbance		Complied	Meets Class B Limit

- Note : These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

## 2. General Information

### 2.1 Test facility

The following firm has submitted the information required by Section 2.948 of the FCC Rules for measuring devices subject to Certification under Parts 15 & 18. The FCC takes no responsibility regarding the capability of this firm for performing the required measurements. Accordingly, this firm should not advertise or otherwise imply FCC approval of CSQAL.

CHINA SAMSUNG QUALITY ASSURANCE LABORATORY is LOCATED ON Block D, 17 - 19, Wei 4 Road, Microelectronics Industrial Park, Jingang Highway, Tianjin China.

Registration Number: 745769

E-mail Address:xiaoli@samsung.com

Phone Number:86-22-2396-1234-5211

All testing are performed in Semi-anechoic chambers conforming to the site attenuation Characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2 and Shielded rooms.

CSQAL is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

### 3. Test Setup configuration

#### 3.1 Test Peripherals

The peripherals which were interconnected to the EUT during the test are as follows:

Item	Model No.	Serial No.	Manufacturer	Note
LCD Monitor	LS24B150	-	Samsung	EUT
ADAPTER	PS30W-14J1	-	Samsung	FOR EUT
PC	DM-V200-PA15	500832K	Samsung	-
USB Keyboard	SK-8185	OY526K	Dell	-
USB Mouse	SNJ-B138	Z164146	Dell	-
Printer	ML-2545	Z6FJBACB600011N	Samsung	-

#### 3.2 EUT operating mode(s)

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

<b>Operating Mode 1</b>	D-Sub (PC Video IN or Analog) IN Display
<b>Operating Mode 2</b>	DVI IN Display

#### 3.3 Details of Sampling

Customer selected, single unit.

#### 3.4 Cable description

The type(s) of cables which were connected to the ports (of the EUT) are as follows:

No	Connect Cable	Length [m]	Ferrite core [Y/N]	Remark
1	VGA in	1.5	Y	To PC
2	DVI in	1.5	Y	To PC
3	POWER	1.8	N	FOR EUT

### 3.5 EUT Description


The following features describe EUT represented by this report:

<b>Model Name</b>		<b>S19B150B</b>	<b>S24B150BL</b>
Panel	Size	18.5 Inches (47 cm)	23.6 Inches (59 cm)
	Display area	409.8 mm (H) x 230.4 mm (V)	521.28 mm (H) x 293.22 mm (V)
Synchronization	Horizontal Frequency	30 ~ 81 kHz	
	Vertical Frequency	56 ~ 75 kHz	
Display Color		16.7M	
Resolution	Optimum Resolution	1366x768@60Hz	1920x1080@60Hz
	Maximum Resolution	1366x768@60Hz	1920x1080@60Hz
Maximum Pixel Clock		95MHz (Analog,Digital)	164MHz (Analog,Digital)
Power Supply		This product uses 100 to 240V. Refer to the label at the back of the product as the standard voltage can vary in different countries.	
Signal connectors		15pin-to-15pin D-sub cable, Detachable DVI-D to DVI-D connector, Detachable	
Dimensions (W x H x D) / Weight	Without Stand	445 x 273 x 53 mm 17.5 x 10.7 x 2.1 Inches	569 x 342 x 53 mm 22.4 x 13.5 x 2.1 Inches
	With Stand	445 x 348 x 177 mm / 2.1 kg 17.5 x 13.7 x 7.0 Inches / 4.6 lbs	569 x 416 x 197 mm / 3.6 kg 22.4 x 16.4 x 7.8 Inches / 7.9 lbs
Environmental considerations	Operating	Temperature : 50°F – 104°F (10°C – 40°C) Humidity : 10 % – 80 %, non-condensing	
	Storage	Temperature : -4°F – 113°F (-20°C – 45°C) Humidity : 5 % – 95 %, non-condensing	
Plug-and-Play		This monitor can be installed and used with any Plug-and-Play compatible systems. Two-way data exchange between the monitor and PC system optimizes the monitor settings. Monitor installation takes place automatically. However, you can customize the installation settings if desired.	
Panel Dots (Pixels)		Due to the nature of the manufacturing of this product, approximately 1 pixel per million (1ppm) may be brighter or darker on the LCD panel. This does not affect product performance.	

### 3.6 Description of the EUT exercising method

The EUT exercise program used during EMI testing was CSQAL standardized test program for MS Windows. The program repetitively sends a screen of H – Character to the display. Connect video output of computer on EUT's PC IN (D-sub),DVI port and scrolled H – character continuously on EUT's screen.

The EUT system includes a monitor, the operational conditions shown as follows, within the selected area.



**Notes:**

1. Set the brightness control to maximum
2. Set the contrast control to maximum
3. Display a pattern of a full screen of scrolling letter-H characters with a font size to get as close as possible to three characters per linear cm and use single line spacing

### 3.7 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

Test type		Measurement uncertainty (C.L. 95 %, k = 2)	
Disturbance voltage at the mains terminals		2. 9 dB	
Radiated Disturbance	Horizontal	30 MHz - 1 GHz	3. 86 dB
	Vertical	30 MHz - 1 GHz	4. 90 dB
	Horizontal	1GHz - 6 GHz	3. 964 dB
	Vertical	1GHz - 6 GHz	3. 964 dB

## 4. Results of individual test

### 4.1 Conducted disturbance

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.

The EUT measured in accordance with the methods described in standards.

#### Limits for conducted disturbance at the mains ports of class B ITE

Frequency range Limits MHz	Limits dB(µV)	
	Quasi-peak	Average
<b>0,15 to 0,50</b>	<b>66 to 56</b>	<b>56 to 46</b>
<b>0,50 to 5</b>	<b>56</b>	<b>46</b>
<b>5 to 30</b>	<b>60</b>	<b>50</b>

Note 1: 1 µV is regarded as 0 dB.  
 Note 2: The limits shall decreases linearly with the logarithm of the frequency in the range 150 – 500 kHz.  
 Note 3: If the average limit is met in the measurement with quasi-peak detector, the measurement with average detector is unnecessary.  
 Note 4: The lower limit shall apply at the transition frequency.

If the reading on the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 seconds at each measurement frequency, the highest reading shall be recorded, with the exception of any brief isolated high reading (which shall be ignored).


#### 4.1.1 Test instrumentation

Test instrumentation used in the Conducted disturbance test was as follows:


Test instrumentation	Model name	Manufacturer	Serial or Firmware (No./Ver.)	Calibration	
				Date	Interval (Month)
Test Software	EP5CE	TOYO	V 4.7.10	N/A	N/A
Measuring receiver	ESCI	R&S	101027	2012.03.02	12
Artificial mains network	ENV216	R&S	101122	2011.08.23	12
Artificial mains network	ENV216	R&S	101059	2011.08.23	12
ISN	ISN T800	TESEQ	28602	2011.09.05	12
ISN	ISN T8-CAT6	TESEQ	27286	2012.03.02	12

#### **4.1.2 Photograph of the test Configuration**

**(Front)**



**(Rear)**



### 4.1.3 Test results

Test date	2012.04.16		Test engineer		Xinxing Fu	
Climate condition	Ambient temperature	21°C	Relative humidity	27%	Atmospheric pressure	101.5 kPa
Test place	Shielded Room #2					


### 4.1.4 Test data

#### ■ Operating Mode: VGA IN

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result

--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f. [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]	Remark
1	0.19533	41.8	34.2	9.6	51.4	43.8	63.8	53.8	12.4	10.0	
2	0.25397	35.3	23.4	9.6	44.9	33.0	61.6	51.6	16.7	18.6	
3	0.47452	34.5	23.2	9.6	44.1	32.8	56.4	46.4	12.3	13.6	
4	0.54008	31.0	19.1	9.6	40.6	28.7	56.0	46.0	15.4	17.3	
5	0.57181	34.1	20.6	9.6	43.7	30.2	56.0	46.0	12.3	15.8	
6	2.74035	30.9	18.4	9.7	40.6	28.1	56.0	46.0	15.4	17.9	
7	2.77849	29.1	18.6	9.7	38.8	28.3	56.0	46.0	17.2	17.7	

--- L1 Phase ---


No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f. [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]	Remark
1	0.1907	41.0	29.4	9.6	50.6	39.0	64.0	54.0	13.4	15.0	
2	0.47561	33.4	21.0	9.6	43.0	30.6	56.4	46.4	13.4	15.8	
3	0.57259	32.6	19.8	9.6	42.2	29.4	56.0	46.0	13.8	16.6	

## ■ Operating Mode: DVI IN

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



### Final Result

--- N Phase ---												
No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f	Result QP [dB]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]	Remark	
1	0.19206	42.6	31.5	9.6	52.2	41.1	63.9	53.9	11.7	12.8		
2	0.25668	36.4	25.6	9.6	46.0	35.2	61.5	51.5	15.5	16.3		
3	0.47227	34.6	24.5	9.6	44.2	34.1	56.5	46.5	12.3	12.4		
4	0.5716	34.0	20.0	9.6	43.6	29.6	56.0	46.0	12.4	16.4		

--- L1 Phase ---												
No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f	Result QP [dB]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]	Remark	
1	0.19107	41.9	29.4	9.6	51.5	39.0	64.0	54.0	12.5	15.0		
2	0.25741	35.7	24.7	9.6	45.3	34.3	61.5	51.5	16.2	17.2		
3	0.47301	33.2	22.9	9.6	42.8	32.5	56.5	46.5	13.7	14.0		
4	0.51368	28.9	16.9	9.6	38.5	26.5	56.0	46.0	17.5	19.5		
5	0.57211	33.0	19.2	9.6	42.6	28.8	56.0	46.0	13.4	17.2		
6	5.18028	30.2	17.2	9.7	39.9	26.9	60.0	50.0	20.1	23.1		

Note) Level (Quasi-Peak and/or Average) = Meter Reading (Quasi-Peak and/or Average) + Factor (LISN Insertion Loss + Cable Loss)

Margin = Limit – Level (Quasi-Peak and/or Average)



## 4.2 Radiated disturbance

Of those disturbances above ( $L - 20\text{dB}$ ), where  $L$  is the limit level in logarithmic units, record at least the disturbance levels and the frequencies of the six highest disturbances.

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin. All measurements were taken utilizing quasi-peak detection unless stated otherwise.

Measurements were performed at an antenna to EUT distance of 3 meters and elevated between 1 and 4 meters. Both vertical and horizontal antenna polarizations were measured.

Above 1GHz, peak detector function mode was used with resolution bandwidth of 1 MHz and a video bandwidth of 1 MHz. If the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range Limits MHz	Quasi-peak Limits (microvolts/meter)
	Class B
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

Note 1: The lower limit shall apply at the transition frequency.  
 Note 2: Additional provisions may be required for cases where interference occurs.  
 Note 3: 1  $\mu\text{V}/\text{m}$  is regarded as 0 dB.

Measurements above 1GHz were performed at an antenna to EUT distance of 3 meters and elevated 1 to 4 meters in FAC. Both vertical and horizontal antenna polarizations were measured.

### Limits for radiated disturbance of ITE at a measuring distance of 3 m

Frequency range Limits MHz	Class A		Class B	
	Peak dB( $\mu\text{V}/\text{m}$ )	Average dB( $\mu\text{V}/\text{m}$ )	Peak dB( $\mu\text{V}/\text{m}$ )	Average dB( $\mu\text{V}/\text{m}$ )
1000 to 3000	76	56	70	50
3000 to 6000	80	60	74	54

Note 1: The lower limit shall apply at the transition frequency.

#### 4.2.1 Test instrumentation

Test instrumentation used in the Radiated disturbance was as follows:

**30MHz~1GHz**

<b>Test instrumentation</b>	<b>Model name</b>	<b>Manufacturer</b>	<b>Serial or Firmware (No./Ver.)</b>	<b>Calibration</b>	
				<b>Date</b>	<b>Interval (Month)</b>
Test Software	EP5/RE	TOYO	V 4.7.10	N/A	N/A
Bi-con Antenna	CBL6112D	SCHAFFNER	29069	2011.04.04	24
EMI Receiver	ESCI	R&S	101026	2012.03.02	12
AMPLIFIER	310N	SONOMA	300911	2011.08.23	12
Ant Mast	MA4000	INN CO	-	N/A	N/A
Mast Controller	CO2000	INN CO	-	N/A	N/A
RF Selector	NS4900N	TOYO	-	N/A	N/A


**1GHz-2GHz**

<b>Test instrumentation</b>	<b>Model name</b>	<b>Manufacturer</b>	<b>Serial or Firmware (No./Ver.)</b>	<b>Calibration</b>	
				<b>Date</b>	<b>Interval (Month)</b>
Test Software	e3	AUDIX	6.110709d	N/A	N/A
Broad-Band Horn Antenna	BBHA9120B	Schwarzbeck	519	2011.04.05	24
EMI Receiver	ESU26	R&S	100243	2012.03.02	12
AMPLIFIER	AMF-4D-00500800-18-13P	TOYO	0934	2011.08.23	12
Ant Mast	AUDIX	AUDIX	-	N/A	N/A

#### 4.2.2 Photograph of the test Configuration

30MHz~1GHz

**(Front)**




**(Rear)**




**1GHz-2GHz**

**(Front)**



**(Rear)**



### 4.2.3 Test results

#### 30MHz~1GHz


Test date	2012.04.16		Test engineer	Xinxing Fu	
Climate condition	Ambient temperature	24 °C	Relative humidity	20 %	Atmospheric pressure
Test place	3m Semi-Anechoic Chamber				

#### ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1600\*900@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result


No.	Frequency	(P)	Reading	c.f.	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		[dB(µV)]	[dB(1/m)]	[dB(µV/m)]	QP	QP	[dB]	[cm]	[°]
1	655.165	V	36.1	-1.2	34.9	46.0	11.1	100.0	338.8	
2	234.064	H	44.3	-11.6	32.7	46.0	13.3	100.0	194.8	
3	197.931	H	42.4	-13.3	29.1	43.5	14.4	100.0	280.0	
4	240.975	H	42.7	-10.8	31.9	46.0	14.1	100.0	200.7	
5	655.408	H	32.9	-1.2	31.7	46.0	14.3	201.0	343.0	
6	103.720	V	41.4	-12.2	29.2	43.5	14.3	100.0	250.6	
7	103.720	H	40.9	-12.2	28.7	43.5	14.8	301.0	151.4	
8	234.185	V	38.5	-11.6	26.9	46.0	19.1	100.0	159.0	

## ■ Operating Mode: DVI IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1600\*900@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



### Final Result

No.	Frequency [MHz]	(P) QP [dB (µV)]	Reading QP [dB (µV)]	c.f. [dB (1/m)]	Result QP [dB (µV/m)]	Limit QP [dB (µV/m)]	Margin QP [dB]	Height [cm]	Angle [°]	Remark
1	890.511	H 28.5	28.5	2.0	30.5	46.0	15.5	200.0	228.6	
2	445.524	H 42.4	42.4	-4.4	38.0	46.0	8.0	100.0	223.0	
3	66.011	V 49.2	49.2	-17.9	31.3	40.0	8.7	100.0	52.7	
4	445.524	V 41.2	41.2	-4.4	36.8	46.0	9.2	100.0	45.6	
5	296.993	H 43.9	43.9	-8.7	35.2	46.0	10.8	100.0	188.1	
6	214.300	H 42.1	42.1	-13.1	29.0	43.5	14.5	100.0	195.7	
7	890.511	V 25.2	25.2	2.0	27.2	46.0	18.8	100.0	151.6	
8	148.461	V 42.7	42.7	-12.1	30.6	43.5	12.9	100.0	200.5	

Note) Receiving antenna polarization : Horizontal and/or Vertical

Test Distance : 3m, Antenna Height : 1 to 4 meters

Result (Quasi-Peak) = Reading QP + C.F (Antenna Factor + Cable Loss - Amp. Gain)

Margin QP (Quasi-Peak) = Limit – Level QP

## 1GHz-2GHz


Test date	2012.04.17		Test engineer	Xinxing Fu	
Climate condition	Ambient temperature	26 °C	Relative humidity	25 %	Atmospheric pressure
Test place	3m Semi-Anechoic Chamber				

### ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1600\*900@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.




No.	Frequency [MHz]	(P)		Reading		Reading		c.f.		Result		Result		Limit		Limit		Margin		Margin		Height		Angle		Remark	
		AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	PK	cm	°	AV	PK	cm	°				
1	1485.079	V	61.9	H	75.7	V	61.9	H	75.7	V	61.9	H	75.7	V	60.6	H	60.6	50.0	70.0	3.2	9.4	109.0	160.7				
2	1484.408	H	59.6	V	71.7	H	59.6	V	71.7	H	59.6	V	71.7	H	44.5	V	56.6	50.0	70.0	5.5	13.4	186.0	119.8				
3	1929.952	V	58.6	H	71.3	V	58.6	H	71.3	V	58.6	H	71.3	V	-13.1	H	45.5	58.2	50.0	70.0	4.5	11.8	100.0	150.8			
4	1929.875	H	49.3	V	64.2	H	49.3	V	64.2	H	49.3	V	64.2	H	-13.1	V	36.2	51.1	50.0	70.0	13.8	18.9	100.0	243.8			
5	1482.750	H	43.3	V	69.1	H	43.3	V	69.1	H	43.3	V	69.1	H	-15.1	V	28.2	54.0	50.0	70.0	21.8	16.0	200.0	114.6			
6	1391.250	V	36.9	H	64.1	V	36.9	H	64.1	V	36.9	H	64.1	V	-15.6	H	21.3	48.5	50.0	70.0	28.7	21.5	301.0	180.8			
7	1781.000	V	51.9	H	64.8	V	51.9	H	64.8	V	51.9	H	64.8	V	-13.7	H	38.2	51.1	50.0	70.0	11.8	18.9	100.0	199.5			
8	1392.000	V	37.1	H	62.6	V	37.1	H	62.6	V	37.1	H	62.6	V	-15.6	H	21.5	47.0	50.0	70.0	28.5	23.0	301.0	179.7			
9	1500.000	V	58.2	H	63.1	V	58.2	H	63.1	V	58.2	H	63.1	V	-15.0	H	43.2	48.1	50.0	70.0	6.8	21.9	100.0	339.8			
10	1393.125	V	42.1	H	72.2	V	42.1	H	72.2	V	42.1	H	72.2	V	-15.6	H	26.5	56.6	50.0	70.0	23.5	13.4	100.0	310.1			

## ■ Operating Mode: DVI IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1600\*900@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



No.	Frequency [MHz]	(P)		Reading AV		Reading PK		c.f.		Result AV		Result PK		Limit AV		Limit PK		Margin AV		Margin PK		Height		Angle		Remark	
		Frequency	(P)	Reading	Reading	c.f.	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Remark												
1	1113.461	V	43.7	75.2	-16.1	27.6	59.1	50.0	70.0	22.4	10.9	102.0	256.5														
2	1113.465	V	43.6	78.0	-16.1	27.5	61.9	50.0	70.0	22.5	8.1	102.0	267.7														
3	1112.125	V	42.4	73.4	-16.2	26.2	57.2	50.0	70.0	23.8	12.8	201.0	281.7														
4	1214.125	V	38.8	69.8	-15.6	23.2	54.2	50.0	70.0	26.8	15.8	100.0	290.0														
5	1115.400	V	37.0	62.0	-16.1	20.9	45.9	50.0	70.0	29.1	24.1	201.0	34.1														
6	1113.625	H	36.8	55.9	-16.1	20.7	39.8	50.0	70.0	29.3	30.2	200.0	139.8														
7	1400.250	V	56.0	61.7	-19.0	41.0	46.7	50.0	70.0	9.0	23.3	100.0	343.8														
8	1418.825	V	40.0	67.4	-18.5	24.5	51.9	50.0	70.0	25.5	18.1	302.0	348.3														
9	1342.750	V	40.6	64.0	-15.8	24.8	48.2	50.0	70.0	25.2	21.8	199.0	343.6														
10	1500.250	H	43.0	52.9	-15.0	28.0	37.9	50.0	70.0	22.0	32.1	199.0	256.7														

Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3m, Antenna Height : 1 to 4 meters

Result (Average) = Reading AV + C.F (Antenna Factor + Cable Loss - Amp. Gain)

Margin AV (Average) = Limit – Result AV

## Appendix A – EUT photography

**(Front)**



**(Rear)**



---

(Power Adapter)






(Panel )



**(Board 1)**



**(Board 2)**



(Crystal)

