

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification and Description
Processor	TEMUJIN(300 MHz)
Standard System memory	Embedded SDRAM core of ESMTwith 32 MB size
Resolution	True 1 200 x 1 200 dpi
Paper Handling	150-sheet Cassette @ 80 g/m ² , 10-sheet @ Special Paper
Power Rating	110 VAC~127 VAC, 5A, 50 Hz / 60 Hz
Power Consumption	Power save mode : 1.2 Watts Printing mode: MAX 310 Watts
Printer Language	SPL
PC Interfaces	USB 2.0, 802.11 b/g/n
OS compatibility	Windows 7/2000/XP(32/64bit)/2003(32/64bit)/Vista(32/64bit)/2008 Server(32/64bit) Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13 (32/64 bit), SuSE Linux 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04 (32/64 bit) SuSE Linux Enterprise Desktop 10, 11 (32/64 bit), Debian 4.0, 5.0 (32/64 bit) Mac OS 10.4~10.6, Sun Solaris 9,10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium), IBM AIX 5.1, 5.2, 5.3, 5.4
Modes of Operation	USB Printing, Wireless LAN Printing
Intended Class for Emissions	Class B