



3.5 EUT Description

Item	Specification	Remarks
Printing speed	Up to 28 ppm in A4 (30 ppm in Letter) Duplex: 14 ipm in A4 (14 ipm in Letter)	-
Resolution	Up to 1200 x 1200 dpi effective output	-
Warm-up time	20 seconds (Power ON)	-
First Print Out Time	8.5 seconds (From Ready)	-
Power rating	AC 110-127V, 6.4A, 50/60 Hz	-
Power consumption	Average Operating mode : less than 400 W Ready mode: less than 60 W Power Save mode: less than 8 W Power Off mode: less than 0.4 W	-
Noise Level	Standby mode: Less than 26 dB(A) Printing mode: Less than 50 dB(A)	-
Toner cartridge life	Standard Yield: Average cartridge yield 2,000 standard pages High Yield: Average cartridge yield 5,000 standard pages. Declared cartridge yield in accordance with ISO/IEC 19752.	-
Duty cycle	Max. Monthly Duty: 50,000 sheets	-
Weight	9.7 kg (including consumables)	-
External dimensions	W x D x H: 391 x 370 x 235 mm (15.4 x 14.6 x 9.3 inches)	-
Operating environment	Temperature : 10 to 32°C (50 to 90°F) Humidity : 20% to 80% RH	-
Printer Language	PCL6, IBM ProPrinter, EPSON, PostScript3, SPL	
Memory	Std. 64MB (Max. 192MB)	
LCD Display	16 characters x 2 lines	
Interface	USB: Hi-Speed USB 2.0 Wired Network: Ethernet 10/100 Base TX	
OS compatibility	Windows 2000/ 2003 Server/ XP/ Vista Various Linux OS Mac OS 8.6 ~ 9.2, 10.1 ~ 10.5	
Options	250-sheet cassette tray, 128MB DIMM(SAMSUNG approved only)	