

### 3.5 EUT Description

1. The following features describe EUT represented by this report:

Item	Specification and Description
<b>Processor</b>	CHOURS3N(533 Mhz)
<b>Standard System memory</b>	DDR2 64 MB
<b>Resolution</b>	True 600 x 600 dpi, addressable 1 200 x 1 200
<b>Copy Quality mode</b>	N.A
<b>Paper Handling</b>	250-sheet Cassette @ 80 g/m <sup>2</sup> , 1-sheet Multi Purpose Tray
<b>Power Rating</b>	[90 ~ 135 ] VAC, 2.8 A, 50 Hz /60 Hz
<b>Power Consumption</b>	Power save mode : 1.4 Wh Ready mode : 37 Wh Printing mode : 400 Wh(Max)
<b>Printer Language</b>	PCL6, SPL
<b>PC Interfaces</b>	High Speed USB 2.0 Ethernet 10/100 802.11 b/g/n
<b>OS compatibility</b>	Windows 2000/XP(32 bits /64 bits)/Vista(32 bits /64 bits)/2003 Server(32 bits /64 bits)/2008 Server(32 bits /64 bits)/7(32 bits /64 bits)/2008 Server R2(64 bits) Mac OS X 10.4 ~ 10.6 RedHat Enterprise Linux WS 4, 5 (32 bits /64 bit) Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13 (32 bits /64 bit) SuSE Linux 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32 bits /64 bit) Mandriva 2007, 2008, 2009, 2009.1, 2010 (32 bits /64 bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04 (32 bits /64 bit) SuSE Linux Enterprise Desktop 10, 11 (32 bits /64 bit) Debian 4.0, 5.0 (32 bits /64 bit) Sun Solaris 9,10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) IBM AIX 5.1, 5.2, 5.3, 5.4
<b>Modes of Operation</b>	USB Printing, Network Printing, Wireless
<b>Intended Class for Emissions</b>	Class B

2. The variant models

: ML-2950DW, ML-2955ND, ML-2950ND