

## TEST REPORT

### Maximal Permissible Exposure [MPE] REPORT

**Applicant Name:**  
 Samsung Electronics Co., Ltd.  
 129, Samsung-ro,  
 Yeongtong-gu, Suwon-si  
 Gyeonggi-do, 16677, Korea

**Date of Testing:**  
 04/21/2023 - 05/24/2023  
**Test Site/Location:**  
 Element Lab., Suwon,  
 Yongin-si, Gyeonggi-do, Korea  
**Test Report Serial No.:**  
 8K23041001-01.A3L

<b>FCC ID:</b>	<b>A3LMT1602D-48A</b>
<b>APPLICANT:</b>	<b>Samsung Electronics Co., Ltd.</b>

**Application Type:** Certification  
**Model:** MT1602d-48A  
**EUT Type:** MMU(MT1602d)  
**FCC Classification:** Licensed Non-Broadcast Station Transmitter  
**FCC Rule Part(s):** FCC Part 1 (§1.1310) and Part 2 (§2.1091)  
**Test Procedure(s):** KDB 447498 D01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.




Prepared by Jonathan Jang  
 Test Engineer



Reviewed by Charles Shin  
 Technical Manager

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 1 of 10	

## TABLE OF CONTENTS



---

1.0	REVISION RECORD .....	3
2.0	INTRODUCTION .....	4
	2.1 Scope .....	4
	2.2 Element Test Location.....	4
	2.3 Test Facility / Accreditation .....	4
3.0	PRODUCT INFORMATION.....	5
	3.1 Equipment Description .....	5
	3.2 Device Capabilities.....	5
4.0	RF EXPOSURE EVALUATION - MPE .....	6
	4.1 Introduction .....	6
	4.2 MPE Requirements Overview .....	7
	4.3 Procedure.....	8
	4.4 Results of Maximum Permissible Exposure .....	9
5.0	CONCLUSION.....	10

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 2 of 10	

## 1.0 REVISION RECORD

Issue Number	Issued Date	Revision History
8K23041001-01.A3L	05/25/2023	Initial Issue

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)		Page 3 of 10

## 2.0 INTRODUCTION

### 2.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 2.2 Element Test Location

These measurement tests were conducted at the Element Materials Technology Suwon. Ltd. facility located at (#1407) 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do 16954, Korea.

### 2.3 Test Facility / Accreditation

Measurements were performed at Element Materials Technology Suwon Lab located in Yongin-si, Gyeonggi, Korea.

- Element Materials Technology Suwon is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation(A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Materials Technology Suwon facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.
  - Designation Number / CABID: KR0169
  - Test Firm Registration Number of FCC: 417945
  - Test Firm Registration Number of IC: 26168

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 4 of 10	

## 3.0 PRODUCT INFORMATION


### 3.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung MMU(MT1602d) FCC ID: A3LMT1602D-48A**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 27.

### 3.2 Device Capabilities

This device supports the following conditional features and filter information declared by the manufacturer.

EUT Type	MMU(MT1602d)		
Model Name	MT1602d-48A		
Test Device Serial No	S619345961		
Device Capabilities:	5G NR		
Operating Band/Frequency Range:	Band	Tx	Rx
	n77:	3700 MHz to 3980 MHz	3700 MHz to 3980 MHz
Supported Modulation	QPSK, 16QAM, 64QAM, 256QAM		
Numerology	SCS 30 kHz		
Supported Number of Carriers and Channel Bandwidth	NR: 40, 60, 80 and 100MHz bandwidth 1C modes for 5G NR n77 with up to 2CC aggregated of Max. Bandwidth 200 MHz		
Maximum Output Power	1CC: 40 MHz: 3.75W/path, 60W/unit 1CC: 60, 80, 100 MHz: 5.625W/path, 90W/unit 2CC: 100 MHz + 40 MHz, 100 MHz + 60 MHz, 100 MHz + 80 MHz, 100 MHz + 100 MHz: 5.625W/path, 90W/unit		
IBW/OBW	200 MHz / 200 MHz		
Number of Antenna ports	16T16R		
Supported Configurations	Single carrier, Multi-carrier		
Input Voltage:	-48 VDC		
Maximum antenna gain	Max 20.7 dBi (20.2 dBi ± 0.5 dB tolerance) Antenna gain declared by the manufacturer.		

FCC ID: A3LMT1602D-48A		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 8K23041001-01.A3L	Test Dates: 04/21/2023 - 05/24/2023	EUT Type: MMU(MT1602d)	Page 5 of 10	

## 4.0 RF EXPOSURE EVALUATION - MPE

### 4.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
<u>1500-100,000</u>	...	...	<u>1.0</u>	30

**Table 4-1. Limits for Maximum Permissible Exposure (MPE)**

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 6 of 10	

## 4.2 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC KDB 447498 D01. These categories are fixed installation, mobile and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 46 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR §2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The **Samsung MMU(MT1602d) FCC ID: A3LMT1602D-48A** is professionally installed on poles or walls in fixed locations. The device is a fixed mounted base station and MPE is evaluated to the General Population/Uncontrolled Exposure limits per 1.1310.

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 7 of 10	

### 4.3 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each operating mode used in this product was initially measured with a spectrum analyzer and powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated for the safe distance which must be maintained during installation based on maximum power and antenna gain.

#### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,


$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi$  = 3.1416

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 8 of 10	



#### 4.4 Results of Maximum Permissible Exposure

Maximum Permissible Exposure			Result
Frequency (MHz)	3700 – 3980	MHz	Pass
Distance (R)	11	m	
Total MIMO Max measured Output power	50.24	dBm	
Total MIMO Rated conducted power	49.54	dBm	
Tune-up tolerance	± 1	dBm	
Total MIMO Max Output Power (P) (The Output Power scaled to maximum tune-up tolerance)	50.54	dBm	
Antenna Gain (G) Typical	20.70	dBi	
Power density (S)	0.87	mW/m <sup>2</sup>	
MPE Limit (W/m <sup>2</sup> )	1.00	mW/m <sup>2</sup>	

**Table 4-2. Calculated Max MPE Data for n77**

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 9 of 10	

## 5.0 CONCLUSION

**Samsung Electronics Co., Ltd. FCC ID: A3LMT1602D-48A** meets the MPE Compliance requirements as specified in §2.1091 of the FCC Rules and Regulations with minimum safe distance of 11 m for operation. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: A3LMT1602D-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 8K23041001-01.A3L	<b>Test Dates:</b> 04/21/2023 - 05/24/2023	<b>EUT Type:</b> MMU(MT1602d)	Page 10 of 10	