



# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
http://www.pctest.com

## TEST REPORT DP/CBSD-SAS Interoperability

**Applicant Name:**  
Samsung Electronics Co. Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea


**Date of Testing:**  
7/5/2019 – 7/30/2019  
**Test Site/Location:**  
PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
1M1907220128-04.A3L

<b>FCC ID:</b>	<b>A3LMT6402-48A</b>
<b>APPLICANT:</b>	<b>Samsung Electronics Co. Ltd.</b>

**Application Type:** Certification  
**Model:** MT6402-48A  
**EUT Type:** LTE Base Station  
**Frequency Range:** 3550 – 3700 MHz  
**FCC Classification:** Citizens Band Category A and B Devices (CBD)  
**FCC Rule Part(s):** Part 96  
**Test Procedure(s):** KDB 940660 D01 v02, WINNF-TS-0122-V1.0.0, CBRSA-TS-9001 V.1.0.0

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in the test procedures listed above. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortanez  
President



<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 1 of 12

# TABLE OF CONTENTS

1.0	INTRODUCTION.....	3
1.1	Scope.....	3
1.2	PCTEST Test Location .....	3
1.3	Test Facility / Accreditations .....	3
2.0	PRODUCT INFORMATION .....	4
2.1	Equipment Description.....	4
2.2	Device Capabilities .....	4
2.3	Test Configuration .....	4
2.4	Modifications.....	4
3.0	TEST EQUIPMENT CALIBRATION DATA.....	5
4.0	ENVIRONMENTAL CONDITIONS .....	6
5.0	EVALUATION PROCEDURE .....	7
6.0	TEST Summary.....	8
6.1	Summary .....	8
7.0	RF Power Measurements .....	10
8.0	CONCLUSION .....	11
	APPENDIX A – TEST LOGS.....	12

<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station	Page 2 of 12	

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of compliance with the technical rules and regulations of the Federal Communications Commission.

## 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046.

## 1.3 Test Facility / Accreditations

**Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.**

- PCTEST is a CBRS Alliance (OnGo) Approved Test Lab
- PCTEST is a WinnForum Approved Test Lab
- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for CBRS Alliance Certification Test Plan and WinnForum Conformance and Performance Test Technical Standard.
- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 3 of 12

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung LTE Base Station FCC ID: A3LMT6402-48A**. The test data contained in this report pertains only to DP/CBSD-SAS interoperability. The EUT is a Domain Proxy.

**Test Device Serial Number(s):** SN-SRCS0982, SN-SRCS0985

### 2.2 Device Capabilities

This device contains the following capabilities:

LTE Band 48

This device supports the following conditional features:

	Conditional Test Case Definitions	Supported
C1	Mandatory for UUT which supports multi-step registration message	<input checked="" type="checkbox"/>
C2	Mandatory for UUT which supports single-step registration with no CPI-signed data in the registration message. By definition, this is a subset of Category A devices which determine all registration information, including location, without CPI intervention.	<input type="checkbox"/>
C3	Mandatory for UUT which supports single-step registration containing CPI-signed data in the registration message.	<input type="checkbox"/>
C4	Mandatory for UUT which supports RECEIVED_POWER_WITHOUT_GRANT measurement report type.	<input checked="" type="checkbox"/>
C5	Mandatory for UUT which supports RECEIVED_POWER_WITH_GRANT measurement report type.	<input type="checkbox"/>
C6	Mandatory for UUT which supports parameter change being made at the UUT and prior to sending a deregistration	<input type="checkbox"/>

**Table 2-1. Conditional Features**

### 2.3 Test Configuration

The EUT was connected to the SAS Test Harness developed by WINNF WG4-CBSD. The latest version of the SAS Test Harness (V1.0.0.2) provided by CBRS Alliance was used. The SAS Test Harness is synchronized to UTC time.

### 2.4 Modifications

No modifications were made to EUT during testing.

<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station	Page 4 of 12	

### 3.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9030A	PXA Signal Analyzer	6/12/2019	Annual	6/12/2020	MY52350166
Dell	Latitude 5580	Test Harness Laptop	N/A	N/A	N/A	N/A
AA-MCS	PWD-2W-0.5-6G-10W-SF	2-Way Power Divider/Combiner	2/20/2019	Annual	2/20/2020	1020 - 004
Weinschel	4T-20	20dB Attenuator	2/20/2019	Annual	2/20/2020	N/A
Seekonk	NC-100	Torque Wrench	5/4/2018	2 year	5/4/2020	N/A
Agilent HP	6032A	AutoRanging System Power Supply	N/A	N/A	N/A	N/A
Tektronix	RSA306B	Real-Time Spectrum Analyzer	N/A	N/A	N/A	B034467

**Table 3-1 Annual Test Equipment Calibration Schedule**

<b>FCC ID:</b> A3LMT6402-48A	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 5 of 12

## 4.0 ENVIRONMENTAL CONDITIONS

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 6 of 12

## 5.0 EVALUATION PROCEDURE

The measurement procedure described in KDB 940660 D01 v02 and WINNF-TS-0122-V1.0.0 was used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

<b>FCC ID:</b> A3LMT6402-48A	 <small>ENGINEERING LABORATORY, INC.</small>	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station	Page 7 of 12	

## 6.0 TEST SUMMARY

### 6.1 Summary

Company Name: Samsung Electronics Co. Ltd.

FCC ID: A3LMT6402-48A

**Table 6-1. Summary of Test Results**

FCC Part Section(s)	KDB940660 D01 Section 3.3 a)	Test Case Description	WInnForum Test Case	Test Result
96.39 (c)	1	Confirm that the device will only transmit after it receives authorization from a SAS	WINNF.FT.D.REG.2 WINNF.FT.D.REG.9 WINNF.FT.D.REG.11 WINNF.FT.D.REG.13 WINNF.FT.D.REG.15 WINNF.FT.D.REG.17 WINNF.FT.D.REG.19 WINNF.FT.D.GRA.1 WINNF.FT.C.GRA.2 WINNF.FT.C.HBT.11	Pass
96.39 (c)	2	Check the device registration and authorization with the SAS – determine if the device behaves appropriately for successful and unsuccessful registrations. The device should not be transmitting without authorization from the SAS.	WINNF.FT.D.REG.2 WINNF.FT.D.REG.9 WINNF.FT.D.REG.11 WINNF.FT.D.REG.13 WINNF.FT.D.REG.15 WINNF.FT.D.REG.17 WINNF.FT.D.REG.19	Pass
96.39(c)(1)	3	Confirm that the device changes its operating power and/or channel in response to a command from the SAS.	WINNF.FT.D.HBT.2	Pass
96.39	4	Confirm that the device correctly configures based on the different license classes	N/A	Pass
96.39(c)(1)	5	Confirm that the device transmits at a power level less than or equal to the maximum power level approved by the SAS.	WINNF.PT.C.HBT	Pass
96.39(b)(c)	6	Confirm that the device transmits with a bandwidth less than or equal to the SAS specified bandwidth.	WINNF.FT.D.HBT.2	Pass
96.39(c)(2)	7	Confirm that the device transmits on the SAS specified frequency.	WINNF.FT.D.HBT.2	Pass
96.39(c)(2)	8	Confirm that the device stops transmission in response to a command from the SAS, within a period as required by Part 96.	WINNF.FT.C.HBT.3 WINNF.FT.C.HBT.5 WINNF.FT.C.HBT.6 WINNF.FT.C.HBT.7 WINNF.FT.D.HBT.8 WINNF.FT.C.HBT.10 WINNF.FT.D.RLQ.2 WINNF.FT.D.RLQ.4 WINNF.FT.D.RLQ.6 WINNF.FT.D.DRG.2 WINNF.FT.D.DRG.4 WINNF.FT.C.DRG.5	Pass

FCC ID: A3LMT6402-48A		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1907220128-04.A3L	Test Dates: 7/5/2019 – 7/30/2019	EUT Type: LTE Base Station		Page 8 of 12



**Table 6-2. Summary of Test Results (continued)**

96.39 (c)	9	Confirm that the device sends measurements data in response to the command from the SAS.	WINNF.FT.D.MES.2	Pass
96.39(a)	10	For devices with geo-location, confirm that it notifies the SAS of a new location when it is beyond the required distance parameter ( $\pm 50$ m) within the required time frame.	N/A	N/A
96.39 (c)	11	Confirm that the device is capable of reporting the signal level (measurement data) and frequency to SAS.	WINNF.FT.D.MES.2	Pass
	12	For a device that operates as a Category A CBSD and then desires to operate as a Category B CBSD (or vice versa), confirm that it re-registers with the SAS for the updated authorization status.	N/A	Pass
96 E	13	When CBSDs communicate through a management system, confirm compliance with all requirements.	N/A	Pass
96.39	14	When communication between the CBSD and SAS is lost: i) Describe how the CBSD would react if the communications between the device and the SAS is lost. Confirm that the CBSD stops transmission once it loses the link to the SAS. ii) Describe the process for re-establishment of the communications and confirm that the CBSD acts accordingly. iii) Confirm power-on restart process for registration (re-registration) occurs as expected. iv) Confirm the process for de-registration occurs as expected.	WINNF.FT.C.HBT.9 WINNF.FT.C.HBT.10	Pass
96.39(f)	KDB940660 D01 Section 4	SAS and Device Security Requirements	WINNF.FT.C.SCS.1 WINNF.FT.C.SCS.2 WINNF.FT.C.SCS.3 WINNF.FT.C.SCS.4 WINNF.FT.C.SCS.5	Pass

**Notes:**

- Test cases denoted as “N/A” in the table above are not applicable to the EUT and are either Optional or Conditional per Section 6 of WINNF-TS-0122.
- TX monitor port was utilized to simultaneously monitor all 64 ports.
- Please see Appendix for test data.

FCC ID: A3LMT6402-48A		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1907220128-04.A3L	Test Dates: 7/5/2019 – 7/30/2019	EUT Type: LTE Base Station		Page 9 of 12

## 7.0 RF POWER MEASUREMENTS

### RF Power Measurements:

Testing is performed per KDB 971168 D01 and across the transmit dynamic range of 37dBm/MHz to 27dBm/MHz for 20MHz Bandwidth.

The UUT was configured in the 16-User Beam Configuration (1CC) such that all ports were transmitting at the same output power level. The 64 ports of the UUT are the same design and pretesting showed that the power levels between sampling of various ports is the same. As all 64 ports are identical in design and equivalent power levels, the PSD was measured and the total MIMO Conducted Power was calculated for 64 ports. The MIMO EIRP was calculated with adding the antenna gain, 16 Beam reduction, and BF Gain to the conducted power level.

Frequency [MHz]	Bandwidth [MHz]	SAS Granted maxEIRP [dBm/MHz]	Sampled Conducted PSD [dBm/MHz]	Calculated Total MIMO Conducted Power (64ports) [dBm/MHz]	Ant Gain [dBi]	16 Beam Reduction [dB]	BF Gain [dB]	MIMO EIRP [dBm/MHz]
3620 (mid)	20	37	-1.01	17.05	23.5	12.04	3	31.51
3620 (mid)	20	32	-6.19	11.87	23.5	12.04	3	26.33
3620 (mid)	20	30	-7.85	10.21	23.5	12.04	3	24.67
3620 (mid)	20	27	-11.04	7.02	23.5	12.04	3	21.48
3560 (low)	20	37	-0.53	17.53	23.5	12.04	3	31.99
3690 (High)	20	37	-0.67	17.39	23.5	12.04	3	31.85

**Table 7-1 RF Output Power Measurements (WINNF.PT.C.HBT.1)**

FCC ID: A3LMT6402-48A	 <b>MEASUREMENT REPORT (CERTIFICATION)</b>			<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 10 of 12

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung LTE Base Station FCC ID: A3LMT6402-48A** has been tested to show compliance with Part 96 and KDB 940660 D01 v02.

<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 11 of 12

# APPENDIX A – TEST LOGS

Logs are available upon request

- |  |  |   |
|--|--|---|
| <ul style="list-style-type: none"> <li>📄 WINNF.FT.C.DRG.5_2019-05-02T04.37.42Z</li> <li>📄 WINNF.FT.C.HBT.3_2019-05-02T03.33.51Z</li> <li>📄 WINNF.FT.C.HBT.7_2019-05-02T03.41.44Z</li> <li>📄 WINNF.FT.C.HBT.11_2019-05-07T02.47.36Z</li> <li>📄 WINNF.FT.C.SCS.3_2019-05-06T23.57.48Z</li> <li>📄 WINNF.FT.D.DRG.2_2019-05-03T23.12.07Z</li> <li>📄 WINNF.FT.D.HBT.8_2019-05-07T00.54.55Z</li> <li>📄 WINNF.FT.D.REG.9_2019-05-03T18.44.41Z</li> <li>📄 WINNF.FT.D.REG.15_2019-05-03T19.43.36Z</li> <li>📄 WINNF.FT.D.RLQ.2_2019-05-03T23.46.26Z</li> </ul> | <ul style="list-style-type: none"> <li>📄 WINNF.FT.C.GRA.1_2019-05-02T01.31.12Z</li> <li>📄 WINNF.FT.C.HBT.5_2019-05-02T02.38.31Z</li> <li>📄 WINNF.FT.C.HBT.9_2019-05-02T03.50.07Z</li> <li>📄 WINNF.FT.C.SCS.1_2019-05-06T23.22.32Z</li> <li>📄 WINNF.FT.C.SCS.4_2019-05-07T00.10.31Z</li> <li>📄 WINNF.FT.D.DRG.4_2019-05-03T23.26.56Z</li> <li>📄 WINNF.FT.D.MES.2_2019-05-02T20.33.42Z</li> <li>📄 WINNF.FT.D.REG.11_2019-05-03T19.28.09Z</li> <li>📄 WINNF.FT.D.REG.17_2019-05-03T19.48.02Z</li> <li>📄 WINNF.FT.D.RLQ.4_2019-05-04T00.30.06Z</li> </ul> | <ul style="list-style-type: none"> <li>📄 WINNF.FT.C.GRA.2_2019-05-02T01.45.25Z</li> <li>📄 WINNF.FT.C.HBT.6_2019-05-02T03.25.35Z</li> <li>📄 WINNF.FT.C.HBT.10_2019-05-02T04.00.08Z</li> <li>📄 WINNF.FT.C.SCS.2_2019-05-09T19.18.19Z</li> <li>📄 WINNF.FT.C.SCS.5_2019-05-07T00.34.31Z</li> <li>📄 WINNF.FT.D.HBT.2_2019-05-08T00.22.40Z</li> <li>📄 WINNF.FT.D.REG.2_2019-05-03T18.34.14Z</li> <li>📄 WINNF.FT.D.REG.13_2019-05-03T19.38.45Z</li> <li>📄 WINNF.FT.D.REG.19_2019-05-03T19.51.18Z</li> <li>📄 WINNF.FT.D.RLQ.6_2019-05-04T00.17.28Z</li> </ul> |
|--|--|---|

<b>FCC ID:</b> A3LMT6402-48A		<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Quality Manager
<b>Test Report S/N:</b> 1M1907220128-04.A3L	<b>Test Dates:</b> 7/5/2019 – 7/30/2019	<b>EUT Type:</b> LTE Base Station		Page 12 of 12