

**MEASUREMENT REPORT**  
**FCC Part 15.407 802.11ax/be WiFi 6E/7 (OFDMA)****Applicant Name:**Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea**Date of Testing:**

7/30/2024 – 8/26/2024

**Test Report Issue Date:**

8/28/2024

**Test Site/Location:**

Element lab., Columbia, MD, USA

**Test Report Serial No.:**

1M2407080057-09-R1.A3L

**FCC ID:****A3LNP750XQA****APPLICANT:****Samsung Electronics Co., Ltd.****Application Type:**

Certification

**Model:**

NP750XQA

**Additional Model(s)**

NP754XQA

**EUT Type:**

Portable Computing Device

**Frequency Range:**

5935 – 7115MHz

**Modulation Type:**

OFDMA

**FCC Classification:**

15E 6GHz Low Power Dual Client (6CD)

**FCC Rule Part(s):**

Part 15 Subpart E (15.407)

**Test Procedure(s):**

ANSI C63.10-2013, KDB 987594 D02 v01r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2407080057-09-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2407080057-09.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez  
Executive Vice President

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 1 of 291

## T A B L E O F C O N T E N T S

1	INTRODUCTION.....	6
1.1	Scope.....	6
1.2	Element Test Location.....	6
1.3	Test Facility / Accreditations.....	6
2	PRODUCT INFORMATION.....	7
2.1	Equipment Description.....	7
2.2	Device Capabilities.....	7
2.3	Antenna Description.....	11
2.4	Test Configuration.....	11
2.5	Software and Firmware.....	11
2.6	EMI Suppression Device(s) / Modifications.....	11
3	DESCRIPTION OF TESTS.....	12
3.1	Evaluation Procedure.....	12
3.2	AC Line Conducted Emissions.....	12
3.3	Radiated Emissions.....	13
3.4	Environmental Conditions.....	13
4	ANTENNA REQUIREMENTS.....	14
5	MEASUREMENT UNCERTAINTY.....	15
6	TEST EQUIPMENT CALIBRATION DATA.....	16
7	TEST RESULTS.....	17
7.1	Summary.....	17
7.2	26dB Bandwidth Measurement.....	19
7.2.1	MIMO Antenna-1 Bandwidth Measurements - (Partial Tones).....	23
7.2.2	MIMO Antenna-1 Bandwidth Measurements - (Full Tones).....	35
7.2.3	MIMO Antenna-1 Bandwidth Measurements - (Partial Tones - MRU).....	47
7.2.4	MIMO Antenna-2 Bandwidth Measurements - (Partial Tones).....	55
7.2.5	MIMO Antenna-2 Bandwidth Measurements - (Full Tones).....	67
7.2.6	MIMO Antenna-2 Bandwidth Measurements - (Partial Tones - MRU).....	79
7.3	UNII Output Power Measurement.....	87
7.4	Maximum Power Spectral Density.....	99
7.4.1	MIMO Antenna-1 Power Spectral Density Measurements.....	105
7.4.2	MIMO Antenna-2 Power Spectral Density Measurements.....	140
7.5	In-Band Emissions.....	176
7.5.1	MIMO Antenna-1 In-Band Emission Measurements.....	181
7.5.2	MIMO Antenna-2 In-Band Emission Measurements.....	216
7.6	Contention Based Protocol.....	251
7.6.1	AWGN Plots.....	255
7.6.2	CBP Timing Plots.....	256
7.6.3	Channel Move Plots.....	264

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 2 of 291

7.8	Radiated Emission Measurements .....	266
7.8.1	MIMO Radiated Spurious Emission Measurements (26 Tones) .....	270
7.8.2	MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII Band 5 .....	272
7.8.3	MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII Band 6 .....	273
7.8.4	MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII Band 7 .....	274
7.8.5	MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII Band 8 .....	275
7.8.6	MIMO Radiated Spurious Emission Measurements (242 Tones) .....	276
7.8.7	MIMO Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T).....	282
7.8.8	MIMO Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T) .....	283
7.8.9	MIMO Radiated Band Edge Measurements (20MHz BW – Partial Tone – MRU).....	284
7.8.10	MIMO Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T) .....	285
7.8.11	MIMO Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T) .....	286
7.8.12	MIMO Radiated Band Edge Measurements (80MHz BW – Partial Tone – MRU).....	287
7.8.13	MIMO Radiated Band Edge Measurements (160MHz BW – Full Tone – 2x996T) .....	288
7.8.14	MIMO Radiated Band Edge Measurements (160MHz BW – Partial Tone – MRU).....	289
7.8.15	MIMO Radiated Band Edge Measurements (320MHz BW – Partial Tone – MRU).....	290
8	CONCLUSION .....	291

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 3 of 291

## MEASUREMENT REPORT

Channel Bandwidth [MHz]	UNII Band	Tx Frequency [MHz]	MIMO	
			Max. Power [mW]	Max. Power [dBm]
20	5	5925 - 6425	9.81	9.92
	6	6435 - 6515	9.41	9.74
	7	6535 - 6875	8.63	9.36
	8	6895 - 7115	7.49	8.74
40	5	5965 - 6405	17.61	12.46
	6	6445 - 6525	17.56	12.44
	7	6565 - 6845	15.71	11.96
	8	6885 - 7085	13.91	11.43
80	5	5985 - 6385	26.45	14.22
	6	6465	24.08	13.82
	7	6545 - 6865	25.84	14.12
	8	6945 - 7025	23.50	13.71
160	5	6025 - 6345	27.32	14.37
	6	6505	27.52	14.40
	7	6665 - 6825	25.16	14.01
	8	6985	22.57	13.54
320	5	6105 - 6265	26.30	14.20
	6	6425	26.66	14.26
	7	6585 - 6745	25.83	14.12
	8	6905	22.32	13.49

**EUT Overview – LPI**

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 4 of 291

Channel Bandwidth [MHz]	UNII Band	Tx Frequency [MHz]	MIMO	
			Max. Power [mW]	Max. Power [dBm]
20	5	5925 - 6425	28.10	14.49
	7	6535 - 6875	26.56	14.24
40	5	5965 - 6405	24.56	13.90
	7	6565 - 6845	25.35	14.04
80	5	5985 - 6385	25.84	14.12
	7	6545 - 6865	25.27	14.03
160	5	6025 - 6345	27.22	14.35
	7	6665 - 6825	25.44	14.06
320	5	6105 - 6265	26.59	14.25
	7	6585 - 6745	24.29	13.85

**EUT Overview – SP**

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 5 of 291

# 1 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

## 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO\IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 6 of 291

## 2 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Electronics Co., Ltd. Portable Computing Device FCC: A3LNP750XQA**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter while operating in the 6GHz band.

**Test Device Serial No.:** 0721L, 0677B, 0713E, 06717, 0802Y

### 2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ac/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE)

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
2	5935	97	6435	117	6535	189	6895
:	:	:	:	:	:	:	:
45	6175	105	6475	149	6695	209	6995
:	:	:	:	:	:	:	:
93	6415	113	6515	185	6875	233	7115

Table 2-1. 802.11ax/be (20MHz) Frequency / Channel Operations

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
3	5965	99	6445	123	6565	187	6885
:	:	:	:	:	:	:	:
43	6165	107	6485	155	6725	211	7005
:	:	:	:	:	:	:	:
91	6405	115	6525	179	6845	227	7085

Table 2-2. 802.11ax/be (40MHz BW) Frequency / Channel Operations

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
7	5985	103	6465	119	6545	199	6945
:	:			:	:	:	:
39	6145			151	6705	215	7025
:	:			:	:		
87	6385			183	6865		

Table 2-3. 802.11ax/be (80MHz BW) Frequency / Channel Operations

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 7 of 291

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
15	6025	111	6505	143	6665	207	6985
:	:			:	:		
47	6185			175	6825		
:	:						
79	6345						

**Table 2-4. 802.11ax/be (160MHz BW) Frequency / Channel Operations**

Band 5		Band 6		Band 7		Band 8	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
31	6105	95	6425	127	6585	191	6905
63	6265			159	6745		

**Table 2-5. 802.11be (320MHz BW) Frequency / Channel Operations**

**Notes:**

1. 6GHz NII operation is possible in 20MHz, 40MHz, 80MHz, 160MHz, and 320MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 8 of 291



Band	Bandwidth	Tone Type	Tone Size	MIMO (1+2)		
				Duty Cycle [%]	Radiated DCCF [dB]	
6GHz	20MHz	RU	26T	99.39	N/A	
			52T	99.61	N/A	
			106T	99.32	N/A	
			242T	98.50	N/A	
		MRU	52+26T	99.49	N/A	
			106+26T	99.12	N/A	
		40MHz	RU	26T	99.49	N/A
				52T	99.55	N/A
	106T			99.32	N/A	
	242T			98.42	N/A	
	MRU		484T	99.37	N/A	
			52+26T	99.46	N/A	
	106+26T		99.16	N/A		
	80MHz		RU	26T	99.57	N/A
		52T		99.47	N/A	
		106T		99.24	N/A	
		242T		98.42	N/A	
		484T		97.29	0.12	
		996T		97.36	0.12	
		MRU	52+26T	99.46	N/A	
			106+26T	99.16	N/A	
			484+242T	97.89	0.09	
		160MHz	RU	26T	99.59	N/A
				52T	99.61	N/A
				106T	99.28	N/A
	242T			98.26	N/A	
	484T			97.26	0.12	
	996T			97.20	0.12	
	2x996T			99.63	N/A	
	MRU			52+26T	99.41	N/A
			106+26T	99.08	N/A	
			484+242T	98.02	N/A	
			996+484T	97.95	0.09	
	RU		26T	99.65	N/A	
			52T	99.43	N/A	
			106T	99.25	N/A	
			242T	98.50	N/A	
			484T	97.36	0.12	
			996T	97.44	0.11	
			2x996T	97.39	0.11	
			4x996T	97.93	0.09	
	MRU		52+26T	99.46	N/A	
			106+26T	99.12	N/A	
			484+242T	98.06	N/A	
			996+484T	97.93	0.09	
			966+484+242T	99.91	N/A	
		2x996+484T	96.76	0.14		
		3x996T	96.10	0.17		
3x996+484T		96.77	0.14			
320MHz	RU	26T	99.59	N/A		
		52T	99.61	N/A		
		106T	99.28	N/A		
		242T	98.26	N/A		
		484T	97.26	0.12		
		996T	97.20	0.12		
	MRU	2x996T	99.63	N/A		
		52+26T	99.41	N/A		
		106+26T	99.08	N/A		
		484+242T	98.02	N/A		
		996+484T	97.95	0.09		
		966+484+242T	99.91	N/A		

**Table 2-6. Measured Duty Cycles – MIMO**

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 9 of 291

2. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		CDD		SDM	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
6 GHz	11ax	x	x	✓	✓	✓	✓
	11be	x	x	✓	✓	✓	✓

**Table 2-7. Frequency / Channel Operations**

✓ = Support; x = NOT Support

**SISO** = Single Input Single Output

**SDM** = Spatial Diversity Multiplexing – MIMO function

**CDD** = Cyclic Delay Diversity - 2Tx Function

3. The device supports the following data rates (shown in Mbps):

MCS Index	Spatial Stream	OFDMA (802.11ax/be)																								OFDMA (802.11be)		
		26T			52T			106T			242T			484T			996T			2x996T			4x996T					
		0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI			
0	0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6	72.1	68.1	61.3	144.1	136.1	122.5		
1	1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5	288.2	272.2	245		
2	2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9	216.2	204.2	183.8	432.4	408.3	367.5		
3	3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245	576.5	544.4	490		
4	4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5	864.7	816.7	735		
5	5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490	1152.9	1088.9	980		
6	6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6	648.5	612.5	551.3	1297.1	1225	1102.5		
7	7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3	720.6	680.6	612.5	1441.2	1361.1	1225		
8	8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735	1729.4	1633.3	1470		
9	9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3	960.8	907.4	816.7	1921.6	1814.8	1633.3		
10	10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4	1080.9	1020.8	918.8	2161.8	2041.7	1837.5		
11	11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4	1201	1134.3	1020.8	2402	2268.5	2041.7		
12	12	1	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5	2594.1	2450	2205		
13	13	1	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225	2882.4	2722.2	2450		
0	0	2	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5	288.2	272.2	245		
1	1	2	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245	576.5	544.4	490		
2	2	2	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5	864.7	816.7	735		
3	3	2	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490	1152.9	1088.9	980		
4	4	2	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735	1729.4	1633.3	1470		
5	5	2	14.1	13.3	12	28.2	26.7	24	60	56.7	51	137.6	130	117	275.3	260	234	576.5	544.4	490	1152.9	1088.9	980	2305.9	2177.8	1960		
6	6	2	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5	2594.1	2450	2205		
7	7	2	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225	2882.4	2722.2	2450		
8	8	2	21.2	20	18	42.4	40	36	90	85	76.5	206.5	195	175.5	412.9	390	351	864.7	816.7	735	1729.4	1633.3	1470	3458.8	3266.7	2940		
9	9	2	23.5	22.2	20	47.1	44.4	40	100	94.4	85	229.4	216.7	195	458.8	433.3	390	960.8	907.4	816.7	1921.6	1814.8	1633.3	3843.1	3629.6	3266.7		
10	10	2	26.5	25	22.5	52.9	50	45	112.5	106.3	95.6	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8	2161.8	2041.7	1837.5	4323.5	4083.3	3675		
11	11	2	29.4	27.8	25	58.8	55.6	50	125	118.1	106.3	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8	2402	2268.5	2041.7	4803.9	4537	4083.3		
12	12	2	31.8	30	27	63.5	60	54	135	127.5	114.8	309.7	292.5	263.3	619.4	585	526.5	1297.1	1225	1102.5	2594.1	2450	2205	5188.2	4900	4410		
13	13	2	35.3	33.3	30	70.6	66.7	60	150	141.7	127.5	344.1	325	292.5	688.2	650	585	1441.2	1361.1	1225	2882.4	2722.2	2450	5764.7	5444.4	4900		

**Table 2-8. Supported Data Rates**

4. The device supports either Standard Power (SP) or Low Power Indoor (LPI) operation in the following UNII bands:

UNII Band	Standard Power (SP)	Low Power Indoor (LPI)
UNII 5	✓	✓
UNII 6	x	✓
UNII 7	✓	✓
UNII 8	x	✓

**Table 2-9. Power Operation**

✓ = Support; x = NOT Support

5. 320MHz Operation is limited to a max “full” tone case of 2x996T.

6. MRU Operation has cases that exceed the “full” tone bandwidth. Care was taken to test and represent the widest bandwidth (3x996T+484T) measurements within this report.

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 10 of 291

## 2.3 Antenna Description

The following antenna gains were used for the testing.

	Ant1 Peak Gain [dBi]	Ant2 Peak Gain [dBi]	Directional Gain [dBi]
5925 – 6425 MHz	-0.15	-0.82	2.53
6425 – 6525 MHz	-0.09	-0.86	2.54
6525 – 6875 MHz	-0.53	-0.87	2.31
6875 – 7125 MHz	-1.18	-1.29	1.78

**Table 2-10. Antenna Peak Gain**

## 2.4 Test Configuration

ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5 and 7.6 for antenna port conducted emissions test setups.

This device supports operation under control of either a low-power indoor access point or standard power access point for frequency ranges 5925 – 6425 MHz and 6525 – 6875 MHz. Power for the EUT may vary depending on whether the device is connected to a standard access point (SP Operation) or a low-power indoor access point (LPI Operation). In cases where these targets differ two data sets have been provided to demonstrate compliance. The worst-case emissions data is shown in this report.

## 2.5 Software and Firmware

The test was conducted with firmware version Windows 11 installed on the EUT.

## 2.6 EMI Suppression Device(s) / Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 11 of 291

### 3 DESCRIPTION OF TESTS

#### 3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 987594 D02 v01r01 were used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

#### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1-meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 12 of 291

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3-meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 13 of 291

## 4 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The EUT complies with the requirement of §15.203.

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 14 of 291

## 5 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Contention Based Protocol Conducted Measurements	0.86
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 15 of 291

## 6 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	4/2/2024	Annual	4/2/2025	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	4/2/2024	Annual	4/2/2025	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	4/2/2024	Annual	4/2/2025	WL40-1
-	AP1-002	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	AP1-002
-	ETS-001	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	ETS-001
-	ETS-002	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	ETS-002
-	MD 1M 18-40	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	MD 1M 18-40
Anritsu	MA24406A	Microwave Peak Power Sensor	9/7/2023	Annual	9/7/2024	11240
Emco	3116	Horn Antenna (18 - 40GHz)	8/8/2022	Biennial	8/8/2024	9203-2178
Rohde & Schwarz	TC-TA18	Vivaldi Antenna	2/23/2023	Biennial	2/23/2025	26040036
Rohde & Schwarz	FSW26	Signal and spectrum analyzer	3/8/2024	Annual	3/8/2025	103187
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	4/2/2024	Annual	4/2/2025	NMLC-2
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	8/11/2022	Biennial	8/11/2024	114451
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	4/9/2024	Annual	4/9/2025	MY52350166
Keysight Technologies	N9020A	MXA Signal Analyzer	4/11/2024	Annual	4/11/2025	MY54500644
Keysight Technologies	N9030A	PXA Signal Analyzer	2/29/2024	Annual	3/1/2025	MY55410501
Keysight Technologies	N9030B	PXA Signal Analyzer, Multi-touch	9/7/2023	Annual	9/7/2024	MY57141001
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	9/25/2023	Annual	9/25/2024	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/11/2023	Annual	9/11/2024	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	4/5/2024	Annual	4/5/2025	101716
Rohde & Schwarz	FSW26	Signal and spectrum analyze (26.5GHz)	3/8/2024	Annual	3/8/2025	103187
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	2/15/2024	Annual	2/15/2025	103200
Sunol	JB6	JB6 Antenna	3/2/2023	Biennial	3/2/2025	A082816
Sunol	JB5	Bi-Log Antenna (30M-5GHz)	8/30/2022	Biennial	8/30/2024	A051107

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 16 of 291



## 7 TEST RESULTS

### 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LNP750XQA  
 FCC Classification: 15E 6GHz Low Power Dual Client (6CD)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1046, 15.407(a)(11)	Maximum Conducted Output Power	N/A	CONDUCTED	PASS	Section 7.2.4
15.407(a)(8), 15.407(a)(7)	Maximum Radiated Output Power	< 24dBm over the frequency band of operation <30dBm over the frequency band of operation when connecting to a standard power access point		PASS	Section 7.2.4
2.1049, 15.407(a)(10)	Occupied Bandwidth/ 26dB Bandwidth	99% of the occupied bandwidth of any channel must be contained within each of its respective U-NII sub bands  The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.		PASS	Section 7.2
15.407(a)(8), 15.407(a)(7)	Maximum Power Spectral Density	< -1dBm/MHz e.i.r.p. <17dBm/MHz when operating with a standard power access point		PASS	Section 7.4
15.407(b)(7)	In-Band Emissions	EUT must meet the limits detailed in 15.407(b)(6)		PASS	Section 7.5
15.407(a)(7)	Power Reduction Verification for standard client device	EUT must limit its power to no more than 6dB below its associated standard power access point's authorized transmit power.  EUT must distinguish its associated access point as standard or low power and control its power levels accordingly.		Pass	Please see Dual Client PRV report
15.407(d)(6)	Contention Based Protocol	EUT must detect AWGN signal with 90% (or better) certainty	RADIATED	PASS	Section 7.6
15.407(b)(6)	Undesirable Emissions	< -27dBm/MHz e.i.r.p. outside of the 5.925 – 7.125GHz band		PASS	Section 7.8
15.205, 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		PASS	Section 7.8
15.407	AC Conducted Emissions 150kHz – 30MHz	<FCC 15.207 limits	LINE CONDUCTED	PASS	Please see UNII 6E OFDM report

**Table 7-1. Summary of Test Results**

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 17 of 291

**Notes:**

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "UNII Automation," Version 4.7.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.3.1.
- 6) Per 15.407(a)(7), a device operating under the control of a standard power access point in 5.925-6.425 GHz and 6.525-6.875 GHz bands must not have the maximum power spectral density exceed 17 dBm/MHz e.i.r.p., must limit the maximum e.i.r.p. over the frequency band of operation not exceed 30 dBm, and must limit its power to no more than 6 dB below its associated standard power access point's authorized transmit power. Compliance to this clause is addressed in the AFC PRV supplemental report.
- 7) 802.11ax OFDMA testing was performed for all signal tone configurations as specified by the 802.11ax standard. Worst case results are determined and reported per the guidance provided at the October 2018 TCB Workshop.
- 8) Only one RU index could be selected at a time, so no contiguous or non-contiguous RUs were considered for testing.

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 18 of 291

## 7.2 26dB Bandwidth Measurement

### Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

### Test Procedure Used

ANSI C63.10-2013 – Section 12.4

### Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 26$ . The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

7. 320MHz Operation is limited to a max "full" tone case of 2x996T.
8. MRU Operation has cases that exceed the "full" tone bandwidth. Care was taken to test and represent the widest bandwidth (3x996T+484T) measurements within this report.

FCC ID: A3LNP750XQA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 19 of 291

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 5	5935	2	be (20MHz)	19.93	19.69
	6175	45	be (20MHz)	19.89	19.59
	6415	93	be (20MHz)	20.23	20.02
	5965	3	be (40MHz)	25.10	24.91
	6165	43	be (40MHz)	25.29	25.41
	6405	91	be (40MHz)	24.86	25.18
	5985	7	be (80MHz)	25.22	33.30
	6145	39	be (80MHz)	33.12	32.78
	6385	87	be (80MHz)	35.48	33.90
	6025	15	be (160MHz)	43.62	33.93
	6185	47	be (160MHz)	40.83	34.40
	6345	79	be (160MHz)	35.85	39.83
	6105	31	be (320MHz)	48.27	47.19
Band 6	6265	63	be (320MHz)	48.77	49.47
	6435	97	be (20MHz)	19.97	19.91
	6475	105	be (20MHz)	19.86	20.06
	6515	113	be (20MHz)	19.96	19.87
	6445	99	be (40MHz)	25.45	25.06
	6485	107	be (40MHz)	25.53	25.30
	6525	115	be (40MHz)	24.83	24.92
	6465	103	be (80MHz)	34.82	31.69
Band 5/6/7	6505	111	be (160MHz)	41.85	34.34
Band 7	6425	95	be (320MHz)	41.10	40.71
	6695	117	be (20MHz)	20.08	20.14
	6695	149	be (20MHz)	20.23	20.12
	6875	185	be (20MHz)	20.27	19.97
	6565	123	be (40MHz)	23.90	23.87
	6685	155	be (40MHz)	26.87	24.48
	6845	179	be (40MHz)	26.14	23.69
	6545	119	be (80MHz)	34.63	35.13
	6705	151	be (80MHz)	37.97	26.99
	6865	183	be (80MHz)	29.91	35.03
	6665	143	be (160MHz)	32.39	34.82
	6825	175	be (160MHz)	40.01	40.46
	Band 6/7	6585	127	be (320MHz)	47.62
Band 7/8	6745	159	be (320MHz)	50.81	49.89
Band 8	7115	189	be (20MHz)	20.08	19.82
	6995	209	be (20MHz)	20.42	20.08
	7115	233	be (20MHz)	19.79	20.04
	6885	187	be (40MHz)	24.30	24.72
	6965	211	be (40MHz)	24.26	24.36
	7085	227	be (40MHz)	24.22	25.48
	6945	199	be (80MHz)	32.91	30.49
	7025	215	be (80MHz)	35.17	30.79
	6985	207	be (160MHz)	34.18	37.55
Band 7/8	6905	191	be (320MHz)	45.85	42.30

**Table 7-2. Occupied Bandwidth Results – 26 Tones**

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 20 of 291

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 5	5935	2	be (20MHz)	21.28	21.39
	6175	45	be (20MHz)	21.11	21.24
	6415	93	be (20MHz)	21.51	21.25
	5965	3	be (40MHz)	42.31	42.92
	6165	43	be (40MHz)	41.93	42.17
	6405	91	be (40MHz)	41.96	42.55
	5985	7	be (80MHz)	86.30	87.69
	6145	39	be (80MHz)	85.70	88.54
	6385	87	be (80MHz)	90.32	93.14
	6025	15	be (160MHz)	174.03	173.67
	6185	47	be (160MHz)	175.37	175.47
	6345	79	be (160MHz)	175.02	174.33
	6105	31	be (320MHz)	254.78	297.91
	6265	63	be (320MHz)	269.81	301.64
Band 6	6435	97	be (20MHz)	21.48	21.42
	6475	105	be (20MHz)	21.56	21.15
	6515	113	be (20MHz)	21.33	21.35
	6445	99	be (40MHz)	41.98	43.19
	6485	107	be (40MHz)	42.69	42.46
	6525	115	be (40MHz)	41.95	42.45
	6465	103	be (80MHz)	89.18	91.86
	6505	111	be (160MHz)	171.23	173.66
Band 5/6/7	6425	95	be (320MHz)	256.38	265.72
Band 7	6695	117	be (20MHz)	21.60	21.18
	6695	149	be (20MHz)	21.44	21.21
	6875	185	be (20MHz)	21.45	21.19
	6565	123	be (40MHz)	41.78	42.90
	6685	155	be (40MHz)	42.23	43.06
	6845	179	be (40MHz)	41.81	42.52
	6545	119	be (80MHz)	87.52	92.32
	6705	151	be (80MHz)	87.25	92.26
	6865	183	be (80MHz)	85.78	92.21
	6665	143	be (160MHz)	175.34	177.10
6825	175	be (160MHz)	174.06	175.91	
Band 6/7	6585	127	be (320MHz)	260.21	298.62
Band 7/8	6745	159	be (320MHz)	262.58	273.09
Band 8	7115	189	be (20MHz)	21.59	21.14
	6995	209	be (20MHz)	21.52	21.25
	7115	233	be (20MHz)	21.10	21.12
	6885	187	be (40MHz)	42.06	42.92
	6965	211	be (40MHz)	42.96	43.01
	7085	227	be (40MHz)	42.67	42.93
	6945	199	be (80MHz)	86.35	93.29
	7025	215	be (80MHz)	89.63	89.78
Band 7/8	6985	207	be (160MHz)	174.21	178.13
Band 7/8	6905	191	be (320MHz)	260.07	265.88

**Table 7-3. Occupied Bandwidth Results – Full Tones**


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 21 of 291

	Frequency [MHz]	Channel	802.11 MODE	MRU Configuration	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]	Antenna-1 Occupied Bandwidth [MHz]	Antenna-2 Occupied Bandwidth [MHz]
Band 5	6175	45	be (20MHz)	106+26T	20.43	19.99	-	-
	6145	39	be (80MHz)	484+242T	91.14	87.03	-	-
	6185	47	be (160MHz)	996+484T	177.50	174.25	-	-
	6105	31	be (320MHz)	3x996+484T	-	-	312.45	313.23
	6105	31	be (320MHz)	3x996T	-	-	312.85	316.66
Band 6	6105	31	be (320MHz)	2x996+484T	298.96	307.21	-	-
	6475	105	be (20MHz)	106+26T	19.69	20.09	-	-
	6465	103	be (80MHz)	484+242T	86.50	91.71	-	-
Band 5/6/7	6505	111	be (160MHz)	996+484T	175.84	176.20	-	-
	6425	95	be (320MHz)	3x996+484T	-	-	311.68	316.90
	6425	95	be (320MHz)	3x996T	-	-	312.04	317.47
Band 7	6425	95	be (320MHz)	2x996+484T	305.54	312.63	-	-
	6695	149	be (20MHz)	106+26T	20.56	20.41	-	-
	6705	151	be (80MHz)	484+242T	86.75	91.92	-	-
Band 7/8	6665	143	be (160MHz)	996+484T	174.34	175.81	-	-
	6745	159	be (320MHz)	3x996+484T	-	-	312.81	316.40
	6745	159	be (320MHz)	3x996T	-	-	312.62	316.92
Band 8	6745	159	be (320MHz)	2x996+484T	299.80	302.58	-	-
	6995	209	be (20MHz)	106+26T	20.42	20.14	-	-
	6945	199	be (80MHz)	484+242T	87.90	92.23	-	-
Band 7/8	6985	207	be (160MHz)	996+484T	174.86	176.13	-	-
	6905	191	be (320MHz)	3x996+484T	-	-	316.06	317.11
	6905	191	be (320MHz)	3x996T	-	-	313.31	316.97
	6905	191	be (320MHz)	2x996+484T	294.53	305.38	-	-

**Table 7-4. Occupied Bandwidth Results – MRU**

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 22 of 291

## 7.2.1 MIMO Antenna-1 Bandwidth Measurements - (Partial Tones)




Plot 7-1. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45)




Plot 7-2. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 23 of 291




Plot 7-3. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 39)



Plot 7-4. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 47)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 24 of 291







Plot 7-5. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (26 Tones) (UNII Band 5) – Ch. 31)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 25 of 291

## MIMO Antenna-1 Bandwidth Measurements - (Partial Tones)




Plot 7-6. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 105)




Plot 7-7. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 107)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 26 of 291




Plot 7-8. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 103)



Plot 7-9. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 111)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 27 of 291



Plot 7-10. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (26 Tones) (UNII Band 6) – Ch. 95)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 28 of 291

## MIMO Antenna-1 Bandwidth Measurements - (Partial Tones)




Plot 7-11. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 149)




Plot 7-12. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 155)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 29 of 291




Plot 7-13. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 151)



Plot 7-14. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 143)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 30 of 291




Plot 7-15. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (26 Tones) (UNII Band 7) – Ch. 159)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 31 of 291

## MIMO Antenna-1 Bandwidth Measurements - (Partial Tones)




Plot 7-16. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 209)




Plot 7-17. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 211)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 32 of 291






Plot 7-18. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 199)



Plot 7-19. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 207)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 33 of 291




Plot 7-20. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (26 Tones) (UNII Band 8) – Ch. 191)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 34 of 291

## 7.2.2 MIMO Antenna-1 Bandwidth Measurements - (Full Tones)




Plot 7-21. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45)




Plot 7-22. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 43)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 35 of 291




Plot 7-23. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 39)



Plot 7-24. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 36 of 291




Plot 7-25. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (Full Tones) (UNII Band 5) – Ch. 31)

FCC ID: A3LNP750XQA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 37 of 291

## MIMO Antenna-1 Bandwidth Measurements - (Full Tones)




Plot 7-26. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 105)




Plot 7-27. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 107)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 38 of 291




Plot 7-28. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 103)



Plot 7-29. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 111)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 39 of 291




Plot 7-30. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (Full Tones) (UNII Band 6) – Ch. 95)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 40 of 291



## MIMO Antenna-1 Bandwidth Measurements - (Full Tones)




Plot 7-31. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 149)




Plot 7-32. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 155)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 41 of 291




Plot 7-33. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 151)



Plot 7-34. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 143)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 42 of 291




Plot 7-35. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (Full Tones) (UNII Band 7) – Ch. 159)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 43 of 291

## MIMO Antenna-1 Bandwidth Measurements - (Full Tones)




Plot 7-36. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 8) – Ch. 209)




Plot 7-37. Occupied Bandwidth Plot MIMO ANT1 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 8) – Ch. 211)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 44 of 291




Plot 7-38. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 8) – Ch. 199)



Plot 7-39. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 8) – Ch. 207)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 45 of 291




Plot 7-40. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (Full Tones) (UNII Band 8) – Ch. 191)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 46 of 291

### 7.2.3 MIMO Antenna-1 Bandwidth Measurements - (Partial Tones - MRU)




Plot 7-41. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be (106+26 Tones) (UNII Band 5) – Ch. 45)




Plot 7-42. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 47 of 291



Plot 7-43. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47)




Plot 7-44. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (3\*996+484 Tones) (UNII Band 5) – Ch. 31)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 48 of 291



## MIMO Antenna-1 Bandwidth Measurements - (Partial Tones - MRU)




Plot 7-45. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be (52+26 Tones) (UNII Band 6) – Ch. 105)




Plot 7-46. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be (484+242 Tones) (UNII Band 6) – Ch. 103)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 49 of 291




Plot 7-47. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be (996+484 Tones) (UNII Band 6) – Ch. 111)




Plot 7-48. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (3\*996+484 Tones) (UNII Band 6) – Ch. 95)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 50 of 291

## MIMO Antenna-1 Bandwidth Measurements - (Partial Tones - MRU)




Plot 7-49. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be (106+26 Tones) (UNII Band 7) – Ch. 149)




Plot 7-50. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be (484+242 Tones) (UNII Band 7) – Ch. 151)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 51 of 291




Plot 7-51. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be (996+484 Tones) (UNII Band 7) – Ch. 143)




Plot 7-52. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (3\*996+484 Tones) (UNII Band 7) – Ch. 159)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 52 of 291

### MIMO Antenna-1 Bandwidth Measurements - (Partial Tones - MRU)




Plot 7-53. Occupied Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be (106+26 Tones) (UNII Band 8) – Ch. 209)




Plot 7-54. Occupied Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be (484+242 Tones) (UNII Band 8) – Ch. 199)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 53 of 291




Plot 7-55. Occupied Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be (996+484 Tones) (UNII Band 8) – Ch. 207)




Plot 7-56. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (3\*996+484 Tones) (UNII Band 8) – Ch. 191)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 54 of 291

### 7.2.4 MIMO Antenna-2 Bandwidth Measurements - (Partial Tones)




Plot 7-57. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45)




Plot 7-58. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 55 of 291




Plot 7-59. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 39)



Plot 7-60. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax (26 Tones) (UNII Band 5) – Ch. 47)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 56 of 291







Plot 7-61. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (26 Tones) (UNII Band 5) – Ch. 31)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 57 of 291

## MIMO Antenna-2 Bandwidth Measurements - (Partial Tones)




Plot 7-62. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 105)




Plot 7-63. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 107)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 58 of 291




Plot 7-64. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 103)



Plot 7-65. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 6) – Ch. 111)


FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 59 of 291



Plot 7-66. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (26 Tones) (UNII Band 6) – Ch. 95)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 60 of 291

## MIMO Antenna-2 Bandwidth Measurements - (Partial Tones)




Plot 7-67. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 149)




Plot 7-68. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 155)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 61 of 291




Plot 7-69. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 151)



Plot 7-70. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 7) – Ch. 143)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 62 of 291




Plot 7-71. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (26 Tones) (UNII Band 7) – Ch. 159)

FCC ID: A3LNP750XQA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 63 of 291

## MIMO Antenna-2 Bandwidth Measurements - (Partial Tones)




Plot 7-72. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 209)




Plot 7-73. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 211)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 64 of 291






Plot 7-74. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 199)



Plot 7-75. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax/be (26 Tones) (UNII Band 8) – Ch. 207)


FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 65 of 291




Plot 7-76. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (26 Tones) (UNII Band 8) – Ch. 191)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 66 of 291

## 7.2.5 MIMO Antenna-2 Bandwidth Measurements - (Full Tones)




Plot 7-77. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45)




Plot 7-78. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 43)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 67 of 291




Plot 7-79. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 39)



Plot 7-80. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 68 of 291




Plot 7-81. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (Full Tones) (UNII Band 5) – Ch. 31)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 69 of 291

## MIMO Antenna-2 Bandwidth Measurements - (Full Tones)




Plot 7-82. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 105)




Plot 7-83. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 107)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 70 of 291




Plot 7-84. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 103)



Plot 7-85. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 6) – Ch. 111)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 71 of 291




Plot 7-86. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (Full Tones) (UNII Band 6) – Ch. 95)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 72 of 291



## MIMO Antenna-2 Bandwidth Measurements - (Full Tones)




Plot 7-87. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 149)




Plot 7-88. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 155)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 73 of 291




Plot 7-89. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 151)



Plot 7-90. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax/be (Full Tones) (UNII Band 7) – Ch. 143)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 74 of 291




Plot 7-91. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (Full Tones) (UNII Band 7) – Ch. 159)

<b>FCC ID:</b> A3LNP750XQA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2407080057-09-R1.A3L	<b>Test Dates:</b> 7/30/2024 – 8/26/2024	<b>EUT Type:</b> Portable Computing Device	Page 75 of 291

## MIMO Antenna-2 Bandwidth Measurements - (Full Tones)




Plot 7-92. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11ax (Full Tones) (UNII Band 8) – Ch. 209)




Plot 7-93. Occupied Bandwidth Plot MIMO ANT2 (40MHz BW 802.11ax (Full Tones) (UNII Band 8) – Ch. 211)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 76 of 291




Plot 7-94. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11ax (Full Tones) (UNII Band 8) – Ch. 199)



Plot 7-95. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11ax (Full Tones) (UNII Band 8) – Ch. 207)


FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 77 of 291




Plot 7-96. Occupied Bandwidth Plot MIMO ANT1 (320MHz BW 802.11be (Full Tones) (UNII Band 8) – Ch. 191)

FCC ID: A3LNP750XQA		MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device		Page 78 of 291

## 7.2.6 MIMO Antenna-2 Bandwidth Measurements - (Partial Tones - MRU)




Plot 7-97. Occupied Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be (106+26 Tones) (UNII Band 5) – Ch. 45)




Plot 7-98. Occupied Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 79 of 291



Plot 7-99. Occupied Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47)



Plot 7-100. Occupied Bandwidth Plot MIMO ANT2 (320MHz BW 802.11be (3\*996+484 Tones) (UNII Band 5) – Ch. 31)

FCC ID: A3LNP750XQA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2407080057-09-R1.A3L	Test Dates: 7/30/2024 – 8/26/2024	EUT Type: Portable Computing Device	Page 80 of 291