



# ELEMENT WASHINGTON DC LLC

7185 Oakland Mills Road, Columbia, MD 21046 USA  
Tel. 410.290.6652 / Fax 410.381.1520  
<http://www.element.com>

## MEASUREMENT REPORT FCC PART 15.247 802.11b/g/n/ax/be (OFDM)

**Applicant Name:**  
Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**  
03/18/2024-05/01/2024  
**Test Report Issue Date:**  
05/02/2024  
**Test Site/Location:**  
Element lab., Columbia, MD, USA  
**Test Report Serial No.:**  
1M2401250007-03-R1.A3L

<b>FCC ID:</b>	<b>A3LNP960XMA</b>
<b>APPLICANT:</b>	<b>Samsung Electronics Co., Ltd.</b>

**Application Type:** Certification  
**Model:** NP960XMA  
**Additional Model(s):** NP960XMB, NP964XMA, NP964XMB  
**EUT Type:** Portable Computing Device  
**Frequency Range:** 2412 – 2472MHz  
**Modulation Type:** CCK, DSSS, OFDM  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15 Subpart C (15.247)  
**Test Procedure(s):** ANSI C63.10-2013, KDB 484596 D01 v02r03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2401250007-03-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2401250007-03.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**RJ Ortanez**  
**Executive Vice President**



<b>FCC ID:</b> A3LNP960XMA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401250007-03-R1.A3L	<b>Test Dates:</b> 03/18/2024-05/01/2024	<b>EUT Type:</b> Portable Computing Device	Page 1 of 119

## TABLE OF CONTENTS

1.0	INTRODUCTION.....	4
1.1	Scope .....	4
1.2	Element Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION .....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities.....	5
2.3	Test Configuration .....	7
2.4	Antenna Description .....	7
2.5	Software and Firmware .....	7
2.6	EMI Suppression Device(s) / Modifications .....	7
3.0	DESCRIPTION OF TESTS .....	8
3.1	Evaluation Procedure .....	8
3.2	AC Line Conducted Emissions .....	8
3.3	Radiated Emissions.....	9
3.4	Environmental Conditions.....	9
4.0	ANTENNA REQUIREMENTS .....	10
5.0	MEASUREMENT UNCERTAINTY.....	11
6.0	TEST EQUIPMENT CALIBRATION DATA.....	12
7.0	TEST RESULTS.....	13
7.1	Summary .....	13
7.2	6dB Bandwidth Measurement .....	16
7.3	Output Power Measurement.....	37
7.4	Power Spectral Density .....	42
7.5	Conducted Band Edge Emissions .....	64
7.6	Conducted Spurious Emissions.....	89
7.7	Radiated Emission Measurements.....	100
7.8	Line-Conducted Test Data.....	115
8.0	CONCLUSION .....	119

<b>FCC ID:</b> A3LNP960XMA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401250007-03-R1.A3L	<b>Test Dates:</b> 03/18/2024-05/01/2024	<b>EUT Type:</b> Portable Computing Device	Page 2 of 119

## MEASUREMENT REPORT

Channel Bandwidth [MHz]	IEEE Mode	Tx Frequency [MHz]	Ant2				MIMO			
			Avg. Conducted		Peak Conducted		Avg. Conducted		Peak Conducted	
			Max. Power [mW]	Max. Power [dBm]	Max. Power [mW]	Max. Power [dBm]	Max. Power [mW]	Max. Power [dBm]	Max. Power [mW]	Max. Power [dBm]
20	802.11b	2412 - 2472	30.13	14.79	71.94	18.57	61.38	17.88	134.55	21.29
	802.11g	2412 - 2472	30.62	14.86	104.47	20.19	57.15	17.57	195.33	22.91
	802.11n	2412 - 2472	30.62	14.86	101.62	20.07	54.45	17.36	179.21	22.53
	802.11ax	2412 - 2472	27.35	14.37	110.41	20.43	49.32	16.93	195.50	22.91
	802.11be	2412 - 2472	27.93	14.46	112.20	20.50	49.66	16.96	200.27	23.02

### EUT Overview

<b>FCC ID:</b> A3LNP960XMA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401250007-03-R1.A3L	<b>Test Dates:</b> 03/18/2024-05/01/2024	<b>EUT Type:</b> Portable Computing Device	Page 3 of 119

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO\IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 4 of 119

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Computing Device FCC ID: A3LNP960XMA**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

**Test Device Serial No.:** 1224R, 1105D, 0851W, 1123F

### 2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE)

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	12	2467
		13	2472

**Table 2-1. Frequency \ Channel Operations**

#### Notes:

1. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of ANSI C63.10-2013 and KDB 558074 D01 v05r02. The RBW and VBW were both greater than 50\T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

802.11 Mode/Band		ANT2	MIMO (1+2)
		Duty Cycle [%]	Duty Cycle [%]
2.4GHz	b	99.86	99.77
	g	99.10	99.53
	n (HT20)	99.65	99.63
	ax (HE20)	99.67	99.63
	be (EHT20)	99.65	99.63

**Table 2-2. Measured Duty Cycles**

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 5 of 119



2. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CDD	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
2.4GHz	11b	✗	✓	✗	✗	✓	✓
2.4GHz	11g	✗	✓	✓	✓	✓	✓
2.4GHz	11n	✗	✓	✓	✓	✓	✓
2.4GHz	11ax	✗	✓	✓	✓	✓	✓
2.4GHz	11be	✗	✓	✓	✓	✓	✓

**Table 2-3. Antenna / Technology Configuration**

✓ = Support; ✗ = NOT Support

**SISO** = Single Input Single Output

**SDM** = Spatial Diversity Multiplexing – MIMO function

**CDD** = Cyclic Delay Diversity - 2Tx Function

3. The device supports the following data rates (shown in Mbps):

802.11b	802.11a/g 20MHz	MCS Index		Spatial Stream	OFDM (802.11n)		OFDM (802.11ax)		
					20MHz		20MHz		
		HT	HE		0.8µs GI	0.4µs GI	0.8µs GI	1.6µs GI	3.2µs GI
1	6	0	0	1	6.5	7.2	8.6	8.1	7.3
2	9	1	1	1	13	14.4	17.2	16.3	14.6
5.5	12	2	2	1	19.5	21.7	25.8	24.4	21.9
11	18	3	3	1	26	28.9	34.4	32.5	29.3
	24	4	4	1	39	43.3	51.6	48.8	43.9
	36	5	5	1	52	57.8	68.8	65	58.5
	48	6	6	1	58.5	65	77.4	73.1	65.8
	54	7	7	1	65	72.2	86	81.3	73.1
			8	1			103.2	97.5	87.8
			9	1			114.7	108.3	97.5
			10	1			129	121.9	109.7
			11	1			143.4	135.4	121.9
1	6	8	0	2	13	14.4	17.2	16.3	14.6
2	9	9	1	2	26	28.9	34.4	32.5	29.3
5.5	12	10	2	2	39	43.3	51.6	48.8	43.9
11	18	11	3	2	52	57.8	68.8	65	58.5
	24	12	4	2	78	86.7	103.2	97.5	87.8
	36	13	5	2	104	115.6	137.6	130	117
	48	14	6	2	117	130	154.9	146.3	131.6
	54	15	7	2	130	144.4	172.1	162.5	146.3
			8	2	156	173.3	206.5	195	175.5
			9	2	N/A	N/A	229.4	216.7	195
			10	2			258.1	243.8	219.4
			11	2			286.8	270.8	243.8

**Table 2-4. Supported Data Rates**

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 6 of 119



This device supports simultaneous transmission operation, which allows for two SISO channels to operate independently of one another in the 2.4GHz and 5GHz bands simultaneously on each antenna. The following tables show the worst-case configurations determined during testing.

**Configuration 1:** ANT1 and ANT2 both transmit in 2.4GHz and 5GHz modes simultaneously.

Description	2.4 GHz Emission	5 GHz Emission
Antenna	1, 2	1, 2
Channel	6	120
Operating Frequency (MHz)	2437	5600
Data Rate (Mbps)	1Mbps	6Mbps
Mode	802.11b	802.11a

**Table 2-5. Config-1 (2.4GHz MIMO & 5GHz MIMO)**

**Configuration 2:** ANT1 and ANT2 both transmit in 2.4GHz and 6GHz modes simultaneously.

Description	2.4 GHz Emission	6 GHz Emission
Antenna	1, 2	1, 2
Channel	6	2
Operating Frequency (MHz)	2437	5935
Data Rate (Mbps)	1Mbps	6Mbps
Mode	802.11b	802.11a

**Table 2-6. Config-2 (2.4GHz MIMO & 6GHz MIMO)**

## 2.3 Test Configuration

ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 7.8 for AC line conducted emissions test setups, 7.7 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

## 2.4 Antenna Description

This device is only used with its integral antennas as shown in the documentation of this filing. The antenna gains for this device are as shown in the table below:

Frequency [GHz]	Antenna-1 Gain [dBi]	Antenna-2 Gain [dBi]	Directional Gain [dBi]
2.4	-1.62	-1.82	1.29

**Table 2-7. Antenna Peak Gain**

## 2.5 Software and Firmware

The test was conducted with firmware version REV0.1 and software version Windows 11 installed on the EUT.

## 2.6 EMI Suppression Device(s) / Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 7 of 119

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω\50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI\RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration\arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.8. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401250007-03-R1.A3L	<b>Test Dates:</b> 03/18/2024-05/01/2024	<b>EUT Type:</b> Portable Computing Device	Page 8 of 119



### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 9 of 119

## 4.0 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules\Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

**Conclusion:**

The EUT unit complies with the requirement of §15.203.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 10 of 119

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 11 of 119

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
N/A	WL25-1	Conducted Cable Set (25GHz)	11/15/2023	Annual	11/15/2024	WL25-1
N/A	WL25-2	Conducted Cable Set (25GHz)	11/15/2023	Annual	11/15/2024	WL25-2
N/A	WL40-1	Conducted Cable Set (40GHz)	11/15/2023	Annual	11/15/2024	WL40-1
N/A	ETS-001	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	ETS-001
N/A	ETS-002	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	ETS-002
N/A	AP1-002	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	AP1-002
N/A	AP2-001	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	AP2-001
N/A	AP2-001	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	AP2-001
Anritsu	MA2411B	Pulse Power Sensor	11/8/2023	Annual	11/8/2024	1027293
Anritsu	MA2411B	Pulse Power Sensor	6/14/2023	Annual	6/14/2024	1911105
Com-Power	AL-130	9kHz-30MHz Loop Antenna	4/13/2022	Biennial	4/13/2025	121034
Keysight Technologies	N9038A	MXE EMI Reciever	8/30/2023	Annual	8/30/2024	MY51210133
Keysight Technologies	N9038A	PXA Signal Analyzer	2/29/2023	Annual	3/1/2025	MY55410501
Keysight Technologies	N6020A	MXA Signal Analyzer	3/22/2024	Annual	3/22/2025	US46470561
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	11/15/2023	Annual	11/15/2024	NMLC-2
Rohde & Schwarz	ESU26	EMI Test Reciever (26.5GHz)	9/25/2023	Annual	9/25/2023	100342
Rohde & Schwarz	ESU40	EMI Test Reciever (40GHz)	9/11/2023	Annual	9/11/2024	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	2/15/2024	Annual	2/15/2025	103200
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	3/15/2023	Annual	3/15/2025	102136
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	3/15/2023	Annual	3/15/2025	102132
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	1/11/2024	Annual	1/11/2025	102151
Sunol Sciences	DRH-118	Horn (Small)	2/21/2024	Biennial	2/21/2026	A050307
Sunol Sciences	JB5	Bi-Log Antenna (30M-5GHz)	8/30/2022	Biennial	8/30/2024	A051107

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 12 of 119

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LNP960XMA  
 FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2(a)]	6dB Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.	CONDUCTED	PASS	Section 7.2
15.247(b)(3)	RSS-247 [5.4(b)]	Transmitter Output Power	shall not exceed 1 W		PASS	Section 7.3
N/A	RSS-247 [5.4(b)]	e.i.r.p.	shall not exceed 4 W		PASS	Section 7.3
15.247(e)	RSS-247 [5.2(b)]	Transmitter Power Spectral Density	shall not be greater than 8 dBm in any 3 kHz band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge \\ Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Section 7.7
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen [8.8])	LINE CONDUCTED	PASS	Section 7.8

**Table 7-1. Summary of Test Results**

#### Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst-case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “WLAN Automation,” Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 1.3.1.

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 13 of 119



6) Data was leveraged from model NP960XMA for the certification of NP960XMB. See Table 7-2 for spot-check results.

FCC Rules	Test Item	Test Case	Units	Limit	Reference Model: NP960XMA	Variant Model: NP960XMB	Deviation	Max Deviation	Pass/Fail
15.247(b)(3)	Conducted Output Power	20MHz, Ch.6, 802.11b	dBm	N/A	17.88	17.01	0.87	3	PASS
15.207	AC Line Conducted	-	dBm		-	-	-	-	PASS
15.209	Radiated Spurious Emissions	20MHz, Ch.6, 802.11b	dBm	53.98	31.04	34.01	2.97	3	PASS
15.209	Radiated Band Edge Emissions	20MHz, Ch.13, 802.11be	dBm	53.98	51.95	51.42	0.53	3	PASS

**Table 7-2. Summary of Spot-checks**

2.4GHz WIFI (20MHz 802.11b MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dB]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq [MHz]	Channel	Detector	Conducted Power [dBm]								
			ANT1	ANT2	MIMO						
2437	6	Average	13.73	14.25	17.01	30.00	-12.99	1.29	18.30	36.02	-17.72

**Table 7-3. Conducted Output Power Measurements (Spot-check)**

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2437MHz  
 Channel: 6


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m ]	Margin [dB]
4874.00	Avg	H	-	-	-82.59	9.60	0.00	34.01	53.98	-19.97
4874.00	Peak	H	-	-	-70.22	9.60	0.00	46.38	73.98	-27.60

**Table 7-4. Radiated Measurements MIMO (Spot-check)**

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 14 of 119



Worst Case Mode: 802.11be  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2472MHz  
 Channel: 13



**Plot 7-1. Radiated Restricted Upper Band Edge Measurement MIMO (Average) - (Spot-check)**

- 7) Each spot check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.
- 8) All test cases were performed to verify the variant EUT is still in compliance with the spot checked results to the reference device and was performed using the guidance of ANSI C63.10-2013.
- 9) In this report, AC line conducted spurious emissions were taken with model NP960XMA and NP960XMB and label in section 7.8 as M1 and M2 respectively.

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 15 of 119

## 7.2 6dB Bandwidth Measurement

### Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

***The minimum 6 dB bandwidth shall be at least 500 kHz.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 16 of 119



## 6dB Bandwidth Measurements

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
2412	1	b	1	8.079	0.500
2437	6	b	1	8.078	0.500
2462	11	b	1	8.083	0.500
2412	1	g	6	16.38	0.500
2437	6	g	6	16.38	0.500
2462	11	g	6	16.37	0.500
2412	1	n	6.5/7.2 (MCS0)	17.62	0.500
2437	6	n	6.5/7.2 (MCS0)	17.63	0.500
2462	11	n	6.5/7.2 (MCS0)	17.61	0.500
2412	1	ax/be	6.5/7.2 (MCS0)	19.14	0.500
2437	6	ax/be	6.5/7.2 (MCS0)	19.16	0.500
2462	11	ax/be	6.5/7.2 (MCS0)	19.10	0.500

**Table 7-5. Conducted 6dB Bandwidth Measurements SISO ANT2**


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 17 of 119

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]	Minimum Bandwidth [MHz]
2412	1	b	1	7.630	8.080	0.500
2437	6	b	1	7.557	7.568	0.500
2462	11	b	1	8.091	8.083	0.500
2412	1	g	6	16.40	16.40	0.500
2437	6	g	6	16.38	16.41	0.500
2462	11	g	6	16.39	16.41	0.500
2412	1	n	6.5/7.2 (MCS0)	17.62	17.63	0.500
2437	6	n	6.5/7.2 (MCS0)	17.64	17.61	0.500
2462	11	n	6.5/7.2 (MCS0)	17.65	17.63	0.500
2412	1	ax/be	6.5/7.2 (MCS0)	19.00	19.08	0.500
2437	6	ax/be	6.5/7.2 (MCS0)	19.03	19.04	0.500
2462	11	ax/be	6.5/7.2 (MCS0)	19.02	19.00	0.500


**Table 7-6. Conducted 6dB Bandwidth Measurements MIMO**

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 18 of 119

## 7.2.1 SISO Antenna-2 6dB Bandwidth Measurements




Plot 7-2. 6dB Bandwidth Plot SISO ANT2 (802.11b – Ch. 1)




Plot 7-3. 6dB Bandwidth Plot SISO ANT2 (802.11b – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 19 of 119




Plot 7-4. 6dB Bandwidth Plot SISO ANT2 (802.11b – Ch. 11)




Plot 7-5. 6dB Bandwidth Plot SISO ANT2 (802.11g – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 20 of 119




Plot 7-6. 6dB Bandwidth Plot SISO ANT2 (802.11g – Ch. 6)




Plot 7-7. 6dB Bandwidth Plot SISO ANT2 (802.11g – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 21 of 119




Plot 7-8. 6dB Bandwidth Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-9. 6dB Bandwidth Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 22 of 119




Plot 7-10. 6dB Bandwidth Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-11. 6dB Bandwidth Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 23 of 119



Plot 7-12. 6dB Bandwidth Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 6)




Plot 7-13. 6dB Bandwidth Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 11)


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 24 of 119



## 7.2.2 MIMO 6dB Bandwidth Measurements




Plot 7-14. 6dB Bandwidth Plot MIMO ANT1 (802.11b – Ch. 1)




Plot 7-15. 6dB Bandwidth Plot MIMO ANT1 (802.11b – Ch. 6)

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 25 of 119




Plot 7-16. 6dB Bandwidth Plot MIMO ANT1 (802.11b – Ch. 11)




Plot 7-17. 6dB Bandwidth Plot MIMO ANT1 (802.11g – Ch. 1)

FCC ID: A3LNP960XMA	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 26 of 119




Plot 7-18. 6dB Bandwidth Plot MIMO ANT1 (802.11g – Ch. 6)




Plot 7-19. 6dB Bandwidth Plot MIMO ANT1 (802.11g – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 27 of 119




Plot 7-20. 6dB Bandwidth Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 1)




Plot 7-21. 6dB Bandwidth Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 28 of 119




Plot 7-22. 6dB Bandwidth Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 11)




Plot 7-23. 6dB Bandwidth Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 29 of 119




Plot 7-24. 6dB Bandwidth Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 6)




Plot 7-25. 6dB Bandwidth Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 30 of 119




Plot 7-26. 6dB Bandwidth Plot MIMO ANT2 (802.11b – Ch. 1)




Plot 7-27. 6dB Bandwidth Plot MIMO ANT2 (802.11b – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 31 of 119






Plot 7-28. 6dB Bandwidth Plot MIMO ANT2 (802.11b – Ch. 11)




Plot 7-29. 6dB Bandwidth Plot MIMO ANT2 (802.11g – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 32 of 119






Plot 7-30. 6dB Bandwidth Plot MIMO ANT2 (802.11g – Ch. 6)




Plot 7-31. 6dB Bandwidth Plot MIMO ANT2 (802.11g – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 33 of 119




Plot 7-32. 6dB Bandwidth Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-33. 6dB Bandwidth Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 34 of 119




Plot 7-34. 6dB Bandwidth Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-35. 6dB Bandwidth Plot MIMO ANT2 (802.11ax/be (2.4GHz) – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 35 of 119



Plot 7-36. 6dB Bandwidth Plot MIMO ANT2 (802.11ax/be (2.4GHz) – Ch. 6)



Plot 7-37. 6dB Bandwidth Plot MIMO ANT2 (802.11ax/be (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 36 of 119

### 7.3 Output Power Measurement

#### Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

***The maximum permissible conducted output power is 1 Watt per 15.247.***

#### Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3 PKPM1 Peak Power Method

ANSI C63.10-2013 – Section 11.9.2.3.2 Method AVGPM-G

ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique

#### Test Settings

##### Method PKPM1 (Peak Power Measurement)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

##### Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-2. Test Instrument & Measurement Setup for Power Meter Measurements**

#### Test Notes

None.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 37 of 119



2.4GHz WIFI (20MHz 802.11b SISO ANT2)				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]						
2412	1	Average	14.72	30.00	-15.28	-1.82	12.90	36.02	-23.12
2437	6		14.79	30.00	-15.21	-1.82	12.97	36.02	-23.05
2462	11		14.45	30.00	-15.55	-1.82	12.63	36.02	-23.39
2467	12		5.77	30.00	-24.23	-1.82	3.95	36.02	-32.07
2472	13		-5.33	30.00	-35.33	-1.82	-7.15	36.02	-43.17
2412	1	Peak	18.41	30.00	-11.59	-1.82	16.59	36.02	-19.43
2437	6		18.57	30.00	-11.43	-1.82	16.75	36.02	-19.27
2462	11		18.33	30.00	-11.67	-1.82	16.51	36.02	-19.51
2467	12		12.07	30.00	-17.93	-1.82	10.25	36.02	-25.77
2472	13		-1.66	30.00	-31.66	-1.82	-3.48	36.02	-39.50

**Table 7-7. Conducted Output Power Measurements SISO ANT2(802.11b)**

2.4GHz WIFI (20MHz 802.11g SISO ANT2)				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]						
2412	1	Average	14.64	30.00	-15.36	-1.82	12.82	36.02	-23.20
2437	6		14.86	30.00	-15.14	-1.82	13.04	36.02	-22.98
2462	11		14.64	30.00	-15.36	-1.82	12.82	36.02	-23.20
2467	12		5.74	30.00	-24.26	-1.82	3.92	36.02	-32.10
2472	13		-5.32	30.00	-35.32	-1.82	-7.14	36.02	-43.16
2412	1	Peak	19.90	30.00	-10.10	-1.82	18.08	36.02	-17.94
2437	6		20.19	30.00	-9.81	-1.82	18.37	36.02	-17.65
2462	11		20.02	30.00	-9.98	-1.82	18.20	36.02	-17.82
2467	12		12.15	30.00	-17.85	-1.82	10.33	36.02	-25.69
2472	13		-0.70	30.00	-30.70	-1.82	-2.52	36.02	-38.54

**Table 7-8. Conducted Output Power Measurements SISO ANT2(802.11g)**

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 38 of 119



2.4GHz WIFI (20MHz 802.11n SISO ANT2)				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]						
2412	1	Average	14.65	30.00	-15.35	-1.82	12.83	36.02	-23.19
2437	6		14.86	30.00	-15.14	-1.82	13.04	36.02	-22.98
2462	11		14.67	30.00	-15.33	-1.82	12.85	36.02	-23.17
2467	12		5.73	30.00	-24.27	-1.82	3.91	36.02	-32.11
2472	13		-5.66	30.00	-35.66	-1.82	-7.48	36.02	-43.50
2412	1	Peak	19.90	30.00	-10.10	-1.82	18.08	36.02	-17.94
2437	6		20.07	30.00	-9.93	-1.82	18.25	36.02	-17.77
2462	11		19.93	30.00	-10.07	-1.82	18.11	36.02	-17.91
2467	12		12.36	30.00	-17.64	-1.82	10.54	36.02	-25.48
2472	13		6.09	30.00	-23.92	-1.82	4.27	36.02	-31.76

Table 7-9. Conducted Output Power Measurements SISO ANT2(802.11n)

2.4GHz WIFI (20MHz 802.11ax SISO ANT2)				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]						
2412	1	Average	14.22	30.00	-15.78	-1.82	12.40	36.02	-23.62
2437	6		14.37	30.00	-15.63	-1.82	12.55	36.02	-23.47
2462	11		14.26	30.00	-15.74	-1.82	12.44	36.02	-23.58
2467	12		5.81	30.00	-24.19	-1.82	3.99	36.02	-32.03
2472	13		-3.60	30.00	-33.60	-1.82	-5.42	36.02	-41.44
2412	1	Peak	20.20	30.00	-9.80	-1.82	18.38	36.02	-17.64
2437	6		20.43	30.00	-9.57	-1.82	18.61	36.02	-17.41
2462	11		20.26	30.00	-9.74	-1.82	18.44	36.02	-17.58
2467	12		12.97	30.00	-17.03	-1.82	11.15	36.02	-24.87
2472	13		-1.32	30.00	-31.32	-1.82	-3.14	36.02	-39.16

Table 7-10. Conducted Output Power Measurements SISO ANT2(802.11ax)

2.4GHz WIFI (20MHz 802.11be SISO ANT2)				Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq. [MHz]	Channel	Detector	Conducted Power [dBm]						
2412	1	Average	14.25	30.00	-15.75	-1.82	12.43	36.02	-23.59
2437	6		14.46	30.00	-15.54	-1.82	12.64	36.02	-23.38
2462	11		14.32	30.00	-15.68	-1.82	12.50	36.02	-23.52
2467	12		5.97	30.00	-24.03	-1.82	4.15	36.02	-31.87
2472	13		-3.56	30.00	-33.56	-1.82	-5.38	36.02	-41.40
2412	1	Peak	20.24	30.00	-9.76	-1.82	18.42	36.02	-17.60
2437	6		20.50	30.00	-9.50	-1.82	18.68	36.02	-17.34
2462	11		20.31	30.00	-9.69	-1.82	18.49	36.02	-17.53
2467	12		12.89	30.00	-17.11	-1.82	11.07	36.02	-24.95
2472	13		-1.42	30.00	-31.42	-1.82	-3.24	36.02	-39.26

Table 7-11. Conducted Output Power Measurements SISO ANT2(802.11be)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 39 of 119

2.4GHz WIFI (20MHz 802.11b MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq [MHz]	Channel	Detector	Conducted Power [dBm]								
			ANT1	ANT2	MIMO						
2412	1	Average	14.66	14.60	17.64	30.00	-12.36	1.29	18.93	36.02	-17.09
2437	6		14.88	14.86	17.88	30.00	-12.12	1.29	19.17	36.02	-16.85
2462	11		14.45	14.51	17.49	30.00	-12.51	1.29	18.78	36.02	-17.24
2467	12		5.21	5.36	8.30	30.00	-21.70	1.29	9.59	36.02	-26.43
2472	13		-5.38	-5.25	-2.30	30.00	-32.30	1.29	-1.01	36.02	-37.03
2412	1	Peak	17.39	18.22	20.84	30.00	-9.16	1.29	22.13	36.02	-13.89
2437	6		17.65	18.51	21.11	30.00	-8.89	1.29	22.40	36.02	-13.62
2462	11		17.86	18.66	21.29	30.00	-8.71	1.29	22.58	36.02	-13.44
2467	12		8.22	8.16	11.20	30.00	-18.80	1.29	12.49	36.02	-23.53
2472	13		-1.67	-1.54	1.41	30.00	-28.59	1.29	2.70	36.02	-33.32

Table 7-12. Conducted Output Power Measurements MIMO (802.11b)

2.4GHz WIFI (20MHz 802.11g MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq [MHz]	Channel	Detector	Conducted Power [dBm]								
			ANT1	ANT2	MIMO						
2412	1	Average	14.10	14.98	17.57	30.00	-12.43	1.29	18.86	36.02	-17.16
2437	6		13.88	14.66	17.30	30.00	-12.70	1.29	18.59	36.02	-17.43
2462	11		14.09	14.96	17.56	30.00	-12.44	1.29	18.85	36.02	-17.17
2467	12		5.36	5.49	8.44	30.00	-21.56	1.29	9.73	36.02	-26.29
2472	13		-5.30	-5.20	-2.24	30.00	-32.24	1.29	-0.95	36.02	-36.97
2412	1	Peak	19.46	20.21	22.86	30.00	-7.14	1.29	24.15	36.02	-11.87
2437	6		19.20	19.91	22.58	30.00	-7.42	1.29	23.87	36.02	-12.15
2462	11		19.49	20.27	22.91	30.00	-7.09	1.29	24.20	36.02	-11.82
2467	12		9.87	10.31	13.11	30.00	-16.89	1.29	14.40	36.02	-21.62
2472	13		-0.72	-0.40	2.45	30.00	-27.55	1.29	3.74	36.02	-32.28

Table 7-13. Conducted Output Power Measurements MIMO (802.11g)

2.4GHz WIFI (20MHz 802.11n MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq [MHz]	Channel	Detector	Conducted Power [dBm]								
			ANT1	ANT2	MIMO						
2412	1	Average	13.67	14.59	17.16	30.00	-12.84	1.29	18.45	36.02	-17.57
2437	6		13.90	14.76	17.36	30.00	-12.64	1.29	18.65	36.02	-17.37
2462	11		13.74	14.56	17.18	30.00	-12.82	1.29	18.47	36.02	-17.55
2467	12		5.17	5.62	8.41	30.00	-21.59	1.29	9.70	36.02	-26.32
2472	13		-5.70	-5.21	-2.44	30.00	-32.44	1.29	-1.15	36.02	-37.17
2412	1	Peak	18.77	19.74	22.29	30.00	-7.71	1.29	23.58	36.02	-12.44
2437	6		19.05	19.95	22.53	30.00	-7.47	1.29	23.82	36.02	-12.20
2462	11		18.94	19.77	22.39	30.00	-7.61	1.29	23.68	36.02	-12.34
2467	12		9.40	9.78	12.60	30.00	-17.40	1.29	13.90	36.02	-22.12
2472	13		-1.37	-1.09	1.78	30.00	-28.22	1.29	3.07	36.02	-32.95

Table 7-14. Conducted Output Power Measurements MIMO (802.11n)

2.4GHz WIFI (20MHz 802.11ax MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq [MHz]	Channel	Detector	Conducted Power [dBm]								
			ANT1	ANT2	MIMO						
2412	1	Average	13.20	14.09	16.68	30.00	-13.32	1.29	17.97	36.02	-18.05
2437	6		13.51	14.30	16.93	30.00	-13.07	1.29	18.22	36.02	-17.80
2462	11		13.18	14.05	16.65	30.00	-13.35	1.29	17.94	36.02	-18.08
2467	12		5.44	5.45	8.46	30.00	-21.54	1.29	9.75	36.02	-26.27
2472	13		-3.20	-3.20	-0.19	30.00	-30.19	1.29	1.10	36.02	-34.92
2412	1	Peak	19.25	20.16	22.74	30.00	-7.26	1.29	24.03	36.02	-11.99
2437	6		19.45	20.31	22.91	30.00	-7.09	1.29	24.20	36.02	-11.82
2462	11		19.15	20.01	22.61	30.00	-7.39	1.29	23.90	36.02	-12.12
2467	12		10.22	10.28	13.26	30.00	-16.74	1.29	14.55	36.02	-21.47
2472	13		1.28	1.74	4.53	30.00	-25.47	1.29	5.82	36.02	-30.20

Table 7-15. Conducted Output Power Measurements MIMO (802.11ax)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 40 of 119





2.4GHz WiFi (20MHz 802.11be MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Freq [MHz]	Channel	Detector	Conducted Power [dBm]								
			ANT1	ANT2	MIMO						
2412	1	Average	13.23	14.09	16.69	30.00	-13.31	1.29	17.98	36.02	-18.04
2437	6		13.53	14.33	16.96	30.00	-13.04	1.29	18.25	36.02	-17.77
2462	11		13.23	14.14	16.72	30.00	-13.28	1.29	18.01	36.02	-18.01
2467	12		5.44	5.85	8.66	30.00	-21.34	1.29	9.95	36.02	-26.07
2472	13		-3.52	-3.18	-0.34	30.00	-30.34	1.29	0.95	36.02	-35.07
2412	1	Peak	19.25	20.16	22.74	30.00	-7.26	1.29	24.03	36.02	-11.99
2437	6		19.56	20.41	23.02	30.00	-6.98	1.29	24.31	36.02	-11.71
2462	11		19.24	20.17	22.74	30.00	-7.26	1.29	24.03	36.02	-11.99
2467	12		10.25	10.75	13.52	30.00	-16.48	1.29	14.81	36.02	-21.21
2472	13		1.52	1.85	4.70	30.00	-25.30	1.29	5.99	36.02	-30.03

**Table 7-16. Conducted Output Power Measurements MIMO (802.11be)**

**Note:**

Per ANSI C63.10-2013 Section 14.2, the conducted powers at Antenna 1 and Antenna 2 were first measured separately during MIMO transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

**Sample MIMO Calculation:**

At 2412MHz the average conducted output power was measured to be 13.65 dBm for Antenna 1 and 14.54 dBm for Antenna 2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(14.66 \text{ dBm} + 14.60 \text{ dBm}) = (29.24 \text{ mW} + 28.84 \text{ mW}) = 58.08 \text{ mW} = 17.64 \text{ dBm}$$

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 41 of 119

## 7.4 Power Spectral Density

### Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates are investigated and the worst-case configuration results are reported in this section.

***The maximum permissible power spectral density shall not be greater than 8 dBm in any 3 kHz band.***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD

ANSI C63.10-2013 – Section 14.3.1 Measure-and-Sum Technique

### Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 10kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-3. Test Instrument & Measurement Setup**

### Test Notes

None.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 42 of 119



## Power Spectral Density Measurements

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	-2.13	8.00	-10.13	Pass
2437	6	b	1	-1.22	8.00	-9.22	Pass
2462	11	b	1	-2.41	8.00	-10.41	Pass
2412	1	g	6	-9.84	8.00	-17.84	Pass
2437	6	g	6	-7.52	8.00	-15.52	Pass
2462	11	g	6	-9.17	8.00	-17.17	Pass
2412	1	n	6.5/7.2 (MCS0)	-6.12	8.00	-14.12	Pass
2437	6	n	6.5/7.2 (MCS0)	-5.34	8.00	-13.34	Pass
2462	11	n	6.5/7.2 (MCS0)	-7.11	8.00	-15.11	Pass
2412	1	ax/be	6.5/7.2 (MCS0)	-9.34	8.00	-17.34	Pass
2437	6	ax/be	6.5/7.2 (MCS0)	-7.05	8.00	-15.05	Pass
2462	11	ax/be	6.5/7.2 (MCS0)	-8.93	8.00	-16.93	Pass

**Table 7-17. Conducted Power Spectral Density Measurements SISO ANT2**


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 43 of 119

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	ANT 1 Power Spectral Density [dBm]	ANT 2 Power Spectral Density [dBm]	Summed MIMO Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	1.65	3.66	5.78	8.00	-2.22	Pass
2437	6	b	1	2.15	3.65	5.98	8.00	-2.02	Pass
2462	11	b	1	1.30	3.39	5.48	8.00	-2.52	Pass
2412	1	g	6	-6.02	-1.46	-0.16	8.00	-8.16	Pass
2437	6	g	6	-3.98	-1.20	0.64	8.00	-7.36	Pass
2462	11	g	6	-6.00	-3.07	-1.28	8.00	-9.28	Pass
2412	1	n	6.5/7.2 (MCS0)	-5.70	-2.21	-0.61	8.00	-8.61	Pass
2437	6	n	6.5/7.2 (MCS0)	-5.18	-1.44	0.09	8.00	-7.91	Pass
2462	11	n	6.5/7.2 (MCS0)	-5.19	-1.47	0.07	8.00	-7.93	Pass
2412	1	ax/be	6.5/7.2 (MCS0)	-6.09	-3.81	-1.79	8.00	-9.79	Pass
2437	6	ax/be	6.5/7.2 (MCS0)	-5.60	-3.83	-1.62	8.00	-9.62	Pass
2462	11	ax/be	6.5/7.2 (MCS0)	-6.52	-4.52	-2.39	8.00	-10.39	Pass


**Table 7-18. Conducted Power Spectral Density Measurements MIMO**

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 44 of 119

### 7.4.1 SISO Antenna-2 Power Spectral Density Measurements




Plot 7-38. Power Spectral Density Plot SISO ANT2 (802.11b – Ch. 1)




Plot 7-39. Power Spectral Density Plot SISO ANT2 (802.11b – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 45 of 119





Plot 7-42. Power Spectral Density Plot SISO ANT2 (802.11g – Ch. 6)




Plot 7-43. Power Spectral Density Plot SISO ANT2 (802.11g – Ch. 11)


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 47 of 119








Plot 7-46. Power Spectral Density Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-47. Power Spectral Density Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 49 of 119



Plot 7-48. Power Spectral Density Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 6)




Plot 7-49. Power Spectral Density Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 11)


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 50 of 119








Plot 7-54. Power Spectral Density Plot MIMO ANT1 (802.11g – Ch. 6)




Plot 7-55. Power Spectral Density Plot MIMO ANT1 (802.11g – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 53 of 119




Plot 7-56. Power Spectral Density Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 1)




Plot 7-57. Power Spectral Density Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 54 of 119




Plot 7-58. Power Spectral Density Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 11)




Plot 7-59. Power Spectral Density Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 55 of 119






Plot 7-60. Power Spectral Density Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 6)




Plot 7-61. Power Spectral Density Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 56 of 119






Plot 7-62. Power Spectral Density Plot MIMO ANT2 (802.11b – Ch. 1)




Plot 7-63. Power Spectral Density Plot MIMO ANT2 (802.11b – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 57 of 119




Plot 7-64. Power Spectral Density Plot MIMO ANT2 (802.11b – Ch. 11)




Plot 7-65. Power Spectral Density Plot MIMO ANT2 (802.11g – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 58 of 119




Plot 7-66. Power Spectral Density Plot MIMO ANT2 (802.11g – Ch. 6)




Plot 7-67. Power Spectral Density Plot MIMO ANT2 (802.11g – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1-A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 59 of 119




Plot 7-68. Power Spectral Density Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-69. Power Spectral Density Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 60 of 119




Plot 7-70. Power Spectral Density Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-71. Power Spectral Density Plot MIMO ANT2 (802.11ax/be (2.4GHz) – Ch. 1)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 61 of 119



Plot 7-72. Power Spectral Density Plot MIMO ANT2 (802.11ax/be (2.4GHz) – Ch. 6)



Plot 7-73. Power Spectral Density Plot MIMO ANT2 (802.11ax/be (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 62 of 119



**Note:**

Per ANSI C63.10-2013 Section 14.3.1, the power spectral density at Antenna 1 and Antenna 2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

**Sample MIMO Calculation:**

At 2412MHz the average conducted power spectral density was measured to be 1.65 dBm for Antenna 1 and 3.66 dBm for Antenna 2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(1.65 \text{ dBm} + 3.66 \text{ dBm}) = (1.46 \text{ mW} + 2.32 \text{ mW}) = 3.79 \text{ mW} = 5.78 \text{ dBm}$$

<b>FCC ID:</b> A3LNP960XMA	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401250007-03-R1.A3L	<b>Test Dates:</b> 03/18/2024-05/01/2024	<b>EUT Type:</b> Portable Computing Device	Page 63 of 119

## 7.5 Conducted Band Edge Emissions

### Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate of 1Mbps for “b” mode, 6 Mbps for “g” mode, 6.5\7.2Mbps for “n” mode, and 8.6Mbps for “ax” mode as these settings produced the worst-case emissions.

***The limit for out-of-band spurious emissions at the band edge is 20 dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 7.4).***

### Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 1MHz
5. Detector = Peak
6. Number of sweep points  $\geq 2 \times \text{Span} \backslash \text{RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Test Instrument & Measurement Setup**


### Test Notes

None.


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 64 of 119



### 7.5.1 SISO Antenna-2 Conducted Band Edge Emissions




Plot 7-74. Band Edge Plot SISO ANT2 (802.11b – Ch. 1)




Plot 7-75. Band Edge Plot SISO ANT2 (802.11b – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 65 of 119




Plot 7-76. Band Edge Plot SISO ANT2 (802.11b – Ch. 12)




Plot 7-77. Band Edge Plot SISO ANT2 (802.11b – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 66 of 119




Plot 7-78. Band Edge Plot SISO ANT2 (802.11g- Ch. 1)




Plot 7-79. Band Edge Plot SISO ANT2 (802.11g - Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 67 of 119




Plot 7-80. Band Edge Plot SISO ANT2 (802.11g – Ch. 12)




Plot 7-81. Band Edge Plot SISO ANT2 (802.11g – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 68 of 119




Plot 7-82. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-83. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 69 of 119




Plot 7-84. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 12)




Plot 7-85. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 70 of 119




Plot 7-86. Band Edge Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 1)




Plot 7-87. Band Edge Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 71 of 119



Plot 7-88. Band Edge Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 12)




Plot 7-89. Band Edge Plot SISO ANT2 (802.11ax/be (2.4GHz) – Ch. 13)


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 72 of 119



## 7.5.2 MIMO Conducted Band Edge Emissions




Plot 7-90. Band Edge Plot MIMO ANT1 (802.11b – Ch. 1)




Plot 7-91. Band Edge Plot MIMO ANT1 (802.11b – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 73 of 119




Plot 7-92. Band Edge Plot MIMO ANT1 (802.11b – Ch. 12)




Plot 7-93. Band Edge Plot MIMO ANT1 (802.11b – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1-A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 74 of 119




Plot 7-94. Band Edge Plot MIMO ANT1 (802.11g- Ch. 1)




Plot 7-95. Band Edge Plot MIMO ANT1 (802.11g - Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 75 of 119




Plot 7-96. Band Edge Plot MIMO ANT1 (802.11g – Ch. 12)




Plot 7-97. Band Edge Plot MIMO ANT1 (802.11g – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1-A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 76 of 119




Plot 7-98. Band Edge Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 1)




Plot 7-99. Band Edge Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 77 of 119




Plot 7-100. Band Edge Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 12)




Plot 7-101. Band Edge Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1-A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 78 of 119




Plot 7-102. Band Edge Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 1)




Plot 7-103. Band Edge Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 79 of 119






Plot 7-104. Band Edge Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 12)




Plot 7-105. Band Edge Plot MIMO ANT1 (802.11ax/be (2.4GHz) – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1-A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 80 of 119






Plot 7-106. Band Edge Plot MIMO ANT2 (802.11b – Ch. 1)




Plot 7-107. Band Edge Plot MIMO ANT2 (802.11b – Ch. 11)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1.A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 81 of 119



Plot 7-108. Band Edge Plot MIMO ANT2 (802.11b – Ch. 12)



Plot 7-109. Band Edge Plot MIMO ANT2 (802.11b – Ch. 13)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-03-R1-A3L	Test Dates: 03/18/2024-05/01/2024	EUT Type: Portable Computing Device	Page 82 of 119