

1.2 Detail Information related product

1.2.1 Specification

Item	Specification	Remark
CPU	Intel Yonah ULV Processor single-core 1.2GHz	-
Chipset	Intel 945GMS+ ICH7M	-
Main Memory	On B'D 256MB (SAMSUNG)	-
Graphic controller	Internal GMA 950 Graphic	-
Inverter Board	Delta, DAC-09N016 REV:AF	-
LCD DISPLAY	Toshiba; LTD121EX1R , 12.1" WXGA (1280 x 768, 16:9)	-
Modem	Agere systems, Athens(AM2) S/W Modem, 56KBPS, Fax/Data Azalia MDC 1456VQL-T1(INT-LF), MIC No.:TE-A22/K012-04-0410	-
HDD	Hitachi, HTC426060G8CE00, 60G, 1.8"	-
ODD	None	-
LAN	BROADCOM, BCM5751MKFBG , Gigabit Ethernet	-
Wireless LAN	Intel, WM3945ABG KR, 802.11abg, 54Mbps, Mini-card MIC No.:INT-WM3945ABGKR FCC ID : PD9WM3945ABG	-
Bluetooth	Broadcom, BCM92045NMD, USB 2.0 type, Bluetooth Ver 2.0 MIC No.:R-LARN-05-0240, FCC ID:QDS-BRCM1018	-
DMB	MBridge, SDM-2000, Korea only	-
ADAPTER	Lishin, 0455A1990, AD-9019S, 90W, 3 pin	-
Battery	SANYO[6Cell]; Q30LS6	-
Input Devices	Keyboard, 18.05mm pitch, 2.6mmH travel length PS/2 Touchpad	-
Ports	LAN & Modem Combo, 1 1394, 2 USB, 1 VGA, DC IN, 1 MIC-IN, CF Card Socket, 4 in 1 socket, Docking	-
X-dock	SEC, X-DOCK(AA- RD2NX25), 1 PS/2, 4 USB, 1 LAN, 1 1394, 1 TV- OUT, 1 DVI, 1 VGA, DC-IN, 1 Parallel, 1 Serial, 1 MIC- IN, 1 SPDIF/1HP-OUT	-

Operating Frequency

1.2GHz(CPU Speed), 667MHz(Host Clock), 533MHz(DDR2),
33MHz(PCI Clock), 96MHz (PCIE Clock), 14.318MHz(Ref), 33MHz(MICOM Clock),
33Mhz(Cardbus controller), 25Mhz(LAN controller)