

1.2 Detail Information related product

1.2.1 Specification

Item	Specification	Remark
CPU	Intel® Core™2 CPU, T5600@1.83GHz Cache 2MB, FSB 667MHz	-
Chipset	Intel Calistoga 945PM + ICH7M	-
Main Memory	Samsung, PC2-4200S, M470T6554CZ3, 512MB	-
Graphic controller	Intel, Internal Gfx, Calistoga 945GM Express Chipset	-
LCD DISPLAY	CPT, CLAA141WB05A, 14.1" WXGA, GLARE, 1280*800	-
Inverter Board	Dafon, VK.21209.201	-
Modem	Agere systems, Athens(AM2) S/W Modem, 56KBPS, Fax/Data A zalia MDC MIC No.:TE-A22/K012-04-0410	-
HDD	Hitachi, HTS541040G9SA00, 40GB, 5.4k, SATA	-
ODD	TEAC, DV-W28EA	-
LAN	BROADCOM, BCM5751EKFBG , 10/100 Ethernet	-
Wireless LAN	Intel, WM3945ABG KR, 802.11abg, 54Mbps, Mini-card MIC No.:INT-WM3945ABGKR FCC ID : PD9WM3945ABG	-
Bluetooth	Broadcom, BCM92045NMD, USB 2.0 type, Bluetooth Ver 2.0 Foxconn Module, MIC No.:R-LARN-05-0240 FCC ID : QDS-BRCM1018	-
DMB	SDM-1000, Personal Telecom, INC	-
ADAPTER	Li Shin, CNBA4400215AD, AD-9019S, 90W, 3 pin	-
Battery	Sanyo[4Cell]	-
Input Devices	Keyboard, 19.05mm pitch, 2.6mmH travel length PS/2 Touchpad	-
Ports	LAN & Modem Combo, 1 1394, 3 USB, 1 VGA, DC IN, 1 MIC-IN, 1HP-OUT, S- VHS, Serial port, PCMCIA socket, Express card socket, 6 in 1 so cket	-
X-dock	SEC, X-DOCK(AA- RD2NX25), 1 PS/2, 4 USB, 1 LAN, 1 1394, 1 TV- OUT, 1 DVI, 1 VGA, DC-IN, 1 Parallel, 1 Serial, 1 MIC- IN, 1 SPDIF/1HP-OUT	-

Operating Frequency

1.83GHz(CPU Speed), 166MHz(Host Clock), 667MHz(DDR2), 12.288MHz(AC97 DOT clock)
33MHz(PCI Clock), 100MHz (PCIE Clock), 14.318MHz(Ref), 10MHz(MICOM Clock),
24.576MHz(Cardbus controller), 25MHz(LAN controller), 48MHz(USB controller), 32.768KHz(RTC)