

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification	Remarks
Processor	CHORUS3 (ARM926EJS, 16/32 Bit Risc Architecture)	-
Standard System memory	64Mbyte DDR SDRAM	-
Resolution	1200 x 1200dpi	-
Copy Quality mode	Text :300 x 300 dpi Mixed :300 x 300 dpi Photo :600 x 600 dpi	-
Paper Handling	Paper Tray(standard) 100 Sheets 2nd Tray(optional) : NA Bypass Tray : NA	-
Power Rating	110~127 VAC, 4.0A, 50/60 Hz	-
Power Consumption	Power save mode : 8.12Watts Printing simplex : 350Watts	-
Printer Language	SPL	-
Interfaces	Hi-Speed USB2.0 Ethernet 10/100 Base TX IEEE802.11 b/g Wireless LAN	-
OS compatibility	Windows 2000(32bit)/XP(32/64bit)/2003(32/64bit)/Vista(32/64bit) MAC 10.3/10.5, Linux Red Hat 8~9, Fedora Core 1~3, Mandrake 9.2~10.1, and SuSE 8.2~9.2	-
Modes of Operation	USB Printing, copy Network Printing, wireless network printing	-
Intended Class for Emissions	Class B	-