

3.5 EUT Description

| Item | Specification | Remarks |
|-------------------------------------|---|---------|
| Processor | CHORUS3(360MHz) | - |
| Standard System memory | 128MB DDR2 SDRAM (Option 256MB → MAX. 384MB) | - |
| Resolution | True 600x600dpi (Addressible 1200dpi support) | - |
| Copy Quality mode | Text : 600x300dpi(ADF) Mixed : 600x300dpi(ADF) Photo : 600x300dpi(ADF) ,600x600dpi (Platen) | - |
| Paper Handling | Paper Tray(standard) 250 Sheets 2nd Tray(optional) 250 Sheets Bypass Tray 50 Sheets | - |
| Power Rating | 110~127 VAC, 7A, 50/60 Hz | - |
| Power Consumption | Power save mode : 1 Watts Printing mode: MAX. 600 Watts | - |
| Printer Language | GDI, PCL6, PCL5e PostScript Level3(Clone) | - |
| PC Interfaces | USB2.0, NW, FAX, WirelessLAN(option) | - |
| OS compatibility | MS Windows 98/2000/XP/NT/Me,MAC (English only, no status monitor, web download only) Linux: Red Hat 8.0~9.0, Fedora Core 1~3, Mandrake 9.0~10.2, SuSE 8.2~9.2. Windows 2003. Netware 4.x | - |
| Modes of Operation | USB Printing, ADF Scan, ADF Copy, 1200dpi Printing, Fax RX, Fax TX, Network Printing, Duplex Printing, Scan To USB | - |
| Intended Class for Emissions | Class B | - |