



**Technical Description**

1. Use FILM provided by SAMSUNG for letter and contents
2. Background color is **White**, letter color is **BLACK** (reverse for SAMSUNG LOGO)
3. Put Back paper on the back side after the adhesive.
4. No blur and spread for letter
5. Proceed with manufacturing process after the approval of R&D Group
6. The spec. of product must be based on approved limit samples.
7. Stock on as a ROLL
8. Follow drawing instruction above for CE or WEEE mark
9. Unify material and color as one color (blue) for glassine paper

ROLLING

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L

1 2 3 4 5 6 7 8

Rev. No

MAT. White Polypropylene 80 $\mu$		FIN. translucent opp laminating+uvp coating			
TITLE	SGH-T105G(US)		LABEL(R)-MAIN		
UNIT	mm	DESIGNED	CHECKED	APPROVED	PROJECTION
TOLERANCE	+0.0 -0.1	KIM TAE HIN	X	KIM JUNE SOP	
SCALE	N/S				
Manufacture	HSINS	090511		090511	SHEET NO 1/1
		Doc. CODE			





The label is placed  
inside the battery compartment

Note: The FCC ID label shown will be readily visible at the time of purchase.