

# FCC MPE REPORT

## FCC Certification

**Applicant Name:**  
SAMSUNG Electronics Co., Ltd.

**Address:**  
129, Samsung-ro, Yeongtong-gu, Suwon-si,  
Gyeonggi-do, 16677, Rep. of Korea

**Date of Issue:**  
November 21, 2017

**Test Site/Location:**  
HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-  
myeo, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA  
**Report No.:** HCT-R-1711-E005-1

**FCC ID** : A3LSLS-BU10G

**APPLICANT** : SAMSUNG Electronics Co.,Ltd.

**Model:** SLS-BU10G

**EUT Type:** 4G LTE Network Extender 2 for Enterprise

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)



**Report prepared by : Kyung Soo Kang**  
**Engineer of Telecommunication testing center**



**Approved by : Jong Seok Lee**  
**Manager of Telecommunication testing center**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1711-E005	November 16, 2017	- First Approval Report
HCT-R-1711-E005-1	November 21, 2017	- Revised the LAA data.

# Result of Test

## CONTENTS

RF Exposure Statement .....	4
1. LIMITS .....	4
2. MAXIMUM PERMISSIBLE EXPOSURE Prediction.....	4
3. RESULTS .....	5

# RF Exposure Statement

## 1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

\* = Plane-wave equivalent power density

## 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 3. RESULTS

#### LTE – 1 TX

##### 3-1. LTE Band (13)

Average Peak output Power at antenna input terminal	26.000	dBm
Average Peak output Power at antenna input terminal	398.107	mW
Prediction distance	30.000	cm
Prediction frequency	746 ~ 756	MHz
Antenna Gain(typical)	2.000	dBi
Antenna Gain(numeric)	1.585	-
Power density at prediction frequency( S)	0.0558	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

##### 3-2. LTE Band (66)

Average Peak output Power at antenna input terminal	26.000	dBm
Average Peak output Power at antenna input terminal	398.107	mW
Prediction distance	30.000	cm
Prediction frequency	2110 ~ 2180	MHz
Antenna Gain(typical)	4.000	dBi
Antenna Gain(numeric)	2.512	-
Power density at prediction frequency( S)	0.0884	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**LTE – 2 TX****3-3. LTE Band (13)**

Average Peak output Power at antenna input terminal	29.000	dBm
Average Peak output Power at antenna input terminal	794.328	mW
Prediction distance	30.000	cm
Prediction frequency	746 ~ 756	MHz
Antenna Gain(typical)	2.000	dBi
Antenna Gain(numeric)	1.585	-
Power density at prediction frequency( S)	0.1113	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**3-4. LTE Band (66)**

Average Peak output Power at antenna input terminal	29.000	dBm
Average Peak output Power at antenna input terminal	794.328	mW
Prediction distance	30.000	cm
Prediction frequency	2110 ~ 2180	MHz
Antenna Gain(typical)	4.000	dBi
Antenna Gain(numeric)	2.512	-
Power density at prediction frequency( S)	0.1764	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**WiFi (UNII 1 BAND)**

3-5 802.11a (5180 ~5240)

Average Peak output Power at antenna input terminal	26.500	dBm
Average Peak output Power at antenna input terminal	446.684	mW
Prediction distance	30.000	cm
Prediction frequency	5180 ~ 5240	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.1572	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**(UNII 3 BAND)**

3-6 802.11a (5745 ~5825)

Average Peak output Power at antenna input terminal	26.500	dBm
Average Peak output Power at antenna input terminal	446.684	mW
Prediction distance	30.000	cm
Prediction frequency	5745 ~ 5825	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.1572	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**LTE-LAA 1 Carrier 1 TX**3-7 UNII 1 - (5160 ~ 5240)

Average Peak output Power at antenna input terminal	26.500	dBm
Average Peak output Power at antenna input terminal	446.684	mW
Prediction distance	30.000	cm
Prediction frequency	5160 ~5240	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.1572	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

3-8 UNII 3 - 5745 ~ 5825)

Average Peak output Power at antenna input terminal	26.500	dBm
Average Peak output Power at antenna input terminal	446.684	mW
Prediction distance	30.000	cm
Prediction frequency	5745 ~ 5825	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.1572	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**LTE-LAA 1 Carrier 2 TX****3-9 UNII 1 - (5160 ~ 5240)**

Average Peak output Power at antenna input terminal	29.500	dBm
Average Peak output Power at antenna input terminal	891.251	mW
Prediction distance	30.000	cm
Prediction frequency	5160 ~ 5240	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.3137	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**3-10 UNII 3 - 5745 ~ 5825)**

Average Peak output Power at antenna input terminal	29.500	dBm
Average Peak output Power at antenna input terminal	891.251	mW
Prediction distance	30.000	cm
Prediction frequency	5745 ~ 5825	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.3137	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**LTE-LAA 2 Carrier 1 TX****3-11 UNII 1 - (5170 ~ 5230)**

Average Peak output Power at antenna input terminal	27.000	dBm
Average Peak output Power at antenna input terminal	501.187	mW
Prediction distance	30.000	cm
Prediction frequency	5170 ~ 5230	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.1764	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**3-12 UNII 3 - 5755 ~ 5815)**

Average Peak output Power at antenna input terminal	27.000	dBm
Average Peak output Power at antenna input terminal	501.187	mW
Prediction distance	30.000	cm
Prediction frequency	5755 ~ 5815	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.1764	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**LTE-LAA 2 Carrier 2 TX****3-13 UNII 1 - (5170 ~ 5230)**

Average Peak output Power at antenna input terminal	30.000	dBm
Average Peak output Power at antenna input terminal	1000.000	mW
Prediction distance	30.000	cm
Prediction frequency	5170 ~ 5230	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.3520	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

**3-14 UNII 3 - 5755 ~ 5815)**

Average Peak output Power at antenna input terminal	30.000	dBm
Average Peak output Power at antenna input terminal	1000.000	mW
Prediction distance	30.000	cm
Prediction frequency	5755 ~ 5815	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency( S)	0.3520	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm <sup>2</sup>

## Simultaneous transmission operations

1. Simultaneous MPE 30 cm is  $(0.1764/1.0) + (0.3520/1.0) = 0.5284 < 1$

\*The Worst case LTE(2 TX) : 29.0 dBm, LTE-LAA (2 Carrier TX) : 30.0 dBm is Highest Power.

2. Simultaneous MPE 30 cm is  $(0.1764/1.0) + (0.1572/1.0) = 0.3336 < 1$

\* The Worst case LTE(2 TX) : 29.0 dBm, WiFi : 26.5 dBm is Highest Power.

\* Unlicensed band (LTE-LAA) and WiFi(Active Probing) is not transmitted simultaneously.