



TEST REPORT

<p>KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr</p>	<p>Report No.: KR19-SRF0043-C Page (1) of (20)</p>	
--	--	---

1. Client

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2019-04-01

2. Use of Report : -

3. Name of Product and Model : Mobile Phone / SM-A105FN/DS

4. Manufacturer and Country of Origin : Samsung Electronics Co., Ltd. / Korea

5. FCC ID : A3LSMA105FN

6. Date of Test : 2019-04-04 to 2019-04-17

7. Test Standards : FCC Part 15 Subpart C, 15.225

8. Test Results : Refer to the test result in the test report

Affirmation	Tested by	Technical Manager
	Name : Euijung Kim (Signature) 	Name : Bongok Ko (Signature) 

2019-04-24

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (2) of (20)

**Report revision history**

Date	Revision	Page No
2019-04-19	Initial report	-
2019-04-22	Updated	6, 13~15
2019-04-23	Updated notes	6
2019-04-24	Updated	10~11, 13~16

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.

This test report is a general report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.



CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Accessory information	5
2.2.	Information about derivative model.....	5
2.3.	Frequency/channel operations.....	5
3.	Antenna requirement	6
4.	Summary of tests	6
5.	Measurement uncertainty	7
6.	Test results	8
6.1.	20 dB Bandwidth.....	8
6.2.	Frequency tolerance	10
6.3.	Radiated spurious emissions	12
6.4.	AC Conducted emission	18
7.	Measurement equipment	20

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (4) of (20)



1. General information

Client : Samsung Electronics Co., Ltd.
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,
Rep. of Korea
Manufacturer : Samsung Electronics Co., Ltd.
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,
Rep. of Korea
Laboratory : KCTL Inc.
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
VCCI Registration No. : R-3327, G-198, C-3706, T-1849
Industry Canada Registration No. : 8035A-2
KOLAS No.: KT231

2. Device information

Equipment under test : Mobile Phone
Model : SM-A105FN/DS
Derivative model : SM-A105FN
Frequency range : Bluetooth(BDR/EDR/BLE)_2 402 MHz ~ 2 480 MHz
WIFI(802.11b/g/n20)_2 412 MHz ~ 2 472 MHz
NFC_13.56 MHz
LTE Band5_824.7 MHz ~ 848.3 MHz
LTE Band2_1 850.7 MHz ~ 1 909.3 MHz
LTE Band41_2 498.5 MHz ~ 2 687.5 MHz
GSM850_824.2 MHz ~ 848.8 MHz
GSM1900_1 850.2 MHz ~ 1 909.8 MHz
WCDMA850_826.4 MHz ~ 846.6 MHz
WCDMA1900_1 852.4 MHz ~ 1 907.6 MHz
Modulation technique : Bluetooth(BDR/EDR)_ GFSK, $\pi/4$ DQPSK, 8DPSK
Bluetooth(BLE)_GFSK
WIFI(802.11b/g/n20)_DSSS, OFDM
NFC_ASK
LTE_QPSK, 16QAM
GSM_GMSK, 8-PSK
WCDMA_QPSK
Number of channels : Bluetooth(BDR/EDR)_79 ch
Bluetooth(BLE)_40 ch
WIFI(802.11b/g/n20)_13 ch
NFC_1 ch

Power source : DC 3.85 V

Antenna specification : LTE/GSM/WCDMA/WIFI/Bluetooth(BDR/EDR/BLE)_LDS Antenna
NFC_FPCB Antenna

Software version : A105FN.001

Hardware version : REV1.0

Test device serial No. : Radiated(R38M30F7VSH, R38M30F7PQT, R38M30F7A3B,
R38M30F7KVZ)
Conducted(R38M30F7M7F, R38M30F7JEJ, R38M30F8D0W)

Operation temperature : -30 °C ~ 50 °C

2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
Earphone	Samsung Electronics Co., Ltd.	EHS61ASFWE	-	-
Travel Adapter	Samsung Electronics Co., Ltd.	ETA0U843EWE	-	AC 100-240V 50-60 Hz, 0.15A
Micro USB Data Cable	Samsung Electronics Co., Ltd.	ECB-DU68WE	-	-

2.2. Information about derivative model

The difference between basic and derivative model are:

For SM-A105FN, it does not support Dual-SIM card, support Single-SIM card and changed from Dual SIM tray to Single SIM tray.

2.3. Frequency/channel operations

This device contains the following capabilities:
 Bluetooth(BDR/EDR/BLE), WIFI(802.11b/g/n20), NFC
 LTE Band 5, LTE Band 2, LTE Band 41
 GSM850, GSM1900, WCDMA850, WCDMA 1900

Ch.	Frequency (MHz)
01	13.56

Table 2.3.1. NFC

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (6) of (20)



3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached FPCB Antenna (internal antenna) on board.

4. Summary of tests

FCC Part section(s)	Parameter	Test results
15.225(a)	In-band Fundamental Emission	Pass
15.225(b)	In-band Spurious Emission	Pass
15.225(c)	In-band Spurious Emission	Pass
15.225(a)	Out-of-band Spurious Emission	Pass
15.209	Frequency Stability Tolerance	Pass
15.215(c)	20 dB Bandwidth	Pass
15.207(a)	Conducted emissions	Pass

Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. These tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
3. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that Z orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in Z orientation
4. The test procedure(s) in this report were performed in accordance as following.
 - ◆ ANSI C63.10-2013

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.


Parameter	Expanded uncertainty	
Radiated spurious emissions	9 kHz ~ 30 MHz	2.28 dB
	30 MHz ~ 300 MHz	4.98 dB
	300 MHz ~ 1 000 MHz	5.14 dB
	1 GHz ~ 6 GHz	6.70 dB
	Above 6 GHz	6.60 dB
Conducted emissions	9 kHz ~ 150 kHz	3.66 dB
	150 kHz ~ 30 MHz	3.26 dB



6. Test results

6.1. 20 dB Bandwidth

Test setup



Limit

According to §15.215(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test procedure

ANSI C63.10-2013 - Section 6.9.2

Test settings

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.



- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
Span: Two times and five times the OBW.
- b) RBW = 1 % to 5 % of the OBW and VBW \geq 3 x RBW
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation.
- d) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- e) Detector: peak
- f) Trace mode: max hold.
- g) Allow the trace to stabilize.
- h) Determine the “-xx dB down amplitude” using ((reference value) - xx). Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of

the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

Test results


Frequency [MHz]	20 dB Bandwidth [MHz]		Limit [MHz]	Occupied Bandwidth (99 % BW) [kHz]
	Lowest Frequency	Highest Frequency	Limit	
13.56	Lowest Frequency	13.559 997	13.110	0.211
	Highest Frequency	13.559 866	14.010	

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.



6.2. Frequency tolerance

Test setup



Limit

15.225 (e) The frequency tolerance of the carrier signal shall be maintained within ± 0.01 % of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test procedure

ANSI C63.10-2013 - Section 6.8.1

KCTL

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (11) of (20)

**Test results**

Voltage	Voltage	TEMP	Maintaining time	Measure frequency	Frequency deviation	Deviation
[%]	[V]	[°C]		[Hz]	[Hz]	[%]
100	3.85	20	Startup	13 559 997	-3.00	-0.000 02
			2 minutes	13 559 997	-3.00	-0.000 02
			5 minutes	13 559 997	-3.00	-0.000 02
			10 minutes	13 559 997	-3.00	-0.000 02
		-20	Startup	13 560 001	1.00	0.000 01
			2 minutes	13 560 001	1.00	0.000 01
			5 minutes	13 560 002	2.00	0.000 01
			10 minutes	13 560 002	2.00	0.000 01
		-10	Startup	13 560 001	1.00	0.000 01
			2 minutes	13 560 001	1.00	0.000 01
			5 minutes	13 560 001	1.00	0.000 01
			10 minutes	13 560 001	1.00	0.000 01
		0	Startup	13 559 999	-1.00	-0.000 01
			2 minutes	13 559 999	-1.00	-0.000 01
			5 minutes	13 559 999	-1.00	-0.000 01
			10 minutes	13 559 999	-1.00	-0.000 01
		10	Startup	13 559 999	-1.00	-0.000 01
			2 minutes	13 559 999	-1.00	-0.000 01
			5 minutes	13 559 998	-2.00	-0.000 01
			10 minutes	13 559 998	-2.00	-0.000 01
		25	Startup	13 559 998	-2.00	-0.000 01
			2 minutes	13 559 998	-2.00	-0.000 01
			5 minutes	13 559 997	-3.00	-0.000 02
			10 minutes	13 559 997	-3.00	-0.000 02
		30	Startup	13 559 997	-3.00	-0.000 02
			2 minutes	13 559 997	-3.00	-0.000 02
			5 minutes	13 559 997	-3.00	-0.000 02
			10 minutes	13 559 997	-3.00	-0.000 02
		40	Startup	13 559 996	-4.00	-0.000 03
			2 minutes	13 559 996	-4.00	-0.000 03
			5 minutes	13 559 996	-4.00	-0.000 03
			10 minutes	13 559 996	-4.00	-0.000 03
50	Startup	13 559 998	-2.00	-0.000 01		
	2 minutes	13 559 998	-2.00	-0.000 01		
	5 minutes	13 559 997	-3.00	-0.000 02		
	10 minutes	13 559 998	-2.00	-0.000 01		
85	3.27	20	Startup	13 559 997	-3.00	-0.000 02
			2 minutes	13 559 997	-3.00	-0.000 02
			5 minutes	13 559 997	-3.00	-0.000 02
			10 minutes	13 559 997	-3.00	-0.000 02
115	4.43	20	Startup	13 559 997	-3.00	-0.000 02
			2 minutes	13 559 997	-3.00	-0.000 02
			5 minutes	13 559 997	-3.00	-0.000 02
			10 minutes	13 559 997	-3.00	-0.000 02


This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2


6.3. Radiated spurious emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



Limit

15.225 (a) The field strength of any emission within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

15.225 (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

15.225 (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz, the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

15.225 (d) The Field Strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in 15.209.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (13) of (20)



Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30(29.54 dB $\mu\text{V}/\text{m}$)	30
30.0-88.0	100(40 dB $\mu\text{V}/\text{m}$)	3
88-216	150(43.5 dB $\mu\text{V}/\text{m}$)	3
216-960	200 (46 dB $\mu\text{V}/\text{m}$)	3
Above 960	500 (53.98 dB $\mu\text{V}/\text{m}$)	3

Test procedure

ANSI C63.10-2013 - Section 6.4, 6.5

Test settings

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW $\geq 3 \times$ RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Table. RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

Notes:

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$
 Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in § 15.31(f)(2). Extrapolation Factor = $20 \log_{10}(30/3)^2 = 40$ dB.
3. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d (dB)
4. Result = Reading + Cable loss + Amp gain + Ant. factor - Distance factor
5. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
6. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector.

This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (14) of (20)



Test results for fundamental

15.225 (a) 13.553-13.567 MHz


Face on

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data									
13.56	H	64.30	2.83	-32.67	18.64	40.00	13.10	84.00	70.90

Face off

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data									
13.56	V	53.10	2.83	-32.67	18.64	40.00	1.90	84.00	82.10

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (15) of (20)



Test results for in-band & out-band (9 kHz to 30 MHz)

15.225 (b,c) 13.110-14.010 MHz


Face on

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
Quasi peak data									
13.22	H	34.20	2.73	-32.67	18.64	40.00	-17.10	40.50	57.60
13.55	H	51.30	2.83	-32.67	18.64	40.00	0.10	50.50	50.40
13.57	H	55.90	2.83	-32.67	18.64	40.00	4.70	50.50	45.80
13.92	H	34.30	2.83	-32.67	18.64	40.00	-16.90	40.50	57.40

Face off

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
Quasi peak data									
13.35	V	34.10	2.73	-32.67	18.64	40.00	-17.20	40.50	57.70
13.55	V	41.20	2.83	-32.67	18.64	40.00	-10.00	50.50	60.50
13.57	V	47.50	2.83	-32.67	18.64	40.00	-3.70	50.50	54.20
13.86	V	34.00	2.83	-32.67	18.64	40.00	-17.20	40.50	57.70

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (16) of (20)



Test results (9 kHz to 30 MHz)

15.225 (d) 0.009-30 MHz


Face on

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data									
7.63	H	34.90	2.36	-32.68	19.02	40.00	-16.40	29.54	45.94
25.40	H	32.40	4.44	-32.68	18.24	40.00	-17.60	29.54	47.14

Face off

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data									
2.54	V	35.50	1.31	-32.71	19.60	40.00	-16.30	29.54	45.84
26.71	V	32.90	4.23	-32.68	18.35	40.00	-17.20	29.54	46.74

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (17) of (20)




Test results (Below 1 000 MHz)

15.225 (d) 30-1000 MHz


Frequency	Pol.	Reading	Cable Loss	Amp Gain	Antenna Factor	Distance Factor	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data									
31.33	V	27.60	1.11	-27.16	12.35	-	13.90	40.00	26.10
99.96	V	30.60	2.14	-25.74	8.60	-	15.60	43.50	27.90
140.10	V	20.50	2.57	-25.97	12.70	-	9.80	43.50	33.70
201.33	V	20.30	3.13	-26.38	9.95	-	7.00	43.50	36.50
887.48	H	18.20	6.96	-25.83	23.47	-	22.80	46.00	23.20
974.17	H	17.60	7.38	-25.00	24.12	-	24.10	54.00	29.90

Horizontal/Vertical



6.4. AC Conducted emission

Test setup



Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Korea
 TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
 KR19-SRF0043-C

Page (19) of (20)



Test results



Final Result

--- N_A Phase ---										
No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.1683	29.4	12.4	10.0	39.4	22.4	65.0	55.0	25.6	32.6
2	0.24404	22.3	8.0	9.7	32.0	17.7	62.0	52.0	30.0	34.3

--- L1_A Phase ---										
No.	Frequency	Reading QP	Reading CAV	c. f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.27575	21.3	14.1	9.7	31.0	23.8	60.9	50.9	29.9	27.1
2	0.80466	34.2	22.4	9.9	44.1	32.3	56.0	46.0	11.9	13.7
3	1.073	34.9	25.2	9.8	44.7	35.0	56.0	46.0	11.3	11.0
4	1.87763	37.8	28.3	9.8	47.6	38.1	56.0	46.0	8.4	7.9
5	2.88689	34.1	25.8	9.9	44.0	35.7	56.0	46.0	12.0	10.3
6	3.74962	29.9	18.0	9.9	39.8	27.9	56.0	46.0	16.2	18.1
7	8.60104	41.2	28.3	10.2	51.4	38.5	60.0	50.0	8.6	11.5
8	9.23752	41.2	28.9	10.3	51.5	39.2	60.0	50.0	8.5	10.8
9	10.30803	37.4	27.6	10.4	47.8	38.0	60.0	50.0	12.2	12.0
10	19.70487	25.4	5.4	10.9	36.3	16.3	60.0	50.0	23.7	33.7



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0043-C

Page (20) of (20)



7. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
PXA Signal Analyzer	KEYSIGHT	N9040B	US55230151	19.10.31
EMI TEST RECEIVER	R & S	ESCI	100732	19.08.23
Bi-Log Antenna	SCHWARZBECK	VULB 9168	583	20.05.04
Amplifier	SONOMA INSTRUMENT	310N	284608	19.08.23
COAXIAL FIXED ATTENUATOR	Agilent	8491B-003	2708A18758	20.05.04
LOOP Antenna	R & S	HFH2-Z2	100355	20.08.24
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	DT2000	79	-
TWO-LINE V - NETWORK	R&S	ENV216	101584	20.04.05
EMI TEST RECEIVER	R & S	ESCI3	100718	19.08.23
Vector Signal Generator	R & S	SMBV100A	257566	20.01.04
Signal Generator	R & S	SMR40	100007	19.05.15
Cable Assembly	RadiAll	2301761768000PJ	1724.659	-
Cable Assembly	gigalane	RG-400	-	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-

End of test report