

KCTL

KP20-05426

REPORT REVISION HISTORY

Date	Revision	Page No
2020-11-16	Originally issued	-
2020-11-20	General information modification and change the radiated emission test picture/data	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

General remarks for test reports

Nothing significant to report.

Contents

1. Applicant information	4
2. Laboratory information.....	5
3. Test system configuration.....	6
3.1 Operation environment.....	6
3.2 Measurement Uncertainty	7
4. Description of EUT	9
4.1 General information.....	9
4.2 Product description.....	10
4.3 Auxiliary equipments	11
4.4 Test configuration	12
4.5 Operating conditions	13
5. Summary of test results	14
5.1 Summary of EMI emission test results	14
6. Test results	15
6.1 Conducted Emissions.....	15
6.2 Radiated Emission	18

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea Tel: 82-31-285-0894 Fax: 82-505-299-8311 www.kctl.co.kr	Report No.: KR20-SEF0177-A Page (4) of (22)	
---	---	---

1. Applicant information

Applicant: Samsung Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
 16677, Rep. of Korea
E-mail: sm3076.lee@samsung.com
Contact name: Sungmin Lee

Manufacturer: Samsung Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
 16677, Rep. of Korea
E-mail: sm3076.lee@samsung.com
Contact name: Sungmin Lee

Factory #1: SAMSUNG ELECTRONICS VIETNAM CO.,LTD.
Address: Yenphong1-I.P YenTrung Commune, Yenphong Dist.,
 Bac Ninh Province, Vietnam

Factory #2: Samsung India Electronics PVT. Ltd
Address: B-1, Sector-81, Phase- II NOIDA U.P. India

Factory #3: Samsung Electronics Vietnam Thai Nguyen Co., Ltd
Address: Yen Binh Industrial Zone, Pho Ten Dist.,
 Thai Nguyen Province, Vietnam

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0177-A
Page (5) of (22)

KCTL

2. Laboratory information

Address

KCTL Inc. (Suwon Lab.)

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Telephone Number: 82 31 285 0894

Facsimile Number: 82 505 299 8311


FCC Site Designation No: KR0040

VCCI Registration No.: R-20080, G-20078, C-20059, T-20056

Industry Canada Registration No. : 8035A

KOLAS NO.: KT231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber 10 m (RE)	23.8 °C / 22.6 °C	35.6 % R.H. / 33.7 % R.H.	-
Shielded room(CE)	24.1 °C	30.1 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted Emission measurement (Confidence level about 95 %, $k = 2$)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz:	3.7 dB
	150 kHz ~ 30 MHz:	3.3 dB
Shielded Room (CE#2)	9 kHz ~ 150 kHz:	3.5 dB
	150 kHz ~ 30 MHz:	3.1 dB
Radiated Emission measurement (Confidence level about 95 %, $k = 2$)		
10 m Chamber (4F)	30 MHz ~ 300 MHz	3 m: 5.4 dB
		10 m: 5.3 dB
	300 MHz ~ 1 000 MHz	3 m: 5.5 dB
		10 m: 5.4 dB
	1 GHz ~ 6 GHz	3 m: 6.4 dB
	6 GHz ~ 18 GHz	3 m: 6.6 dB
	18 GHz ~ 30 GHz	3 m: 6.7 dB
	30 GHz ~ 40 GHz	3 m: 6.2 dB
10 m Chamber (2F)	30 MHz ~ 300 MHz	3 m: 5.0 dB
		10 m: 5.0 dB
	300 MHz ~ 1 000 MHz	3 m: 5.2 dB
		10 m: 5.0 dB
	1 GHz ~ 6 GHz	3 m: 6.4 dB
	6 GHz ~ 18 GHz	3 m: 6.6 dB

3.3 Measurement Program

These test items were performed by software programs;

Test item	Measurement Program		Used
Conducted Emission	EP5CE_V 5.4.0(TOYO)		☒
Radiated Emission	2F	EP5RE_V 4.6.0(TOYO)	☒
	4F	EP5RE_V 5.11.10(TOYO)	

4. Description of EUT

4.1 General information

Declared Hardware Version	REV0.3
Declared Software Version	A125M.001
IMEI No	351405810022638/01
Operating Band(s)	GSM 850/900/1800/1900 WCDMA FDD 1/2/4/5/8 LTE FDD 1/2/3/4/5/7/8/12/17/26/28/66 LTE TDD 38/40/41


4.2 Product description

Type of product	Mobile phone
Model name (Basic)	SM-A125M/DS
Model name (Variant)	SM-A125M
Difference	Single SIM
Serial no	-
Testing voltage	120 V, 60 Hz
Input/Output rating	Adapter (EP-TA200) Input: AC 100 V - 240 V, 50-60 Hz, 0.5 A Output: DC 9.0 V, 1.67 A or DC 5.0 V, 2.0 A Serial no: R37M37LK501DK3
Internal clock frequency	Above 108 MHz
RF Frequency	Bluetooth(BDR/EDR/BLE)_2 402 MHz ~ 2 480 MHz 2 412 MHz ~ 2 472 MHz (802.11 b/g/n_HT20) LTE Band 2_1 850.7 MHz ~ 1 909.3 MHz LTE Band 4_1 710.7 MHz ~ 1 754.3 MHz LTE Band 5_824.7 MHz ~ 848.3 MHz LTE Band 12_699.7 MHz ~ 715.3 MHz LTE Band 17_706.5 MHz ~ 713.5 MHz LTE Band 26_824.7 MHz ~ 848.3 MHz, 814.7 MHz ~ 823.3 MHz LTE Band 41_2 498.5 MHz ~ 2 687.5 MHz LTE Band 66_1 710.7 MHz ~ 1 779.3 MHz GSM 850_824.2 MHz ~ 848.8 MHz GSM 1900_1 850.2 MHz ~ 1 909.8 MHz WCDMA 850_826.4 MHz ~ 846.6 MHz WCDMA 1700_1 712.4 MHz ~ 1 752.6 MHz WCDMA 1900_1 852.4 MHz ~ 1 907.6 MHz
Note	-

4.3 Auxiliary equipments

Type	Model / Part #	S/N	Manufacturer
Adapter (EUT)	EP-TA200	R37M37LK501DK3	SAMSUNG
USB Cable (EUT)	-	-	SAMSUNG
Earphone (EUT)	EHS64AVFWE	-	SAMSUNG
USIM Card	-	-	-
Micro SD Card (64 GB)	Samsung Pro Plus MB-MD64G	-	SAMSUNG
Radio Communication Tester	CMU200	-	R&S
Spiral ANT	PSA-75301R/170	406827-0001	COBHAM

4.4 Test configuration



	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT	Power	Adapter (EUT)	-	0.8	Shield
2		USIM	USIM Card	-	Direct	-
3		Micro SD	Micro SD Card	-	Direct	-
4		Earphone	Earphone (EUT)	-	1.25	Unshield
5	Adapter (EUT)	Power	AC Main	-	Direct	-
6	Radio Communication Tester	RF	Spiral ANT	-	2.0	Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
Test #1	Charging(w/TA) + Cellular receiver (GSM 850_Low)

Note 1. All cellular RX bands operating below 1 GHz, including GSM, WCDMA and LTE have been investigated with low/middle/high channels. Among the bands, GSM 850 is the worst mode.

Note 2. It means this device needs to be tested with 3 orientations (x, y and z) and at least the worst case orientation shall be set for final test.

It was determined that Z orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in Z orientation.

5. Summary of test results

5.1 Summary of EMI emission test results

Applied	Test items	Test method	Result
☒	Conducted Emission	FCC Part 15 Subpart B (Class B) ANSI C63.4:2014	Pass
☒	Radiated Emission	FCC Part 15 Subpart B (Class B) ANSI C63.4:2014	Pass

6. Test results

6.1 Conducted Emissions

Test specification	ANSI C63.4:2014, Class B FCC Part 15 Subpart B		
Testing voltage	120 V, 60 Hz		
Test facility	Shielded room (CE#1)		
Date	2020-11-13		
Temperature (°C)	24.1 °C	Humidity (% R.H.)	30.1 % R.H.
Remarks	Pass		

6.1.1 Limits of conducted emissions measurement

Frequency [MHz]	Class A (dB(μ V))		Class B (dB(μ V))	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79	66	66 ~ 56 ¹⁾	56 ~ 46 ¹⁾
0.5 ~ 5	73	60	56	46
5 ~ 30	73	60	60	50

¹⁾ The limit decreases linearly with the logarithm of frequency

6.1.2 Measurement procedure

The measurements were performed in a shielded room. EUT was setup as shown in photograph and placed on a non-metallic table height of 0.8 m above the reference ground plane. The rear of table was located 0.4 m to the vertical conducted plane. EUT was power through the LISN, which was bonded to the ground plane. The LISN power was filtered. Each EUT power lead, except ground (safety) lead was individually connected through a LISN to input power source. EUT signal cables that hung closer than 0.4 m to the Horizontal metal ground 0.3 m ~ 0.4 m long. The power cord was bundles in the center. All peripheral equipment was powered from a sub LISN. The LISN and ISN were positioned 0.8 m from the EUT. Peak and Average detection were used in preliminary testing and Quasi-peak and Average detections were used at final measurement.

6.1.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
EMI TEST RECEIVER	ESCI	100001	R&S	2021.08.20	☒
TWO-LINE V-NETWORK	ENV216	101358	R&S	2021.09.29	☒
TWO-LINE V-NETWORK	ENV216	101352	R&S	2021.04.06	☐

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0177-A
Page (17) of (22)



6.1.4 Conducted emissions measurement result

AC Main



Final Result

--- N_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.17094	38.1	24.9	10.2	48.3	35.1	64.9	54.9	16.6	19.8
2	0.22822	33.6	21.0	9.8	43.4	30.8	62.5	52.5	19.1	21.7
3	0.71019	22.8	9.3	9.9	32.7	19.2	56.0	46.0	23.3	26.8
4	4.82301	18.2	5.8	10.0	28.2	15.8	56.0	46.0	27.8	30.2
5	6.22612	23.5	11.4	10.0	33.5	21.4	60.0	50.0	26.5	28.6
6	19.17807	15.0	3.1	10.9	25.9	14.0	60.0	50.0	34.1	36.0

--- L1_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.17111	38.8	25.5	10.2	49.0	35.7	64.9	54.9	15.9	19.2
2	0.22818	34.2	21.5	9.8	44.0	31.3	62.5	52.5	18.5	21.2
3	0.71432	23.3	13.1	9.9	33.2	23.0	56.0	46.0	22.8	23.0
4	4.84311	18.7	6.0	10.0	28.7	16.0	56.0	46.0	27.3	30.0
5	6.43886	21.7	13.1	10.0	31.7	23.1	60.0	50.0	28.3	26.9
6	19.34822	14.9	2.7	10.7	25.6	13.4	60.0	50.0	34.4	36.6

6.2 Radiated Emission

Test specification		ANSI C63.4:2014, Class B FCC Part 15 Subpart B		
Testing voltage		120 V, 60 Hz		
Test facility		10 m Chamber (4F)		
Test distance		3 m		
Date		2020-11-13 / 2020-11-19		
30 MHz ~ 1 GHz	Temperature (°C)	23.8 °C	Humidity (% R.H.)	35.6 % R.H.
1 GHz ~ 30 GHz		22.6 °C		33.7 % R.H.
Remarks		Pass		

6.2.1 Limits of radiated emission measurement

Frequency [MHz]	Class A (dB(μ N/m)) @ 10 m	Class B (dB(μ N/m)) @ 3 m
30-88	39	40
88-216	43.5	43.5
216-960	46.4	46
Above 960	49.5	54

Note- Alternative standard: CISPR, Pub. 22

6.2.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane.

Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.2.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
EMI TEST RECEIVER	ESR7	101078	R&S	2021.08.20	☑
Bilog Antenna	CBL 6112D	55545	TESEQ	2022.04.24	☑
AMPLIFIER	310N	293004	SONOMA	2021.08.20	☑
ATTENUATOR	8491B-6dB	MY39271060	KEYSIGHT	-	☑
Antenna Mast	MA4640-XP-ET	-	Innco Systems	-	☑
Turn Table	TT 3.0-3t	-	MATURO	-	☑
DOUBLE RIDGED HORN ANTENNA	3117-PA	00161083	ETS-LINDGREN	2021.09.18	☑
AMPLIFIER	JS44-18004000-33-8P	2000996	L-3Narda-MITEQ	2021.01.22	☑
Horn antenna	3116	00086635	ETS-LINDGREN	2021.05.12	☑
PREAMPLIFIER	8449B	3008A01802	AGILENT	2021.04.03	☑
DOUBLE RIDGED HORN ANTENNA	3115	00086706	ETS-LINDGREN	2021.08.28	☑
Spectrum Analyzer	FSV40	100988	R&S	2021.01.03	☑

6.2.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 6 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G = Amplifier Gain

6 dB Att = 6 dB Attenuator

If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 6 dB, A.G 35 dB

The result is $30 + 12 + 5 + 6 - 35 = 18 \text{ dB } (\mu\text{V/m})$

Bilog Antenna and ATTENUATOR (6 dB) were calibrated together.

AV = CAV : Abbreviation of CISPR Average

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0177-A
Page (20) of (22)



6.2.5 Radiated emission measurement result

30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	41.750	V	40.7	-11.6	29.1	40.0	10.9	307.0	80.0
2	61.425	V	43.9	-16.7	27.2	40.0	12.8	109.0	47.0
3	93.075	V	32.9	-12.9	20.0	43.5	23.5	389.0	152.0
4	182.900	V	29.7	-11.9	17.8	43.5	25.7	120.0	212.0
5	227.100	V	30.5	-9.4	21.1	46.0	24.9	100.0	357.0
6	638.966	V	22.9	0.7	23.6	46.0	22.4	303.0	285.0
7	815.585	H	18.8	4.0	22.8	46.0	23.2	198.0	177.0
8	965.158	V	18.7	5.9	24.6	54.0	29.4	200.0	229.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0177-A
Page (21) of (22)



1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	1327.740	H	58.9	47.1	-15.7	43.2	31.4	74.0	54.0	30.8	22.6	106.0	319.0
2	1380.632	V	58.3	44.9	-15.8	42.5	29.1	74.0	54.0	31.5	24.9	109.0	331.0
3	3059.948	V	50.4	37.0	-8.5	41.9	28.5	74.0	54.0	32.1	25.5	115.0	211.0
4	3076.004	H	51.9	39.0	-8.7	43.2	30.3	74.0	54.0	30.8	23.7	206.0	317.0
5	17105.560	H	39.7	25.5	8.9	48.6	34.4	74.0	54.0	25.4	19.6	387.0	290.0
6	17911.220	V	40.2	26.8	9.2	49.4	36.0	74.0	54.0	24.6	18.0	105.0	136.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0177-A
Page (22) of (22)



18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	19166.730	V	44.1	31.8	1.8	45.9	33.6	74.0	54.0	28.1	20.4	109.0	203.0
2	20908.830	V	44.7	32.4	3.5	48.2	35.9	74.0	54.0	25.8	18.1	313.0	334.0
3	23826.320	V	44.8	31.4	4.7	49.5	36.1	74.0	54.0	24.5	17.9	192.0	64.0
4	23888.330	H	45.3	32.1	4.7	50.0	36.8	74.0	54.0	24.0	17.2	107.0	54.0
5	26203.790	H	42.3	30.0	7.8	50.1	37.8	74.0	54.0	23.9	16.2	400.0	303.0
6	27704.540	H	41.8	30.1	8.8	50.6	38.9	74.0	54.0	23.4	15.1	100.0	51.0