



CERTIFICATION TEST REPORT

Report Number. : 4789793179-E5V3

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-A125U, SM-S127DL, SM-A125U1/DS, SM-A125U1

FCC ID : A3LSMA125U

EUT Description : GSM/CDMA/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac and
NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:

March 23, 2021

Prepared by:

UL Korea, Ltd.

26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory

218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea

TEL: (031) 337-9902

FAX: (031) 213-5433



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	03/02/21	Initial issue	Hyunsik Yun
V2	03/08/21	Updated to address TCB's question	Hyunsik Yun
V3	03/23/21	Added SM-A125U1 model	Hyunsik Yun

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. DECISION RULES AND MEASUREMENT UNCERTAINTY	7
4.1. METROLOGICAL TRACEABILITY.....	7
4.2. SAMPLE CALCULATION.....	7
4.3. DECISION RULES.....	7
4.4. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST.....	8
5.1. EUT DESCRIPTION.....	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE.....	9
5.5. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. TEST RESULTS SUMMARY.....	13
8. MEASUREMENT METHODS.....	14
9. ANTENNA PORT TEST RESULTS.....	15
9.1. ON TIME AND DUTY CYCLE.....	15
9.2. 20 dB AND 99% BANDWIDTH.....	16
9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	16
9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	16
9.3. HOPPING FREQUENCY SEPARATION.....	19
9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	20
9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	20
9.4. NUMBER OF HOPPING CHANNELS	21
9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	22
9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	23
9.5. AVERAGE TIME OF OCCUPANCY.....	24
9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	25
9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	27
9.6. OUTPUT POWER.....	29
9.6.1. BASIC DATA RATE GFSK MODULATION.....	29
9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION	29
9.6.3. ENHANCED DATA RATE 8PSK MODULATION	29

9.6.4. OUTPUT POWER PLOTS.....	30
9.7. AVERAGE POWER.....	32
9.7.1. BASIC DATA RATE GFSK MODULATION.....	32
9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION.....	32
9.7.3. ENHANCED DATA RATE 8PSK MODULATION.....	32
9.8. CONDUCTED SPURIOUS EMISSIONS.....	33
9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION.....	34
9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	36
10. RADIATED TEST RESULTS.....	38
10.1. TRANSMITTER ABOVE 1 GHz.....	40
10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION.....	40
10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	47
10.2. WORST CASE BELOW 1 GHz.....	54
11. AC POWER LINE CONDUCTED EMISSIONS.....	55
11.1.1. AC Power Line.....	56

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/CDMA/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac and NFC

MODEL: SM-A125U, SM-S127DL, SM-A125U1/DS, SM-A125U1

SERIAL NUMBER: R38R100SMVZ (CONDUCTED);
R37R100SNBW, R38R100SPAF (RADIATED);

DATE TESTED: FEB 10, 2021 – FEB 26, 2021;

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Hyunsik Yun
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. DECISION RULES

Decision rule for statement(s) of conformity is based on Procedure 1, Clause 4.4.2 in IEC Guide 115:2007.

4.4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.01 dB
Radiated Disturbance, 30 MHz to 1 GHz	4.26 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.90 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.49 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a GSM/CDMA/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac and NFC. This test report addresses the BT(DSS) operational mode.

This report covers the Samsung models SM-A125U, SM-A125U1/DS, SM-A125U1 and SM-S127DL.

These models are identical in hardware except SM-A125U1/DS has dual SIM tray, SM-A125U1 has single SIM tray and SM-S127DL is not supported CDMA.

With some pre-scan, model SM-A125U was set for final test.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 - 2 480	Basic GFSK	Average	8.389	6.900
		Peak	9.047	8.030
	Enhanced Pi/4-DPSK	Average	6.208	4.176
		Peak	8.280	6.730
	Enhanced 8PSK	Average	6.286	4.252
		Peak	8.290	6.745

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The internal antenna was Permanently attached.
 Therefore this E.U.T Complies with the requirement of §15.203.**

The radio utilizes an internal antennas, with maximum gain of -4.26 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA200	R37NBH409C3SE3	N/A
Data Cable	SAMSUNG	EP-DR140AWE	N/A	N/A
Earphone	SAMSUNG	EHS64AVFWE	N/A	N/A


I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A
2	Audio	2	AUX	Unshielded	1.1 m	N/A


TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
 Test software enable BT communications.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-19-22
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	08-13-22
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-13-22
Antenna, Horn, 18 GHz	ETS	3115	00167211	07-27-22
Antenna, Horn, 18 GHz	ETS	3115	00161451	08-15-22
Antenna, Horn, 18 GHz	ETS	3117	00168724	07-27-22
Antenna, Horn, 18 GHz	ETS	3117	00168717	08-15-22
Antenna, Horn, 40 GHz	ETS	3116C	00166155	08-04-22
Antenna, Horn, 40 GHz	ETS	3116C	00168645	10-02-21
Preamplifier	ETS	3116C-PA	00168841	08-06-21
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-03-21
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-03-21
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-06-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-03-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-03-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-04-21
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-05-21
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-05-21
Spectrum Analyzer, 43.5 GHz	R&S	FSW43	104089	08-06-21
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-05-21
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-05-21
Power Splitter	MINI-CIRCUITS	WA1534	UL001	01-27-22
Attenuator	PASTERNAK	PE7087-10	A001	08-03-21
Attenuator	PASTERNAK	PE7087-10	A008	08-03-21
Attenuator	PASTERNAK	PE7004-10	2	08-04-21
Attenuator	PASTERNAK	PE7087-10	A009	08-03-21
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-03-21
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-03-21
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-03-21
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-03-21
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-03-21
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-04-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-03-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-03-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-04-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-03-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-03-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-04-21
LISN	R&S	ENV-216	101837	08-06-21
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-02-21
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247(d)	Band Edge / Conducted Spurious Emission	-20 dBc	Conducted	PASS
15.247 (b)(1)	TX conducted output power	< 21 dBm		PASS
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		PASS
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		PASS
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 8 dBm		PASS
15.207(a)	AC Power Line conducted emissions	Section 11	Power Line conducted	PASS
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	PASS

8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW : ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION : ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS : ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY : ANSI C63.10, Section 7.8.4

OUTPUT POWER : ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.6, 7.8.8

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 6.

Out-of-band EMISSIONS IN RESTRICTED BANDS : ANSI C63.10, Section 6.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE

ANSI C63.10, Section 11.6 : Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	On time [msec]	Period [msec]	Duty Cycle [%]	Duty Cycle Correction Factor[dB]	1/T Minimum VBW [kHz]
2 400 ~ 2 483.5 MHz Band					
Bluetooth	2.879	3.749	76.79	-	0.345



9.2. 20 dB AND 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to $\geq 1\%$ of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.

RESULTS


9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [kHz]
0	2 402	864.8	744.2
39	2 441	835.0	721.4
78	2 480	834.9	743.3


9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [kHz]
0	2 402	1220.0	1157.3
39	2 441	1218.0	1129.4
78	2 480	1219.0	1130.1


- BDR




20 dB bandwidth / 0 CHANNEL




99% bandwidth / 0 CHANNEL




20 dB bandwidth / 39 CHANNEL



99% bandwidth / 39 CHANNEL




20 dB bandwidth / 78 CHANNEL




99% bandwidth / 78 CHANNEL


- EDR




20 dB bandwidth / 0 CHANNEL




99% bandwidth / 0 CHANNEL



20 dB bandwidth / 39 CHANNEL



99% bandwidth / 39 CHANNEL



20 dB bandwidth / 78 CHANNEL



99% bandwidth / 78 CHANNEL

9.3. HOPPING FREQUENCY SEPARATION

LIMITS

FCC §15.247 (a) (1)

RSS-247 (5.1) (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to $VBW \geq RBW$. The sweep time is coupled.

RESULTS

9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



HOPPING FREQUENCY SEPARATION PLOT

9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



HOPPING FREQUENCY SEPARATION PLOT

9.4. NUMBER OF HOPPING CHANNELS

LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.





TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS

Normal Mode: All Channels Observed


9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION




9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION




100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3



30MHz SPAN, SEGMENT 2 OF 3



30MHz SPAN, SEGMENT 3 OF 3

9.5. AVERAGE TIME OF OCCUPANCY

LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 3.16 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{ pulse width}$.


RESULTS

9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION


DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.376	32	0.120	0.4	-0.280
DH3	1.631	16	0.261	0.4	-0.139
DH5	2.879	11	0.317	0.4	-0.083
GFSK AFH					
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH					
DH1	0.376	8	0.030	0.4	-0.370
DH3	1.631	4	0.065	0.4	-0.335
DH5	2.879	2.75	0.079	0.4	-0.321




PULSE WIDTH – DH1



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1




PULSE WIDTH – DH3



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3




PULSE WIDTH – DH5




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5

9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION


DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Normal					
DH1	0.384	32	0.123	0.4	-0.277
DH3	1.633	16	0.261	0.4	-0.139
DH5	2.884	11	0.317	0.4	-0.083
8PSK AFH					
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK AFH					
DH1	0.384	8	0.031	0.4	-0.369
DH3	1.633	4	0.065	0.4	-0.335
DH5	2.884	2.75	0.079	0.4	-0.321



PULSE WIDTH – 3-DH1




**NUMBER OF PULSES IN 3.16 SECOND
 OBSERVATION PERIOD – 3-DH1**



PULSE WIDTH – 3-DH3



**NUMBER OF PULSES IN 3.16 SECOND
 OBSERVATION PERIOD – 3-DH3**



PULSE WIDTH – 3-DH5



**NUMBER OF PULSES IN 3.16 SECOND
 OBSERVATION PERIOD – 3-DH5**

9.6. OUTPUT POWER

LIMITS

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

9.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dBm]
0	2 402	9.047	21.000	-11.953
39	2 441	8.753	21.000	-12.247
78	2 480	7.898	21.000	-13.102
Worst		9.047	21.000	-11.953

9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION


Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dBm]
0	2 402	8.280	21.000	-12.720
39	2 441	7.880	21.000	-13.120
78	2 480	7.731	21.000	-13.269
Worst		8.280	21.000	-12.720


9.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dBm]
0	2 402	8.290	21.000	-12.710
39	2 441	8.071	21.000	-12.929
78	2 480	7.842	21.000	-13.158
Worst		8.290	21.000	-12.710

9.6.4. OUTPUT POWER PLOTS

PEAK OUTPUT POWER





9.7. AVERAGE POWER

LIMITS

None; for reporting purposes only

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter.
 The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

9.7.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
0	2 402	8.389	6.900
39	2 441	8.243	6.672
78	2 480	7.240	5.296

9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
0	2 402	6.208	4.176
39	2 441	5.828	3.826
78	2 480	5.554	3.592

9.7.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
0	2 402	6.286	4.252
39	2 441	5.834	3.832
78	2 480	5.566	3.603

9.8. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The band-edges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS

9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION


SPURIOUS EMISSIONS, NON-HOPPING




0 CHANNEL BANDEDGE




OUT-OF-BAND 0 CHANNEL




IN-BAND REFERENCE LEVEL



OUT-OF-BAND 39 CHANNEL




78 CHANNEL BANDEDGE




OUT-OF-BAND 78 CHANNEL

SPURIOUS BANDEGE EMISSIONS WITH HOPPING ON




9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION


SPURIOUS EMISSIONS, NON-HOPPING




0 CHANNEL BANDEDGE




OUT-OF-BAND 0 CHANNEL




IN-BAND REFERENCE LEVEL



OUT-OF-BAND 39 CHANNEL




78 CHANNEL BANDEDGE



OUT-OF-BAND 78 CHANNEL

SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON



10. RADIATED TEST RESULTS

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

FCC Part 15.205 (a) : Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 – 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 – 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.17	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	167.72 ~ 173.2	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	240 ~ 285	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	322 ~ 335.4	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	399.90 ~ 410	3345.8 ~ 3358		
		608 ~ 614	3600 ~ 4400		
		960 ~ 1240			

▪ FCC Part 15.205(b) : The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements.(Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1/T (on time) for average measurement.

$$\text{GFSK} = 1/T = 1 / 0.002879\text{s} = 347\text{Hz}.$$

The minimum VBW was 347Hz, but test receiver(ESU40) couldn't set value 347Hz. Due to this reason, testing VBW was set to 360Hz(Worst cases).

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9kHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.


Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

10.1. TRANSMITTER ABOVE 1 GHz

10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

BANDEDGE (0 CHANNEL)

HORIZONTAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	43.68	Pk	31.8	-25.6	49.88	-	-	74	-24.12	173	238	H
2	* 2.36542	44.74	Pk	31.7	-25.5	50.94	-	-	74	-23.06	173	238	H
3	* 2.39	31.8	VA1T	31.8	-25.6	38	54	-16	-	-	173	238	H
4	* 2.38906	32.16	VA1T	31.8	-25.5	38.46	54	-15.54	-	-	173	238	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK - Peak detector
 VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

VERTICAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.95	Pk	31.8	-25.6	48.15	-	-	74	-25.85	200	331	V
2	* 2.33856	45.03	Pk	31.7	-25.6	51.13	-	-	74	-22.87	200	331	V
3	* 2.39	31.79	VA1T	31.8	-25.6	37.99	54	-16.01	-	-	200	331	V
4	* 2.38892	32.16	VA1T	31.8	-25.5	38.46	54	-15.54	-	-	200	331	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

BANDEDGE (78 CHANNEL)

HORIZONTAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	43.59	Pk	32	-25.3	50.29	-	-	74	-23.71	171	168	H
2	2.54415	44.66	Pk	32	-25.2	51.46	-	-	74	-22.54	171	168	H
3	* 2.4835	32.33	VA1T	32	-25.3	39.03	54	-14.97	-	-	171	168	H
4	* 2.48394	32.41	VA1T	32	-25.3	39.11	54	-14.89	-	-	171	168	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL RESULT




Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	43.5	Pk	32	-25.3	50.2	-	-	74	-23.8	206	306	V
2	2.54837	44.78	Pk	32	-25.1	51.68	-	-	74	-22.32	206	306	V
3	* 2.4835	32	VA1T	32	-25.3	38.7	54	-15.3	-	-	206	306	V
4	2.56264	32.03	VA1T	32.1	-25.1	39.03	54	-14.97	-	-	206	306	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS 0 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.80433	43.83	Pk	34.1	-31.5	46.43	-	-	74	-27.57	16	125	H
* 4.804	34.67	VA1T	34.1	-31.5	37.27	54	-16.73	-	-	16	125	H
* 4.8041	42.53	Pk	34.1	-31.5	45.13	-	-	74	-28.87	87	145	V
* 4.80389	29.15	VA1T	34.1	-31.5	31.75	54	-22.25	-	-	87	146	V
7.21118	27.31	Pk	35.9	-27.6	35.61	-	-	74	-38.39	0	100	H
7.21536	28.97	Pk	35.9	-27.5	37.37	-	-	74	-36.63	0	100	V
9.58772	24.07	Pk	37.1	-23	38.17	-	-	74	-35.83	0	100	H
9.58302	18.67	Pk	37.1	-23	32.77	-	-	74	-41.23	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

39 CHANNEL RESULTS



HORIZONTAL



VERTICAL


Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88179	42.71	Pk	34.1	-31.3	45.51	-	-	74	-28.49	16	119	H
* 4.88232	33.5	VA1T	34.1	-31.4	36.2	54	-17.8	-	-	16	118	H
* 4.88179	38.54	Pk	34.1	-31.3	41.34	-	-	74	-32.66	296	354	V
* 4.87984	27.34	VA1T	34.1	-31.4	30.04	54	-23.96	-	-	296	354	V
* 7.31649	35.39	Pk	35.8	-27.4	43.79	-	-	74	-30.21	360	100	H
* 7.32507	37.82	Pk	35.8	-27.3	46.32	-	-	74	-27.68	360	100	V
9.7547	23.74	Pk	37.4	-23.7	37.44	-	-	74	-36.56	360	100	H
9.76353	22.54	Pk	37.4	-23.7	36.24	-	-	74	-37.76	360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

78 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96023	41.61	Pk	34.1	-31.5	44.21	-	-	74	-29.79	20	400	H
* 4.9598	30.79	VA1T	34.1	-31.4	33.49	54	-20.51	-	-	20	400	H
* 4.96045	41.48	Pk	34.1	-31.5	44.08	-	-	74	-29.92	289	343	V
* 4.95994	32.63	VA1T	34.1	-31.4	35.33	54	-18.67	-	-	289	342	V
* 7.4337	35.58	Pk	35.8	-26.8	44.58	-	-	74	-29.42	360	100	H
* 7.44605	35.48	Pk	35.8	-26.9	44.38	-	-	74	-29.62	360	100	V
9.91392	33.17	Pk	37.7	-21.6	49.27	-	-	74	-24.73	360	100	H
9.93864	32.53	Pk	37.7	-21.4	48.83	-	-	74	-25.17	360	100	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

BANDEDGE (0 CHANNEL)

HORIZONTAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.13	Pk	31.8	-25.6	48.33	-	-	74	-25.67	178	223	H
2	* 2.37826	44.76	Pk	31.8	-25.6	50.96	-	-	74	-23.04	178	223	H
3	* 2.39	31.83	VA1T	31.8	-25.6	38.03	54	-15.97	-	-	178	223	H
4	* 2.3885	32.21	VA1T	31.8	-25.5	38.51	54	-15.49	-	-	178	223	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.51	Pk	31.8	-25.6	48.71	-	-	74	-25.29	201	331	V
2	* 2.34303	45.31	Pk	31.7	-25.7	51.31	-	-	74	-22.69	201	331	V
3	* 2.39	31.79	VA1T	31.8	-25.6	37.99	54	-16.01	-	-	201	331	V
4	* 2.38964	32.2	VA1T	31.8	-25.6	38.4	54	-15.6	-	-	201	331	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Antenna 1 / BANDEDGE (78 CHANNEL)

HORIZONTAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	43.24	PK	32	-25.3	49.94	-	-	74	-24.06	171	216	H
2	* 2.49915	45.55	PK	32	-25.1	52.45	-	-	74	-21.55	171	216	H
3	* 2.4835	32.39	VA1T	32	-25.3	39.09	54	-14.91	-	-	171	216	H
4	* 2.48368	32.54	VA1T	32	-25.3	39.24	54	-14.76	-	-	171	216	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL RESULT




Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBu)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBu/m)	Average Limit (dBu/m)	Margin (dB)	Peak Limit (dBu/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	41.35	Pk	32	-25.3	48.05	-	-	74	-25.95	267	103	V
2	2.54243	44.94	Pk	32	-25	51.94	-	-	74	-22.06	267	103	V
3	* 2.4835	31.86	VA1T	32	-25.3	38.56	54	-15.44	-	-	267	103	V
4	2.5458	32.2	VA1T	32	-25.1	39.1	54	-14.9	-	-	267	103	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS 0 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.80411	43.06	Pk	34.1	-31.5	45.66	-	-	74	-28.34	16	127	H
* 4.80412	31.13	VA1T	34.1	-31.5	33.73	54	-20.27	-	-	16	127	H
* 4.80482	41.78	Pk	34.1	-31.4	44.48	-	-	74	-29.52	83	101	V
* 4.80405	28.57	VA1T	34.1	-31.5	31.17	54	-22.83	-	-	83	101	V
7.20699	34.91	Pk	35.9	-27.6	43.21	-	-	74	-30.79	0	101	H
7.20699	33.6	Pk	35.9	-27.6	41.9	-	-	74	-32.1	0	101	V
9.60792	31.08	Pk	37.1	-23	45.18	-	-	74	-28.82	0	101	H
9.60792	31.99	Pk	37.1	-23	46.09	-	-	74	-27.91	0	101	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $VB=1/Ton$ where: Ton is transmit duration

39 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88134	42.16	Pk	34.1	-31.3	44.96	-	-	74	-29.04	0	100	H
* 4.87812	41.8	Pk	34.1	-31.4	44.5	-	-	74	-29.5	0	100	V
* 7.32377	39.73	Pk	35.8	-27.3	48.23	-	-	74	-25.77	0	100	H
* 7.31771	37.74	Pk	35.8	-27.4	46.14	-	-	74	-27.86	0	100	V
9.76238	34.37	Pk	37.4	-23.7	48.07	-	-	74	-25.93	0	100	H
9.76367	34.33	PK	37.4	-23.7	48.03	-	-	74	-25.97	0	100	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

78 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.95963	40.41	Pk	34.1	-31.4	43.11	-	-	74	-30.89	0	100	H
* 4.9592	40.85	Pk	34.1	-31.4	43.55	-	-	74	-30.45	0	100	V
* 7.44266	35.77	PK	35.8	-26.8	44.77	-	-	74	-29.23	0	100	H
* 7.44728	34.76	PK	35.8	-26.8	43.76	-	-	74	-30.24	0	100	V
9.91964	33.28	PK	37.7	-21.6	49.38	-	-	74	-24.62	0	100	H
9.92196	32.91	PK	37.7	-21.5	49.11	-	-	74	-24.89	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK - Peak detector

10.2. WORST CASE BELOW 1 GHZ

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



HORIZONTAL



VERTICAL

Below 1GHz Data

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_750	Below_1G[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	32.813	41.18	Pk	15.8	-31.1	25.88	40	-14.12	0-360	300	H
2	96.057	37.87	Pk	16.8	-29.7	24.97	43.52	-18.55	0-360	300	H
3	* 240.102	33.35	Pk	18.2	-28.2	23.35	46.02	-22.67	0-360	100	H
4	43.774	37	Pk	19.5	-30.7	25.8	40	-14.2	0-360	100	V
5	66.957	38.99	Pk	16.6	-30.3	25.29	40	-14.71	0-360	200	V
6	143.587	35.01	Pk	13.8	-29.1	19.71	43.52	-23.81	0-360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

11.1.1. AC Power Line

LINE 1 RESULTS



Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_L1[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.168	38.74	Pk	10	.1	48.84	65.06	-16.22	-	-
2	.159	18.86	Av	9.9	.1	28.86	-	-	55.52	-26.66
3	.231	36.83	Pk	9.8	.2	46.83	62.41	-15.58	-	-
4	.222	16.36	Av	9.8	.2	26.36	-	-	52.74	-26.38
5	.399	28.74	Pk	9.9	.2	38.84	57.87	-19.03	-	-
6	.408	8.76	Av	9.9	.2	18.86	-	-	47.69	-28.83
7	.777	25.22	Pk	9.8	.2	35.22	56	-20.78	-	-
8	.777	16.23	Av	9.8	.2	26.23	-	-	46	-19.77
9	3.627	24.7	Pk	9.8	.3	34.8	56	-21.2	-	-
10	3.624	9.83	Av	9.8	.3	19.93	-	-	46	-26.07
11	12.201	29.18	Pk	10	.3	39.48	60	-20.52	-	-
12	12.204	15.53	Av	10	.3	25.83	-	-	50	-24.17

Pk - Peak detector

Av - Average detection

LINE 2 RESULTS



Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_N[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.165	38.12	Pk	10	.1	48.22	65.21	-16.99	-	-
14	.162	20.34	Av	10	.1	30.44	-	-	55.36	-24.92
15	.225	34.92	Pk	9.8	.2	44.92	62.63	-17.71	-	-
16	.225	20.01	Av	9.8	.2	30.01	-	-	52.63	-22.62
17	.387	26.1	Pk	9.9	.2	36.2	58.13	-21.93	-	-
18	.387	12.91	Av	9.9	.2	23.01	-	-	48.13	-25.12
19	.786	25.52	Pk	9.9	.2	35.62	56	-20.38	-	-
20	.786	17.97	Av	9.9	.2	28.07	-	-	46	-17.93
21	4.629	21.71	Pk	9.8	.3	31.81	56	-24.19	-	-
22	4.644	6.64	Av	9.8	.3	16.74	-	-	46	-29.26
23	12.249	28.24	Pk	10	.3	38.54	60	-21.46	-	-
24	12.225	16.01	Av	10	.3	26.31	-	-	50	-23.69

Pk - Peak detector

Av - Average detection

END OF TEST REPORT