

APPENDIX D: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.



Table D-1
SAR System Validation Summary – 1g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
G	750	05/20/2021	7357	750	Head	0.923	43.827	PASS	PASS	PASS	N/A	N/A	N/A
J	835	06/01/2021	7526	835	Head	0.932	41.465	PASS	PASS	PASS	GMSK	PASS	N/A
L	1750	06/06/2021	7539	1750	Head	1.396	40.369	PASS	PASS	PASS	N/A	N/A	N/A
J	1900	04/02/2021	7526	1900	Head	1.446	40.380	PASS	PASS	PASS	GMSK	PASS	N/A
E	2450	01/07/2021	7571	2450	Head	1.847	39.716	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
J	2450	04/08/2021	7526	2450	Head	1.848	40.201	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
E	2600	01/07/2021	7571	2600	Head	2.025	39.117	PASS	PASS	PASS	TDD	PASS	N/A
J	2600	04/08/2021	7526	2600	Head	1.966	39.986	PASS	PASS	PASS	TDD	PASS	N/A
G	750	05/27/2021	7357	750	Body	0.997	53.630	PASS	PASS	PASS	N/A	N/A	N/A
P	835	09/08/2020	7308	835	Body	0.977	54.534	PASS	PASS	PASS	GMSK	PASS	N/A
P	1750	09/08/2020	7308	1750	Body	1.478	52.861	PASS	PASS	PASS	N/A	N/A	N/A
L	1750	03/31/2021	7539	1750	Body	1.477	51.903	PASS	PASS	PASS	N/A	N/A	N/A
H	1900	03/31/2021	7410	1900	Body	1.570	53.138	PASS	PASS	PASS	GMSK	PASS	N/A
K	2450	03/26/2021	7538	2450	Body	1.962	51.166	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
L	2450	07/02/2021	7539	2450	Body	2.020	52.209	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
K	2600	03/26/2021	7538	2600	Body	2.150	50.900	PASS	PASS	PASS	TDD	PASS	N/A
L	2600	03/31/2021	7539	2600	Body	2.152	50.557	PASS	PASS	PASS	TDD	PASS	N/A

Table D-2
SAR System Validation Summary – 10g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
P	1750	09/08/2020	7308	1750	Body	1.478	52.861	PASS	PASS	PASS	N/A	N/A	N/A
H	1900	03/31/2021	7410	1900	Body	1.570	53.138	PASS	PASS	PASS	GMSK	PASS	N/A
K	2450	03/26/2021	7538	2450	Body	1.962	51.166	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
K	2600	03/26/2021	7538	2600	Body	2.150	50.900	PASS	PASS	PASS	TDD	PASS	N/A

NOTE: The probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID A3LSMA127M		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 05/31/21 – 07/07/21	DUT Type: Portable Handset	APPENDIX D: Page 1 of 1		