



# **CERTIFICATION TEST REPORT**

**Report Number.** : 4790215265-E5V3

**Applicant** : SAMSUNG ELECTRONICS CO., LTD.  
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,  
GYEONGGI-DO, 16677, KOREA

**Model** : SM-A135M/DS, SM-A135M

**FCC ID** : A3LSMA135M

**EUT Description** : GSM/WCDMA/LTE Phone + BT/BLE and DTS/UNII a/b/g/n/ac

**Test Standard(s)** : FCC 47 CFR PART 15 SUBPART C

**Date Of Issue:**

2022-02-16

**Prepared by:**

UL Korea, Ltd.

26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory

218 Maeyeong-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16675, Korea

TEL: (031) 337-9902

FAX: (031) 213-5433



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2022-02-08	Initial issue	Sungeun Lee
V2	2022-02-10	Updated to address TCB's question	Sungeun Lee
V3	2022-02-16	Updated to address TCB's question	Sungeun Lee

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b>	<b>5</b>
1.1. INTRODUCTION OF TEST DATA REUSE	6
1.2. DIFFERENCE	6
1.3. SPOT CHECK VERIFICATION SUMMARY DATA	6
1.4. REFERENCE DETAIL	6
<b>2. TEST METHODOLOGY</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION</b>	<b>7</b>
<b>4. DECISION RULES AND MEASUREMENT UNCERTAINTY</b>	<b>8</b>
4.1. METROLOGICAL TRACEABILITY	8
4.2. SAMPLE CALCULATION	8
4.3. MEASUREMENT UNCERTAINTY	8
4.4. DECISION RULES	8
<b>5. EQUIPMENT UNDER TEST</b>	<b>9</b>
5.1. EUT DESCRIPTION	9
5.2. MAXIMUM OUTPUT POWER	9
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.4. WORST-CASE CONFIGURATION AND MODE	10
5.5. DESCRIPTION OF TEST SETUP	10
<b>6. TEST AND MEASUREMENT EQUIPMENT</b>	<b>12</b>
<b>7. TEST RESULTS SUMMARY</b>	<b>13</b>
<b>8. MEASUREMENT METHODS</b>	<b>14</b>
<b>9. ANTENNA PORT TEST RESULTS</b>	<b>15</b>
9.1. ON TIME AND DUTY CYCLE	15
9.2. 20 dB BANDWIDTH	16
9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	16
9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION	16
9.3. HOPPING FREQUENCY SEPARATION	18
9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	19
9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION	19
9.4. NUMBER OF HOPPING CHANNELS	20
9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	21
9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION	22
9.5. AVERAGE TIME OF OCCUPANCY	23

---

9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION .....	24
9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	26
9.6. <i>OUTPUT POWER</i> .....	28
9.6.1. BASIC DATA RATE GFSK MODULATION.....	28
9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION .....	28
9.6.3. ENHANCED DATA RATE 8PSK MODULATION .....	28
9.6.4. OUTPUT POWER PLOTS.....	29
9.7. <i>AVERAGE POWER</i> .....	32
9.7.1. BASIC DATA RATE GFSK MODULATION.....	32
9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION .....	32
9.7.3. ENHANCED DATA RATE 8PSK MODULATION .....	32
9.8. <i>CONDUCTED SPURIOUS EMISSIONS</i> .....	33
9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION .....	34
9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	36
<b>10. RADIATED TEST RESULTS .....</b>	<b>38</b>
10.1. <i>TRANSMITTER ABOVE 1 GHz</i> .....	40
10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION .....	40
10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION .....	47
10.2. <i>WORST CASE BELOW 1 GHZ</i> .....	54
<b>11. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>55</b>
11.1.1. AC Power Line.....	56
<b>12. SPOT-CHECK TEST RESULT .....</b>	<b>58</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SAMSUNG ELECTRONICS CO., LTD.  
**EUT DESCRIPTION:** GSM/WCDMA/LTE Phone + BT/BLE and DTS/UNII a/b/g/n/ac  
**MODEL:** SM-A135M/DS, SM-A135M  
**SERIAL NUMBER:** R38RB002TVY, R38RB002VFR (CONDUCTED, Original);  
R38RB01SY3Z (RADIATED, Original);  
R38RB00DXFZ, R38RB00DVEE (RADIATED, Spot-check);  
**DATE TESTED:** 2021-12-22 ~ 2022-01-21(Original);  
2022-01-14 ~ 2022-01-27(Spot-Check);

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Korea, Ltd. By:



Seokhwan Hong  
Suwon Lab Engineer  
UL Korea, Ltd.

Tested By:



Sungeun Lee  
Suwon Lab Engineer  
UL Korea, Ltd.

### 1.1. INTRODUCTION OF TEST DATA REUSE

This report referenced from the FCC ID: A3LSMA135M DSS BT (FCC CFR 47 Part 15C). And the applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID.

### 1.2. DIFFERENCE

The FCC ID: A3LSMA135M shares the same enclosure and circuit board as FCC ID: A3LSMA135FDSN. The BT antennas and surrounding circuitry and layout are identical between these two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMA135FDSN remains representative of FCC ID: A3LSMA135M. The test data of FCC ID: A3LSMA135FDSN being submitted for this application to cover BT features.

### 1.3. SPOT CHECK VERIFICATION SUMMARY DATA

(Worst case of the radiated band-edge and radiated spurious emissions)

Band	Test Item	Mode	Frequency	Test Limit	Original model	Spot check model	Deviation	Remark
					SM-A135F/DSN Results	SM-A135M/DS Results		
					FCC ID : A3LSMA135FDSN	FCC ID : A3LSMA135M		
DSS BT (2.4GHz)	Band Edge	GFSK 2480	2480 MHz	54 dBuV/m	42.77 dBuV/m	42.98 dBuV/m	0.21 dB	
	RSE	GFSK 2441	9764 MHz	74 dBuV/m	46.99 dBuV/m	48.32 dBuV/m	1.33 dB	Noise floor

Comparison of two models, upper deviation is within 3 dB range and all test results are under FCC Technical Limits. Please refer to the spot-check test result in section 12.

### 1.4. REFERENCE DETAIL

Reference application that contains the reused reference data in the individual test reports:

Equipment Class	Reference FCC ID (Parent)	Application Type	Reference Test report number	Exhibit Type	Variant Test Report Number	Data Re-used
DTS	A3LSMA135FDSN	Original Grant	4790215260-E3 (802.11b/g/n)	Test Report	4790215265-E3 (802.11b/g/n)	All
			4790215260-E4 Bluetooth LE	Test Report	4790215265-E4 Bluetooth LE	All
DSS	A3LSMA135FDSN	Original Grant	4790215260-E5 (Bluetooth)	Test Report	4790215265-E5 (Bluetooth)	All
NII	A3LSMA135FDSN	Original Grant	4790215260-E6 (802.11a/n/ac)	Test Report	4790215265-E6 (802.11a/n/ac)	All

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input checked="" type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

## 4. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.02 dB
Radiated Disturbance, 30 MHz to 1 GHz	4.05 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.78 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.58 dB

Uncertainty figures are valid to a confidence level of 95%.

### 4.4. DECISION RULES

Decision rule for statement(s) of conformity is based on Procedure 2, Clause 4.4.3 in IEC Guide 115:2007.



## 5. EQUIPMENT UNDER TEST

### 5.1. EUT DESCRIPTION

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac and NFC.  
This test report addresses the BT(DSS) operational mode.

This report covers the Samsung models SM-A135M/DS and SM-A135M.  
These models are identical in hardware except SM-A135M has single SIM tray.  
With some pre-scan, model SM-A135M/DS was set for final test.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 ~ 2 480	Basic GFSK	Peak	9.256	8.426
		Average	8.567	7.190
	Enhanced Pi/4-DPSK	Peak	9.458	8.827
		Average	7.160	5.200
	Enhanced 8PSK	Peak	<b>10.349</b>	<b>10.837</b>
		Average	7.181	5.225

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The internal antenna was Permanently attached.  
Therefore this E.U.T Complies with the requirement of §15.203.**

The radio utilizes an internal antennas, with ANT maximum gain of -5.04 dBi

## 5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance.

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA800	R37N9Q14289RT3	N/A
Data Cable	SAMSUNG	EP-DN980BWE (GH39-02115A, C to C)	N/A	N/A


### I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A


### TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests. Test software enable BT communications.

**SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)**



**SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	2022/08/19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	2022/08/13
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	2022/08/13
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	2023/10/06
Antenna, Horn, 18 GHz	ETS	3115	00167211	2022/07/27
Antenna, Horn, 18 GHz	ETS	3115	00161451	2022/08/15
Antenna, Horn, 18 GHz	ETS	3117	00168724	2022/07/27
Antenna, Horn, 18 GHz	ETS	3117	00168717	2022/08/15
Antenna, Horn, 40 GHz	ETS	3116C	00166155	2022/08/04
Preamplifier	ETS	3116C-PA	00168841	2022/08/04
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	80108-0004	N/A
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	110367-0003	N/A
Preamplifier, 1000 MHz	Sonoma	310N	341282	2022/08/02
Preamplifier, 1000 MHz	Sonoma	310N	351741	2022/08/02
Preamplifier, 1000 MHz	Sonoma	310N	370599	2022/08/02
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	2022/08/02
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	2022/08/02
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029168	2022/08/02
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	2022/08/04
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	2022/08/04
Average Power Sensor	Agilent / HP	U2000	MY54270007	2022/08/04
Average Power Sensor	Agilent / HP	U2000	MY54260010	2022/08/04
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	2022/08/04
Power Splitter	MINI-CIRCUITS	WA1534	UL003	2023/01/11
Power Splitter	MINI-CIRCUITS	WA1534	UL004	2023/01/11
Attenuator	PASTERNAK	PE7087-10	A009	2022/08/03
Attenuator	PASTERNAK	PE7087-10	A001	2022/08/03
Attenuator	PASTERNAK	PE7087-10	A008	2022/08/03
Attenuator	PASTERNAK	PE7004-10	2	2022/08/02
EMI Test Receive, 40 GHz	R&S	ESU40	100439	2022/08/02
EMI Test Receive, 40 GHz	R&S	ESU40	100457	2022/08/02
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	2022/08/02
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	2022/08/02
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	019	2022/08/02
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	2022/08/02
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	2022/08/02
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	2022/08/02
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	2022/08/02
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	2022/08/02
High Pass Filter 6GHz	Micro-Tronics	HPS17542	020	2022/08/02
LISN	R&S	ENV-216	101837	2022/08/05
Termination	WEINSCHEL	M1406A	T09	2022/08/03
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

## 7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247(d)	Band Edge / Conducted Spurious Emission	-20 dBc	Conducted	PASS
15.247 (b)(1)	TX conducted output power	< 21 dBm		PASS
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		PASS
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		PASS
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 8 dBm		PASS
15.207(a)	AC Power Line conducted emissions	Section 11	Power Line conducted	PASS
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	PASS

## 8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW : ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION : ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS : ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY : ANSI C63.10, Section 7.8.4

OUTPUT POWER : ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.6, 7.8.8

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 6.

Out-of-band EMISSIONS IN RESTRICTED BANDS : ANSI C63.10, Section 6.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.

## 9. ANTENNA PORT TEST RESULTS

### 9.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only.

#### PROCEDURE

ANSI C63.10, Section 11.6 : Zero-Span Spectrum Analyzer Method.

#### ON TIME AND DUTY CYCLE RESULTS



Mode	On time [msec]	Period [msec]	Duty Cycle [%]	Duty Cycle Correction Factor[dB]	1/T Minimum VBW [kHz]
<b>2 400 ~ 2 483.5 MHz Band</b>					
Bluetooth	2.877	3.752	76.679	1.15	0.35

## 9.2. 20 dB BANDWIDTH

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq 1\%$  of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled.

### RESULTS


#### 9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]
0	2 402	1.024
39	2 441	1.016
78	2 480	1.038
<b>Worst</b>		<b>1.038</b>


#### 9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]
0	2 402	1.341
39	2 441	1.341
78	2 480	1.334
<b>Worst</b>		<b>1.341</b>







**20 dB bandwidth / 0 CHANNEL**




**20 dB bandwidth / 0 CHANNEL**




**20 dB bandwidth / 39 CHANNEL**



**20 dB bandwidth / 39 CHANNEL**



**20 dB bandwidth / 78 CHANNEL**



**20 dB bandwidth / 78 CHANNEL**

### **9.3. HOPPING FREQUENCY SEPARATION**

#### **LIMITS**

FCC §15.247 (a) (1)

RSS-247 (5.1) (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to  $VBW \geq RBW$ . The sweep time is coupled.

#### **RESULTS**

### 9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



### 9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



## **9.4. NUMBER OF HOPPING CHANNELS**

### **LIMITS**

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


### **TEST PROCEDURE**

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


### **RESULTS**

Normal Mode: All Channels Observed


### 9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION




100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3




30MHz SPAN, SEGMENT 2 OF 3




30MHz SPAN, SEGMENT 3 OF 3


### 9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION




100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3



30MHz SPAN, SEGMENT 2 OF 3



30MHz SPAN, SEGMENT 3 OF 3

## 9.5. AVERAGE TIME OF OCCUPANCY

### LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 3.16 second period (79 channels \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$ .


For AFH mode, the average time of occupancy in the specified 8 second period (20 channels \* 0.4 seconds) is equal to  $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{ pulse width}$ .

### RESULTS


### 9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK ANT1 Normal					
DH1	0.373	32	0.119	0.4	-0.281
DH3	1.626	17	0.276	0.4	-0.124
DH5	2.876	12	0.345	0.4	-0.055
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK ANT1 AFH					
DH1	0.373	8	0.030	0.4	-0.370
DH3	1.626	4	0.069	0.4	-0.331
DH5	2.876	3	0.086	0.4	-0.314







**PULSE WIDTH – DH1**




**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1**




**PULSE WIDTH – DH3**



**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3**




**PULSE WIDTH – DH5**




**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5**

### 9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION


DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK ANT1 Normal					
DH1	0.385	32	0.123	0.4	-0.277
DH3	1.632	15	0.245	0.4	-0.155
DH5	2.881	11	0.317	0.4	-0.083
8PSK ANT1 AFH					
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK ANT1 AFH					
DH1	0.385	8	0.031	0.4	-0.369
DH3	1.632	4	0.061	0.4	-0.339
DH5	2.881	3	0.079	0.4	-0.321




**PULSE WIDTH – 3-DH1**




**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH1**




**PULSE WIDTH – 3-DH3**



**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH3**



**PULSE WIDTH – 3-DH5**



**NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH5**

## 9.6. OUTPUT POWER

### LIMITS

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

### RESULTS

#### 9.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
0	2 402	9.256	21.000	-11.744
39	2 441	8.987		-12.013
78	2 480	8.645		-12.355
Worst		<b>9.256</b>		<b>-11.744</b>

#### 9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION


Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
0	2 402	9.458	21.000	-11.542
39	2 441	9.196		-11.804
78	2 480	8.813		-12.187
Worst		<b>9.458</b>		<b>-11.542</b>


#### 9.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
0	2 402	10.349	21.000	-10.651
39	2 441	9.979		-11.021
78	2 480	9.593		-11.407
Worst		<b>10.349</b>		<b>-10.651</b>


### 9.6.4. OUTPUT POWER PLOTS

#### PEAK OUTPUT POWER







**0 CHANNEL**



**39 CHANNEL**



**78 CHANNEL**



## 9.7. AVERAGE POWER

### LIMITS

None; for reporting purposes only

### TEST PROCEDURE

Measurements perform using a wideband gated RF power meter.  
 The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

### RESULTS

#### 9.7.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
0	2 402	8.546	7.155
39	2 441	8.567	7.190
78	2 480	8.192	6.595

#### 9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
0	2 402	7.160	5.200
39	2 441	7.031	5.048
78	2 480	6.700	4.677

#### 9.7.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
0	2 402	7.181	5.225
39	2 441	7.054	5.075
78	2 480	6.727	4.707



## **9.8. CONDUCTED SPURIOUS EMISSIONS**

### **LIMITS**

FCC §15.247 (d)

Limit = -20 dBc

### **TEST PROCEDURE**

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The band-edges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


### **RESULTS**

### 9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION


#### SPURIOUS EMISSIONS, NON-HOPPING




**0 CHANNEL BANDEGE**




**OUT-OF-BAND 0 CHANNEL**




**IN-BAND REFERENCE LEVEL**



**OUT-OF-BAND 39 CHANNEL**




**78 CHANNEL BANDEGE**




**OUT-OF-BAND 78 CHANNEL**

**SPURIOUS BANDEGE EMISSIONS WITH HOPPING ON**




## 9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION


### SPURIOUS EMISSIONS, NON-HOPPING




**0 CHANNEL BANDEDGE**




**OUT-OF-BAND 0 CHANNEL**




**IN-BAND REFERENCE LEVEL**



**OUT-OF-BAND 39 CHANNEL**




**78 CHANNEL BANDEDGE**




**OUT-OF-BAND 78 CHANNEL**

**SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON**



**LOW BANDEDGE**



**HIGH BANDEDGE**

## 10. RADIATED TEST RESULTS

### LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

FCC Part 15.205 (a) : Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 – 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 – 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.17	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	167.72 ~ 173.2	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	240 ~ 285	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	322 ~ 335.4	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	399.90 ~ 410	3345.8 ~ 3358		
		608 ~ 614	3600 ~ 4400		
		960 ~ 1240			

▪ FCC Part 15.205(b) : The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

## **TEST PROCEDURE**

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements.(Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1/T (on time) for average measurement.

$$\text{GFSK} = 1/T = 1 / 0.00288\text{s} = 347\text{Hz}.$$

The minimum VBW was 347Hz, but test receiver(ESU40) couldn't set value 347Hz. Due to this reason, testing VBW was set to 500Hz(Worst cases).

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.  
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9kHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).  
Per FCC part 15.31(o), test results were not reported.


Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.  
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

## 10.1. TRANSMITTER ABOVE 1 GHz

### 10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

#### BANDEDGE (0 CHANNEL)

#### HORIZONTAL RESULT



#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.63	Pk		-20.6	51.93	-	-	74	-22.07	164	127	H
2	* 2.38813	43.89	Pk		-20.6	55.19	-	-	74	-18.81	164	127	H
3	* 2.39	30.52	VA1T		-20.6	41.82	54	-12.18	-	-	164	127	H
4	* 2.38364	30.96	VA1T		-20.6	42.26	54	-11.74	-	-	164	127	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average  $VB=1/Ton$  where: Ton is transmit duration



### VERTICAL RESULT




### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.17	Pk	31.9	-20.6	53.47	-	-	74	-20.53	202	359	V
2	* 2.33912	44.03	Pk	31.8	-20.7	55.13	-	-	74	-18.87	202	359	V
3	* 2.39	30.4	VA1T	31.9	-20.6	41.7	54	-12.3	-	-	202	359	V
4	* 2.37989	31.07	VA1T	31.9	-20.6	42.37	54	-11.63	-	-	202	359	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

**BANDEDGE (78 CHANNEL)**

**HORIZONTAL RESULT**




**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	41.5	Pk	32	-20.4	53.1	-	-	74	-20.9	173	268	H
2	2.56035	43.9	Pk	32.2	-20.2	55.9	-	-	74	-18.1	173	268	H
3	* 2.48351	30.9	VA1T	32	-20.4	42.5	54	-11.5	-	-	173	268	H
4	* 2.48839	31.07	VA1T	32.1	-20.4	42.77	54	-11.23	-	-	173	268	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

### VERTICAL RESULT




### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	40.15	Pk	32	-20.4	51.75	-	-	74	-22.25	189	100	V
2	2.54343	44.18	Pk	32.1	-20.3	55.98	-	-	74	-18.02	189	100	V
3	* 2.48351	30.76	VA1T	32	-20.4	42.36	54	-11.64	-	-	189	100	V
4	2.54019	30.96	VA1T	32.1	-20.3	42.76	54	-11.24	-	-	189	100	V


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

# HARMONICS AND SPURIOUS EMISSIONS

## 0 CHANNEL RESULTS



### HORIZONTAL




### VERTICAL

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP(dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.80056	35.69	PKFH	34.1	-28	41.79	-	-	74	-32.21	0	100	H
* 4.80499	36.4	PKFH	34.1	-28	42.5	-	-	74	-31.5	0	100	V
7.19644	34.06	PKFH	36.2	-25.3	44.96	-	-	74	-29.04	0	100	H
7.19654	33.59	PKFH	36.2	-25.3	44.49	-	-	74	-29.51	0	100	V
9.60997	31.48	PKFH	37	-21.7	46.78	-	-	74	-27.22	0	100	H
9.61437	32	PKFH	37	-21.7	47.3	-	-	74	-26.7	0	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

### 39 CHANNEL RESULTS



### HORIZONTAL




### VERTICAL

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.87483	35.52	PKFH	34.1	-27.9	41.72	-	-	74	-32.28	0	100	H
* 4.88967	35.98	PKFH	34.1	-27.7	42.38	-	-	74	-31.62	0	100	V
* 7.32065	33.96	PKFH	36.1	-24.8	45.26	-	-	74	-28.74	0	100	H
* 7.32624	34.35	PKFH	36.1	-24.9	45.55	-	-	74	-28.45	0	100	V
9.76832	31.29	PKFH	37.2	-21.5	46.99	-	-	74	-27.01	0	100	H
9.76979	31.49	PKFH	37.2	-21.5	47.19	-	-	74	-26.81	0	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

### 78 CHANNEL RESULTS



### HORIZONTAL



### VERTICAL

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96522	35.28	PKFH	34.1	-27.2	42.18	-	-	74	-31.82	0	100	H
* 4.95061	35.5	PKFH	34.1	-27.2	42.4	-	-	74	-31.6	0	100	V
* 7.44292	33.58	PKFH	36	-24.1	45.48	-	-	74	-28.52	0	100	H
* 7.44557	33.2	PKFH	36	-24.1	45.1	-	-	74	-28.9	0	100	V
9.91521	31.25	PKFH	37.4	-21.3	47.35	-	-	74	-26.65	0	100	H
9.91868	31.43	PKFH	37.4	-21.3	47.53	-	-	74	-26.47	0	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

## 10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

### BANDEDGE (0 CHANNEL)

#### HORIZONTAL RESULT




#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.44	Pk	31.9	-20.6	52.74	-	-	74	-21.26	136	100	H
2	* 2.33391	44.23	Pk	31.8	-20.7	55.33	-	-	74	-18.67	136	100	H
3	* 2.39	30.83	VA1T	31.9	-20.6	42.13	54	-11.87	-	-	136	100	H
4	* 2.37156	31.26	VA1T	31.8	-20.6	42.46	54	-11.54	-	-	136	100	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

### VERTICAL RESULT




### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.59	Pk	31.9	-20.6	52.89	-	-	74	-21.11	181	100	V
2	* 2.36682	44.1	Pk	31.8	-20.6	55.3	-	-	74	-16.7	181	100	V
3	* 2.39	30.63	VA1T	31.9	-20.6	41.93	54	-12.07	-	-	181	100	V
4	* 2.38721	31.01	VA1T	31.9	-20.5	42.41	54	-11.59	-	-	181	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration



**BANDEDGE (78 CHANNEL)**




**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	43.51	Pk	32	-20.4	55.11	-	-	74	-18.89	177	189	H
2	* 2.48368	50.53	Pk	32	-20.4	62.13	-	-	74	-11.87	177	189	H
3	* 2.48351	31.51	VA1T	32	-20.4	43.11	54	-10.89	-	-	177	189	H
4	* 2.48366	31.82	VA1T	32	-20.4	43.42	54	-10.58	-	-	177	189	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

### VERTICAL RESULT




### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	43.82	Pk	32	-20.4	55.42	-	-	74	-18.58	135	101	V
2	2.52129	44.29	Pk	32.1	-20.3	56.09	-	-	74	-17.91	135	101	V
3	* 2.48351	31.15	VA1T	32	-20.4	42.75	54	-11.25	-	-	135	101	V
4	* 2.48354	31.14	VA1T	32	-20.4	42.74	54	-11.26	-	-	135	101	V


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector  
 VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

# HARMONICS AND SPURIOUS EMISSIONS

## 0 CHANNEL RESULTS



### HORIZONTAL




### VERTICAL

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.8041	35.22	PKFH	34.1	-28	41.32	-	-	74	-32.68	0	100	H
* 4.81121	35.93	PKFH	34.1	-28	42.03	-	-	74	-31.97	0	100	V
7.20463	33.97	PKFH	36.2	-25.3	44.87	-	-	74	-29.13	0	100	H
7.21185	34.16	PKFH	36.2	-25.4	44.96	-	-	74	-29.04	0	100	V
9.60785	32.51	PKFH	37	-21.7	47.81	-	-	74	-26.19	0	100	H
9.61425	31.88	PKFH	37	-21.7	47.18	-	-	74	-26.82	0	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

### 39 CHANNEL RESULTS



### HORIZONTAL




### VERTICAL

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP(dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88003	35.65	PKFH	34.1	-27.8	41.95	-	-	74	-32.05	0	100	H
* 4.87487	35.81	PKFH	34.1	-27.9	42.01	-	-	74	-31.99	0	100	V
* 7.33097	34.89	PKFH	36.1	-24.8	46.19	-	-	74	-27.81	0	100	H
* 7.32016	35.06	PKFH	36.1	-24.9	46.26	-	-	74	-27.74	0	100	V
9.75507	31.39	PKFH	37.2	-21.4	47.19	-	-	74	-26.81	0	100	H
9.75754	31.9	PKFH	37.2	-21.5	47.6	-	-	74	-26.4	0	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

### 78 CHANNEL RESULTS



### HORIZONTAL




### VERTICAL

### Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP(dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.96114	35.35	PKFH	34.1	-27.2	42.25	-	-	74	-31.75	0	100	H
* 4.96496	35.02	PKFH	34.1	-27.2	41.92	-	-	74	-32.08	0	100	V
* 7.4415	33.33	PKFH	36	-24.1	45.23	-	-	74	-28.77	0	100	H
* 7.43569	33.33	PKFH	36	-24	45.33	-	-	74	-28.67	0	100	V
9.91921	30.53	PKFH	37.4	-21.3	46.63	-	-	74	-27.37	0	100	H
9.91296	31.17	PKFH	37.4	-21.3	47.27	-	-	74	-26.73	0	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

## 10.2. WORST CASE BELOW 1 GHZ SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



HORIZONTAL



VERTICAL

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_749	Below 1G[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	47.46	37.3	Pk	19.8	-31.7	25.4	40	-14.6	0-360	200	H
2	* 135.536	44.47	Pk	13.8	-31.1	27.17	43.52	-16.35	0-360	300	H
3	223.709	41.1	Pk	17.2	-30.7	27.6	46.02	-18.42	0-360	100	H
4	50.467	44.77	Pk	19.9	-31.8	32.87	40	-7.13	0-360	100	V
5	* 123.993	40.77	Pk	14.9	-31.2	24.47	43.52	-19.05	0-360	100	V
6	* 255.137	42.88	Pk	18.4	-30.5	30.78	46.02	-15.24	0-360	100	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector

## 11. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

RSS-Gen 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 <sup>*</sup>	56 to 46 <sup>*</sup>
0.5-5	56	46
5-30	60	50

<sup>\*</sup> Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10:2013.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

### RESULTS

### 11.1.1. AC Power Line

#### LINE 1 RESULTS



#### Trace Markers

Range 1: Phase L1 .15 - 30MHz


Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_L1[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.189	39.66	Pk	9.9	.2	49.76	64.08	-14.32	-	-
2	.189	25.47	Av	9.9	.2	35.57	-	-	54.08	-18.51
3	.237	33.67	Pk	9.7	.2	43.57	62.2	-18.63	-	-
4	.237	20.43	Av	9.7	.2	30.33	-	-	52.2	-21.87
5	.654	32.06	Pk	9.8	.2	42.06	56	-13.94	-	-
6	.651	23.99	Av	9.8	.2	33.99	-	-	46	-12.01
7	.693	28.99	Pk	9.8	.2	38.99	56	-17.01	-	-
8	.693	22.52	Av	9.8	.2	32.52	-	-	46	-13.48
9	3.288	25.57	Pk	9.7	.3	35.57	56	-20.43	-	-
10	3.288	14.7	Av	9.7	.3	24.7	-	-	46	-21.3
11	6.12	25.17	Pk	9.7	.3	35.17	60	-24.83	-	-
12	6.108	13.15	Av	9.7	.3	23.15	-	-	50	-26.85

Pk - Peak detector

Av - Average detection



### LINE 2 RESULTS



#### Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	101836_With EX_N[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.186	38.59	Pk	9.9	.2	48.69	64.21	-15.52	-	-
14	.186	21.83	Av	9.9	.2	31.93	-	-	54.21	-22.28
15	.234	33.25	Pk	9.7	.2	43.15	62.31	-19.16	-	-
16	.234	17.52	Av	9.7	.2	27.42	-	-	52.31	-24.89
17	.639	36.45	Pk	9.8	.2	46.45	56	-9.55	-	-
18	.645	25.73	Av	9.8	.2	35.73	-	-	46	-10.27
19	.687	32.23	Pk	9.8	.2	42.23	56	-13.77	-	-
20	.69	22.94	Av	9.8	.2	32.94	-	-	46	-13.06
21	3.3	31.24	Pk	9.7	.3	41.24	56	-14.76	-	-
22	3.3	16.49	Av	9.7	.3	26.49	-	-	46	-19.51
23	5.433	30.33	Pk	9.7	.3	40.33	60	-19.67	-	-
24	5.433	15.68	Av	9.7	.3	25.68	-	-	50	-24.32

Pk - Peak detector  
 Av - Average detection

#### Quasi-Peak Emissions


Range 2: Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBUV)	Det	101836_With EX_N[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
.63825	34.64	Qp	9.8	.2	44.64	56	-11.36	-	-
.64575	32.77	Qp	9.8	.2	42.77	56	-13.23	-	-

Qp - Quasi-Peak detector

## 12. SPOT-CHECK TEST RESULT

### BANDEDGE (WORST CASE: GFSK / 2480 MHz)



### Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	44.93	Pk	32	-20.4	56.53	-	-	74	-17.47	178	108	H
2	* 2.4867	47.78	Pk	32	-20.4	59.38	-	-	74	-14.62	178	108	H
3	* 2.48351	31.23	VA1T	32	-20.4	42.83	54	-11.17	-	-	178	108	H
4	* 2.48356	31.38	VA1T	32	-20.4	42.98	54	-11.02	-	-	178	108	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

**HARMONICS AND SPURIOUS EMISSIONS(WORST CASE: GFSK / 2441 MHz)**  
**2441 MHz HORIZONTAL**



**2441 MHz VERTICAL**



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**Radiated Emissions**

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
9.76008	32.62	PKFH	37.2	-21.5	48.32	-	-	74	-25.68	0	100	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

**END OF TEST REPORT**