

PART 22 & 90 MEASUREMENT REPORT

Applicant Name:
 Samsung Electronics Co., Ltd.
 129, Samsung-ro,
 Yeongtong-gu, Suwon-si
 Gyeonggi-do, 16677, Korea

Date of Testing:
 9/8/2023 - 11/22/2023
Test Report Issue Date:
 11/22/2023
Test Site/Location:
 Element lab., Columbia, MD, USA
Test Report Serial No.:
 1M2309070105-05.A3L

FCC ID:	A3LSMA156E
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type: Certification
Model: SM-A156E/DS
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part: §22(H), §90(S), §90(R)
Test Procedure(s): ANSI C63.26-2015

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortanez
 Executive Vice President



FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 1 of 49

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	Software and Firmware	5
2.5	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS	10
7.1	Summary.....	10
7.2	Conducted Output Power Data	11
7.3	Occupied Bandwidth	13
7.4	Spurious and Harmonic Emissions at Antenna Terminal	26
7.5	Band Edge Emissions at Antenna Terminal	31
7.6	Radiated Power (ERP).....	36
7.7	Radiated Spurious Emissions Measurements.....	39
7.8	Frequency Stability / Temperature Variation	46
8.0	CONCLUSION.....	49

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 2 of 49

MEASUREMENT REPORT

FCC Part 22 & 90

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Measurement	Max. Power [W]	Max. Power [dBm]	Emission Designator
LTE Band 26	15 MHz	QPSK	821.5	ERP	0.081	19.11	13M5G7D
		16QAM	821.5	ERP	0.072	18.56	13M5W7D
	15 MHz	QPSK	821.5	Conducted	0.257	24.10	13M5G7D
		16QAM	821.5	Conducted	0.218	23.39	13M5W7D
	10 MHz	QPSK	819.0	Conducted	0.250	23.98	8M98G7D
		16QAM	819.0	Conducted	0.217	23.36	8M99W7D
	5 MHz	QPSK	816.5 - 821.5	Conducted	0.256	24.08	4M51G7D
		16QAM	816.5 - 821.5	Conducted	0.226	23.55	4M51W7D
	3 MHz	QPSK	815.5 - 822.5	Conducted	0.254	24.04	2M70G7D
		16QAM	815.5 - 822.5	Conducted	0.233	23.68	2M71W7D
	1.4 MHz	QPSK	814.7 - 823.3	Conducted	0.251	24.00	1M10G7D
		16QAM	814.7 - 823.3	Conducted	0.219	23.41	1M10W7D
NR Band n26	20 MHz	$\pi/2$ BPSK	824.0	ERP	0.060	17.80	18M0G7D
		QPSK	824.0	ERP	0.060	17.81	19M1G7D
		16QAM	824.0	ERP	0.050	17.01	19M0W7D
	15 MHz	$\pi/2$ BPSK	821.5	ERP	0.069	18.38	13M5G7D
		QPSK	821.5	ERP	0.067	18.28	14M2G7D
		16QAM	821.5	ERP	0.057	17.58	14M2W7D
	20 MHz	$\pi/2$ BPSK	824.0	Conducted	0.262	24.18	18M0G7D
		QPSK	824.0	Conducted	0.254	24.05	19M1G7D
		16QAM	824.0	Conducted	0.216	23.35	19M0W7D
	15 MHz	$\pi/2$ BPSK	821.5	Conducted	0.256	24.08	13M5G7D
		QPSK	821.5	Conducted	0.261	24.17	14M2G7D
		16QAM	821.5	Conducted	0.211	23.24	14M2W7D
	10 MHz	$\pi/2$ BPSK	819.0	Conducted	0.261	24.17	9M03G7D
		QPSK	819.0	Conducted	0.260	24.15	9M31G7D
		16QAM	819.0	Conducted	0.213	23.28	9M34W7D
	5 MHz	$\pi/2$ BPSK	816.5 - 821.5	Conducted	0.268	24.28	4M52G7D
		QPSK	816.5 - 821.5	Conducted	0.265	24.23	4M52G7D
		16QAM	816.5 - 821.5	Conducted	0.229	23.59	4M52W7D

EUT Overview

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 3 of 49

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreement.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 4 of 49

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA156E**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 90 and 22H.

Test Device Serial No.: 1958M, 0441M, 0447M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-band 5G NR (FR1), 802.11b/g/n WLAN, 802.11a/n/ac UNII (5GHz), Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 Software and Firmware

Testing was performed on device(s) using software/firmware version A156EDXE0AWI4 installed on the EUT.

2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 5 of 49

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the “American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services” (ANSI C63.26-2015) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI C63.26-2015. For emissions below 1GHz, a half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]};$$

where P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

For radiated spurious emissions measurements, the field strength conversion method is used per the formulas in Section 5.2.7 of ANSI C63.26-2015. Field Strength (EIRP) is calculated using the following formulas:

$$E_{\text{[dB}\mu\text{V/m]}} = \text{Measured amplitude level}_{\text{[dBm]}} + 107 + \text{Cable Loss}_{\text{[dB]}} + \text{Antenna Factor}_{\text{[dB/m]}}$$

And

$$\text{EIRP}_{\text{[dBm]}} = E_{\text{[dB}\mu\text{V/m]}} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 6 of 49

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 7 of 49

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	AP2-001	EMC Cable and Switch System	1/11/2023	Annual	1/11/2024	AP2-001
-	AP2-002	EMC Cable and Switch System	1/11/2023	Annual	1/11/2024	AP2-002
-	ETS-001	EMC Cable and Switch System	1/11/2023	Annual	1/11/2024	ETS-001
-	ETS-002	EMC Cable and Switch System	1/11/2023	Annual	1/11/2024	ETS-002
-	LTX4	Licensed Transmitter Cable Set	1/12/2023	Annual	1/12/2024	LTX4
-	LTX5	Licensed Transmitter Cable Set	1/12/2023	Annual	1/12/2024	LTX5
Anritsu	MT8821C	Radio Communication Analyzer	N/A			620152694
Com-Power	AL-130R	9kHz - 30MHz Loop Antenna	1/18/2022	Biennial	1/19/2024	121085
EMCO	3115	Horn Antenna (1-18GHz)	8/8/2022	Biennial	8/8/2024	9704-5182
EMCO	3116	Horn Antenna (18-40GHz)	7/5/2023	Biennial	7/5/2025	9203-2178
Keysight Technologies	N9030A	PXA Signal Analyzer (3Hz-26.5GHz)	8/7/2023	Annual	8/7/2024	MYS4490576
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	3/15/2023	Annual	3/15/2024	MYS2350166
Rohde & Schwarz	CMM500	Radio Communication Tester	N/A			112347
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Test Antenna	9/28/2022	Biennial	9/28/2024	101058
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	9/25/2023	Annual	9/25/2024	100342
Rohde & Schwarz	ESW44	EMI Test Receiver (2Hz-44GHz)	3/1/2023	Annual	3/1/2024	101716
Rohde & Schwarz	VULB9162	Bi-Log Antenna	2/21/2023	Biennial	2/21/2025	00301
Sunol	DRH-118	Horn Antenna (1-18GHz)	2/14/2022	Biennial	2/14/2024	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	8/30/2022	Biennial	8/30/2024	A051107

Table 5-1. Test Equipment

Notes:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 8 of 49

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 9 of 49

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA156E
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE, NR

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Transmitter Conducted Output Power*	2.1046(a), 90.635(b)	< 100 Watts	PASS	Section 7.2
	Occupied Bandwidth	2.1049(h)	N/A	PASS	Section 7.3
	Conducted Band Edge / Spurious Emissions (LTE Band 26, NR Band n26)	2.1051, 90.691(a)	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions except emissions beyond 37.5kHz from the block edge > 50 + 10 log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	PASS	Sections 7.4, 7.5
	Peak-to-Average Ratio	N/A	≤ 13 dB	PASS	Section 7.6
	Frequency Stability	2.1055, 90.213	< 2.5 ppm **Fundamental emissions stay within authorized frequency block	PASS	Section 7.9
RADIATED	Effective Radiated Power (LTE Band 26, NR Band n26)	22.913(a)(2)	< 7 Watts max. ERP	PASS	Section 7.7
	Radiated Spurious Emissions (LTE Band 26, NR Band n26)	2.1053, 90.691(a)	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions except emissions beyond 37.5kHz from the block edge > 50 + 10 log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	PASS	Section 7.8

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is EMC Software Tool v1.2.2.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 10 of 49

7.2 Conducted Output Power Data

Test Overview

All emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

Test Procedure Used

ANSI C63.26-2015 – Section 5.2

Test Settings

1. Span = 2 x OBW to 3 x OBW
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. For LTE/NR modes, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst-case emissions are reported with 1 RB.
2. Conducted power measurements were evaluated using various combinations of RB size, RB offset, modulation, and channel bandwidth. Channel bandwidth data is shown in the tables below based only on the channel bandwidths that were supported in this device.
3. Conducted power was found to reduce for the higher order QAM modulations when compared to 16QAM. Due to this trend, only the worst-case QAM (16QAM) powers are included in this section.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 11 of 49

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
15 MHz	QPSK	26765	821.5	1 / 37	24.10	0.257	50.00	-25.90
	16-QAM	26765	821.5	1 / 37	23.39	0.218	50.00	-26.61
10 MHz	QPSK	26740	819.0	1 / 25	23.98	0.250	50.00	-26.02
	16-QAM	26740	819.0	1 / 0	23.36	0.217	50.00	-26.64
5 MHz	QPSK	26715	816.5	1 / 12	24.08	0.256	50.00	-25.92
		26765	821.5	1 / 12	23.92	0.247	50.00	-26.08
	16-QAM	26715	816.5	1 / 0	23.55	0.226	50.00	-26.45
		26765	821.5	1 / 12	23.36	0.217	50.00	-26.64
3 MHz	QPSK	26705	815.5	1 / 14	23.98	0.250	50.00	-26.02
		26775	822.5	1 / 14	24.04	0.254	50.00	-25.96
	16-QAM	26705	815.5	1 / 7	23.68	0.233	50.00	-26.32
		26775	822.5	1 / 14	23.33	0.215	50.00	-26.67
1.4 MHz	QPSK	26697	814.7	1 / 5	23.87	0.244	50.00	-26.13
		26783	823.3	1 / 5	24.00	0.251	50.00	-26.00
	16-QAM	26697	814.7	1 / 3	23.22	0.210	50.00	-26.78
		26783	823.3	1 / 3	23.41	0.219	50.00	-26.59

Table 7-2. Conducted Power Output Data (LTE Band 26)

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
20 MHz	$\pi/2$ BPSK	164800	824.0	1 / 53	24.18	0.262	50.00	-25.82
	QPSK	164800	824.0	1 / 53	24.05	0.254	50.00	-25.95
	16-QAM	164800	824.0	1 / 53	23.35	0.216	50.00	-26.65
15 MHz	$\pi/2$ BPSK	164300	821.5	1 / 39	24.08	0.256	50.00	-25.92
	QPSK	164300	821.5	1 / 39	24.17	0.261	50.00	-25.83
	16-QAM	164300	821.5	1 / 39	23.24	0.211	50.00	-26.76
10 MHz	$\pi/2$ BPSK	163800	819.0	1 / 50	24.17	0.261	50.00	-25.83
	QPSK	163800	819.0	1 / 50	24.15	0.260	50.00	-25.85
	16-QAM	163800	819.0	1 / 50	23.28	0.213	50.00	-26.72
5 MHz	$\pi/2$ BPSK	163300	816.5	1 / 12	24.28	0.268	50.00	-25.72
		164300	821.5	1 / 23	24.16	0.261	50.00	-25.84
	QPSK	163300	816.5	1 / 12	24.07	0.255	50.00	-25.93
		164300	821.5	1 / 23	24.23	0.265	50.00	-25.77
	16-QAM	163300	816.5	1 / 12	23.59	0.229	50.00	-26.41
		164300	821.5	1 / 23	23.28	0.213	50.00	-26.72

Table 7-3. Conducted Power Output Data (NR Band n26)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 12 of 49

7.3 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.26-2015 – Section 5.4.4

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes

None.


FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 13 of 49

Mode	Bandwidth	Modulation	OBW [MHz]
LTE Band 26	15 MHz	QPSK	13.45
		16QAM	13.47
	15 MHz	QPSK	13.45
		16QAM	13.47
	10 MHz	QPSK	8.98
		16QAM	8.99
	5 MHz	QPSK	4.51
		16QAM	4.51
	3 MHz	QPSK	2.70
		16QAM	2.71
	1.4 MHz	QPSK	1.10
		16QAM	1.10
NR Band n26	20 MHz	$\pi/2$ BPSK	18.04
		QPSK	19.06
		16QAM	19.04
	15 MHz	$\pi/2$ BPSK	13.52
		QPSK	14.17
		16QAM	14.23
	20 MHz	$\pi/2$ BPSK	18.04
		QPSK	19.06
		16QAM	19.04
	15 MHz	$\pi/2$ BPSK	13.52
		QPSK	14.17
		16QAM	14.23
	10 MHz	$\pi/2$ BPSK	9.03
		QPSK	9.31
		16QAM	9.34
5 MHz	$\pi/2$ BPSK	4.52	
	QPSK	4.52	
	16QAM	4.52	


Table 7-4. Occupied Bandwidth Test Results

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 14 of 49

LTE Band 26




Plot 7-1. Occupied Bandwidth Plot (LTE Band 26 - 15MHz QPSK - Full RB)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 16-QAM - Full RB)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 15 of 49




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 16 of 49




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 17 of 49




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMA156E		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset		Page 18 of 49




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB)



Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB)

FCC ID: A3LSMA156E		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset		Page 19 of 49

NR Band n26




Plot 7-11. Occupied Bandwidth Plot (NR Band n26 - 20MHz $\pi/2$ BPSK - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (NR Band n26 - 20MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA156E		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset		Page 20 of 49




Plot 7-13. Occupied Bandwidth Plot (NR Band n26 - 20MHz 16-QAM - Full RB Configuration)



Plot 7-14. Occupied Bandwidth Plot (NR Band n26 - 15MHz $\pi/2$ BPSK - Full RB Configuration)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 21 of 49




Plot 7-15. Occupied Bandwidth Plot (NR Band n26 - 15MHz QPSK - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (NR Band n26 - 15MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 22 of 49




Plot 7-17. Occupied Bandwidth Plot (NR Band n26 - 10MHz $\pi/2$ BPSK - Full RB Configuration)




Plot 7-18. Occupied Bandwidth Plot (NR Band n26 - 10MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA156E		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset		Page 23 of 49




Plot 7-19. Occupied Bandwidth Plot (NR Band n26 - 10MHz 16-QAM - Full RB Configuration)



Plot 7-20. Occupied Bandwidth Plot (NR Band n26 - 5MHz $\pi/2$ BPSK - Full RB Configuration)

FCC ID: A3LSMA156E		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset		Page 24 of 49



Plot 7-21. Occupied Bandwidth Plot (NR Band n26 - 5MHz QPSK - Full RB Configuration)



Plot 7-22. Occupied Bandwidth Plot (NR Band n26 - 5MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA156E		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset		Page 25 of 49

7.4 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

ANSI C63.26-2015 – Section 5.7.4

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW \geq 100kHz
3. VBW \geq 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


1. Per Part 22H and 90, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.
2. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 26 of 49

LTE Band 26




Plot 7-23. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - 1RB)



Plot 7-24. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - 1RB)


FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 27 of 49




Plot 7-25. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - 1RB)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 28 of 49

NR Band n26




Plot 7-26. Conducted Spurious Plot (NR Band n26 - 20MHz QPSK – 1RB)



Plot 7-27. Conducted Spurious Plot (NR Band n26 - 20MHz QPSK - 1RB)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 29 of 49



Plot 7-28. Conducted Spurious Plot (NR Band n26 - 20MHz QPSK - 1RB)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 30 of 49

7.5 Band Edge Emissions at Antenna Terminal

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee’s frequency block by greater than 37.5 kHz is $43 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee’s frequency block by up to and including 37.5 kHz is $50 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

ANSI C63.26-2015 – Section 5.7.3

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 31 of 49

Test Notes

1. For channel edge emission, the signal analyzer’s “ACP” measurement capability is used.
2. Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
3. For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.


FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 32 of 49

Mode	Bandwidth	Channel	Test Case	Level [dBm]	Limit [dBm]	Margin [dB]
LTE B26	15MHz	Mid	Band Edge	-37.68	-20	-17.68
	10MHz	Mid	Band Edge	-37.47	-20	-17.47
	5MHz	Low	Band Edge	-31.80	-20	-11.80
		High	Band Edge	-31.23	-20	-11.23
	3MHz	Low	Band Edge	-30.92	-20	-10.92
		High	Band Edge	-30.41	-20	-10.41
	1.4MHz	Low	Band Edge	-26.99	-20	-6.99
		High	Band Edge	-26.18	-20	-6.18
NR n26	20MHz	Mid	Band Edge	-36.14	-20	-16.14
	15MHz	Mid	Band Edge	-36.98	-20	-16.98
	10MHz	Mid	Band Edge	-35.15	-20	-15.15
	5MHz	Low	Band Edge	-31.73	-20	-11.73
		High	Band Edge	-31.99	-20	-11.99


Table 7-5. Band Edge Test Results

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 33 of 49

LTE Band 26




Plot 7-29. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - Low Channel)




Plot 7-30. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - High Channel)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 34 of 49

NR Band n26



Plot 7-31. Channel Edge Plot (NR Band n26 - 5MHz QPSK - Low Channel)



Plot 7-32. Channel Edge Plot (NR Band n26 - 5MHz QPSK - High Channel)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 35 of 49



7.6 Radiated Power (ERP)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

ANSI C63.26-2015 – Section 5.2.4.4

Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”.
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 36 of 49

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup > 1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 37 of 49

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
15 MHz	QPSK	821.50	H	205	303	1.30	1 / 74	19.96	19.11	0.081	38.45	-19.34
	16-QAM	821.50	H	205	303	1.30	1 / 74	19.41	18.56	0.072	38.45	-19.89

Table 7-6. ERP Data (LTE Band 26)

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
20 MHz	$\pi/2$ BPSK	824.00	H	247	292	1.34	1 / 1	18.61	17.80	0.060	38.45	-20.65
	QPSK	824.00	H	247	292	1.34	1 / 1	18.62	17.81	0.060	38.45	-20.64
	16-QAM	824.00	H	247	292	1.34	1 / 1	17.82	17.01	0.050	38.45	-21.44
15 MHz	$\pi/2$ BPSK	821.50	H	137	292	1.30	1 / 1	19.23	18.38	0.069	38.45	-20.07
	QPSK	821.50	H	137	292	1.30	1 / 1	19.13	18.28	0.067	38.45	-20.17
	16-QAM	821.50	H	137	292	1.30	1 / 1	18.43	17.58	0.057	38.45	-20.87

Table 7-7. ERP Data (NR Band n26)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 38 of 49



7.7 Radiated Spurious Emissions Measurements

Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using hybrid (biconical/log) antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

ANSI C63.26-2015 – Section 5.5.4

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 39 of 49

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup < 1GHz




Figure 7-8. Test Instrument & Measurement Setup >1 GHz


FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 40 of 49

Test Notes

- 1) Field strengths are calculated using the Measurement quantity conversions in ANSI C63.26-2015 Section 5.2.7:
 - a) $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
 - b) $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$; where D is the measurement distance in meters.
- 2) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 3) This unit was tested with its standard battery.
- 4) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 5) Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
- 6) The "-" shown in the following RSE tables are used to denote a noise floor measurement.
- 7) For NR operation, all subcarrier spacings (SCS) and transmission schemes (e.g. CP-OFDM and DFT-s-OFDM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.
- 8) Spurious emissions shown in this section are measured while operating in EN-DC mode with Sub 6GHz NR carrier as well as an LTE carrier (anchor). Spurious emissions from the NR carrier device are subject to the rules under which the NR carrier operates. Spurious emissions caused by the LTE carrier must meet the requirements of the rules under which the LTE carrier operates.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 41 of 49

LTE Band 26




Plot 7-33. Radiated Spurious Plot Below 1GHz (LTE Band 26)

Bandwidth (MHz):	10
Frequency (MHz):	819
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	ERP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
926.29	V	-	-	-79.72	2.46	29.74	-67.67	-13.00	-54.67

Table 7-8. Radiated Spurious Data Below 1GHz (LTE Band 26)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 42 of 49



Plot 7-34. Radiated Spurious Plot Above 1GHz (LTE Band 26)


Bandwidth (MHz):	10
Frequency (MHz):	819
RB Config (Size / Offset):	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1638.00	V	-	-	-78.01	-0.32	28.67	-66.59	-13.00	-53.59
2457.00	V	368	158	-77.50	3.81	33.31	-61.94	-13.00	-48.94
3276.00	V	142	354	-78.46	6.17	34.71	-60.55	-13.00	-47.55
4095.00	V	155	154	-71.96	8.01	43.05	-52.21	-13.00	-39.21
4914.00	V	227	317	-77.67	9.58	38.91	-56.35	-13.00	-43.35
5733.00	V	143	5	-79.54	12.04	39.50	-55.75	-13.00	-42.75
6552.00	V	121	340	-79.52	13.47	40.95	-54.31	-13.00	-41.31
7371.00	V	319	358	-79.08	15.41	43.33	-51.92	-13.00	-38.92

Table 7-9. Radiated Spurious Data Above 1GHz (LTE Band 26)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 43 of 49

NR Band n26




Plot 7-35. Radiated Spurious Plot Below 1GHz (NR Band n26)

Bandwidth (MHz):	15
Frequency (MHz):	821.5
RB / Offset:	1 / 39

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	ERP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
124.32	V	-	-	-83.31	20.32	44.01	-53.39	-13.00	-40.39
190.57	V	-	-	-83.15	18.84	42.69	-54.72	-13.00	-41.72
487.64	V	-	-	-83.08	25.73	49.65	-47.76	-13.00	-34.76

Table 7-10. Radiated Spurious Data Below 1GHz (NR Band n26)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 44 of 49



Plot 7-36. Radiated Spurious Plot Above 1GHz (NR Band n26)

Bandwidth (MHz):	15
Frequency (MHz):	821.5
RB / Offset:	1 / 39

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dB μ V/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.00	V	291	204	-74.85	-7.22	24.93	-70.33	-13.00	-57.33
2464.50	V	-	-	-75.76	-4.20	27.04	-68.21	-13.00	-55.21
3286.00	V	128	333	-71.91	-0.91	34.18	-61.08	-13.00	-48.08
4107.50	V	134	56	-71.08	1.92	37.84	-57.42	-13.00	-44.42
4929.00	V	139	136	-70.15	2.61	39.46	-55.80	-13.00	-42.80
5750.50	V	130	127	-74.12	4.95	37.83	-57.43	-13.00	-44.43
6572.00	V	333	358	-76.47	6.90	37.43	-57.83	-13.00	-44.83
7393.50	V	-	-	-78.32	9.45	38.13	-57.12	-13.00	-44.12

Table 7-11. Radiated Spurious Data Above 1GHz (NR Band n26)

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 45 of 49



7.8 Frequency Stability / Temperature Variation

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Test Procedure Used

ANSI C63.26-2015 – Section 5.6

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.


Test Notes

None

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 46 of 49

LTE Band 26					
Operating Frequency (Hz):		821,500,000			
Ref. Voltage (VDC):		4.331			
Deviation Limit:		± 0.00025% or 2.5 ppm			
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.331	- 30	821,499,849	375	0.0000456
		- 20	821,500,192	718	0.0000874
		- 10	821,500,038	564	0.0000687
		0	821,499,697	223	0.0000271
		+ 10	821,499,967	493	0.0000600
		+ 20 (Ref)	821,499,474	0	0.0000000
		+ 30	821,499,858	384	0.0000467
		+ 40	821,499,649	175	0.0000213
		+ 50	821,499,753	279	0.0000340
Battery Endpoint	3.355	+ 20	821,500,390	916	0.0001115

Table 7-12. LTE Band 26 Frequency Stability Data




Plot 7-37. LTE Band 26 Frequency Stability Chart

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 47 of 49

NR Band n26					
Operating Frequency (Hz):		821,500,000			
Ref. Voltage (VDC):		4.331			
Deviation Limit:		± 0.00025% or 2.5 ppm			
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.331	- 30	821,592,974	342	0.0000416
		- 20	821,593,967	1,335	0.0001625
		- 10	821,592,159	-473	-0.0000576
		0	821,593,427	795	0.0000967
		+ 10	821,592,118	-514	-0.0000626
		+ 20 (Ref)	821,592,632	0	0.0000000
		+ 30	821,593,395	762	0.0000928
		+ 40	821,593,761	1,129	0.0001374
		+ 50	821,594,324	1,691	0.0002059
Battery Endpoint	3.355	+ 20	821,592,681	49	0.0000060

Table 7-13. NR Band n26 Frequency Stability Data



Plot 7-38. NR Band n26 Frequency Stability Chart

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 48 of 49

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA156E** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: A3LSMA156E	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2309070105-05.A3L	Test Dates: 9/8/2023 - 11/22/2023	EUT Type: Portable Handset	Page 49 of 49