

## APPENDIX F: POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process was divided into two parts: (1) evaluation of output power levels for individual or multiple triggering mechanisms and (2) evaluation of the triggering distances for proximity-based sensors.

### F.1 Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

FCC ID A3LSMA156M	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX F: Page 1 of 3

## F.2 Main Antenna Verification Summary

**Table F-1  
Power Measurement Verification for Main Antenna**

Mechanism(s)		Mode/Band	Exposure Condition Index (ECI)		
1st	2nd		Free Space	Mechanism #1	Mechanism #2
Held-to-Ear	Hotspot On	Low Band Ant A	4	1	1
Hotspot On	Held-to-Ear	Low Band Ant A	4	2	1
Held-to-Ear	Hotspot On	Mid Band Ant B	4	1	1
Hotspot On	Held-to-Ear	Mid Band Ant B	4	2	1
Held-to-Ear	Hotspot On	Mid Band Ant C	4	1	1
Hotspot On	Held-to-Ear	Mid Band Ant C	4	2	1
Held-to-Ear	Hotspot On	High Band Ant B	4	1	1
Hotspot On	Held-to-Ear	High Band Ant B	4	2	1

\*Note: Low band refers to: GSM850, UMTS B5, LTE 12/17/13/26/5, NR n5; Mid band refers to: GSM1900, UMTS B2/4, LTE B2/66/4, NR n66; High band refers to: LTE B41

This device uses different Exposure Condition Indices (ECI) to configure different time averaged power levels based on certain exposure scenarios. For this device ECI = 1 represents the case where the device is held to ear, and ECI = 2 represents the case when hotspot mode is active. ECI = 4 is configured when the device cannot detect the use conditions.

<b>FCC ID</b> A3LSMA156M	<b>SAR EVALUATION REPORT</b>	<b>Approved by:</b> Technical Manager
<b>DUT Type:</b> Portable Handset		APPENDIX F: Page 2 of 3

### F.3 WIFI Verification Summary

**Table F-2  
Power Measurement Verification WIFI**

Mechanism(s)	Mode/Band	Exposure Condition Index (ECI)	
1st		Un-triggered (Max)	Mechanism #1 (Reduced)
Held-to-Ear	802.11b	0	1
Held-to-Ear	802.11g	0	1
Held-to-Ear	802.11n (2.4GHz)	0	1
Held-to-Ear	802.11a (5GHz)	0	1
Held-to-Ear	802.11n (5GHz, 20MHz BW)	0	1
Held-to-Ear	802.11n (5GHz, 40MHz BW)	0	1
Held-to-Ear	802.11ac (20MHz BW)	0	1
Held-to-Ear	802.11ac (40MHz BW)	0	1
Held-to-Ear	802.11ac (80MHz BW)	0	1

This device uses different Exposure Condition Indices (ECI) to configure different time averaged power levels based on certain exposure scenarios. For this device ECI = 1 represents the case where the device is held to ear, ECI = 0 is configured when the device cannot detect the use conditions.

FCC ID A3LSMA156M	<b>SAR EVALUATION REPORT</b>	<b>Approved by:</b> Technical Manager
DUT Type: Portable Handset		APPENDIX F: Page 3 of 3