

CERTIFICATION TEST REPORT

Report Number. : 4790976587-E1V2

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-A256E/DSN, SM-A256E/N

FCC ID : A3LSMA256E

EUT Description : GSM/WCDMA/LTE 5G Phone with BT/BLE, DTS/UNII a/b/g/n/ac,
NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART E

Date Of Issue:
2023-10-25

Prepared by:
UL KOREA LTD.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL KOREA LTD. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433

Revision History

| <u>Rev.</u> | <u>Issue Date</u> | <u>Revisions</u> | <u>Revised By</u> |
|-------------|-------------------|-----------------------------------|---------------------|
| V1 | 2023-10-19 | Initial issue | Hyunsik(Dexter) Yun |
| V2 | 2023-10-25 | Updated to address TCB's question | Hyunsik(Dexter) Yun |

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. ATTESTATION OF TEST RESULTS | 4 |
| 2. TEST METHODOLOGY | 5 |
| 3. FACILITIES AND ACCREDITATION | 5 |
| 4. CALIBRATION AND UNCERTAINTY | 5 |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> | <i>5</i> |
| 4.2. <i>DECISION RULE.....</i> | <i>5</i> |
| 5. EQUIPMENT UNDER TEST | 6 |
| 5.1. <i>DESCRIPTION OF EUT</i> | <i>6</i> |
| 5.2. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> | <i>6</i> |
| 5.3. <i>DESCRIPTION OF TEST SETUP.....</i> | <i>7</i> |
| 6. TEST AND MEASUREMENT EQUIPMENT | 8 |
| 7. SUMMARY TABLE | 9 |
| 8. MEASUREMENT METHODS | 9 |
| 9. DYNAMIC FREQUENCY SELECTION..... | 10 |
| 9.1. <i>OVERVIEW</i> | <i>10</i> |
| 9.1.1. <i>LIMITS.....</i> | <i>10</i> |
| 9.1.2. <i>TEST AND MEASUREMENT SYSTEM.....</i> | <i>13</i> |
| 9.1.3. <i>SETUP OF EUT.....</i> | <i>16</i> |
| 9.1.4. <i>DESCRIPTION OF EUT</i> | <i>17</i> |
| 9.2. <i>RESULTS FOR 80 MHz BANDWIDTH (UNII-2A BAND).....</i> | <i>18</i> |
| 9.2.1. <i>TEST CHANNEL</i> | <i>18</i> |
| 9.2.2. <i>RADAR WAVEFORM AND TRAFFIC</i> | <i>18</i> |
| 9.2.3. <i>OVERLAPPING CHANNEL TESTS.....</i> | <i>19</i> |
| 9.2.4. <i>MOVE AND CLOSING TIME</i> | <i>19</i> |
| 9.3. <i>RESULTS FOR 80 MHz BANDWIDTH (UNII-2C BAND)</i> | <i>22</i> |
| 9.3.1. <i>TEST CHANNEL</i> | <i>22</i> |
| 9.3.2. <i>RADAR WAVEFORM AND TRAFFIC.....</i> | <i>22</i> |
| 9.3.3. <i>OVERLAPPING CHANNEL TESTS.....</i> | <i>23</i> |
| 9.3.4. <i>MOVE AND CLOSING TIME</i> | <i>23</i> |

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE 5G Phone with BT/BLE, DTS/UNII a/b/g/n/ac, NFC
MODEL NUMBER: SM-A256E/DSN, SM-A256E/N
SERIAL NUMBER: R3CW50B47FV (CONDUCTED);
DATE TESTED: 2023-10-07 ~ 2023-10-19

| APPLICABLE STANDARDS | |
|--------------------------|--------------|
| STANDARD | TEST RESULTS |
| CFR 47 Part 15 Subpart E | Complies |

UL KOREA LTD. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL KOREA LTD. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL KOREA LTD. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL KOREA LTD. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL KOREA LTD. By:



Seokhwan Hong
Suwon Lab Engineer
UL KOREA LTD.

Tested By:



Dexter(Hyunsik) Yun
Suwon Lab Engineer
UL KOREA LTD.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. KDB 789033 D02 General UNII Test Procedures New Rules v02r01
2. KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
3. KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

| 218 Maeyeong-ro | |
|--------------------------|-------------------------------------|
| <input type="checkbox"/> | Chamber 1(3m semi-anechoic chamber) |
| <input type="checkbox"/> | Chamber 2(3m semi-anechoic chamber) |
| <input type="checkbox"/> | Chamber 3(3m semi-anechoic chamber) |
| <input type="checkbox"/> | Chamber 4(3m Full-anechoic chamber) |
| <input type="checkbox"/> | Chamber 5(3m Full-anechoic chamber) |

UL KOREA LTD. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. DECISION RULE

Decision rule for statement(s) of conformity is based on Procedure 2, Clause 4.4.3 in IEC Guide 115:2021.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE 5G Phone with BT/BLE, DTS/UNII a/b/g/n/ac, NFC.
 This test report addresses the NII (WLAN) operational mode.

| Representative model | Difference | Derivative model |
|----------------------|------------|-------------------------|
| | | SM-A256E/N |
| SM-A256E/DSN | Hardware | Different Sim Card tray |
| | Software | Same |

The model SM-A256E/DSN was used for final testing and is representative of the test results in this report.

WiFi operating mode

| Frequency range | Mode | ANT1 |
|-------------------------------|---------------|-------|
| 5GHz (5180 MHz ~ 5825 MHz) | 802.11a MIMO | TX/RX |
| | 802.11n MIMO | TX/RX |
| | 802.11ac MIMO | TX/RX |

5.2. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The internal antenna was Permanently attached.
 Therefore this E.U.T Complies with the requirement of §15.203.**

The radio utilizes a internal antenna, with a maximum gain of:

| Frequency Band [MHz] | ANT1 Gain [dBi] |
|------------------------|-----------------|
| UNII 2A 5250 - 5350 | -6.24 |
| UNII 2C 5470 - 5725 | -6.24 |

“WiFi 5G” as indicated in antenna specification are written as ANT1 in this report.

5.3. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

| Support Equipment List | | | | |
|------------------------|--------------|----------|----------------|--------|
| Description | Manufacturer | Model | Serial Number | FCC ID |
| Charger | SAMSUNG | EP-TA800 | R37TC7A00EBDKA | N/A |
| Data Cable | SAMSUNG | EP-DN980 | GH39-02115A | N/A |

I/O CABLE

| I/O Cable List | | | | | | |
|----------------|----------|----------------------|----------------|------------|------------------|---------|
| Cable No. | Port | # of identical ports | Connector Type | Cable Type | Cable Length (m) | Remarks |
| 1 | DC Power | 1 | C Type | Shielded | 1.0 m | N/A |

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

| Test Equipment List | | | | |
|----------------------------|--------------|------------|------------|------------|
| Description | Manufacturer | Model | S/N | Cal Due |
| Spectrum Analyzer, 44 GHz | Agilent / HP | N9030A | MY54170614 | 2024-07-25 |
| Spectrum Analyzer, 44 GHz | Agilent / HP | N9030A | MY54490312 | 2024-07-24 |
| Attenuator | PASTERNAK | PE7087-10 | A001 | 2024-07-23 |
| Attenuator | PASTERNAK | PE7087-10 | A008 | 2024-07-27 |
| Attenuator | PASTERNAK | PE7004-10 | 2 | 2024-07-23 |
| Attenuator | PASTERNAK | PE7087-10 | A009 | 2024-07-24 |
| Termination | WEINSHEL | M1406A | T09 | 2024-07-23 |
| Attenuator | WEINSHEL | WA76-30-21 | A015 | 2024-07-24 |
| UL Software | | | | |
| Description | Manufacturer | Model | Version | |
| Radiated software | UL | UL EMC | Ver 9.5 | |
| AC Line Conducted software | UL | UL EMC | Ver 9.5 | |

7. SUMMARY TABLE

| FCC Part Section | Test Description | Test Limit | Test Condition | Test Result |
|------------------|-----------------------------|------------|----------------|--------------------------|
| 15.407 (h)(2) | Dynamic Frequency Selection | Section 9 | Condcuted | Complies ^{Note} |

Note. This EUT does not support channel puncturing.

8. MEASUREMENT METHODS

DFS: 905462 D02 UNII DFS Compliance Procedures New Rules v02

9. DYNAMIC FREQUENCY SELECTION

9.1. OVERVIEW

9.1.1. LIMITS

FCC

§15.407 (h), FCC KDB 905462 D02 “COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION” and KDB 905462 D03 “U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY”.

Table 1: Applicability of DFS requirements prior to use of a channel

| Requirement | Operational Mode | | |
|---------------------------------|------------------|----------------------------------|-------------------------------|
| | Master | Client (without radar detection) | Client (with radar detection) |
| Non-Occupancy Period | Yes | Not required | Yes |
| DFS Detection Threshold | Yes | Not required | Yes |
| Channel Availability Check Time | Yes | Not required | Not required |
| U-NII Detection Bandwidth | Yes | Not required | Yes |

Table 2: Applicability of DFS requirements during normal operation

| Requirement | Operational Mode | | |
|-----------------------------------|------------------|----------------------|-------------------|
| | Master | Client (without DFS) | Client (with DFS) |
| DFS Detection Threshold | Yes | Not required | Yes |
| Channel Closing Transmission Time | Yes | Yes | Yes |
| Channel Move Time | Yes | Yes | Yes |
| U-NII Detection Bandwidth | Yes | Not required | Yes |

| Additional requirements for devices with multiple bandwidth modes | Master Device or Client with Radar DFS | Client (without DFS) |
|---|--|--|
| U-NII Detection Bandwidth and Statistical Performance Check | All BW modes must be tested | Not required |
| Channel Move Time and Channel Closing Transmission Time | Test using widest BW mode available | Test using the widest BW mode available for the link |
| All other tests | Any single BW mode | Not required |

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in all 20 MHz channel blocks and a null frequency between the bonded 20 MHz channel blocks.

Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring

| | |
|---|----------------------|
| Maximum Transmit Power | Value (see notes) |
| E.I.R.P. \geq 200 mill watt | -64 dBm |
| E.I.R.P. < 200 mill watt and power spectral density < 10 dBm/MHz | -62 dBm |
| E.I.R.P. < 200 mill watt that do not meet power spectral density requirement | -64 dBm |
| <p>Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: E.I.R.P. is based on the highest antenna gain. For MIMO devices refer to KDB publication 662911 D01.</p> | |

Table 4: DFS Response requirement values

| | |
|--|---|
| Parameter | Value |
| <i>Non-occupancy period</i> | 30 minutes |
| <i>Channel Availability Check Time</i> | 60 seconds |
| <i>Channel Move Time</i> | 10 seconds (See Note 1) |
| <i>Channel Closing Transmission Time</i> | 200 milliseconds + approx. 60 milliseconds over remaining 10 second period. (See Notes 1 and 2) |
| <i>U-NII Detection Bandwidth</i> | Minimum 100% of the U- NII 99% transmission power bandwidth. (See Note 3) |
| <p>Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.</p> | |

Table 5 – Short Pulse Radar Test Waveforms

| Radar Type | Pulse Width (usec) | PRI (usec) | Pulses | Minimum Percentage of Successful Detection | Minimum Trials |
|---|--------------------|---|---|--|----------------|
| 0 | 1 | 1428 | 18 | See Note 1 | See Note 1 |
| 1 | 1 | Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in table 5a | Roundup: $\{(1/360) \times (19 \times 10^6 \text{ PRI}_{\text{usec}})\}$ | 60% | 30 |
| | | Test B: 15 unique PRI values randomly selected within the range of 518-3066 usec. With a minimum increment of 1 usec, excluding PRI values selected in Test A | | | |
| 2 | 1-5 | 150-230 | 23-29 | 60% | 30 |
| 3 | 6-10 | 200-500 | 16-18 | 60% | 30 |
| 4 | 11-20 | 200-500 | 12-16 | 60% | 30 |
| Aggregate (Radar Types 1-4) | | | | 80% | 120 |
| Note 1: Short Pulse Radar Type 0 should be used for the <i>Detection Bandwidth</i> test, <i>Channel Move Time</i> , and <i>Channel Closing Time</i> tests. | | | | | |

Table 6 – Long Pulse Radar Test Signal


| Radar Waveform Type | Pulse Width (μsec) | Chirp Width (MHz) | PRI (μsec) | Pulses per Burst | Number of Bursts | Minimum Percentage of Successful Detection | Minimum Trials |
|---------------------|--------------------|-------------------|------------|------------------|------------------|--|----------------|
| 5 | 50-100 | 5-20 | 1000-2000 | 1-3 | 8-20 | 80% | 30 |

Table 7 – Frequency Hopping Radar Test Signal

| Radar Waveform Type | Pulse Width (μsec) | PRI (μsec) | Pulses per Hop | Hopping Rate (kHz) | Hopping Sequence Length (msec) | Minimum Percentage of Successful Detection | Minimum Trials |
|---------------------|--------------------|------------|----------------|--------------------|--------------------------------|--|----------------|
| 6 | 1 | 333 | 9 | 0.333 | 300 | 70% | 30 |

9.1.2. TEST AND MEASUREMENT SYSTEM

CONDUCTED METHOD SYSTEM BLOCK DIAGRAM



SYSTEM OVERVIEW

The short pulse and long pulse signal generating system utilizes the Keysite Signal Studio for Pulse Building as N5172B. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.

The short pulse types 1, 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of KDB 905462 D02. The frequency of the signal generator is incremented in 1 MHz steps from F_L to F_H for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

SYSTEM CALIBRATION

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a horn antenna via a coaxial cable, with the reference level offset set to (horn antenna gain – coaxial cable loss). The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of –64 dBm as measured on the spectrum analyzer.

Without changing any of the instrument settings, the spectrum analyzer is reconnected to the Common port of the Spectrum Analyzer Combiner/Divider. The Reference Level Offset of the spectrum analyzer is adjusted so that the displayed amplitude of the signal is –64 dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of –64 dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

ADJUSTMENT OF DISPLAYED TRAFFIC LEVEL

A link is established between the Master and Slave and the distance between the units is adjusted as needed to provide a suitable received level at the Master and Slave devices. The video test file is streamed to generate WLAN traffic. The monitoring antenna is adjusted so that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold.


TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the DFS tests documented in this report:

| TEST EQUIPMENT LIST | | | | |
|-------------------------------|--------------|--------|------------|--------------|
| Description | Manufacturer | Model | S/N | Next Cal Due |
| Spectrum Analyzer, 7 GHz | Agilent / HP | N9010A | MY54200580 | 07-23-24 |
| Vector Signal Generator, 6GHz | Agilent / HP | N5182B | MY53051241 | 07-23-24 |
| Combiner | WEINSCHTEL | WA1534 | UL001 | 01-13-24 |
| Combiner | WEINSCHTEL | WA1534 | UL003 | 01-09-24 |

9.1.3. SETUP OF EUT

CONDUCTED METHOD EUT TEST SETUP



SUPPORT EQUIPMENT

The following support equipment was utilized for the DFS tests documented in this report:

| PERIPHERAL SUPPORT EQUIPMENT LIST | | | | |
|-----------------------------------|--------------|-------------------------|---------------|-----------|
| Description | Manufacturer | Model | Serial Number | FCC ID |
| Wireless Access Point | Cisco | AIR-CAP3702E-A-K9 | FTX182276QX | LDK102087 |
| Notebook PC (Controller/Server) | HP | HP EliteDesk 800 G1 TWR | CZC4125J25 | DoC |

9.1.4. DESCRIPTION OF EUT

The EUT operates over the 5250-5350 MHz and 5470-5725 MHz ranges.

The EUT is a Slave Device without Radar Detection.

The highest power level of the widest bandwidth (802.11ac VHT80) within these bands is 8.23 dBm in the 5250-5350 MHz band and 12.57 dBm in the 5470-5725 MHz band.

The antenna assembly utilized two antenna.

Gain of ANT1 : -6.24 dBi for UNII 2A and -6.24 dBi for UNII 2C.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required conducted threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

The EUT uses one transmitter/receiver chain connected to an antenna to perform radiated tests. WLAN traffic that meets or exceeds the minimum required loading was generated by transferring a data stream from the controller/server PC to the EUT using iPerf version 2.0.5 software package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11 architecture. Three nominal channel bandwidths are implemented: 20 MHz, 40 MHz and 80 MHz.

The software installed in the access point is 12.4(25d)JA1.

UNIFORM CHANNEL SPREADING

This requirement is not applicable to Slave radio devices.

OVERVIEW OF MASTER DEVICE WITH RESPECT TO §15.407 (h) REQUIREMENTS

The Master Device is a Cisco Access Point, FCC ID: LDK102087. The minimum antenna gain for the Master Device is 6 dBi.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.


9.2. RESULTS FOR 80 MHz BANDWIDTH (UNII-2A BAND)

9.2.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5290 MHz.

9.2.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



9.2.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

9.2.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS


| Channel Move Time (sec) | Limit (sec) |
|-------------------------|-------------|
| 0.718 | 10 |

| Aggregate Channel Closing Transmission Time (msec) | Limit (msec) |
|--|--------------|
| 1.500 | 60 |

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME


No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.




9.3. RESULTS FOR 80 MHz BANDWIDTH (UNII-2C BAND)

9.3.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5530 MHz.

9.3.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



9.3.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

9.3.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

| Channel Move Time (sec) | Limit (sec) |
|-------------------------|-------------|
| 0.730 | 10 |

| Aggregate Channel Closing Transmission Time (msec) | Limit (msec) |
|--|--------------|
| 3.375 | 60 |

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME

No transmissions are observed during the aggregate monitoring period.

