

# FCC LTE REPORT

## Certification

**Applicant Name:**  
SAMSUNG Electronics Co., Ltd.

**Date of Issue:**  
September 26, 2023

**Address:**  
129, Samsung-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Location:**  
HCT CO., LTD.,  
74, Seoicheon-ro 578beon-gil, Majang-myeon,  
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA  
**Report No.:** HCT-RF-2309-FC026

**FCC ID:** A3LSMA256U

**APPLICANT:** SAMSUNG Electronics Co., Ltd.

Model(s): SM-A256U  
 Additional Model(s): SM-A256U1/DS, SM-S256VL  
 EUT Type: Mobile Phone  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 38 (5)	2572.5 – 2617.5	4M51G7D	QPSK	0.236	23.72
		4M51W7D	16QAM	0.190	22.78
		4M51W7D	64QAM	0.150	21.77
		4M51W7D	256QAM	0.073	18.64
LTE – Band 38 (10)	2575.0 – 2615.0	9M01G7D	QPSK	0.236	23.72
		9M00W7D	16QAM	0.195	22.89
		8M98W7D	64QAM	0.159	22.01
		8M99W7D	256QAM	0.075	18.76
LTE – Band 38 (15)	2577.5 – 2612.5	13M5G7D	QPSK	0.238	23.77
		13M5W7D	16QAM	0.190	22.78
		13M5W7D	64QAM	0.159	22.01
		13M5W7D	256QAM	0.074	18.70
LTE – Band 38 (20)	2580.0 – 2610.0	17M9G7D	QPSK	0.239	23.78
		17M9W7D	16QAM	0.194	22.88
		17M9W7D	64QAM	0.156	21.94
		17M9W7D	256QAM	0.075	18.77

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.  
 HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report No.: HCT-RF-2309-FC026

---

REVIEWED BY



---

Report prepared by : Jae Mun Do  
Engineer of Telecommunication Testing Center

---

Report approved by : Jong Seok Lee  
Manager of Telecommunication Testing Center

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked \*.  
The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

The report shall not be reproduced except in full(only partly) without approval of the laboratory.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2309-FC026	September 26, 2023	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Table of Contents

REVIEWED BY .....	2
1. GENERAL INFORMATION .....	5
2. INTRODUCTION .....	6
2.1. DESCRIPTION OF EUT .....	6
2.2. MEASURING INSTRUMENT CALIBRATION .....	6
2.3. TEST FACILITY .....	6
3. DESCRIPTION OF TESTS.....	7
3.1 TEST PROCEDURE .....	7
3.2 RADIATED POWER.....	8
3.3 RADIATED SPURIOUS EMISSIONS .....	9
3.4 PEAK- TO- AVERAGE RATIO.....	10
3.5 OCCUPIED BANDWIDTH. ....	12
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL .....	13
3.7 CHANNEL EDGE .....	14
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	16
3.9 WORST CASE(RADIATED TEST) .....	17
3.10 WORST CASE(CONDUCTED TEST) .....	18
4. LIST OF TEST EQUIPMENT .....	19
5. MEASUREMENT UNCERTAINTY .....	20
6. SUMMARY OF TEST RESULTS .....	21
7. SAMPLE CALCULATION .....	22
8. TEST DATA .....	24
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	24
8.2 RADIATED SPURIOUS EMISSIONS .....	26
8.3 PEAK-TO-AVERAGE RATIO.....	30
8.4 OCCUPIED BANDWIDTH .....	31
8.5 CONDUCTED SPURIOUS EMISSIONS .....	32
8.6 CHANNEL EDGE .....	33
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	35
9. TEST PLOTS.....	47
10. ANNEX A_ TEST SETUP PHOTO.....	124

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

<b>Applicant Name:</b>	SAMSUNG Electronics Co., Ltd.
<b>Address:</b>	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
<b>FCC ID:</b>	A3LSMA256U
<b>Application Type:</b>	Certification
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)
<b>FCC Rule Part(s):</b>	§27, §2
<b>EUT Type:</b>	Mobile Phone
<b>Model(s):</b>	SM-A256U
<b>Additional Model(s):</b>	SM-A256U1/DS, SM-S256VL
<b>Tx Frequency:</b>	2572.5 – 2617.5 : 5 MHz 2575.0 – 2615.0 : 10 MHz 2577.5 – 2612.5 : 15 MHz 2580.0 – 2610.0 : 20 MHz
<b>Date(s) of Tests:</b>	May 22, 2023 ~ September 04, 2023
<b>Serial number:</b>	Radiated: R3CW50MGDKF Conducted: 74530c3036337ece

## **2. INTRODUCTION**

### **2.1. DESCRIPTION OF EUT**

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac (20/40/80 MHz), Bluetooth, BT LE, NFC.

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

### 3. DESCRIPTION OF TESTS

#### 3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

## 3.2 RADIATED POWER

### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $>$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.  
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

#### Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $> 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin  $> 20$  dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(dBm)} = P_g_{(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dBi)}$$

Where:  $P_g$  is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(dBm)} = \text{ERP}_{(dBm)} + 2.15$$

### 3.4 PEAK- TO- AVERAGE RATIO



**Test setup**

#### ① CCDF Procedure for PAPR

##### **Test Settings**

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
  - for continuous transmissions, set to 1 ms,
  - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

**② Alternate Procedure for PAPR**

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as  $P_{Pk}$ .  
Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as  $P_{Avg}$ . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

**Test Settings(Peak Power)**


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW  $\geq 3 \times$  RBW.

1. Set the RBW  $\geq$  OBW.
2. Set VBW  $\geq 3 \times$  RBW.
3. Set span  $\geq 2 \times$  OBW.
4. Sweep time  $\geq 10 \times$  (number of points in sweep)  $\times$  (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

**Test Settings(Average Power)**

1. Set span to  $2 \times$  to  $3 \times$  the OBW.
2. Set RBW  $\geq$  OBW.
3. Set VBW  $\geq 3 \times$  RBW.
4. Set number of measurement points in sweep  $\geq 2 \times$  span / RBW.
5. Sweep time:  
Set  $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$  for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add  $[10 \log (1/\text{duty cycle})]$  to the measured maximum power level to compute the average power during continuous transmission. For example, add  $[10 \log (1/0.25)] = 6$  dB if the duty cycle is a constant 25 %.

### 3.5 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

### 3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



**Test setup**


#### **Test Overview**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### **Test Settings**

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = RMS
4. Trace Mode = Average
5. Sweep time = auto
6. Number of points in sweep  $\geq$  2 x Span / RBW

### 3.7 CHANNEL EDGE



#### Test setup

##### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum power and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

##### Test Settings


1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1MHz of the channel edge the RBW should be 2% of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

**Test Notes**

1. The attenuation factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,
2.  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge.
3.  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge.
4. The attenuation factor shall not be less that  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz.
5.  $55 + 10 \log (P)$  dB at or below 2490.5 MHz.
6. X is the greater of 6MHz or the actual emission bandwidth
7. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer

Where Margin < 1 dB the emission level is either corrected by  $10 \log(1 \text{ MHz/ RB})$  or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

### 3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



**Test setup**

#### **Test Overview**

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.

- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

#### **Test Settings**

1. The carrier frequency of the transmitter is measured at room temperature

(20 °C to provide a reference).

2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.



**3.9 WORST CASE(RADIATED TEST)**

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.  
 Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)  
 Worst case : Stand alone
- We were performed the RSE test in condition of co-location.  
 Mode : Stand alone, Simultaneous transmission scenarios  
 Worst case : Stand alone
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- SM-A256U & additional models were tested and the worst case results are reported.  
 (Worst case : SM-A256U)

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	1	0	Z
Radiated Spurious and Harmonic Emissions	QPSK	1	0	X

**3.10 WORST CASE(CONDUCTED TEST)**

- All modes of operation were investigated and the worst case configuration results are reported.
- SM-A256U & additional models were tested and the worst case results are reported.  
(Worst case : SM-A256U)

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
<b>Occupied Bandwidth</b>	QPSK, 16QAM, 64QAM, 256QAM	5, 10, 15, 20	Mid	Full RB	0
<b>Peak-To-Average Ratio</b>	QPSK, 16QAM, 64QAM, 256QAM	5, 10, 15, 20	Mid	Full RB	0
<b>Channel Edge</b>	QPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		5, 10, 15, 20	Low, Mid, High	Full RB	0
<b>Spurious and Harmonic Emissions at Antenna Terminal</b>	QPSK	5, 10, 15, 20	Low, Mid, High	1	0

#### 4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	FBSR-02B(1.2G HPF+LNA)	T&M SYSTEM	F1L1	01/19/2024	Annual
RF Switching System	FBSR-02B(3.3G HPF+LNA)	T&M SYSTEM	F1L2	01/19/2024	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/19/2024	Annual
DC Power Supply	E3632A	Agilent	MY40010147	06/23/2024	Annual
Dipole Antenna	UHAP	Schwarzbeck	557	03/09/2025	Biennial
Dipole Antenna	UHAP	Schwarzbeck	558	03/09/2025	Biennial
Chamber	SU-642	ESPEC	93008124	02/22/2024	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/17/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/15/2023	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/29/2024	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/20/2024	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/19/2024	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/17/2024	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/10/2024	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/17/2024	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/16/2024	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	03/21/2024	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	12/01/2023	Annual
Wideband Radio Communication Tester	MT8820C	Anritsu Corp.	6201026545	01/05/2024	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	06/22/2024	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/24/2024	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

**Note:**

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.90 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (9 kHz ~ 30 MHz)	4.14 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (30 MHz ~ 1 GHz)	5.16 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (1 GHz ~ 18 GHz)	5.57 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (18 GHz ~ 40 GHz)	5.76 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (Above 40 GHz)	5.52 (Confidence level about 95 %, $k=2$ )

## 6. SUMMARY OF TEST RESULTS

### 6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(m)(4)	<ul style="list-style-type: none"> <li>■ &lt; 40 + 10log10 (P[Watts]) at Channel edges</li> <li>■ &lt; 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges</li> <li>■ &lt; 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges</li> <li>■ &lt; 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz</li> </ul>	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. See SAR Report

### 6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§27.50(h)(2)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(m)(4)	< 55 + 10log10 (P[Watts])	PASS
Receiver Spurious Emissions	N/A	Section 8.8	PASS

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

**ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)**

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

**EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)**

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

**GSM Emission Designator**

**Emission Designator = 249KGXW**

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

**EDGE Emission Designator**

**Emission Designator = 249KG7W**

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

**WCDMA Emission Designator**

**Emission Designator = 4M17F9W**

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

**QPSK Modulation**

**Emission Designator = 4M48G7D**

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

**QAM Modulation**

**Emission Designator = 4M48W7D**

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

## 8. TEST DATA

### 8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit		EIRP	
								W	W	dBm	dBm
2572.5	LTE B38/ 5 MHz	QPSK	-21.20	15.49	10.70	2.47	V	< 2.00	0.236	23.72	
		16-QAM	-22.14	14.55	10.70	2.47	V		0.190	22.78	
		64-QAM	-23.15	13.54	10.70	2.47	V		0.150	21.77	
		256-QAM	-26.28	10.41	10.70	2.47	V		0.073	18.64	
2595.0		QPSK	-21.05	15.40	10.70	2.53	V		0.228	23.57	
		16-QAM	-21.97	14.48	10.70	2.53	V		0.184	22.65	
		64-QAM	-22.96	13.49	10.70	2.53	V		0.147	21.66	
		256-QAM	-26.13	10.32	10.70	2.53	V		0.071	18.49	
2617.5		QPSK	-21.20	15.45	10.66	2.60	V		0.224	23.51	
		16-QAM	-22.22	14.43	10.66	2.60	V		0.177	22.49	
		64-QAM	-23.09	13.56	10.66	2.60	V		0.145	21.62	
		256-QAM	-26.30	10.35	10.66	2.60	V		0.069	18.41	

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit		EIRP	
								W	W	dBm	dBm
2575.0	LTE B38/ 5 MHz	QPSK	-21.19	15.50	10.70	2.48	V	< 2.00	0.236	23.72	
		16-QAM	-22.02	14.67	10.70	2.48	V		0.195	22.89	
		64-QAM	-22.90	13.79	10.70	2.48	V		0.159	22.01	
		256-QAM	-26.15	10.54	10.70	2.48	V		0.075	18.76	
2595.0		QPSK	-20.99	15.46	10.70	2.53	V		0.231	23.63	
		16-QAM	-21.83	14.62	10.70	2.53	V		0.190	22.79	
		64-QAM	-22.84	13.61	10.70	2.53	V		0.151	21.78	
		256-QAM	-26.05	10.40	10.70	2.53	V		0.072	18.57	
2615.0		QPSK	-21.30	15.33	10.67	2.60	V		0.219	23.40	
		16-QAM	-22.11	14.52	10.67	2.60	V		0.182	22.59	
		64-QAM	-23.32	13.31	10.67	2.60	V		0.138	21.38	
		256-QAM	-26.21	10.42	10.67	2.60	V		0.071	18.49	



Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2577.5	LTE B38/ 5 MHz	QPSK	-21.13	15.56	10.70	2.49	V	< 2.00	0.238	23.77
		16-QAM	-22.12	14.57	10.70	2.49	V		0.190	22.78
		64-QAM	-22.89	13.80	10.70	2.49	V		0.159	22.01
		256-QAM	-26.20	10.49	10.70	2.49	V		0.074	18.70
2595.0		QPSK	-20.86	15.59	10.70	2.53	V		0.238	23.76
		16-QAM	-21.86	14.59	10.70	2.53	V		0.189	22.76
		64-QAM	-22.80	13.65	10.70	2.53	V		0.152	21.82
		256-QAM	-25.98	10.47	10.70	2.53	V		0.073	18.64
2612.5		QPSK	-21.12	15.49	10.68	2.59	V		0.228	23.58
		16-QAM	-21.99	14.62	10.68	2.59	V		0.187	22.71
		64-QAM	-22.96	13.65	10.68	2.59	V		0.149	21.74
		256-QAM	-26.10	10.51	10.68	2.59	V		0.072	18.60

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2580.0	LTE B38/ 5 MHz	QPSK	-21.12	15.57	10.70	2.49	V	< 2.00	0.239	23.78
		16-QAM	-22.02	14.67	10.70	2.49	V		0.194	22.88
		64-QAM	-22.98	13.71	10.70	2.49	V		0.156	21.92
		256-QAM	-26.13	10.56	10.70	2.49	V		0.075	18.77
2595.0		QPSK	-20.94	15.51	10.70	2.53	V		0.233	23.68
		16-QAM	-21.78	14.67	10.70	2.53	V		0.192	22.84
		64-QAM	-22.68	13.77	10.70	2.53	V		0.156	21.94
		256-QAM	-25.99	10.46	10.70	2.53	V		0.073	18.63
2610.0		QPSK	-21.05	15.56	10.68	2.59	V		0.232	23.65
		16-QAM	-21.86	14.75	10.68	2.59	V		0.192	22.84
		64-QAM	-22.95	13.66	10.68	2.59	V		0.150	21.75
		256-QAM	-26.00	10.61	10.68	2.59	V		0.074	18.70

### 8.2 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY : 2502.5 MHz
- ▣ MEASURED OUTPUT POWER: 23.72 dBm = 0.236 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10}(W) =$  48.72 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37775 (2572.5)	5 145.00	-56.39	12.29	-64.14	3.70	H	-55.55	79.28
	7 717.50	-57.45	11.40	-58.44	4.68	H	-51.72	75.44
	10 290.00	-59.19	11.50	-53.96	5.81	V	-48.27	71.99
38000 (2595.0)	5 190.00	-56.32	12.46	-65.95	3.75	H	-57.24	80.96
	7 785.00	-56.11	11.40	-55.92	4.69	V	-49.21	72.93
	10 380.00	-60.92	11.40	-55.74	5.77	H	-50.11	73.84
38225 (2617.5)	5 235.00	-58.20	12.71	-67.54	3.82	V	-58.65	82.37
	7 852.50	-58.61	11.40	-58.24	4.69	H	-51.53	75.26
	10 470.00	-58.05	11.26	-53.08	5.85	H	-47.67	71.39

- ▣ OPERATING FREQUENCY : 2505.0 MHz
- ▣ MEASURED OUTPUT POWER: 23.72 dBm = 0.236 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10}(W) =$  48.72 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37800 (2575.0)	5 150.00	-57.95	12.30	-65.81	3.69	V	-57.20	80.92
	7 725.00	-57.49	11.40	-58.53	4.67	V	-51.80	75.52
	10 300.00	-60.38	11.50	-55.03	5.72	H	-49.25	72.97
38000 (2595.0)	5 190.00	-57.21	12.46	-66.84	3.75	V	-58.13	81.85
	7 785.00	-58.03	11.40	-57.84	4.69	H	-51.13	74.85
	10 380.00	-59.70	11.40	-54.52	5.77	V	-48.89	72.61
38200 (2615.0)	5 230.00	-56.42	12.68	-65.88	3.84	H	-57.04	80.76
	7 845.00	-58.82	11.40	-58.63	4.70	V	-51.92	75.64
	10 460.00	-60.07	11.28	-55.21	5.70	V	-49.63	73.35

- ▣ OPERATING FREQUENCY : 2507.5 MHz
- ▣ MEASURED OUTPUT POWER: 23.77 dBm = 0.238 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10}(W) =$  48.77 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37825 (2577.5)	5 155.00	-57.46	12.32	-65.46	3.70	H	-56.84	80.60
	7 732.50	-55.09	11.40	-56.19	4.66	H	-49.45	73.21
	10 310.00	-60.11	11.48	-54.74	5.61	V	-48.87	72.64
38000 (2595.0)	5 190.00	-57.27	12.46	-66.90	3.75	H	-58.19	81.96
	7 785.00	-57.84	11.40	-57.65	4.69	H	-50.94	74.71
	10 380.00	-60.38	11.40	-55.20	5.77	H	-49.57	73.34
38175 (2612.5)	5 225.00	-58.74	12.65	-68.36	3.85	H	-59.56	83.33
	7 837.50	-58.93	11.40	-58.91	4.70	H	-52.21	75.98
	10 450.00	-59.09	11.30	-54.07	5.57	H	-48.34	72.11

- ▣ OPERATING FREQUENCY : 2510.0 MHz
- ▣ MEASURED OUTPUT POWER: 23.78 dBm = 0.239 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10} (W) =$  48.78 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37850 (2580.0)	5 160.00	-56.34	12.34	-64.47	3.71	V	-55.84	79.62
	7 740.00	-57.33	11.40	-58.17	4.66	H	-51.43	75.21
	10 320.00	-59.88	11.46	-54.31	5.52	H	-48.37	72.15
38000 (2595.0)	5 190.00	-56.66	12.46	-66.29	3.75	H	-57.58	81.36
	7 785.00	-56.73	11.40	-56.54	4.69	H	-49.83	73.61
	10 380.00	-58.29	11.40	-53.11	5.77	V	-47.48	71.26
38150 (2610.0)	5 220.00	-58.01	12.62	-67.80	3.86	H	-59.04	82.81
	7 830.00	-58.50	11.40	-58.74	4.71	V	-52.05	75.83
	10 440.00	-59.94	11.32	-54.66	5.51	H	-48.85	72.63

**8.3 PEAK-TO-AVERAGE RATIO**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB )
38	5 MHz	2595.0	QPSK	25	0	6.17
			16-QAM			6.58
			64-QAM			6.90
			256-QAM			6.78
	10 MHz		QPSK	50		5.84
			16-QAM			6.31
			64-QAM			6.98
			256-QAM			6.95
	15 MHz		QPSK	75		5.51
			16-QAM			6.23
			64-QAM			6.97
			256-QAM			7.06
	20 MHz		QPSK	100		5.61
			16-QAM			6.28
			64-QAM			6.51
			256-QAM			6.79

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 64 ~ 79.

**8.4 OCCUPIED BANDWIDTH**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )
38	5 MHz	2595.0	QPSK	25	0	4.5088
			16-QAM			4.5082
			64-QAM			4.5124
			256-QAM			4.5084
	10 MHz		QPSK	50		9.0096
			16-QAM			8.9973
			64-QAM			8.9804
			256-QAM			8.9894
	15 MHz		QPSK	75		13.484
			16-QAM			13.474
			64-QAM			13.458
			256-QAM			13.453
	20 MHz		QPSK	100		17.938
			16-QAM			17.852
			64-QAM			17.883
			256-QAM			17.877

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 48 ~ 63.

**8.5 CONDUCTED SPURIOUS EMISSIONS**

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
38	5	2572.5	26.1449	34.110	-76.731	-42.621	-25.00
		2595.0	26.1385	34.110	-76.761	-42.651	
		2617.5	25.8231	34.110	-76.149	-42.039	
	10	2575.0	26.1508	34.110	-76.589	-42.479	
		2595.0	26.1470	34.110	-76.690	-42.580	
		2615.0	26.1313	34.110	-76.820	-42.710	
	15	2577.5	26.2205	34.110	-76.697	-42.587	
		2595.0	25.8244	34.110	-76.430	-42.320	
		2612.5	26.1717	34.110	-76.630	-42.520	
	20	2580.0	26.1602	34.110	-76.652	-42.542	
		2595.0	26.1160	34.110	-76.653	-42.543	
		2610.0	26.1215	34.110	-76.648	-42.538	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 100 ~ 123.
2. Duty Cycle factor already applied on the factor.
  - Duty Cycle factor(dB) = 3.010
  - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
  - Result(dBm) = Reading + Factor

Frequency Range (GHz)	Factor [dB]
0.03 – 1	29.249
1 – 5	31.955
5 – 10	32.570
10 – 15	33.095
15 – 20	33.468
Above 20	34.110



**8.6 CHANNEL EDGE**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1 MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
Band 38	5 MHz	2572.5	QPSK	25	0	-23.33	-24.19	-28.94	-28.76
		2595.0	QPSK	25	0	-23.30	-23.67	-29.37	-30.01
		2617.5	QPSK	25	0	-23.41	-24.10	-29.69	-30.39
	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1 MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
	10 MHz	2575.0	QPSK	50	0	-27.83	-27.78	-30.64	-31.07
		2595.0	QPSK	50	0	-28.11	-27.18	-31.54	-31.65
		2615.0	QPSK	50	0	-27.22	-27.16	-31.77	-31.28
	15 MHz	2577.5	QPSK	75	0	-30.34	-29.74	-32.13	-32.08
		2595.0	QPSK	75	0	-30.13	-30.18	-33.35	-32.57
		2612.5	QPSK	75	0	-30.61	-29.66	-33.44	-33.41
	20 MHz	2580.0	QPSK	100	0	-33.49	-32.19	-34.63	-34.32
		2595.0	QPSK	100	0	-33.87	-32.28	-35.38	-35.28
		2610.0	QPSK	100	0	-33.28	-32.16	-35.59	-35.16
	Limit						-10.0		-10.0

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz)		Above (C.E ± X MHz)		
						~				
						(C.E ± X MHz)		Lower	Upper	Lower
Band 38	5 MHz	2572.5	QPSK	25	0	-35.99	-36.44	-38.17	-37.98	
		2595.0	QPSK	25	0	-36.11	-36.45	-37.83	-38.48	
		2617.5	QPSK	25	0	-36.22	-35.82	-37.99	-37.93	
	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz)		Above (C.E ± X MHz)		
						~				
						(C.E ± X MHz)		Lower	Upper	Lower
	10 MHz	2575.0	QPSK	50	0	-34.48	-34.45	-40.00	-39.73	
		2595.0	QPSK	50	0	-34.31	-34.37	-39.92	-40.17	
		2615.0	QPSK	50	0	-34.23	-33.68	-40.25	-39.58	
		15 MHz	2577.5	QPSK	75	0	-35.51	-35.74	-41.08	-40.90
			2595.0	QPSK	75	0	-36.17	-36.14	-40.67	-41.33
			2612.5	QPSK	75	0	-36.40	-35.31	-41.32	-40.89
		20 MHz	2580.0	QPSK	100	0	-37.08	-36.70	-41.67	-42.03
			2595.0	QPSK	100	0	-37.27	-37.45	-41.94	-41.92
			2610.0	QPSK	100	0	-37.60	-36.36	-41.87	-41.40
Limit						-13.0		-25.0		


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6 MHz or the actual emission bandwidth.
3. X = 6 MHz(5 MHz Bandwidth), 10 MHz(10 MHz Bandwidth), 15 MHz(15 MHz Bandwidth), 20 MHz(20 MHz Bandwidth)
4. RB = Resource Block
5. Duty Cycle factor already applied on the factor.
  - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
  - Result(dBm) = Reading + Factor
  - Duty Cycle Factor(dB) = 3.979
6. Plots of the EUT's Channel Edge are shown Page 80 ~ 99. (1RB & Full RB)

**8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE**


- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2572,500,000 Hz
- ▣ BANDWIDTH: 37775 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2572 499 995	0.0	0.000 000	0.000
100 %		-30	2572 499 992	-3.3	0.000 000	-0.001
100 %		-20	2572 499 993	-2.5	0.000 000	-0.001
100 %		-10	2572 499 992	-3.1	0.000 000	-0.001
100 %		0	2572 499 992	-3.4	0.000 000	-0.001
100 %		+10	2572 499 992	-3.4	0.000 000	-0.001
100 %		+30	2572 499 991	-4.3	0.000 000	-0.002
100 %		+40	2572 499 992	-3.3	0.000 000	-0.001
100 %		+50	2572 499 992	-3.5	0.000 000	-0.001
Batt. Endpoint		3.550	+20	2572 499 991	-4.8	0.000 000




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2575,000,000 Hz
- ▣ BANDWIDTH: 37800 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2574 999 997	0.0	0.000 000	0.000
100 %		-30	2574 999 993	-3.4	0.000 000	-0.001
100 %		-20	2575 000 000	3.4	0.000 000	0.001
100 %		-10	2574 999 999	2.6	0.000 000	0.001
100 %		0	2574 999 994	-3.2	0.000 000	-0.001
100 %		+10	2575 000 000	3.4	0.000 000	0.001
100 %		+30	2574 999 994	-2.5	0.000 000	-0.001
100 %		+40	2575 000 000	3.6	0.000 000	0.001
100 %		+50	2574 999 994	-2.6	0.000 000	-0.001
Batt. Endpoint	3.550	+20	2574 999 993	-3.6	0.000 000	-0.001




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2577,500,000 Hz
- ▣ BANDWIDTH: 37825 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2577 499 997	0.0	0.000 000	0.000
100 %		-30	2577 499 992	-4.5	0.000 000	-0.002
100 %		-20	2577 499 993	-3.2	0.000 000	-0.001
100 %		-10	2577 499 991	-5.1	0.000 000	-0.002
100 %		0	2577 499 993	-4.0	0.000 000	-0.002
100 %		+10	2577 499 993	-3.3	0.000 000	-0.001
100 %		+30	2577 499 992	-4.9	0.000 000	-0.002
100 %		+40	2577 499 993	-3.8	0.000 000	-0.001
100 %		+50	2577 499 993	-3.9	0.000 000	-0.002
Batt. Endpoint	3.550	+20	2577 499 991	-5.2	0.000 000	-0.002




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2580,000,000 Hz
- ▣ BANDWIDTH: 37850 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2579 999 997	0.0	0.000 000	0.000
100 %		-30	2579 999 994	-2.5	0.000 000	-0.001
100 %		-20	2580 000 000	3.1	0.000 000	0.001
100 %		-10	2579 999 992	-4.7	0.000 000	-0.002
100 %		0	2579 999 999	2.5	0.000 000	0.001
100 %		+10	2580 000 001	4.7	0.000 000	0.002
100 %		+30	2579 999 994	-3.0	0.000 000	-0.001
100 %		+40	2580 000 000	3.2	0.000 000	0.001
100 %		+50	2579 999 993	-3.5	0.000 000	-0.001
Batt. Endpoint		3.550	+20	2579 999 993	-3.6	0.000 000




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2594 999 997	0.0	0.000 000	0.000
100 %		-30	2594 999 993	-3.3	0.000 000	-0.001
100 %		-20	2594 999 993	-3.7	0.000 000	-0.001
100 %		-10	2594 999 992	-4.6	0.000 000	-0.002
100 %		0	2594 999 993	-3.6	0.000 000	-0.001
100 %		+10	2594 999 994	-2.5	0.000 000	-0.001
100 %		+30	2595 000 001	3.8	0.000 000	0.001
100 %		+40	2594 999 991	-5.4	0.000 000	-0.002
100 %		+50	2594 999 992	-5.0	0.000 000	-0.002
Batt. Endpoint		3.550	+20	2594 999 993	-3.4	0.000 000



- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2594 999 998	0.0	0.000 000	0.000
100 %		-30	2594 999 995	-2.4	0.000 000	-0.001
100 %		-20	2594 999 995	-2.8	0.000 000	-0.001
100 %		-10	2594 999 994	-3.4	0.000 000	-0.001
100 %		0	2595 000 001	3.4	0.000 000	0.001
100 %		+10	2595 000 001	3.0	0.000 000	0.001
100 %		+30	2595 000 002	3.9	0.000 000	0.002
100 %		+40	2595 000 001	2.8	0.000 000	0.001
100 %		+50	2594 999 995	-2.8	0.000 000	-0.001
Batt. Endpoint		3.550	+20	2595 000 001	3.5	0.000 000






- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2594 999 995	0.0	0.000 000	0.000
100 %		-30	2594 999 992	-3.8	0.000 000	-0.001
100 %		-20	2594 999 991	-4.0	0.000 000	-0.002
100 %		-10	2594 999 999	3.6	0.000 000	0.001
100 %		0	2595 000 001	5.3	0.000 000	0.002
100 %		+10	2594 999 999	3.8	0.000 000	0.001
100 %		+30	2594 999 991	-4.5	0.000 000	-0.002
100 %		+40	2594 999 992	-3.4	0.000 000	-0.001
100 %		+50	2594 999 992	-3.3	0.000 000	-0.001
Batt. Endpoint	3.550	+20	2594 999 992	-3.7	0.000 000	-0.001




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2594 999 997	0.0	0.000 000	0.000
100 %		-30	2595 000 001	3.9	0.000 000	0.002
100 %		-20	2594 999 992	-4.5	0.000 000	-0.002
100 %		-10	2594 999 995	-2.0	0.000 000	-0.001
100 %		0	2595 000 001	4.1	0.000 000	0.002
100 %		+10	2595 000 001	3.7	0.000 000	0.001
100 %		+30	2594 999 994	-3.4	0.000 000	-0.001
100 %		+40	2594 999 994	-2.9	0.000 000	-0.001
100 %		+50	2594 999 994	-2.8	0.000 000	-0.001
Batt. Endpoint	3.550	+20	2594 999 994	-2.8	0.000 000	-0.001




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2617,500,000 Hz
- ▣ BANDWIDTH: 38225 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2617 499 997	0.0	0.000 000	0.000
100 %		-30	2617 499 993	-4.0	0.000 000	-0.002
100 %		-20	2617 499 994	-3.3	0.000 000	-0.001
100 %		-10	2617 499 995	-2.0	0.000 000	-0.001
100 %		0	2617 499 993	-4.2	0.000 000	-0.002
100 %		+10	2617 499 993	-3.5	0.000 000	-0.001
100 %		+30	2617 499 999	1.8	0.000 000	0.001
100 %		+40	2617 499 994	-3.3	0.000 000	-0.001
100 %		+50	2617 499 994	-3.0	0.000 000	-0.001
Batt. Endpoint		3.550	+20	2617 500 000	3.0	0.000 000




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2615,000,000 Hz
- ▣ BANDWIDTH: 38200 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2614 999 995	0.0	0.000 000	0.000
100 %		-30	2614 999 992	-3.6	0.000 000	-0.001
100 %		-20	2614 999 992	-3.6	0.000 000	-0.001
100 %		-10	2614 999 992	-3.6	0.000 000	-0.001
100 %		0	2614 999 991	-4.2	0.000 000	-0.002
100 %		+10	2614 999 992	-3.1	0.000 000	-0.001
100 %		+30	2614 999 992	-3.6	0.000 000	-0.001
100 %		+40	2614 999 991	-4.3	0.000 000	-0.002
100 %		+50	2614 999 992	-3.6	0.000 000	-0.001
Batt. Endpoint	3.550	+20	2614 999 992	-3.0	0.000 000	-0.001




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2612,500,000 Hz
- ▣ BANDWIDTH: 38175 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2612 499 997	0.0	0.000 000	0.000
100 %		-30	2612 499 993	-3.4	0.000 000	-0.001
100 %		-20	2612 499 992	-4.2	0.000 000	-0.002
100 %		-10	2612 499 994	-2.9	0.000 000	-0.001
100 %		0	2612 499 993	-3.2	0.000 000	-0.001
100 %		+10	2612 499 994	-2.3	0.000 000	-0.001
100 %		+30	2612 499 993	-3.8	0.000 000	-0.001
100 %		+40	2612 499 994	-2.9	0.000 000	-0.001
100 %		+50	2612 499 992	-4.8	0.000 000	-0.002
Batt. Endpoint	3.550	+20	2612 499 994	-3.1	0.000 000	-0.001




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2610,000,000 Hz
- ▣ BANDWIDTH: 38150 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2609 999 995	0.0	0.000 000	0.000
100 %		-30	2609 999 991	-3.5	0.000 000	-0.001
100 %		-20	2609 999 992	-2.9	0.000 000	-0.001
100 %		-10	2609 999 992	-2.8	0.000 000	-0.001
100 %		0	2609 999 992	-2.7	0.000 000	-0.001
100 %		+10	2609 999 991	-4.1	0.000 000	-0.002
100 %		+30	2609 999 992	-3.0	0.000 000	-0.001
100 %		+40	2609 999 991	-3.6	0.000 000	-0.001
100 %		+50	2609 999 992	-2.7	0.000 000	-0.001
Batt. Endpoint	3.550	+20	2609 999 992	-3.0	0.000 000	-0.001




## 9. TEST PLOTS

BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 QPSK RB 25)







BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 16-QAM RB 25)




BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 64-QAM RB 25)




BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 256-QAM RB 25)




BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 QPSK RB 50)




BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 16-QAM RB 50)




BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 64-QAM RB 50)



BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 256-QAM RB 50)




BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 QPSK RB 75)







BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 16-QAM RB 75)




BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 64-QAM RB 75)




BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 256-QAM RB 75)




BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 QPSK RB 100)




BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 16-QAM RB 100)




BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 64-QAM RB 100)



BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 256-QAM RB 100)




BAND 38. PAR Plot (5 M BW\_Ch.38000\_QPSK\_RB25\_0)







BAND 38. PAR Plot (5 M BW\_Ch.38000\_16QAM\_RB25\_0)




BAND 38. PAR Plot (5 M BW\_Ch.38000\_64QAM\_RB25\_0)




BAND 38. PAR Plot (5 M BW\_Ch.38000\_256QAM\_RB25\_0)




BAND 38. PAR Plot (10 M BW\_Ch.38000\_QPSK\_RB50\_0)




BAND 38. PAR Plot (10 M BW\_Ch.38000\_16QAM\_RB50\_0)




BAND 38. PAR Plot (10 M BW\_Ch.38000\_64QAM\_RB50\_0)



BAND 38. PAR Plot (10 M BW\_Ch.38000\_256QAM\_RB50\_0)




BAND 38. PAR Plot (15 M BW\_Ch.38000\_QPSK\_RB75\_0)







BAND 38. PAR Plot (15 M BW\_Ch.38000\_16QAM\_RB75\_0)




BAND 38. PAR Plot (15 M BW\_Ch.38000\_64QAM\_RB75\_0)




BAND 38. PAR Plot (15 M BW\_Ch.38000\_256QAM\_RB75\_0)




BAND 38. PAR Plot (20 M BW\_Ch.38000\_QPSK\_RB100\_0)




BAND 38. PAR Plot (20 M BW\_Ch.38000\_16QAM\_RB100\_0)




BAND 38. PAR Plot (20 M BW\_Ch.38000\_64QAM\_RB100\_0)



BAND 38. PAR Plot (20 M BW\_Ch.38000\_256QAM\_RB100\_0)




BAND 38. Low Channel Edge Plot (5 MHz Ch.37775 QPSK RB 1, Offset 0)







BAND 38. Low Channel Edge Plot (5 MHz Ch.37775 QPSK RB 25, Offset 0)




BAND 38. Mid Channel Edge Plot (5 MHz Ch.38000 QPSK RB 25)




BAND 38. High Channel Edge Plot (5 MHz Ch.38225 QPSK RB 1, Offset 0)




BAND 38. High Channel Edge Plot (5 MHz Ch.38225 QPSK\_RB25\_Offset 0)




BAND 38. Low Channel Edge Plot (10 MHz Ch.37800 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (10 MHz Ch.37800 QPSK RB 25, Offset 0)



BAND 38. Mid Channel Edge Plot (10 MHz Ch.38000 QPSK RB 50)




BAND 38. High Channel Edge Plot (10 MHz Ch.38200 QPSK RB 1, Offset 0)







BAND 38. High Channel Edge Plot (10 MHz Ch.38200 QPSK\_RB50\_Offset 0)




BAND 38. Low Channel Edge Plot (15 MHz Ch.37825 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (15 MHz Ch.37825 QPSK RB 75, Offset 0)




BAND 38. Mid Channel Edge Plot (15 MHz Ch.38000 QPSK RB 75)




BAND 38. High Channel Edge Plot (15 MHz Ch.38175 QPSK RB 1, Offset 0)




BAND 38. High Channel Edge Plot (15 MHz Ch.38175 QPSK\_RB75\_Offset 0)



BAND 38. Low Channel Edge Plot (20 MHz Ch.37850 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (20 MHz Ch.37850 QPSK RB 25, Offset 0)







BAND 38. Mid Channel Edge Plot (20 MHz Ch.38000 QPSK RB 100)




BAND 38. High Channel Edge Plot (20 MHz Ch.38150 QPSK RB 1, Offset 0)



BAND 38. High Channel Edge Plot (20 MHz Ch.38150 QPSK\_RB100\_Offset 0)




BAND 38. Conducted Spurious Plot 1 (5 MHz Ch.3775 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (5 MHz Ch. 37775 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (5 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (5 MHz Ch. 38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 1 (5 MHz Ch.38225 QPSK RB 1, Offset 0)






BAND 38. Conducted Spurious Plot 2 (5 MHz Ch. 38225 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (10 MHz Ch.37800 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (10 MHz Ch. 37800 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (10 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (10 MHz Ch. 38000 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (10 MHz Ch. 38200 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (10 MHz Ch. 38200 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 1 (15 MHz Ch.37825 QPSK RB 1, Offset 0)






BAND 38. Conducted Spurious Plot 2 (15 MHz Ch. 37825 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (15 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (15 MHz Ch. 38000 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (15 MHz Ch.38175 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (15 MHz Ch. 38175 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (20 MHz Ch.37850 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (20 MHz Ch. 37850 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 1 (20 MHz Ch.38000 QPSK RB 1, Offset 0)






BAND 38. Conducted Spurious Plot 2 (20 MHz Ch. 38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 1 (20 MHz Ch.38150 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (20 MHz Ch. 38150 QPSK RB 1, Offset 0)



## 10. ANNEX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2309-FC026-P