



FCC CFR47 PART 15 SUBPART C

DTS Wireless LAN

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n, ANT+ and NFC

MODEL NUMBER : SM-A310M/DS, SM-A310M

FCC ID: A3LSMA310M

REPORT NUMBER: 15K22210-E1

ISSUE DATE: DEC 01, 2015

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	11/25/15	Initial issue	Junwhan Lee
2	12/01/15	Revised equipment list and OBW test data	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE	8
5.5. DESCRIPTION OF TEST SETUP	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. MEASUREMENT METHODS	12
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	12
8.1. ON TIME AND DUTY CYCLE RESULTS	12
9. SUMMARY TABLE	13
10. ANTENNA PORT TEST RESULTS	14
10.1. 6 dB BANDWIDTH	14
10.1.1. 802.11b MODE IN THE 2.4 GHz BAND	14
10.1.2. 802.11g MODE IN THE 2.4 GHz BAND	14
10.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	14
10.1.4. 6 dB BANDWIDTH PLOTS	15
10.2. 99% BANDWIDTH	18
10.2.1. 802.11b MODE IN THE 2.4 GHz BAND	18
10.2.2. 802.11g MODE IN THE 2.4 GHz BAND	18
10.2.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	18
10.2.4. 99% BANDWIDTH PLOTS	19
10.3. OUTPUT POWER	22
10.3.1. 802.11b MODE IN THE 2.4 GHz BAND	22
10.3.2. 802.11g MODE IN THE 2.4 GHz BAND	23
10.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND	23
10.4. PSD	24

10.4.1.	802.11b MODE IN THE 2.4 GHz BAND	25
10.4.2.	802.11g MODE IN THE 2.4 GHz BAND	25
10.4.3.	802.11n HT20 MODE IN THE 2.4 GHz BAND	25
10.4.4.	PSD PLOTS	26
10.5.	<i>OUT-OF-BAND EMISSIONS</i>	29
10.5.1.	802.11b MODE IN THE 2.4 GHz BAND	30
10.5.2.	802.11g MODE IN THE 2.4 GHz BAND	31
10.5.3.	802.11n HT20 MODE IN THE 2.4 GHz BAND	32
11.	RADIATED TEST RESULTS	33
11.1.	<i>LIMITS AND PROCEDURE</i>	33
11.2.	<i>TRANSMITTER ABOVE 1 GHz</i>	34
11.2.1.	TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND	34
11.2.2.	TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND	44
11.2.3.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND	54
11.3.	<i>WORST-CASE BELOW 1 GHz</i>	64
12.	AC POWER LINE CONDUCTED EMISSIONS	66
13.	SETUP PHOTOS	69

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n, ANT+ and NFC
MODEL NUMBER: SM-A310M/DS, SM-A310M
SERIAL NUMBER: 31004a4aeb191221 (RADIATED); R38GA0PDTTJ (CONDUCTED)
DATE TESTED: NOV 09, 2015 - NOV 24, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
<input checked="" type="checkbox"/> Chamber 1
<input checked="" type="checkbox"/> Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

This EUT is GSM/WCDMA/LTE Phone + BT/BLE, DTS b/g/n, ANT+ and NFC.
This test report addresses the DTS (WLAN) operational mode.

SM-A310M and SM-A310M/DS are same hardware but for different number of SIM card slot.
SM-A310M has one slot. SM-A310M/DS is dual SIM version.
SM-A310M/DS was used for the test.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range [MHz]	Mode	Output Power [dBm]	Output Power [mW]
2412 - 2462	802.11b	17.27	53.33
	802.11g	14.26	26.67
	802.11n HT20	13.31	21.43

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antennas, with a antenna's maximum gain of -3.75 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Based on the baseline scan, the worst-case data rates were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50EWE	DK2G608VS/A-E	N/A
Data Cable	SAMSUNG	EP-DG920UWE	N/A	N/A
Earphone	SAMSUNG	EHS64AVFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-16
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-16
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-16
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-16
Antenna, Horn, 40 GHz	ETS	3116C	00166255	09-23-16
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	09-29-16
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-18-16
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-18-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-19-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-19-16
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-16
Average Power Sensor	R&S	NRZ-Z91	102681	08-18-16
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-18-16
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-19-16
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-19-16
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-19-16
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	08-18-16
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	015	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	016	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	015	08-18-16
LISN	R&S	ENV-216	101836	08-19-16
LISN	R&S	ENV-216	101837	08-19-16

7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r03: Measurement Procedure §9.2.3.1 AVGPm is used for average power and §10.2 AVGPS-2 is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
2400MHz Bands						
802.11b	8.607	8.706	0.989	98.9%	0.00	0.010
802.11g	1.428	1.53	0.933	93.3%	0.30	0.700
802.11n HT20	1.335	1.437	0.929	92.9%	0.32	0.749



[802.11b Mode]

[802.11g Mode]

[802.11n Mode]

9. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	9.036 MHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-30dBc		Pass	-29.531 dBm
15.247	TX conducted output power	<30dBm		Pass	17.27 dBm
15.247	PSD	<8dBm		Pass	-13.352 dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	48.32 dBuV (QP)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	49.13 dBuV/m (AV)

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to KDB 558074 D01 DTS Meas Guidance v03r03: The transmitter output is connected to a spectrum analyzer with the RBW set to 100KHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

10.1.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Minimum Limit [MHz]
Low	2412	9.541	0.5
Mid	2437	9.533	0.5
High	2462	9.036	0.5
Worst		9.036	0.5


10.1.2. 802.11g MODE IN THE 2.4 GHz BAND


Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Minimum Limit [MHz]
Low	2412	15.435	0.5
Mid	2437	15.696	0.5
High	2462	15.668	0.5
Worst		15.435	0.5


10.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Minimum Limit [MHz]
Low	2412	15.456	0.5
Mid	2437	16.076	0.5
High	2462	15.920	0.5
Worst		15.456	0.5

10.1.4. 6 dB BANDWIDTH PLOTS







10.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.2.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2412	14.232
Mid	2437	14.025
High	2462	14.170
Worst		14.232


10.2.2. 802.11g MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2412	16.281
Mid	2437	16.411
High	2462	16.321
Worst		16.411


10.2.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2412	17.428
Mid	2437	17.545
High	2462	17.473
Worst		17.545

10.2.4. 99% BANDWIDTH PLOTS







10.3. OUTPUT POWER

LIMITS

FCC §15.247

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

10.3.1. 802.11b MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-3.75	30.00	30.00	36.00	30.00
Mid	2437	-3.89	30.00	30.00	36.00	30.00
High	2462	-4.02	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	16.92	16.92	36.00	-19.08
Mid	2437	17.27	17.27	36.00	-18.73
High	2462	16.84	16.84	36.00	-19.16
Worst			17.27	36.00	-18.73

10.3.2. 802.11g MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-3.75	30.00	30.00	36.00	30.00
Mid	2437	-3.89	30.00	30.00	36.00	30.00
High	2462	-4.02	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	13.93	13.93	36.00	-22.07
Mid	2437	14.26	14.26	36.00	-21.74
High	2462	13.83	13.83	36.00	-22.17
Worst			14.26	36.00	-21.74

10.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-3.75	30.00	30.00	36.00	30.00
Mid	2437	-3.89	30.00	30.00	36.00	30.00
High	2462	-4.02	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	12.77	12.77	36.00	-23.23
Mid	2437	13.31	13.31	36.00	-22.69
High	2462	12.72	12.72	36.00	-23.28
Worst			13.31	36.00	-22.69

10.4. PSD

LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

Power Spectral Density was performed utilizing the "Method AVGPS-2" under KDB558074 D01 DTS Meas Guidance v03r03

RESULTS

10.4.1. 802.11b MODE IN THE 2.4 GHz BAND

PSD Results

Channel	Frequency [MHz]	PSD Meas [dBm]	Duty Factor [dB]	Final PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-13.968	0.00	-13.968	8.00	-21.968
Mid	2437	-13.352	0.00	-13.352	8.00	-21.352
High	2462	-13.944	0.00	-13.944	8.00	-21.944

10.4.2. 802.11g MODE IN THE 2.4 GHz BAND

PSD Results


Channel	Frequency [MHz]	PSD Meas [dBm]	Duty Factor [dB]	Final PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-20.507	0.30	-20.207	8.00	-28.507
Mid	2437	-19.772	0.30	-19.472	8.00	-27.772
High	2462	-20.262	0.30	-19.962	8.00	-28.262


10.4.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND


PSD Results

Channel	Frequency [MHz]	PSD Meas [dBm]	Duty Factor [dB]	Final PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-21.011	0.33	-20.681	8.00	-29.011
Mid	2437	-20.614	0.33	-20.284	8.00	-28.614
High	2462	-20.986	0.33	-20.656	8.00	-28.986

10.4.4. PSD PLOTS







10.5. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.

RESULTS


10.5.1. 802.11b MODE IN THE 2.4 GHz BAND



10.5.2. 802.11g MODE IN THE 2.4 GHz BAND



10.5.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND



11. RADIATED TEST RESULTS

11.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor = $10 \log(1/x)$ For this sample B mode = 0dB (duty cycle >98%); G mode = 0.30dB; N mode = 0.32dB.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

11.2. TRANSMITTER ABOVE 1 GHz

11.2.1. TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	49.63	PK	31.8	-28.4	0	53.03	-	-	74	-20.97	241	100	H
2	* 2.389	52.82	PK	31.8	-28.4	0	56.22	-	-	74	-17.78	241	100	H
3	* 2.39	40.09	RMS	31.8	-28.4	0	43.49	54	-10.51	-	-	241	100	H
4	* 2.389	42.3	RMS	31.8	-28.4	0	45.7	54	-8.3	-	-	241	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	48.21	PK	31.8	-28.4	0	51.61	-	-	74	-22.39	216	309	V
2	* 2.387	50.59	PK	31.8	-28.5	0	53.89	-	-	74	-20.11	216	309	V
3	* 2.39	38.06	RMS	31.8	-28.4	0	41.46	54	-12.54	-	-	216	309	V
4	* 2.389	40.59	RMS	31.8	-28.4	0	43.99	54	-10.01	-	-	216	309	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17_150619)	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	50.1	PK	32	-28.3	0	53.8	-	-	74	-20.2	319	102	H
2	* 2.488	51.3	PK	32	-28.3	0	55	-	-	74	-19	319	102	H
3	* 2.484	39.44	RMS	32	-28.3	0	43.14	54	-10.86	-	-	319	102	H
4	* 2.487	40.8	RMS	32	-28.3	0	44.5	54	-9.5	-	-	319	102	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	49.38	Pk	32	-28.3	0	53.08	-	-	74	-20.92	212	359	V
2	* 2.486	51.99	PK	32	-28.3	0	55.69	-	-	74	-18.31	212	359	V
3	* 2.484	39.31	RMS	32	-28.3	0	43.01	54	-10.99	-	-	212	359	V
4	* 2.487	40.82	RMS	32	-28.3	0	44.52	54	-9.48	-	-	212	359	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.823	38.99	PK	34	-33	0	39.99	-	-	74	-34.01	0-360	100	H
3	7.236	38.33	PK	35.7	-30.1	0	43.93	-	-	74	-30.07	0-360	200	H
5	9.651	30.65	PK	37.1	-26.8	0	40.95	-	-	74	-33.05	0-360	200	H
2	* 4.823	37.05	PK	34	-33	0	38.05	-	-	74	-35.95	0-360	200	V
4	7.236	44.38	PK	35.7	-30.1	0	49.98	-	-	74	-24.02	0-360	100	V
6	9.645	30.81	PK	37.1	-26.8	0	41.11	-	-	74	-32.89	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.824	49.09	PK2	34	-33	0	50.09	-	-	74	-23.91	112	307	H
* 4.824	37.51	MAv1	34	-33	0	38.51	54	-15.49	-	-	112	307	H
* 4.824	48.38	PK2	34	-33	0	49.38	-	-	74	-24.62	246	331	V
* 4.824	37.75	MAv1	34	-33	0	38.75	54	-15.25	-	-	246	331	V
7.235	49.44	PK2	35.7	-30.1	0	55.04	-	-	74	-18.96	344	293	H
7.235	51.42	PK2	35.7	-30.1	0	57.02	-	-	74	-16.98	248	101	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.877	36.45	PK	34	-33.1	0	37.35	-	-	74	-36.65	0-360	200	H
3	* 7.309	37.25	PK	35.7	-30.1	0	42.85	-	-	74	-31.15	0-360	200	H
5	9.751	30.56	PK	37.2	-26	0	41.76	-	-	74	-32.24	0-360	100	H
2	* 4.871	36.78	PK	34	-33.1	0	37.68	-	-	74	-36.32	0-360	200	V
4	* 7.309	42.64	PK	35.7	-30.1	0	48.24	-	-	74	-25.76	0-360	100	V
6	9.751	30.69	PK	37.2	-26	0	41.89	-	-	74	-32.11	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001 68717)_1 50619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.31	48.33	PK2	35.7	-30.1	0	53.93	-	-	74	-20.07	350	391	H
* 7.312	38.4	MAv1	35.7	-30.1	0	44	54	-10	-	-	350	391	H
* 7.312	51.21	PK2	35.7	-30.1	0	56.81	-	-	74	-17.19	249	100	V
* 7.31	43.53	MAv1	35.7	-30.1	0	49.13	54	-4.87	-	-	249	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.924	38.62	PK	34	-33.1	0	39.52	-	-	74	-34.48	0-360	100	H
3	* 7.386	40.2	PK	35.8	-29.9	0	46.1	-	-	74	-27.9	0-360	200	H
5	9.853	31.78	PK	37.3	-27	0	42.08	-	-	74	-31.92	0-360	200	H
2	* 4.924	37.46	PK	34	-33.1	0	38.36	-	-	74	-35.64	0-360	200	V
4	* 7.385	45.41	PK	35.8	-29.9	0	51.31	-	-	74	-22.69	0-360	100	V
6	9.847	31.17	PK	37.3	-26.9	0	41.57	-	-	74	-32.43	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001 68717)_1 50619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.924	36.46	MAv1	34	-33.1	0	37.36	54	-16.64	-	-	172	201	H
* 4.926	47.64	PK2	34	-33.1	0	48.54	-	-	74	-25.46	172	201	H
* 7.387	40.48	MAv1	35.8	-29.9	0	46.38	54	-7.62	-	-	339	283	H
* 7.387	48.85	PK2	35.8	-29.9	0	54.75	-	-	74	-19.25	339	283	H
* 7.386	49.97	PK2	35.8	-29.9	0	55.87	-	-	74	-18.13	253	354	V
* 7.387	41.95	MAv1	35.8	-29.9	0	47.85	54	-6.15	-	-	253	354	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

11.2.2. TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND
RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	55.21	Pk	31.8	-28.4	0	58.61	-	-	74	-15.39	306	111	H
2	* 2.39	60.25	Pk	31.8	-28.4	0	63.65	-	-	74	-10.35	306	111	H
3	* 2.39	43.93	RMS	31.8	-28.4	.3	47.63	54	-6.37	-	-	306	111	H
4	* 2.39	44.42	RMS	31.8	-28.4	.3	48.12	54	-5.88	-	-	306	111	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	54.51	Pk	31.8	-28.4	0	57.91	-	-	74	-16.09	206	302	V
2	* 2.389	56.26	Pk	31.8	-28.4	0	59.66	-	-	74	-14.34	206	302	V
3	* 2.39	42.47	RMS	31.8	-28.4	.3	46.17	54	-7.83	-	-	206	302	V
4	* 2.39	42.62	RMS	31.8	-28.4	.3	46.32	54	-7.68	-	-	206	302	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	57.6	Pk	32	-28.3	0	61.3	-	-	74	-12.7	297	103	H
2	* 2.484	60.7	Pk	32	-28.3	0	64.4	-	-	74	-9.6	297	103	H
3	* 2.484	44.61	RMS	32	-28.3	.3	48.61	54	-5.39	-	-	297	103	H
4	* 2.484	44.82	RMS	32	-28.3	.3	48.82	54	-5.18	-	-	297	103	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	52.03	Pk	32	-28.3	0	55.73	-	-	74	-18.27	199	356	V
2	* 2.484	57.83	Pk	32	-28.3	0	61.53	-	-	74	-12.47	199	356	V
3	* 2.484	42.37	RMS	32	-28.3	.3	46.37	54	-7.63	-	-	199	356	V
4	* 2.484	42.33	RMS	32	-28.3	.3	46.33	54	-7.67	-	-	199	356	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.826	36.35	PK	34	-33	0	37.35	-	-	74	-36.65	0-360	100	H
3	7.234	35.83	PK	35.7	-30.1	0	41.43	-	-	74	-32.57	0-360	200	H
5	9.647	30.51	PK	37.1	-26.8	0	40.81	-	-	74	-33.19	0-360	200	H
2	* 4.824	36.22	PK	34	-33	0	37.22	-	-	74	-36.78	0-360	100	V
4	7.229	40.7	PK	35.7	-30.1	0	46.3	-	-	74	-27.7	0-360	100	V
6	9.651	30.78	PK	37.1	-26.8	0	41.08	-	-	74	-32.92	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
7.24	48.3	PK2	35.7	-30.1	0	53.9	-	-	74	-20.1	350	290	H
7.235	54.7	PK2	35.7	-30.1	0	60.3	-	-	74	-13.7	240	101	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.877	35.62	PK	34	-33.1	0	36.52	-	-	74	-37.48	0-360	200	H
3	* 7.31	34.47	PK	35.7	-30.1	0	40.07	-	-	74	-33.93	0-360	200	H
5	9.748	30.55	PK	37.2	-26.1	0	41.65	-	-	74	-32.35	0-360	100	H
2	* 4.877	35.99	PK	34	-33.1	0	36.89	-	-	74	-37.11	0-360	100	V
4	* 7.31	39.62	PK	35.7	-30.1	0	45.22	-	-	74	-28.78	0-360	100	V
6	9.748	30.97	PK	37.2	-26.1	0	42.07	-	-	74	-31.93	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001 68717)_1 50619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.318	48.42	PK2	35.8	-30	0	54.22	-	-	74	-19.78	9	313	H
* 7.311	33.94	MAv1	35.7	-30.1	.3	39.84	54	-14.16	-	-	9	313	H
* 7.312	53.82	PK2	35.7	-30.1	0	59.42	-	-	74	-14.58	255	102	V
* 7.311	38.03	MAv1	35.7	-30.1	.3	43.93	54	-10.07	-	-	255	102	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.925	35.77	Avg	34	-33.1	0	36.67	-	-	74	-37.33	0-360	100	H
3	* 7.386	35.32	Avg	35.8	-29.9	0	41.22	-	-	74	-32.78	0-360	200	H
5	9.848	31.08	Avg	37.3	-27	0	41.38	-	-	74	-32.62	0-360	200	H
2	* 4.924	35.64	Avg	34	-33.1	0	36.54	-	-	74	-37.46	0-360	200	V
4	* 7.386	41.44	Avg	35.8	-29.9	0	47.34	-	-	74	-26.66	0-360	100	V
6	9.849	31.17	Avg	37.3	-27	0	41.47	-	-	74	-32.53	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.386	49.5	PK2	35.8	-29.9	0	55.4	-	-	74	-18.6	322	360	H
* 7.386	35.62	MAv1	35.8	-29.9	.3	41.82	54	-12.18	-	-	322	360	H
* 7.386	54.21	PK2	35.8	-29.9	0	60.11	-	-	74	-13.89	256	101	V
* 7.386	39.01	MAv1	35.8	-29.9	.3	45.21	54	-8.79	-	-	256	101	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

11.2.3. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	59.58	Pk	31.8	-28.4	0	62.98	-	-	74	-11.02	304	101	H
2	* 2.39	61.57	Pk	31.8	-28.4	0	64.97	-	-	74	-9.03	304	101	H
3	* 2.39	45.05	RMS	31.8	-28.4	.32	48.77	54	-5.23	-	-	304	101	H
4	* 2.39	45.31	RMS	31.8	-28.4	.32	49.03	54	-4.97	-	-	304	101	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	51.17	Pk	31.8	-28.4	0	54.57	-	-	74	-19.43	195	298	V
2	* 2.389	53.69	Pk	31.8	-28.4	0	57.09	-	-	74	-16.91	195	298	V
3	* 2.39	40.64	RMS	31.8	-28.4	.32	44.36	54	-9.64	-	-	195	298	V
4	* 2.39	40.86	RMS	31.8	-28.4	.32	44.58	54	-9.42	-	-	195	298	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	56.03	Pk	32	-28.3	0	59.73	-	-	74	-14.27	312	103	H
2	* 2.484	60.45	Pk	32	-28.3	0	64.15	-	-	74	-9.85	312	103	H
3	* 2.484	42.94	RMS	32	-28.3	.32	46.96	54	-7.04	-	-	312	103	H
4	* 2.484	43.75	RMS	32	-28.3	.32	47.77	54	-6.23	-	-	312	103	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	56.06	Pk	32	-28.3	0	59.76	-	-	74	-14.24	199	357	V
2	* 2.484	58.63	Pk	32	-28.3	0	62.33	-	-	74	-11.67	199	357	V
3	* 2.484	40.88	RMS	32	-28.3	.32	44.9	54	-9.1	-	-	199	357	V
4	* 2.484	42.06	RMS	32	-28.3	.32	46.08	54	-7.92	-	-	199	357	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.821	35.95	PK	34	-33	0	36.95	-	-	74	-37.05	0-360	200	H
3	7.241	34.71	PK	35.7	-30.1	0	40.31	-	-	74	-33.69	0-360	200	H
5	9.647	30.93	PK	37.1	-26.8	0	41.23	-	-	74	-32.77	0-360	100	H
2	* 4.83	36.14	PK	34	-33	0	37.14	-	-	74	-36.86	0-360	200	V
4	7.235	38.61	PK	35.7	-30.1	0	44.21	-	-	74	-29.79	0-360	100	V
6	9.647	31.28	PK	37.1	-26.8	0	41.58	-	-	74	-32.42	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
7.239	34.16	PK2	35.7	-30.1	0	39.76	-	-	74	-34.24	334	365	H
7.236	45.5	PK2	35.7	-30.1	0	51.1	-	-	74	-22.9	249	102	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.876	35.98	PK	34	-33.1	0	36.88	-	-	74	-37.12	0-360	100	H
3	* 7.307	35.12	PK	35.7	-30.1	0	40.72	-	-	74	-33.28	0-360	200	H
5	9.744	30.99	PK	37.2	-26.2	0	41.99	-	-	74	-32.01	0-360	100	H
2	* 4.874	35.64	PK	34	-33.1	0	36.54	-	-	74	-37.46	0-360	100	V
4	* 7.308	36.6	PK	35.7	-30.1	0	42.2	-	-	74	-31.8	0-360	100	V
6	9.744	30.67	PK	37.2	-26.2	0	41.67	-	-	74	-32.33	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001 68717)_1 50619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.306	46.77	PK2	35.7	-30.1	0	52.37	-	-	74	-21.63	344	286	H
* 7.31	32.99	MAv1	35.7	-30.1	.32	38.91	54	-15.09	-	-	344	286	H
* 7.306	51.63	PK2	35.7	-30.1	0	57.23	-	-	74	-16.77	265	100	V
* 7.307	36.46	MAv1	35.7	-30.1	.32	42.38	54	-11.62	-	-	265	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.927	36.2	PK	34	-33.1	0	37.1	-	-	74	-36.9	0-360	200	H
3	* 7.384	35.66	PK	35.8	-29.9	0	41.56	-	-	74	-32.44	0-360	200	H
5	9.844	31.11	PK	37.3	-26.9	0	41.51	-	-	74	-32.49	0-360	200	H
2	* 4.924	35.47	PK	34	-33.1	0	36.37	-	-	74	-37.63	0-360	200	V
4	* 7.385	37.5	PK	35.8	-29.9	0	43.4	-	-	74	-30.6	0-360	100	V
6	9.847	31.61	PK	37.3	-26.9	0	42.01	-	-	74	-31.99	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.392	48.76	PK2	35.8	-29.9	0	54.66	-	-	74	-19.34	340	380	H
* 7.386	33.73	MAv1	35.8	-29.9	.32	39.95	54	-14.05	-	-	340	380	H
* 7.386	50.01	PK2	35.8	-29.9	0	55.91	-	-	74	-18.09	256	353	V
* 7.386	37	MAv1	35.8	-29.9	.32	43.22	54	-10.78	-	-	256	353	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak


MAv1 - KDB558074 Option 1 Maximum RMS Average

11.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



Below 1G Data

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	97.235	51.57	Pk	11	-30.6	31.97	43.52	-11.55	0-360	300	H
5	146.4075	50.77	Pk	8.1	-30.4	28.47	43.52	-15.05	0-360	200	H
6	* 162.7275	50.25	Pk	8.7	-30.4	28.55	43.52	-14.97	0-360	200	H
1	47.085	47.46	Pk	14	-30.8	30.66	40	-9.34	0-360	100	V
2	57.625	39.02	Pk	13.1	-30.7	21.42	40	-18.58	0-360	300	V
3	97.065	48.65	Pk	11	-30.6	29.05	43.52	-14.47	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

12. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10 2009.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers


Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.168	34.66	Pk	10.1	0	44.76	65.06	-20.3	-	-
2	.168	13.92	Av	10.1	0	24.02	-	-	55.06	-31.04
3	.267	32.7	Pk	9.9	0	42.6	61.21	-18.61	-	-
4	.2625	14.57	Av	9.9	0	24.47	-	-	51.35	-26.88
5	.582	33.06	Pk	10.1	0	43.16	56	-12.84	-	-
6	.573	17.85	Av	10.1	0	27.95	-	-	46	-18.05
7	1.2075	25.78	Pk	9.8	.1	35.68	56	-20.32	-	-
8	1.2165	10.72	Av	9.8	.1	20.62	-	-	46	-25.38
9	9.9465	38.29	Pk	9.7	.2	48.19	60	-11.81	-	-
10	9.951	22.45	Av	9.7	.2	32.35	-	-	50	-17.65
11	10.5135	38.42	Pk	9.7	.2	48.32	60	-11.68	-	-
12	10.419	21.98	Av	9.7	.2	31.88	-	-	50	-18.12

Pk - Peak detector

Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L 1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.195	32.53	Pk	9.7	0	42.23	63.82	-21.59	-	-
14	.168	12.13	Av	9.8	0	21.93	-	-	55.06	-33.13
15	.267	32.07	Pk	9.7	0	41.77	61.21	-19.44	-	-
16	.267	13.73	Av	9.7	0	23.43	-	-	51.21	-27.78
17	.5775	31.62	Pk	10	0	41.62	56	-14.38	-	-
18	.5685	18.72	Av	10	0	28.72	-	-	46	-17.28
19	1.1805	26.98	Pk	9.5	.1	36.58	56	-19.42	-	-
20	1.2075	11.3	Av	9.5	.1	20.9	-	-	46	-25.1
21	9.9645	37.01	Pk	9.3	.2	46.51	60	-13.49	-	-
22	9.969	21.56	Av	9.3	.2	31.06	-	-	50	-18.94
23	10.5675	35.84	Pk	9.3	.2	45.34	60	-14.66	-	-
24	10.5855	20.74	Av	9.3	.2	30.24	-	-	50	-19.76

Pk - Peak detector