

FCC LTE REPORT

Certification

Applicant Name: SAMSUNG Electronics Co., Ltd.	Date of Issue: February 26, 2020
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea	Location: HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
	Report No.: HCT-RF-2002-FC017

FCC ID: A3LSMA315GL

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-A315G/DSL
Additional Model(s): SM-A315G/L
EUT Type: Mobile Phone
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band12 (1.4)	699.7 – 715.3	1M09G7D	QPSK	0.064	18.04
		1M09W7D	16QAM	0.054	17.29
		1M09W7D	64QAM	0.042	16.28
LTE – Band12 (3)	700.5 – 714.5	2M70G7D	QPSK	0.062	17.95
		2M69W7D	16QAM	0.053	17.23
		2M69W7D	64QAM	0.042	16.19
LTE – Band12/17 (5)	701.5 – 713.5	4M52G7D	QPSK	0.059	17.67
		4M50W7D	16QAM	0.050	16.95
		4M53W7D	64QAM	0.039	15.93
LTE – Band12/17 (10)	704.0 – 711.0	8M96G7D	QPSK	0.053	17.28
		8M98W7D	16QAM	0.045	16.49
		8M97W7D	64QAM	0.035	15.47

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Report prepared by : Jae Ryang Do
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2002-FC017	February 26, 2020	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.(HCT Accreditation No.: KT197)

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. DESCRIPTION OF EUT.....	5
2.2. MEASURING INSTRUMENT CALIBRATION	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 TEST PROCEDURE	6
3.2 RADIATED POWER.....	7
3.3 RADIATED SPURIOUS EMISSIONS	8
3.4 OCCUPIED BANDWIDTH.....	9
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	10
3.6 BAND EDGE	11
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	12
3.8 WORST CASE(RADIATED TEST).....	13
3.9 WORST CASE(CONDUCTED TEST)	14
4. LIST OF TEST EQUIPMENT	15
5. MEASUREMENT UNCERTAINTY	16
6. SUMMARY OF TEST RESULTS	17
7. SAMPLE CALCULATION	18
8. TEST DATA	20
8.1 EFFECTIVE RADIATED POWER.....	20
8.2 RADIATED SPURIOUS EMISSIONS	22
8.3 OCCUPIED BANDWIDTH	26
8.4 CONDUCTED SPURIOUS EMISSIONS	27
8.5 BAND EDGE	27
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	28
9. TEST PLOTS.....	40
10. ANNEX A_ TEST SETUP PHOTO.....	92

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMA315GL
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§27, §2
EUT Type:	Mobile Phone
Model(s):	SM-A315G/DSL
Additional Model(s):	SM-A315G/L
Tx Frequency:	699.7 MHz – 715.3 MHz (LTE – Band 12 (1.4 MHz)) 700.5 MHz – 714.5 MHz (LTE – Band 12 (3 MHz)) 701.5 MHz – 713.5 MHz (LTE – Band 12/17 (5 MHz)) 704.0 MHz – 711.0 MHz (LTE – Band 12/17 (10 MHz))
Date(s) of Tests:	February 05, 2020 ~ February 17, 2020

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), Bluetooth, BT LE, NFC, ANT+.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dB})$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = \text{Pg}_{(\text{dBm})} - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dBi})$$

Where: Pg is the generator output power into the substitution antenna.

If the fundamental frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 * Span / RBW

3.6 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- LTE Band 12 (698 – 716 MHz, 5/10MHzbandwidth) overlaps the entire frequency range of LTE Band 17 (704 - 716 MHz) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 17 as well as Band 12.

- SM-A315G/DSL & additional models were tested and the worst case results are reported.

(Worst case : SM-A315G/DSL)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM	1	0	Y
Radiated Spurious and Harmonic Emissions	QPSK	1	0	X

3.9 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- LTE Band 12 (698 – 716 MHz, 5/10MHzbandwidth) overlaps the entire frequency range of LTE Band 17 (704 - 716 MHz) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 17 as well as Band 12.

- SM-A315G/DSL & additional models were tested and the worst case results are reported.

(Worst case : SM-A315G/DSL)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	1.4, 3, 5, 10	Mid	Full RB	0
Band Edge	* QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		1.4, 3, 5, 10	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	* QPSK	1.4, 3, 5, 10	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacturer	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	06/10/2019	Annual	06/10/2020
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	06/10/2019	Annual	06/10/2020
WAINWRIGHT INSTRUMENT	WHNX6.0/26.5G-6SS/H.P.F	1	03/20/2019	Annual	03/20/2020
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/03/2019	Annual	05/03/2020
Agilent	E3632A/DC Power Supply	MY40004326	07/01/2019	Annual	07/01/2020
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93000717	08/14/2019	Annual	08/14/2020
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	01/28/2019	Biennial	01/28/2021
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	05/08/2019	Annual	05/08/2020
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2019	Annual	06/04/2020
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2019	Annual	10/14/2020
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/27/2019	Annual	08/27/2020
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/09/2019	Annual	08/09/2020
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/22/2021
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/15/2019	Annual	07/15/2020
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	05/17/2019	Annual	05/17/2020
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(g)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§27.50(c)(10)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(g)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

64QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP		
								W	W	dBm	
699.7	LTE B12 (1.4 MHz)	QPSK	-32.94	27.82	-9.92	1.18	V	< 3.00	0.047	16.72	
		16-QAM	-33.67	27.09	-9.92	1.18	V		0.040	15.99	
		64-QAM	-34.70	26.06	-9.92	1.18	V		0.031	14.96	
707.5		QPSK	-32.27	28.50	-9.93	1.18	V		0.055	17.39	
		16-QAM	-33.05	27.72	-9.93	1.18	V		0.046	16.61	
		64-QAM	-34.05	26.72	-9.93	1.18	V		0.036	15.61	
715.3		QPSK	-31.33	29.17	-9.94	1.19	V		0.064	18.04	
		16-QAM	-32.08	28.42	-9.94	1.19	V		0.054	17.29	
		64-QAM	-33.09	27.41	-9.94	1.19	V		0.042	16.28	

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP		
								W	W	dBm	
700.5	LTE B12 (3 MHz)	QPSK	-32.88	27.90	-9.92	1.18	V	< 3.00	0.048	16.80	
		16-QAM	-33.59	27.19	-9.92	1.18	V		0.041	16.09	
		64-QAM	-34.64	26.14	-9.92	1.18	V		0.032	15.04	
707.5		QPSK	-32.30	28.47	-9.93	1.18	V		0.055	17.36	
		16-QAM	-33.08	27.69	-9.93	1.18	V		0.046	16.58	
		64-QAM	-34.11	26.66	-9.93	1.18	V		0.036	15.55	
714.5		QPSK	-31.44	29.08	-9.94	1.19	V		0.062	17.95	
		16-QAM	-32.16	28.36	-9.94	1.19	V		0.053	17.23	
		64-QAM	-33.20	27.32	-9.94	1.19	V		0.042	16.19	

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP			
									W	W	dBm	
701.5	LTE B12/17 (5 MHz)	QPSK	-33.00	27.80	-9.92	1.18	V	< 3.00	0.047	16.70		
		16-QAM	-33.73	27.07	-9.92	1.18	V		0.040	15.97		
		64-QAM	-34.75	26.05	-9.92	1.18	V		0.031	14.95		
707.5		QPSK	-32.51	28.26	-9.93	1.18	V		0.052	17.15		
		16-QAM	-33.31	27.46	-9.93	1.18	V		0.043	16.35		
		64-QAM	-34.32	26.45	-9.93	1.18	V		0.034	15.34		
713.5		QPSK	-31.78	28.79	-9.94	1.18	V		0.059	17.67		
		16-QAM	-32.50	28.07	-9.94	1.18	V		0.050	16.95		
		64-QAM	-33.52	27.05	-9.94	1.18	V		0.039	15.93		

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP			
									W	W	dBm	
704.0	LTE B12/17 (10 MHz)	QPSK	-32.90	27.94	-9.92	1.18	V	< 3.00	0.048	16.84		
		16-QAM	-33.61	27.23	-9.92	1.18	V		0.041	16.13		
		64-QAM	-34.67	26.17	-9.92	1.18	V		0.032	15.07		
707.5		QPSK	-32.61	28.16	-9.93	1.18	V		0.051	17.05		
		16-QAM	-33.38	27.39	-9.93	1.18	V		0.043	16.28		
		64-QAM	-34.44	26.33	-9.93	1.18	V		0.033	15.22		
711.0		QPSK	-32.29	28.40	-9.94	1.18	V		0.053	17.28		
		16-QAM	-33.08	27.61	-9.94	1.18	V		0.045	16.49		
		64-QAM	-34.10	26.59	-9.94	1.18	V		0.035	15.47		

8.2 RADIATED SPURIOUS EMISSIONS

OPERATING FREQUENCY: 715.3 MHz
 MEASURED OUTPUT POWER: 20.19 dBm = 0.104 W
 MODE: LTE B12
 MODULATION SIGNAL: 1.4 MHz QPSK
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.19 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23017 (699.7)	1,399.40	-46.98	7.60	-56.07	1.70	H	-50.17	70.35
	2,099.10	-55.77	9.80	-60.19	2.10	V	-52.49	72.68
	2,798.80	-57.03	10.90	-59.70	2.45	H	-51.25	71.44
23095 (707.5)	1,415.00	-50.06	7.72	-59.23	1.71	H	-53.22	73.40
	2,122.50	-56.42	9.55	-60.56	2.11	H	-53.12	73.30
	2,830.00	-57.79	10.95	-59.87	2.47	H	-51.39	71.57
23173 (715.3)	1,430.60	-49.00	7.75	-58.34	1.70	H	-52.29	72.48
	2,145.90	-55.84	9.37	-59.71	2.12	V	-52.46	72.65
	2,861.20	-57.27	11.03	-59.39	2.47	H	-50.83	71.02

OPERATING FREQUENCY: 714.5 MHz
 MEASURED OUTPUT POWER: 20.10 dBm = 0.102 W
 MODE: LTE B12
 MODULATION SIGNAL: 3 MHz QPSK
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.10 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23025 (700.5)	1,401.00	-48.16	7.60	-57.25	1.70	H	-51.35	71.45
	2,101.50	-56.13	9.80	-60.55	2.10	H	-52.85	72.96
	2,802.00	-57.66	10.90	-60.33	2.45	H	-51.88	71.99
23095 (707.5)	1,415.00	-50.85	7.72	-60.02	1.71	H	-54.01	74.11
	2,122.50	-56.36	9.55	-60.50	2.11	H	-53.06	73.16
	2,830.00	-56.79	10.95	-58.87	2.47	H	-50.39	70.49
23165 (714.5)	1,429.00	-49.09	7.75	-58.43	1.70	H	-52.38	72.48
	2,143.50	-56.31	9.37	-60.18	2.12	H	-52.93	73.03
	2,858.00	-57.28	11.03	-59.40	2.47	H	-50.84	70.95

OPERATING FREQUENCY: 713.5 MHz
 MEASURED OUTPUT POWER: 19.82 dBm = 0.096 W
 MODE: LTE B12/17
 MODULATION SIGNAL: 5 MHz QPSK
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.82 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23035 (701.5)	1,403.00	-48.97	7.60	-58.06	1.70	H	-52.16	71.98
	2,104.50	-56.09	9.74	-60.67	2.10	H	-53.03	72.85
	2,806.00	-57.76	10.92	-60.12	2.46	H	-51.66	71.48
23095 (707.5)	1,415.00	-51.14	7.72	-60.31	1.71	H	-54.30	74.12
	2,122.50	-56.83	9.55	-60.97	2.11	H	-53.53	73.35
	2,830.00	-57.07	10.95	-59.15	2.47	H	-50.67	70.49
23155 (713.5)	1,427.00	-48.18	7.75	-57.52	1.70	H	-51.47	71.29
	2,140.50	-56.70	9.43	-60.69	2.11	H	-53.37	73.20
	2,854.00	-56.30	11.02	-58.53	2.47	H	-49.98	69.80

OPERATING FREQUENCY: 711.0 MHz
 MEASURED OUTPUT POWER: 19.43 dBm = 0.088 W
 MODE: LTE B12/17
 MODULATION SIGNAL: 10 MHz QPSK
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 32.43 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23060 (704.0)	1,408.00	-49.67	7.68	-59.13	1.70	H	-53.15	72.58
	2,112.00	-55.92	9.68	-60.66	2.10	H	-53.08	72.51
	2,816.00	-57.50	10.94	-59.70	2.47	H	-51.23	70.66
23095 (707.5)	1,415.00	-51.01	7.72	-60.18	1.71	H	-54.17	73.60
	2,122.50	-57.00	9.55	-61.14	2.11	H	-53.70	73.13
	2,830.00	-57.92	10.95	-60.00	2.47	H	-51.52	70.95
23130 (711.0)	1,422.00	-49.00	7.75	-57.87	1.71	H	-51.83	71.26
	2,133.00	-56.82	9.55	-61.06	2.11	H	-53.62	73.06
	2,844.00	-57.42	10.99	-59.65	2.46	H	-51.12	70.55

8.3 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)		
12	1.4 MHz	707.5	QPSK	6	0	1.0914		
			16-QAM			1.0919		
			64-QAM			1.0942		
	3 MHz		QPSK	15		2.6986		
			16-QAM			2.6889		
			64-QAM			2.6935		
	5 MHz		QPSK	25		4.5182		
			16-QAM			4.4986		
			64-QAM			4.5248		
	10 MHz		QPSK	50		8.9612		
			16-QAM			8.9837		
			64-QAM			8.9729		

Note:

- Plots of the EUT's Occupied Bandwidth are shown Page 41 ~ 52.

8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
12	1.4	699.7	3.6920	27.976	-67.364	-39.388	-13.00
		707.5	3.6691	27.976	-67.359	-39.383	
		715.3	3.6960	27.976	-67.243	-39.267	
	3	700.5	3.7079	27.976	-66.957	-38.981	
		707.5	3.7020	27.976	-67.090	-39.114	
		714.5	3.7229	27.976	-67.204	-39.228	
	5	701.5	3.7034	27.976	-67.161	-39.185	
		707.5	3.7005	27.976	-67.306	-39.330	
		713.5	3.7124	27.976	-67.442	-39.466	
12(17)	10	704.0	3.6925	27.976	-67.529	-39.553	
		707.5	3.7199	27.976	-67.304	-39.328	
		711.0	3.6805	27.976	-67.400	-39.424	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 80 ~ 91.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 53 ~ 79.

8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- MODE: LTE B12
- OPERATING FREQUENCY: 699,700,000 Hz
- CHANNEL: 23017 (1.4 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	699 699 992	0.0	0.000 000	0.000
100%		-30	699 699 983	-8.6	-0.000 001	-0.012
100%		-20	699 699 986	-5.2	-0.000 001	-0.007
100%		-10	699 699 980	-11.7	-0.000 002	-0.017
100%		0	699 699 984	-7.7	-0.000 001	-0.011
100%		+10	699 699 980	-11.2	-0.000 002	-0.016
100%		+30	699 699 980	-11.7	-0.000 002	-0.017
100%		+40	699 699 983	-8.5	-0.000 001	-0.012
100%		+50	699 699 983	-8.8	-0.000 001	-0.013
Batt. Endpoint	3.500	+20	699 699 985	-6.9	-0.000 001	-0.010




- MODE: LTE B12
 OPERATING FREQUENCY: 700,500,000 Hz
 CHANNEL: 23025 (3 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	700 499 994	0.0	0.000 000	0.000
100%		-30	700 499 988	-5.4	-0.000 001	-0.008
100%		-20	700 499 982	-11.7	-0.000 002	-0.017
100%		-10	700 499 981	-12.5	-0.000 002	-0.018
100%		0	700 499 984	-9.6	-0.000 001	-0.014
100%		+10	700 499 986	-7.7	-0.000 001	-0.011
100%		+30	700 499 989	-4.9	-0.000 001	-0.007
100%		+40	700 499 986	-8.1	-0.000 001	-0.012
100%		+50	700 499 987	-6.8	-0.000 001	-0.010
Batt. Endpoint	3.500	+20	700 499 988	-5.3	-0.000 001	-0.008




- MODE: LTE B12/17
 OPERATING FREQUENCY: 701,500,000 Hz
 CHANNEL: 23035 (5 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	701 499 989	0.0	0.000 000	0.000
100%		-30	701 499 980	-8.9	-0.000 001	-0.013
100%		-20	701 499 982	-6.9	-0.000 001	-0.010
100%		-10	701 499 984	-5.3	-0.000 001	-0.008
100%		0	701 499 982	-6.5	-0.000 001	-0.009
100%		+10	701 499 982	-7.1	-0.000 001	-0.010
100%		+30	701 499 986	-3.0	0.000 000	-0.004
100%		+40	701 499 981	-7.5	-0.000 001	-0.011
100%		+50	701 499 982	-6.8	-0.000 001	-0.010
Batt. Endpoint	3.500	+20	701 499 983	-6.0	-0.000 001	-0.009




- MODE: LTE B12/17
- OPERATING FREQUENCY: 704,000,000 Hz
- CHANNEL: 23060 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	703 999 989	0.0	0.000 000	0.000
100%		-30	703 999 977	-11.4	-0.000 002	-0.016
100%		-20	703 999 977	-11.7	-0.000 002	-0.017
100%		-10	703 999 976	-12.7	-0.000 002	-0.018
100%		0	703 999 984	-4.2	-0.000 001	-0.006
100%		+10	703 999 983	-5.9	-0.000 001	-0.008
100%		+30	703 999 982	-7.0	-0.000 001	-0.010
100%		+40	703 999 982	-6.3	-0.000 001	-0.009
100%		+50	703 999 982	-6.6	-0.000 001	-0.009
Batt. Endpoint	3.500	+20	703 999 983	-5.7	-0.000 001	-0.008




- MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (1.4 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 997	0.0	0.000 000	0.000
100%		-30	707 499 995	-2.6	0.000 000	-0.004
100%		-20	707 499 995	-2.8	0.000 000	-0.004
100%		-10	707 500 000	3.1	0.000 000	0.004
100%		0	707 499 994	-3.0	0.000 000	-0.004
100%		+10	707 499 994	-3.4	0.000 000	-0.005
100%		+30	707 499 990	-7.1	-0.000 001	-0.010
100%		+40	707 499 992	-5.6	-0.000 001	-0.008
100%		+50	707 499 993	-4.1	-0.000 001	-0.006
Batt. Endpoint	3.500	+20	707 499 987	-10.0	-0.000 001	-0.014




- MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (3 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 992	0.0	0.000 000	0.000
100%		-30	707 499 985	-7.1	-0.000 001	-0.010
100%		-20	707 499 985	-6.8	-0.000 001	-0.010
100%		-10	707 499 985	-6.4	-0.000 001	-0.009
100%		0	707 499 986	-5.8	-0.000 001	-0.008
100%		+10	707 499 990	-1.9	0.000 000	-0.003
100%		+30	707 499 984	-8.3	-0.000 001	-0.012
100%		+40	707 499 982	-9.4	-0.000 001	-0.013
100%		+50	707 499 989	-2.9	0.000 000	-0.004
Batt. Endpoint	3.500	+20	707 499 994	2.0	0.000 000	0.003




- MODE: LTE B12/17
- OPERATING FREQUENCY: 707,500,000 Hz
- CHANNEL: 23095 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 995	0.0	0.000 000	0.000
100%		-30	707 499 987	-7.9	-0.000 001	-0.011
100%		-20	707 499 989	-6.0	-0.000 001	-0.008
100%		-10	707 499 991	-3.9	-0.000 001	-0.006
100%		0	707 499 991	-4.1	-0.000 001	-0.006
100%		+10	707 499 990	-4.6	-0.000 001	-0.007
100%		+30	707 499 993	-2.4	0.000 000	-0.003
100%		+40	707 499 994	-1.2	0.000 000	-0.002
100%		+50	707 499 983	-12.1	-0.000 002	-0.017
Batt. Endpoint	3.500	+20	707 499 984	-11.3	-0.000 002	-0.016




- MODE: LTE B12/17
- OPERATING FREQUENCY: 707,500,000 Hz
- CHANNEL: 23095 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 993	0.0	0.000 000	0.000
100%		-30	707 499 985	-8.0	-0.000 001	-0.011
100%		-20	707 499 983	-10.1	-0.000 001	-0.014
100%		-10	707 499 986	-7.0	-0.000 001	-0.010
100%		0	707 499 982	-10.3	-0.000 001	-0.015
100%		+10	707 499 983	-9.9	-0.000 001	-0.014
100%		+30	707 499 987	-5.5	-0.000 001	-0.008
100%		+40	707 499 986	-6.3	-0.000 001	-0.009
100%		+50	707 499 985	-7.5	-0.000 001	-0.011
Batt. Endpoint	3.500	+20	707 499 985	-8.1	-0.000 001	-0.011




- MODE: LTE B12
- OPERATING FREQUENCY: 715,300,000 Hz
- CHANNEL: 23173 (1.4 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	715 299 995	0.0	0.000 000	0.000
100%		-30	715 299 988	-7.0	-0.000 001	-0.010
100%		-20	715 299 987	-8.7	-0.000 001	-0.012
100%		-10	715 299 983	-12.6	-0.000 002	-0.018
100%		0	715 299 988	-7.4	-0.000 001	-0.010
100%		+10	715 299 984	-11.2	-0.000 002	-0.016
100%		+30	715 299 988	-7.5	-0.000 001	-0.010
100%		+40	715 299 989	-6.4	-0.000 001	-0.009
100%		+50	715 299 991	-4.4	-0.000 001	-0.006
Batt. Endpoint	3.500	+20	715 299 987	-8.6	-0.000 001	-0.012




- MODE: LTE B12
- OPERATING FREQUENCY: 714,500,000 Hz
- CHANNEL: 23165 (3 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	714 499 988	0.0	0.000 000	0.000
100%		-30	714 499 982	-6.1	-0.000 001	-0.009
100%		-20	714 499 980	-8.3	-0.000 001	-0.012
100%		-10	714 499 982	-6.2	-0.000 001	-0.009
100%		0	714 499 979	-9.3	-0.000 001	-0.013
100%		+10	714 499 979	-9.4	-0.000 001	-0.013
100%		+30	714 499 982	-5.8	-0.000 001	-0.008
100%		+40	714 499 974	-14.1	-0.000 002	-0.020
100%		+50	714 499 969	-19.2	-0.000 003	-0.027
Batt. Endpoint	3.500	+20	714 499 978	-9.9	-0.000 001	-0.014




- MODE: LTE B12/17
- OPERATING FREQUENCY: 713,500,000 Hz
- CHANNEL: 23155 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	713 499 994	0.0	0.000 000	0.000
100%		-30	713 499 983	-10.4	-0.000 001	-0.015
100%		-20	713 499 986	-8.0	-0.000 001	-0.011
100%		-10	713 499 988	-6.0	-0.000 001	-0.008
100%		0	713 499 984	-9.4	-0.000 001	-0.013
100%		+10	713 499 980	-13.4	-0.000 002	-0.019
100%		+30	713 499 989	-4.8	-0.000 001	-0.007
100%		+40	713 499 986	-7.5	-0.000 001	-0.011
100%		+50	713 499 985	-8.3	-0.000 001	-0.012
Batt. Endpoint	3.500	+20	713 499 985	-9.1	-0.000 001	-0.013




- MODE: LTE B12/17
 OPERATING FREQUENCY: 711,000,000 Hz
 CHANNEL: 23130 (10 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	710 999 996	0.0	0.000 000	0.000
100%		-30	710 999 985	-10.9	-0.000 002	-0.015
100%		-20	710 999 985	-10.9	-0.000 002	-0.015
100%		-10	710 999 984	-12.1	-0.000 002	-0.017
100%		0	710 999 981	-14.8	-0.000 002	-0.021
100%		+10	710 999 991	-5.2	-0.000 001	-0.007
100%		+30	710 999 981	-15.2	-0.000 002	-0.021
100%		+40	710 999 993	-2.7	0.000 000	-0.004
100%		+50	710 999 990	-6.3	-0.000 001	-0.009
Batt. Endpoint	3.500	+20	710 999 990	-5.8	-0.000 001	-0.008




9. TEST PLOTS


BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 QPSK_RB6_0)




BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 16QAM_RB6_0)




BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 64QAM_RB6_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 QPSK_RB15_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 16QAM_RB15_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 64QAM_RB15_0)




BAND 12/17. Occupied Bandwidth Plot (5M BW Ch.23095 QPSK_RB25_0)




BAND 12/17. Occupied Bandwidth Plot (5M BW Ch.23095 16QAM_RB25_0)




BAND 12/17. Occupied Bandwidth Plot (5M BW Ch.23095 64QAM_RB25_0)




BAND 12/17. Occupied Bandwidth Plot (10M BW Ch.23095 QPSK_RB50_0)



BAND 12/17. Occupied Bandwidth Plot (10M BW Ch.23095 16QAM_RB50_0)



BAND 12/17. Occupied Bandwidth Plot (10M BW Ch.23095 64QAM_RB50_0)



BAND 12. Lower Band Edge Plot (1.4M BW Ch.23017 QPSK_RB1_Offset 0)




BAND 12. Lower Band Edge Plot (1.4M BW Ch.23017 QPSK_RB6_Offset 0)



BAND 12. Lower Extended Band Edge Plot (1.4M BW Ch.23017 QPSK_RB6_0)



BAND 12. Lower Band Edge Plot (3M BW Ch.23025 QPSK_RB1_Offset 0)



BAND 12. Lower Band Edge Plot (3M BW Ch.23025 QPSK_RB15_Offset 0)



BAND 12. Lower Extended Band Edge Plot (3M BW Ch.23025 QPSK_RB15_0)



BAND 12/17. Lower Band Edge Plot (5M BW Ch.23035 QPSK_RB1_Offset 0)




BAND 12/17. Lower Band Edge Plot (5M BW Ch.23035 QPSK_RB25_Offset 0)



BAND 12/17. Lower Extended Band Edge Plot (5M BW Ch.23035 QPSK_RB25_0)



BAND 12/17. Lower Band Edge Plot (10M BW Ch.23060 QPSK_RB1_Offset 0)



BAND 12/17. Lower Band Edge Plot (10M BW Ch.23060 QPSK_RB50_Offset 0)



BAND 12/17. Lower Extended Band Edge Plot (10M BW Ch.23060 QPSK_RB50_0)



BAND 12. Upper Band Edge Plot (1.4M BW Ch.23173 QPSK_RB1_Offset 5)_1



BAND 12. Upper Band Edge Plot (1.4M BW Ch.23173 QPSK_RB1_Offset 5)_2



BAND 12. Upper Band Edge Plot (1.4M BW Ch.23173 QPSK_RB6_Offset 0)



BAND 12. Upper Extended Band Edge Plot (1.4M BW Ch.23173 QPSK_RB6_0)



BAND 12. Upper Band Edge Plot (3M BW Ch.23165 QPSK_RB1_Offset 14)-1



BAND 12. Upper Band Edge Plot (3M BW Ch.23165 QPSK_RB1_Offset 14)-2




BAND 12. Upper Band Edge Plot (3M BW Ch.23165 QPSK_RB15_Offset 0)



BAND 12. Upper Extended Band Edge Plot (3M BW Ch.23165 QPSK_RB15_0)



BAND 12/17. Upper Band Edge Plot (5M BW Ch.23155 QPSK_RB1_Offset 24)-1



BAND 12/17. Upper Band Edge Plot (5M BW Ch.23155 QPSK_RB1_Offset 24)-2



BAND 12/17. Upper Band Edge Plot (5M BW Ch.23155 QPSK_RB25_Offset 0)



BAND 12/17. Upper Extended Band Edge Plot (5M BW Ch.23155 QPSK_RB25_0)



BAND 12/17. Upper Band Edge Plot (10M BW Ch.23130 QPSK_RB1_Offset 49)




BAND 12/17. Upper Band Edge Plot (10M BW Ch.23130 QPSK_RB50_Offset 0)




BAND 12/17. Upper Extended Band Edge Plot (10M BW Ch.23130 QPSK_RB50_0)




BAND 12. Conducted Spurious Plot _ (23017ch_1.4MHz_QPSK_RB 1_0)




BAND 12. Conducted Spurious Plot _ (23095ch_1.4MHz_QPSK_RB 1_0)




BAND 12. Conducted Spurious Plot _ (23173ch_1.4MHz_QPSK_RB 1_0)




BAND 12. Conducted Spurious Plot _ (23025ch_3MHz_QPSK_RB 1_0)




BAND 12. Conducted Spurious Plot _ (23095ch_3MHz_QPSK_RB 1_0)




BAND 12. Conducted Spurious Plot _ (23165ch_3MHz_QPSK_RB 1_0)




BAND 12/17. Conducted Spurious Plot _ (23035ch_5MHz_QPSK_RB 1_0)




BAND 12/17. Conducted Spurious Plot _ (23095ch_5MHz_QPSK_RB 1_0)




BAND 12/17. Conducted Spurious Plot _ (23155ch_5MHz_QPSK_RB 1_0)




BAND 12/17. Conducted Spurious Plot _ (23060ch_10MHz_QPSK_RB 1_0)



BAND 12/17. Conducted Spurious Plot _ (23095ch_10MHz_QPSK_RB 1_0)



BAND 12/17. Conducted Spurious Plot _ (23130ch_10MHz_QPSK_RB 1_0)



10. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2002-FC017-P