

# FCC LTE REPORT

## Certification

**Applicant Name:**  
 SAMSUNG Electronics Co., Ltd.

**Date of Issue:**  
 December 11, 2020

**Address:**  
 129, Samsung-ro, Yeongtong-gu,  
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Location:**  
 HCT CO., LTD.,  
 74, Seoicheon-ro 578beon-gil, Majang-myeon,  
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA  
**Report No.:** HCT-RF-2012-FC023

**FCC ID:** A3LSM A326B

**APPLICANT:** SAMSUNG Electronics Co., Ltd.

Model(s): SM-A326B/DS  
 Additional Model(s): SM-A326B  
 EUT Type: Mobile Phone  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 FCC Rule Part(s): §22, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band5/26 (1.4)	824.7 – 848.3	1M09G7D	QPSK	0.070	18.48
		1M09W7D	16QAM	0.061	17.86
		1M10W7D	64QAM	0.047	16.70
LTE – Band5/26 (3)	825.5 – 847.5	2M70G7D	QPSK	0.071	18.51
		2M70W7D	16QAM	0.061	17.86
		2M70W7D	64QAM	0.047	16.70
LTE – Band5/26 (5)	826.5 – 846.5	4M51G7D	QPSK	0.072	18.59
		4M50W7D	16QAM	0.062	17.93
		4M50W7D	64QAM	0.048	16.78
LTE – Band5/26 (10)	829.0 – 844.0	9M00G7D	QPSK	0.074	18.70
		9M01W7D	16QAM	0.064	18.03
		8M99W7D	64QAM	0.049	16.87
LTE – Band26 (15)	831.5 – 841.5	13M4G7D	QPSK	0.073	18.65
		13M5W7D	16QAM	0.063	17.98
		13M5W7D	64QAM	0.049	16.86

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.  
 HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

## REVIEWED BY



---

**Report prepared by : Jae Mun Do**  
**Engineer of Telecommunication Testing Center**

---

**Report approved by : Kwon Jeong**  
**Manager of Telecommunication Testing Center**

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked \*.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

\* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

# Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2012-FC023	December 11, 2020	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Table of Contents

REVIEWED BY .....	2
1. GENERAL INFORMATION .....	5
2. INTRODUCTION.....	6
2.1. DESCRIPTION OF EUT .....	6
2.2. MEASURING INSTRUMENT CALIBRATION.....	6
2.3. TEST FACILITY.....	6
3. DESCRIPTION OF TESTS.....	7
3.1 TEST PROCEDURE.....	7
3.2 RADIATED POWER .....	8
3.3 RADIATED SPURIOUS EMISSIONS.....	9
3.4 OCCUPIED BANDWIDTH.....	10
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL .....	11
3.6 BAND EDGE .....	12
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE.....	13
3.8 WORST CASE(RADIATED TEST).....	14
3.9 WORST CASE(CONDUCTED TEST).....	15
4. LIST OF TEST EQUIPMENT.....	16
5. MEASUREMENT UNCERTAINTY .....	17
6. SUMMARY OF TEST RESULTS .....	18
7. SAMPLE CALCULATION .....	19
8. TEST DATA .....	21
8.1 EFFECTIVE RADIATED POWER .....	21
8.2 RADIATED SPURIOUS EMISSIONS.....	24
8.3 OCCUPIED BANDWIDTH.....	25
8.4 CONDUCTED SPURIOUS EMISSIONS .....	26
8.5 BAND EDGE .....	26
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE.....	27
9. TEST PLOTS .....	32
10. ANNEX A_ TEST SETUP PHOTO .....	93

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

<b>Applicant Name:</b>	SAMSUNG Electronics Co., Ltd.
<b>Address:</b>	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
<b>FCC ID:</b>	A3LSMA326B
<b>Application Type:</b>	Certification
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)
<b>FCC Rule Part(s):</b>	§22, §2
<b>EUT Type:</b>	Mobile Phone
<b>Model(s):</b>	SM-A326B/DS
<b>Additional Model(s):</b>	SM-A326B
<b>Tx Frequency:</b>	824.7 MHz – 848.3 MHz (LTE – Band5 / 26 (1.4 MHz)) 825.5 MHz – 847.5 MHz (LTE – Band5 / 26 (3 MHz)) 826.5 MHz – 846.5 MHz (LTE – Band5 / 26 (5 MHz)) 829.0 MHz – 844.0 MHz (LTE – Band5 / 26 (10 MHz)) 831.5 MHz – 841.5 MHz (LTE – Band 26 (15 MHz))
<b>Date(s) of Tests:</b>	November 24, 2020 ~ December 04, 2020

## 2. INTRODUCTION

### 2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), Bluetooth, BT LE, NFC.

### 2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### 2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

### 3. DESCRIPTION OF TESTS

#### 3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

### 3.2 RADIATED POWER

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

#### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

#### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dB})$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.  
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

#### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = \text{Pg}_{(\text{dBm})} - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dBi})$$

Where: Pg is the generator output power into the substitution antenna.

If the fundamental frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

### 3.4 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



#### Test setup

##### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

##### Test Settings

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep  $\geq$  2 x Span / RBW

### 3.6 BAND EDGE



#### Test setup

#### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

#### Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB.

In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

### 3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



#### Test setup

##### Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

##### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

**3.8 WORST CASE(RADIATED TEST)**

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- LTE Band 26(1.4M/3M/5M/10M) overlaps the entire frequency range of LTE Band 5(1.4M/3M/5M/10M) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 5 as well as Band 26.

- SM-A326B/DS & additional models were tested and the worst case results are reported.

(Worst case : SM-A326B/DS)

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
<b>Effective Radiated Power</b>	QPSK, 16QAM, 64QAM	1	0	X
<b>Radiated Spurious and Harmonic Emissions</b>	QPSK	1	0	Z

### 3.9 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- LTE Band 26(1.4M/3M/5M/10M) overlaps the entire frequency range of LTE Band 5(1.4M/3M/5M/10M) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 5 as well as Band 26.

- SM-A326B/DS & additional models were tested and the worst case results are reported.

(Worst case : SM-A326B/DS)

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	1.4, 3, 5, 10, 15	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		1.4, 3, 5, 10, 15	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15	Low, Mid, High	1	0

#### 4. LIST OF TEST EQUIPMENT

Manufacturer	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	04/27/2020	Annual	04/27/2021
Hewlett Packard	E3632A/DC Power Supply	MY40004427	09/16/2020	Annual	09/16/2021
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93008124	03/18/2020	Annual	03/18/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	02/11/2020	Biennial	02/11/2022
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	04/27/2020	Annual	04/27/2021
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2020	Annual	06/04/2021
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2020	Annual	10/14/2021
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/26/2020	Annual	08/26/2021
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/26/2019	Biennial	04/26/2021
Schwarzbeck	VULB9160/ Bilog Antenna	3150	03/12/2019	Biennial	03/12/2021
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6262116770	07/22/2020	Annual	07/22/2021
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/22/2020	Annual	01/22/2021
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/13/2020	Annual	07/13/2021
KEYSIGHT	N9030B / Signal Analyzer(5Hz~40.0GHz)	MY55480167	06/04/2020	Annual	06/04/2021
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).
3. Model : FSV40/Spectrum
  - Use date of equipment: September 23, 2020 ~ October 12, 2020, October 14, 2020 ~

## 5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

## 6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §22.917(a)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§2.1055, §22.355	< 2.5 ppm	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§22.913(a)(5)	< 7 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §22.917(a)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

## 7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

## 8. TEST DATA

### 8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP			
									W	W	dBm	
824.7	LTE B5/ 26 (1.4 MHz)	QPSK	-33.87	29.63	-10.24	1.40	H	< 7.00	0.063	17.99		
		16-QAM	-34.49	29.01	-10.24	1.40	H		0.055	17.37		
		64-QAM	-35.61	27.89	-10.24	1.40	H		0.042	16.25		
836.5		QPSK	-33.85	30.08	-10.19	1.41	H		0.070	18.48		
		16-QAM	-34.47	29.46	-10.19	1.41	H		0.061	17.86		
		64-QAM	-35.63	28.30	-10.19	1.41	H		0.047	16.70		
848.3		QPSK	-34.88	29.26	-10.14	1.42	H		0.059	17.70		
		16-QAM	-35.54	28.60	-10.14	1.42	H		0.051	17.04		
		64-QAM	-36.69	27.45	-10.14	1.42	H		0.039	15.89		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP			
									W	W	dBm	
825.5	LTE B5/ 26 (3 MHz)	QPSK	-33.85	29.66	-10.24	1.40	H	< 7.00	0.063	18.02		
		16-QAM	-34.49	29.02	-10.24	1.40	H		0.055	17.38		
		64-QAM	-35.62	27.89	-10.24	1.40	H		0.042	16.25		
836.5		QPSK	-33.82	30.11	-10.19	1.41	H		0.071	18.51		
		16-QAM	-34.47	29.46	-10.19	1.41	H		0.061	17.86		
		64-QAM	-35.63	28.30	-10.19	1.41	H		0.047	16.70		
847.5		QPSK	-34.78	29.32	-10.15	1.42	H		0.060	17.75		
		16-QAM	-35.41	28.69	-10.15	1.42	H		0.052	17.12		
		64-QAM	-36.56	27.54	-10.15	1.42	H		0.040	15.97		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP		
								W	W	dBm	
826.5	LTE B5/ 26 (5 MHz)	QPSK	-33.82	29.76	-10.24	1.40	H	< 7.00	0.065	18.12	
		16-QAM	-34.47	29.11	-10.24	1.40	H		0.056	17.47	
		64-QAM	-35.59	27.99	-10.24	1.40	H		0.043	16.35	
836.5		QPSK	-33.74	30.19	-10.19	1.41	H		0.072	18.59	
		16-QAM	-34.40	29.53	-10.19	1.41	H		0.062	17.93	
		64-QAM	-35.55	28.38	-10.19	1.41	H		0.048	16.78	
846.5		QPSK	-34.53	29.47	-10.15	1.42	H		0.062	17.90	
		16-QAM	-35.21	28.79	-10.15	1.42	H		0.053	17.22	
		64-QAM	-36.35	27.65	-10.15	1.42	H		0.041	16.08	

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP		
								W	W	dBm	
829.0	LTE B5/ 26 (10 MHz)	QPSK	-33.83	29.88	-10.22	1.40	H	< 7.00	0.067	18.26	
		16-QAM	-34.47	29.24	-10.22	1.40	H		0.058	17.62	
		64-QAM	-35.63	28.08	-10.22	1.40	H		0.044	16.46	
836.5		QPSK	-33.63	30.30	-10.19	1.41	H		0.074	18.70	
		16-QAM	-34.30	29.63	-10.19	1.41	H		0.064	18.03	
		64-QAM	-35.46	28.47	-10.19	1.41	H		0.049	16.87	
844.0		QPSK	-34.17	29.69	-10.16	1.41	H		0.065	18.12	
		16-QAM	-34.80	29.06	-10.16	1.41	H		0.056	17.49	
		64-QAM	-35.98	27.88	-10.16	1.41	H		0.043	16.31	

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP		
									W	W	dBm
831.5	LTE B26 (15 MHz)	QPSK	-33.89	29.94	-10.21	1.40	H	< 7.00	0.068	18.33	
		16-QAM	-34.55	29.28	-10.21	1.40	H		0.058	17.67	
		64-QAM	-35.67	28.16	-10.21	1.40	H		0.045	16.55	
836.5		QPSK	-33.68	30.25	-10.19	1.41	H		0.073	18.65	
		16-QAM	-34.35	29.58	-10.19	1.41	H		0.063	17.98	
		64-QAM	-35.47	28.46	-10.19	1.41	H		0.049	16.86	
841.5		QPSK	-33.89	30.01	-10.17	1.41	H		0.070	18.43	
		16-QAM	-34.54	29.36	-10.17	1.41	H		0.060	17.78	
		64-QAM	-35.68	28.22	-10.17	1.41	H		0.046	16.64	

## 8.2 RADIATED SPURIOUS EMISSIONS

- MODE: LTE B5/ 26  
 MODULATION SIGNAL: 10 MHz QPSK  
 DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
26840 (829.0)	1658.00	-51.76	9.58	-61.76	2.01	V	-54.19	-13.00
	2487.00	-56.28	10.65	-60.32	2.49	V	-52.16	-13.00
	3316.00	-58.21	12.38	-59.19	2.91	H	-49.72	-13.00
26915 (836.5)	1673.00	-52.73	9.65	-62.50	2.01	V	-54.86	-13.00
	2509.50	-55.88	10.75	-59.60	2.50	V	-51.35	-13.00
	3346.00	-58.86	12.48	-59.85	2.92	V	-50.29	-13.00
26990 (844.0)	1688.00	-53.14	9.73	-62.82	2.03	V	-55.12	-13.00
	2532.00	-55.40	10.80	-58.62	2.50	H	-50.32	-13.00
	3376.00	-58.76	12.60	-59.89	2.93	V	-50.22	-13.00

### 8.3 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )		
5/ 26	1.4 MHz	836.5	QPSK	6	0	1.0915		
			16-QAM			1.0920		
			64-QAM			1.0958		
	3 MHz		QPSK	15		2.7021		
			16-QAM			2.6957		
			64-QAM			2.7028		
	5 MHz		QPSK	25		4.5131		
			16-QAM			4.4950		
			64-QAM			4.5005		
	10 MHz		QPSK	50		9.0004		
			16-QAM			9.0064		
			64-QAM			8.9922		
	15 MHz		QPSK	75		13.438		
			16-QAM			13.478		
			64-QAM			13.477		

Note:

- Plots of the EUT's Occupied Bandwidth are shown Page 33 ~ 47.

#### 8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
5/ 26	1.4	824.7	3.6925	27.976	-67.343	-39.367	-13.00
		836.5	3.6965	27.976	-67.061	-39.085	
		848.3	3.6830	27.976	-67.292	-39.316	
	3	825.5	3.7039	27.976	-66.964	-38.988	
		836.5	3.6900	27.976	-67.405	-39.429	
		847.5	3.7109	27.976	-66.891	-38.915	
	5	826.5	3.6930	27.976	-67.372	-39.396	
		836.5	3.6975	27.976	-67.293	-39.317	
		846.5	3.7034	27.976	-66.759	-38.783	
	10	829.0	3.6825	27.976	-67.425	-39.449	
		836.5	3.6780	27.976	-67.224	-39.248	
		844.0	3.7084	27.976	-67.028	-39.052	
	26	831.5	3.7044	27.976	-67.390	-39.414	
		836.5	3.6955	27.976	-67.113	-39.137	
		841.5	3.7154	27.976	-67.323	-39.347	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 78 ~ 92.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


#### 8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 48 ~ 77.

## 8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- MODE: LTE B5/ 26
- OPERATING FREQUENCY: 836,500,000 Hz
- CHANNEL: 26915 (1.4 MHz)
- REFERENCE VOLTAGE: 3.86 VDC
- DEVIATION LIMIT:  $\pm 0.000\ 25\%$  or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	836 500 004	0.0	0.000 000	0.000
100%		-30	836 500 001	-2.4	0.000 000	-0.003
100%		-20	836 500 009	5.2	0.000 001	0.006
100%		-10	836 500 006	2.1	0.000 000	0.003
100%		0	836 500 008	4.4	0.000 001	0.005
100%		+10	836 500 011	7.0	0.000 001	0.008
100%		+30	836 500 007	3.2	0.000 000	0.004
100%		+40	836 500 013	9.5	0.000 001	0.011
100%		+50	836 500 002	-1.8	0.000 000	-0.002
Batt. Endpoint	3.400	+20	836 500 007	3.6	0.000 000	0.004




- MODE: LTE B5/ 26
- OPERATING FREQUENCY: 836,500,000 Hz
- CHANNEL: 26915 (3 MHz)
- REFERENCE VOLTAGE: 3.86 VDC
- DEVIATION LIMIT:  $\pm 0.000\ 25\%$  or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	836 500 004	0.0	0.000 000	0.000
100%		-30	836 500 014	9.9	0.000 001	0.012
100%		-20	836 500 006	1.4	0.000 000	0.002
100%		-10	836 500 009	4.9	0.000 001	0.006
100%		0	836 500 009	4.5	0.000 001	0.005
100%		+10	836 500 010	5.8	0.000 001	0.007
100%		+30	836 500 010	5.3	0.000 001	0.006
100%		+40	836 500 002	-2.1	0.000 000	-0.003
100%		+50	836 500 007	2.6	0.000 000	0.003
Batt. Endpoint	3.400	+20	836 500 015	10.8	0.000 001	0.013




- MODE: LTE B5/ 26  
 OPERATING FREQUENCY: 836,500,000 Hz  
 CHANNEL: 26915 (5 MHz)  
 REFERENCE VOLTAGE: 3.86 VDC  
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	836 500 002	0.0	0.000 000	0.000
100%		-30	836 500 013	10.9	0.000 001	0.013
100%		-20	836 500 007	4.5	0.000 001	0.005
100%		-10	836 500 005	2.4	0.000 000	0.003
100%		0	836 500 010	7.6	0.000 001	0.009
100%		+10	836 500 006	3.8	0.000 000	0.005
100%		+30	836 500 009	7.1	0.000 001	0.008
100%		+40	836 499 998	-4.6	-0.000 001	-0.005
100%		+50	836 500 005	2.8	0.000 000	0.003
Batt. Endpoint	3.400	+20	836 500 000	-2.0	0.000 000	-0.002




- MODE: LTE B5/ 26  
 OPERATING FREQUENCY: 836,500,000 Hz  
 CHANNEL: 26915 (10 MHz)  
 REFERENCE VOLTAGE: 3.86 VDC  
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	836 500 003	0.0	0.000 000	0.000
100%		-30	836 500 010	6.7	0.000 001	0.008
100%		-20	836 500 006	3.3	0.000 000	0.004
100%		-10	836 500 007	3.9	0.000 000	0.005
100%		0	836 500 010	6.7	0.000 001	0.008
100%		+10	836 500 006	2.9	0.000 000	0.003
100%		+30	836 500 010	7.4	0.000 001	0.009
100%		+40	836 500 006	3.2	0.000 000	0.004
100%		+50	836 500 010	6.7	0.000 001	0.008
Batt. Endpoint		3.400	+20	836 500 005	2.2	0.000 000



- MODE: LTE B26  
 OPERATING FREQUENCY: 836,500,000 Hz  
 CHANNEL: 26915 (15 MHz)  
 REFERENCE VOLTAGE: 3.86 VDC  
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	836 500 006	0.0	0.000 000	0.000
100%		-30	836 500 012	9.1	0.000 001	0.011
100%		-20	836 500 007	4.2	0.000 001	0.005
100%		-10	836 500 007	4.0	0.000 000	0.005
100%		0	836 500 008	5.3	0.000 001	0.006
100%		+10	836 500 011	8.2	0.000 001	0.010
100%		+30	836 500 008	5.2	0.000 001	0.006
100%		+40	836 500 011	8.6	0.000 001	0.010
100%		+50	836 500 015	12.1	0.000 001	0.014
Batt. Endpoint	3.400	+20	836 500 006	3.4	0.000 000	0.004




---

## 9. TEST PLOTS


BAND5/ 26. Occupied Bandwidth Plot (1.4M BW Ch.26915 QPSK\_RB6\_0)




BAND5/ 26. Occupied Bandwidth Plot (1.4M BW Ch.26915 16QAM\_RB6\_0)




BAND5/ 26. Occupied Bandwidth Plot (1.4M BW Ch.26915 64QAM\_RB6\_0)




BAND5/ 26. Occupied Bandwidth Plot (3M BW Ch.26915 QPSK\_RB15\_0)




BAND5/ 26. Occupied Bandwidth Plot (3M BW Ch.26915 16QAM\_RB15\_0)




BAND5/ 26. Occupied Bandwidth Plot (3M BW Ch.26915 64QAM\_RB15\_0)




BAND5/ 26. Occupied Bandwidth Plot (5M BW Ch.26915 QPSK\_RB25\_0)




BAND5/ 26. Occupied Bandwidth Plot (5M BW Ch.26915 16QAM\_RB25\_0)




BAND5/ 26. Occupied Bandwidth Plot (5M BW Ch.26915 64QAM\_RB25\_0)




BAND5/ 26. Occupied Bandwidth Plot (10M BW Ch.26915 QPSK\_RB50\_0)




BAND5/ 26. Occupied Bandwidth Plot (10M BW Ch.26915 16QAM\_RB50\_0)




BAND5/ 26. Occupied Bandwidth Plot (10M BW Ch.26915 64QAM\_RB50\_0)




BAND 26. Occupied Bandwidth Plot (15M BW Ch.26915 QPSK RB 75\_0)




BAND 26. Occupied Bandwidth Plot (15M BW Ch.26915 16QAM RB 75\_0)




BAND 26. Occupied Bandwidth Plot (15M BW Ch.26915 64QAM RB 75\_0)




BAND5/ 26. Lower Band Edge Plot (1.4M BW Ch.26797 QPSK\_RB1\_Offset 0)




BAND5/ 26. Lower Band Edge Plot (1.4M BW Ch.26797 QPSK\_RB6\_Offset 0)



BAND5/ 26. Lower Extended Band Edge Plot (1.4M BW Ch.26797 QPSK\_RB6\_0)




BAND5/ 26. Lower Band Edge Plot (3M BW Ch.26805 QPSK\_RB1\_Offset 0)



BAND5/ 26. Lower Band Edge Plot (3M BW Ch.26805 QPSK\_RB15\_Offset 0)




BAND5/ 26. Lower Extended Band Edge Plot (3M BW Ch.26805 QPSK\_RB15\_0)




BAND5/ 26. Lower Band Edge Plot (5M BW Ch.26815 QPSK\_RB1\_Offset 0)




BAND5/ 26. Lower Band Edge Plot (5M BW Ch.26815 QPSK\_RB25\_Offset 0)




BAND5/ 26. Lower Extended Band Edge Plot (5M BW Ch.26815 QPSK\_RB25\_0)




BAND5/ 26. Lower Band Edge Plot (10M BW Ch.26840 QPSK\_RB1\_Offset 0)




BAND5/ 26. Lower Band Edge Plot (10M BW Ch.26840 QPSK\_RB50\_Offset 0)




BAND5/ 26. Lower Extended Band Edge Plot (10M BW Ch.26840 QPSK\_RB50\_0)



BAND 26. Lower Band Edge Plot (15M BW Ch.26865 QPSK\_RB1\_Offset 0)




BAND 26. Lower Band Edge Plot (15M BW Ch.26865 QPSK\_RB75\_Offset 0)



BAND 26. Lower Extended Band Edge Plot (15M BW Ch.26865 QPSK\_RB75\_0)




BAND5/ 26. Upper Band Edge Plot (1.4M BW Ch.27033 QPSK\_RB1\_Offset 5)




BAND5/ 26. Upper Band Edge Plot (1.4M BW Ch.27033 QPSK\_RB6\_Offset 0)



BAND5/ 26. Upper Extended Band Edge Plot (1.4M BW Ch.27033 QPSK\_RB6\_0)




BAND5/ 26. Upper Band Edge Plot (3M BW Ch.27025 QPSK\_RB1\_Offset 14)




BAND5/ 26. Upper Band Edge Plot (3M BW Ch.27025 QPSK\_RB15\_Offset 0)



BAND5/ 26. Upper Extended Band Edge Plot (3M BW Ch.27025 QPSK\_RB15\_0)




BAND5/ 26. Upper Band Edge Plot (5M BW Ch.27015 QPSK\_RB1\_Offset 24)



BAND5/ 26. Upper Band Edge Plot (5M BW Ch.27015 QPSK\_RB25\_Offset 0)



BAND5/ 26. Upper Extended Band Edge Plot (5M BW Ch.27015 QPSK\_RB25\_0)



BAND5/ 26. Upper Band Edge Plot (10M BW Ch.26990 QPSK\_RB1\_Offset 49)




BAND5/ 26. Upper Band Edge Plot (10M BW Ch.26990 QPSK\_RB50\_Offset 0)



BAND5/ 26. Upper Extended Band Edge Plot (10M BW Ch.26990 QPSK\_RB50\_0)




BAND 26. Upper Band Edge Plot (15M BW Ch.26965 QPSK\_RB1\_Offset 74)




BAND 26. Upper Band Edge Plot (15M BW Ch.26965 QPSK\_RB75\_Offset 0)




BAND 26. Upper Extended Band Edge Plot (15M BW Ch.26965 QPSK\_RB75\_0)




BAND5/ 26. Conducted Spurious Plot (26797ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26915ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (27033ch\_1.4MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26805ch\_3MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26915ch\_3MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (27025ch\_3MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26815ch\_5MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26915ch\_5MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (27015ch\_5MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26840ch\_10MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26915ch\_10MHz\_QPSK\_RB 1\_0)




BAND5/ 26. Conducted Spurious Plot (26990ch\_10MHz\_QPSK\_RB 1\_0)




BAND 26. Conducted Spurious (26865ch\_15MHz\_QPSK\_RB 1\_0)



BAND 26. Conducted Spurious (26915ch\_15MHz\_QPSK\_RB 1\_0)



BAND 26. Conducted Spurious (26965ch\_15MHz\_QPSK\_RB 1\_0)



**10. ANNEX A\_ TEST SETUP PHOTO**

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2012-FC023-P