

FCC LTE REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

February 10, 2021

Location:

HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Address:

129, Samsung-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Report No.: HCT-RF-2102-FC020

FCC ID: A3LSMA326U

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-A326U
 Additional Model(s): SM-A326U1/DS, SM-S326DL
 EUT Type: Mobile Phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 38 (5)	2572.5 – 2617.5	4M50G7D	QPSK	0.187	22.72
		4M50W7D	16QAM	0.148	21.72
		4M51W7D	64QAM	0.118	20.74
LTE – Band 38 (10)	2575.0 – 2615.0	8M96G7D	QPSK	0.186	22.69
		8M99W7D	16QAM	0.150	21.76
		8M99W7D	64QAM	0.118	20.72
LTE – Band 38 (15)	2577.5 – 2612.5	13M5G7D	QPSK	0.190	22.80
		13M5W7D	16QAM	0.153	21.85
		13M4W7D	64QAM	0.121	20.84
LTE – Band 38 (20)	2580.0 – 2610.0	18M0G7D	QPSK	0.187	22.73
		17M9W7D	16QAM	0.148	21.70
		17M9W7D	64QAM	0.116	20.66

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

Report No.: HCT-RF-2102-FC020

REVIEWED BY



Report prepared by : Jae Mun Do
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2102-FC020	February 10, 2021	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Table of Contents

REVIEWED BY	2
1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1. DESCRIPTION OF EUT	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
3. DESCRIPTION OF TESTS	7
3.1 TEST PROCEDURE	7
3.2 RADIATED POWER.....	8
3.3 RADIATED SPURIOUS EMISSIONS	9
3.4 PEAK- TO- AVERAGE RATIO.....	10
3.5 OCCUPIED BANDWIDTH.	12
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	13
3.7 CHANNEL EDGE.....	14
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	16
3.9 WORST CASE(RADIATED TEST)	17
3.10 WORST CASE(CONDUCTED TEST)	18
4. LIST OF TEST EQUIPMENT	19
5. MEASUREMENT UNCERTAINTY.....	20
6. SUMMARY OF TEST RESULTS	21
7. SAMPLE CALCULATION	22
8. TEST DATA	24
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	24
8.2 RADIATED SPURIOUS EMISSIONS	26
8.3 PEAK-TO-AVERAGE RATIO.....	30
8.4 OCCUPIED BANDWIDTH	31
8.5 CONDUCTED SPURIOUS EMISSIONS	32
8.6 CHANNEL EDGE.....	33
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	35
9. TEST PLOTS.....	47
10. ANNEX A_ TEST SETUP PHOTO.....	116

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMA326U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§27, §2
EUT Type:	Mobile Phone
Model(s):	SM-A326U
Additional Model(s):	SM-A326U1/DS, SM-S326DL
Tx Frequency:	2572.5 – 2617.5 : 5 MHz 2575.0 – 2615.0 : 10 MHz 2577.5 – 2612.5 : 15 MHz 2580.0 – 2610.0 : 20 MHz
Date(s) of Tests:	January 04, 2021 ~ February 08, 2021
Serial number:	Radiated: 4CE3358DE11C7ECE Conducted: 4C9941A5171C7ECE

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS, CDMA(BC0, 1, 10) and LTE, Sub6. It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), Bluetooth, BT LE, NFC.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $> 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1%.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.


1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:

Set $\geq [10 \times$ (number of points in sweep) \times (transmission period)] for single sweep
(automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25%.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.


Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = Average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

Test Notes

1. Duty Cycle factor already applied on the factor.
 - Duty Cycle factor(dB) = 3.98
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
 - Result(dBm) = Reading + Factor

3.7 CHANNEL EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.


Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1MHz of the channel edge the RBW should be 2% of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

1. The attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge,
2. $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge.
3. $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge.
4. The attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz.
5. $55 + 10 \log (P)$ dB at or below 2490.5 MHz.
6. X is the greater of 6MHz or the actual emission bandwidth
7. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- All modes of operation were investigated and the worst case configuration results are reported.
- Please refer to the table below.
- SM-A326U & additional models were tested and the worst case results are reported.
(Worst case : SM-A326U)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM	1	0	Z
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Z

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
- SM-A326U & additional models were tested and the worst case results are reported.

(Worst case : SM-A326U)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset		
Occupied Bandwidth	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0		
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0		
Channel Edge	QPSK	5	Low	1	0		
			High	1	24		
		10	Low	1	0		
			High	1	49		
		15	Low	1	0		
			High	1	74		
		20	Low	1	0		
			High	1	99		
				5, 10, 15, 20	Low, Mid, High	Full RB	0
		Spurious and Harmonic Emissions at Antenna Terminal	QPSK	5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibrati on Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	04/27/2020	Annual	04/27/2021
Hewlett Packard	E3632A/DC Power Supply	MY40004427	09/16/2020	Annual	09/16/2021
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93008124	03/18/2020	Annual	03/18/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	02/11/2020	Biennial	02/11/2022
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	04/27/2020	Annual	04/27/2021
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2020	Annual	06/04/2021
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2020	Annual	10/14/2021
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/26/2020	Annual	08/26/2021
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/26/2019	Biennial	04/26/2021
Schwarzbeck	VULB9160/ Bilog Antenna	3150	03/12/2019	Biennial	03/12/2021
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6262116770	07/22/2020	Annual	07/22/2021
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/07/2021	Annual	01/07/2022
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/13/2020	Annual	07/13/2021
KEYSIGHT	N9030B / Signal Analyzer(5Hz~40.0GHz)	MY55480167	06/04/2020	Annual	06/04/2021
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(m)(4)	<ul style="list-style-type: none"> ■ < 40 + 10log10 (P[Watts]) at Channel edges ■ < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges ■ < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges ■ < 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz 	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. See SAR Report

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§27.50(h)(2)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(m)(4)	< 55 + 10log10 (P[Watts])	PASS
Receiver Spurious Emissions	N/A	Section 8.8	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$ERP = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
38000	2595.0	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$EIRP = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2572.5	LTE B38/ 5 MHz	QPSK	-23.19	14.01	10.95	2.52	H	< 2.00	0.176	22.44
		16-QAM	-24.15	13.05	10.95	2.52	H		0.141	21.48
		64-QAM	-25.14	12.06	10.95	2.52	H		0.112	20.49
2595.0		QPSK	-23.19	14.27	10.99	2.54	H		0.187	22.72
		16-QAM	-24.19	13.27	10.99	2.54	H		0.148	21.72
		64-QAM	-25.17	12.29	10.99	2.54	H		0.118	20.74
2617.5		QPSK	-23.81	13.62	11.05	2.56	H		0.162	22.11
		16-QAM	-24.80	12.63	11.05	2.56	H		0.129	21.12
		64-QAM	-25.79	11.64	11.05	2.56	H		0.103	20.13

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2575.0	LTE B38/ 10 MHz	QPSK	-23.22	14.15	10.95	2.53	H	< 2.00	0.181	22.57
		16-QAM	-24.16	13.21	10.95	2.53	H		0.145	21.63
		64-QAM	-25.21	12.16	10.95	2.53	H		0.114	20.58
2595.0		QPSK	-23.22	14.24	10.99	2.54	H		0.186	22.69
		16-QAM	-24.15	13.31	10.99	2.54	H		0.150	21.76
		64-QAM	-25.19	12.27	10.99	2.54	H		0.118	20.72
2615.0		QPSK	-23.89	13.50	11.04	2.56	H		0.158	21.98
		16-QAM	-24.85	12.54	11.04	2.56	H		0.127	21.02
		64-QAM	-25.89	11.50	11.04	2.56	H		0.100	19.98

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2577.5	LTE B38/ 15 MHz	QPSK	-23.25	14.28	10.95	2.54	H	< 2.00	0.186	22.69
		16-QAM	-24.21	13.32	10.95	2.54	H		0.149	21.73
		64-QAM	-25.22	12.31	10.95	2.54	H		0.118	20.72
2595.0		QPSK	-23.11	14.35	10.99	2.54	H		0.190	22.80
		16-QAM	-24.06	13.40	10.99	2.54	H		0.153	21.85
		64-QAM	-25.07	12.39	10.99	2.54	H		0.121	20.84
2612.5		QPSK	-23.57	13.78	11.03	2.55	H		0.168	22.26
		16-QAM	-24.52	12.83	11.03	2.55	H		0.135	21.31
		64-QAM	-25.54	11.81	11.03	2.55	H		0.107	20.29

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2580.0	LTE B38/ 20 MHz	QPSK	-23.33	14.20	10.95	2.54	H	< 2.00	0.182	22.61
		16-QAM	-24.28	13.25	10.95	2.54	H		0.147	21.66
		64-QAM	-25.29	12.24	10.95	2.54	H		0.116	20.65
2595.0		QPSK	-23.18	14.28	10.99	2.54	H		0.187	22.73
		16-QAM	-24.21	13.25	10.99	2.54	H		0.148	21.70
		64-QAM	-25.25	12.21	10.99	2.54	H		0.116	20.66
2610.0		QPSK	-23.54	13.81	11.03	2.55	H		0.169	22.29
		16-QAM	-24.50	12.85	11.03	2.55	H		0.136	21.33
		64-QAM	-25.54	11.81	11.03	2.55	H		0.107	20.29

8.2 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.72 dBm = 0.187 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.72 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37775 (2572.5)	5 145.00	-56.21	12.47	-65.09	3.66	H	-56.28	79.00
	7 717.50	-58.64	11.70	-59.16	4.50	V	-51.96	74.68
	10 290.00	-54.39	10.85	-49.84	5.40	V	-44.39	67.11
38000 (2595.0)	5 190.00	-57.42	12.80	-66.17	3.70	V	-57.07	79.79
	7 785.00	-58.60	11.64	-59.70	4.54	H	-52.60	75.31
	10 380.00	-53.60	10.75	-49.05	5.44	V	-43.74	66.45
38225 (2617.5)	5 235.00	-56.08	13.09	-66.62	3.70	H	-57.23	79.95
	7 852.50	-58.22	11.50	-58.22	4.53	V	-51.25	73.96
	10 470.00	-53.76	10.70	-49.47	5.46	V	-44.23	66.95

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.69 dBm = 0.186 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.69 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37800 (2575.0)	5 150.00	-56.57	12.50	-65.55	3.65	H	-56.70	79.41
	7 725.00	-59.00	11.70	-59.52	4.50	H	-52.32	75.03
	10 300.00	-54.63	10.80	-50.07	5.40	H	-44.67	67.38
38000 (2595.0)	5 190.00	-57.40	12.80	-66.15	3.70	H	-57.05	79.77
	7 785.00	-58.93	11.64	-60.03	4.54	H	-52.93	75.64
	10 380.00	-53.61	10.75	-49.06	5.44	H	-43.75	66.46
38200 (2615.0)	5 230.00	-56.22	13.05	-66.73	3.69	H	-57.37	80.08
	7 845.00	-58.52	11.52	-58.39	4.53	H	-51.40	74.12
	10 460.00	-53.48	10.70	-49.14	5.48	H	-43.92	66.63

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.80 dBm = 0.190 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10} (W) =$ 47.80 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37825 (2577.5)	5 155.00	-56.42	12.55	-65.39	3.65	H	-56.49	79.20
	7 732.50	-58.93	11.70	-59.44	4.50	H	-52.24	74.95
	10 310.00	-54.31	10.80	-49.68	5.39	H	-44.27	66.98
38000 (2595.0)	5 190.00	-57.61	12.80	-66.36	3.70	H	-57.26	79.98
	7 785.00	-58.84	11.64	-59.94	4.54	H	-52.84	75.55
	10 380.00	-53.53	10.75	-48.98	5.44	H	-43.67	66.38
38175 (2612.5)	5 225.00	-55.96	13.05	-66.30	3.70	H	-56.95	79.66
	7 837.50	-58.26	11.53	-58.00	4.53	H	-51.00	73.71
	10 450.00	-53.62	10.70	-49.08	5.47	H	-43.85	66.56

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.73 dBm = 0.187 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.73 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
37850 (2580.0)	5 160.00	-56.11	12.60	-65.07	3.65	H	-56.12	78.83
	7 740.00	-58.51	11.70	-58.78	4.50	H	-51.58	74.30
	10 320.00	-54.18	10.80	-49.27	5.38	H	-43.85	66.56
38000 (2595.0)	5 190.00	-57.35	12.80	-66.10	3.70	H	-57.00	79.72
	7 785.00	-58.55	11.64	-59.65	4.54	H	-52.55	75.26
	10 380.00	-53.47	10.75	-48.92	5.44	H	-43.61	66.32
38150 (2610.0)	5 220.00	-55.72	13.05	-65.90	3.70	H	-56.55	79.27
	7 830.00	-58.06	11.55	-57.92	4.53	H	-50.90	73.61
	10 440.00	-53.32	10.70	-48.47	5.45	H	-43.22	65.93

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
38	5 MHz	2595.0	QPSK	25	0	5.21
			16-QAM			5.99
			64-QAM			6.26
	10 MHz		QPSK	50		5.38
			16-QAM			6.04
			64-QAM			6.36
	15 MHz		QPSK	75		5.29
			16-QAM			6.03
			64-QAM			6.40
	20 MHz		QPSK	100		5.29
			16-QAM			6.02
			64-QAM			6.37

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 60 ~ 71.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
38	5 MHz	2595.0	QPSK	25	0	4.5041
			16-QAM			4.5004
			64-QAM			4.5115
	10 MHz		QPSK	50		8.9565
			16-QAM			8.9881
			64-QAM			8.9892
	15 MHz		QPSK	75		13.453
			16-QAM			13.473
			64-QAM			13.427
	20 MHz		QPSK	100		17.972
			16-QAM			17.907
			64-QAM			17.929

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 48 ~ 59.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
38	5	2572.5	26.1514	30.131	-76.648	-46.517	-25.00
		2595.0	26.2195	30.131	-76.756	-46.625	
		2617.5	26.2145	30.131	-76.693	-46.562	
	10	2575.0	26.1733	30.131	-76.574	-46.443	
		2595.0	26.1160	30.131	-76.722	-46.591	
		2615.0	26.2022	30.131	-76.653	-46.522	
	15	2577.5	26.1308	30.131	-76.381	-46.250	
		2595.0	26.1370	30.131	-76.343	-46.212	
		2612.5	26.1729	30.131	-76.769	-46.638	
	20	2580.0	26.1250	30.131	-76.373	-46.242	
		2595.0	26.1403	30.131	-76.535	-46.404	
		2610.0	26.1461	30.131	-76.618	-46.487	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 92 ~ 115.
2. Duty Cycle factor already applied on the factor.
 - Duty Cycle factor(dB) = 3.98
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
 - Result(dBm) = Reading + Factor

Frequency Range (GHz)	Factor [dB]
0.03 – 1	29.250
1 – 5	31.956
5 – 10	32.571
10 – 15	33.096
15 – 20	33.469
Above 20	34.111

8.6 CHANNEL EDGE

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
Band 38	5 MHz	2572.5	QPSK	25	0	-25.21	-26.17	-18.73	-19.27
		2595.0	QPSK	25	0	-26.87	-26.73	-21.93	-22.58
		2617.5	QPSK	25	0	-27.91	-28.01	-24.63	-25.71
	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
	10 MHz	2575.0	QPSK	50	0	-26.77	-26.69	-21.59	-21.68
		2595.0	QPSK	50	0	-27.46	-27.13	-24.06	-24.30
		2615.0	QPSK	50	0	-31.17	-30.53	-25.02	-25.64
	15 MHz	2577.5	QPSK	75	0	-27.31	-27.34	-22.73	-22.90
		2595.0	QPSK	75	0	-28.51	-29.16	-25.86	-25.89
		2612.5	QPSK	75	0	-30.36	-31.21	-28.24	-28.59
	20 MHz	2580.0	QPSK	100	0	-27.32	-27.46	-24.25	-24.75
		2595.0	QPSK	100	0	-29.34	-29.41	-26.26	-26.85
		2610.0	QPSK	100	0	-31.27	-31.47	-28.28	-29.35
	Limit						-10.0		-10.0

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz)		Above (C.E ± X MHz)	
						~			
						(C.E ± X MHz)		Lower	Upper
Band 38	5 MHz	2572.5	QPSK	25	0	-30.68	-30.96	-34.30	-34.79
		2595.0	QPSK	25	0	-31.84	-31.83	-35.27	-35.25
		2617.5	QPSK	25	0	-34.07	-33.51	-36.62	-36.30
	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz)		Above (C.E ± X MHz)	
						~			
						(C.E ± X MHz)		Lower	Upper
	10 MHz	2575.0	QPSK	50	0	-23.69	-23.96	-32.67	-32.70
		2595.0	QPSK	50	0	-26.30	-26.39	-33.83	-33.31
		2615.0	QPSK	50	0	-30.02	-30.20	-37.85	-36.52
	15 MHz	2577.5	QPSK	75	0	-24.57	-24.67	-35.36	-35.22
		2595.0	QPSK	75	0	-27.16	-27.27	-36.76	-35.98
		2612.5	QPSK	75	0	-30.53	-30.83	-39.88	-38.39
	20 MHz	2580.0	QPSK	100	0	-25.64	-25.93	-37.55	-37.18
		2595.0	QPSK	100	0	-27.92	-28.39	-38.97	-37.91
		2610.0	QPSK	100	0	-30.64	-31.30	-40.25	-38.64
Limit						-13.0		-25.0	


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth.
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. Plots of the EUT's Channel Edge are shown Page 72 ~ 91. (1RB & Full RB)

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2572,500,000 Hz
- ▣ BANDWIDTH: 37775 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2572 500 011	0.0	0.000 000	0.000
100%		-30	2572 500 023	11.5	0.000 000	0.004
100%		-20	2572 500 022	10.9	0.000 000	0.004
100%		-10	2572 500 019	7.6	0.000 000	0.003
100%		0	2572 500 027	15.2	0.000 001	0.006
100%		+10	2572 500 023	11.9	0.000 000	0.005
100%		+30	2572 500 017	5.8	0.000 000	0.002
100%		+40	2572 500 020	8.1	0.000 000	0.003
100%		+50	2572 500 015	3.1	0.000 000	0.001
85%		3.400	+20	2572 500 018	6.9	0.000 000




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2575,000,000 Hz
- ▣ BANDWIDTH: 37800 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2575 000 009	0.0	0.000 000	0.000
100%		-30	2575 000 015	5.3	0.000 000	0.002
100%		-20	2575 000 019	9.7	0.000 000	0.004
100%		-10	2575 000 015	5.6	0.000 000	0.002
100%		0	2575 000 018	8.3	0.000 000	0.003
100%		+10	2575 000 018	8.7	0.000 000	0.003
100%		+30	2575 000 016	7.1	0.000 000	0.003
100%		+40	2575 000 020	10.4	0.000 000	0.004
100%		+50	2575 000 018	9.1	0.000 000	0.004
85%	3.400	+20	2575 000 019	9.7	0.000 000	0.004




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2577,500,000 Hz
- ▣ BANDWIDTH: 37825 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2577 500 010	0.0	0.000 000	0.000
100%		-30	2577 500 020	9.6	0.000 000	0.004
100%		-20	2577 500 015	4.8	0.000 000	0.002
100%		-10	2577 500 016	6.0	0.000 000	0.002
100%		0	2577 500 017	6.8	0.000 000	0.003
100%		+10	2577 500 020	10.3	0.000 000	0.004
100%		+30	2577 500 019	8.9	0.000 000	0.003
100%		+40	2577 500 020	9.5	0.000 000	0.004
100%		+50	2577 500 022	12.0	0.000 000	0.005
85%	3.400	+20	2577 500 022	11.5	0.000 000	0.004




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2580,000,000 Hz
- ▣ BANDWIDTH: 37850 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2580 000 009	0.0	0.000 000	0.000
100%		-30	2580 000 014	5.1	0.000 000	0.002
100%		-20	2580 000 017	8.9	0.000 000	0.003
100%		-10	2580 000 016	7.1	0.000 000	0.003
100%		0	2580 000 015	6.7	0.000 000	0.003
100%		+10	2580 000 015	6.5	0.000 000	0.003
100%		+30	2580 000 017	8.4	0.000 000	0.003
100%		+40	2580 000 016	7.7	0.000 000	0.003
100%		+50	2580 000 021	12.4	0.000 000	0.005
85%		3.400	+20	2580 000 017	8.1	0.000 000




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2595 000 011	0.0	0.000 000	0.000
100%		-30	2595 000 021	10.3	0.000 000	0.004
100%		-20	2595 000 027	16.4	0.000 001	0.006
100%		-10	2595 000 018	7.6	0.000 000	0.003
100%		0	2595 000 024	13.2	0.000 001	0.005
100%		+10	2595 000 021	10.3	0.000 000	0.004
100%		+30	2595 000 017	6.7	0.000 000	0.003
100%		+40	2595 000 018	7.9	0.000 000	0.003
100%		+50	2595 000 017	6.2	0.000 000	0.002
85%	3.400	+20	2595 000 020	9.5	0.000 000	0.004




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2595 000 012	0.0	0.000 000	0.000
100%		-30	2595 000 020	8.5	0.000 000	0.003
100%		-20	2595 000 024	12.3	0.000 000	0.005
100%		-10	2595 000 026	14.5	0.000 001	0.006
100%		0	2595 000 021	9.0	0.000 000	0.003
100%		+10	2595 000 020	8.2	0.000 000	0.003
100%		+30	2595 000 019	7.5	0.000 000	0.003
100%		+40	2595 000 022	10.7	0.000 000	0.004
100%		+50	2595 000 020	8.7	0.000 000	0.003
85%	3.400	+20	2595 000 022	10.7	0.000 000	0.004




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2595 000 007	0.0	0.000 000	0.000
100%		-30	2595 000 018	10.6	0.000 000	0.004
100%		-20	2595 000 017	9.9	0.000 000	0.004
100%		-10	2595 000 021	13.2	0.000 001	0.005
100%		0	2595 000 020	12.8	0.000 000	0.005
100%		+10	2595 000 014	6.4	0.000 000	0.002
100%		+30	2595 000 017	9.4	0.000 000	0.004
100%		+40	2595 000 013	5.6	0.000 000	0.002
100%		+50	2595 000 014	6.6	0.000 000	0.003
85%	3.400	+20	2595 000 015	7.2	0.000 000	0.003




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2595 000 013	0.0	0.000 000	0.000
100%		-30	2595 000 026	12.6	0.000 000	0.005
100%		-20	2595 000 024	10.7	0.000 000	0.004
100%		-10	2595 000 019	5.7	0.000 000	0.002
100%		0	2595 000 024	11.0	0.000 000	0.004
100%		+10	2595 000 023	9.7	0.000 000	0.004
100%		+30	2595 000 026	13.1	0.000 001	0.005
100%		+40	2595 000 017	3.8	0.000 000	0.001
100%		+50	2595 000 023	10.1	0.000 000	0.004
85%	3.400	+20	2595 000 024	10.8	0.000 000	0.004




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2617,500,000 Hz
- ▣ BANDWIDTH: 38225 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2617 500 008	0.0	0.000 000	0.000
100%		-30	2617 500 017	8.4	0.000 000	0.003
100%		-20	2617 500 018	9.3	0.000 000	0.004
100%		-10	2617 500 029	20.5	0.000 001	0.008
100%		0	2617 500 019	10.7	0.000 000	0.004
100%		+10	2617 500 012	3.3	0.000 000	0.001
100%		+30	2617 500 015	6.8	0.000 000	0.003
100%		+40	2617 500 017	8.8	0.000 000	0.003
100%		+50	2617 500 016	7.6	0.000 000	0.003
85%	3.400	+20	2617 500 013	4.7	0.000 000	0.002




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2615,000,000 Hz
- ▣ BANDWIDTH: 38200 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2615 000 011	0.0	0.000 000	0.000
100%		-30	2615 000 021	9.7	0.000 000	0.004
100%		-20	2615 000 016	5.0	0.000 000	0.002
100%		-10	2615 000 018	6.7	0.000 000	0.003
100%		0	2615 000 019	7.6	0.000 000	0.003
100%		+10	2615 000 019	8.2	0.000 000	0.003
100%		+30	2615 000 023	11.6	0.000 000	0.004
100%		+40	2615 000 015	4.2	0.000 000	0.002
100%		+50	2615 000 019	8.1	0.000 000	0.003
85%	3.400	+20	2615 000 022	10.5	0.000 000	0.004




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2612,500,000 Hz
- ▣ BANDWIDTH: 38175 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2612 500 008	0.0	0.000 000	0.000
100%		-30	2612 500 015	7.0	0.000 000	0.003
100%		-20	2612 500 015	6.9	0.000 000	0.003
100%		-10	2612 500 004	-4.3	0.000 000	-0.002
100%		0	2612 500 016	7.4	0.000 000	0.003
100%		+10	2612 500 015	6.8	0.000 000	0.003
100%		+30	2612 500 016	7.7	0.000 000	0.003
100%		+40	2612 500 013	4.6	0.000 000	0.002
100%		+50	2612 500 015	6.4	0.000 000	0.002
85%	3.400	+20	2612 500 014	5.8	0.000 000	0.002




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2610,000,000 Hz
- ▣ BANDWIDTH: 38150 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.86 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.860	+20(Ref)	2610 000 009	0.0	0.000 000	0.000
100%		-30	2610 000 019	10.3	0.000 000	0.004
100%		-20	2610 000 019	10.1	0.000 000	0.004
100%		-10	2610 000 018	9.5	0.000 000	0.004
100%		0	2610 000 018	8.9	0.000 000	0.003
100%		+10	2610 000 021	12.3	0.000 000	0.005
100%		+30	2610 000 016	6.8	0.000 000	0.003
100%		+40	2610 000 017	8.1	0.000 000	0.003
100%		+50	2610 000 020	11.4	0.000 000	0.004
85%	3.400	+20	2610 000 018	9.1	0.000 000	0.003




9. TEST PLOTS


BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 QPSK RB 25)




BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 16-QAM RB 25)




BAND 38. Occupied Bandwidth Plot (5 MHz Ch.38000 64-QAM RB 25)




BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 QPSK RB 50)




BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 16-QAM RB 50)




BAND 38. Occupied Bandwidth Plot (10 MHz Ch.38000 64-QAM RB 50)




BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 QPSK RB 75)




BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 16-QAM RB 75)




BAND 38. Occupied Bandwidth Plot (15 MHz Ch.38000 64-QAM RB 75)




BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 QPSK RB 100)




BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 16-QAM RB 100)




BAND 38. Occupied Bandwidth Plot (20 MHz Ch.38000 64-QAM RB 100)




BAND 38. PAR Plot (5M BW_Ch.38000_QPSK_RB25_0)




BAND 38. PAR Plot (5M BW_Ch.38000_16QAM_RB25_0)




BAND 38. PAR Plot (5M BW_Ch.38000_64QAM_RB25_0)




BAND 38. PAR Plot (10M BW_Ch.38000_QPSK_RB50_0)




BAND 38. PAR Plot (10M BW_Ch.38000_16QAM_RB50_0)




BAND 38. PAR Plot (10M BW_Ch.38000_64QAM_RB50_0)




BAND 38. PAR Plot (15M BW_Ch.38000_QPSK_RB75_0)




BAND 38. PAR Plot (15M BW_Ch.38000_16QAM_RB75_0)




BAND 38. PAR Plot (15M BW_Ch.38000_64QAM_RB75_0)




BAND 38. PAR Plot (20M BW_Ch.38000_QPSK_RB100_0)




BAND 38. PAR Plot (20M BW_Ch.38000_16QAM_RB100_0)




BAND 38. PAR Plot (20M BW_Ch.38000_64QAM_RB100_0)




BAND 38. Low Channel Edge Plot (5 MHz Ch.37775 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (5 MHz Ch.37775 QPSK RB 25, Offset 0)




BAND 38. Mid Channel Edge Plot (5 MHz Ch.38000 QPSK RB 25)




BAND 38. High Channel Edge Plot (5 MHz Ch.38225 QPSK RB 1, Offset 0)




BAND 38. High Channel Edge Plot (5 MHz Ch.38225 QPSK_RB25_Offset 0)




BAND 38. Low Channel Edge Plot (10 MHz Ch.37800 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (10 MHz Ch.37800 QPSK RB 25, Offset 0)




BAND 38. Mid Channel Edge Plot (10 MHz Ch.38000 QPSK RB 50)




BAND 38. High Channel Edge Plot (10 MHz Ch.38200 QPSK RB 1, Offset 0)




BAND 38. High Channel Edge Plot (10 MHz Ch.38200 QPSK_RB50_Offset 0)




BAND 38. Low Channel Edge Plot (15 MHz Ch.37825 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (15 MHz Ch.37825 QPSK RB 75, Offset 0)




BAND 38. Mid Channel Edge Plot (15 MHz Ch.38000 QPSK RB 75)




BAND 38. High Channel Edge Plot (15 MHz Ch.38175 QPSK RB 1, Offset 0)




BAND 38. High Channel Edge Plot (15 MHz Ch.38175 QPSK_RB75_Offset 0)




BAND 38. Low Channel Edge Plot (20 MHz Ch.37850 QPSK RB 1, Offset 0)




BAND 38. Low Channel Edge Plot (20 MHz Ch.37850 QPSK RB 25, Offset 0)




BAND 38. Mid Channel Edge Plot (20 MHz Ch.38000 QPSK RB 100)




BAND 38. High Channel Edge Plot (20 MHz Ch.38150 QPSK RB 1, Offset 0)



BAND 38. High Channel Edge Plot (20 MHz Ch.38150 QPSK_RB100_Offset 0)




BAND 38. Conducted Spurious Plot 1 (5 MHz Ch.37775 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (5 MHz Ch. 37775 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (5 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (5 MHz Ch. 38000 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (5 MHz Ch.38225 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (5 MHz Ch. 38225 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (10 MHz Ch.37800 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (10 MHz Ch. 37800 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (10 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (10 MHz Ch. 38000 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (10 MHz Ch. 38200 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (10 MHz Ch. 38200 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (15 MHz Ch.37825 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (15 MHz Ch. 37825 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (15 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (15 MHz Ch. 38000 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (15 MHz Ch.38175 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (15 MHz Ch. 38175 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (20 MHz Ch.37850 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (20 MHz Ch. 37850 QPSK RB 1, Offset 0)




BAND 38. Conducted Spurious Plot 1 (20 MHz Ch.38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (20 MHz Ch. 38000 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 1 (20 MHz Ch.38150 QPSK RB 1, Offset 0)



BAND 38. Conducted Spurious Plot 2 (20 MHz Ch. 38150 QPSK RB 1, Offset 0)



10. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2102-FC020-P