





# TEST REPORT

<b>Eurofins KCTL Co.,Ltd.</b> 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a>	Report No.: KR23-SRF0027-A Page (1) of (24)	   <b>KCTL</b>
<b>1. Client</b>		
<ul style="list-style-type: none"> <li>◦ Name : Samsung Electronics Co., Ltd.</li> <li>◦ Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea</li> <li>◦ Date of Receipt : 2022-10-17</li> </ul>		
<b>2. Use of Report</b> : Certification		
<b>3. Name of Product / Model</b> : Mobile phone / SM-A346B/DSN		
<b>4. Manufacturer / Country of Origin</b> : Samsung Electronics Co., Ltd. / Vietnam		
<b>5. FCC ID</b> : A3LSMA346B		
<b>6. Date of Test</b> : 2022-11-09 to 2023-01-04		
<b>7. Location of Test</b> : <input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing (Address:65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)		
<b>8. Test method used</b> : FCC Part 15 Subpart C, 15.247		
<b>9. Test Result</b> : Refer to the test result in the test report		
Affirmation	Tested by  Name : Sunghyun Yoon (Signature)	Technical Manager  Name : Seungyong Kim (Signature)
2023-01-20		
<b>Eurofins KCTL Co.,Ltd.</b>		
As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.		

<p><b>Eurofins KCTL Co.,Ltd.</b>  65, Sinwon-ro, Yeongtong-gu,  Suwon-si, Gyeonggi-do, 16677, Korea  TEL: 82-31-285-0894 FAX: 82-505-299-8311  <a href="http://www.kctl.co.kr">www.kctl.co.kr</a></p>	<p>Report No.:  KR23-SRF0027-A  Page (2) of (24)</p>	
---	--	---

## REPORT REVISION HISTORY

Date	Revision	Page No
2023-01-17	Originally issued	-
2023-01-20	Updated to TCB comment	10 ~ 11

*This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

Note. The report No. KR23-SRF0027 is superseded by the report No. KR23-SRF0027-A.

## General remarks for test reports

### Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

### Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

Statement not required by the standard or client used for type testing

# CONTENTS

1.	General information .....	4
2.	Device information .....	4
2.1.	Frequency/channel operations.....	5
2.2.	Duty Cycle Factor .....	6
3.	Antenna requirement .....	8
3.1	Antenna information.....	9
3.2	Directional Gain Calculations.....	9
4.	Introduction .....	10
4.1	Difference .....	10
4.2	Spot check verification data (Band-edge & Spurious emission).....	10
4.3	Reference Detail .....	11
5.	Summary of tests .....	12
6.	Measurement uncertainty .....	13
7.	Test results .....	14
7.1.	Spurious Emission, Band Edge and Restricted bands.....	14
8.	Measurement equipment .....	24

## 1. General information

Client : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
Manufacturer : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
Factory : Samsung Electronics Vietnam Thai Nguyen Co., Ltd  
Address : Yen Binh Industrial Park, Dong Tien Ward, Pho Yen Town, Thai Nguyen Province, Vietnam  
Laboratory : Eurofins KCTL Co.,Ltd.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
CAB Identifier: KR0040  
ISED Number: 8035A  
KOLAS No.: KT231

## 2. Device information

Equipment under test : Mobile phone  
Model : SM-A346B/DSN  
Modulation technique : DSSS, OFDM (802.11b/g/n)  
Number of channels : 13 ch (20 MHz)  
Power source : DC 3.88 V  
Antenna specification : Antenna 1 : Metal+LDS Antenna  
Antenna 2 : LDS Antenna  
Antenna gain : Antenna 1 : -9.43 dBi  
Antenna 2 : -9.03 dBi  
Frequency range : 2 412 MHz ~ 2 472 MHz (802.11b/g/n\_HT20)  
Software version : A346B.001  
Hardware version : REV1.0  
Test device serial No. : Conducted : R3CTA0N813K  
Radiated : R3CTA0N84EX  
Operation temperature : -20 °C ~ 60 °C

## 2.1. Frequency/channel operations

This device contains the following capabilities:

WLAN (11a/b/g/n/ac), Bluetooth (BDR/EDR/BLE), LTE B2/4/5/12/17/26/41/66, GSM 850/1900, WCDMA 850/1700/1900, NFC

Ch.	Frequency (MHz)
01	2 412
.	.
06	2 437
.	.
11	2 462
12	2 467
13	2 472

Table 2.1-1. 802.11b/g/n\_HT20 mode


## 2.2. Duty Cycle Factor

### SISO

Test mode	Period (ms)	On time (ms)	Duty cycle		Duty Cycle Factor (dB)
			(Linear)	(%)	
802.11b	8.457	8.369	0.989 6	98.96	0.05
802.11g	1.486	1.388	0.934 1	93.41	0.30
802.11n_HT20	1.394	1.297	0.930 4	93.04	0.31

### Notes.

- 1) Duty cycle (Linear) = Ton time / Period
- 2) DCF(Duty cycle factor) =  $10\log(1/\text{duty cycle})$
- 3) DCF is not compensated to Average result if duty cycle is more than 98%




**MIMO**

Test mode	Period (ms)	On time (ms)	Duty cycle		Duty Cycle Factor (dB)
			(Linear)	(%)	
802.11b	8.457	8.359	0.988 4	98.84	0.05
802.11g	1.486	1.388	0.934 1	93.41	0.30
802.11n_HT20	1.394	1.296	0.929 7	92.97	0.32

**Notes.**

- 1) Duty cycle (Linear) = Ton time / Period
- 2) DCF(Duty cycle factor) =  $10\log(1/\text{duty cycle})$
- 3) DCF is not compensated to Average result if duty cycle is more than 98%



### **3. Antenna requirement**

#### **Requirement of FCC part section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached FPCB Antenna (Internal antenna) on board.  
Antenna 1 : Metal+LDS Antenna, Antenna 2 : LDS Antenna
- The E.U.T Complies with the requirement of §15.203, §15.247.





### 3.1 Antenna information

Mode	SISO		CDD	MIMO
	ANT 1	ANT 2	ANT 1 + 2	ANT 1 + 2
802.11b	√	√	√	X
802.11g	√	√	√	X
802.11n HT20	√	√	√	√

√ = Support, X = Not support

### 3.2 Directional Gain Calculations

According to clause F), 2), d), (i) of KDB 662911 D01 Multiple Transmitter Output, Directional gain may be calculated by using the formulas as below.

#### Directional Antenna Gain

ANT 1 Gain (dBi)	ANT 2 Gain (dBi)	Combined Gain (dBi)
-9.43	-9.03	-6.22

#### Note.

Unequal antenna gains, with equal transmit powers. For antenna gains given by  $G_1, G_2, \dots, G_N$  dBi  
 Directional gain =  $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$  dB i

#### Sample calculation

Directional gain =  $10 \log[(10^{-9.43/20} + 10^{-9.03/20})^2 / 2] = -6.22$  dB i

## 4. Introduction

This report referenced from the FCC ID: A3LSMA346M

Based on their similarity, the FCC Part 15C (equipment class: DTS) reuse the original model's result and do spot-check, following the FCC KDB 484596 D01 v01.

And the applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID.

### 4.1 Difference

The FCC ID: A3LSMA346B shares the same enclosure and circuit board as FCC ID: A3LSMA346M. The WIFI/BT/BLE/NFC/WCDMA/GSM/LTE antenna and surrounding circuitry and layout are identical between these two units.

As for all bands, they have been verified and the parent model test results under FCC ID: A3LSMA346M shall remain representative of FCC ID: A3LSMA346B.

**Note.** The difference between the parent and variant is that the RF circuit for NR/LTE Bands (13/n5/n66), ULCA Band 4 and EN-DC for Band 2/66 in the parent model A3LSMA346M is removed from the variant model A3LSMA346B.

### 4.2 Spot check verification data (Band-edge & Spurious emission)

Test band	Test item	Test mode	Channel	Measured frequency (MHz)	SM-A346M/DSN (dB $\mu$ V)		SM-A346B/DSN (dB $\mu$ V)		Deviation (dB)	
					Avg.	Peak	Avg.	Peak	Avg.	Peak
2.4G WIFI	Band edge	802.11b (ANT1)	13	2 483.5 ~ 2 500	45.10	54.73	43.99	54.58	-1.11	-0.15
	RSE	802.11b (MIMO)	11	4 923.99	50.31	51.57	34.35	44.92	-15.96	-6.65
	Band edge	802.11g (ANT1)	11	2 483.5 ~ 2 500	51.77	62.08	44.61	53.81	-7.16	-8.27
	RSE	802.11g (MIMO)	1	7 231.48	N/A	49.39	N/A	46.93	N/A	-2.46
	Band edge	802.11n(HT20) (MIMO)	1	2 310 ~ 2 390	51.80	61.99	44.23	55.05	-7.57	-6.94
	RSE	802.11n(HT20) (ANT1)	1	7 236.92	N/A	48.54	N/A	46.26	N/A	-2.28

#### Notes:

- FCC ID: A3LSMA346B has been verified the performance as for WIFI identical with the FCC ID: A3LSMA346M.
- Comparison of two models, the variant model emissions are less than 3 dB higher than the parent model, and all test results are under FCC technical limits.
- The test procedure(s) in this report were performed in accordance as following.
  - ◆ KDB 484596 D01 v01

### 4.3 Reference Detail

Reference application that contains the reused reference data in the individual test reports.

Equipment Class	Reference FCC ID	Application Type	Reference Test report Number	Exhibit Type	Variant Test Report Number	Date Re-used
DTS	A3LSMA346M	Original	KR23-SRF0005 (802.11b/g/n)	Test report	KR23-SRF0027	All
			KR23-SRF0004 (Bluetooth LE)	Test report	KR23-SRF0026	All
DSS	A3LSMA346M	Original	KR23-SRF0003 (Bluetooth)	Test report	KR23-SRF0025	All
NII	A3LSMA346M	Original	KP23-SRF0006 (802.11a/n/ac)	Test report	KR23-SRF0028	All
DXX	A3LSMA346M	Original	KP23-SRF0012 (NFC)	Test report	KR23-SRF0033	All
PCE	A3LSMA346M	Original	KR23-SRF0008 (2G, 3G)	Test report	KR23-SRF0030	All
			KR23-SRF0009 (LTE)	Test report	KR23-SRF0031	Partial <sup>1),2)</sup>
			KR23-SRF0010 (LTE Part90)	Test report	KR23-SRF0032	All

**Notes:**

1. This device does not support the LTE Band 13.
2. This device does not support sub antenna for usage of ULCA (LTE B4) and EN-DC (LTE B2/66).
3. This device does not support the 5G NR Bands of n5/n66.

## 5. Summary of tests

FCC Part section(s)	Parameter	Test Condition	Test results
15.205(a), 15.209(a)	Spurious emission	Radiated	Pass
	Band-edge, restricted band		Pass

### Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **X** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **X** orientation
- The maximum production power and tolerance are not impacted by the change. So only spot-check test was done against the worst case from the original model.
- All the radiated tests have been performed several case. (Stand-alone, with accessories (DLC Cable etc.))
  - Worst case: stand-alone
- The test procedure(s) in this report were performed in accordance as following.
  - ◆ ANSI C63.10-2013
  - ◆ KDB 558074 D01 v05r02
  - ◆ KDB 662911 D01 v02r01
- The worst-case data rate were:
  - 802.11b mode: 1Mbps
  - 802.11g mode: 6Mbps
  - 802.11n\_HT20 mode: MCS8
  - 802.11ac\_VHT20 mode: MCS0

## 6. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ( $\pm$ )	
Radiated spurious emissions	Below 30 MHz:	2.4 dB
	30 MHz ~ 1 000 MHz	2.3 dB
	1 000 MHz ~ 18 000 MHz	5.6 dB
	Above 18 000 MHz	5.7 dB




## 7. Test results


### 7.1. Spurious Emission, Band Edge and Restricted bands

#### Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



### Limit

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ( $\mu\text{V}/\text{m}$ )	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 - 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

**Test procedure**

ANSI C63.10-2013

**Test settings**

**Peak field strength measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW  $\geq$  (3 $\times$ RBW)
4. Detector = peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

**Table. RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

**Average field strength measurements**

**Trace averaging with continuous EUT transmission at full power**

If the EUT can be configured or modified to transmit continuously (D  $\geq$  98%), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):



- ◆ RBW = 1 MHz (unless otherwise specified).
- ◆ VBW  $\geq$  (3 $\times$ RBW).
- ◆ Detector = RMS (power averaging), if [span / (# of points in sweep)]  $\leq$  (RBW / 2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ◆ Averaging type = power (i.e., rms):
  1. As an alternative, the detector and averaging type may be set for linear voltage averaging.
  2. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- ◆ Sweep time = auto.
- ◆ Perform a trace average of at least 100 traces.

**Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction**

If continuous transmission of the EUT (D  $\geq$  98%) cannot be achieved and the duty cycle is constant (duty cycle variations are less than  $\pm 2\%$ ), then the following procedure shall be used:

- 1) The EUT shall be configured to operate at the maximum achievable duty cycle.
- 2) Measure the duty cycle D of the transmitter output signal as described in 11.6.
- 3) RBW = 1 MHz (unless otherwise specified).
- 4) VBW  $\geq$  [3  $\times$  RBW].
- 5) Detector = RMS (power averaging), if [span / (# of points in sweep)]  $\leq$  (RBW / 2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.



<p align="center"><b>Eurofins KCTL Co.,Ltd.</b>  65, Sinwon-ro, Yeongtong-gu,  Suwon-si, Gyeonggi-do, 16677, Korea  TEL: 82-31-285-0894 FAX: 82-505-299-8311  <a href="http://www.kctl.co.kr">www.kctl.co.kr</a></p>	<p align="center">Report No.:  KR23-SRF0027-A  Page (17) of (24)</p>	 
--	--	---

- 6) Averaging type = power (i.e., rms):
  1. As an alternative, the detector and averaging type may be set for linear voltage averaging.
  2. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- 7) Sweep time = auto.
- 8) Perform a trace average of at least 100 traces.
- 9) A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle.
  - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $D \geq 98\%$ ) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Notes:**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40 \log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20 \log(D_m/D_s)$   
Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
2. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or  $F_d$ (dB)
3. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
4. Average test would be performed if the peak result were greater than the average limit.
5. <sup>1)</sup> means restricted band.
6. Below 30 MHz frequency range, In order to search for the worst result, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported. when the emission level was higher than 20 dB of the limit, then the following statement shall be made: "No spurious emissions were detected within 20 dB of the limit."


**Spot-check Test results**

**SISO ANT1 802.11b / Band-edge**

**Highest Channel (2 472 MHz)**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 484.54 <sup>1)</sup>	H	40.09	32.37	-17.88	-	54.58	74.00	19.42
<b>Average Data</b>								
2 484.54 <sup>1)</sup>	H	29.50	32.37	-17.88	-	43.99	54.00	10.01

**Average data**



Blank


**Horizontal/Vertical for Band-edge**




**MIMO 802.11b / Harmonic**

**11 Channel (2 462 MHz)**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
<b>Peak data</b>								
4 841.75 <sup>1)</sup>	V	66.34	33.70	-55.12	-	44.92	74.00	29.08
7 339.78 <sup>1)</sup>	V	62.43	35.17	-51.58	-	46.02	74.00	27.98
<b>Average Data</b>								
4 841.75 <sup>1)</sup>	V	55.77	33.70	-55.12	-	34.35	54.00	19.65



**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**




**SISO ANT1 802.11g / Band-edge**

**11 Channel (2 462 MHz)**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 484.30 <sup>1)</sup>	H	39.32	32.37	-17.88	-	53.81	74.00	20.19
<b>Average Data</b>								
2 484.30 <sup>1)</sup>	H	29.82	32.37	-17.88	0.30	44.61	54.00	9.39

**Average data**



Blank

**Horizontal/Vertical for Band-edge**




**MIMO 802.11g / Harmonic**

**Lowest Channel (2 412 MHz)**

Frequency (MHz)	Pol. (V/H)	Reading (dB( $\mu V$ ))	Ant. Factor (dB)	Amp. + Cable (dB)	DCF (dB)	Result (dB( $\mu V/m$ ))	Limit (dB( $\mu V/m$ ))	Margin (dB)
<b>Peak data</b>								
4 839.44 <sup>1)</sup>	H	66.15	33.70	-55.13	-	44.72	74.00	29.28
7 164.42	V	63.34	35.13	-51.54	-	46.93	74.00	27.07
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								

**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**




**MIMO 802.11n HT20 / Band-edge**

**Lowest Channel (2 412 MHz)**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 389.85 <sup>1)</sup>	H	41.06	32.16	-18.17	-	55.05	74.00	18.95
<b>Average Data</b>								
2 389.85 <sup>1)</sup>	H	29.93	32.16	-18.17	0.31	44.23	54.00	9.77

**Average data**



Blank


**Horizontal/Vertical for Band-edge**



**SISO 802.11n HT20 / Harmonic**

**Lowest Channel (2 412 MHz)**

Frequency (MHz)	Pol. (V/H)	Reading (dB(μV))	Ant. Factor (dB)	Amp. + Cable (dB)	DCF (dB)	Result (dB(μV/m))	Limit (dB(μV/m))	Margin (dB)
<b>Peak data</b>								
4 857.11 <sup>1)</sup>	H	66.23	33.70	-55.11		44.82	74.00	29.18
7 216.08	V	62.67	35.14	-51.55		46.26	74.00	27.74
<b>Average Data</b>								
No spurious emissions were detected within 20 dB of the limit.								



## 8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV40	100989	23.10.14
Power Sensor	R&S	NRP-Z81	1137.9009.02-106225-JM	23.05.02
Horn antenna	ETS.lindgren	3117	155787	23.09.29
Horn antenna	ETS.lindgren	3116	00086635	23.05.04
Attenuator	API Inmet	40AH2W-10	12	23.05.03
AMPLIFIER	B&Z Technologies	BZRT-00504000-481055-382525	26299-27735	23.09.19
AMPLIFIER	B&Z Technologies	BZR-0050400-551028-252525	27736	23.09.19
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	CO3000	1175/45850319/P	-
High pass Filter	WT	WT-A1698-HS	WT160411001	23.05.03
Vector Signal Generator	R&S	SMBV100A	257566	23.07.04
Signal Generator	R&S	SMB100A	176206	23.01.19

**End of test report**