


Plot 7-95. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 484 Tones (UNII Band 3) – Ch. 151)



Plot 7-96. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – 996 Tones (UNII Band 3) – Ch. 155)

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 74 of 110                    |



**Note:**

Per ANSI C63.10-2013 Section 14.3.2.2 and KDB 662911 v02r01 Section E)2), the power spectral density at Antenna-1 and Antenna-2 were first measured separately with reduced Antenna-1 and Antenna-2 powers per manufacture’s tune-up document. The measured values were then summed in linear power units then converted back to dBm.

**Sample Directional Gain Calculation:**

Assuming the antenna gain is -8.61 dBi for Antenna-1 and -7.68 dBi for Antenna-2.

$$\begin{aligned}
\text{Directional gain} &= 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}] \text{ dBi} \\
&= 10 \log[(10^{-8.61/20} + 10^{-7.68/20} / 2] \text{ dBi} \\
&= (-5.12) \text{ dBi}
\end{aligned}$$

**Sample MIMO Calculation:**

Assuming the average conducted power spectral density was measured to be 5.88 dBm for Antenna-1 and 6.27 dBm for Antenna-2.

$$\begin{aligned}
&\text{Antenna-1} + \text{Antenna-2} = \text{MIMO} \\
(5.88 \text{ dBm} + 6.27 \text{ dBm}) &= (3.87 \text{ mW} + 4.24 \text{ mW}) = 8.11 \text{ mW} = 9.09 \text{ dBm}
\end{aligned}$$

**Sample e.i.r.p Power Spectral Density Calculation:**

Assuming the average MIMO power density was calculated to be 9.09 dBm with directional gain of -5.12 dBi.

$$\begin{aligned}
\text{e.i.r.p. Power Spectral Density(dBm)} &= \text{Power Spectral Density (dBm)} + \text{directional gain (dBi)} \\
9.09 \text{ dBm} + (-5.12) \text{ dBi} &= 3.97 \text{ dBm}
\end{aligned}$$

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 75 of 110                    |

## 7.6 Radiated Emission Measurements

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes, and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

**For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of  $-27$  dBm/MHz.**

**For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of  $-27$  dBm/MHz.**

**For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.**

**All out of band emissions appearing in a restricted band as specified in FCC §15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in the table below per FCC §15.209 and RSS-Gen (8.9).**

| Frequency         | Field Strength<br>[ $\mu$ V/m] | Measured Distance<br>[Meters] |
|-------------------|--------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400\F (kHz)                   | 300                           |
| 0.490 – 1.705 MHz | 24000\F (kHz)                  | 30                            |
| 1.705 – 30.00 MHz | 30                             | 30                            |
| 30.00 – 88.00 MHz | 100                            | 3                             |
| 88.00 – 216.0 MHz | 150                            | 3                             |
| 216.0 – 960.0 MHz | 200                            | 3                             |
| Above 960.0 MHz   | 500                            | 3                             |

**Table 7-16. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5 (Radiated Spurious Emissions)

ANSI C63.10-2013 – Section 12.7.4.4 (Band Edge Measurements)

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 76 of 110                    |

**Test Settings – Above 1GHz**

**Average Field Strength Measurements (Method AD – Average Detection)**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times \text{span} \backslash \backslash \text{RBW}$ )
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

**Peak Field Strength Measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.

**Test Settings – Below 1GHz**


**Quasi-Peak Field Strength Measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.


**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| FCC ID: A3LSMA356U                             | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 77 of 110                           |




**Figure 7-5. Radiated Test Setup < 30MHz**



**Figure 7-6. Radiated Test Setup < 1GHz**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| FCC ID: A3LSMA356U                             | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 78 of 110                           |



**Figure 7-7. Radiated Test Setup > 1GHz**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 79 of 110                           |

**Test Notes**

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dB $\mu$ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB $\mu$ V/m.
2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dB $\mu$ V/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. In the case where a peak-detector measurement passed the given RMS limit it was determined sufficient to demonstrate compliance.
10. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
11. For radiated measurements, emissions were investigated for the fully-loaded RU configuration and for all of the partially-loaded RU configurations. Among all of the available partially-loaded RU configurations, only the configuration with the worst case emissions is reported.

**Sample Calculations**

**Determining Spurious Emissions Levels**

- Field Strength Level [dB $\mu$ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB $\mu$ V/m] – Limit [dB $\mu$ V/m]

**Radiated Band Edge Measurement Offset**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 80 of 110                    |


- The amplitude offset shown in the radiated restricted band edge plots in Section Radiated Spurious Emission Measurements – Above 1GHz was calculated using the formula:  

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


|  |  |                                      |  |
|--|--|--------------------------------------|--|
| FCC ID: A3LSMA356U                             | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 81 of 110                           |




### 7.6.1 MIMO Radiated Spurious Emission Measurements (26 Tones)



**Plot 7-97. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 1 Ch. 40)**




**Plot 7-98. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 2A Ch. 56)**




**Plot 7-99. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 2C Ch. 120)**


|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 82 of 110                    |



**Plot 7-100. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 3 Ch. 157)**



**Plot 7-101. Radiated Spurious Plot 18GHz - 26.5GHz (802.11ax)**



**Plot 7-102. Radiated Spurious Plot 26.5GHz - 40GHz (802.11ax)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 83 of 110                           |

### MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII 1

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10360.00        | Peak     | V               | 209                 | 31                         | -65.72               | 12.12       | 0.00                            | 53.40                   | 68.20          | -14.80      |
| * 15540.00      | Average  | V               | 111                 | 333                        | -72.67               | 14.11       | 0.00                            | 48.44                   | 53.98          | -5.54       |
| * 15540.00      | Peak     | V               | 111                 | 333                        | -54.40               | 14.11       | 0.00                            | 66.71                   | 73.98          | -7.27       |
| * 20720.00      | Average  | V               | -                   | -                          | -67.29               | 3.27        | -9.54                           | 33.44                   | 53.98          | -20.54      |
| * 20720.00      | Peak     | V               | -                   | -                          | -57.51               | 3.27        | -9.54                           | 43.22                   | 73.98          | -30.76      |
| 25900.00        | Peak     | V               | -                   | -                          | -56.95               | 4.35        | -9.54                           | 44.85                   | 68.20          | -23.35      |

**Table 7-17. Radiated Measurements MIMO (26 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10400.00        | Peak     | V               | 211                 | 28                         | -66.55               | 12.37       | 0.00                            | 52.82                   | 68.20          | -15.38      |
| * 15600.00      | Average  | V               | 111                 | 336                        | -75.31               | 14.22       | 0.00                            | 45.91                   | 53.98          | -8.07       |
| * 15600.00      | Peak     | V               | 111                 | 336                        | -55.72               | 14.22       | 0.00                            | 65.50                   | 73.98          | -8.48       |
| * 20800.00      | Average  | V               | -                   | -                          | -66.52               | 3.40        | -9.54                           | 34.34                   | 53.98          | -19.64      |
| * 20800.00      | Peak     | V               | -                   | -                          | -56.04               | 3.40        | -9.54                           | 44.82                   | 73.98          | -29.16      |
| 26000.00        | Peak     | V               | -                   | -                          | -57.12               | 4.39        | -9.54                           | 44.72                   | 68.20          | -23.48      |

**Table 7-18. Radiated Measurements MIMO (26 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 84 of 110                    |



Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10480.00        | Peak     | V               | 211                 | 22                         | -67.43               | 13.08       | 0.00                            | 52.65                   | 68.20          | -15.55      |
| * 15720.00      | Average  | V               | 109                 | 332                        | -75.38               | 14.65       | 0.00                            | 46.27                   | 53.98          | -7.71       |
| * 15720.00      | Peak     | V               | 109                 | 332                        | -56.24               | 14.65       | 0.00                            | 65.41                   | 73.98          | -8.57       |
| * 20960.00      | Average  | V               | -                   | -                          | -67.78               | 3.41        | -9.54                           | 33.09                   | 53.98          | -20.89      |
| * 20960.00      | Peak     | V               | -                   | -                          | -57.69               | 3.41        | -9.54                           | 43.19                   | 73.98          | -30.79      |
| 26200.00        | Peak     | V               | -                   | -                          | -56.61               | 4.35        | -9.54                           | 45.20                   | 68.20          | -23.00      |

**Table 7-19. Radiated Measurements MIMO (26 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 85 of 110                           |



**MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII 2A**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10520.00        | Peak     | V               | 146                 | 38                         | -65.73               | 12.95       | 0.00                            | 54.22                   | 68.20          | -13.98      |
| * 15780.00      | Average  | V               | 164                 | 4                          | -79.55               | 14.23       | 0.00                            | 41.68                   | 53.98          | -12.30      |
| * 15780.00      | Peak     | V               | 164                 | 4                          | -62.46               | 14.23       | 0.00                            | 58.77                   | 73.98          | -15.21      |
| * 21040.00      | Average  | V               | -                   | -                          | -67.22               | 3.53        | -9.54                           | 33.77                   | 53.98          | -20.21      |
| * 21040.00      | Peak     | V               | -                   | -                          | -57.89               | 3.53        | -9.54                           | 43.10                   | 73.98          | -30.88      |
| 26300.00        | Peak     | V               | -                   | -                          | -57.02               | 4.27        | -9.54                           | 44.70                   | 68.20          | -23.50      |

**Table 7-20. Radiated Measurements MIMO (26 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10560.00        | Peak     | V               | 146                 | 43                         | -67.14               | 12.97       | 0.00                            | 52.83                   | 68.20          | -15.37      |
| * 15840.00      | Average  | V               | 169                 | 0                          | -79.13               | 14.09       | 0.00                            | 41.96                   | 53.98          | -12.02      |
| * 15840.00      | Peak     | V               | 169                 | 0                          | -60.96               | 14.09       | 0.00                            | 60.13                   | 73.98          | -13.85      |
| * 21120.00      | Average  | V               | -                   | -                          | -67.36               | 3.66        | -9.54                           | 33.75                   | 53.98          | -20.23      |
| * 21120.00      | Peak     | V               | -                   | -                          | -56.59               | 3.66        | -9.54                           | 44.52                   | 73.98          | -29.46      |
| 26400.00        | Peak     | V               | -                   | -                          | -57.78               | 4.21        | -9.54                           | 43.89                   | 68.20          | -24.31      |

**Table 7-21. Radiated Measurements MIMO (26 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 86 of 110                    |

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 10640.00      | Average  | V               | 151                 | 41                         | -77.65               | 12.51       | 0.00                            | 41.86                   | 53.98          | -12.12      |
| * 10640.00      | Peak     | V               | 151                 | 41                         | -66.61               | 12.51       | 0.00                            | 52.90                   | 73.98          | -21.08      |
| * 15960.00      | Average  | V               | 156                 | 1                          | -80.99               | 15.27       | 0.00                            | 41.28                   | 53.98          | -12.70      |
| * 15960.00      | Peak     | V               | 156                 | 1                          | -64.79               | 15.27       | 0.00                            | 57.48                   | 73.98          | -16.50      |
| * 21280.00      | Average  | V               | -                   | -                          | -67.62               | 3.75        | -9.54                           | 33.59                   | 53.98          | -20.39      |
| * 21280.00      | Peak     | V               | -                   | -                          | -57.68               | 3.75        | -9.54                           | 43.53                   | 73.98          | -30.45      |
| 26600.00        | Peak     | V               | -                   | -                          | -57.76               | 4.20        | -9.54                           | 43.90                   | 68.20          | -24.30      |

**Table 7-22. Radiated Measurements MIMO (26 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 87 of 110                    |



**MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII 2C**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11000.00      | Average  | V               | 222                 | 5                          | -76.55               | 12.66       | 0.00                            | 43.11                   | 53.98          | -10.87      |
| * 11000.00      | Peak     | V               | 222                 | 5                          | -66.91               | 12.66       | 0.00                            | 52.75                   | 73.98          | -21.23      |
| 16500.00        | Peak     | V               | 125                 | 323                        | -65.15               | 15.81       | 0.00                            | 57.66                   | 68.20          | -10.54      |
| 22000.00        | Peak     | V               | -                   | -                          | -57.42               | 3.75        | -9.54                           | 43.79                   | 68.20          | -24.41      |
| 27500.00        | Peak     | V               | -                   | -                          | -57.24               | 4.29        | -9.54                           | 44.50                   | 68.20          | -23.70      |

**Table 7-23. Radiated Measurements MIMO (26 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5600MHz  
 Channel: 120

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11200.00      | Average  | V               | 207                 | 7                          | -77.15               | 12.54       | 0.00                            | 42.39                   | 53.98          | -11.59      |
| * 11200.00      | Peak     | V               | 207                 | 7                          | -67.98               | 12.54       | 0.00                            | 51.56                   | 73.98          | -22.42      |
| 16800.00        | Peak     | V               | 124                 | 322                        | -65.34               | 16.25       | 0.00                            | 57.91                   | 68.20          | -10.29      |
| * 22400.00      | Average  | V               | -                   | -                          | -66.73               | 3.72        | -9.54                           | 34.45                   | 53.98          | -19.53      |
| * 22400.00      | Peak     | V               | -                   | -                          | -56.38               | 3.72        | -9.54                           | 44.79                   | 73.98          | -29.19      |
| 28000.00        | Peak     | V               | -                   | -                          | -57.51               | 4.51        | -9.54                           | 44.46                   | 68.20          | -23.74      |

**Table 7-24. Radiated Measurements MIMO (26 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 88 of 110                    |



Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5720MHz  
 Channel: 144

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11440.00      | Average  | V               | 209                 | 352                        | -78.53               | 13.54       | 0.00                            | 42.01                   | 53.98          | -11.97      |
| * 11440.00      | Peak     | V               | 209                 | 352                        | -68.85               | 13.54       | 0.00                            | 51.69                   | 73.98          | -22.29      |
| 17160.00        | Peak     | V               | 112                 | 321                        | -64.24               | 16.79       | 0.00                            | 59.55                   | 68.20          | -8.65       |
| * 22880.00      | Average  | V               | -                   | -                          | -67.03               | 3.87        | -9.54                           | 34.30                   | 53.98          | -19.68      |
| * 22880.00      | Peak     | V               | -                   | -                          | -57.38               | 3.87        | -9.54                           | 43.95                   | 73.98          | -30.03      |
| 28600.00        | Peak     | V               | -                   | -                          | -57.27               | 5.03        | -9.54                           | 45.22                   | 68.20          | -22.98      |

**Table 7-25. Radiated Measurements MIMO (26 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 89 of 110                           |





### MIMO Radiated Spurious Emission Measurements (26 Tones) – UNII 3

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11490.00      | Average  | V               | 199                 | 345                        | -76.90               | 13.10       | 0.00                            | 43.20                   | 53.98          | -10.78      |
| * 11490.00      | Peak     | V               | 199                 | 345                        | -68.04               | 13.10       | 0.00                            | 52.06                   | 73.98          | -21.92      |
| 17235.00        | Peak     | V               | 304                 | 20                         | -64.03               | 16.91       | 0.00                            | 59.88                   | 68.20          | -8.32       |
| * 22980.00      | Average  | V               | -                   | -                          | -66.91               | 3.75        | -9.54                           | 34.30                   | 53.98          | -19.68      |
| * 22980.00      | Peak     | V               | -                   | -                          | -55.99               | 3.75        | -9.54                           | 45.22                   | 73.98          | -28.76      |
| 28725.00        | Peak     | V               | -                   | -                          | -56.15               | 5.10        | -9.54                           | 46.41                   | 68.20          | -21.79      |

**Table 7-26. Radiated Measurements MIMO (26 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11570.00      | Average  | V               | 195                 | 340                        | -75.24               | 12.96       | 0.00                            | 44.72                   | 53.98          | -9.26       |
| * 11570.00      | Peak     | V               | 195                 | 340                        | -66.44               | 12.96       | 0.00                            | 53.52                   | 73.98          | -20.46      |
| 17355.00        | Peak     | V               | 297                 | 23                         | -66.34               | 17.83       | 0.00                            | 58.49                   | 68.20          | -9.71       |
| 23140.00        | Peak     | V               | -                   | -                          | -56.58               | 3.70        | -9.54                           | 44.58                   | 68.20          | -23.62      |
| 28925.00        | Peak     | V               | -                   | -                          | -57.13               | 5.00        | -9.54                           | 45.33                   | 68.20          | -22.87      |

**Table 7-27. Radiated Measurements MIMO (26 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 90 of 110                    |




Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 4  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11650.00      | Average  | V               | 198                 | 345                        | -76.65               | 13.39       | 0.00                            | 43.74                   | 53.98          | -10.24      |
| * 11650.00      | Peak     | V               | 198                 | 345                        | -68.00               | 13.39       | 0.00                            | 52.39                   | 73.98          | -21.59      |
| 17475.00        | Peak     | V               | 301                 | 22                         | -65.50               | 17.09       | 0.00                            | 58.59                   | 68.20          | -9.61       |
| 23300.00        | Peak     | V               | -                   | -                          | -56.40               | 3.73        | -9.54                           | 44.79                   | 68.20          | -23.41      |
| 29125.00        | Peak     | V               | -                   | -                          | -56.40               | 5.04        | -9.54                           | 46.10                   | 68.20          | -22.10      |


**Table 7-28. Radiated Measurements MIMO (26 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 91 of 110                           |


## 7.6.2 MIMO Radiated Spurious Emission Measurements (242 Tones)



**Plot 7-103. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 1 Ch. 40)**




**Plot 7-104. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 2A Ch. 56)**




**Plot 7-105. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 2C Ch. 120)**


|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 92 of 110                    |



**Plot 7-106. Radiated Spurious Plot above 1GHz MIMO (802.11ax – UNII 3 Ch. 157)**



**Plot 7-107. Radiated Spurious Plot 18GHz - 26.5GHz (802.11ax)**



**Plot 7-108. Radiated Spurious Plot 26.5GHz - 40GHz (802.11ax)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 93 of 110                    |



## MIMO Radiated Spurious Emission Measurements (242 Tones) – UNII 1

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5180MHz  
 Channel: 36

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10360.00        | Peak     | V               | 207                 | 26                         | -68.01               | 12.12       | 0.00                            | 51.11                   | 68.20          | -17.09      |
| * 15540.00      | Average  | V               | 116                 | 35                         | -76.75               | 14.11       | 0.00                            | 44.36                   | 53.98          | -9.62       |
| * 15540.00      | Peak     | V               | 116                 | 35                         | -62.58               | 14.11       | 0.00                            | 58.53                   | 73.98          | -15.45      |
| * 20720.00      | Average  | V               | -                   | -                          | -66.92               | 3.27        | -9.54                           | 33.81                   | 53.98          | -20.17      |
| * 20720.00      | Peak     | V               | -                   | -                          | -57.14               | 3.27        | -9.54                           | 43.59                   | 73.98          | -30.39      |
| 25900.00        | Peak     | V               | -                   | -                          | -56.89               | 4.35        | -9.54                           | 44.92                   | 68.20          | -23.28      |

**Table 7-29. Radiated Measurements MIMO (242 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5200MHz  
 Channel: 40

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10400.00        | Peak     | V               | 227                 | 38                         | -67.79               | 12.37       | 0.00                            | 51.58                   | 68.20          | -16.62      |
| * 15600.00      | Average  | V               | 110                 | 37                         | -77.22               | 14.22       | 0.00                            | 44.00                   | 53.98          | -9.98       |
| * 15600.00      | Peak     | V               | 110                 | 37                         | -61.99               | 14.22       | 0.00                            | 59.23                   | 73.98          | -14.75      |
| * 20800.00      | Average  | V               | -                   | -                          | -66.81               | 3.40        | -9.54                           | 34.05                   | 53.98          | -19.93      |
| * 20800.00      | Peak     | V               | -                   | -                          | -56.99               | 3.40        | -9.54                           | 43.87                   | 73.98          | -30.11      |
| 26000.00        | Peak     | V               | -                   | -                          | -57.00               | 4.39        | -9.54                           | 44.84                   | 68.20          | -23.36      |

**Table 7-30. Radiated Measurements MIMO (242 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 94 of 110                    |

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5240MHz  
 Channel: 48

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10480.00        | Peak     | V               | 212                 | 31                         | -68.84               | 13.08       | 0.00                            | 51.24                   | 68.20          | -16.96      |
| * 15720.00      | Average  | V               | 113                 | 36                         | -76.08               | 14.65       | 0.00                            | 45.57                   | 53.98          | -8.41       |
| * 15720.00      | Peak     | V               | 113                 | 36                         | -60.32               | 14.65       | 0.00                            | 61.33                   | 73.98          | -12.65      |
| * 20960.00      | Average  | V               | -                   | -                          | -67.22               | 3.41        | -9.54                           | 33.65                   | 53.98          | -20.33      |
| * 20960.00      | Peak     | V               | -                   | -                          | -57.51               | 3.41        | -9.54                           | 43.36                   | 73.98          | -30.62      |
| 26200.00        | Peak     | V               | -                   | -                          | -56.81               | 4.35        | -9.54                           | 45.00                   | 68.20          | -23.20      |

**Table 7-31. Radiated Measurements MIMO (242 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 95 of 110                           |



## MIMO Radiated Spurious Emission Measurements (242 Tones) – UNII 2A

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5260MHz  
 Channel: 52

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10520.00        | Peak     | V               | 116                 | 43                         | -67.02               | 12.95       | 0.00                            | 52.93                   | 68.20          | -15.27      |
| * 15780.00      | Average  | V               | 110                 | 34                         | -77.96               | 14.23       | 0.00                            | 43.27                   | 53.98          | -10.71      |
| * 15780.00      | Peak     | V               | 110                 | 34                         | -63.13               | 14.23       | 0.00                            | 58.10                   | 73.98          | -15.88      |
| * 21040.00      | Average  | V               | -                   | -                          | -67.35               | 3.53        | -9.54                           | 33.64                   | 53.98          | -20.34      |
| * 21040.00      | Peak     | V               | -                   | -                          | -57.55               | 3.53        | -9.54                           | 43.44                   | 73.98          | -30.54      |
| 26300.00        | Peak     | V               | -                   | -                          | -56.81               | 4.27        | -9.54                           | 44.91                   | 68.20          | -23.29      |

**Table 7-32. Radiated Measurements MIMO (242 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5280MHz  
 Channel: 56

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| 10560.00        | Peak     | V               | 120                 | 39                         | -68.57               | 12.97       | 0.00                            | 51.40                   | 68.20          | -16.80      |
| * 15840.00      | Average  | V               | 112                 | 35                         | -77.78               | 14.09       | 0.00                            | 43.31                   | 53.98          | -10.67      |
| * 15840.00      | Peak     | V               | 112                 | 35                         | -63.69               | 14.09       | 0.00                            | 57.40                   | 73.98          | -16.58      |
| * 21120.00      | Average  | V               | -                   | -                          | -67.13               | 3.66        | -9.54                           | 33.99                   | 53.98          | -19.99      |
| * 21120.00      | Peak     | V               | -                   | -                          | -56.99               | 3.66        | -9.54                           | 44.13                   | 73.98          | -29.85      |
| 26400.00        | Peak     | V               | -                   | -                          | -57.33               | 4.21        | -9.54                           | 44.33                   | 68.20          | -23.87      |

**Table 7-33. Radiated Measurements MIMO (242 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 96 of 110                    |

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5320MHz  
 Channel: 64

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 10640.00      | Average  | V               | 127                 | 47                         | -78.26               | 12.51       | 0.00                            | 41.25                   | 53.98          | -12.73      |
| * 10640.00      | Peak     | V               | 127                 | 47                         | -67.78               | 12.51       | 0.00                            | 51.73                   | 73.98          | -22.25      |
| * 15960.00      | Average  | V               | 125                 | 37                         | -79.86               | 15.27       | 0.00                            | 42.41                   | 53.98          | -11.57      |
| * 15960.00      | Peak     | V               | 125                 | 37                         | -65.50               | 15.27       | 0.00                            | 56.77                   | 73.98          | -17.21      |
| * 21280.00      | Average  | V               | -                   | -                          | -67.55               | 3.75        | -9.54                           | 33.66                   | 53.98          | -20.32      |
| * 21280.00      | Peak     | V               | -                   | -                          | -57.46               | 3.75        | -9.54                           | 43.75                   | 73.98          | -30.23      |
| 26600.00        | Peak     | V               | -                   | -                          | -57.77               | 4.20        | -9.54                           | 43.89                   | 68.20          | -24.31      |

**Table 7-34. Radiated Measurements MIMO (242 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 97 of 110                           |





**MIMO Radiated Spurious Emission Measurements (242 Tones) – UNII 2C**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11000.00      | Average  | V               | 208                 | 1                          | -77.10               | 12.66       | 0.00                            | 42.56                   | 53.98          | -11.42      |
| * 11000.00      | Peak     | V               | 208                 | 1                          | -66.57               | 12.66       | 0.00                            | 53.09                   | 73.98          | -20.89      |
| 16500.00        | Peak     | V               | 152                 | 322                        | -67.22               | 15.81       | 0.00                            | 55.59                   | 68.20          | -12.61      |
| 22000.00        | Peak     | V               | -                   | -                          | -57.12               | 3.75        | -9.54                           | 44.09                   | 68.20          | -24.11      |
| 27500.00        | Peak     | V               | -                   | -                          | -56.84               | 4.29        | -9.54                           | 44.90                   | 68.20          | -23.30      |

**Table 7-35. Radiated Measurements MIMO (26 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5600MHz  
 Channel: 120

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11200.00      | Average  | V               | 193                 | 8                          | -77.14               | 12.54       | 0.00                            | 42.40                   | 53.98          | -11.58      |
| * 11200.00      | Peak     | V               | 193                 | 8                          | -67.61               | 12.54       | 0.00                            | 51.93                   | 73.98          | -22.05      |
| 16800.00        | Peak     | V               | 137                 | 323                        | -67.15               | 16.25       | 0.00                            | 56.10                   | 68.20          | -12.10      |
| * 22400.00      | Average  | V               | -                   | -                          | -66.82               | 3.72        | -9.54                           | 34.35                   | 53.98          | -19.63      |
| * 22400.00      | Peak     | V               | -                   | -                          | -57.23               | 3.72        | -9.54                           | 43.94                   | 73.98          | -30.04      |
| 28000.00        | Peak     | V               | -                   | -                          | -56.88               | 4.51        | -9.54                           | 45.09                   | 68.20          | -23.11      |

**Table 7-36. Radiated Measurements MIMO (26 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 98 of 110                           |

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5720MHz  
 Channel: 144

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11440.00      | Average  | V               | 202                 | 352                        | -78.56               | 13.54       | 0.00                            | 41.98                   | 53.98          | -12.00      |
| * 11440.00      | Peak     | V               | 202                 | 352                        | -69.23               | 13.54       | 0.00                            | 51.31                   | 73.98          | -22.67      |
| 17160.00        | Peak     | V               | 137                 | 323                        | -67.40               | 16.79       | 0.00                            | 56.39                   | 68.20          | -11.81      |
| * 22880.00      | Average  | V               | -                   | -                          | -67.13               | 3.87        | -9.54                           | 34.20                   | 53.98          | -19.78      |
| * 22880.00      | Peak     | V               | -                   | -                          | -57.12               | 3.87        | -9.54                           | 44.21                   | 73.98          | -29.77      |
| 28600.00        | Peak     | V               | -                   | -                          | -56.55               | 5.03        | -9.54                           | 45.94                   | 68.20          | -22.26      |

**Table 7-37. Radiated Measurements MIMO (26 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 99 of 110                           |



**MIMO Radiated Spurious Emission Measurements (242 Tones) – UNII 3**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11490.00      | Average  | V               | 194                 | 344                        | -76.89               | 13.10       | 0.00                            | 43.21                   | 53.98          | -10.77      |
| * 11490.00      | Peak     | V               | 194                 | 344                        | -68.11               | 13.10       | 0.00                            | 51.99                   | 73.98          | -21.99      |
| 17235.00        | Peak     | V               | 230                 | 26                         | -65.92               | 16.91       | 0.00                            | 57.99                   | 68.20          | -10.21      |
| * 22980.00      | Average  | V               | -                   | -                          | -66.81               | 3.75        | -9.54                           | 34.40                   | 53.98          | -19.58      |
| * 22980.00      | Peak     | V               | -                   | -                          | -56.23               | 3.75        | -9.54                           | 44.98                   | 73.98          | -29.00      |
| 28725.00        | Peak     | V               | -                   | -                          | -56.44               | 5.10        | -9.54                           | 46.12                   | 68.20          | -22.08      |

**Table 7-38. Radiated Measurements MIMO (242 Tones)**

Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11570.00      | Average  | V               | 197                 | 345                        | -75.72               | 12.96       | 0.00                            | 44.24                   | 53.98          | -9.74       |
| * 11570.00      | Peak     | V               | 197                 | 345                        | -67.34               | 12.96       | 0.00                            | 52.62                   | 73.98          | -21.36      |
| 17355.00        | Peak     | V               | 222                 | 27                         | -67.17               | 17.83       | 0.00                            | 57.66                   | 68.20          | -10.54      |
| 23140.00        | Peak     | V               | -                   | -                          | -56.91               | 3.70        | -9.54                           | 44.24                   | 68.20          | -23.96      |
| 28925.00        | Peak     | V               | -                   | -                          | -57.03               | 5.00        | -9.54                           | 45.43                   | 68.20          | -22.77      |

**Table 7-39. Radiated Measurements MIMO (242 Tones)**

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 100 of 110                          |



Worst Case Mode: 802.11ax (20MHz BW)  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 1 & 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165


| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Distance Correction Factor [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|---------------------------------|-------------------------|----------------|-------------|
| * 11650.00      | Average  | V               | 200                 | 339                        | -76.06               | 13.39       | 0.00                            | 44.33                   | 53.98          | -9.65       |
| * 11650.00      | Peak     | V               | 200                 | 339                        | -68.38               | 13.39       | 0.00                            | 52.01                   | 73.98          | -21.97      |
| 17475.00        | Peak     | V               | 224                 | 21                         | -66.46               | 17.09       | 0.00                            | 57.63                   | 68.20          | -10.57      |
| 23300.00        | Peak     | V               | -                   | -                          | -56.49               | 3.73        | -9.54                           | 44.70                   | 68.20          | -23.50      |
| 29125.00        | Peak     | V               | -                   | -                          | -56.11               | 5.04        | -9.54                           | 46.39                   | 68.20          | -21.81      |

**Table 7-40. Radiated Measurements MIMO (242 Tones)**


|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 101 of 110                          |

### 7.6.3 MIMO Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T)

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 53       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5180MHz  |
| Channel:                  | 36       |




**Plot 7-109. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 106 Tones)**




**Plot 7-110. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 106 Tones)**

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 54       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5320MHz  |
| Channel:                  | 64       |




**Plot 7-111. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 106 Tones)**




**Plot 7-112. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 106 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 102 of 110                   |

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 53  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100




**Plot 7-113. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 106 Tones)**



**Plot 7-114. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 106 Tones)**

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 54  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165




**Plot 7-115. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 106 Tones)**


|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 103 of 110                   |

### 7.6.4 MIMO Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T)

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 61       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5180MHz  |
| Channel:                  | 36       |




**Plot 7-116. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 242 Tones)**




**Plot 7-117. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 242 Tones)**

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 61       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5320MHz  |
| Channel:                  | 64       |




**Plot 7-118. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 242 Tones)**




**Plot 7-119. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 242 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 104 of 110                   |

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5500MHz  
 Channel: 100




**Plot 7-120. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 242 Tones)**



**Plot 7-121. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 242 Tones)**

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 61  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165




**Plot 7-122. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 242 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 105 of 110                   |




### 7.6.5 MIMO Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T)

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 65       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5190MHz  |
| Channel:                  | 38       |




**Plot 7-123. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 484 Tones)**




**Plot 7-124. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 484 Tones)**

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 65       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5310MHz  |
| Channel:                  | 62       |



**Plot 7-125. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 484 Tones)**




**Plot 7-126. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 484 Tones)**


|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 106 of 110                   |



Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 65  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5510MHz  
 Channel: 102




**Plot 7-127. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 484 Tones)**



**Plot 7-128. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 484 Tones)**

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 65  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5795MHz  
 Channel: 159




**Plot 7-129. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 484 Tones)**


|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 107 of 110                   |

## 7.6.6 MIMO Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T)

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 67       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5210MHz  |
| Channel:                  | 42       |




**Plot 7-130. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 996 Tones)**




**Plot 7-131. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 996 Tones)**

|                           |          |
|---------------------------|----------|
| Worst Case Mode:          | 802.11ax |
| Worst Case Transfer Rate: | MCS0     |
| RU Index:                 | 67       |
| Distance of Measurements: | 3 Meters |
| Operating Frequency:      | 5290MHz  |
| Channel:                  | 58       |




**Plot 7-132. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 996 Tones)**




**Plot 7-133. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 996 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | MEASUREMENT REPORT              |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 108 of 110                   |

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 67  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5530MHz  
 Channel: 106




**Plot 7-134. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 996 Tones)**



**Plot 7-135. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 996 Tones)**

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 RU Index: 67  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5775MHz  
 Channel: 155



**Plot 7-136. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 996 Tones)**

|   |                                 |                               |                                   |
|---|---------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMA356U                      | <b>MEASUREMENT REPORT</b>       |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2311010111-14.A3L | Test Dates:<br>11/07-12/29/2023 | EUT Type:<br>Portable Handset | Page 109 of 110                   |

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC: A3LSMA356U** is in compliance with FCC Part Subpart E (15.407) of the FCC rules.

|  |  |                                      |  |
|--|--|--------------------------------------|--|
| <b>FCC ID:</b> A3LSMA356U                      | <b>MEASUREMENT REPORT</b>              |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2311010111-14.A3L | <b>Test Dates:</b><br>11/07-12/29/2023 | <b>EUT Type:</b><br>Portable Handset | Page 110 of 110                          |