

FCC DTS REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Date of Issue:
March 09, 2020

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Test Site/Location:
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Report No.: HCT-RF-2003-FC003-R1

FCC ID: A3LSMA415FN

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model: SM-A415F/DSN

EUT Type: Mobile Phone

Average Output Power: 802.11b : 19.14 dBm / 802.11g : 15.98 dBm / 802.11n(HT20) : 15.95 dBm

Frequency Range: 2 412 MHz ~ 2 472 MHz

Modulation type: CCK/DSSS/OFDM

FCC Classification: Digital Transmission System(DTS)

FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

Report prepared by : Jeong Ho Kim
Engineer of Telecommunication testing center

Approved by : Jong Seok Lee
Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2003-FC003	March 03, 2020	- First Approval Report
HCT-RF-2003-FC003-R1	March 09, 2020	- On Page 27, 6dB BW result revised.

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

Table of Contents

1. EUT DESCRIPTION	4
2. TEST METHODOLOGY	5
EUT CONFIGURATION	5
EUT EXERCISE	5
GENERAL TEST PROCEDURES	5
DESCRIPTION OF TEST MODES	5
3. INSTRUMENT CALIBRATION.....	6
4. FACILITIES AND ACCREDITATIONS	6
FACILITIES	6
EQUIPMENT	6
5. ANTENNA REQUIREMENTS	7
6. MEASUREMENT UNCERTAINTY.....	7
7. DESCRIPTION OF TESTS	8
8. SUMMARY TEST OF RESULTS	23
9. TEST RESULT	24
9.1 DUTY CYCLE.....	24
9.2 6dB BANDWIDTH.....	27
9.3 OUTPUT POWER	30
9.4 POWER SPECTRAL DENSITY.....	36
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS.....	39
9.6 RADIATED SPURIOUS EMISSIONS	53
9.7 RADIATED RESTRICTED BAND EDGES	64
9.8 POWERLINE CONDUCTED EMISSIONS	71
10. LIST OF TEST EQUIPMENT	75
11. ANNEX A_ TEST SETUP PHOTO	77

1. EUT DESCRIPTION

Model	SM-A415F/DSN
Additional Model	-
EUT Type	Mobile Phone
Power Supply	DC 3.85 V
Battery Information	Model: EB-BA415ABY Type: Li-ion Battery
Travel Adapter Information	Model : EP-TA200 Manufacture: SOLUM
Data Cable Information	Model : EP-DR140ABE Manufacture: KSD
Ear-jack Information	Model : EHS61ASFBE Manufacture: FOSTER
Frequency Range	2 412 MHz ~ 2 472 MHz
Max. RF Output Power	Peak Power(For information only) 802.11b : 21.63 dBm 802.11g : 25.88 dBm 802.11n(HT20) : 25.95 dBm Average Power 802.11b : 19.14 dBm 802.11g : 15.98 dBm 802.11n(HT20) : 15.95 dBm
Modulation Type	DSSS/CCK : 802.11b OFDM : 802.11g, 802.11n
Number of Channels	13 Channels
Antenna Specification	Antenna type: MFA Peak Gain : -5.04 dBi
Date(s) of Tests	February 01, 2020~ March 03, 2020

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled "guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) 'the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices'.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on}/T_{total} and Duty Cycle Factor = $10\log(1/\text{Duty Cycle})$

7.2. 6dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW \geq 3 x RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
 - : Measure the peak power of the transmitter.

- Average Power (Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Reading Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3) RBW = 3 kHz ≤ RBW ≤ 100 kHz.
- 4) VBW ≥ 3 x RBW.
- 5) Sweep = auto couple
- 6) Detector = power averaging (rms) or sample detector (when rms not available).
- 7) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- 8) Employ trace averaging (rms) mode over a minimum of 100 traces
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11) if then duty factor shall be added to adjust the result if the duty cycle is less than 98%


Sample Calculation

- Power Spectral Density = Reading Value + ATT loss + Cable loss

7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions**Limit**

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 30 dBc]

Test Configuration**Test Procedure**

The transmitter output is connected to the spectrum analyzer.

(Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW \geq 3 x RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points \geq 2 x Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	20.10
100	20.17
200	20.24
300	20.33
400	20.36
500	20.40
600	20.40
700	20.43
800	20.46
900	20.48
1000	20.51
2000	20.72
2400	20.79
2480	20.80
2500	20.81
3000	20.88
4000	21.01
5000	21.14
5150	21.16
5850	21.24
6000	21.26
7000	21.37
8000	21.49
9000	21.57
10000	21.66
11000	21.75
12000	21.84
13000	21.89
14000	21.92
15000	21.97
16000	22.03
17000	22.09
18000	22.13
19000	22.19
20000	22.25
21000	22.27
22000	22.29
23000	22.34
24000	22.47
25000	22.45
26000	22.58

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Attenuator loss(10 dB) + Cable loss(1ea)


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor($0.009\text{ MHz} - 0.490\text{ MHz}$) = $40\log(3\text{ m}/300\text{ m}) = -80\text{ dB}$

Measurement Distance : 3 m

7. Distance Correction Factor($0.490 \text{ MHz} - 30 \text{ MHz}$) = $40\log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$

Measurement Distance : 3 m

8. Spectrum Setting

- Frequency Range = 9 kHz ~ 30 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 9 kHz
- VBW $\geq 3 \times \text{RBW}$

9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW $\geq 3 \times \text{RBW}$

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

7. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).

◆ Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)

6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)

(1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS

- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW \geq 3 x RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(G)} + \text{Distance Factor(D.F)}$$

Total(Measurement Type : Average, Duty cycle \geq 98%)

$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(G)} + \text{Distance Factor(D.F)}$$

Total(Measurement Type : Average, Duty cycle < 98%)

$$\begin{aligned} &= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(G)} + \text{Distance Factor(D.F)} \\ &+ \text{Duty Cycle Factor} \end{aligned}$$

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
 - ◆ Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$,

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit

in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.

- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle \geq 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $<$ 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) + Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

7.8. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : Y
 - Radiated Restricted Band Edge : X
3. Duty cycle factor applies only 802.11g/n(Duty cycle < 98%).
4. All data rate of operation were investigated and the test results are worst case in lowest datarate of each mode.
 - 802.11b : 1Mbps
 - 802.11g : 6Mbps
 - 802.11n_HT20 : MCS0
5. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Earphone, etc)+Travel Adapter,
Stand alone + Travel Adapter
 - Worstcase : Stand alone + Travel Adapter

Conducted test

1. The EUT was configured with data rate of highest power.

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 7.6		PASS


9. TEST RESULT

9.1 DUTY CYCLE


Mode	Data Rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1	8.392	8.422	0.996	0.016
	2	4.286	4.324	0.991	0.038
	5.5	1.681	1.720	0.977	0.102
	11	0.938	0.975	0.962	0.169
802.11g	6	1.391	1.435	0.969	0.136
	9	0.935	0.980	0.954	0.203
	12	0.707	0.752	0.940	0.267
	18	0.480	0.525	0.915	0.388
	24	0.364	0.409	0.890	0.504
	36	0.252	0.297	0.849	0.709
	48	0.192	0.236	0.813	0.898
	54	0.176	0.220	0.797	0.984
802.11n (HT20)	6.5 (MCS0)	1.301	1.345	0.967	0.144
	13 (MCS1)	0.668	0.713	0.937	0.282
	19.5 (MCS2)	0.460	0.505	0.911	0.404
	26 (MCS3)	0.353	0.397	0.889	0.509
	39 (MCS4)	0.248	0.293	0.847	0.722
	52 (MCS5)	0.196	0.241	0.816	0.882
	58.5 (MCS6)	0.180	0.225	0.802	0.957
	65 (MCS7)	0.164	0.209	0.787	1.041

█ Test Plots


Duty cycle plot (802.11b(1Mbps))



Duty cycle plot (802.11g(6Mbps))



Duty cycle plot (802.11n(MCS0))



Note:

In order to simplify the report, attached plots were only the most lowest data rate.

9.2 6dB BANDWIDTH


802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	8.571	0.5
2437	6	8.113	0.5
2462	11	8.086	0.5
2467	12	7.612	0.5
2472	13	7.135	0.5

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	15.79	0.5
2437	6	16.38	0.5
2462	11	15.76	0.5
2467	12	16.08	0.5
2472	13	16.09	0.5

802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	16.42	0.5
2437	6	17.62	0.5
2462	11	16.41	0.5
2467	12	16.39	0.5
2472	13	16.98	0.5

□ Test Plots


6dB Bandwidth plot (802.11b-CH 13)



6dB Bandwidth plot (802.11g-CH 11)



6dB Bandwidth plot (802.11n_HT20-CH 12)



Note:

In order to simplify the report, attached plots were only the most narrow 6 dB BW channel.

9.3 OUTPUT POWER

Peak Power

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 20.81 dB is offset for 2.4 GHz Band

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	1	21.33	30	18
		2	21.32	30	
		5.5	21.32	30	
		11	21.34	30	
2437	6	1	21.60	30	18
		2	21.63	30	
		5.5	21.57	30	
		11	21.62	30	
2462	11	1	20.94	30	16
		2	20.96	30	
		5.5	21.00	30	
		11	21.04	30	
2467	12	1	18.86	30	16
		2	18.88	30	
		5.5	18.87	30	
		11	18.85	30	
2472	13	1	15.36	30	12
		2	15.38	30	
		5.5	15.35	30	
		11	15.32	30	

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	6	24.03	30	13
		9	24.17	30	
		12	23.99	30	
		18	24.07	30	
		24	24.04	30	
		36	24.13	30	
		48	25.06	30	
		54	24.94	30	
2437	6	6	25.67	30	15
		9	25.70	30	
		12	25.73	30	
		18	25.85	30	
		24	25.59	30	
		36	25.66	30	
		48	25.88	30	
		54	25.88	30	
2462	11	6	23.74	30	13
		9	24.11	30	
		12	23.93	30	
		18	23.92	30	
		24	24.52	30	
		36	24.18	30	
		48	25.00	30	
		54	25.00	30	
2467	12	6	21.32	30	10
		9	21.57	30	
		12	21.45	30	
		18	21.34	30	
		24	21.67	30	
		36	21.35	30	
		48	21.33	30	
		54	21.82	30	
2472	13	6	13.79	30	2
		9	13.68	30	
		12	13.27	30	
		18	13.81	30	
		24	14.34	30	
		36	13.49	30	
		48	13.59	30	
		54	13.17	30	

802.11n(HT20) Mode		MCS Index	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	0	24.06	30	13
		1	23.90	30	
		2	24.21	30	
		3	24.34	30	
		4	24.14	30	
		5	25.05	30	
		6	25.55	30	
		7	24.81	30	
2437	6	0	25.75	30	15
		1	25.64	30	
		2	25.67	30	
		3	25.71	30	
		4	25.75	30	
		5	25.93	30	
		6	25.88	30	
		7	25.95	30	
2462	11	0	23.11	30	12
		1	22.94	30	
		2	22.84	30	
		3	22.85	30	
		4	23.11	30	
		5	23.97	30	
		6	24.84	30	
		7	24.66	30	
2467	12	0	21.38	30	10
		1	21.28	30	
		2	20.86	30	
		3	21.28	30	
		4	21.24	30	
		5	21.91	30	
		6	22.16	30	
		7	21.55	30	
2472	13	0	13.83	30	2
		1	13.77	30	
		2	13.84	30	
		3	13.85	30	
		4	13.47	30	
		5	13.68	30	
		6	14.17	30	
		7	13.67	30	

Average Power

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 20.81 dB is offset for 2.4 GHz Band.

802.11b Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	1	18.60	0.016	18.62	30	18
		2	18.56	0.038	18.60	30	
		5.5	18.59	0.102	18.69	30	
		11	18.45	0.169	18.62	30	
2437	6	1	19.00	0.016	19.02	30	18
		2	18.97	0.038	19.01	30	
		5.5	19.04	0.102	19.14	30	
		11	18.91	0.169	19.08	30	
2462	11	1	18.27	0.016	18.29	30	16
		2	18.23	0.038	18.27	30	
		5.5	18.25	0.102	18.35	30	
		11	18.15	0.169	18.32	30	
2467	12	1	16.28	0.016	16.30	30	16
		2	16.25	0.038	16.29	30	
		5.5	16.26	0.102	16.36	30	
		11	16.05	0.169	16.22	30	
2472	13	1	11.91	0.016	11.93	30	12
		2	11.87	0.038	11.91	30	
		5.5	11.86	0.102	11.96	30	
		11	11.78	0.169	11.95	30	

802.11g Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	6	13.27	0.136	13.41	30	13
		9	13.21	0.203	13.41	30	
		12	13.15	0.267	13.42	30	
		18	13.04	0.388	13.43	30	
		24	12.95	0.504	13.45	30	
		36	12.76	0.709	13.47	30	
		48	12.54	0.898	13.44	30	
		54	12.48	0.984	13.46	30	
2437	6	6	15.75	0.136	15.89	30	15
		9	15.68	0.203	15.88	30	
		12	15.63	0.267	15.90	30	
		18	15.52	0.388	15.91	30	
		24	15.41	0.504	15.91	30	
		36	15.23	0.709	15.94	30	
		48	15.08	0.898	15.98	30	
		54	14.99	0.984	15.97	30	
2462	11	6	13.23	0.136	13.37	30	13
		9	13.13	0.203	13.33	30	
		12	13.08	0.267	13.35	30	
		18	12.95	0.388	13.34	30	
		24	12.86	0.504	13.36	30	
		36	12.69	0.709	13.40	30	
		48	12.58	0.898	13.48	30	
		54	12.51	0.984	13.49	30	
2467	12	6	10.08	0.136	10.22	30	10
		9	10.03	0.203	10.23	30	
		12	9.96	0.267	10.23	30	
		18	9.76	0.388	10.15	30	
		24	9.56	0.504	10.06	30	
		36	9.38	0.709	10.09	30	
		48	9.33	0.898	10.23	30	
		54	9.27	0.984	10.25	30	
2472	13	6	1.81	0.136	1.95	30	2
		9	1.74	0.203	1.94	30	
		12	1.72	0.267	1.99	30	
		18	1.61	0.388	2.00	30	
		24	1.46	0.504	1.96	30	
		36	1.09	0.709	1.80	30	
		48	0.92	0.898	1.82	30	
		54	0.85	0.984	1.83	30	

802.11n(HT20) Mode		MCS Index	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	0	13.29	0.144	13.43	30	13
		1	13.17	0.282	13.45	30	
		2	13.07	0.404	13.47	30	
		3	12.96	0.509	13.47	30	
		4	12.79	0.722	13.51	30	
		5	12.58	0.882	13.46	30	
		6	12.52	0.957	13.48	30	
		7	12.46	1.041	13.50	30	
2437	6	0	15.75	0.144	15.89	30	15
		1	15.62	0.282	15.90	30	
		2	15.51	0.404	15.91	30	
		3	15.38	0.509	15.89	30	
		4	15.16	0.722	15.88	30	
		5	15.07	0.882	15.95	30	
		6	14.97	0.957	15.93	30	
		7	14.90	1.041	15.94	30	
2462	11	0	12.17	0.144	12.31	30	12
		1	12.09	0.282	12.37	30	
		2	11.85	0.404	12.25	30	
		3	11.75	0.509	12.26	30	
		4	11.64	0.722	12.36	30	
		5	11.56	0.882	12.44	30	
		6	11.50	0.957	12.46	30	
		7	11.43	1.041	12.47	30	
2467	12	0	9.96	0.144	10.10	30	10
		1	9.76	0.282	10.04	30	
		2	9.65	0.404	10.05	30	
		3	9.56	0.509	10.07	30	
		4	9.39	0.722	10.11	30	
		5	9.32	0.882	10.20	30	
		6	9.08	0.957	10.04	30	
		7	9.01	1.041	10.05	30	
2472	13	0	1.61	0.144	1.75	30	2
		1	1.63	0.282	1.91	30	
		2	1.48	0.404	1.88	30	
		3	1.41	0.509	1.92	30	
		4	0.90	0.722	1.62	30	
		5	0.89	0.882	1.77	30	
		6	0.83	0.957	1.79	30	
		7	0.74	1.041	1.78	30	

9.4 POWER SPECTRAL DENSITY

Mode	Frequency (MHz)	Channel No.	Test Result			
			Measured PSD (dBm)	Duty Cycle Factor	Measured PSD(dBm) + Duty Cycle Factor	Limit (dBm)
802.11b	2412	1	1.387	0.102	1.489	8
	2437	6	1.725	0.102	1.827	8
	2462	11	1.012	0.102	1.114	8
	2467	12	-1.085	0.102	-0.983	8
	2472	13	-4.991	0.102	-4.889	8
802.11g	2412	1	-6.347	0.709	-5.638	8
	2437	6	-3.963	0.898	-3.065	8
	2462	11	-6.387	0.984	-5.403	8
	2467	12	-9.039	0.984	-8.055	8
	2472	13	-18.244	0.388	-17.856	8
802.11n	2412	1	-6.410	0.722	-5.688	8
	2437	6	-3.558	0.882	-2.676	8
	2462	11	-7.367	1.041	-6.326	8
	2467	12	-8.414	0.882	-7.532	8
	2472	13	-17.930	0.509	-17.421	8

Note :

1. Spectrum reading values are not plot data.

The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss(20 dB) + Cable loss(1ea)


3. 20.81 dB is offset for 2.4 GHz Band.

□ Test Plots

Power Spectral Density (802.11b-CH 6)



Power Spectral Density (802.11g-CH 6)



Power Spectral Density (802.11n_HT20 -CH 6)


Note :

In order to simplify the report, attached plots were only the worst case PSD channel.


9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.

□ Test Plots(BandEdge)


Band Edge (802.11b-CH1)




Band Edge (802.11b-CH11)




Band Edge (802.11b-CH12)




Band Edge (802.11b-CH13)




Band Edge (802.11g-CH1)




Band Edge (802.11g-CH11)




Band Edge (802.11g-CH12)




Band Edge (802.11g-CH13)




Band Edge (802.11n_HT20 -CH1)




Band Edge (802.11n_HT20 -CH11)



Band Edge (802.11n_HT20 -CH12)




Band Edge (802.11n_HT20 -CH13)



■ Test Plots(Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11b Ch.6 5.5 Mbps)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11b Ch.6 5.5 Mbps)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11b Ch.6 5.5 Mbps)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




17 GHz ~ 19 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




19 GHz ~ 21 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11b_Ch.6_5.5 Mbps)



9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40\log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency 2412
 Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	47.15	4.31	V	51.46	73.98	22.52	PK
4824	42.09	4.31	V	46.40	53.98	7.58	AV
7236	44.23	12.35	V	56.58	73.98	17.40	PK
7236	36.07	12.35	V	48.42	53.98	5.56	AV
4824	49.30	4.31	H	53.61	73.98	20.37	PK
4824	44.35	4.31	H	48.66	53.98	5.32	AV
7236	44.86	12.35	H	57.21	73.98	16.77	PK
7236	36.97	12.35	H	49.32	53.98	4.66	AV

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency 2437
 Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	46.59	4.40	V	50.99	73.98	22.99	PK
4874	41.22	4.40	V	45.62	53.98	8.36	AV
7311	41.19	12.37	V	53.56	73.98	20.42	PK
7311	31.48	12.37	V	43.85	53.98	10.13	AV
4874	47.46	4.40	H	51.86	73.98	22.12	PK
4874	42.67	4.40	H	47.07	53.98	6.91	AV
7311	42.31	12.37	H	54.68	73.98	19.30	PK
7311	32.67	12.37	H	45.04	53.98	8.94	AV

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency 2462
 Channel No. 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	46.75	4.51	V	51.26	73.98	22.72	PK
4924	42.34	4.51	V	46.85	53.98	7.13	AV
7386	40.34	12.31	V	52.65	73.98	21.33	PK
7386	30.22	12.31	V	42.53	53.98	11.45	AV
4924	47.82	4.51	H	52.33	73.98	21.65	PK
4924	43.08	4.51	H	47.59	53.98	6.39	AV
7386	41.13	12.31	H	53.44	73.98	20.54	PK
7386	31.01	12.31	H	43.32	53.98	10.66	AV

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency 2467
 Channel No. 12 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4934	45.29	4.52	V	49.81	73.98	24.17	PK
4934	39.81	4.52	V	44.33	53.98	9.65	AV
7401	38.55	12.45	V	51.00	73.98	22.98	PK
7401	27.20	12.45	V	39.65	53.98	14.33	AV
4934	46.18	4.52	H	50.70	73.98	23.28	PK
4934	40.72	4.52	H	45.24	53.98	8.74	AV
7401	39.34	12.45	H	51.79	73.98	22.19	PK
7401	27.93	12.45	H	40.38	53.98	13.60	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2472
Channel No.	13 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4944	42.63	4.53	V	47.16	73.98	26.82	PK
4944	34.77	4.53	V	39.30	53.98	14.68	AV
7416	38.17	12.39	V	50.56	73.98	23.42	PK
7416	26.02	12.39	V	38.41	53.98	15.57	AV
4944	43.76	4.53	H	48.29	73.98	25.69	PK
4944	35.85	4.53	H	40.38	53.98	13.60	AV
7416	38.63	12.39	H	51.02	73.98	22.96	PK
7416	26.22	12.39	H	38.61	53.98	15.37	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	42.63	0.00	4.31	V	46.94	73.98	27.04	PK
4824	29.74	0.14	4.31	V	34.19	53.98	19.79	AV
7236	43.51	0.00	12.35	V	55.86	73.98	18.12	PK
7236	27.62	0.14	12.35	V	40.11	53.98	13.87	AV
4824	43.31	0.00	4.31	H	47.62	73.98	26.36	PK
4824	30.87	0.14	4.31	H	35.32	53.98	18.66	AV
7236	44.65	0.00	12.35	H	57.00	73.98	16.98	PK
7236	28.88	0.14	12.35	H	41.37	53.98	12.61	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	41.67	0.00	4.40	V	46.07	73.98	27.91	PK
4874	29.03	0.14	4.40	V	33.57	53.98	20.41	AV
7311	39.73	0.00	12.37	V	52.10	73.98	21.88	PK
7311	26.46	0.14	12.37	V	38.97	53.98	15.01	AV
4874	42.91	0.00	4.40	H	47.31	73.98	26.67	PK
4874	29.99	0.14	4.40	H	34.53	53.98	19.45	AV
7311	40.42	0.00	12.37	H	52.79	73.98	21.19	PK
7311	27.15	0.14	12.37	H	39.66	53.98	14.32	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4924	41.14	0.00	4.51	V	45.65	73.98	28.33	PK
4924	29.07	0.14	4.51	V	33.72	53.98	20.26	AV
7386	38.76	0.00	12.31	V	51.07	73.98	22.91	PK
7386	25.52	0.14	12.31	V	37.97	53.98	16.01	AV
4924	42.57	0.00	4.51	H	47.08	73.98	26.90	PK
4924	30.11	0.14	4.51	H	34.76	53.98	19.22	AV
7386	40.05	0.00	12.31	H	52.36	73.98	21.62	PK
7386	26.66	0.14	12.31	H	39.11	53.98	14.87	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2467
Channel No.	12 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4934	40.54	0.00	4.52	V	45.06	73.98	28.92	PK
4934	28.12	0.14	4.52	V	32.78	53.98	21.20	AV
7401	38.21	0.00	12.45	V	50.66	73.98	23.32	PK
7401	25.86	0.14	12.45	V	38.45	53.98	15.53	AV
4934	41.79	0.00	4.52	H	46.31	73.98	27.67	PK
4934	28.96	0.14	4.52	H	33.62	53.98	20.36	AV
7401	38.79	0.00	12.45	H	51.24	73.98	22.74	PK
7401	26.04	0.14	12.45	H	38.63	53.98	15.35	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2472
Channel No.	13 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4944	40.48	0.00	4.53	V	45.01	73.98	28.97	PK
4944	28.25	0.14	4.53	V	32.92	53.98	21.06	AV
7416	38.04	0.00	12.39	V	50.43	73.98	23.55	PK
7416	25.87	0.14	12.39	V	38.40	53.98	15.58	AV
4944	41.61	0.00	4.53	H	46.14	73.98	27.84	PK
4944	29.03	0.14	4.53	H	33.70	53.98	20.28	AV
7416	38.69	0.00	12.39	H	51.08	73.98	22.90	PK
7416	26.03	0.14	12.39	H	38.56	53.98	15.42	AV

Operation Mode: 802.11n (HT20)

Transfer MCS Index: 0

Operating Frequency 2412

Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	42.99	0.00	4.31	V	47.30	73.98	26.68	PK
4824	30.12	0.14	4.31	V	34.57	53.98	19.41	AV
7236	42.78	0.00	12.35	V	55.13	73.98	18.85	PK
7236	27.89	0.14	12.35	V	40.38	53.98	13.60	AV
4824	43.11	0.00	4.31	H	47.42	73.98	26.56	PK
4824	30.83	0.14	4.31	H	35.28	53.98	18.70	AV
7236	43.39	0.00	12.35	H	55.74	73.98	18.24	PK
7236	28.72	0.14	12.35	H	41.21	53.98	12.77	AV

Operation Mode: 802.11n (HT20)

Transfer MCS Index: 0

Operating Frequency 2437

Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	41.30	0.00	4.40	V	45.70	73.98	28.28	PK
4874	28.74	0.14	4.40	V	33.28	53.98	20.70	AV
7311	39.24	0.00	12.37	V	51.61	73.98	22.37	PK
7311	26.32	0.14	12.37	V	38.83	53.98	15.15	AV
4874	42.76	0.00	4.40	H	47.16	73.98	26.82	PK
4874	29.93	0.14	4.40	H	34.47	53.98	19.51	AV
7311	40.64	0.00	12.37	H	53.01	73.98	20.97	PK
7311	27.13	0.14	12.37	H	39.64	53.98	14.34	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	41.41	0.00	4.51	V	45.92	73.98	28.06	PK
4924	28.87	0.14	4.51	V	33.52	53.98	20.46	AV
7386	39.12	0.00	12.31	V	51.43	73.98	22.55	PK
7386	25.43	0.14	12.31	V	37.88	53.98	16.10	AV
4924	42.30	0.00	4.51	H	46.81	73.98	27.17	PK
4924	30.07	0.14	4.51	H	34.72	53.98	19.26	AV
7386	40.33	0.00	12.31	H	52.64	73.98	21.34	PK
7386	26.63	0.14	12.31	H	39.08	53.98	14.90	AV

Operation Mode:	802.11n (HT20)
Transfer Rate:	0
Operating Frequency	2467
Channel No.	12 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4934	40.76	0.00	4.52	V	45.28	73.98	28.70	PK
4934	28.10	0.14	4.52	V	32.76	53.98	21.22	AV
7401	38.13	0.00	12.45	V	50.58	73.98	23.40	PK
7401	25.87	0.14	12.45	V	38.46	53.98	15.52	AV
4934	41.01	0.00	4.52	H	45.53	73.98	28.45	PK
4934	28.89	0.14	4.52	H	33.55	53.98	20.43	AV
7401	38.53	0.00	12.45	H	50.98	73.98	23.00	PK
7401	26.01	0.14	12.45	H	38.60	53.98	15.38	AV

Operation Mode:	802.11n (HT20)
Transfer Rate:	0
Operating Frequency	2472
Channel No.	13 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4944	40.82	0.00	4.53	V	45.35	73.98	28.63	PK
4944	28.09	0.14	4.53	V	32.76	53.98	21.22	AV
7416	37.98	0.00	12.39	V	50.37	73.98	23.61	PK
7416	25.74	0.14	12.39	V	38.27	53.98	15.71	AV
4944	41.22	0.00	4.53	H	45.75	73.98	28.23	PK
4944	28.94	0.14	4.53	H	33.61	53.98	20.37	AV
7416	38.68	0.00	12.39	H	51.07	73.98	22.91	PK
7416	26.04	0.14	12.39	H	38.57	53.98	15.41	AV


Test Plots (Worst case : Y-H)

Radiated Spurious Emissions plot – Average Reading (802.11b_1 Mbps, Ch.1 3rd Harmonic)



Date: 10.FEB.2020 17:05:05

Radiated Spurious Emissions plot – Peak Reading (802.11b_1 Mbps, Ch.1 3rd Harmonic)



Date: 10.FEB.2020 17:06:25

Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	50.51	2.61	H	53.12	73.98	20.86	PK
2390.0	39.76	2.61	H	42.37	53.98	11.61	AV
2390.0	49.72	2.61	V	52.33	73.98	21.65	PK
2390.0	39.20	2.61	V	41.81	53.98	12.17	AV
2483.5	54.18	3.13	H	57.31	73.98	16.67	PK
2483.5	43.92	3.13	H	47.05	53.98	6.93	AV
2483.5	53.38	3.13	V	56.51	73.98	17.47	PK
2483.5	43.28	3.13	V	46.41	53.98	7.57	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2467 MHz
Channel No.	12 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	55.55	3.13	H	58.68	73.98	15.30	PK
2483.5	47.22	3.13	H	50.35	53.98	3.63	AV
2483.5	54.92	3.13	V	58.05	73.98	15.93	PK
2483.5	46.14	3.13	V	49.27	53.98	4.71	AV

Operation Mode: 802.11b
Transfer Rate: 1 Mbps
Operating Frequency 2472 MHz
Channel No. 13 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	55.20	3.13	H	58.33	73.98	15.65	PK
2483.5	47.07	3.13	H	50.20	53.98	3.78	AV
2483.5	55.11	3.13	V	58.24	73.98	15.74	PK
2483.5	46.88	3.13	V	50.01	53.98	3.97	AV

Operation Mode:	802.11g	
Transfer Rate:	6 Mbps	
Operating Frequency	2412 MHz, 2462 MHz	
Channel No.	01 Ch, 11 Ch	

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	64.23	0.00	2.61	H	66.84	73.98	7.14	PK
2390.0	45.09	0.14	2.61	H	47.84	53.98	6.14	AV
2390.0	63.54	0.00	2.61	V	66.15	73.98	7.83	PK
2390.0	44.72	0.14	2.61	V	47.47	53.98	6.51	AV
2483.5	65.88	0.00	3.13	H	69.01	73.98	4.97	PK
2483.5	46.13	0.14	3.13	H	49.40	53.98	4.58	AV
2483.5	64.81	0.00	3.13	V	67.94	73.98	6.04	PK
2483.5	45.22	0.14	3.13	V	48.49	53.98	5.49	AV

Operation Mode:	802.11g	
Transfer Rate:	6 Mbps	
Operating Frequency	2417 MHz	
Channel No.	02 Ch	

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	57.67	0.00	2.61	H	60.28	73.98	13.70	PK
2390.0	40.16	0.14	2.61	H	42.91	53.98	11.07	AV
2390.0	56.48	0.00	2.61	V	59.09	73.98	14.89	PK
2390.0	39.51	0.14	2.61	V	42.26	53.98	11.72	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2467 MHz
Channel No.	12 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	66.31	0.00	3.13	H	69.44	73.98	4.54	PK
2483.5	47.13	0.14	3.13	H	50.40	53.98	3.58	AV
2483.5	66.02	0.00	3.13	V	69.15	73.98	4.83	PK
2483.5	46.74	0.14	3.13	V	50.01	53.98	3.97	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2472 MHz
Channel No.	13 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	63.67	0.00	3.13	H	66.80	73.98	7.18	PK
2483.5	47.30	0.14	3.13	H	50.57	53.98	3.41	AV
2483.5	62.55	0.00	3.13	V	65.68	73.98	8.30	PK
2483.5	46.48	0.14	3.13	V	49.75	53.98	4.23	AV

Operation Mode:	802.11n (HT20)	
Transfer Rate:	0	
Operating Frequency	2412 MHz, 2462 MHz	
Channel No.	01 Ch, 11 Ch	

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	65.99	0.00	2.61	H	68.60	73.98	5.38	PK
2390.0	45.08	0.14	2.61	H	47.83	53.98	6.15	AV
2390.0	64.21	0.00	2.61	V	66.82	73.98	7.16	PK
2390.0	44.22	0.14	2.61	V	46.97	53.98	7.01	AV
2483.5	66.35	0.00	3.13	H	69.48	73.98	4.50	PK
2483.5	45.54	0.14	3.13	H	48.81	53.98	5.17	AV
2483.5	65.49	0.00	3.13	V	68.62	73.98	5.36	PK
2483.5	45.11	0.14	3.13	V	48.38	53.98	5.60	AV

Operation Mode:	802.11n (HT20)	
Transfer Rate:	0	
Operating Frequency	2417 MHz	
Channel No.	02 Ch	

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	59.71	0.00	2.61	H	62.32	73.98	11.66	PK
2390.0	40.84	0.14	2.61	H	43.59	53.98	10.39	AV
2390.0	58.46	0.00	2.61	V	61.07	73.98	12.91	PK
2390.0	40.18	0.14	2.61	V	42.93	53.98	11.05	AV

Operation Mode:	802.11n (HT20)		
Transfer Rate:	0		
Operating Frequency	2467 MHz		
Channel No.	12 Ch		


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	64.65	0.00	3.13	H	67.78	73.98	6.20	PK
2483.5	44.89	0.14	3.13	H	48.16	53.98	5.82	AV
2483.5	63.40	0.00	3.13	V	66.53	73.98	7.45	PK
2483.5	44.29	0.14	3.13	V	47.56	53.98	6.42	AV

Operation Mode:	802.11n (HT20)		
Transfer Rate:	0		
Operating Frequency	2472 MHz		
Channel No.	13 Ch		

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.-A.G +ATT+D.F [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	62.16	0.00	3.13	H	65.29	73.98	8.69	PK
2483.5	47.62	0.14	3.13	H	50.89	53.98	3.09	AV
2483.5	62.11	0.00	3.13	V	65.24	73.98	8.74	PK
2483.5	46.92	0.14	3.13	V	50.19	53.98	3.79	AV


Test Plots (Worst case : X-H)

Radiated Restricted Band Edges plot – Average Reading (802.11n (HT20)_ Ch.13)



Date: 12.FEB.2020 14:23:25

Radiated Restricted Band Edges plot – Peak Reading (802.11n (HT20)_ Ch.13)



Date: 12.FEB.2020 14:24:16

Note:

Plot of worst case are only reported.

9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

Test

1 / 2


HCT TEST Report

Common Information

EUT:
Manufacturer:
Test Site:
Operating Conditions:

SM-A415F/DSN
SAMSUNG
SHIELD ROOM
WLAN 2.4G_L1

FCC CLASS B_Exten Cable



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.152000	35.5	9.000	Off	L1	9.8	30.3	65.9
0.156000	45.8	9.000	Off	L1	9.8	19.8	65.7
0.162000	41.0	9.000	Off	L1	9.8	24.4	65.4
0.170000	42.3	9.000	Off	L1	9.8	22.7	65.0
0.258000	36.2	9.000	Off	L1	9.8	25.3	61.5
0.600000	35.3	9.000	Off	L1	9.8	20.7	56.0
4.204000	29.9	9.000	Off	L1	10.0	26.1	56.0
4.292000	29.9	9.000	Off	L1	10.0	26.1	56.0
4.340000	38.7	9.000	Off	L1	10.0	17.3	56.0
4.354000	36.0	9.000	Off	L1	10.0	20.0	56.0
4.384000	37.2	9.000	Off	L1	10.0	18.8	56.0
4.644000	37.3	9.000	Off	L1	10.0	18.7	56.0
13.074000	40.9	9.000	Off	L1	10.3	19.1	60.0
13.150000	40.9	9.000	Off	L1	10.3	19.1	60.0
13.190000	40.9	9.000	Off	L1	10.3	19.1	60.0
13.318000	40.7	9.000	Off	L1	10.3	19.3	60.0
13.364000	43.2	9.000	Off	L1	10.3	16.8	60.0
13.580000	42.9	9.000	Off	L1	10.3	17.1	60.0

2020-02-06

오후 1:38:35

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	18.6	9.000	Off	L1	9.8	37.3	55.9
0.156000	30.5	9.000	Off	L1	9.8	25.2	55.7
0.166000	20.6	9.000	Off	L1	9.8	34.5	55.2
0.170000	20.6	9.000	Off	L1	9.8	34.3	55.0
0.174000	19.4	9.000	Off	L1	9.8	35.4	54.8
0.258000	21.0	9.000	Off	L1	9.8	30.5	51.5
4.204000	20.2	9.000	Off	L1	10.0	25.8	46.0
4.214000	21.1	9.000	Off	L1	10.0	24.9	46.0
4.292000	20.0	9.000	Off	L1	10.0	26.0	46.0
4.338000	28.0	9.000	Off	L1	10.0	18.0	46.0
4.384000	26.6	9.000	Off	L1	10.0	19.4	46.0
4.644000	27.0	9.000	Off	L1	10.0	19.0	46.0
12.962000	34.1	9.000	Off	L1	10.3	15.9	50.0
13.098000	29.7	9.000	Off	L1	10.3	20.3	50.0
13.190000	29.8	9.000	Off	L1	10.3	20.2	50.0
13.262000	29.4	9.000	Off	L1	10.3	20.6	50.0
13.364000	29.0	9.000	Off	L1	10.3	21.0	50.0
13.580000	33.6	9.000	Off	L1	10.3	16.4	50.0

2020-02-06

오후 1:38:35

Conducted Emissions (Line 2)


Test

1 / 2

HCT TEST Report**Common Information**

EUT: SM-A415F/DSN
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: WLAN 2.4G_N

FCC CLASS B_Exten Cable

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	48.9	9.000	Off	N	9.8	17.0	65.9
0.156000	49.4	9.000	Off	N	9.8	16.3	65.7
0.228000	41.8	9.000	Off	N	9.8	20.7	62.5
0.234000	43.2	9.000	Off	N	9.8	19.1	62.3
0.240000	43.2	9.000	Off	N	9.8	18.9	62.1
0.246000	36.1	9.000	Off	N	9.8	25.8	61.9
4.676000	38.8	9.000	Off	N	10.0	17.2	56.0
4.884000	37.3	9.000	Off	N	10.0	18.7	56.0
4.948000	32.8	9.000	Off	N	10.0	23.2	56.0
4.962000	30.6	9.000	Off	N	10.0	25.4	56.0
4.968000	30.6	9.000	Off	N	10.0	25.4	56.0
4.996000	29.1	9.000	Off	N	10.0	26.9	56.0
13.462000	37.9	9.000	Off	N	10.4	22.1	60.0
13.690000	41.1	9.000	Off	N	10.4	18.9	60.0
13.750000	41.0	9.000	Off	N	10.4	19.0	60.0
13.834000	40.7	9.000	Off	N	10.4	19.3	60.0
13.982000	39.8	9.000	Off	N	10.4	20.2	60.0
14.262000	38.7	9.000	Off	N	10.4	21.3	60.0

2020-02-06

오후 1:27:56

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	31.9	9.000	Off	N	9.8	24.0	55.9
0.156000	35.0	9.000	Off	N	9.8	20.6	55.7
0.160000	34.2	9.000	Off	N	9.8	21.3	55.5
0.164000	29.1	9.000	Off	N	9.8	26.2	55.3
0.234000	27.1	9.000	Off	N	9.8	25.2	52.3
0.238000	25.8	9.000	Off	N	9.8	26.4	52.2
4.676000	28.3	9.000	Off	N	10.0	17.7	46.0
4.832000	27.7	9.000	Off	N	10.0	18.3	46.0
4.884000	26.6	9.000	Off	N	10.0	19.4	46.0
4.948000	23.4	9.000	Off	N	10.0	22.6	46.0
4.968000	23.5	9.000	Off	N	10.0	22.5	46.0
4.996000	23.9	9.000	Off	N	10.0	22.1	46.0
13.462000	27.7	9.000	Off	N	10.4	22.3	50.0
13.690000	31.5	9.000	Off	N	10.4	18.6	50.0
13.750000	31.1	9.000	Off	N	10.4	18.9	50.0
13.778000	31.0	9.000	Off	N	10.4	19.0	50.0
13.834000	30.7	9.000	Off	N	10.4	19.3	50.0
14.262000	27.5	9.000	Off	N	10.4	22.5	50.0

2020-02-06

오후 1:27:56

10. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	09/11/2019	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/18/2019	Annual	100584
ESPAC	SU-642 /Temperature Chamber	03/12/2019	Annual	0093008124
Agilent	N9020A / Signal Analyzer	05/23/2019	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	05/09/2019	Annual	MY49432108
Agilent	N1911A / Power Meter	04/10/2019	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/10/2019	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/11/2019	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	05/24/2019	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/18/2019	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/02/2019	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/16/2019	Annual	100422

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
TNM system	FBSM-01B / Amp & Filter Bank Switch Controller	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	04/26/2019	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/02/2019	Biennial	01039
Schwarzbeck	BBHA 9120D / Horn Antenna	06/28/2019	Biennial	1300
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/29/2019	Biennial	BBHA9170342
Rohde & Schwarz	FSP(9 kHz ~ 40 GHz) / Spectrum Analyzer	07/16/2019	Annual	100843
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	01/21/2020	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	02/10/2020	Annual	1
CERNEX	CBL18265035 / Power Amplifier	12/26/2019	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/18/2019	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/26/2019	Annual	3000C000276
TNM system	FBSM-05B / HPF(3~18GHz) + LNA1(1~18GHz)	01/21/2020	Annual	F6
TNM system	FBSM-05B / ATT(10dB) + LNA1(1~18GHz)	01/21/2020	Annual	None
TNM system	FBSM-05B / ATT(3dB) + LNA1(1~18GHz)	01/21/2020	Annual	None
TNM system	FBSM-05B / LNA1(1~18GHz)	01/21/2020	Annual	25540
TNM system	FBSM-05B / HPF(7~18GHz) + LNA2(6~18GHz)	01/21/2020	Annual	28550
TNM system	FBSM-05B / Thru(30MHz ~ 18GHz)	01/21/2020	Annual	None

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2003-FC003-P