



# TEST REPORT

<p><b>KCTL Inc.</b>          65, Sinwon-ro, Yeongtong-gu,          Suwon-si, Gyeonggi-do, 16677, Korea          TEL: 82-31-285-0894 FAX: 82-505-299-8311  <a href="http://www.kctl.co.kr">www.kctl.co.kr</a></p>	<p>Report No.:          KR20-SRF0113          Page (1) of (22)</p>	
<p><b>1. Client</b></p> <ul style="list-style-type: none"> <li>◦ Name : Samsung Electronics Co., Ltd.</li> <li>◦ Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea</li> <li>◦ Date of Receipt : 2020-03-26</li> </ul> <p><b>2. Use of Report</b> : Certification</p> <p><b>3. Name of Product and Model</b> : Mobile Phone / SC-41A, SCV48</p> <p><b>4. Manufacturer and Country of Origin</b> : Samsung Electronics Co., Ltd. / Vietnam</p> <p><b>5. FCC ID</b> : A3LSMA415JPN</p> <p><b>6. Date of Test</b> : 2020-03-27 to 2020-04-22</p> <p><b>7. Test Standards</b> : FCC Part 15 Subpart C, 15.225</p> <p><b>8. Test Results</b> : Refer to the test result in the test report</p>		
<p>Affirmation</p>	<p>Tested by</p> <p>Name : Kwonse Kim (Signature)</p>	<p>Technical Manager</p> <p>Name : Seungyong Kim (Signature)</p>
<p style="text-align: right;">2020-04-29</p>		
<p style="text-align: center;"><b>KCTL Inc.</b></p>		
<p>As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.</p>		

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (2) of (22)

**Report revision history**

Date	Revision	Page No
2020-04-29	Initial report	-

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.*



## CONTENTS

1.	General information .....	4
2.	Device information .....	4
2.1.	Accessory information .....	5
2.2.	Model Information .....	6
2.3.	Frequency/channel operations.....	6
3.	Antenna requirement .....	6
4.	Summary of tests .....	7
5.	Measurement uncertainty .....	8
6.	Test results .....	9
6.1.	20 dB Bandwidth & 99% Bandwidth.....	9
6.2.	Frequency tolerance .....	12
6.3.	Radiated spurious emissions .....	14
6.4.	AC Conducted emission .....	20
7.	Measurement equipment .....	22

## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (4) of (22)

# KCTL

### 1. General information

Client : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,  
Rep. of Korea  
Manufacturer : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,  
Rep. of Korea  
Factory : Samsung Electronics Vietnam Thai Nguyen Co., Ltd  
Address : YEN BINH 1 INDUSTRIAL PARK, PHO YEN DISTRICT, THAI NGUYEN  
PROVINCE THAI NGUYEN 23000  
Laboratory : KCTL Inc.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
Industry Canada Registration No. : 8035A  
KOLAS No.: KT231

### 2. Device information

Equipment under test : Mobile Phone  
Model : SC-41A, SCV48  
Difference in model name : Model SCV48 is electrically identical to model SC-41A. Two model numbers are allocated for marketing and logistic purposes only.  
Modulation technique : Bluetooth(BDR/EDR)\_GFSK,  $\pi/4$ DQPSK, 8DPSK  
Bluetooth(BLE)\_GFSK  
WIFI(802.11b/g/n20/n40/ac20/ac40/ac80)\_DSSS, OFDM  
NFC\_ASK  
LTE\_QPSK, 16QAM, 64QAM  
WCDMA\_QPSK  
GSM\_GMSK, 8-PSK  
Number of channels : Bluetooth(BDR/EDR)\_79 ch / Bluetooth(BLE)\_40 ch  
802.11b/g/n\_HT20 : 13 ch  
UNII-1: 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
UNII-2A: 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
UNII-2C: 12 ch (20 MHz), 6 ch (40 MHz), 3 ch (80 MHz)  
UNII-3: 5 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
Power source : DC 3.85 V  
Antenna specification : LTE/GSM/WCDMA\_LDS+METAL Antenna  
WIFI/Bluetooth(BDR/EDR/BLE)\_LDS+METAL Antenna  
NFC\_FPCB Antenna

Antenna gain : WIFI/Bluetooth(BDR/EDR/BLE) : -5.74 dBi  
 UNII-1 -5.41 dBi  
 UNII-2A -5.78 dBi  
 UNII-2C -6.86 dBi  
 UNII-3 -5.61 dBi

Frequency range : Bluetooth(BDR/EDR/BLE)\_2 402 MHz ~ 2 480 MHz  
 2 412 MHz ~ 2 472 MHz (802.11b/g/n\_HT20)  
 UNII-1: 5 180 MHz ~ 5 240 MHz (802.11a/n\_HT20/ac\_VHT20)  
 UNII-1: 5 190 MHz ~ 5 230 MHz (802.11n\_HT40/ac\_VHT40)  
 UNII-1: 5 210 MHz (802.11ac\_VHT80)  
 UNII-2A: 5 260 MHz ~ 5 320 MHz (802.11a/n\_HT20/ac\_VHT20)  
 UNII-2A: 5 270 MHz ~ 5 310 MHz (802.11n\_HT40/ac\_VHT40)  
 UNII-2A: 5 290 MHz (802.11ac\_VHT80)  
 UNII-2C: 5 500 MHz ~ 5 720 MHz (802.11a/n\_HT20/ac\_VHT20)  
 UNII-2C: 5 510 MHz ~ 5 710 MHz (802.11n\_HT40/ac\_VHT40)  
 UNII-2C: 5 530 MHz ~ 5 690 MHz (802.11ac\_VHT80)  
 UNII-3: 5 745 MHz ~ 5 825 MHz (802.11a/n\_HT20/ac\_VHT20)  
 UNII-3: 5 755 MHz ~ 5 795 MHz (802.11n\_HT40/ac\_VHT40)  
 UNII-3: 5 775 MHz (802.11ac\_VHT80)  
 LTE Band 5\_824.7 MHz ~ 848.3 MHz  
 LTE Band 12\_699.7 MHz ~ 715.3 MHz  
 LTE Band 41\_2 498.5 MHz ~ 2 687.5 MHz  
 GSM 850\_824.2 MHz ~ 848.8 MHz  
 GSM 1900\_1 850.2 MHz ~ 1 909.8 MHz  
 WCDMA 850\_826.4 MHz ~ 846.6 MHz

Software version : SC-41A\_A415D.001, SCV48\_A415J.001

Hardware version : REV0.1

Test device serial No. : Conducted(R38N301XM3J, R38N301XM2M)  
 Radiated(R38N301XMFK, R38N301XMBP, R38N301XMCA)

Operation temperature : -30 °C ~ 50 °C

**2.1. Accessory information**

Equipment	Manufacturer	Model	Serial No.	Power source
Earphone	Samsung Electronics Co., Ltd.	EHS61ASFBE	-	-

## 2.2. Model Information

The only difference between the SCV48 and SC-41A is:

1. H/W  
-All part is same.
2. S/W  
- Supported WCDMA, LTE FDD/TDD bands are different by Software.  
\* SC-41A  
: 3G(B1,B5,B6,B19), 4G FDD(B1,B3,B5,B12,B19,B21), 4G TDD(B38,B39,B41)  
\* SCV48  
: 3G(B1,B5), 4G FDD(B1,B3,B12,B18), 4G TDD(B41)  
  
- Other part is same.

## 2.3. Frequency/channel operations

This device contains the following capabilities:

2.4GHz WIFI(802.11b/g/n(HT20)), 5GHz WIFI(802.11a/n(HT20/HT40)/ac(VHT20/VHT40/VHT80)

Bluetooth(BDR/EDR/BLE), NFC,

LTE Band 5, LTE Band 12, LTE Band 41, GSM 850, GSM 1900, WCDMA 850

Ch.	Frequency (MHz)
01	13.56

Table 2.3.1. NFC

## 3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached FPCB Antenna (internal antenna) on board.

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (7) of (22)



#### 4. Summary of tests

FCC Part section(s)	Parameter	Test results
15.225(a)	In-band Fundamental Emission	Pass
15.225(b)	In-band Spurious Emission	Pass
15.225(c)	In-band Spurious Emission	Pass
15.225(a)	Out-of-band Spurious Emission	Pass
15.209	Frequency Stability Tolerance	Pass
15.215(c)	20 dB Bandwidth	Pass
15.207(a)	Conducted emissions	Pass

#### Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- These tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **Z** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **Z** orientation
- The test procedure(s) in this report were performed in accordance as following.
  - ANSI C63.10-2013
- Radiated(fundamental level and spurious emissions) tests were performed both without reading a passive tag condition[test mode] and with reading a passive tag condition
  - Worst case : Without passive tag

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (8) of (22)

**KCTL****5. Measurement uncertainty**


The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ( $\pm$ )	
Radiated spurious emissions	9 kHz ~ 30 MHz:	2.28 dB
	30 MHz ~ 1 000 MHz	3.66 dB
	1 GHz ~ 18 GHz	5.70 dB
Conducted emissions	9 kHz ~ 150 kHz	3.66 dB
	150 kHz ~ 30 MHz	3.26 dB

**KCTL**



**6. Test results****6.1. 20 dB Bandwidth & 99% Bandwidth****Test setup****Limit**

According to §15.215(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

**Test procedure**

ANSI C63.10 - Section 6.9.2

**KCTL**

**Test settings**

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
- b) Span: Two times and five times the OBW.
- c) RBW = 1 % to 5 % of the OBW and VBW  $\geq$  3 x RBW
- d) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Detector: peak
- g) Trace mode: max hold.
- h) Allow the trace to stabilize.
- i) Determine the “-xx dB down amplitude” using ((reference value) - xx). Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- j) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- k) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)



Report No.:  
KR20-SRF0113

Page (11) of (22)



## Test results

Frequency [MHz]	20 dB Bandwidth [MHz]		Limit [MHz]	20 dB Bandwidth [MHz]	Occupied Bandwidth (99 % BW) [MHz]
	Lowest Frequency	Highest Frequency			
13.56	Lowest Frequency	13.553	13.110	0.015	0.014
	Highest Frequency	13.568	14.010		



### Note:

Because the measured signal is CW/CW-like, adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR20-SRF0113

Page (12) of (22)

**KCTL**

## 6.2. Frequency tolerance

### Test setup



### Limit

15.225 (e) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01$  % of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### Test procedure

ANSI C63.10 - Section 6.8.1

**KCTL**


**Test results**

Voltage [%]	Voltage [V]	TEMP [°C]	Maintaining time	Measure frequency [Hz]	Frequency deviation [Hz]	Deviation [%]		
100	3.85	20(Ref.)	Startup	13 560 191	-191.0	0.001 41		
			2 minutes	13 560 204	-204.0	0.001 50		
			5 minutes	13 560 225	-225.0	0.001 66		
			10 minutes	13 560 269	-269.0	0.001 98		
		-30.00	Startup	13 560 377	-377.0	0.002 78		
			2 minutes	13 560 377	-377.0	0.002 78		
			5 minutes	13 560 377	-377.0	0.002 78		
			10 minutes	13 560 377	-377.0	0.002 78		
		-20.00	Startup	13 560 365	-365.0	0.002 69		
			2 minutes	13 560 365	-365.0	0.002 69		
			5 minutes	13 560 365	-365.0	0.002 69		
			10 minutes	13 560 366	-366.0	0.002 70		
		-10.00	Startup	13 560 366	-366.0	0.002 70		
			2 minutes	13 560 364	-364.0	0.002 68		
			5 minutes	13 560 363	-363.0	0.002 68		
			10 minutes	13 560 361	-361.0	0.002 66		
		0.00	Startup	13 560 348	-348.0	0.002 57		
			2 minutes	13 560 342	-342.0	0.002 52		
			5 minutes	13 560 340	-340.0	0.002 51		
			10 minutes	13 560 337	-337.0	0.002 49		
		10.00	Startup	13 560 321	-321.0	0.002 37		
			2 minutes	13 560 319	-319.0	0.002 35		
			5 minutes	13 560 311	-311.0	0.002 29		
			10 minutes	13 560 299	-299.0	0.002 21		
		30.00	Startup	13 560 232	-232.0	0.001 71		
			2 minutes	13 560 230	-230.0	0.001 70		
			5 minutes	13 560 227	-227.0	0.001 67		
			10 minutes	13 560 221	-221.0	0.001 63		
		40.00	Startup	13 560 202	-202.0	0.001 49		
			2 minutes	13 560 202	-202.0	0.001 49		
			5 minutes	13 560 198	-198.0	0.001 46		
			10 minutes	13 560 191	-191.0	0.001 41		
		50.00	Startup	13 560 173	-173.0	0.001 28		
			2 minutes	13 560 173	-173.0	0.001 28		
			5 minutes	13 560 175	-175.0	0.001 29		
			10 minutes	13 560 175	-175.0	0.001 29		
		85	3.27	20	Startup	13 560 189	-189.0	0.001 39
					2 minutes	13 560 189	-189.0	0.001 39
					5 minutes	13 560 189	-189.0	0.001 39
					10 minutes	13 560 189	-189.0	0.001 39
115	4.43	20	Startup	13 560 188	-188.0	0.001 39		
			2 minutes	13 560 188	-188.0	0.001 39		
			5 minutes	13 560 188	-188.0	0.001 39		
			10 minutes	13 560 188	-188.0	0.001 39		


### 6.3. Radiated spurious emissions

#### Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



#### Limit

15.225 (a) The field strength of any emission within the band 13.553-13.567 MHz shall not exceed 15, 848 microvolts/meter at 30 meters.

15.225 (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

15.225 (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz, the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

15.225 (d) The Field Strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in 15.209.

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30(29.54 dB $\mu\text{V/m}$ )	30
30.0-88.0	100(40 dB $\mu\text{V/m}$ )	3
88-216	150(43.5 dB $\mu\text{V/m}$ )	3
216-960	200 (46 dB $\mu\text{V/m}$ )	3
Above 960	500 (53.98 dB $\mu\text{V/m}$ )	3

**Test procedure**

ANSI C63.10-2013 - Section 6.4, 6.5

**Test settings**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW  $\geq 3 \times$  RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Table. RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

**Notes:**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40 \log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20 \log(D_m/D_s)$   
 Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
2. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in § 15.31(f)(2). Extrapolation Factor =  $40 \log_{10}(30/3) = 40$  dB.
3. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or  $F_d$ (dB)
4. Result = Reading + Cable loss + Amp gain + Ant. factor - Distance factor
5. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
6. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector.
7. Below 30 MHz frequency range, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported and the worse orientations of Face-on and Face-off were set for final test.
8. Face-on = Parallel, Face-off = Perpendicular

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (16) of (22)


**Test results for fundamental****15.225 (a) 13.553-13.567 MHz**

[Face-on]

Frequency	Reading	Antenna Factor	Amp. + Cable	Distance Factor	Result	Limit	Margin
(MHz)	(dB( $\mu V$ ))	(dB)	(dB)	(dB)	(dB( $\mu V/m$ ))	(dB( $\mu V/m$ ))	(dB)
<b>Quasi peak data</b>							
13.56	65.20	20.27	-31.44	40.00	14.03	84.00	69.97

[Face-off]

Frequency	Reading	Antenna Factor	Amp. + Cable	Distance Factor	Result	Limit	Margin
(MHz)	(dB( $\mu V$ ))	(dB)	(dB)	(dB)	(dB( $\mu V/m$ ))	(dB( $\mu V/m$ ))	(dB)
<b>Quasi peak data</b>							
13.56	58.10	20.27	-31.44	40.00	6.93	84.00	77.07

**Face-on/Face-off**



# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (17) of (22)



## Test results for in-band & out-band (9 kHz to 30 MHz)

### 15.225 (b,c) 13.110-14.010 MHz


[Face-on]

Frequency	Reading	Antenna Factor	Amp. + Cable	Distance Factor	Result	Limit	Margin
(MHz)	(dB( $\mu V$ ))	(dB)	(dB)	(dB)	(dB( $\mu V/m$ ))	(dB( $\mu V/m$ ))	(dB)
<b>Quasi peak data</b>							
13.20	39.70	20.26	-31.45	40.00	-11.49	40.50	51.99
13.55	51.40	20.27	-31.44	40.00	0.23	50.50	50.27
13.57	58.60	20.27	-31.44	40.00	7.43	50.50	43.07
13.75	38.20	20.27	-31.43	40.00	-12.96	29.54	42.50

[Face-off]

Frequency	Reading	Antenna Factor	Amp. + Cable	Distance Factor	Result	Limit	Margin
(MHz)	(dB( $\mu V$ ))	(dB)	(dB)	(dB)	(dB( $\mu V/m$ ))	(dB( $\mu V/m$ ))	(dB)
<b>Quasi peak data</b>							
13.27	38.30	20.27	-31.45	40.00	-12.88	40.50	53.38
13.55	44.60	20.27	-31.44	40.00	-6.57	50.50	57.07
13.57	51.00	20.27	-31.44	40.00	-0.17	50.50	50.67
13.72	38.40	20.27	-31.43	40.00	-12.76	29.54	42.30

### Face-on/Face-off



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (18) of (22)



### Test results (9 kHz to 30 MHz)


#### 15.225 (d) 0.009-30 MHz

[Face-on]

Frequency	Reading	Antenna Factor	Amp. + Cable	Distance Factor	Result	Limit	Margin
(MHz)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
<b>Quasi peak data</b>							
2.20	42.20	20.06	-31.93	40.00	-9.67	29.50	39.17
24.78	38.60	20.99	-31.06	40.00	-11.47	29.50	40.97


[Face-off]

Frequency	Reading	Antenna Factor	Amp. + Cable	Distance Factor	Result	Limit	Margin
(MHz)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
<b>Quasi peak data</b>							
7.99	40.50	20.24	-31.57	40.00	-10.83	29.50	40.33
14.64	40.40	20.29	-31.38	40.00	-10.69	29.50	40.19




**Test results (Below 1 000 MHz)****15.225 (d) 30-1000 MHz**

Frequency (MHz)	Pol. (V/H)	Reading (dB( $\mu\text{V}$ ))	Antenna Factor (dB)	Amp. + Cable (dB)	Distance Factor (dB)	Result (dB( $\mu\text{V}/\text{m}$ ))	Limit (dB( $\mu\text{V}/\text{m}$ ))	Margin (dB)
<b>Quasi peak data</b>								
33.27	H	21.70	17.37	-30.80	-	8.27	40.00	31.73
37.88	V	22.40	17.98	-30.65	-	9.73	40.00	30.27
40.67	V	22.60	18.40	-30.58	-	10.42	40.00	29.58
187.99	V	24.80	16.44	-28.35	-	12.89	43.50	30.61
189.08	V	25.10	16.31	-28.34	-	13.07	43.50	30.43
195.39	V	24.90	15.69	-28.28	-	12.31	43.50	31.19

**Horizontal/Vertical**

## 6.4. AC Conducted emission

### Test setup



### Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

### Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 $\Omega$ /50 $\mu$ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity — Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (21) of (22)




## Test results



### Final Result

--- N_A Phase ---										
No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15729	40.4	19.2	10.2	50.6	29.4	65.6	55.6	15.0	26.2
2	0.17307	40.2	20.1	10.3	50.5	30.4	64.8	54.8	14.3	24.4
3	0.23311	35.2	15.9	10.0	45.2	25.9	62.3	52.3	17.1	26.4
4	0.28174	31.8	13.4	10.0	41.8	23.4	60.8	50.8	19.0	27.4
5	0.84084	11.8	0.0	10.2	22.0	10.2	56.0	46.0	34.0	35.8
6	13.56089	42.0	38.0	10.8	52.8	48.8	60.0	50.0	7.2	1.2

--- L1_A Phase ---										
No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.15473	41.1	20.4	10.1	51.2	30.5	65.7	55.7	14.5	25.2
2	0.1997	37.5	16.9	10.2	47.7	27.1	63.6	53.6	15.9	26.5
3	0.39822	25.9	6.1	10.2	36.1	16.3	57.9	47.9	21.8	31.6
4	0.50564	24.0	6.3	10.2	34.2	16.5	56.0	46.0	21.8	29.5
5	13.55958	42.1	38.1	10.8	52.9	48.9	60.0	50.0	7.1	1.1
6	27.11914	29.8	23.6	11.5	41.3	35.1	60.0	50.0	18.7	14.9



**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR20-SRF0113

Page (22) of (22)

**KCTL****7. Measurement equipment**

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100806	20.07.30
Temp & Humid Chamber	ESPEC CORP.	SH-641	92005476	20.07.30
EMI TEST RECEIVER	R&S	ESC17	100732	20.08.22
Bi-Log Antenna	SCHWARZBECK	VULB 9168	440	20.08.17
Amplifier	SONOMA INSTRUMENT	310N	284608	20.08.22
COAXIAL FIXED ATTENUATOR	Agilent	8491B-003	2708A18758	20.05.04
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000996	21.01.22
LOOP Antenna	R&S	HFH2-Z2	100355	20.08.24
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	DT2000	79	-
TWO-LINE V - NETWORK	R&S	ENV216	101358	20.10.02
EMI TEST RECEIVER	R&S	ESCI	100001	20.08.22
Vector Signal Generator	R&S	SMBV100A	257566	20.07.16
Signal Generator	R&S	SMR40	100007	20.05.13

**End of test report**