





**802.11n HT20****2 412 MHz**


Frequency (MHz)	Pol.	Reading (dB(μV))	Ant. Factor (dB)	Amp. + Cable (dB)	DCCF (dB)	Result (dB(μV/m))	Limit (dB(μV/m))	Margin (dB)
<b>Peak data</b>								
2 389.95 <sup>1)</sup>	H	53.12	31.88	-29.04	-	55.96	74.00	18.04
4 827.66 <sup>1)</sup>	H	64.43	33.93	-53.57	-	44.79	74.00	29.21
7 228.31 <sup>1)</sup>	H	69.46	35.40	-53.00	-	51.86	74.00	22.14
<b>Average Data</b>								
2 389.95 <sup>1)</sup>	H	42.07	31.88	-29.04	0.34	45.25	54.00	8.75






**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

**2 437 MHz**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(µV))	(dB)	(dB)	(dB)	(dB(µV/m))	(dB(µV/m))	(dB)
<b>Peak data</b>								
4 872.52 <sup>1)</sup>	H	65.21	33.95	-54.42	-	44.74	74.00	29.26
7 308.79 <sup>1)</sup>	H	71.66	35.40	-52.58		54.48	74.00	19.52
<b>Average Data</b>								
7 308.79 <sup>1)</sup>	H	62.50	35.40	-52.58	0.34	45.66	54.00	8.34






**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

**2 462 MHz**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 483.54 <sup>1)</sup>	H	54.09	32.07	-29.21	-	56.95	74.00	17.05
4 925.98 <sup>1)</sup>	H	67.18	33.97	-54.79	-	46.36	74.00	27.64
7 382.19 <sup>1)</sup>	H	70.55	35.40	-52.19	-	53.76	74.00	20.24
<b>Average Data</b>								
2 483.54 <sup>1)</sup>	H	41.90	32.07	-29.21	0.34	45.10	54.00	8.90






**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

**2 467 MHz**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(µV))	(dB)	(dB)	(dB)	(dB(µV/m))	(dB(µV/m))	(dB)
<b>Peak data</b>								
2 483.54 <sup>1)</sup>	H	60.31	32.07	-29.21	-	63.17	74.00	10.83
4 936.86 <sup>1)</sup>	H	66.28	33.97	-54.72	-	45.53	74.00	28.47
7 397.30 <sup>1)</sup>	H	69.57	35.40	-52.12	-	52.85	74.00	21.15
<b>Average Data</b>								
2 483.54 <sup>1)</sup>	H	47.61	32.07	-29.21	0.34	50.81	54.00	3.19






**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

**2 472 MHz**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB( $\mu$ V))	(dB)	(dB)	(dB)	(dB( $\mu$ V/m))	(dB( $\mu$ V/m))	(dB)
<b>Peak data</b>								
2 483.50 <sup>1)</sup>	H	60.33	32.07	-29.21	-	63.19	74.00	10.81
4 943.20 <sup>1)</sup>	H	62.87	33.98	-54.69	-	42.16	74.00	31.84
7 417.72 <sup>1)</sup>	H	61.31	35.40	-52.01	-	44.70	74.00	29.30
<b>Average Data</b>								
2 483.50 <sup>1)</sup>	H	47.75	32.07	-29.21	0.34	50.95	54.00	3.05



**Horizontal/Vertical for 1 GHz ~ 3.5 GHz****Horizontal/Vertical for 3.5 GHz ~ 18 GHz****Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

## 7.5. Conducted Spurious Emission

### Test setup



### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operation, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation specified in §15.209(a) is not required. In addition, radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limit : 20 dBc

### Test procedure

ANSI C63.10 - Section 11.11.3

### Test settings

Set the spectrum analyzer as follows:

- 1) Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic.  
Typically, several plots are required to cover this entire span.
- 2) RBW = 100 kHz
- 3) VBW  $\geq$  RBW
- 4) Sweep = auto
- 5) Detector function = peak
- 6) Trace = max hold
- 7) Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
- 8) Each frequency found during preliminary measurements was re-examined and investigated.  
The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

# KCTL Inc.






65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR19-SRF0164-B

Page (63) of (71)

# KCTL

## Test results

802.11b	
<b>Conducted band-edge / 2 412 MHz</b>	<b>Conducted spurious / 2 412 MHz</b>
	
<b>Conducted band-edge / 2 437 MHz</b>	<b>Conducted spurious / 2 437 MHz</b>
Blank	
<b>Conducted band-edge / 2 462 MHz</b>	<b>Conducted spurious / 2 462 MHz</b>
	

# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR19-SRF0164-B


Page (64) of (71)

# KCTL


## Conducted band-edge / 2 467 MHz




## Conducted spurious / 2 467 MHz





## Conducted band-edge / 2 472 MHz






## Conducted spurious / 2 472 MHz



**802.11g****Conducted band-edge / 2 412 MHz****Conducted spurious / 2 412 MHz****Conducted band-edge / 2 437 MHz****Conducted spurious / 2 437 MHz**

Blank

**Conducted band-edge / 2 462 MHz****Conducted spurious / 2 462 MHz**

# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR19-SRF0164-B


Page (66) of (71)

# KCTL


## Conducted band-edge / 2 467 MHz




## Conducted spurious / 2 467 MHz





## Conducted band-edge / 2 472 MHz










## Conducted spurious / 2 472 MHz



**802.11n HT20****Conducted band-edge / 2 412 MHz****Conducted spurious / 2 412 MHz****Conducted band-edge / 2 437 MHz****Conducted spurious / 2 437 MHz**


Blank

**Conducted band-edge / 2 462 MHz****Conducted spurious / 2 462 MHz**

**Conducted band-edge / 2 467 MHz****Conducted spurious / 2 467 MHz****Conducted band-edge / 2 472 MHz****Conducted spurious / 2 472 MHz**

## 7.6. AC Conducted emission

### Test setup




### Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall be on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

### Measurement procedure

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50Ω/50μH LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

**Test results – Worst case: : 802.11n HT20/ 2 412 MHz**

## Final Result

## --- N Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c. f	Result QP [dB]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.18914	22.1	8.3	10.0	32.1	18.3	64.1	54.1	32.0	35.8
2	0.44664	15.4	5.6	9.8	25.2	15.4	56.9	46.9	31.7	31.5
3	0.62368	29.8	20.8	9.8	39.6	30.6	56.0	46.0	16.4	15.4
4	1.16234	14.2	5.4	9.7	23.9	15.1	56.0	46.0	32.1	30.9
5	4.84323	25.3	16.1	9.6	34.9	25.7	56.0	46.0	21.1	20.3
6	8.63575	28.6	19.4	9.8	38.4	29.2	60.0	50.0	21.6	20.8

## --- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c. f	Result QP [dB]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.26285	25.8	17.6	9.6	35.4	27.2	61.3	51.3	25.9	24.1
2	0.63384	33.7	23.3	9.8	43.5	33.1	56.0	46.0	12.5	12.9
3	0.69832	38.3	29.7	9.8	48.1	39.5	56.0	46.0	7.9	6.5
4	1.48364	27.2	18.5	9.7	36.9	28.2	56.0	46.0	19.1	17.8
5	4.31117	28.9	19.6	9.6	38.5	29.2	56.0	46.0	17.5	16.8
6	11.97359	31.1	21.8	9.9	41.0	31.7	60.0	50.0	19.0	18.3

## 8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSW50	101013	20.05.13
Spectrum Analyzer	R&S	FSV40	100988	20.01.04
Wideband Power Sensor	R&S	NRP-Z81	102398	20.01.25
ATTENUATOR	R&S	DNF Dämpfungsglied 10 dB in N-50 Ohm	31212	20.05.13
EMI TEST RECEIVER	R&S	ESCI7	100732	20.08.22
Bi-Log Antenna	SCHWARZBECK	VULB 9168	583	20.05.04
Amplifier	SONOMA INSTRUMENT	310N	284608	20.08.22
COAXIAL FIXED ATTENUATOR	Agilent	8491B-003	2708A18758	20.05.04
Horn antenna	ETS.lindgren	3116	00086632	20.02.15
Horn antenna	ETS.lindgren	3117	155787	20.02.15
Attenuator	API Inmet	40AH2W-10	12	20.05.15
Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	20.07.30
AMPLIFIER	L-3 Narda-MITEQ	AFS5-00101800-25-S- 5	2054571	20.02.21
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800 -22-10P	2031196	20.02.21
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33 -8P	2000997	20.08.01
LOOP Antenna	R&S	HFH2-Z2	100355	20.08.24
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	DT2000	79	-
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	DT2000	79	-
Highpass Filter	WT	WT-A1698-HS	WT160411001	20.05.14
TWO-LINE V - NETWORK	R&S	ENV216	101358	20.04.05
EMI TEST RECEIVER	R&S	ESCI	100001	20.08.22
Vector Signal Generator	R&S	SMBV100A	257566	20.01.04
Signal Generator	R&S	SMR40	100007	20.05.13
Cable Assembly	RadiAll	2301761768000PJ	1724.659	-
Cable Assembly	gigalane	RG-400	-	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-

**End of test report**