

**LTE Band 71**

BW (MHz)	Mode	RB/RB Size	f(MHz)	ERP	
				dBm	W
20	QPSK	1/0	673	17.78	0.0600
		1/0	680.5	19.43	0.0877
		1/0	688	17.68	0.0586
	16QAM	1/0	673	17.15	0.0519
		1/0	680.5	18.17	0.0656
		1/0	688	16.99	0.0500
15	QPSK	1/0	670.5	18.04	0.0637
		1/0	680.5	19.31	0.0853
		1/0	690.5	19.06	0.0805
	16QAM	1/0	670.5	17.34	0.0542
		1/0	680.5	18.12	0.0649
		1/0	690.5	17.74	0.0594
10	QPSK	1/0	668	18.26	0.0670
		1/0	680.5	19.47	0.0885
		1/0	693	18.85	0.0767
	16QAM	1/0	668	17.02	0.0504
		1/0	680.5	18.09	0.0644
		1/0	693	17.67	0.0585
5	QPSK	1/0	665.5	18.08	0.0643
		1/0	680.5	19.14	0.0820
		1/0	695.5	18.88	0.0773
	16QAM	1/0	665.5	16.87	0.0486
		1/0	680.5	17.95	0.0624
		1/0	695.5	17.67	0.0585

9.1.1. GSM

GPRS 850									EGPRS 850																																																																																																																																																																																												
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> GPRS 850 MHz Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>824.20</td><td>23.22</td><td>V</td><td>3.7</td><td>0.5</td><td>20.03</td><td>38.5</td><td>-18.5</td><td></td></tr> <tr><td>824.20</td><td>30.42</td><td>H</td><td>3.7</td><td>0.3</td><td>27.02</td><td>38.5</td><td>-11.5</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.60</td><td>22.85</td><td>V</td><td>3.7</td><td>0.5</td><td>19.63</td><td>38.5</td><td>-18.9</td><td></td></tr> <tr><td>836.60</td><td>30.45</td><td>H</td><td>3.7</td><td>0.3</td><td>27.03</td><td>38.5</td><td>-11.5</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>848.80</td><td>23.46</td><td>V</td><td>3.8</td><td>0.5</td><td>20.21</td><td>38.5</td><td>-18.3</td><td></td></tr> <tr><td>848.80</td><td>30.92</td><td>H</td><td>3.8</td><td>0.3</td><td>27.47</td><td>38.5</td><td>-11.0</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									824.20	23.22	V	3.7	0.5	20.03	38.5	-18.5		824.20	30.42	H	3.7	0.3	27.02	38.5	-11.5		Mid Ch									836.60	22.85	V	3.7	0.5	19.63	38.5	-18.9		836.60	30.45	H	3.7	0.3	27.03	38.5	-11.5		High Ch									848.80	23.46	V	3.8	0.5	20.21	38.5	-18.3		848.80	30.92	H	3.8	0.3	27.47	38.5	-11.0		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> EGPRS 850 MHz Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>824.20</td><td>18.37</td><td>V</td><td>3.7</td><td>0.5</td><td>15.18</td><td>38.5</td><td>-23.3</td><td></td></tr> <tr><td>824.20</td><td>25.72</td><td>H</td><td>3.7</td><td>0.3</td><td>22.32</td><td>38.5</td><td>-16.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.60</td><td>17.55</td><td>V</td><td>3.7</td><td>0.5</td><td>14.33</td><td>38.5</td><td>-24.2</td><td></td></tr> <tr><td>836.60</td><td>25.33</td><td>H</td><td>3.7</td><td>0.3</td><td>21.91</td><td>38.5</td><td>-16.6</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>848.80</td><td>18.40</td><td>V</td><td>3.8</td><td>0.5</td><td>15.15</td><td>38.5</td><td>-23.4</td><td></td></tr> <tr><td>848.80</td><td>25.55</td><td>H</td><td>3.8</td><td>0.3</td><td>22.10</td><td>38.5</td><td>-16.4</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									824.20	18.37	V	3.7	0.5	15.18	38.5	-23.3		824.20	25.72	H	3.7	0.3	22.32	38.5	-16.2		Mid Ch									836.60	17.55	V	3.7	0.5	14.33	38.5	-24.2		836.60	25.33	H	3.7	0.3	21.91	38.5	-16.6		High Ch									848.80	18.40	V	3.8	0.5	15.15	38.5	-23.4		848.80	25.55	H	3.8	0.3	22.10	38.5	-16.4	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
824.20	23.22	V	3.7	0.5	20.03	38.5	-18.5																																																																																																																																																																																														
824.20	30.42	H	3.7	0.3	27.02	38.5	-11.5																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
836.60	22.85	V	3.7	0.5	19.63	38.5	-18.9																																																																																																																																																																																														
836.60	30.45	H	3.7	0.3	27.03	38.5	-11.5																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
848.80	23.46	V	3.8	0.5	20.21	38.5	-18.3																																																																																																																																																																																														
848.80	30.92	H	3.8	0.3	27.47	38.5	-11.0																																																																																																																																																																																														
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
824.20	18.37	V	3.7	0.5	15.18	38.5	-23.3																																																																																																																																																																																														
824.20	25.72	H	3.7	0.3	22.32	38.5	-16.2																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
836.60	17.55	V	3.7	0.5	14.33	38.5	-24.2																																																																																																																																																																																														
836.60	25.33	H	3.7	0.3	21.91	38.5	-16.6																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
848.80	18.40	V	3.8	0.5	15.15	38.5	-23.4																																																																																																																																																																																														
848.80	25.55	H	3.8	0.3	22.10	38.5	-16.4																																																																																																																																																																																														
GPRS 1900									EGPRS 1900																																																																																																																																																																																												
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/6/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> GPRS 1900 MHz Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1850.20</td><td>26.56</td><td>V</td><td>5.6</td><td>4.5</td><td>25.43</td><td>33.0</td><td>-7.6</td><td></td></tr> <tr><td>1850.20</td><td>28.32</td><td>H</td><td>5.6</td><td>4.5</td><td>27.19</td><td>33.0</td><td>-6.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1880.00</td><td>23.53</td><td>V</td><td>5.7</td><td>4.6</td><td>22.43</td><td>33.0</td><td>-10.6</td><td></td></tr> <tr><td>1880.00</td><td>26.90</td><td>H</td><td>5.7</td><td>4.6</td><td>25.80</td><td>33.0</td><td>-7.2</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1909.80</td><td>25.00</td><td>V</td><td>5.7</td><td>4.6</td><td>23.90</td><td>33.0</td><td>-9.1</td><td></td></tr> <tr><td>1909.80</td><td>26.79</td><td>H</td><td>5.7</td><td>4.6</td><td>25.69</td><td>33.0</td><td>-7.3</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1850.20	26.56	V	5.6	4.5	25.43	33.0	-7.6		1850.20	28.32	H	5.6	4.5	27.19	33.0	-6.8		Mid Ch									1880.00	23.53	V	5.7	4.6	22.43	33.0	-10.6		1880.00	26.90	H	5.7	4.6	25.80	33.0	-7.2		High Ch									1909.80	25.00	V	5.7	4.6	23.90	33.0	-9.1		1909.80	26.79	H	5.7	4.6	25.69	33.0	-7.3		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/6/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> EGPRS 1900 MHz Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1850.20</td><td>22.47</td><td>V</td><td>5.6</td><td>4.5</td><td>21.34</td><td>33.0</td><td>-11.7</td><td></td></tr> <tr><td>1850.20</td><td>24.56</td><td>H</td><td>5.6</td><td>4.5</td><td>23.43</td><td>33.0</td><td>-9.6</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1880.00</td><td>20.22</td><td>V</td><td>5.7</td><td>4.6</td><td>19.12</td><td>33.0</td><td>-13.9</td><td></td></tr> <tr><td>1880.00</td><td>23.63</td><td>H</td><td>5.7</td><td>4.6</td><td>22.53</td><td>33.0</td><td>-10.5</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1909.80</td><td>22.04</td><td>V</td><td>5.7</td><td>4.6</td><td>20.94</td><td>33.0</td><td>-12.1</td><td></td></tr> <tr><td>1909.80</td><td>23.49</td><td>H</td><td>5.7</td><td>4.6</td><td>22.39</td><td>33.0</td><td>-10.6</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1850.20	22.47	V	5.6	4.5	21.34	33.0	-11.7		1850.20	24.56	H	5.6	4.5	23.43	33.0	-9.6		Mid Ch									1880.00	20.22	V	5.7	4.6	19.12	33.0	-13.9		1880.00	23.63	H	5.7	4.6	22.53	33.0	-10.5		High Ch									1909.80	22.04	V	5.7	4.6	20.94	33.0	-12.1		1909.80	23.49	H	5.7	4.6	22.39	33.0	-10.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
1850.20	26.56	V	5.6	4.5	25.43	33.0	-7.6																																																																																																																																																																																														
1850.20	28.32	H	5.6	4.5	27.19	33.0	-6.8																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
1880.00	23.53	V	5.7	4.6	22.43	33.0	-10.6																																																																																																																																																																																														
1880.00	26.90	H	5.7	4.6	25.80	33.0	-7.2																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
1909.80	25.00	V	5.7	4.6	23.90	33.0	-9.1																																																																																																																																																																																														
1909.80	26.79	H	5.7	4.6	25.69	33.0	-7.3																																																																																																																																																																																														
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
1850.20	22.47	V	5.6	4.5	21.34	33.0	-11.7																																																																																																																																																																																														
1850.20	24.56	H	5.6	4.5	23.43	33.0	-9.6																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
1880.00	20.22	V	5.7	4.6	19.12	33.0	-13.9																																																																																																																																																																																														
1880.00	23.63	H	5.7	4.6	22.53	33.0	-10.5																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
1909.80	22.04	V	5.7	4.6	20.94	33.0	-12.1																																																																																																																																																																																														
1909.80	23.49	H	5.7	4.6	22.39	33.0	-10.6																																																																																																																																																																																														

9.1.2. CDMA

BC10 1xRTT										BC10 EVDO																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/15/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: RTT BC10 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>817.25</td><td>13.45</td><td>V</td><td>3.7</td><td>0.5</td><td>10.30</td><td>38.5</td><td>-28.2</td><td></td><td></td></tr> <tr><td>817.25</td><td>21.38</td><td>H</td><td>3.7</td><td>0.3</td><td>18.00</td><td>38.5</td><td>-20.5</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>820.00</td><td>13.29</td><td>V</td><td>3.7</td><td>0.5</td><td>10.12</td><td>38.5</td><td>-28.4</td><td></td><td></td></tr> <tr><td>820.00</td><td>21.46</td><td>H</td><td>3.7</td><td>0.3</td><td>18.07</td><td>38.5</td><td>-20.4</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>822.75</td><td>13.64</td><td>V</td><td>3.7</td><td>0.5</td><td>10.46</td><td>38.5</td><td>-28.0</td><td></td><td></td></tr> <tr><td>822.75</td><td>21.60</td><td>H</td><td>3.7</td><td>0.3</td><td>18.21</td><td>38.5</td><td>-20.3</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										817.25	13.45	V	3.7	0.5	10.30	38.5	-28.2			817.25	21.38	H	3.7	0.3	18.00	38.5	-20.5			Mid Ch										820.00	13.29	V	3.7	0.5	10.12	38.5	-28.4			820.00	21.46	H	3.7	0.3	18.07	38.5	-20.4			High Ch										822.75	13.64	V	3.7	0.5	10.46	38.5	-28.0			822.75	21.60	H	3.7	0.3	18.21	38.5	-20.3			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/15/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: EVDO BC10 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>817.25</td><td>13.53</td><td>V</td><td>3.7</td><td>0.5</td><td>10.38</td><td>38.5</td><td>-28.1</td><td></td><td></td></tr> <tr><td>817.25</td><td>21.56</td><td>H</td><td>3.7</td><td>0.3</td><td>18.18</td><td>38.5</td><td>-20.3</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>820.00</td><td>13.66</td><td>V</td><td>3.7</td><td>0.5</td><td>10.49</td><td>38.5</td><td>-28.0</td><td></td><td></td></tr> <tr><td>820.00</td><td>21.45</td><td>H</td><td>3.7</td><td>0.3</td><td>18.06</td><td>38.5</td><td>-20.4</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>822.75</td><td>13.50</td><td>V</td><td>3.7</td><td>0.5</td><td>10.32</td><td>38.5</td><td>-28.2</td><td></td><td></td></tr> <tr><td>822.75</td><td>21.67</td><td>H</td><td>3.7</td><td>0.3</td><td>18.28</td><td>38.5</td><td>-20.2</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										817.25	13.53	V	3.7	0.5	10.38	38.5	-28.1			817.25	21.56	H	3.7	0.3	18.18	38.5	-20.3			Mid Ch										820.00	13.66	V	3.7	0.5	10.49	38.5	-28.0			820.00	21.45	H	3.7	0.3	18.06	38.5	-20.4			High Ch										822.75	13.50	V	3.7	0.5	10.32	38.5	-28.2			822.75	21.67	H	3.7	0.3	18.28	38.5	-20.2		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
817.25	13.45	V	3.7	0.5	10.30	38.5	-28.2																																																																																																																																																																																																																				
817.25	21.38	H	3.7	0.3	18.00	38.5	-20.5																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
820.00	13.29	V	3.7	0.5	10.12	38.5	-28.4																																																																																																																																																																																																																				
820.00	21.46	H	3.7	0.3	18.07	38.5	-20.4																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
822.75	13.64	V	3.7	0.5	10.46	38.5	-28.0																																																																																																																																																																																																																				
822.75	21.60	H	3.7	0.3	18.21	38.5	-20.3																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
817.25	13.53	V	3.7	0.5	10.38	38.5	-28.1																																																																																																																																																																																																																				
817.25	21.56	H	3.7	0.3	18.18	38.5	-20.3																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
820.00	13.66	V	3.7	0.5	10.49	38.5	-28.0																																																																																																																																																																																																																				
820.00	21.45	H	3.7	0.3	18.06	38.5	-20.4																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
822.75	13.50	V	3.7	0.5	10.32	38.5	-28.2																																																																																																																																																																																																																				
822.75	21.67	H	3.7	0.3	18.28	38.5	-20.2																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/13/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: RTT BC0 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>824.70</td><td>16.15</td><td>V</td><td>3.7</td><td>0.5</td><td>11.95</td><td>38.5</td><td>-26.5</td><td></td><td></td></tr> <tr><td>824.70</td><td>23.22</td><td>H</td><td>3.7</td><td>0.3</td><td>19.82</td><td>38.5</td><td>-18.7</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>836.52</td><td>14.42</td><td>V</td><td>3.7</td><td>0.5</td><td>11.20</td><td>38.5</td><td>-27.3</td><td></td><td></td></tr> <tr><td>836.52</td><td>22.32</td><td>H</td><td>3.7</td><td>0.3</td><td>19.90</td><td>38.5</td><td>-19.6</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>848.31</td><td>15.28</td><td>V</td><td>3.8</td><td>0.5</td><td>12.03</td><td>38.5</td><td>-26.5</td><td></td><td></td></tr> <tr><td>848.31</td><td>23.05</td><td>H</td><td>3.8</td><td>0.3</td><td>19.60</td><td>38.5</td><td>-18.9</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										824.70	16.15	V	3.7	0.5	11.95	38.5	-26.5			824.70	23.22	H	3.7	0.3	19.82	38.5	-18.7			Mid Ch										836.52	14.42	V	3.7	0.5	11.20	38.5	-27.3			836.52	22.32	H	3.7	0.3	19.90	38.5	-19.6			High Ch										848.31	15.28	V	3.8	0.5	12.03	38.5	-26.5			848.31	23.05	H	3.8	0.3	19.60	38.5	-18.9			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/13/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: EVDO BC0 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>824.70</td><td>16.21</td><td>V</td><td>3.7</td><td>0.5</td><td>12.01</td><td>38.5</td><td>-26.5</td><td></td><td></td></tr> <tr><td>824.70</td><td>23.40</td><td>H</td><td>3.7</td><td>0.3</td><td>20.00</td><td>38.5</td><td>-18.5</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>836.52</td><td>14.54</td><td>V</td><td>3.7</td><td>0.5</td><td>11.32</td><td>38.5</td><td>-27.2</td><td></td><td></td></tr> <tr><td>836.52</td><td>22.43</td><td>H</td><td>3.7</td><td>0.3</td><td>19.01</td><td>38.5</td><td>-19.5</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>848.31</td><td>15.39</td><td>V</td><td>3.8</td><td>0.5</td><td>12.14</td><td>38.5</td><td>-26.4</td><td></td><td></td></tr> <tr><td>848.31</td><td>23.17</td><td>H</td><td>3.8</td><td>0.3</td><td>19.72</td><td>38.5</td><td>-18.8</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										824.70	16.21	V	3.7	0.5	12.01	38.5	-26.5			824.70	23.40	H	3.7	0.3	20.00	38.5	-18.5			Mid Ch										836.52	14.54	V	3.7	0.5	11.32	38.5	-27.2			836.52	22.43	H	3.7	0.3	19.01	38.5	-19.5			High Ch										848.31	15.39	V	3.8	0.5	12.14	38.5	-26.4			848.31	23.17	H	3.8	0.3	19.72	38.5	-18.8		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
824.70	16.15	V	3.7	0.5	11.95	38.5	-26.5																																																																																																																																																																																																																				
824.70	23.22	H	3.7	0.3	19.82	38.5	-18.7																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
836.52	14.42	V	3.7	0.5	11.20	38.5	-27.3																																																																																																																																																																																																																				
836.52	22.32	H	3.7	0.3	19.90	38.5	-19.6																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
848.31	15.28	V	3.8	0.5	12.03	38.5	-26.5																																																																																																																																																																																																																				
848.31	23.05	H	3.8	0.3	19.60	38.5	-18.9																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
824.70	16.21	V	3.7	0.5	12.01	38.5	-26.5																																																																																																																																																																																																																				
824.70	23.40	H	3.7	0.3	20.00	38.5	-18.5																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
836.52	14.54	V	3.7	0.5	11.32	38.5	-27.2																																																																																																																																																																																																																				
836.52	22.43	H	3.7	0.3	19.01	38.5	-19.5																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
848.31	15.39	V	3.8	0.5	12.14	38.5	-26.4																																																																																																																																																																																																																				
848.31	23.17	H	3.8	0.3	19.72	38.5	-18.8																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/15/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: RTT BC1 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1851.25</td><td>19.88</td><td>V</td><td>5.6</td><td>4.5</td><td>18.73</td><td>33.0</td><td>-14.3</td><td></td><td></td></tr> <tr><td>1851.25</td><td>23.16</td><td>H</td><td>5.6</td><td>4.5</td><td>22.01</td><td>33.0</td><td>-11.0</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1880.00</td><td>18.53</td><td>V</td><td>5.7</td><td>4.6</td><td>17.53</td><td>33.0</td><td>-15.5</td><td></td><td></td></tr> <tr><td>1880.00</td><td>23.89</td><td>H</td><td>5.7</td><td>4.6</td><td>22.79</td><td>33.0</td><td>-10.2</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1908.75</td><td>19.14</td><td>V</td><td>5.7</td><td>4.5</td><td>18.00</td><td>33.0</td><td>-16.0</td><td></td><td></td></tr> <tr><td>1908.75</td><td>21.91</td><td>H</td><td>5.7</td><td>4.5</td><td>20.77</td><td>33.0</td><td>-12.2</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1851.25	19.88	V	5.6	4.5	18.73	33.0	-14.3			1851.25	23.16	H	5.6	4.5	22.01	33.0	-11.0			Mid Ch										1880.00	18.53	V	5.7	4.6	17.53	33.0	-15.5			1880.00	23.89	H	5.7	4.6	22.79	33.0	-10.2			High Ch										1908.75	19.14	V	5.7	4.5	18.00	33.0	-16.0			1908.75	21.91	H	5.7	4.5	20.77	33.0	-12.2			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/15/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: EVDO BC1 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1851.25</td><td>20.15</td><td>V</td><td>5.6</td><td>4.5</td><td>19.00</td><td>33.0</td><td>-14.0</td><td></td><td></td></tr> <tr><td>1851.25</td><td>23.38</td><td>H</td><td>5.6</td><td>4.5</td><td>22.23</td><td>33.0</td><td>-10.8</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1880.00</td><td>19.06</td><td>V</td><td>5.7</td><td>4.6</td><td>17.96</td><td>33.0</td><td>-15.0</td><td></td><td></td></tr> <tr><td>1880.00</td><td>23.77</td><td>H</td><td>5.7</td><td>4.6</td><td>22.67</td><td>33.0</td><td>-10.3</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1908.75</td><td>19.32</td><td>V</td><td>5.7</td><td>4.5</td><td>18.18</td><td>33.0</td><td>-14.8</td><td></td><td></td></tr> <tr><td>1908.75</td><td>22.17</td><td>H</td><td>5.7</td><td>4.5</td><td>21.03</td><td>33.0</td><td>-12.0</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1851.25	20.15	V	5.6	4.5	19.00	33.0	-14.0			1851.25	23.38	H	5.6	4.5	22.23	33.0	-10.8			Mid Ch										1880.00	19.06	V	5.7	4.6	17.96	33.0	-15.0			1880.00	23.77	H	5.7	4.6	22.67	33.0	-10.3			High Ch										1908.75	19.32	V	5.7	4.5	18.18	33.0	-14.8			1908.75	22.17	H	5.7	4.5	21.03	33.0	-12.0		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1851.25	19.88	V	5.6	4.5	18.73	33.0	-14.3																																																																																																																																																																																																																				
1851.25	23.16	H	5.6	4.5	22.01	33.0	-11.0																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1880.00	18.53	V	5.7	4.6	17.53	33.0	-15.5																																																																																																																																																																																																																				
1880.00	23.89	H	5.7	4.6	22.79	33.0	-10.2																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1908.75	19.14	V	5.7	4.5	18.00	33.0	-16.0																																																																																																																																																																																																																				
1908.75	21.91	H	5.7	4.5	20.77	33.0	-12.2																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1851.25	20.15	V	5.6	4.5	19.00	33.0	-14.0																																																																																																																																																																																																																				
1851.25	23.38	H	5.6	4.5	22.23	33.0	-10.8																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1880.00	19.06	V	5.7	4.6	17.96	33.0	-15.0																																																																																																																																																																																																																				
1880.00	23.77	H	5.7	4.6	22.67	33.0	-10.3																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1908.75	19.32	V	5.7	4.5	18.18	33.0	-14.8																																																																																																																																																																																																																				
1908.75	22.17	H	5.7	4.5	21.03	33.0	-12.0																																																																																																																																																																																																																				

9.1.3. WCDMA

B5 REL99										B5 HSDPA																																																																																																																																																																																													
<p align="center"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: Re99 Band 5 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>826.40</td><td>14.90</td><td>V</td><td>3.7</td><td>0.5</td><td>11.70</td><td>38.5</td><td>-26.8</td><td></td></tr> <tr><td>826.40</td><td>22.08</td><td>H</td><td>3.7</td><td>0.3</td><td>18.68</td><td>38.5</td><td>-19.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.60</td><td>14.36</td><td>V</td><td>3.7</td><td>0.5</td><td>11.14</td><td>38.5</td><td>-27.4</td><td></td></tr> <tr><td>836.60</td><td>22.13</td><td>H</td><td>3.7</td><td>0.3</td><td>18.71</td><td>38.5</td><td>-19.8</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>846.60</td><td>15.27</td><td>V</td><td>3.7</td><td>0.5</td><td>12.02</td><td>38.5</td><td>-26.5</td><td></td></tr> <tr><td>846.60</td><td>22.75</td><td>H</td><td>3.7</td><td>0.3</td><td>19.30</td><td>38.5</td><td>-19.2</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									826.40	14.90	V	3.7	0.5	11.70	38.5	-26.8		826.40	22.08	H	3.7	0.3	18.68	38.5	-19.8		Mid Ch									836.60	14.36	V	3.7	0.5	11.14	38.5	-27.4		836.60	22.13	H	3.7	0.3	18.71	38.5	-19.8		High Ch									846.60	15.27	V	3.7	0.5	12.02	38.5	-26.5		846.60	22.75	H	3.7	0.3	19.30	38.5	-19.2		<p align="center"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: HSDPA Band 5 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>826.40</td><td>13.28</td><td>V</td><td>3.7</td><td>0.5</td><td>10.08</td><td>38.5</td><td>-28.4</td><td></td></tr> <tr><td>826.40</td><td>20.61</td><td>H</td><td>3.7</td><td>0.3</td><td>17.21</td><td>38.5</td><td>-21.3</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.60</td><td>12.78</td><td>V</td><td>3.7</td><td>0.5</td><td>9.56</td><td>38.5</td><td>-28.9</td><td></td></tr> <tr><td>836.60</td><td>20.58</td><td>H</td><td>3.7</td><td>0.3</td><td>17.16</td><td>38.5</td><td>-21.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>846.60</td><td>13.88</td><td>V</td><td>3.7</td><td>0.5</td><td>10.63</td><td>38.5</td><td>-27.9</td><td></td></tr> <tr><td>846.60</td><td>21.38</td><td>H</td><td>3.7</td><td>0.3</td><td>17.93</td><td>38.5</td><td>-20.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									826.40	13.28	V	3.7	0.5	10.08	38.5	-28.4		826.40	20.61	H	3.7	0.3	17.21	38.5	-21.3		Mid Ch									836.60	12.78	V	3.7	0.5	9.56	38.5	-28.9		836.60	20.58	H	3.7	0.3	17.16	38.5	-21.3		High Ch									846.60	13.88	V	3.7	0.5	10.63	38.5	-27.9		846.60	21.38	H	3.7	0.3	17.93	38.5	-20.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
826.40	14.90	V	3.7	0.5	11.70	38.5	-26.8																																																																																																																																																																																																
826.40	22.08	H	3.7	0.3	18.68	38.5	-19.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.60	14.36	V	3.7	0.5	11.14	38.5	-27.4																																																																																																																																																																																																
836.60	22.13	H	3.7	0.3	18.71	38.5	-19.8																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
846.60	15.27	V	3.7	0.5	12.02	38.5	-26.5																																																																																																																																																																																																
846.60	22.75	H	3.7	0.3	19.30	38.5	-19.2																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
826.40	13.28	V	3.7	0.5	10.08	38.5	-28.4																																																																																																																																																																																																
826.40	20.61	H	3.7	0.3	17.21	38.5	-21.3																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.60	12.78	V	3.7	0.5	9.56	38.5	-28.9																																																																																																																																																																																																
836.60	20.58	H	3.7	0.3	17.16	38.5	-21.3																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
846.60	13.88	V	3.7	0.5	10.63	38.5	-27.9																																																																																																																																																																																																
846.60	21.38	H	3.7	0.3	17.93	38.5	-20.6																																																																																																																																																																																																
<p align="center"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: Re99 Band 2 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1852.40</td><td>11.54</td><td>V</td><td>5.6</td><td>4.5</td><td>10.36</td><td>33.0</td><td>-22.6</td><td></td></tr> <tr><td>1852.40</td><td>22.66</td><td>H</td><td>5.6</td><td>4.5</td><td>21.48</td><td>33.0</td><td>-11.5</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1880.00</td><td>11.76</td><td>V</td><td>5.7</td><td>4.6</td><td>10.66</td><td>33.0</td><td>-22.3</td><td></td></tr> <tr><td>1880.00</td><td>21.34</td><td>H</td><td>5.7</td><td>4.6</td><td>20.24</td><td>33.0</td><td>-12.8</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1907.60</td><td>12.12</td><td>V</td><td>5.7</td><td>4.5</td><td>10.96</td><td>33.0</td><td>-22.0</td><td></td></tr> <tr><td>1907.60</td><td>21.45</td><td>H</td><td>5.7</td><td>4.5</td><td>20.29</td><td>33.0</td><td>-12.7</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1852.40	11.54	V	5.6	4.5	10.36	33.0	-22.6		1852.40	22.66	H	5.6	4.5	21.48	33.0	-11.5		Mid Ch									1880.00	11.76	V	5.7	4.6	10.66	33.0	-22.3		1880.00	21.34	H	5.7	4.6	20.24	33.0	-12.8		High Ch									1907.60	12.12	V	5.7	4.5	10.96	33.0	-22.0		1907.60	21.45	H	5.7	4.5	20.29	33.0	-12.7		<p align="center"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: HSDPA Band 2 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1852.40</td><td>10.45</td><td>V</td><td>5.6</td><td>4.5</td><td>9.27</td><td>33.0</td><td>-23.7</td><td></td></tr> <tr><td>1852.40</td><td>21.59</td><td>H</td><td>5.6</td><td>4.5</td><td>20.41</td><td>33.0</td><td>-12.6</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1880.00</td><td>10.70</td><td>V</td><td>5.7</td><td>4.6</td><td>9.60</td><td>33.0</td><td>-23.4</td><td></td></tr> <tr><td>1880.00</td><td>20.18</td><td>H</td><td>5.7</td><td>4.6</td><td>19.08</td><td>33.0</td><td>-13.9</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1907.60</td><td>10.78</td><td>V</td><td>5.7</td><td>4.5</td><td>9.62</td><td>33.0</td><td>-23.4</td><td></td></tr> <tr><td>1907.60</td><td>20.29</td><td>H</td><td>5.7</td><td>4.5</td><td>19.13</td><td>33.0</td><td>-13.9</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1852.40	10.45	V	5.6	4.5	9.27	33.0	-23.7		1852.40	21.59	H	5.6	4.5	20.41	33.0	-12.6		Mid Ch									1880.00	10.70	V	5.7	4.6	9.60	33.0	-23.4		1880.00	20.18	H	5.7	4.6	19.08	33.0	-13.9		High Ch									1907.60	10.78	V	5.7	4.5	9.62	33.0	-23.4		1907.60	20.29	H	5.7	4.5	19.13	33.0	-13.9	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1852.40	11.54	V	5.6	4.5	10.36	33.0	-22.6																																																																																																																																																																																																
1852.40	22.66	H	5.6	4.5	21.48	33.0	-11.5																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1880.00	11.76	V	5.7	4.6	10.66	33.0	-22.3																																																																																																																																																																																																
1880.00	21.34	H	5.7	4.6	20.24	33.0	-12.8																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1907.60	12.12	V	5.7	4.5	10.96	33.0	-22.0																																																																																																																																																																																																
1907.60	21.45	H	5.7	4.5	20.29	33.0	-12.7																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1852.40	10.45	V	5.6	4.5	9.27	33.0	-23.7																																																																																																																																																																																																
1852.40	21.59	H	5.6	4.5	20.41	33.0	-12.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1880.00	10.70	V	5.7	4.6	9.60	33.0	-23.4																																																																																																																																																																																																
1880.00	20.18	H	5.7	4.6	19.08	33.0	-13.9																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1907.60	10.78	V	5.7	4.5	9.62	33.0	-23.4																																																																																																																																																																																																
1907.60	20.29	H	5.7	4.5	19.13	33.0	-13.9																																																																																																																																																																																																
<p align="center"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: Re99 Band 4 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1712.40</td><td>22.05</td><td>V</td><td>5.4</td><td>5.7</td><td>22.37</td><td>30.0</td><td>-7.8</td><td></td></tr> <tr><td>1712.40</td><td>17.44</td><td>H</td><td>5.4</td><td>5.7</td><td>17.76</td><td>30.0</td><td>-12.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1732.60</td><td>21.25</td><td>V</td><td>5.5</td><td>5.5</td><td>21.27</td><td>30.0</td><td>-8.7</td><td></td></tr> <tr><td>1732.60</td><td>17.96</td><td>H</td><td>5.5</td><td>5.5</td><td>17.88</td><td>30.0</td><td>-12.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1752.60</td><td>22.54</td><td>V</td><td>5.5</td><td>5.3</td><td>22.32</td><td>30.0</td><td>-7.7</td><td></td></tr> <tr><td>1752.60</td><td>17.75</td><td>H</td><td>5.5</td><td>5.3</td><td>17.53</td><td>30.0</td><td>-12.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1712.40	22.05	V	5.4	5.7	22.37	30.0	-7.8		1712.40	17.44	H	5.4	5.7	17.76	30.0	-12.2		Mid Ch									1732.60	21.25	V	5.5	5.5	21.27	30.0	-8.7		1732.60	17.96	H	5.5	5.5	17.88	30.0	-12.1		High Ch									1752.60	22.54	V	5.5	5.3	22.32	30.0	-7.7		1752.60	17.75	H	5.5	5.3	17.53	30.0	-12.5		<p align="center"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: HSDPA Band 4 Fundamentals</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1712.40</td><td>20.85</td><td>V</td><td>5.4</td><td>5.7</td><td>21.17</td><td>30.0</td><td>-8.8</td><td></td></tr> <tr><td>1712.40</td><td>16.27</td><td>H</td><td>5.4</td><td>5.7</td><td>16.59</td><td>30.0</td><td>-13.4</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1732.60</td><td>20.12</td><td>V</td><td>5.5</td><td>5.5</td><td>20.14</td><td>30.0</td><td>-9.9</td><td></td></tr> <tr><td>1732.60</td><td>16.65</td><td>H</td><td>5.5</td><td>5.5</td><td>16.67</td><td>30.0</td><td>-13.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1752.60</td><td>21.40</td><td>V</td><td>5.5</td><td>5.3</td><td>21.18</td><td>30.0</td><td>-8.8</td><td></td></tr> <tr><td>1752.60</td><td>16.83</td><td>H</td><td>5.5</td><td>5.3</td><td>16.41</td><td>30.0</td><td>-13.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1712.40	20.85	V	5.4	5.7	21.17	30.0	-8.8		1712.40	16.27	H	5.4	5.7	16.59	30.0	-13.4		Mid Ch									1732.60	20.12	V	5.5	5.5	20.14	30.0	-9.9		1732.60	16.65	H	5.5	5.5	16.67	30.0	-13.3		High Ch									1752.60	21.40	V	5.5	5.3	21.18	30.0	-8.8		1752.60	16.83	H	5.5	5.3	16.41	30.0	-13.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1712.40	22.05	V	5.4	5.7	22.37	30.0	-7.8																																																																																																																																																																																																
1712.40	17.44	H	5.4	5.7	17.76	30.0	-12.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1732.60	21.25	V	5.5	5.5	21.27	30.0	-8.7																																																																																																																																																																																																
1732.60	17.96	H	5.5	5.5	17.88	30.0	-12.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1752.60	22.54	V	5.5	5.3	22.32	30.0	-7.7																																																																																																																																																																																																
1752.60	17.75	H	5.5	5.3	17.53	30.0	-12.5																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1712.40	20.85	V	5.4	5.7	21.17	30.0	-8.8																																																																																																																																																																																																
1712.40	16.27	H	5.4	5.7	16.59	30.0	-13.4																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1732.60	20.12	V	5.5	5.5	20.14	30.0	-9.9																																																																																																																																																																																																
1732.60	16.65	H	5.5	5.5	16.67	30.0	-13.3																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1752.60	21.40	V	5.5	5.3	21.18	30.0	-8.8																																																																																																																																																																																																
1752.60	16.83	H	5.5	5.3	16.41	30.0	-13.6																																																																																																																																																																																																

9.1.4. LTE Band 5

10MHz QPSK										10MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_QPSK Band 5 Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_16QAM Band 5 Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
829.00	15.28	V	3.7	0.5	12.07	38.5	-26.4			829.00	14.26	V	3.7	0.5	11.05	38.5	-27.4			
829.00	22.53	H	3.7	0.3	19.12	38.5	-19.4			829.00	21.29	H	3.7	0.3	17.88	38.5	-20.6			
Mid Ch										Mid Ch										
836.50	15.07	V	3.7	0.5	11.85	38.5	-26.7			836.50	13.78	V	3.7	0.5	10.57	38.5	-27.9			
836.50	22.22	H	3.7	0.3	18.89	38.5	-19.7			836.50	21.10	H	3.7	0.3	17.68	38.5	-20.8			
High Ch										High Ch										
844.00	15.56	V	3.7	0.5	12.32	38.5	-26.2			844.00	14.51	V	3.7	0.5	11.27	38.5	-27.2			
844.00	22.88	H	3.7	0.3	19.44	38.5	-19.1			844.00	21.94	H	3.7	0.3	18.50	38.5	-20.0			
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_QPSK Band 5 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_16QAM Band 5 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
826.50	16.31	V	3.7	0.5	12.11	38.5	-26.4			826.50	14.00	V	3.7	0.5	10.80	38.5	-27.7			
826.50	22.51	H	3.7	0.3	19.11	38.5	-19.4			826.50	21.19	H	3.7	0.3	17.79	38.5	-20.7			
Mid Ch										Mid Ch										
836.50	14.91	V	3.7	0.5	11.69	38.5	-26.8			836.50	13.60	V	3.7	0.5	10.38	38.5	-28.1			
836.50	22.18	H	3.7	0.3	18.76	38.5	-19.7			836.50	21.02	H	3.7	0.3	17.60	38.5	-20.9			
High Ch										High Ch										
846.50	16.09	V	3.7	0.5	12.84	38.5	-25.7			846.50	15.02	V	3.7	0.5	11.77	38.5	-26.7			
846.50	23.54	H	3.7	0.3	20.09	38.5	-18.4			846.50	22.42	H	3.7	0.3	18.97	38.5	-19.5			
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_QPSK Band 5 Fundamentals, 3MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_16QAM Band 5 Fundamentals, 3MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
825.50	14.99	V	3.7	0.5	11.79	38.5	-26.7			825.50	13.70	V	3.7	0.5	10.50	38.5	-28.0			
825.50	22.60	H	3.7	0.3	19.20	38.5	-19.3			825.50	21.40	H	3.7	0.3	18.00	38.5	-20.5			
Mid Ch										Mid Ch										
836.50	14.36	V	3.7	0.5	11.14	38.5	-27.4			836.50	13.01	V	3.7	0.5	9.79	38.5	-28.7			
836.50	22.27	H	3.7	0.3	18.85	38.5	-19.7			836.50	20.94	H	3.7	0.3	17.52	38.5	-21.0			
High Ch										High Ch										
847.50	15.51	V	3.7	0.5	12.26	38.5	-26.2			847.50	14.62	V	3.7	0.5	11.37	38.5	-27.1			
847.50	23.16	H	3.7	0.3	19.70	38.5	-18.8			847.50	22.28	H	3.7	0.3	18.83	38.5	-19.7			
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_QPSK Band 5 Fundamentals, 1.4MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 1/2/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber I Mode: LTE_16QAM Band 5 Fundamentals, 1.4MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0184971, and Chamber I SMA Cables Substitution: Dipole T416, Chamber I Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
824.70	16.08	V	3.7	0.5	11.88	38.5	-26.6			824.70	13.89	V	3.7	0.5	10.69	38.5	-27.8			
824.70	22.27	H	3.7	0.3	18.87	38.5	-19.6			824.70	21.02	H	3.7	0.3	17.62	38.5	-20.9			
Mid Ch										Mid Ch										
836.50	14.42	V	3.7	0.5	11.20	38.5	-27.3			836.50	13.31	V	3.7	0.5	10.09	38.5	-28.4			
836.50	21.85	H	3.7	0.3	18.43	38.5	-20.1			836.50	20.63	H	3.7	0.3	17.21	38.5	-21.3			
High Ch										High Ch										
848.30	15.12	V	3.8	0.5	11.87	38.5	-26.6			848.30	13.88	V	3.8	0.5	10.63	38.5	-27.9			
848.30	22.87	H	3.8	0.3	19.42	38.5	-19.1			848.30	21.78	H	3.8	0.3	18.33	38.5	-20.2			

### 9.1.5. LTE Band 7

20MHz QPSK										20MHz 16QAM																																																																																																																																																																																													
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 7 Fundamentals, 20MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2510.00</td><td>23.00</td><td>V</td><td>6.6</td><td>5.8</td><td>22.16</td><td>33.0</td><td>-10.8</td><td></td></tr> <tr><td>2510.00</td><td>24.77</td><td>H</td><td>6.6</td><td>5.8</td><td>23.93</td><td>33.0</td><td>-9.1</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>22.44</td><td>V</td><td>6.7</td><td>5.8</td><td>21.54</td><td>33.0</td><td>-11.5</td><td></td></tr> <tr><td>2535.00</td><td>24.13</td><td>H</td><td>6.7</td><td>5.8</td><td>23.23</td><td>33.0</td><td>-9.8</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2560.00</td><td>21.09</td><td>V</td><td>6.8</td><td>5.9</td><td>20.16</td><td>33.0</td><td>-12.8</td><td></td></tr> <tr><td>2560.00</td><td>23.02</td><td>H</td><td>6.8</td><td>5.9</td><td>22.09</td><td>33.0</td><td>-10.9</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2510.00	23.00	V	6.6	5.8	22.16	33.0	-10.8		2510.00	24.77	H	6.6	5.8	23.93	33.0	-9.1		Mid Ch									2535.00	22.44	V	6.7	5.8	21.54	33.0	-11.5		2535.00	24.13	H	6.7	5.8	23.23	33.0	-9.8		High Ch									2560.00	21.09	V	6.8	5.9	20.16	33.0	-12.8		2560.00	23.02	H	6.8	5.9	22.09	33.0	-10.9		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 7 Fundamentals, 20MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2510.00</td><td>21.91</td><td>V</td><td>6.6</td><td>5.8</td><td>21.07</td><td>33.0</td><td>-11.9</td><td></td></tr> <tr><td>2510.00</td><td>23.64</td><td>H</td><td>6.6</td><td>5.8</td><td>22.80</td><td>33.0</td><td>-10.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>21.23</td><td>V</td><td>6.7</td><td>5.8</td><td>20.33</td><td>33.0</td><td>-12.7</td><td></td></tr> <tr><td>2535.00</td><td>22.95</td><td>H</td><td>6.7</td><td>5.8</td><td>22.05</td><td>33.0</td><td>-10.9</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2560.00</td><td>19.89</td><td>V</td><td>6.8</td><td>5.9</td><td>18.96</td><td>33.0</td><td>-14.0</td><td></td></tr> <tr><td>2560.00</td><td>21.82</td><td>H</td><td>6.8</td><td>5.9</td><td>20.89</td><td>33.0</td><td>-12.1</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2510.00	21.91	V	6.6	5.8	21.07	33.0	-11.9		2510.00	23.64	H	6.6	5.8	22.80	33.0	-10.2		Mid Ch									2535.00	21.23	V	6.7	5.8	20.33	33.0	-12.7		2535.00	22.95	H	6.7	5.8	22.05	33.0	-10.9		High Ch									2560.00	19.89	V	6.8	5.9	18.96	33.0	-14.0		2560.00	21.82	H	6.8	5.9	20.89	33.0	-12.1	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2510.00	23.00	V	6.6	5.8	22.16	33.0	-10.8																																																																																																																																																																																																
2510.00	24.77	H	6.6	5.8	23.93	33.0	-9.1																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	22.44	V	6.7	5.8	21.54	33.0	-11.5																																																																																																																																																																																																
2535.00	24.13	H	6.7	5.8	23.23	33.0	-9.8																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2560.00	21.09	V	6.8	5.9	20.16	33.0	-12.8																																																																																																																																																																																																
2560.00	23.02	H	6.8	5.9	22.09	33.0	-10.9																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2510.00	21.91	V	6.6	5.8	21.07	33.0	-11.9																																																																																																																																																																																																
2510.00	23.64	H	6.6	5.8	22.80	33.0	-10.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	21.23	V	6.7	5.8	20.33	33.0	-12.7																																																																																																																																																																																																
2535.00	22.95	H	6.7	5.8	22.05	33.0	-10.9																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2560.00	19.89	V	6.8	5.9	18.96	33.0	-14.0																																																																																																																																																																																																
2560.00	21.82	H	6.8	5.9	20.89	33.0	-12.1																																																																																																																																																																																																
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 7 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2507.50</td><td>22.67</td><td>V</td><td>6.6</td><td>5.7</td><td>21.82</td><td>33.0</td><td>-11.2</td><td></td></tr> <tr><td>2507.50</td><td>24.70</td><td>H</td><td>6.6</td><td>5.7</td><td>23.85</td><td>33.0</td><td>-9.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>22.24</td><td>V</td><td>6.7</td><td>5.8</td><td>21.34</td><td>33.0</td><td>-11.7</td><td></td></tr> <tr><td>2535.00</td><td>23.96</td><td>H</td><td>6.7</td><td>5.8</td><td>23.06</td><td>33.0</td><td>-9.9</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2562.50</td><td>20.34</td><td>V</td><td>6.8</td><td>5.9</td><td>19.41</td><td>33.0</td><td>-13.6</td><td></td></tr> <tr><td>2562.50</td><td>22.93</td><td>H</td><td>6.8</td><td>5.9</td><td>22.00</td><td>33.0</td><td>-11.0</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2507.50	22.67	V	6.6	5.7	21.82	33.0	-11.2		2507.50	24.70	H	6.6	5.7	23.85	33.0	-9.2		Mid Ch									2535.00	22.24	V	6.7	5.8	21.34	33.0	-11.7		2535.00	23.96	H	6.7	5.8	23.06	33.0	-9.9		High Ch									2562.50	20.34	V	6.8	5.9	19.41	33.0	-13.6		2562.50	22.93	H	6.8	5.9	22.00	33.0	-11.0		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 7 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2507.50</td><td>21.89</td><td>V</td><td>6.6</td><td>5.7</td><td>20.84</td><td>33.0</td><td>-12.2</td><td></td></tr> <tr><td>2507.50</td><td>23.74</td><td>H</td><td>6.6</td><td>5.7</td><td>22.89</td><td>33.0</td><td>-10.1</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>21.16</td><td>V</td><td>6.7</td><td>5.8</td><td>20.26</td><td>33.0</td><td>-12.7</td><td></td></tr> <tr><td>2535.00</td><td>22.82</td><td>H</td><td>6.7</td><td>5.8</td><td>21.92</td><td>33.0</td><td>-11.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2562.50</td><td>19.35</td><td>V</td><td>6.8</td><td>5.9</td><td>18.42</td><td>33.0</td><td>-14.6</td><td></td></tr> <tr><td>2562.50</td><td>21.91</td><td>H</td><td>6.8</td><td>5.9</td><td>20.98</td><td>33.0</td><td>-12.0</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2507.50	21.89	V	6.6	5.7	20.84	33.0	-12.2		2507.50	23.74	H	6.6	5.7	22.89	33.0	-10.1		Mid Ch									2535.00	21.16	V	6.7	5.8	20.26	33.0	-12.7		2535.00	22.82	H	6.7	5.8	21.92	33.0	-11.1		High Ch									2562.50	19.35	V	6.8	5.9	18.42	33.0	-14.6		2562.50	21.91	H	6.8	5.9	20.98	33.0	-12.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2507.50	22.67	V	6.6	5.7	21.82	33.0	-11.2																																																																																																																																																																																																
2507.50	24.70	H	6.6	5.7	23.85	33.0	-9.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	22.24	V	6.7	5.8	21.34	33.0	-11.7																																																																																																																																																																																																
2535.00	23.96	H	6.7	5.8	23.06	33.0	-9.9																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2562.50	20.34	V	6.8	5.9	19.41	33.0	-13.6																																																																																																																																																																																																
2562.50	22.93	H	6.8	5.9	22.00	33.0	-11.0																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2507.50	21.89	V	6.6	5.7	20.84	33.0	-12.2																																																																																																																																																																																																
2507.50	23.74	H	6.6	5.7	22.89	33.0	-10.1																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	21.16	V	6.7	5.8	20.26	33.0	-12.7																																																																																																																																																																																																
2535.00	22.82	H	6.7	5.8	21.92	33.0	-11.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2562.50	19.35	V	6.8	5.9	18.42	33.0	-14.6																																																																																																																																																																																																
2562.50	21.91	H	6.8	5.9	20.98	33.0	-12.0																																																																																																																																																																																																
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 7 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2505.00</td><td>22.52</td><td>V</td><td>6.6</td><td>5.7</td><td>21.66</td><td>33.0</td><td>-11.3</td><td></td></tr> <tr><td>2505.00</td><td>24.13</td><td>H</td><td>6.6</td><td>5.7</td><td>23.27</td><td>33.0</td><td>-9.7</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>22.08</td><td>V</td><td>6.7</td><td>5.8</td><td>21.18</td><td>33.0</td><td>-11.8</td><td></td></tr> <tr><td>2535.00</td><td>23.91</td><td>H</td><td>6.7</td><td>5.8</td><td>23.01</td><td>33.0</td><td>-10.0</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2565.00</td><td>20.44</td><td>V</td><td>6.8</td><td>5.9</td><td>19.54</td><td>33.0</td><td>-13.5</td><td></td></tr> <tr><td>2565.00</td><td>22.49</td><td>H</td><td>6.8</td><td>5.9</td><td>21.59</td><td>33.0</td><td>-11.4</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2505.00	22.52	V	6.6	5.7	21.66	33.0	-11.3		2505.00	24.13	H	6.6	5.7	23.27	33.0	-9.7		Mid Ch									2535.00	22.08	V	6.7	5.8	21.18	33.0	-11.8		2535.00	23.91	H	6.7	5.8	23.01	33.0	-10.0		High Ch									2565.00	20.44	V	6.8	5.9	19.54	33.0	-13.5		2565.00	22.49	H	6.8	5.9	21.59	33.0	-11.4		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 7 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2505.00</td><td>21.47</td><td>V</td><td>6.6</td><td>5.7</td><td>20.61</td><td>33.0</td><td>-12.4</td><td></td></tr> <tr><td>2505.00</td><td>23.10</td><td>H</td><td>6.6</td><td>5.7</td><td>22.24</td><td>33.0</td><td>-10.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>21.03</td><td>V</td><td>6.7</td><td>5.8</td><td>20.13</td><td>33.0</td><td>-12.9</td><td></td></tr> <tr><td>2535.00</td><td>22.84</td><td>H</td><td>6.7</td><td>5.8</td><td>21.94</td><td>33.0</td><td>-11.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2565.00</td><td>19.38</td><td>V</td><td>6.8</td><td>5.9</td><td>18.48</td><td>33.0</td><td>-14.5</td><td></td></tr> <tr><td>2565.00</td><td>21.42</td><td>H</td><td>6.8</td><td>5.9</td><td>20.52</td><td>33.0</td><td>-12.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2505.00	21.47	V	6.6	5.7	20.61	33.0	-12.4		2505.00	23.10	H	6.6	5.7	22.24	33.0	-10.8		Mid Ch									2535.00	21.03	V	6.7	5.8	20.13	33.0	-12.9		2535.00	22.84	H	6.7	5.8	21.94	33.0	-11.1		High Ch									2565.00	19.38	V	6.8	5.9	18.48	33.0	-14.5		2565.00	21.42	H	6.8	5.9	20.52	33.0	-12.5	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2505.00	22.52	V	6.6	5.7	21.66	33.0	-11.3																																																																																																																																																																																																
2505.00	24.13	H	6.6	5.7	23.27	33.0	-9.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	22.08	V	6.7	5.8	21.18	33.0	-11.8																																																																																																																																																																																																
2535.00	23.91	H	6.7	5.8	23.01	33.0	-10.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2565.00	20.44	V	6.8	5.9	19.54	33.0	-13.5																																																																																																																																																																																																
2565.00	22.49	H	6.8	5.9	21.59	33.0	-11.4																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2505.00	21.47	V	6.6	5.7	20.61	33.0	-12.4																																																																																																																																																																																																
2505.00	23.10	H	6.6	5.7	22.24	33.0	-10.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	21.03	V	6.7	5.8	20.13	33.0	-12.9																																																																																																																																																																																																
2535.00	22.84	H	6.7	5.8	21.94	33.0	-11.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2565.00	19.38	V	6.8	5.9	18.48	33.0	-14.5																																																																																																																																																																																																
2565.00	21.42	H	6.8	5.9	20.52	33.0	-12.5																																																																																																																																																																																																
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 7 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2502.50</td><td>22.18</td><td>V</td><td>6.6</td><td>5.7</td><td>21.32</td><td>33.0</td><td>-11.7</td><td></td></tr> <tr><td>2502.50</td><td>23.86</td><td>H</td><td>6.6</td><td>5.7</td><td>23.00</td><td>33.0</td><td>-10.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>21.99</td><td>V</td><td>6.7</td><td>5.8</td><td>21.09</td><td>33.0</td><td>-11.9</td><td></td></tr> <tr><td>2535.00</td><td>23.77</td><td>H</td><td>6.7</td><td>5.8</td><td>22.87</td><td>33.0</td><td>-10.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2567.50</td><td>20.49</td><td>V</td><td>6.8</td><td>5.9</td><td>19.57</td><td>33.0</td><td>-13.4</td><td></td></tr> <tr><td>2567.50</td><td>22.16</td><td>H</td><td>6.8</td><td>5.9</td><td>21.24</td><td>33.0</td><td>-11.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2502.50	22.18	V	6.6	5.7	21.32	33.0	-11.7		2502.50	23.86	H	6.6	5.7	23.00	33.0	-10.0		Mid Ch									2535.00	21.99	V	6.7	5.8	21.09	33.0	-11.9		2535.00	23.77	H	6.7	5.8	22.87	33.0	-10.1		High Ch									2567.50	20.49	V	6.8	5.9	19.57	33.0	-13.4		2567.50	22.16	H	6.8	5.9	21.24	33.0	-11.8		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/14/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 7 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2502.50</td><td>21.08</td><td>V</td><td>6.6</td><td>5.7</td><td>20.22</td><td>33.0</td><td>-12.8</td><td></td></tr> <tr><td>2502.50</td><td>22.71</td><td>H</td><td>6.6</td><td>5.7</td><td>21.85</td><td>33.0</td><td>-11.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2535.00</td><td>20.88</td><td>V</td><td>6.7</td><td>5.8</td><td>19.98</td><td>33.0</td><td>-13.0</td><td></td></tr> <tr><td>2535.00</td><td>22.64</td><td>H</td><td>6.7</td><td>5.8</td><td>21.74</td><td>33.0</td><td>-11.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2567.50</td><td>19.43</td><td>V</td><td>6.8</td><td>5.9</td><td>18.51</td><td>33.0</td><td>-14.5</td><td></td></tr> <tr><td>2567.50</td><td>21.07</td><td>H</td><td>6.8</td><td>5.9</td><td>20.15</td><td>33.0</td><td>-12.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2502.50	21.08	V	6.6	5.7	20.22	33.0	-12.8		2502.50	22.71	H	6.6	5.7	21.85	33.0	-11.2		Mid Ch									2535.00	20.88	V	6.7	5.8	19.98	33.0	-13.0		2535.00	22.64	H	6.7	5.8	21.74	33.0	-11.3		High Ch									2567.50	19.43	V	6.8	5.9	18.51	33.0	-14.5		2567.50	21.07	H	6.8	5.9	20.15	33.0	-12.8	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2502.50	22.18	V	6.6	5.7	21.32	33.0	-11.7																																																																																																																																																																																																
2502.50	23.86	H	6.6	5.7	23.00	33.0	-10.0																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	21.99	V	6.7	5.8	21.09	33.0	-11.9																																																																																																																																																																																																
2535.00	23.77	H	6.7	5.8	22.87	33.0	-10.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2567.50	20.49	V	6.8	5.9	19.57	33.0	-13.4																																																																																																																																																																																																
2567.50	22.16	H	6.8	5.9	21.24	33.0	-11.8																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2502.50	21.08	V	6.6	5.7	20.22	33.0	-12.8																																																																																																																																																																																																
2502.50	22.71	H	6.6	5.7	21.85	33.0	-11.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2535.00	20.88	V	6.7	5.8	19.98	33.0	-13.0																																																																																																																																																																																																
2535.00	22.64	H	6.7	5.8	21.74	33.0	-11.3																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2567.50	19.43	V	6.8	5.9	18.51	33.0	-14.5																																																																																																																																																																																																
2567.50	21.07	H	6.8	5.9	20.15	33.0	-12.8																																																																																																																																																																																																

9.1.6. LTE Band 12

10MHz QPSK										10MHz 16QAM																																																																																																																																																																																													
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_QPSK Band 12 Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>704.00</td><td>13.94</td><td>V</td><td>3.7</td><td>1.3</td><td>11.48</td><td>34.8</td><td>-23.3</td><td></td></tr> <tr><td>704.00</td><td>21.47</td><td>H</td><td>3.7</td><td>1.4</td><td>19.09</td><td>34.8</td><td>-15.7</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>13.63</td><td>V</td><td>3.7</td><td>1.2</td><td>11.13</td><td>34.8</td><td>-23.7</td><td></td></tr> <tr><td>707.50</td><td>21.38</td><td>H</td><td>3.7</td><td>1.3</td><td>18.95</td><td>34.8</td><td>-15.9</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>711.00</td><td>13.08</td><td>V</td><td>3.8</td><td>1.2</td><td>10.54</td><td>34.8</td><td>-24.3</td><td></td></tr> <tr><td>711.00</td><td>21.44</td><td>H</td><td>3.8</td><td>1.3</td><td>18.96</td><td>34.8</td><td>-15.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									704.00	13.94	V	3.7	1.3	11.48	34.8	-23.3		704.00	21.47	H	3.7	1.4	19.09	34.8	-15.7		Mid Ch									707.50	13.63	V	3.7	1.2	11.13	34.8	-23.7		707.50	21.38	H	3.7	1.3	18.95	34.8	-15.9		High Ch									711.00	13.08	V	3.8	1.2	10.54	34.8	-24.3		711.00	21.44	H	3.8	1.3	18.96	34.8	-15.8		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_16QAM Band 12 Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>704.00</td><td>12.94</td><td>V</td><td>3.7</td><td>1.3</td><td>10.48</td><td>34.8</td><td>-24.3</td><td></td></tr> <tr><td>704.00</td><td>20.50</td><td>H</td><td>3.7</td><td>1.4</td><td>18.12</td><td>34.8</td><td>-16.7</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>12.29</td><td>V</td><td>3.7</td><td>1.2</td><td>9.79</td><td>34.8</td><td>-25.0</td><td></td></tr> <tr><td>707.50</td><td>20.06</td><td>H</td><td>3.7</td><td>1.3</td><td>17.63</td><td>34.8</td><td>-17.2</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>711.00</td><td>11.96</td><td>V</td><td>3.8</td><td>1.2</td><td>9.42</td><td>34.8</td><td>-25.4</td><td></td></tr> <tr><td>711.00</td><td>20.30</td><td>H</td><td>3.8</td><td>1.3</td><td>17.82</td><td>34.8</td><td>-17.0</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									704.00	12.94	V	3.7	1.3	10.48	34.8	-24.3		704.00	20.50	H	3.7	1.4	18.12	34.8	-16.7		Mid Ch									707.50	12.29	V	3.7	1.2	9.79	34.8	-25.0		707.50	20.06	H	3.7	1.3	17.63	34.8	-17.2		High Ch									711.00	11.96	V	3.8	1.2	9.42	34.8	-25.4		711.00	20.30	H	3.8	1.3	17.82	34.8	-17.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
704.00	13.94	V	3.7	1.3	11.48	34.8	-23.3																																																																																																																																																																																																
704.00	21.47	H	3.7	1.4	19.09	34.8	-15.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	13.63	V	3.7	1.2	11.13	34.8	-23.7																																																																																																																																																																																																
707.50	21.38	H	3.7	1.3	18.95	34.8	-15.9																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
711.00	13.08	V	3.8	1.2	10.54	34.8	-24.3																																																																																																																																																																																																
711.00	21.44	H	3.8	1.3	18.96	34.8	-15.8																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
704.00	12.94	V	3.7	1.3	10.48	34.8	-24.3																																																																																																																																																																																																
704.00	20.50	H	3.7	1.4	18.12	34.8	-16.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	12.29	V	3.7	1.2	9.79	34.8	-25.0																																																																																																																																																																																																
707.50	20.06	H	3.7	1.3	17.63	34.8	-17.2																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
711.00	11.96	V	3.8	1.2	9.42	34.8	-25.4																																																																																																																																																																																																
711.00	20.30	H	3.8	1.3	17.82	34.8	-17.0																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_QPSK Band 12 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>701.50</td><td>13.90</td><td>V</td><td>3.7</td><td>1.3</td><td>11.46</td><td>34.8</td><td>-23.3</td><td></td></tr> <tr><td>701.50</td><td>21.41</td><td>H</td><td>3.7</td><td>1.4</td><td>19.07</td><td>34.8</td><td>-15.7</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>13.35</td><td>V</td><td>3.7</td><td>1.2</td><td>10.85</td><td>34.8</td><td>-24.0</td><td></td></tr> <tr><td>707.50</td><td>21.19</td><td>H</td><td>3.7</td><td>1.3</td><td>18.76</td><td>34.8</td><td>-16.0</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>713.50</td><td>13.02</td><td>V</td><td>3.8</td><td>1.2</td><td>10.45</td><td>34.8</td><td>-24.3</td><td></td></tr> <tr><td>713.50</td><td>21.61</td><td>H</td><td>3.8</td><td>1.2</td><td>19.09</td><td>34.8</td><td>-15.7</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									701.50	13.90	V	3.7	1.3	11.46	34.8	-23.3		701.50	21.41	H	3.7	1.4	19.07	34.8	-15.7		Mid Ch									707.50	13.35	V	3.7	1.2	10.85	34.8	-24.0		707.50	21.19	H	3.7	1.3	18.76	34.8	-16.0		High Ch									713.50	13.02	V	3.8	1.2	10.45	34.8	-24.3		713.50	21.61	H	3.8	1.2	19.09	34.8	-15.7		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_16QAM Band 12 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>701.50</td><td>12.68</td><td>V</td><td>3.7</td><td>1.3</td><td>10.24</td><td>34.8</td><td>-24.6</td><td></td></tr> <tr><td>701.50</td><td>20.15</td><td>H</td><td>3.7</td><td>1.4</td><td>17.81</td><td>34.8</td><td>-17.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>12.04</td><td>V</td><td>3.7</td><td>1.2</td><td>9.54</td><td>34.8</td><td>-25.3</td><td></td></tr> <tr><td>707.50</td><td>18.89</td><td>H</td><td>3.7</td><td>1.3</td><td>17.46</td><td>34.8</td><td>-17.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>713.50</td><td>11.86</td><td>V</td><td>3.8</td><td>1.2</td><td>9.29</td><td>34.8</td><td>-25.5</td><td></td></tr> <tr><td>713.50</td><td>20.37</td><td>H</td><td>3.8</td><td>1.2</td><td>17.85</td><td>34.8</td><td>-17.0</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									701.50	12.68	V	3.7	1.3	10.24	34.8	-24.6		701.50	20.15	H	3.7	1.4	17.81	34.8	-17.0		Mid Ch									707.50	12.04	V	3.7	1.2	9.54	34.8	-25.3		707.50	18.89	H	3.7	1.3	17.46	34.8	-17.3		High Ch									713.50	11.86	V	3.8	1.2	9.29	34.8	-25.5		713.50	20.37	H	3.8	1.2	17.85	34.8	-17.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
701.50	13.90	V	3.7	1.3	11.46	34.8	-23.3																																																																																																																																																																																																
701.50	21.41	H	3.7	1.4	19.07	34.8	-15.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	13.35	V	3.7	1.2	10.85	34.8	-24.0																																																																																																																																																																																																
707.50	21.19	H	3.7	1.3	18.76	34.8	-16.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
713.50	13.02	V	3.8	1.2	10.45	34.8	-24.3																																																																																																																																																																																																
713.50	21.61	H	3.8	1.2	19.09	34.8	-15.7																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
701.50	12.68	V	3.7	1.3	10.24	34.8	-24.6																																																																																																																																																																																																
701.50	20.15	H	3.7	1.4	17.81	34.8	-17.0																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	12.04	V	3.7	1.2	9.54	34.8	-25.3																																																																																																																																																																																																
707.50	18.89	H	3.7	1.3	17.46	34.8	-17.3																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
713.50	11.86	V	3.8	1.2	9.29	34.8	-25.5																																																																																																																																																																																																
713.50	20.37	H	3.8	1.2	17.85	34.8	-17.0																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_QPSK Band 12 Fundamentals, 3MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>700.50</td><td>13.70</td><td>V</td><td>3.7</td><td>1.3</td><td>11.27</td><td>34.8</td><td>-23.5</td><td></td></tr> <tr><td>700.50</td><td>21.33</td><td>H</td><td>3.7</td><td>1.4</td><td>19.00</td><td>34.8</td><td>-15.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>13.23</td><td>V</td><td>3.7</td><td>1.2</td><td>10.73</td><td>34.8</td><td>-24.1</td><td></td></tr> <tr><td>707.50</td><td>20.85</td><td>H</td><td>3.7</td><td>1.3</td><td>18.42</td><td>34.8</td><td>-16.4</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>714.50</td><td>13.38</td><td>V</td><td>3.8</td><td>1.2</td><td>10.80</td><td>34.8</td><td>-24.0</td><td></td></tr> <tr><td>714.50</td><td>21.23</td><td>H</td><td>3.8</td><td>1.2</td><td>18.89</td><td>34.8</td><td>-16.1</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									700.50	13.70	V	3.7	1.3	11.27	34.8	-23.5		700.50	21.33	H	3.7	1.4	19.00	34.8	-15.8		Mid Ch									707.50	13.23	V	3.7	1.2	10.73	34.8	-24.1		707.50	20.85	H	3.7	1.3	18.42	34.8	-16.4		High Ch									714.50	13.38	V	3.8	1.2	10.80	34.8	-24.0		714.50	21.23	H	3.8	1.2	18.89	34.8	-16.1		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_16QAM Band 12 Fundamentals, 3MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>700.50</td><td>12.66</td><td>V</td><td>3.7</td><td>1.3</td><td>10.23</td><td>34.8</td><td>-24.6</td><td></td></tr> <tr><td>700.50</td><td>20.28</td><td>H</td><td>3.7</td><td>1.4</td><td>17.95</td><td>34.8</td><td>-16.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>12.08</td><td>V</td><td>3.7</td><td>1.2</td><td>9.58</td><td>34.8</td><td>-25.2</td><td></td></tr> <tr><td>707.50</td><td>19.83</td><td>H</td><td>3.7</td><td>1.3</td><td>17.20</td><td>34.8</td><td>-17.6</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>714.50</td><td>12.11</td><td>V</td><td>3.8</td><td>1.2</td><td>9.53</td><td>34.8</td><td>-25.3</td><td></td></tr> <tr><td>714.50</td><td>19.98</td><td>H</td><td>3.8</td><td>1.2</td><td>17.44</td><td>34.8</td><td>-17.4</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									700.50	12.66	V	3.7	1.3	10.23	34.8	-24.6		700.50	20.28	H	3.7	1.4	17.95	34.8	-16.8		Mid Ch									707.50	12.08	V	3.7	1.2	9.58	34.8	-25.2		707.50	19.83	H	3.7	1.3	17.20	34.8	-17.6		High Ch									714.50	12.11	V	3.8	1.2	9.53	34.8	-25.3		714.50	19.98	H	3.8	1.2	17.44	34.8	-17.4	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
700.50	13.70	V	3.7	1.3	11.27	34.8	-23.5																																																																																																																																																																																																
700.50	21.33	H	3.7	1.4	19.00	34.8	-15.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	13.23	V	3.7	1.2	10.73	34.8	-24.1																																																																																																																																																																																																
707.50	20.85	H	3.7	1.3	18.42	34.8	-16.4																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
714.50	13.38	V	3.8	1.2	10.80	34.8	-24.0																																																																																																																																																																																																
714.50	21.23	H	3.8	1.2	18.89	34.8	-16.1																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
700.50	12.66	V	3.7	1.3	10.23	34.8	-24.6																																																																																																																																																																																																
700.50	20.28	H	3.7	1.4	17.95	34.8	-16.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	12.08	V	3.7	1.2	9.58	34.8	-25.2																																																																																																																																																																																																
707.50	19.83	H	3.7	1.3	17.20	34.8	-17.6																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
714.50	12.11	V	3.8	1.2	9.53	34.8	-25.3																																																																																																																																																																																																
714.50	19.98	H	3.8	1.2	17.44	34.8	-17.4																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_QPSK Band 12 Fundamentals, 1.4MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>699.70</td><td>12.60</td><td>V</td><td>3.7</td><td>1.3</td><td>10.18</td><td>34.8</td><td>-24.8</td><td></td></tr> <tr><td>699.70</td><td>20.92</td><td>H</td><td>3.7</td><td>1.4</td><td>18.60</td><td>34.8</td><td>-16.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>12.33</td><td>V</td><td>3.7</td><td>1.2</td><td>9.83</td><td>34.8</td><td>-25.0</td><td></td></tr> <tr><td>707.50</td><td>20.91</td><td>H</td><td>3.7</td><td>1.3</td><td>18.48</td><td>34.8</td><td>-16.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>715.30</td><td>12.05</td><td>V</td><td>3.8</td><td>1.2</td><td>9.46</td><td>34.8</td><td>-25.3</td><td></td></tr> <tr><td>715.30</td><td>21.18</td><td>H</td><td>3.8</td><td>1.2</td><td>18.63</td><td>34.8</td><td>-16.2</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									699.70	12.60	V	3.7	1.3	10.18	34.8	-24.8		699.70	20.92	H	3.7	1.4	18.60	34.8	-16.2		Mid Ch									707.50	12.33	V	3.7	1.2	9.83	34.8	-25.0		707.50	20.91	H	3.7	1.3	18.48	34.8	-16.3		High Ch									715.30	12.05	V	3.8	1.2	9.46	34.8	-25.3		715.30	21.18	H	3.8	1.2	18.63	34.8	-16.2		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 2/12/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber K                      Mode: LTE_16QAM Band 12 Fundamentals, 1.4MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0181574, and Chamber K SMA Cables                      Substitution: Dipole T416, Chamber K Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>699.70</td><td>11.39</td><td>V</td><td>3.7</td><td>1.3</td><td>8.96</td><td>34.8</td><td>-25.8</td><td></td></tr> <tr><td>699.70</td><td>19.78</td><td>H</td><td>3.7</td><td>1.4</td><td>17.46</td><td>34.8</td><td>-17.3</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>707.50</td><td>11.25</td><td>V</td><td>3.7</td><td>1.2</td><td>8.75</td><td>34.8</td><td>-26.1</td><td></td></tr> <tr><td>707.50</td><td>19.95</td><td>H</td><td>3.7</td><td>1.3</td><td>17.52</td><td>34.8</td><td>-17.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>715.30</td><td>11.08</td><td>V</td><td>3.8</td><td>1.2</td><td>8.49</td><td>34.8</td><td>-26.3</td><td></td></tr> <tr><td>715.30</td><td>20.05</td><td>H</td><td>3.8</td><td>1.2</td><td>17.50</td><td>34.8</td><td>-17.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									699.70	11.39	V	3.7	1.3	8.96	34.8	-25.8		699.70	19.78	H	3.7	1.4	17.46	34.8	-17.3		Mid Ch									707.50	11.25	V	3.7	1.2	8.75	34.8	-26.1		707.50	19.95	H	3.7	1.3	17.52	34.8	-17.3		High Ch									715.30	11.08	V	3.8	1.2	8.49	34.8	-26.3		715.30	20.05	H	3.8	1.2	17.50	34.8	-17.3	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
699.70	12.60	V	3.7	1.3	10.18	34.8	-24.8																																																																																																																																																																																																
699.70	20.92	H	3.7	1.4	18.60	34.8	-16.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	12.33	V	3.7	1.2	9.83	34.8	-25.0																																																																																																																																																																																																
707.50	20.91	H	3.7	1.3	18.48	34.8	-16.3																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
715.30	12.05	V	3.8	1.2	9.46	34.8	-25.3																																																																																																																																																																																																
715.30	21.18	H	3.8	1.2	18.63	34.8	-16.2																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
699.70	11.39	V	3.7	1.3	8.96	34.8	-25.8																																																																																																																																																																																																
699.70	19.78	H	3.7	1.4	17.46	34.8	-17.3																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
707.50	11.25	V	3.7	1.2	8.75	34.8	-26.1																																																																																																																																																																																																
707.50	19.95	H	3.7	1.3	17.52	34.8	-17.3																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
715.30	11.08	V	3.8	1.2	8.49	34.8	-26.3																																																																																																																																																																																																
715.30	20.05	H	3.8	1.2	17.50	34.8	-17.3																																																																																																																																																																																																

### 9.1.7. LTE Band 13

10MHz QPSK										10MHz 16QAM																																																																																																																																																																																													
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/3/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 13 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>782.00</td> <td>13.22</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>10.37</td> <td>34.8</td> <td>-24.4</td> <td></td> </tr> <tr> <td>782.00</td> <td>20.06</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>16.99</td> <td>34.8</td> <td>-17.8</td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Mid Ch									782.00	13.22	V	3.6	0.7	10.37	34.8	-24.4		782.00	20.06	H	3.6	0.5	16.99	34.8	-17.8		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/3/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 13 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>782.00</td> <td>11.97</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>9.12</td> <td>34.8</td> <td>-25.6</td> <td></td> </tr> <tr> <td>782.00</td> <td>18.85</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>15.78</td> <td>34.8</td> <td>-19.0</td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Mid Ch									782.00	11.97	V	3.6	0.7	9.12	34.8	-25.6		782.00	18.85	H	3.6	0.5	15.78	34.8	-19.0																																																																																																													
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Mid Ch																																																																																																																																																																																																							
782.00	13.22	V	3.6	0.7	10.37	34.8	-24.4																																																																																																																																																																																																
782.00	20.06	H	3.6	0.5	16.99	34.8	-17.8																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Mid Ch																																																																																																																																																																																																							
782.00	11.97	V	3.6	0.7	9.12	34.8	-25.6																																																																																																																																																																																																
782.00	18.85	H	3.6	0.5	15.78	34.8	-19.0																																																																																																																																																																																																
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/3/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 13 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>Low Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>779.50</td> <td>13.14</td> <td>V</td> <td>3.6</td> <td>0.8</td> <td>10.32</td> <td>34.8</td> <td>-24.4</td> <td></td> </tr> <tr> <td>779.50</td> <td>20.06</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>17.02</td> <td>34.8</td> <td>-17.7</td> <td></td> </tr> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>782.00</td> <td>13.24</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>10.39</td> <td>34.8</td> <td>-24.4</td> <td></td> </tr> <tr> <td>782.00</td> <td>20.16</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>17.08</td> <td>34.8</td> <td>-17.7</td> <td></td> </tr> <tr> <td>High Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>784.50</td> <td>13.39</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>10.52</td> <td>34.8</td> <td>-24.3</td> <td></td> </tr> <tr> <td>784.50</td> <td>20.12</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>17.01</td> <td>34.8</td> <td>-17.8</td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									779.50	13.14	V	3.6	0.8	10.32	34.8	-24.4		779.50	20.06	H	3.6	0.5	17.02	34.8	-17.7		Mid Ch									782.00	13.24	V	3.6	0.7	10.39	34.8	-24.4		782.00	20.16	H	3.6	0.5	17.08	34.8	-17.7		High Ch									784.50	13.39	V	3.6	0.7	10.52	34.8	-24.3		784.50	20.12	H	3.6	0.5	17.01	34.8	-17.8		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/3/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 13 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>Low Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>779.50</td> <td>11.86</td> <td>V</td> <td>3.6</td> <td>0.8</td> <td>9.04</td> <td>34.8</td> <td>-25.7</td> <td></td> </tr> <tr> <td>779.50</td> <td>18.99</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>15.55</td> <td>34.8</td> <td>-19.2</td> <td></td> </tr> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>782.00</td> <td>11.97</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>9.12</td> <td>34.8</td> <td>-25.6</td> <td></td> </tr> <tr> <td>782.00</td> <td>18.72</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>15.65</td> <td>34.8</td> <td>-19.1</td> <td></td> </tr> <tr> <td>High Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>784.50</td> <td>12.17</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>9.30</td> <td>34.8</td> <td>-25.5</td> <td></td> </tr> <tr> <td>784.50</td> <td>18.81</td> <td>H</td> <td>3.6</td> <td>0.5</td> <td>15.70</td> <td>34.8</td> <td>-19.1</td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									779.50	11.86	V	3.6	0.8	9.04	34.8	-25.7		779.50	18.99	H	3.6	0.5	15.55	34.8	-19.2		Mid Ch									782.00	11.97	V	3.6	0.7	9.12	34.8	-25.6		782.00	18.72	H	3.6	0.5	15.65	34.8	-19.1		High Ch									784.50	12.17	V	3.6	0.7	9.30	34.8	-25.5		784.50	18.81	H	3.6	0.5	15.70	34.8	-19.1	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
779.50	13.14	V	3.6	0.8	10.32	34.8	-24.4																																																																																																																																																																																																
779.50	20.06	H	3.6	0.5	17.02	34.8	-17.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
782.00	13.24	V	3.6	0.7	10.39	34.8	-24.4																																																																																																																																																																																																
782.00	20.16	H	3.6	0.5	17.08	34.8	-17.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
784.50	13.39	V	3.6	0.7	10.52	34.8	-24.3																																																																																																																																																																																																
784.50	20.12	H	3.6	0.5	17.01	34.8	-17.8																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
779.50	11.86	V	3.6	0.8	9.04	34.8	-25.7																																																																																																																																																																																																
779.50	18.99	H	3.6	0.5	15.55	34.8	-19.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
782.00	11.97	V	3.6	0.7	9.12	34.8	-25.6																																																																																																																																																																																																
782.00	18.72	H	3.6	0.5	15.65	34.8	-19.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
784.50	12.17	V	3.6	0.7	9.30	34.8	-25.5																																																																																																																																																																																																
784.50	18.81	H	3.6	0.5	15.70	34.8	-19.1																																																																																																																																																																																																



### 9.1.8. LTE Band 14

10MHz QPSK										10MHz 16QAM																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/16/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 14 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>793.00</td> <td>13.46</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>10.52</td> <td>34.8</td> <td>-24.5</td> <td colspan="2"></td> </tr> <tr> <td>793.00</td> <td>21.20</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>17.96</td> <td>34.8</td> <td>-16.8</td> <td colspan="2"></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		793.00	13.46	V	3.6	0.7	10.52	34.8	-24.5			793.00	21.20	H	3.6	0.4	17.96	34.8	-16.8			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/16/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 14 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>793.00</td> <td>12.19</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>9.23</td> <td>34.8</td> <td>-25.5</td> <td colspan="2"></td> </tr> <tr> <td>793.00</td> <td>19.87</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>16.63</td> <td>34.8</td> <td>-18.1</td> <td colspan="2"></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		793.00	12.19	V	3.6	0.7	9.23	34.8	-25.5			793.00	19.87	H	3.6	0.4	16.63	34.8	-18.1																																																																																																																																														
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
793.00	13.46	V	3.6	0.7	10.52	34.8	-24.5																																																																																																																																																																																																																				
793.00	21.20	H	3.6	0.4	17.96	34.8	-16.8																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
793.00	12.19	V	3.6	0.7	9.23	34.8	-25.5																																																																																																																																																																																																																				
793.00	19.87	H	3.6	0.4	16.63	34.8	-18.1																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/16/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_QPSK Band 14 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Low Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>790.50</td> <td>13.23</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>10.29</td> <td>34.8</td> <td>-24.5</td> <td colspan="2"></td> </tr> <tr> <td>790.50</td> <td>21.34</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>18.14</td> <td>34.8</td> <td>-16.6</td> <td colspan="2"></td> </tr> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>793.00</td> <td>13.37</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>10.41</td> <td>34.8</td> <td>-24.4</td> <td colspan="2"></td> </tr> <tr> <td>793.00</td> <td>21.43</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>18.19</td> <td>34.8</td> <td>-16.6</td> <td colspan="2"></td> </tr> <tr> <td>High Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>795.50</td> <td>13.04</td> <td>V</td> <td>3.6</td> <td>0.6</td> <td>10.05</td> <td>34.8</td> <td>-24.7</td> <td colspan="2"></td> </tr> <tr> <td>795.50</td> <td>21.53</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>18.28</td> <td>34.8</td> <td>-16.5</td> <td colspan="2"></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										790.50	13.23	V	3.6	0.7	10.29	34.8	-24.5			790.50	21.34	H	3.6	0.4	18.14	34.8	-16.6			Mid Ch										793.00	13.37	V	3.6	0.7	10.41	34.8	-24.4			793.00	21.43	H	3.6	0.4	18.19	34.8	-16.6			High Ch										795.50	13.04	V	3.6	0.6	10.05	34.8	-24.7			795.50	21.53	H	3.6	0.4	18.28	34.8	-16.5			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/16/2020  <b>Test Engineer:</b> 19480 BS  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber I  <b>Mode:</b> LTE_16QAM Band 14 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Low Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>790.50</td> <td>11.87</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>8.93</td> <td>34.8</td> <td>-25.8</td> <td colspan="2"></td> </tr> <tr> <td>790.50</td> <td>20.03</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>16.83</td> <td>34.8</td> <td>-17.9</td> <td colspan="2"></td> </tr> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>793.00</td> <td>11.88</td> <td>V</td> <td>3.6</td> <td>0.7</td> <td>8.92</td> <td>34.8</td> <td>-25.9</td> <td colspan="2"></td> </tr> <tr> <td>793.00</td> <td>20.13</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>16.89</td> <td>34.8</td> <td>-17.9</td> <td colspan="2"></td> </tr> <tr> <td>High Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="2"></td> </tr> <tr> <td>795.50</td> <td>11.68</td> <td>V</td> <td>3.6</td> <td>0.6</td> <td>8.69</td> <td>34.8</td> <td>-26.1</td> <td colspan="2"></td> </tr> <tr> <td>795.50</td> <td>20.17</td> <td>H</td> <td>3.6</td> <td>0.4</td> <td>16.90</td> <td>34.8</td> <td>-17.9</td> <td colspan="2"></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										790.50	11.87	V	3.6	0.7	8.93	34.8	-25.8			790.50	20.03	H	3.6	0.4	16.83	34.8	-17.9			Mid Ch										793.00	11.88	V	3.6	0.7	8.92	34.8	-25.9			793.00	20.13	H	3.6	0.4	16.89	34.8	-17.9			High Ch										795.50	11.68	V	3.6	0.6	8.69	34.8	-26.1			795.50	20.17	H	3.6	0.4	16.90	34.8	-17.9		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
790.50	13.23	V	3.6	0.7	10.29	34.8	-24.5																																																																																																																																																																																																																				
790.50	21.34	H	3.6	0.4	18.14	34.8	-16.6																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
793.00	13.37	V	3.6	0.7	10.41	34.8	-24.4																																																																																																																																																																																																																				
793.00	21.43	H	3.6	0.4	18.19	34.8	-16.6																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
795.50	13.04	V	3.6	0.6	10.05	34.8	-24.7																																																																																																																																																																																																																				
795.50	21.53	H	3.6	0.4	18.28	34.8	-16.5																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
790.50	11.87	V	3.6	0.7	8.93	34.8	-25.8																																																																																																																																																																																																																				
790.50	20.03	H	3.6	0.4	16.83	34.8	-17.9																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
793.00	11.88	V	3.6	0.7	8.92	34.8	-25.9																																																																																																																																																																																																																				
793.00	20.13	H	3.6	0.4	16.89	34.8	-17.9																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
795.50	11.68	V	3.6	0.6	8.69	34.8	-26.1																																																																																																																																																																																																																				
795.50	20.17	H	3.6	0.4	16.90	34.8	-17.9																																																																																																																																																																																																																				

### 9.1.9. LTE Band 25

20MHz QPSK										20MHz 16QAM																																																																																																																																																																																													
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_QPSK Band 25 Fundamentals, 20MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1860.00</td><td>11.93</td><td>V</td><td>0.3</td><td>4.7</td><td>16.34</td><td>33.0</td><td>-16.7</td><td></td></tr> <tr><td>1860.00</td><td>15.16</td><td>H</td><td>0.3</td><td>4.7</td><td>19.52</td><td>33.0</td><td>-13.5</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1882.50</td><td>11.15</td><td>V</td><td>0.3</td><td>4.7</td><td>15.56</td><td>33.0</td><td>-17.4</td><td></td></tr> <tr><td>1882.50</td><td>14.42</td><td>H</td><td>0.3</td><td>4.7</td><td>18.80</td><td>33.0</td><td>-14.2</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1905.00</td><td>11.37</td><td>V</td><td>0.3</td><td>4.7</td><td>15.78</td><td>33.0</td><td>-17.2</td><td></td></tr> <tr><td>1905.00</td><td>14.05</td><td>H</td><td>0.3</td><td>4.7</td><td>18.48</td><td>33.0</td><td>-14.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1860.00	11.93	V	0.3	4.7	16.34	33.0	-16.7		1860.00	15.16	H	0.3	4.7	19.52	33.0	-13.5		Mid Ch									1882.50	11.15	V	0.3	4.7	15.56	33.0	-17.4		1882.50	14.42	H	0.3	4.7	18.80	33.0	-14.2		High Ch									1905.00	11.37	V	0.3	4.7	15.78	33.0	-17.2		1905.00	14.05	H	0.3	4.7	18.48	33.0	-14.5		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_16QAM Band 25 Fundamentals, 20MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1860.00</td><td>11.83</td><td>V</td><td>0.3</td><td>4.7</td><td>16.24</td><td>33.0</td><td>-16.8</td><td></td></tr> <tr><td>1860.00</td><td>15.06</td><td>H</td><td>0.3</td><td>4.7</td><td>19.42</td><td>33.0</td><td>-13.6</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1882.50</td><td>10.85</td><td>V</td><td>0.3</td><td>4.7</td><td>15.36</td><td>33.0</td><td>-17.6</td><td></td></tr> <tr><td>1882.50</td><td>13.92</td><td>H</td><td>0.3</td><td>4.7</td><td>18.30</td><td>33.0</td><td>-14.7</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1905.00</td><td>11.17</td><td>V</td><td>0.3</td><td>4.7</td><td>15.58</td><td>33.0</td><td>-17.4</td><td></td></tr> <tr><td>1905.00</td><td>13.75</td><td>H</td><td>0.3</td><td>4.7</td><td>18.18</td><td>33.0</td><td>-14.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1860.00	11.83	V	0.3	4.7	16.24	33.0	-16.8		1860.00	15.06	H	0.3	4.7	19.42	33.0	-13.6		Mid Ch									1882.50	10.85	V	0.3	4.7	15.36	33.0	-17.6		1882.50	13.92	H	0.3	4.7	18.30	33.0	-14.7		High Ch									1905.00	11.17	V	0.3	4.7	15.58	33.0	-17.4		1905.00	13.75	H	0.3	4.7	18.18	33.0	-14.8	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1860.00	11.93	V	0.3	4.7	16.34	33.0	-16.7																																																																																																																																																																																																
1860.00	15.16	H	0.3	4.7	19.52	33.0	-13.5																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1882.50	11.15	V	0.3	4.7	15.56	33.0	-17.4																																																																																																																																																																																																
1882.50	14.42	H	0.3	4.7	18.80	33.0	-14.2																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1905.00	11.37	V	0.3	4.7	15.78	33.0	-17.2																																																																																																																																																																																																
1905.00	14.05	H	0.3	4.7	18.48	33.0	-14.5																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1860.00	11.83	V	0.3	4.7	16.24	33.0	-16.8																																																																																																																																																																																																
1860.00	15.06	H	0.3	4.7	19.42	33.0	-13.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1882.50	10.85	V	0.3	4.7	15.36	33.0	-17.6																																																																																																																																																																																																
1882.50	13.92	H	0.3	4.7	18.30	33.0	-14.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1905.00	11.17	V	0.3	4.7	15.58	33.0	-17.4																																																																																																																																																																																																
1905.00	13.75	H	0.3	4.7	18.18	33.0	-14.8																																																																																																																																																																																																
<p style="text-align: center;"><b>15MHz QPSK</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_QPSK Band 25 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1857.50</td><td>12.43</td><td>V</td><td>0.3</td><td>4.7</td><td>16.84</td><td>33.0</td><td>-16.2</td><td></td></tr> <tr><td>1857.50</td><td>15.76</td><td>H</td><td>0.3</td><td>4.7</td><td>20.12</td><td>33.0</td><td>-12.9</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1882.50</td><td>10.65</td><td>V</td><td>0.3</td><td>4.7</td><td>15.06</td><td>33.0</td><td>-17.9</td><td></td></tr> <tr><td>1882.50</td><td>14.62</td><td>H</td><td>0.3</td><td>4.7</td><td>19.00</td><td>33.0</td><td>-14.0</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1907.50</td><td>3.07</td><td>V</td><td>0.3</td><td>4.7</td><td>7.48</td><td>33.0</td><td>-25.5</td><td></td></tr> <tr><td>1907.50</td><td>13.75</td><td>H</td><td>0.3</td><td>4.7</td><td>18.18</td><td>33.0</td><td>-14.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1857.50	12.43	V	0.3	4.7	16.84	33.0	-16.2		1857.50	15.76	H	0.3	4.7	20.12	33.0	-12.9		Mid Ch									1882.50	10.65	V	0.3	4.7	15.06	33.0	-17.9		1882.50	14.62	H	0.3	4.7	19.00	33.0	-14.0		High Ch									1907.50	3.07	V	0.3	4.7	7.48	33.0	-25.5		1907.50	13.75	H	0.3	4.7	18.18	33.0	-14.8		<p style="text-align: center;"><b>15MHz 16QAM</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_16QAM Band 25 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1857.50</td><td>12.03</td><td>V</td><td>0.3</td><td>4.7</td><td>16.44</td><td>33.0</td><td>-16.6</td><td></td></tr> <tr><td>1857.50</td><td>15.46</td><td>H</td><td>0.3</td><td>4.7</td><td>19.82</td><td>33.0</td><td>-13.2</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1882.50</td><td>10.55</td><td>V</td><td>0.3</td><td>4.7</td><td>14.96</td><td>33.0</td><td>-18.0</td><td></td></tr> <tr><td>1882.50</td><td>14.52</td><td>H</td><td>0.3</td><td>4.7</td><td>18.90</td><td>33.0</td><td>-14.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1907.50</td><td>2.77</td><td>V</td><td>0.3</td><td>4.7</td><td>7.18</td><td>33.0</td><td>-25.8</td><td></td></tr> <tr><td>1907.50</td><td>13.46</td><td>H</td><td>0.3</td><td>4.7</td><td>17.88</td><td>33.0</td><td>-15.1</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1857.50	12.03	V	0.3	4.7	16.44	33.0	-16.6		1857.50	15.46	H	0.3	4.7	19.82	33.0	-13.2		Mid Ch									1882.50	10.55	V	0.3	4.7	14.96	33.0	-18.0		1882.50	14.52	H	0.3	4.7	18.90	33.0	-14.1		High Ch									1907.50	2.77	V	0.3	4.7	7.18	33.0	-25.8		1907.50	13.46	H	0.3	4.7	17.88	33.0	-15.1	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1857.50	12.43	V	0.3	4.7	16.84	33.0	-16.2																																																																																																																																																																																																
1857.50	15.76	H	0.3	4.7	20.12	33.0	-12.9																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1882.50	10.65	V	0.3	4.7	15.06	33.0	-17.9																																																																																																																																																																																																
1882.50	14.62	H	0.3	4.7	19.00	33.0	-14.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1907.50	3.07	V	0.3	4.7	7.48	33.0	-25.5																																																																																																																																																																																																
1907.50	13.75	H	0.3	4.7	18.18	33.0	-14.8																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1857.50	12.03	V	0.3	4.7	16.44	33.0	-16.6																																																																																																																																																																																																
1857.50	15.46	H	0.3	4.7	19.82	33.0	-13.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1882.50	10.55	V	0.3	4.7	14.96	33.0	-18.0																																																																																																																																																																																																
1882.50	14.52	H	0.3	4.7	18.90	33.0	-14.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1907.50	2.77	V	0.3	4.7	7.18	33.0	-25.8																																																																																																																																																																																																
1907.50	13.46	H	0.3	4.7	17.88	33.0	-15.1																																																																																																																																																																																																
<p style="text-align: center;"><b>10MHz QPSK</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_QPSK Band 25 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1855.00</td><td>12.43</td><td>V</td><td>0.3</td><td>4.7</td><td>16.84</td><td>33.0</td><td>-16.2</td><td></td></tr> <tr><td>1855.00</td><td>15.96</td><td>H</td><td>0.3</td><td>4.7</td><td>20.32</td><td>33.0</td><td>-12.7</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1882.50</td><td>11.05</td><td>V</td><td>0.3</td><td>4.7</td><td>15.46</td><td>33.0</td><td>-17.5</td><td></td></tr> <tr><td>1882.50</td><td>14.62</td><td>H</td><td>0.3</td><td>4.7</td><td>19.00</td><td>33.0</td><td>-14.0</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1910.00</td><td>0.00</td><td>V</td><td>0.3</td><td>4.7</td><td>0.00</td><td>33.0</td><td>0.0</td><td></td></tr> <tr><td>1910.00</td><td>15.05</td><td>H</td><td>0.3</td><td>4.7</td><td>19.48</td><td>33.0</td><td>-13.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1855.00	12.43	V	0.3	4.7	16.84	33.0	-16.2		1855.00	15.96	H	0.3	4.7	20.32	33.0	-12.7		Mid Ch									1882.50	11.05	V	0.3	4.7	15.46	33.0	-17.5		1882.50	14.62	H	0.3	4.7	19.00	33.0	-14.0		High Ch									1910.00	0.00	V	0.3	4.7	0.00	33.0	0.0		1910.00	15.05	H	0.3	4.7	19.48	33.0	-13.5		<p style="text-align: center;"><b>10MHz 16QAM</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/2/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_16QAM Band 25 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1855.00</td><td>12.13</td><td>V</td><td>0.3</td><td>4.7</td><td>16.54</td><td>33.0</td><td>-16.5</td><td></td></tr> <tr><td>1855.00</td><td>15.86</td><td>H</td><td>0.3</td><td>4.7</td><td>20.02</td><td>33.0</td><td>-13.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1882.50</td><td>10.75</td><td>V</td><td>0.3</td><td>4.7</td><td>15.16</td><td>33.0</td><td>-17.8</td><td></td></tr> <tr><td>1882.50</td><td>14.22</td><td>H</td><td>0.3</td><td>4.7</td><td>18.60</td><td>33.0</td><td>-14.4</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1910.00</td><td>11.57</td><td>V</td><td>0.3</td><td>4.7</td><td>15.98</td><td>33.0</td><td>-17.0</td><td></td></tr> <tr><td>1910.00</td><td>13.55</td><td>H</td><td>0.3</td><td>4.7</td><td>17.98</td><td>33.0</td><td>-15.0</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1855.00	12.13	V	0.3	4.7	16.54	33.0	-16.5		1855.00	15.86	H	0.3	4.7	20.02	33.0	-13.0		Mid Ch									1882.50	10.75	V	0.3	4.7	15.16	33.0	-17.8		1882.50	14.22	H	0.3	4.7	18.60	33.0	-14.4		High Ch									1910.00	11.57	V	0.3	4.7	15.98	33.0	-17.0		1910.00	13.55	H	0.3	4.7	17.98	33.0	-15.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1855.00	12.43	V	0.3	4.7	16.84	33.0	-16.2																																																																																																																																																																																																
1855.00	15.96	H	0.3	4.7	20.32	33.0	-12.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1882.50	11.05	V	0.3	4.7	15.46	33.0	-17.5																																																																																																																																																																																																
1882.50	14.62	H	0.3	4.7	19.00	33.0	-14.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1910.00	0.00	V	0.3	4.7	0.00	33.0	0.0																																																																																																																																																																																																
1910.00	15.05	H	0.3	4.7	19.48	33.0	-13.5																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1855.00	12.13	V	0.3	4.7	16.54	33.0	-16.5																																																																																																																																																																																																
1855.00	15.86	H	0.3	4.7	20.02	33.0	-13.0																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1882.50	10.75	V	0.3	4.7	15.16	33.0	-17.8																																																																																																																																																																																																
1882.50	14.22	H	0.3	4.7	18.60	33.0	-14.4																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1910.00	11.57	V	0.3	4.7	15.98	33.0	-17.0																																																																																																																																																																																																
1910.00	13.55	H	0.3	4.7	17.98	33.0	-15.0																																																																																																																																																																																																

5MHz QPSK										5MHz 16QAM																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_QPSK Band 25 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1852.50</td><td>14.43</td><td>V</td><td>0.3</td><td>4.7</td><td>18.84</td><td>33.0</td><td>-14.2</td><td colspan="2"></td></tr> <tr><td>1852.50</td><td>17.86</td><td>H</td><td>0.3</td><td>4.7</td><td>22.22</td><td>33.0</td><td>-10.8</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1882.50</td><td>12.45</td><td>V</td><td>0.3</td><td>4.7</td><td>16.86</td><td>33.0</td><td>-16.1</td><td colspan="2"></td></tr> <tr><td>1882.50</td><td>15.82</td><td>H</td><td>0.3</td><td>4.7</td><td>20.20</td><td>33.0</td><td>-12.8</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1912.50</td><td>13.67</td><td>V</td><td>0.3</td><td>4.7</td><td>18.08</td><td>33.0</td><td>-14.9</td><td colspan="2"></td></tr> <tr><td>1912.50</td><td>15.75</td><td>H</td><td>0.3</td><td>4.7</td><td>20.18</td><td>33.0</td><td>-12.8</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1852.50	14.43	V	0.3	4.7	18.84	33.0	-14.2			1852.50	17.86	H	0.3	4.7	22.22	33.0	-10.8			Mid Ch										1882.50	12.45	V	0.3	4.7	16.86	33.0	-16.1			1882.50	15.82	H	0.3	4.7	20.20	33.0	-12.8			High Ch										1912.50	13.67	V	0.3	4.7	18.08	33.0	-14.9			1912.50	15.75	H	0.3	4.7	20.18	33.0	-12.8			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_16QAM Band 25 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1852.50</td><td>13.03</td><td>V</td><td>0.3</td><td>4.7</td><td>17.44</td><td>33.0</td><td>-15.6</td><td colspan="2"></td></tr> <tr><td>1852.50</td><td>16.46</td><td>H</td><td>0.3</td><td>4.7</td><td>20.82</td><td>33.0</td><td>-12.2</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1882.50</td><td>11.05</td><td>V</td><td>0.3</td><td>4.7</td><td>15.46</td><td>33.0</td><td>-17.5</td><td colspan="2"></td></tr> <tr><td>1882.50</td><td>14.52</td><td>H</td><td>0.3</td><td>4.7</td><td>18.90</td><td>33.0</td><td>-14.1</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1912.50</td><td>12.17</td><td>V</td><td>0.3</td><td>4.7</td><td>16.58</td><td>33.0</td><td>-16.4</td><td colspan="2"></td></tr> <tr><td>1912.50</td><td>14.25</td><td>H</td><td>0.3</td><td>4.7</td><td>18.68</td><td>33.0</td><td>-14.3</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1852.50	13.03	V	0.3	4.7	17.44	33.0	-15.6			1852.50	16.46	H	0.3	4.7	20.82	33.0	-12.2			Mid Ch										1882.50	11.05	V	0.3	4.7	15.46	33.0	-17.5			1882.50	14.52	H	0.3	4.7	18.90	33.0	-14.1			High Ch										1912.50	12.17	V	0.3	4.7	16.58	33.0	-16.4			1912.50	14.25	H	0.3	4.7	18.68	33.0	-14.3		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1852.50	14.43	V	0.3	4.7	18.84	33.0	-14.2																																																																																																																																																																																																																				
1852.50	17.86	H	0.3	4.7	22.22	33.0	-10.8																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1882.50	12.45	V	0.3	4.7	16.86	33.0	-16.1																																																																																																																																																																																																																				
1882.50	15.82	H	0.3	4.7	20.20	33.0	-12.8																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1912.50	13.67	V	0.3	4.7	18.08	33.0	-14.9																																																																																																																																																																																																																				
1912.50	15.75	H	0.3	4.7	20.18	33.0	-12.8																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1852.50	13.03	V	0.3	4.7	17.44	33.0	-15.6																																																																																																																																																																																																																				
1852.50	16.46	H	0.3	4.7	20.82	33.0	-12.2																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1882.50	11.05	V	0.3	4.7	15.46	33.0	-17.5																																																																																																																																																																																																																				
1882.50	14.52	H	0.3	4.7	18.90	33.0	-14.1																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1912.50	12.17	V	0.3	4.7	16.58	33.0	-16.4																																																																																																																																																																																																																				
1912.50	14.25	H	0.3	4.7	18.68	33.0	-14.3																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_QPSK Band 25 Fundamentals, 3MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1851.50</td><td>12.73</td><td>V</td><td>0.3</td><td>4.7</td><td>17.14</td><td>33.0</td><td>-15.9</td><td colspan="2"></td></tr> <tr><td>1851.50</td><td>17.56</td><td>H</td><td>0.3</td><td>4.7</td><td>21.92</td><td>33.0</td><td>-11.1</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1882.50</td><td>13.25</td><td>V</td><td>0.3</td><td>4.7</td><td>17.66</td><td>33.0</td><td>-15.3</td><td colspan="2"></td></tr> <tr><td>1882.50</td><td>16.42</td><td>H</td><td>0.3</td><td>4.7</td><td>20.80</td><td>33.0</td><td>-12.2</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1913.50</td><td>13.57</td><td>V</td><td>0.3</td><td>4.7</td><td>17.98</td><td>33.0</td><td>-15.0</td><td colspan="2"></td></tr> <tr><td>1913.50</td><td>15.85</td><td>H</td><td>0.3</td><td>4.7</td><td>20.28</td><td>33.0</td><td>-12.7</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1851.50	12.73	V	0.3	4.7	17.14	33.0	-15.9			1851.50	17.56	H	0.3	4.7	21.92	33.0	-11.1			Mid Ch										1882.50	13.25	V	0.3	4.7	17.66	33.0	-15.3			1882.50	16.42	H	0.3	4.7	20.80	33.0	-12.2			High Ch										1913.50	13.57	V	0.3	4.7	17.98	33.0	-15.0			1913.50	15.85	H	0.3	4.7	20.28	33.0	-12.7			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_16QAM Band 25 Fundamentals, 3MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1851.50</td><td>11.33</td><td>V</td><td>0.3</td><td>4.7</td><td>15.74</td><td>33.0</td><td>-17.3</td><td colspan="2"></td></tr> <tr><td>1851.50</td><td>16.06</td><td>H</td><td>0.3</td><td>4.7</td><td>20.42</td><td>33.0</td><td>-12.6</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1882.50</td><td>11.75</td><td>V</td><td>0.3</td><td>4.7</td><td>16.16</td><td>33.0</td><td>-16.8</td><td colspan="2"></td></tr> <tr><td>1882.50</td><td>14.82</td><td>H</td><td>0.3</td><td>4.7</td><td>19.20</td><td>33.0</td><td>-13.8</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1913.50</td><td>12.07</td><td>V</td><td>0.3</td><td>4.7</td><td>16.48</td><td>33.0</td><td>-16.5</td><td colspan="2"></td></tr> <tr><td>1913.50</td><td>14.45</td><td>H</td><td>0.3</td><td>4.7</td><td>18.88</td><td>33.0</td><td>-14.1</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1851.50	11.33	V	0.3	4.7	15.74	33.0	-17.3			1851.50	16.06	H	0.3	4.7	20.42	33.0	-12.6			Mid Ch										1882.50	11.75	V	0.3	4.7	16.16	33.0	-16.8			1882.50	14.82	H	0.3	4.7	19.20	33.0	-13.8			High Ch										1913.50	12.07	V	0.3	4.7	16.48	33.0	-16.5			1913.50	14.45	H	0.3	4.7	18.88	33.0	-14.1		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1851.50	12.73	V	0.3	4.7	17.14	33.0	-15.9																																																																																																																																																																																																																				
1851.50	17.56	H	0.3	4.7	21.92	33.0	-11.1																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1882.50	13.25	V	0.3	4.7	17.66	33.0	-15.3																																																																																																																																																																																																																				
1882.50	16.42	H	0.3	4.7	20.80	33.0	-12.2																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1913.50	13.57	V	0.3	4.7	17.98	33.0	-15.0																																																																																																																																																																																																																				
1913.50	15.85	H	0.3	4.7	20.28	33.0	-12.7																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1851.50	11.33	V	0.3	4.7	15.74	33.0	-17.3																																																																																																																																																																																																																				
1851.50	16.06	H	0.3	4.7	20.42	33.0	-12.6																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1882.50	11.75	V	0.3	4.7	16.16	33.0	-16.8																																																																																																																																																																																																																				
1882.50	14.82	H	0.3	4.7	19.20	33.0	-13.8																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1913.50	12.07	V	0.3	4.7	16.48	33.0	-16.5																																																																																																																																																																																																																				
1913.50	14.45	H	0.3	4.7	18.88	33.0	-14.1																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_QPSK Band 25 Fundamentals, 1.4MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1850.70</td><td>12.43</td><td>V</td><td>0.3</td><td>4.7</td><td>16.84</td><td>33.0</td><td>-16.2</td><td colspan="2"></td></tr> <tr><td>1850.70</td><td>17.66</td><td>H</td><td>0.3</td><td>4.7</td><td>22.02</td><td>33.0</td><td>-11.0</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1882.50</td><td>12.55</td><td>V</td><td>0.3</td><td>4.7</td><td>16.96</td><td>33.0</td><td>-16.0</td><td colspan="2"></td></tr> <tr><td>1882.50</td><td>15.82</td><td>H</td><td>0.3</td><td>4.7</td><td>20.20</td><td>33.0</td><td>-12.8</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1914.30</td><td>13.67</td><td>V</td><td>0.3</td><td>4.7</td><td>18.08</td><td>33.0</td><td>-14.9</td><td colspan="2"></td></tr> <tr><td>1914.30</td><td>16.45</td><td>H</td><td>0.3</td><td>4.7</td><td>20.88</td><td>33.0</td><td>-12.1</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1850.70	12.43	V	0.3	4.7	16.84	33.0	-16.2			1850.70	17.66	H	0.3	4.7	22.02	33.0	-11.0			Mid Ch										1882.50	12.55	V	0.3	4.7	16.96	33.0	-16.0			1882.50	15.82	H	0.3	4.7	20.20	33.0	-12.8			High Ch										1914.30	13.67	V	0.3	4.7	18.08	33.0	-14.9			1914.30	16.45	H	0.3	4.7	20.88	33.0	-12.1			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_16QAM Band 25 Fundamentals, 1.4MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1850.70</td><td>11.23</td><td>V</td><td>0.3</td><td>4.7</td><td>15.64</td><td>33.0</td><td>-17.4</td><td colspan="2"></td></tr> <tr><td>1850.70</td><td>16.56</td><td>H</td><td>0.3</td><td>4.7</td><td>20.92</td><td>33.0</td><td>-12.1</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1882.50</td><td>11.25</td><td>V</td><td>0.3</td><td>4.7</td><td>15.66</td><td>33.0</td><td>-17.3</td><td colspan="2"></td></tr> <tr><td>1882.50</td><td>14.42</td><td>H</td><td>0.3</td><td>4.7</td><td>18.80</td><td>33.0</td><td>-14.2</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1914.30</td><td>12.37</td><td>V</td><td>0.3</td><td>4.7</td><td>16.78</td><td>33.0</td><td>-16.2</td><td colspan="2"></td></tr> <tr><td>1914.30</td><td>15.25</td><td>H</td><td>0.3</td><td>4.7</td><td>19.68</td><td>33.0</td><td>-13.3</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1850.70	11.23	V	0.3	4.7	15.64	33.0	-17.4			1850.70	16.56	H	0.3	4.7	20.92	33.0	-12.1			Mid Ch										1882.50	11.25	V	0.3	4.7	15.66	33.0	-17.3			1882.50	14.42	H	0.3	4.7	18.80	33.0	-14.2			High Ch										1914.30	12.37	V	0.3	4.7	16.78	33.0	-16.2			1914.30	15.25	H	0.3	4.7	19.68	33.0	-13.3		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1850.70	12.43	V	0.3	4.7	16.84	33.0	-16.2																																																																																																																																																																																																																				
1850.70	17.66	H	0.3	4.7	22.02	33.0	-11.0																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1882.50	12.55	V	0.3	4.7	16.96	33.0	-16.0																																																																																																																																																																																																																				
1882.50	15.82	H	0.3	4.7	20.20	33.0	-12.8																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1914.30	13.67	V	0.3	4.7	18.08	33.0	-14.9																																																																																																																																																																																																																				
1914.30	16.45	H	0.3	4.7	20.88	33.0	-12.1																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1850.70	11.23	V	0.3	4.7	15.64	33.0	-17.4																																																																																																																																																																																																																				
1850.70	16.56	H	0.3	4.7	20.92	33.0	-12.1																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1882.50	11.25	V	0.3	4.7	15.66	33.0	-17.3																																																																																																																																																																																																																				
1882.50	14.42	H	0.3	4.7	18.80	33.0	-14.2																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1914.30	12.37	V	0.3	4.7	16.78	33.0	-16.2																																																																																																																																																																																																																				
1914.30	15.25	H	0.3	4.7	19.68	33.0	-13.3																																																																																																																																																																																																																				

### 9.1.10. LTE Band 26 (FCC PART 90S)

15MHz QPSK										15MHz 16QAM																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/13/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>13.35</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>10.17</td> <td>38.5</td> <td>-28.3</td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>21.89</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>19.50</td> <td>38.5</td> <td>-20.0</td> <td></td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Mid Ch										821.50	13.35	V	3.7	0.5	10.17	38.5	-28.3			821.50	21.89	H	3.7	0.3	19.50	38.5	-20.0			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/13/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>11.92</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>8.74</td> <td>38.5</td> <td>-29.8</td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>20.55</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>17.16</td> <td>38.5</td> <td>-21.3</td> <td></td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Mid Ch										821.50	11.92	V	3.7	0.5	8.74	38.5	-29.8			821.50	20.55	H	3.7	0.3	17.16	38.5	-21.3																																																																																																																										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Mid Ch																																																																																																																																																																																																																											
821.50	13.35	V	3.7	0.5	10.17	38.5	-28.3																																																																																																																																																																																																																				
821.50	21.89	H	3.7	0.3	19.50	38.5	-20.0																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Mid Ch																																																																																																																																																																																																																											
821.50	11.92	V	3.7	0.5	8.74	38.5	-29.8																																																																																																																																																																																																																				
821.50	20.55	H	3.7	0.3	17.16	38.5	-21.3																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>12.90</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>9.74</td> <td>50.0</td> <td>-40.3</td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>21.02</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>17.64</td> <td>50.0</td> <td>-32.4</td> <td></td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Mid Ch										819.00	12.90	V	3.7	0.5	9.74	50.0	-40.3			819.00	21.02	H	3.7	0.3	17.64	50.0	-32.4			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>11.74</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>8.58</td> <td>50.0</td> <td>-41.4</td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>19.84</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>16.46</td> <td>50.0</td> <td>-33.5</td> <td></td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Mid Ch										819.00	11.74	V	3.7	0.5	8.58	50.0	-41.4			819.00	19.84	H	3.7	0.3	16.46	50.0	-33.5																																																																																																																										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Mid Ch																																																																																																																																																																																																																											
819.00	12.90	V	3.7	0.5	9.74	50.0	-40.3																																																																																																																																																																																																																				
819.00	21.02	H	3.7	0.3	17.64	50.0	-32.4																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Mid Ch																																																																																																																																																																																																																											
819.00	11.74	V	3.7	0.5	8.58	50.0	-41.4																																																																																																																																																																																																																				
819.00	19.84	H	3.7	0.3	16.46	50.0	-33.5																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Low Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>816.50</td> <td>12.68</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>9.54</td> <td>50.0</td> <td>-40.5</td> <td></td> <td></td> </tr> <tr> <td>816.50</td> <td>20.74</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>17.36</td> <td>50.0</td> <td>-32.6</td> <td></td> <td></td> </tr> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>13.07</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>9.91</td> <td>50.0</td> <td>-40.1</td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>21.08</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>17.68</td> <td>50.0</td> <td>-32.3</td> <td></td> <td></td> </tr> <tr> <td>High Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>13.67</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>10.49</td> <td>50.0</td> <td>-39.5</td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>21.48</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>19.09</td> <td>50.0</td> <td>-31.9</td> <td></td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										816.50	12.68	V	3.7	0.5	9.54	50.0	-40.5			816.50	20.74	H	3.7	0.3	17.36	50.0	-32.6			Mid Ch										819.00	13.07	V	3.7	0.5	9.91	50.0	-40.1			819.00	21.08	H	3.7	0.3	17.68	50.0	-32.3			High Ch										821.50	13.67	V	3.7	0.5	10.49	50.0	-39.5			821.50	21.48	H	3.7	0.3	19.09	50.0	-31.9			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr> <td>Low Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>816.50</td> <td>11.46</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>8.32</td> <td>50.0</td> <td>-41.7</td> <td></td> <td></td> </tr> <tr> <td>816.50</td> <td>19.55</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>16.17</td> <td>50.0</td> <td>-33.8</td> <td></td> <td></td> </tr> <tr> <td>Mid Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>11.92</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>8.76</td> <td>50.0</td> <td>-41.2</td> <td></td> <td></td> </tr> <tr> <td>819.00</td> <td>19.90</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>16.52</td> <td>50.0</td> <td>-33.5</td> <td></td> <td></td> </tr> <tr> <td>High Ch</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>12.50</td> <td>V</td> <td>3.7</td> <td>0.5</td> <td>9.32</td> <td>50.0</td> <td>-40.7</td> <td></td> <td></td> </tr> <tr> <td>821.50</td> <td>20.34</td> <td>H</td> <td>3.7</td> <td>0.3</td> <td>16.95</td> <td>50.0</td> <td>-33.0</td> <td></td> <td></td> </tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										816.50	11.46	V	3.7	0.5	8.32	50.0	-41.7			816.50	19.55	H	3.7	0.3	16.17	50.0	-33.8			Mid Ch										819.00	11.92	V	3.7	0.5	8.76	50.0	-41.2			819.00	19.90	H	3.7	0.3	16.52	50.0	-33.5			High Ch										821.50	12.50	V	3.7	0.5	9.32	50.0	-40.7			821.50	20.34	H	3.7	0.3	16.95	50.0	-33.0		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
816.50	12.68	V	3.7	0.5	9.54	50.0	-40.5																																																																																																																																																																																																																				
816.50	20.74	H	3.7	0.3	17.36	50.0	-32.6																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
819.00	13.07	V	3.7	0.5	9.91	50.0	-40.1																																																																																																																																																																																																																				
819.00	21.08	H	3.7	0.3	17.68	50.0	-32.3																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
821.50	13.67	V	3.7	0.5	10.49	50.0	-39.5																																																																																																																																																																																																																				
821.50	21.48	H	3.7	0.3	19.09	50.0	-31.9																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
816.50	11.46	V	3.7	0.5	8.32	50.0	-41.7																																																																																																																																																																																																																				
816.50	19.55	H	3.7	0.3	16.17	50.0	-33.8																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
819.00	11.92	V	3.7	0.5	8.76	50.0	-41.2																																																																																																																																																																																																																				
819.00	19.90	H	3.7	0.3	16.52	50.0	-33.5																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
821.50	12.50	V	3.7	0.5	9.32	50.0	-40.7																																																																																																																																																																																																																				
821.50	20.34	H	3.7	0.3	16.95	50.0	-33.0																																																																																																																																																																																																																				

3MHz QPSK										3MHz 16QAM																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 3MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>815.50</td><td>12.37</td><td>V</td><td>3.7</td><td>0.5</td><td>9.23</td><td>50.0</td><td>-40.8</td><td></td><td></td></tr> <tr><td>815.50</td><td>20.61</td><td>H</td><td>3.7</td><td>0.3</td><td>17.23</td><td>50.0</td><td>-32.8</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>819.00</td><td>13.23</td><td>V</td><td>3.7</td><td>0.5</td><td>10.07</td><td>50.0</td><td>-39.9</td><td></td><td></td></tr> <tr><td>819.00</td><td>20.80</td><td>H</td><td>3.7</td><td>0.3</td><td>17.42</td><td>50.0</td><td>-32.6</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>822.50</td><td>13.98</td><td>V</td><td>3.7</td><td>0.5</td><td>10.80</td><td>50.0</td><td>-39.2</td><td></td><td></td></tr> <tr><td>822.50</td><td>21.44</td><td>H</td><td>3.7</td><td>0.3</td><td>18.95</td><td>50.0</td><td>-32.0</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										815.50	12.37	V	3.7	0.5	9.23	50.0	-40.8			815.50	20.61	H	3.7	0.3	17.23	50.0	-32.8			Mid Ch										819.00	13.23	V	3.7	0.5	10.07	50.0	-39.9			819.00	20.80	H	3.7	0.3	17.42	50.0	-32.6			High Ch										822.50	13.98	V	3.7	0.5	10.80	50.0	-39.2			822.50	21.44	H	3.7	0.3	18.95	50.0	-32.0			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 3MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>815.50</td><td>11.22</td><td>V</td><td>3.7</td><td>0.5</td><td>8.08</td><td>50.0</td><td>-41.9</td><td></td><td></td></tr> <tr><td>815.50</td><td>19.53</td><td>H</td><td>3.7</td><td>0.3</td><td>16.15</td><td>50.0</td><td>-33.8</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>819.00</td><td>11.93</td><td>V</td><td>3.7</td><td>0.5</td><td>8.77</td><td>50.0</td><td>-41.2</td><td></td><td></td></tr> <tr><td>819.00</td><td>19.53</td><td>H</td><td>3.7</td><td>0.3</td><td>16.15</td><td>50.0</td><td>-33.9</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>822.50</td><td>13.07</td><td>V</td><td>3.7</td><td>0.5</td><td>9.89</td><td>50.0</td><td>-40.1</td><td></td><td></td></tr> <tr><td>822.50</td><td>20.53</td><td>H</td><td>3.7</td><td>0.3</td><td>17.14</td><td>50.0</td><td>-32.9</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										815.50	11.22	V	3.7	0.5	8.08	50.0	-41.9			815.50	19.53	H	3.7	0.3	16.15	50.0	-33.8			Mid Ch										819.00	11.93	V	3.7	0.5	8.77	50.0	-41.2			819.00	19.53	H	3.7	0.3	16.15	50.0	-33.9			High Ch										822.50	13.07	V	3.7	0.5	9.89	50.0	-40.1			822.50	20.53	H	3.7	0.3	17.14	50.0	-32.9		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
815.50	12.37	V	3.7	0.5	9.23	50.0	-40.8																																																																																																																																																																																																																				
815.50	20.61	H	3.7	0.3	17.23	50.0	-32.8																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
819.00	13.23	V	3.7	0.5	10.07	50.0	-39.9																																																																																																																																																																																																																				
819.00	20.80	H	3.7	0.3	17.42	50.0	-32.6																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
822.50	13.98	V	3.7	0.5	10.80	50.0	-39.2																																																																																																																																																																																																																				
822.50	21.44	H	3.7	0.3	18.95	50.0	-32.0																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
815.50	11.22	V	3.7	0.5	8.08	50.0	-41.9																																																																																																																																																																																																																				
815.50	19.53	H	3.7	0.3	16.15	50.0	-33.8																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
819.00	11.93	V	3.7	0.5	8.77	50.0	-41.2																																																																																																																																																																																																																				
819.00	19.53	H	3.7	0.3	16.15	50.0	-33.9																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
822.50	13.07	V	3.7	0.5	9.89	50.0	-40.1																																																																																																																																																																																																																				
822.50	20.53	H	3.7	0.3	17.14	50.0	-32.9																																																																																																																																																																																																																				
1.4MHz QPSK										1.4MHz 16QAM																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 1.4MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>814.70</td><td>12.07</td><td>V</td><td>3.7</td><td>0.5</td><td>8.94</td><td>50.0</td><td>-41.1</td><td></td><td></td></tr> <tr><td>814.70</td><td>20.02</td><td>H</td><td>3.7</td><td>0.3</td><td>16.65</td><td>50.0</td><td>-33.4</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>819.00</td><td>12.87</td><td>V</td><td>3.7</td><td>0.5</td><td>9.71</td><td>50.0</td><td>-40.3</td><td></td><td></td></tr> <tr><td>819.00</td><td>20.47</td><td>H</td><td>3.7</td><td>0.3</td><td>17.09</td><td>50.0</td><td>-32.9</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>823.30</td><td>13.51</td><td>V</td><td>3.7</td><td>0.5</td><td>10.32</td><td>50.0</td><td>-39.7</td><td></td><td></td></tr> <tr><td>823.30</td><td>21.35</td><td>H</td><td>3.7</td><td>0.3</td><td>17.96</td><td>50.0</td><td>-32.0</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										814.70	12.07	V	3.7	0.5	8.94	50.0	-41.1			814.70	20.02	H	3.7	0.3	16.65	50.0	-33.4			Mid Ch										819.00	12.87	V	3.7	0.5	9.71	50.0	-40.3			819.00	20.47	H	3.7	0.3	17.09	50.0	-32.9			High Ch										823.30	13.51	V	3.7	0.5	10.32	50.0	-39.7			823.30	21.35	H	3.7	0.3	17.96	50.0	-32.0			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 1.4MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>814.70</td><td>11.06</td><td>V</td><td>3.7</td><td>0.5</td><td>7.93</td><td>50.0</td><td>-42.1</td><td></td><td></td></tr> <tr><td>814.70</td><td>18.84</td><td>H</td><td>3.7</td><td>0.3</td><td>15.47</td><td>50.0</td><td>-34.5</td><td></td><td></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>819.00</td><td>11.61</td><td>V</td><td>3.7</td><td>0.5</td><td>8.45</td><td>50.0</td><td>-41.5</td><td></td><td></td></tr> <tr><td>819.00</td><td>19.52</td><td>H</td><td>3.7</td><td>0.3</td><td>16.14</td><td>50.0</td><td>-33.9</td><td></td><td></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>823.30</td><td>12.37</td><td>V</td><td>3.7</td><td>0.5</td><td>9.18</td><td>50.0</td><td>-40.8</td><td></td><td></td></tr> <tr><td>823.30</td><td>20.11</td><td>H</td><td>3.7</td><td>0.3</td><td>16.72</td><td>50.0</td><td>-33.3</td><td></td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										814.70	11.06	V	3.7	0.5	7.93	50.0	-42.1			814.70	18.84	H	3.7	0.3	15.47	50.0	-34.5			Mid Ch										819.00	11.61	V	3.7	0.5	8.45	50.0	-41.5			819.00	19.52	H	3.7	0.3	16.14	50.0	-33.9			High Ch										823.30	12.37	V	3.7	0.5	9.18	50.0	-40.8			823.30	20.11	H	3.7	0.3	16.72	50.0	-33.3		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
814.70	12.07	V	3.7	0.5	8.94	50.0	-41.1																																																																																																																																																																																																																				
814.70	20.02	H	3.7	0.3	16.65	50.0	-33.4																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
819.00	12.87	V	3.7	0.5	9.71	50.0	-40.3																																																																																																																																																																																																																				
819.00	20.47	H	3.7	0.3	17.09	50.0	-32.9																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
823.30	13.51	V	3.7	0.5	10.32	50.0	-39.7																																																																																																																																																																																																																				
823.30	21.35	H	3.7	0.3	17.96	50.0	-32.0																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
814.70	11.06	V	3.7	0.5	7.93	50.0	-42.1																																																																																																																																																																																																																				
814.70	18.84	H	3.7	0.3	15.47	50.0	-34.5																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
819.00	11.61	V	3.7	0.5	8.45	50.0	-41.5																																																																																																																																																																																																																				
819.00	19.52	H	3.7	0.3	16.14	50.0	-33.9																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
823.30	12.37	V	3.7	0.5	9.18	50.0	-40.8																																																																																																																																																																																																																				
823.30	20.11	H	3.7	0.3	16.72	50.0	-33.3																																																																																																																																																																																																																				

9.1.11. LTE Band 26 (FCC PART 22)

15MHz QPSK										15MHz 16QAM																																																																																																																																																																																													
<p>UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 15MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>831.50</td><td>14.85</td><td>V</td><td>3.7</td><td>0.5</td><td>11.64</td><td>38.5</td><td>-26.9</td><td></td></tr> <tr><td>831.50</td><td>22.07</td><td>H</td><td>3.7</td><td>0.3</td><td>18.66</td><td>38.5</td><td>-19.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.50</td><td>14.75</td><td>V</td><td>3.7</td><td>0.5</td><td>11.53</td><td>38.5</td><td>-27.0</td><td></td></tr> <tr><td>836.50</td><td>21.57</td><td>H</td><td>3.7</td><td>0.3</td><td>18.15</td><td>38.5</td><td>-20.4</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>841.50</td><td>14.94</td><td>V</td><td>3.7</td><td>0.5</td><td>11.70</td><td>38.5</td><td>-26.8</td><td></td></tr> <tr><td>841.50</td><td>22.15</td><td>H</td><td>3.7</td><td>0.3</td><td>18.71</td><td>38.5</td><td>-19.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									831.50	14.85	V	3.7	0.5	11.64	38.5	-26.9		831.50	22.07	H	3.7	0.3	18.66	38.5	-19.8		Mid Ch									836.50	14.75	V	3.7	0.5	11.53	38.5	-27.0		836.50	21.57	H	3.7	0.3	18.15	38.5	-20.4		High Ch									841.50	14.94	V	3.7	0.5	11.70	38.5	-26.8		841.50	22.15	H	3.7	0.3	18.71	38.5	-19.8		<p>UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 15MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>831.50</td><td>13.60</td><td>V</td><td>3.7</td><td>0.5</td><td>10.39</td><td>38.5</td><td>-28.1</td><td></td></tr> <tr><td>831.50</td><td>20.86</td><td>H</td><td>3.7</td><td>0.3</td><td>17.45</td><td>38.5</td><td>-21.1</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.50</td><td>13.71</td><td>V</td><td>3.7</td><td>0.5</td><td>10.49</td><td>38.5</td><td>-28.0</td><td></td></tr> <tr><td>836.50</td><td>20.26</td><td>H</td><td>3.7</td><td>0.3</td><td>16.84</td><td>38.5</td><td>-21.7</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>841.50</td><td>13.88</td><td>V</td><td>3.7</td><td>0.5</td><td>10.64</td><td>38.5</td><td>-27.9</td><td></td></tr> <tr><td>841.50</td><td>21.35</td><td>H</td><td>3.7</td><td>0.3</td><td>17.91</td><td>38.5</td><td>-20.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									831.50	13.60	V	3.7	0.5	10.39	38.5	-28.1		831.50	20.86	H	3.7	0.3	17.45	38.5	-21.1		Mid Ch									836.50	13.71	V	3.7	0.5	10.49	38.5	-28.0		836.50	20.26	H	3.7	0.3	16.84	38.5	-21.7		High Ch									841.50	13.88	V	3.7	0.5	10.64	38.5	-27.9		841.50	21.35	H	3.7	0.3	17.91	38.5	-20.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
831.50	14.85	V	3.7	0.5	11.64	38.5	-26.9																																																																																																																																																																																																
831.50	22.07	H	3.7	0.3	18.66	38.5	-19.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.50	14.75	V	3.7	0.5	11.53	38.5	-27.0																																																																																																																																																																																																
836.50	21.57	H	3.7	0.3	18.15	38.5	-20.4																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
841.50	14.94	V	3.7	0.5	11.70	38.5	-26.8																																																																																																																																																																																																
841.50	22.15	H	3.7	0.3	18.71	38.5	-19.8																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
831.50	13.60	V	3.7	0.5	10.39	38.5	-28.1																																																																																																																																																																																																
831.50	20.86	H	3.7	0.3	17.45	38.5	-21.1																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.50	13.71	V	3.7	0.5	10.49	38.5	-28.0																																																																																																																																																																																																
836.50	20.26	H	3.7	0.3	16.84	38.5	-21.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
841.50	13.88	V	3.7	0.5	10.64	38.5	-27.9																																																																																																																																																																																																
841.50	21.35	H	3.7	0.3	17.91	38.5	-20.6																																																																																																																																																																																																
<p>UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>829.00</td><td>14.85</td><td>V</td><td>3.7</td><td>0.5</td><td>11.64</td><td>38.5</td><td>-26.9</td><td></td></tr> <tr><td>829.00</td><td>22.15</td><td>H</td><td>3.7</td><td>0.3</td><td>18.74</td><td>38.5</td><td>-19.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.50</td><td>14.59</td><td>V</td><td>3.7</td><td>0.5</td><td>11.37</td><td>38.5</td><td>-27.1</td><td></td></tr> <tr><td>836.50</td><td>21.78</td><td>H</td><td>3.7</td><td>0.3</td><td>18.36</td><td>38.5</td><td>-20.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>844.00</td><td>15.20</td><td>V</td><td>3.7</td><td>0.5</td><td>11.96</td><td>38.5</td><td>-26.5</td><td></td></tr> <tr><td>844.00</td><td>22.31</td><td>H</td><td>3.7</td><td>0.3</td><td>18.87</td><td>38.5</td><td>-19.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									829.00	14.85	V	3.7	0.5	11.64	38.5	-26.9		829.00	22.15	H	3.7	0.3	18.74	38.5	-19.8		Mid Ch									836.50	14.59	V	3.7	0.5	11.37	38.5	-27.1		836.50	21.78	H	3.7	0.3	18.36	38.5	-20.1		High Ch									844.00	15.20	V	3.7	0.5	11.96	38.5	-26.5		844.00	22.31	H	3.7	0.3	18.87	38.5	-19.6		<p>UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>829.00</td><td>13.88</td><td>V</td><td>3.7</td><td>0.5</td><td>10.37</td><td>38.5</td><td>-28.1</td><td></td></tr> <tr><td>829.00</td><td>20.87</td><td>H</td><td>3.7</td><td>0.3</td><td>17.46</td><td>38.5</td><td>-21.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.50</td><td>13.37</td><td>V</td><td>3.7</td><td>0.5</td><td>10.15</td><td>38.5</td><td>-28.4</td><td></td></tr> <tr><td>836.50</td><td>20.52</td><td>H</td><td>3.7</td><td>0.3</td><td>17.10</td><td>38.5</td><td>-21.4</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>844.00</td><td>14.25</td><td>V</td><td>3.7</td><td>0.5</td><td>11.01</td><td>38.5</td><td>-27.5</td><td></td></tr> <tr><td>844.00</td><td>21.38</td><td>H</td><td>3.7</td><td>0.3</td><td>17.94</td><td>38.5</td><td>-20.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									829.00	13.88	V	3.7	0.5	10.37	38.5	-28.1		829.00	20.87	H	3.7	0.3	17.46	38.5	-21.0		Mid Ch									836.50	13.37	V	3.7	0.5	10.15	38.5	-28.4		836.50	20.52	H	3.7	0.3	17.10	38.5	-21.4		High Ch									844.00	14.25	V	3.7	0.5	11.01	38.5	-27.5		844.00	21.38	H	3.7	0.3	17.94	38.5	-20.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
829.00	14.85	V	3.7	0.5	11.64	38.5	-26.9																																																																																																																																																																																																
829.00	22.15	H	3.7	0.3	18.74	38.5	-19.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.50	14.59	V	3.7	0.5	11.37	38.5	-27.1																																																																																																																																																																																																
836.50	21.78	H	3.7	0.3	18.36	38.5	-20.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
844.00	15.20	V	3.7	0.5	11.96	38.5	-26.5																																																																																																																																																																																																
844.00	22.31	H	3.7	0.3	18.87	38.5	-19.6																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
829.00	13.88	V	3.7	0.5	10.37	38.5	-28.1																																																																																																																																																																																																
829.00	20.87	H	3.7	0.3	17.46	38.5	-21.0																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.50	13.37	V	3.7	0.5	10.15	38.5	-28.4																																																																																																																																																																																																
836.50	20.52	H	3.7	0.3	17.10	38.5	-21.4																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
844.00	14.25	V	3.7	0.5	11.01	38.5	-27.5																																																																																																																																																																																																
844.00	21.38	H	3.7	0.3	17.94	38.5	-20.6																																																																																																																																																																																																
<p>UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>826.50</td><td>14.77</td><td>V</td><td>3.7</td><td>0.5</td><td>11.57</td><td>38.5</td><td>-26.9</td><td></td></tr> <tr><td>826.50</td><td>22.10</td><td>H</td><td>3.7</td><td>0.3</td><td>18.70</td><td>38.5</td><td>-19.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.50</td><td>14.40</td><td>V</td><td>3.7</td><td>0.5</td><td>11.18</td><td>38.5</td><td>-27.3</td><td></td></tr> <tr><td>836.50</td><td>21.80</td><td>H</td><td>3.7</td><td>0.3</td><td>18.38</td><td>38.5</td><td>-20.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>846.50</td><td>15.57</td><td>V</td><td>3.7</td><td>0.5</td><td>12.32</td><td>38.5</td><td>-26.2</td><td></td></tr> <tr><td>846.50</td><td>22.75</td><td>H</td><td>3.7</td><td>0.3</td><td>19.30</td><td>38.5</td><td>-19.2</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									826.50	14.77	V	3.7	0.5	11.57	38.5	-26.9		826.50	22.10	H	3.7	0.3	18.70	38.5	-19.8		Mid Ch									836.50	14.40	V	3.7	0.5	11.18	38.5	-27.3		836.50	21.80	H	3.7	0.3	18.38	38.5	-20.1		High Ch									846.50	15.57	V	3.7	0.5	12.32	38.5	-26.2		846.50	22.75	H	3.7	0.3	19.30	38.5	-19.2		<p>UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>826.50</td><td>13.61</td><td>V</td><td>3.7</td><td>0.5</td><td>10.41</td><td>38.5</td><td>-28.1</td><td></td></tr> <tr><td>826.50</td><td>20.94</td><td>H</td><td>3.7</td><td>0.3</td><td>17.54</td><td>38.5</td><td>-21.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>836.50</td><td>13.26</td><td>V</td><td>3.7</td><td>0.5</td><td>10.04</td><td>38.5</td><td>-28.5</td><td></td></tr> <tr><td>836.50</td><td>20.70</td><td>H</td><td>3.7</td><td>0.3</td><td>17.28</td><td>38.5</td><td>-21.2</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>846.50</td><td>14.29</td><td>V</td><td>3.7</td><td>0.5</td><td>11.04</td><td>38.5</td><td>-27.5</td><td></td></tr> <tr><td>846.50</td><td>21.49</td><td>H</td><td>3.7</td><td>0.3</td><td>18.04</td><td>38.5</td><td>-20.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									826.50	13.61	V	3.7	0.5	10.41	38.5	-28.1		826.50	20.94	H	3.7	0.3	17.54	38.5	-21.0		Mid Ch									836.50	13.26	V	3.7	0.5	10.04	38.5	-28.5		836.50	20.70	H	3.7	0.3	17.28	38.5	-21.2		High Ch									846.50	14.29	V	3.7	0.5	11.04	38.5	-27.5		846.50	21.49	H	3.7	0.3	18.04	38.5	-20.5	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
826.50	14.77	V	3.7	0.5	11.57	38.5	-26.9																																																																																																																																																																																																
826.50	22.10	H	3.7	0.3	18.70	38.5	-19.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.50	14.40	V	3.7	0.5	11.18	38.5	-27.3																																																																																																																																																																																																
836.50	21.80	H	3.7	0.3	18.38	38.5	-20.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
846.50	15.57	V	3.7	0.5	12.32	38.5	-26.2																																																																																																																																																																																																
846.50	22.75	H	3.7	0.3	19.30	38.5	-19.2																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
826.50	13.61	V	3.7	0.5	10.41	38.5	-28.1																																																																																																																																																																																																
826.50	20.94	H	3.7	0.3	17.54	38.5	-21.0																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
836.50	13.26	V	3.7	0.5	10.04	38.5	-28.5																																																																																																																																																																																																
836.50	20.70	H	3.7	0.3	17.28	38.5	-21.2																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
846.50	14.29	V	3.7	0.5	11.04	38.5	-27.5																																																																																																																																																																																																
846.50	21.49	H	3.7	0.3	18.04	38.5	-20.5																																																																																																																																																																																																

3MHz QPSK										3MHz 16QAM																																																																																																																																																																																																																	
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 3MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>825.50</td><td>14.63</td><td>V</td><td>3.7</td><td>0.5</td><td>11.43</td><td>38.5</td><td>-27.1</td><td colspan="2"></td></tr> <tr><td>825.50</td><td>21.90</td><td>H</td><td>3.7</td><td>0.3</td><td>19.50</td><td>38.5</td><td>-20.0</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>836.50</td><td>14.13</td><td>V</td><td>3.7</td><td>0.5</td><td>10.91</td><td>38.5</td><td>-27.6</td><td colspan="2"></td></tr> <tr><td>836.50</td><td>21.59</td><td>H</td><td>3.7</td><td>0.3</td><td>18.17</td><td>38.5</td><td>-20.3</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>847.50</td><td>15.55</td><td>V</td><td>3.7</td><td>0.5</td><td>12.30</td><td>38.5</td><td>-28.2</td><td colspan="2"></td></tr> <tr><td>847.50</td><td>22.92</td><td>H</td><td>3.7</td><td>0.3</td><td>19.17</td><td>38.5</td><td>-19.3</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										825.50	14.63	V	3.7	0.5	11.43	38.5	-27.1			825.50	21.90	H	3.7	0.3	19.50	38.5	-20.0			Mid Ch										836.50	14.13	V	3.7	0.5	10.91	38.5	-27.6			836.50	21.59	H	3.7	0.3	18.17	38.5	-20.3			High Ch										847.50	15.55	V	3.7	0.5	12.30	38.5	-28.2			847.50	22.92	H	3.7	0.3	19.17	38.5	-19.3			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 3MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>825.50</td><td>13.54</td><td>V</td><td>3.7</td><td>0.5</td><td>10.34</td><td>38.5</td><td>-28.2</td><td colspan="2"></td></tr> <tr><td>825.50</td><td>20.69</td><td>H</td><td>3.7</td><td>0.3</td><td>17.29</td><td>38.5</td><td>-21.2</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>836.50</td><td>12.89</td><td>V</td><td>3.7</td><td>0.5</td><td>9.67</td><td>38.5</td><td>-28.8</td><td colspan="2"></td></tr> <tr><td>836.50</td><td>20.42</td><td>H</td><td>3.7</td><td>0.3</td><td>17.00</td><td>38.5</td><td>-21.5</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>847.50</td><td>14.61</td><td>V</td><td>3.7</td><td>0.5</td><td>11.36</td><td>38.5</td><td>-27.1</td><td colspan="2"></td></tr> <tr><td>847.50</td><td>21.85</td><td>H</td><td>3.7</td><td>0.3</td><td>18.20</td><td>38.5</td><td>-20.3</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										825.50	13.54	V	3.7	0.5	10.34	38.5	-28.2			825.50	20.69	H	3.7	0.3	17.29	38.5	-21.2			Mid Ch										836.50	12.89	V	3.7	0.5	9.67	38.5	-28.8			836.50	20.42	H	3.7	0.3	17.00	38.5	-21.5			High Ch										847.50	14.61	V	3.7	0.5	11.36	38.5	-27.1			847.50	21.85	H	3.7	0.3	18.20	38.5	-20.3		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
825.50	14.63	V	3.7	0.5	11.43	38.5	-27.1																																																																																																																																																																																																																				
825.50	21.90	H	3.7	0.3	19.50	38.5	-20.0																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
836.50	14.13	V	3.7	0.5	10.91	38.5	-27.6																																																																																																																																																																																																																				
836.50	21.59	H	3.7	0.3	18.17	38.5	-20.3																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
847.50	15.55	V	3.7	0.5	12.30	38.5	-28.2																																																																																																																																																																																																																				
847.50	22.92	H	3.7	0.3	19.17	38.5	-19.3																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
825.50	13.54	V	3.7	0.5	10.34	38.5	-28.2																																																																																																																																																																																																																				
825.50	20.69	H	3.7	0.3	17.29	38.5	-21.2																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
836.50	12.89	V	3.7	0.5	9.67	38.5	-28.8																																																																																																																																																																																																																				
836.50	20.42	H	3.7	0.3	17.00	38.5	-21.5																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
847.50	14.61	V	3.7	0.5	11.36	38.5	-27.1																																																																																																																																																																																																																				
847.50	21.85	H	3.7	0.3	18.20	38.5	-20.3																																																																																																																																																																																																																				
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 26 Fundamentals, 1.4MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>824.70</td><td>14.26</td><td>V</td><td>3.7</td><td>0.5</td><td>11.06</td><td>38.5</td><td>-27.4</td><td colspan="2"></td></tr> <tr><td>824.70</td><td>21.65</td><td>H</td><td>3.7</td><td>0.3</td><td>18.25</td><td>38.5</td><td>-20.2</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>836.50</td><td>13.72</td><td>V</td><td>3.7</td><td>0.5</td><td>10.50</td><td>38.5</td><td>-28.0</td><td colspan="2"></td></tr> <tr><td>836.50</td><td>21.32</td><td>H</td><td>3.7</td><td>0.3</td><td>17.90</td><td>38.5</td><td>-20.6</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>848.30</td><td>14.67</td><td>V</td><td>3.8</td><td>0.5</td><td>11.42</td><td>38.5</td><td>-27.1</td><td colspan="2"></td></tr> <tr><td>848.30</td><td>22.30</td><td>H</td><td>3.8</td><td>0.3</td><td>18.85</td><td>38.5</td><td>-19.7</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										824.70	14.26	V	3.7	0.5	11.06	38.5	-27.4			824.70	21.65	H	3.7	0.3	18.25	38.5	-20.2			Mid Ch										836.50	13.72	V	3.7	0.5	10.50	38.5	-28.0			836.50	21.32	H	3.7	0.3	17.90	38.5	-20.6			High Ch										848.30	14.67	V	3.8	0.5	11.42	38.5	-27.1			848.30	22.30	H	3.8	0.3	18.85	38.5	-19.7			<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/2/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 26 Fundamentals, 1.4MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Hybrid PRE0184971, and Chamber I SMA Cables                      Substitution: Dipole T416, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBd)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>824.70</td><td>13.12</td><td>V</td><td>3.7</td><td>0.5</td><td>9.92</td><td>38.5</td><td>-28.6</td><td colspan="2"></td></tr> <tr><td>824.70</td><td>20.55</td><td>H</td><td>3.7</td><td>0.3</td><td>17.15</td><td>38.5</td><td>-21.3</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>836.50</td><td>12.56</td><td>V</td><td>3.7</td><td>0.5</td><td>9.34</td><td>38.5</td><td>-29.2</td><td colspan="2"></td></tr> <tr><td>836.50</td><td>20.22</td><td>H</td><td>3.7</td><td>0.3</td><td>16.80</td><td>38.5</td><td>-21.7</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>848.30</td><td>13.65</td><td>V</td><td>3.8</td><td>0.5</td><td>10.40</td><td>38.5</td><td>-28.1</td><td colspan="2"></td></tr> <tr><td>848.30</td><td>21.26</td><td>H</td><td>3.8</td><td>0.3</td><td>17.81</td><td>38.5</td><td>-20.7</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										824.70	13.12	V	3.7	0.5	9.92	38.5	-28.6			824.70	20.55	H	3.7	0.3	17.15	38.5	-21.3			Mid Ch										836.50	12.56	V	3.7	0.5	9.34	38.5	-29.2			836.50	20.22	H	3.7	0.3	16.80	38.5	-21.7			High Ch										848.30	13.65	V	3.8	0.5	10.40	38.5	-28.1			848.30	21.26	H	3.8	0.3	17.81	38.5	-20.7		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
824.70	14.26	V	3.7	0.5	11.06	38.5	-27.4																																																																																																																																																																																																																				
824.70	21.65	H	3.7	0.3	18.25	38.5	-20.2																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
836.50	13.72	V	3.7	0.5	10.50	38.5	-28.0																																																																																																																																																																																																																				
836.50	21.32	H	3.7	0.3	17.90	38.5	-20.6																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
848.30	14.67	V	3.8	0.5	11.42	38.5	-27.1																																																																																																																																																																																																																				
848.30	22.30	H	3.8	0.3	18.85	38.5	-19.7																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
824.70	13.12	V	3.7	0.5	9.92	38.5	-28.6																																																																																																																																																																																																																				
824.70	20.55	H	3.7	0.3	17.15	38.5	-21.3																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
836.50	12.56	V	3.7	0.5	9.34	38.5	-29.2																																																																																																																																																																																																																				
836.50	20.22	H	3.7	0.3	16.80	38.5	-21.7																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
848.30	13.65	V	3.8	0.5	10.40	38.5	-28.1																																																																																																																																																																																																																				
848.30	21.26	H	3.8	0.3	17.81	38.5	-20.7																																																																																																																																																																																																																				

### 9.1.12. LTE Band 30 (FCC)

10MHz QPSK									10MHz 16QAM																																																																																																																																																																																												
<p style="text-align: center;">UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 30 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2310.00</td><td>0.00</td><td>V</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> <tr><td>2310.00</td><td>0.00</td><td>H</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2310.00</td><td>19.37</td><td>V</td><td>6.5</td><td>5.7</td><td>18.60</td><td>24.0</td><td>-5.4</td><td></td></tr> <tr><td>2310.00</td><td>21.54</td><td>H</td><td>6.5</td><td>5.7</td><td>20.77</td><td>24.0</td><td>-3.2</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2310.00</td><td>0.00</td><td>V</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> <tr><td>2310.00</td><td>0.00</td><td>H</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0		2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0		Mid Ch									2310.00	19.37	V	6.5	5.7	18.60	24.0	-5.4		2310.00	21.54	H	6.5	5.7	20.77	24.0	-3.2		High Ch									2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0		2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0		<p style="text-align: center;">UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 30 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2310.00</td><td>0.00</td><td>V</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> <tr><td>2310.00</td><td>0.00</td><td>H</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2310.00</td><td>18.47</td><td>V</td><td>6.5</td><td>5.7</td><td>17.70</td><td>24.0</td><td>-6.3</td><td></td></tr> <tr><td>2310.00</td><td>20.43</td><td>H</td><td>6.5</td><td>5.7</td><td>19.66</td><td>24.0</td><td>-4.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2310.00</td><td>0.00</td><td>V</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> <tr><td>2310.00</td><td>0.00</td><td>H</td><td>6.5</td><td>5.7</td><td>0.00</td><td>24.0</td><td>0.0</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0		2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0		Mid Ch									2310.00	18.47	V	6.5	5.7	17.70	24.0	-6.3		2310.00	20.43	H	6.5	5.7	19.66	24.0	-4.3		High Ch									2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0		2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
2310.00	19.37	V	6.5	5.7	18.60	24.0	-5.4																																																																																																																																																																																														
2310.00	21.54	H	6.5	5.7	20.77	24.0	-3.2																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
2310.00	18.47	V	6.5	5.7	17.70	24.0	-6.3																																																																																																																																																																																														
2310.00	20.43	H	6.5	5.7	19.66	24.0	-4.3																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
2310.00	0.00	V	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
2310.00	0.00	H	6.5	5.7	0.00	24.0	0.0																																																																																																																																																																																														
<p style="text-align: center;">UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 30 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2307.50</td><td>18.79</td><td>V</td><td>6.5</td><td>5.7</td><td>18.04</td><td>24.0</td><td>-6.0</td><td></td></tr> <tr><td>2307.50</td><td>20.98</td><td>H</td><td>6.5</td><td>5.7</td><td>20.23</td><td>24.0</td><td>-3.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2310.00</td><td>18.90</td><td>V</td><td>6.5</td><td>5.7</td><td>18.13</td><td>24.0</td><td>-5.9</td><td></td></tr> <tr><td>2310.00</td><td>21.46</td><td>H</td><td>6.5</td><td>5.7</td><td>20.69</td><td>24.0</td><td>-3.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2312.50</td><td>18.85</td><td>V</td><td>6.5</td><td>5.7</td><td>17.85</td><td>24.0</td><td>-6.1</td><td></td></tr> <tr><td>2312.50</td><td>21.52</td><td>H</td><td>6.5</td><td>5.7</td><td>20.72</td><td>24.0</td><td>-3.3</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2307.50	18.79	V	6.5	5.7	18.04	24.0	-6.0		2307.50	20.98	H	6.5	5.7	20.23	24.0	-3.8		Mid Ch									2310.00	18.90	V	6.5	5.7	18.13	24.0	-5.9		2310.00	21.46	H	6.5	5.7	20.69	24.0	-3.3		High Ch									2312.50	18.85	V	6.5	5.7	17.85	24.0	-6.1		2312.50	21.52	H	6.5	5.7	20.72	24.0	-3.3		<p style="text-align: center;">UL Verification Services, Inc. High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/6/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 30 Fundamentals, 5MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>2307.50</td><td>17.80</td><td>V</td><td>6.5</td><td>5.7</td><td>17.05</td><td>24.0</td><td>-6.9</td><td></td></tr> <tr><td>2307.50</td><td>19.90</td><td>H</td><td>6.5</td><td>5.7</td><td>19.15</td><td>24.0</td><td>-4.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>2310.00</td><td>17.97</td><td>V</td><td>6.5</td><td>5.7</td><td>17.20</td><td>24.0</td><td>-6.8</td><td></td></tr> <tr><td>2310.00</td><td>20.51</td><td>H</td><td>6.5</td><td>5.7</td><td>19.74</td><td>24.0</td><td>-4.3</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>2312.50</td><td>17.64</td><td>V</td><td>6.5</td><td>5.7</td><td>16.84</td><td>24.0</td><td>-7.2</td><td></td></tr> <tr><td>2312.50</td><td>20.56</td><td>H</td><td>6.5</td><td>5.7</td><td>19.76</td><td>24.0</td><td>-4.2</td><td></td></tr> </tbody> </table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2307.50	17.80	V	6.5	5.7	17.05	24.0	-6.9		2307.50	19.90	H	6.5	5.7	19.15	24.0	-4.8		Mid Ch									2310.00	17.97	V	6.5	5.7	17.20	24.0	-6.8		2310.00	20.51	H	6.5	5.7	19.74	24.0	-4.3		High Ch									2312.50	17.64	V	6.5	5.7	16.84	24.0	-7.2		2312.50	20.56	H	6.5	5.7	19.76	24.0	-4.2	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
2307.50	18.79	V	6.5	5.7	18.04	24.0	-6.0																																																																																																																																																																																														
2307.50	20.98	H	6.5	5.7	20.23	24.0	-3.8																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
2310.00	18.90	V	6.5	5.7	18.13	24.0	-5.9																																																																																																																																																																																														
2310.00	21.46	H	6.5	5.7	20.69	24.0	-3.3																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
2312.50	18.85	V	6.5	5.7	17.85	24.0	-6.1																																																																																																																																																																																														
2312.50	21.52	H	6.5	5.7	20.72	24.0	-3.3																																																																																																																																																																																														
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																													
Low Ch																																																																																																																																																																																																					
2307.50	17.80	V	6.5	5.7	17.05	24.0	-6.9																																																																																																																																																																																														
2307.50	19.90	H	6.5	5.7	19.15	24.0	-4.8																																																																																																																																																																																														
Mid Ch																																																																																																																																																																																																					
2310.00	17.97	V	6.5	5.7	17.20	24.0	-6.8																																																																																																																																																																																														
2310.00	20.51	H	6.5	5.7	19.74	24.0	-4.3																																																																																																																																																																																														
High Ch																																																																																																																																																																																																					
2312.50	17.64	V	6.5	5.7	16.84	24.0	-7.2																																																																																																																																																																																														
2312.50	20.56	H	6.5	5.7	19.76	24.0	-4.2																																																																																																																																																																																														



9.1.13. LTE Band 38 (IC)

20MHz QPSK										20MHz 16QAM																																																																																																																																																																																													
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 38 Fundamentals, 20MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2580.00</td><td>19.99</td><td>V</td><td>6.9</td><td>5.9</td><td>19.02</td><td>33.0</td><td>-14.0</td><td></td></tr> <tr><td>2580.00</td><td>21.59</td><td>H</td><td>6.9</td><td>5.9</td><td>20.62</td><td>33.0</td><td>-12.4</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>19.53</td><td>V</td><td>7.0</td><td>5.8</td><td>18.42</td><td>33.0</td><td>-14.6</td><td></td></tr> <tr><td>2595.00</td><td>21.51</td><td>H</td><td>7.0</td><td>5.8</td><td>20.40</td><td>33.0</td><td>-12.6</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2610.00</td><td>18.32</td><td>V</td><td>7.0</td><td>5.8</td><td>17.19</td><td>33.0</td><td>-15.8</td><td></td></tr> <tr><td>2610.00</td><td>19.69</td><td>H</td><td>7.0</td><td>5.8</td><td>18.56</td><td>33.0</td><td>-14.4</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2580.00	19.99	V	6.9	5.9	19.02	33.0	-14.0		2580.00	21.59	H	6.9	5.9	20.62	33.0	-12.4		Mid Ch									2595.00	19.53	V	7.0	5.8	18.42	33.0	-14.6		2595.00	21.51	H	7.0	5.8	20.40	33.0	-12.6		High Ch									2610.00	18.32	V	7.0	5.8	17.19	33.0	-15.8		2610.00	19.69	H	7.0	5.8	18.56	33.0	-14.4		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 38 Fundamentals, 20MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2580.00</td><td>18.79</td><td>V</td><td>6.9</td><td>5.9</td><td>17.82</td><td>33.0</td><td>-15.2</td><td></td></tr> <tr><td>2580.00</td><td>20.49</td><td>H</td><td>6.9</td><td>5.9</td><td>19.52</td><td>33.0</td><td>-13.5</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>18.20</td><td>V</td><td>7.0</td><td>5.8</td><td>17.09</td><td>33.0</td><td>-15.9</td><td></td></tr> <tr><td>2595.00</td><td>20.45</td><td>H</td><td>7.0</td><td>5.8</td><td>19.34</td><td>33.0</td><td>-13.7</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2610.00</td><td>17.24</td><td>V</td><td>7.0</td><td>5.8</td><td>16.11</td><td>33.0</td><td>-16.9</td><td></td></tr> <tr><td>2610.00</td><td>18.62</td><td>H</td><td>7.0</td><td>5.8</td><td>17.49</td><td>33.0</td><td>-15.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2580.00	18.79	V	6.9	5.9	17.82	33.0	-15.2		2580.00	20.49	H	6.9	5.9	19.52	33.0	-13.5		Mid Ch									2595.00	18.20	V	7.0	5.8	17.09	33.0	-15.9		2595.00	20.45	H	7.0	5.8	19.34	33.0	-13.7		High Ch									2610.00	17.24	V	7.0	5.8	16.11	33.0	-16.9		2610.00	18.62	H	7.0	5.8	17.49	33.0	-15.5	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2580.00	19.99	V	6.9	5.9	19.02	33.0	-14.0																																																																																																																																																																																																
2580.00	21.59	H	6.9	5.9	20.62	33.0	-12.4																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	19.53	V	7.0	5.8	18.42	33.0	-14.6																																																																																																																																																																																																
2595.00	21.51	H	7.0	5.8	20.40	33.0	-12.6																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2610.00	18.32	V	7.0	5.8	17.19	33.0	-15.8																																																																																																																																																																																																
2610.00	19.69	H	7.0	5.8	18.56	33.0	-14.4																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2580.00	18.79	V	6.9	5.9	17.82	33.0	-15.2																																																																																																																																																																																																
2580.00	20.49	H	6.9	5.9	19.52	33.0	-13.5																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	18.20	V	7.0	5.8	17.09	33.0	-15.9																																																																																																																																																																																																
2595.00	20.45	H	7.0	5.8	19.34	33.0	-13.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2610.00	17.24	V	7.0	5.8	16.11	33.0	-16.9																																																																																																																																																																																																
2610.00	18.62	H	7.0	5.8	17.49	33.0	-15.5																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 38 Fundamentals, 15MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2577.50</td><td>19.52</td><td>V</td><td>6.9</td><td>5.9</td><td>18.55</td><td>33.0</td><td>-14.5</td><td></td></tr> <tr><td>2577.50</td><td>21.36</td><td>H</td><td>6.9</td><td>5.9</td><td>20.39</td><td>33.0</td><td>-12.6</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>19.37</td><td>V</td><td>7.0</td><td>5.8</td><td>18.26</td><td>33.0</td><td>-14.7</td><td></td></tr> <tr><td>2595.00</td><td>21.32</td><td>H</td><td>7.0</td><td>5.8</td><td>20.21</td><td>33.0</td><td>-12.8</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2612.50</td><td>17.95</td><td>V</td><td>7.0</td><td>5.8</td><td>16.82</td><td>33.0</td><td>-16.2</td><td></td></tr> <tr><td>2612.50</td><td>19.92</td><td>H</td><td>7.0</td><td>5.8</td><td>18.39</td><td>33.0</td><td>-14.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2577.50	19.52	V	6.9	5.9	18.55	33.0	-14.5		2577.50	21.36	H	6.9	5.9	20.39	33.0	-12.6		Mid Ch									2595.00	19.37	V	7.0	5.8	18.26	33.0	-14.7		2595.00	21.32	H	7.0	5.8	20.21	33.0	-12.8		High Ch									2612.50	17.95	V	7.0	5.8	16.82	33.0	-16.2		2612.50	19.92	H	7.0	5.8	18.39	33.0	-14.6		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 38 Fundamentals, 15MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2577.50</td><td>18.55</td><td>V</td><td>6.9</td><td>5.9</td><td>17.58</td><td>33.0</td><td>-15.4</td><td></td></tr> <tr><td>2577.50</td><td>20.26</td><td>H</td><td>6.9</td><td>5.9</td><td>19.29</td><td>33.0</td><td>-13.7</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>16.42</td><td>V</td><td>7.0</td><td>5.8</td><td>17.31</td><td>33.0</td><td>-15.7</td><td></td></tr> <tr><td>2595.00</td><td>20.11</td><td>H</td><td>7.0</td><td>5.8</td><td>19.00</td><td>33.0</td><td>-14.0</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2612.50</td><td>16.98</td><td>V</td><td>7.0</td><td>5.8</td><td>15.85</td><td>33.0</td><td>-17.2</td><td></td></tr> <tr><td>2612.50</td><td>18.98</td><td>H</td><td>7.0</td><td>5.8</td><td>17.45</td><td>33.0</td><td>-15.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2577.50	18.55	V	6.9	5.9	17.58	33.0	-15.4		2577.50	20.26	H	6.9	5.9	19.29	33.0	-13.7		Mid Ch									2595.00	16.42	V	7.0	5.8	17.31	33.0	-15.7		2595.00	20.11	H	7.0	5.8	19.00	33.0	-14.0		High Ch									2612.50	16.98	V	7.0	5.8	15.85	33.0	-17.2		2612.50	18.98	H	7.0	5.8	17.45	33.0	-15.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2577.50	19.52	V	6.9	5.9	18.55	33.0	-14.5																																																																																																																																																																																																
2577.50	21.36	H	6.9	5.9	20.39	33.0	-12.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	19.37	V	7.0	5.8	18.26	33.0	-14.7																																																																																																																																																																																																
2595.00	21.32	H	7.0	5.8	20.21	33.0	-12.8																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2612.50	17.95	V	7.0	5.8	16.82	33.0	-16.2																																																																																																																																																																																																
2612.50	19.92	H	7.0	5.8	18.39	33.0	-14.6																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2577.50	18.55	V	6.9	5.9	17.58	33.0	-15.4																																																																																																																																																																																																
2577.50	20.26	H	6.9	5.9	19.29	33.0	-13.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	16.42	V	7.0	5.8	17.31	33.0	-15.7																																																																																																																																																																																																
2595.00	20.11	H	7.0	5.8	19.00	33.0	-14.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2612.50	16.98	V	7.0	5.8	15.85	33.0	-17.2																																																																																																																																																																																																
2612.50	18.98	H	7.0	5.8	17.45	33.0	-15.6																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 38 Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2576.00</td><td>19.70</td><td>V</td><td>6.9</td><td>5.9</td><td>18.70</td><td>33.0</td><td>-14.3</td><td></td></tr> <tr><td>2576.00</td><td>21.41</td><td>H</td><td>6.9</td><td>5.9</td><td>20.41</td><td>33.0</td><td>-12.6</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>18.25</td><td>V</td><td>7.0</td><td>5.8</td><td>18.14</td><td>33.0</td><td>-14.9</td><td></td></tr> <tr><td>2595.00</td><td>21.08</td><td>H</td><td>7.0</td><td>5.8</td><td>19.97</td><td>33.0</td><td>-13.0</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2615.00</td><td>16.89</td><td>V</td><td>7.0</td><td>5.8</td><td>15.73</td><td>33.0</td><td>-17.3</td><td></td></tr> <tr><td>2615.00</td><td>18.21</td><td>H</td><td>7.0</td><td>5.8</td><td>18.05</td><td>33.0</td><td>-14.9</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2576.00	19.70	V	6.9	5.9	18.70	33.0	-14.3		2576.00	21.41	H	6.9	5.9	20.41	33.0	-12.6		Mid Ch									2595.00	18.25	V	7.0	5.8	18.14	33.0	-14.9		2595.00	21.08	H	7.0	5.8	19.97	33.0	-13.0		High Ch									2615.00	16.89	V	7.0	5.8	15.73	33.0	-17.3		2615.00	18.21	H	7.0	5.8	18.05	33.0	-14.9		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 38 Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2576.00</td><td>18.68</td><td>V</td><td>6.9</td><td>5.9</td><td>17.68</td><td>33.0</td><td>-15.3</td><td></td></tr> <tr><td>2576.00</td><td>20.35</td><td>H</td><td>6.9</td><td>5.9</td><td>19.35</td><td>33.0</td><td>-13.6</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>18.13</td><td>V</td><td>7.0</td><td>5.8</td><td>17.02</td><td>33.0</td><td>-16.0</td><td></td></tr> <tr><td>2595.00</td><td>19.93</td><td>H</td><td>7.0</td><td>5.8</td><td>18.82</td><td>33.0</td><td>-14.2</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2615.00</td><td>15.97</td><td>V</td><td>7.0</td><td>5.8</td><td>14.81</td><td>33.0</td><td>-18.2</td><td></td></tr> <tr><td>2615.00</td><td>18.26</td><td>H</td><td>7.0</td><td>5.8</td><td>17.10</td><td>33.0</td><td>-15.9</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2576.00	18.68	V	6.9	5.9	17.68	33.0	-15.3		2576.00	20.35	H	6.9	5.9	19.35	33.0	-13.6		Mid Ch									2595.00	18.13	V	7.0	5.8	17.02	33.0	-16.0		2595.00	19.93	H	7.0	5.8	18.82	33.0	-14.2		High Ch									2615.00	15.97	V	7.0	5.8	14.81	33.0	-18.2		2615.00	18.26	H	7.0	5.8	17.10	33.0	-15.9	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2576.00	19.70	V	6.9	5.9	18.70	33.0	-14.3																																																																																																																																																																																																
2576.00	21.41	H	6.9	5.9	20.41	33.0	-12.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	18.25	V	7.0	5.8	18.14	33.0	-14.9																																																																																																																																																																																																
2595.00	21.08	H	7.0	5.8	19.97	33.0	-13.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2615.00	16.89	V	7.0	5.8	15.73	33.0	-17.3																																																																																																																																																																																																
2615.00	18.21	H	7.0	5.8	18.05	33.0	-14.9																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2576.00	18.68	V	6.9	5.9	17.68	33.0	-15.3																																																																																																																																																																																																
2576.00	20.35	H	6.9	5.9	19.35	33.0	-13.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	18.13	V	7.0	5.8	17.02	33.0	-16.0																																																																																																																																																																																																
2595.00	19.93	H	7.0	5.8	18.82	33.0	-14.2																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2615.00	15.97	V	7.0	5.8	14.81	33.0	-18.2																																																																																																																																																																																																
2615.00	18.26	H	7.0	5.8	17.10	33.0	-15.9																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 38 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2572.50</td><td>19.55</td><td>V</td><td>6.9</td><td>5.8</td><td>18.54</td><td>33.0</td><td>-14.5</td><td></td></tr> <tr><td>2572.50</td><td>21.39</td><td>H</td><td>6.9</td><td>5.8</td><td>20.38</td><td>33.0</td><td>-12.6</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>18.89</td><td>V</td><td>7.0</td><td>5.8</td><td>17.78</td><td>33.0</td><td>-15.2</td><td></td></tr> <tr><td>2595.00</td><td>20.42</td><td>H</td><td>7.0</td><td>5.8</td><td>19.31</td><td>33.0</td><td>-13.7</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2617.50</td><td>16.30</td><td>V</td><td>7.0</td><td>5.8</td><td>15.15</td><td>33.0</td><td>-17.9</td><td></td></tr> <tr><td>2617.50</td><td>18.85</td><td>H</td><td>7.0</td><td>5.8</td><td>17.70</td><td>33.0</td><td>-15.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2572.50	19.55	V	6.9	5.8	18.54	33.0	-14.5		2572.50	21.39	H	6.9	5.8	20.38	33.0	-12.6		Mid Ch									2595.00	18.89	V	7.0	5.8	17.78	33.0	-15.2		2595.00	20.42	H	7.0	5.8	19.31	33.0	-13.7		High Ch									2617.50	16.30	V	7.0	5.8	15.15	33.0	-17.9		2617.50	18.85	H	7.0	5.8	17.70	33.0	-15.3		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/14/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 38 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2572.50</td><td>18.51</td><td>V</td><td>6.9</td><td>5.8</td><td>17.50</td><td>33.0</td><td>-15.5</td><td></td></tr> <tr><td>2572.50</td><td>20.25</td><td>H</td><td>6.9</td><td>5.8</td><td>19.25</td><td>33.0</td><td>-13.8</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2595.00</td><td>17.73</td><td>V</td><td>7.0</td><td>5.8</td><td>16.62</td><td>33.0</td><td>-16.4</td><td></td></tr> <tr><td>2595.00</td><td>19.36</td><td>H</td><td>7.0</td><td>5.8</td><td>18.25</td><td>33.0</td><td>-14.7</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2617.50</td><td>15.50</td><td>V</td><td>7.0</td><td>5.8</td><td>14.35</td><td>33.0</td><td>-16.7</td><td></td></tr> <tr><td>2617.50</td><td>17.83</td><td>H</td><td>7.0</td><td>5.8</td><td>16.68</td><td>33.0</td><td>-16.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2572.50	18.51	V	6.9	5.8	17.50	33.0	-15.5		2572.50	20.25	H	6.9	5.8	19.25	33.0	-13.8		Mid Ch									2595.00	17.73	V	7.0	5.8	16.62	33.0	-16.4		2595.00	19.36	H	7.0	5.8	18.25	33.0	-14.7		High Ch									2617.50	15.50	V	7.0	5.8	14.35	33.0	-16.7		2617.50	17.83	H	7.0	5.8	16.68	33.0	-16.3	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2572.50	19.55	V	6.9	5.8	18.54	33.0	-14.5																																																																																																																																																																																																
2572.50	21.39	H	6.9	5.8	20.38	33.0	-12.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	18.89	V	7.0	5.8	17.78	33.0	-15.2																																																																																																																																																																																																
2595.00	20.42	H	7.0	5.8	19.31	33.0	-13.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2617.50	16.30	V	7.0	5.8	15.15	33.0	-17.9																																																																																																																																																																																																
2617.50	18.85	H	7.0	5.8	17.70	33.0	-15.3																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2572.50	18.51	V	6.9	5.8	17.50	33.0	-15.5																																																																																																																																																																																																
2572.50	20.25	H	6.9	5.8	19.25	33.0	-13.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2595.00	17.73	V	7.0	5.8	16.62	33.0	-16.4																																																																																																																																																																																																
2595.00	19.36	H	7.0	5.8	18.25	33.0	-14.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2617.50	15.50	V	7.0	5.8	14.35	33.0	-16.7																																																																																																																																																																																																
2617.50	17.83	H	7.0	5.8	16.68	33.0	-16.3																																																																																																																																																																																																

9.1.14. LTE Band 41 (FCC) HPUE

20MHz QPSK										20MHz 16QAM																																																																																																																																																																																													
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 41(FCC) Fundamentals, 20MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2506.00</td><td>23.10</td><td>V</td><td>6.6</td><td>5.7</td><td>22.24</td><td>33.0</td><td>-10.8</td><td></td></tr> <tr><td>2506.00</td><td>25.13</td><td>H</td><td>6.6</td><td>5.7</td><td>24.27</td><td>33.0</td><td>-8.7</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>20.98</td><td>V</td><td>6.9</td><td>5.8</td><td>19.88</td><td>33.0</td><td>-13.1</td><td></td></tr> <tr><td>2593.00</td><td>23.09</td><td>H</td><td>6.9</td><td>5.8</td><td>21.89</td><td>33.0</td><td>-11.0</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2680.00</td><td>13.36</td><td>V</td><td>6.9</td><td>6.0</td><td>12.45</td><td>33.0</td><td>-20.6</td><td></td></tr> <tr><td>2680.00</td><td>16.17</td><td>H</td><td>6.9</td><td>6.0</td><td>15.26</td><td>33.0</td><td>-17.7</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2506.00	23.10	V	6.6	5.7	22.24	33.0	-10.8		2506.00	25.13	H	6.6	5.7	24.27	33.0	-8.7		Mid Ch									2593.00	20.98	V	6.9	5.8	19.88	33.0	-13.1		2593.00	23.09	H	6.9	5.8	21.89	33.0	-11.0		High Ch									2680.00	13.36	V	6.9	6.0	12.45	33.0	-20.6		2680.00	16.17	H	6.9	6.0	15.26	33.0	-17.7		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 41(FCC) Fundamentals, 20MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2506.00</td><td>22.19</td><td>V</td><td>6.6</td><td>5.7</td><td>21.33</td><td>33.0</td><td>-11.7</td><td></td></tr> <tr><td>2506.00</td><td>24.28</td><td>H</td><td>6.6</td><td>5.7</td><td>23.42</td><td>33.0</td><td>-9.6</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>20.29</td><td>V</td><td>6.9</td><td>5.8</td><td>19.19</td><td>33.0</td><td>-13.8</td><td></td></tr> <tr><td>2593.00</td><td>21.97</td><td>H</td><td>6.9</td><td>5.8</td><td>20.87</td><td>33.0</td><td>-12.1</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2680.00</td><td>12.49</td><td>V</td><td>6.9</td><td>6.0</td><td>11.58</td><td>33.0</td><td>-21.4</td><td></td></tr> <tr><td>2680.00</td><td>15.07</td><td>H</td><td>6.9</td><td>6.0</td><td>14.16</td><td>33.0</td><td>-18.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2506.00	22.19	V	6.6	5.7	21.33	33.0	-11.7		2506.00	24.28	H	6.6	5.7	23.42	33.0	-9.6		Mid Ch									2593.00	20.29	V	6.9	5.8	19.19	33.0	-13.8		2593.00	21.97	H	6.9	5.8	20.87	33.0	-12.1		High Ch									2680.00	12.49	V	6.9	6.0	11.58	33.0	-21.4		2680.00	15.07	H	6.9	6.0	14.16	33.0	-18.8	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2506.00	23.10	V	6.6	5.7	22.24	33.0	-10.8																																																																																																																																																																																																
2506.00	25.13	H	6.6	5.7	24.27	33.0	-8.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	20.98	V	6.9	5.8	19.88	33.0	-13.1																																																																																																																																																																																																
2593.00	23.09	H	6.9	5.8	21.89	33.0	-11.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2680.00	13.36	V	6.9	6.0	12.45	33.0	-20.6																																																																																																																																																																																																
2680.00	16.17	H	6.9	6.0	15.26	33.0	-17.7																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2506.00	22.19	V	6.6	5.7	21.33	33.0	-11.7																																																																																																																																																																																																
2506.00	24.28	H	6.6	5.7	23.42	33.0	-9.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	20.29	V	6.9	5.8	19.19	33.0	-13.8																																																																																																																																																																																																
2593.00	21.97	H	6.9	5.8	20.87	33.0	-12.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2680.00	12.49	V	6.9	6.0	11.58	33.0	-21.4																																																																																																																																																																																																
2680.00	15.07	H	6.9	6.0	14.16	33.0	-18.8																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 41(FCC) Fundamentals, 15MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2503.50</td><td>22.85</td><td>V</td><td>6.6</td><td>5.7</td><td>21.99</td><td>33.0</td><td>-11.0</td><td></td></tr> <tr><td>2503.50</td><td>24.88</td><td>H</td><td>6.6</td><td>5.7</td><td>24.02</td><td>33.0</td><td>-9.0</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>20.40</td><td>V</td><td>6.9</td><td>5.8</td><td>19.30</td><td>33.0</td><td>-13.7</td><td></td></tr> <tr><td>2593.00</td><td>22.51</td><td>H</td><td>6.9</td><td>5.8</td><td>21.41</td><td>33.0</td><td>-11.6</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2682.50</td><td>12.98</td><td>V</td><td>6.9</td><td>6.0</td><td>12.06</td><td>33.0</td><td>-20.9</td><td></td></tr> <tr><td>2682.50</td><td>14.92</td><td>H</td><td>6.9</td><td>6.0</td><td>13.79</td><td>33.0</td><td>-19.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2503.50	22.85	V	6.6	5.7	21.99	33.0	-11.0		2503.50	24.88	H	6.6	5.7	24.02	33.0	-9.0		Mid Ch									2593.00	20.40	V	6.9	5.8	19.30	33.0	-13.7		2593.00	22.51	H	6.9	5.8	21.41	33.0	-11.6		High Ch									2682.50	12.98	V	6.9	6.0	12.06	33.0	-20.9		2682.50	14.92	H	6.9	6.0	13.79	33.0	-19.3		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 41(FCC) Fundamentals, 15MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2503.50</td><td>21.84</td><td>V</td><td>6.6</td><td>5.7</td><td>20.98</td><td>33.0</td><td>-12.0</td><td></td></tr> <tr><td>2503.50</td><td>23.98</td><td>H</td><td>6.6</td><td>5.7</td><td>22.72</td><td>33.0</td><td>-10.3</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>19.40</td><td>V</td><td>6.9</td><td>5.8</td><td>18.30</td><td>33.0</td><td>-14.7</td><td></td></tr> <tr><td>2593.00</td><td>21.41</td><td>H</td><td>6.9</td><td>5.8</td><td>20.31</td><td>33.0</td><td>-12.7</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2682.50</td><td>12.20</td><td>V</td><td>6.9</td><td>6.0</td><td>11.28</td><td>33.0</td><td>-21.7</td><td></td></tr> <tr><td>2682.50</td><td>14.07</td><td>H</td><td>6.9</td><td>6.0</td><td>13.15</td><td>33.0</td><td>-19.8</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2503.50	21.84	V	6.6	5.7	20.98	33.0	-12.0		2503.50	23.98	H	6.6	5.7	22.72	33.0	-10.3		Mid Ch									2593.00	19.40	V	6.9	5.8	18.30	33.0	-14.7		2593.00	21.41	H	6.9	5.8	20.31	33.0	-12.7		High Ch									2682.50	12.20	V	6.9	6.0	11.28	33.0	-21.7		2682.50	14.07	H	6.9	6.0	13.15	33.0	-19.8	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2503.50	22.85	V	6.6	5.7	21.99	33.0	-11.0																																																																																																																																																																																																
2503.50	24.88	H	6.6	5.7	24.02	33.0	-9.0																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	20.40	V	6.9	5.8	19.30	33.0	-13.7																																																																																																																																																																																																
2593.00	22.51	H	6.9	5.8	21.41	33.0	-11.6																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2682.50	12.98	V	6.9	6.0	12.06	33.0	-20.9																																																																																																																																																																																																
2682.50	14.92	H	6.9	6.0	13.79	33.0	-19.3																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2503.50	21.84	V	6.6	5.7	20.98	33.0	-12.0																																																																																																																																																																																																
2503.50	23.98	H	6.6	5.7	22.72	33.0	-10.3																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	19.40	V	6.9	5.8	18.30	33.0	-14.7																																																																																																																																																																																																
2593.00	21.41	H	6.9	5.8	20.31	33.0	-12.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2682.50	12.20	V	6.9	6.0	11.28	33.0	-21.7																																																																																																																																																																																																
2682.50	14.07	H	6.9	6.0	13.15	33.0	-19.8																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 41(FCC) Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2501.00</td><td>22.79</td><td>V</td><td>6.6</td><td>5.7</td><td>21.94</td><td>33.0</td><td>-11.1</td><td></td></tr> <tr><td>2501.00</td><td>24.64</td><td>H</td><td>6.6</td><td>5.7</td><td>23.79</td><td>33.0</td><td>-9.2</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>20.23</td><td>V</td><td>6.9</td><td>5.8</td><td>19.13</td><td>33.0</td><td>-13.9</td><td></td></tr> <tr><td>2593.00</td><td>22.33</td><td>H</td><td>6.9</td><td>5.8</td><td>21.23</td><td>33.0</td><td>-11.8</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2685.00</td><td>12.42</td><td>V</td><td>6.9</td><td>6.0</td><td>11.49</td><td>33.0</td><td>-21.5</td><td></td></tr> <tr><td>2685.00</td><td>15.44</td><td>H</td><td>6.9</td><td>6.0</td><td>14.51</td><td>33.0</td><td>-18.5</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2501.00	22.79	V	6.6	5.7	21.94	33.0	-11.1		2501.00	24.64	H	6.6	5.7	23.79	33.0	-9.2		Mid Ch									2593.00	20.23	V	6.9	5.8	19.13	33.0	-13.9		2593.00	22.33	H	6.9	5.8	21.23	33.0	-11.8		High Ch									2685.00	12.42	V	6.9	6.0	11.49	33.0	-21.5		2685.00	15.44	H	6.9	6.0	14.51	33.0	-18.5		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 41(FCC) Fundamentals, 10MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2501.00</td><td>21.85</td><td>V</td><td>6.6</td><td>5.7</td><td>21.00</td><td>33.0</td><td>-12.0</td><td></td></tr> <tr><td>2501.00</td><td>23.47</td><td>H</td><td>6.6</td><td>5.7</td><td>22.62</td><td>33.0</td><td>-10.4</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>19.42</td><td>V</td><td>6.9</td><td>5.8</td><td>18.32</td><td>33.0</td><td>-14.7</td><td></td></tr> <tr><td>2593.00</td><td>21.12</td><td>H</td><td>6.9</td><td>5.8</td><td>20.02</td><td>33.0</td><td>-13.0</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2685.00</td><td>11.27</td><td>V</td><td>6.9</td><td>6.0</td><td>10.34</td><td>33.0</td><td>-22.7</td><td></td></tr> <tr><td>2685.00</td><td>14.05</td><td>H</td><td>6.9</td><td>6.0</td><td>13.12</td><td>33.0</td><td>-19.9</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2501.00	21.85	V	6.6	5.7	21.00	33.0	-12.0		2501.00	23.47	H	6.6	5.7	22.62	33.0	-10.4		Mid Ch									2593.00	19.42	V	6.9	5.8	18.32	33.0	-14.7		2593.00	21.12	H	6.9	5.8	20.02	33.0	-13.0		High Ch									2685.00	11.27	V	6.9	6.0	10.34	33.0	-22.7		2685.00	14.05	H	6.9	6.0	13.12	33.0	-19.9	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2501.00	22.79	V	6.6	5.7	21.94	33.0	-11.1																																																																																																																																																																																																
2501.00	24.64	H	6.6	5.7	23.79	33.0	-9.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	20.23	V	6.9	5.8	19.13	33.0	-13.9																																																																																																																																																																																																
2593.00	22.33	H	6.9	5.8	21.23	33.0	-11.8																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2685.00	12.42	V	6.9	6.0	11.49	33.0	-21.5																																																																																																																																																																																																
2685.00	15.44	H	6.9	6.0	14.51	33.0	-18.5																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2501.00	21.85	V	6.6	5.7	21.00	33.0	-12.0																																																																																																																																																																																																
2501.00	23.47	H	6.6	5.7	22.62	33.0	-10.4																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	19.42	V	6.9	5.8	18.32	33.0	-14.7																																																																																																																																																																																																
2593.00	21.12	H	6.9	5.8	20.02	33.0	-13.0																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2685.00	11.27	V	6.9	6.0	10.34	33.0	-22.7																																																																																																																																																																																																
2685.00	14.05	H	6.9	6.0	13.12	33.0	-19.9																																																																																																																																																																																																
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_QPSK Band 41(FCC) Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2498.50</td><td>22.40</td><td>V</td><td>6.6</td><td>5.7</td><td>21.52</td><td>33.0</td><td>-11.5</td><td></td></tr> <tr><td>2498.50</td><td>24.12</td><td>H</td><td>6.6</td><td>5.7</td><td>23.24</td><td>33.0</td><td>-9.8</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>20.06</td><td>V</td><td>6.9</td><td>5.8</td><td>18.96</td><td>33.0</td><td>-14.0</td><td></td></tr> <tr><td>2593.00</td><td>21.98</td><td>H</td><td>6.9</td><td>5.8</td><td>20.86</td><td>33.0</td><td>-12.1</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2687.50</td><td>11.19</td><td>V</td><td>6.9</td><td>6.0</td><td>10.26</td><td>33.0</td><td>-22.7</td><td></td></tr> <tr><td>2687.50</td><td>14.61</td><td>H</td><td>6.9</td><td>6.0</td><td>13.68</td><td>33.0</td><td>-19.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2498.50	22.40	V	6.6	5.7	21.52	33.0	-11.5		2498.50	24.12	H	6.6	5.7	23.24	33.0	-9.8		Mid Ch									2593.00	20.06	V	6.9	5.8	18.96	33.0	-14.0		2593.00	21.98	H	6.9	5.8	20.86	33.0	-12.1		High Ch									2687.50	11.19	V	6.9	6.0	10.26	33.0	-22.7		2687.50	14.61	H	6.9	6.0	13.68	33.0	-19.3		<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/7/2020                      Test Engineer: 19480 BS                      Configuration: EUT Only                      Location: Chamber I                      Mode: LTE_16QAM Band 41(FCC) Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T862, and Chamber I SMA Cables                      Substitution: T120, Chamber I Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>EIRP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2498.50</td><td>21.01</td><td>V</td><td>6.6</td><td>5.7</td><td>20.13</td><td>33.0</td><td>-12.9</td><td></td></tr> <tr><td>2498.50</td><td>22.72</td><td>H</td><td>6.6</td><td>5.7</td><td>21.84</td><td>33.0</td><td>-11.2</td><td></td></tr> <tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2593.00</td><td>19.27</td><td>V</td><td>6.9</td><td>5.8</td><td>18.17</td><td>33.0</td><td>-14.8</td><td></td></tr> <tr><td>2593.00</td><td>21.01</td><td>H</td><td>6.9</td><td>5.8</td><td>19.91</td><td>33.0</td><td>-13.1</td><td></td></tr> <tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>2687.50</td><td>10.31</td><td>V</td><td>6.9</td><td>6.0</td><td>9.38</td><td>33.0</td><td>-23.6</td><td></td></tr> <tr><td>2687.50</td><td>13.55</td><td>H</td><td>6.9</td><td>6.0</td><td>12.62</td><td>33.0</td><td>-20.4</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2498.50	21.01	V	6.6	5.7	20.13	33.0	-12.9		2498.50	22.72	H	6.6	5.7	21.84	33.0	-11.2		Mid Ch									2593.00	19.27	V	6.9	5.8	18.17	33.0	-14.8		2593.00	21.01	H	6.9	5.8	19.91	33.0	-13.1		High Ch									2687.50	10.31	V	6.9	6.0	9.38	33.0	-23.6		2687.50	13.55	H	6.9	6.0	12.62	33.0	-20.4	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2498.50	22.40	V	6.6	5.7	21.52	33.0	-11.5																																																																																																																																																																																																
2498.50	24.12	H	6.6	5.7	23.24	33.0	-9.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	20.06	V	6.9	5.8	18.96	33.0	-14.0																																																																																																																																																																																																
2593.00	21.98	H	6.9	5.8	20.86	33.0	-12.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2687.50	11.19	V	6.9	6.0	10.26	33.0	-22.7																																																																																																																																																																																																
2687.50	14.61	H	6.9	6.0	13.68	33.0	-19.3																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
2498.50	21.01	V	6.6	5.7	20.13	33.0	-12.9																																																																																																																																																																																																
2498.50	22.72	H	6.6	5.7	21.84	33.0	-11.2																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
2593.00	19.27	V	6.9	5.8	18.17	33.0	-14.8																																																																																																																																																																																																
2593.00	21.01	H	6.9	5.8	19.91	33.0	-13.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
2687.50	10.31	V	6.9	6.0	9.38	33.0	-23.6																																																																																																																																																																																																
2687.50	13.55	H	6.9	6.0	12.62	33.0	-20.4																																																																																																																																																																																																

9.1.15. LTE Band 41 (IC)

20MHz QPSK										20MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 41 (IC) Fundamentals, 20MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 41 (IC) Fundamentals, 20MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
2510.00	20.91	V	7.3	5.8	19.42	33.0	-13.6			2510.00	19.73	V	7.3	5.8	18.24	33.0	-14.8			
2510.00	25.85	H	7.3	5.8	24.36	33.0	-8.6			2510.00	25.03	H	7.3	5.8	23.54	33.0	-9.5			
Mid Ch										Mid Ch										
2595.00	16.27	V	7.3	5.8	14.80	33.0	-18.2			2595.00	15.55	V	7.3	5.8	14.08	33.0	-18.9			
2595.00	20.86	H	7.3	5.8	19.39	33.0	-13.6			2595.00	19.90	H	7.3	5.8	18.43	33.0	-14.6			
High Ch										High Ch										
2680.00	11.55	V	7.7	6.0	9.86	33.0	-23.1			2680.00	10.40	V	7.7	6.0	8.71	33.0	-24.3			
2680.00	16.29	H	7.7	6.0	14.60	33.0	-18.4			2680.00	15.27	H	7.7	6.0	13.58	33.0	-19.4			
15MHz QPSK										15MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 41 (IC) Fundamentals, 15MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 41 (IC) Fundamentals, 15MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
2507.50	23.18	V	7.3	5.7	21.67	33.0	-11.3			2507.50	22.21	V	7.3	5.7	20.70	33.0	-12.3			
2507.50	25.43	H	7.3	5.7	23.92	33.0	-9.1			2507.50	24.56	H	7.3	5.7	23.05	33.0	-9.9			
Mid Ch										Mid Ch										
2595.00	18.19	V	7.3	5.8	16.72	33.0	-16.3			2595.00	17.42	V	7.3	5.8	15.95	33.0	-17.0			
2595.00	20.65	H	7.3	5.8	19.18	33.0	-13.8			2595.00	20.02	H	7.3	5.8	18.55	33.0	-14.4			
High Ch										High Ch										
2682.50	14.35	V	7.7	6.0	12.64	33.0	-20.4			2682.50	13.36	V	7.7	6.0	11.65	33.0	-21.4			
2682.50	17.44	H	7.7	6.0	15.73	33.0	-17.3			2682.50	16.62	H	7.7	6.0	14.91	33.0	-18.1			
10MHz QPSK										10MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 41 (IC) Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 41 (IC) Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
2505.00	22.81	V	7.3	5.7	21.29	33.0	-11.7			2505.00	21.85	V	7.3	5.7	20.33	33.0	-12.7			
2505.00	25.35	H	7.3	5.7	23.83	33.0	-9.2			2505.00	24.35	H	7.3	5.7	22.83	33.0	-10.2			
Mid Ch										Mid Ch										
2595.00	16.33	V	7.3	5.8	16.86	33.0	-16.1			2595.00	17.35	V	7.3	5.8	15.88	33.0	-17.1			
2595.00	20.33	H	7.3	5.8	18.86	33.0	-14.1			2595.00	19.54	H	7.3	5.8	18.07	33.0	-14.9			
High Ch										High Ch										
2685.00	13.91	V	7.7	6.0	12.18	33.0	-20.8			2685.00	12.92	V	7.7	6.0	11.19	33.0	-21.8			
2685.00	16.12	H	7.7	6.0	14.39	33.0	-18.6			2685.00	15.29	H	7.7	6.0	13.56	33.0	-19.4			
5MHz QPSK										5MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 41 (IC) Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/27/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 41 (IC) Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Horn T344, and Chamber K SMA Cables Substitution: T120, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
2502.50	23.33	V	7.3	5.7	21.80	33.0	-11.2			2502.50	22.26	V	7.3	5.7	20.73	33.0	-12.3			
2502.50	24.75	H	7.3	5.7	23.22	33.0	-9.8			2502.50	23.67	H	7.3	5.7	22.14	33.0	-10.9			
Mid Ch										Mid Ch										
2595.00	17.73	V	7.3	5.8	16.26	33.0	-16.7			2595.00	16.64	V	7.3	5.8	15.17	33.0	-17.8			
2595.00	19.00	H	7.3	5.8	17.53	33.0	-15.5			2595.00	17.82	H	7.3	5.8	16.35	33.0	-16.6			
High Ch										High Ch										
2687.50	13.42	V	7.7	6.0	11.67	33.0	-21.3			2687.50	12.24	V	7.7	6.0	10.49	33.0	-22.5			
2687.50	15.31	H	7.7	6.0	13.56	33.0	-19.4			2687.50	14.17	H	7.7	6.0	12.42	33.0	-20.6			

9.1.16. LTE Band 66

20MHz QPSK										20MHz 16QAM																																																																																																																																																																																													
<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/13/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_QPSK Band 66 Fundamentals, 20MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1720.00</td><td>13.20</td><td>V</td><td>0.3</td><td>5.6</td><td>18.53</td><td>30.0</td><td>-11.5</td><td></td></tr> <tr><td>1720.00</td><td>12.30</td><td>H</td><td>0.3</td><td>5.6</td><td>17.61</td><td>30.0</td><td>-12.4</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1745.00</td><td>17.90</td><td>V</td><td>0.3</td><td>5.1</td><td>22.71</td><td>30.0</td><td>-7.3</td><td></td></tr> <tr><td>1745.00</td><td>12.10</td><td>H</td><td>0.3</td><td>5.1</td><td>18.91</td><td>30.0</td><td>-13.1</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1770.00</td><td>14.90</td><td>V</td><td>0.3</td><td>4.9</td><td>19.51</td><td>30.0</td><td>-10.5</td><td></td></tr> <tr><td>1770.00</td><td>11.80</td><td>H</td><td>0.3</td><td>4.9</td><td>16.41</td><td>30.0</td><td>-13.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1720.00	13.20	V	0.3	5.6	18.53	30.0	-11.5		1720.00	12.30	H	0.3	5.6	17.61	30.0	-12.4		Mid Ch									1745.00	17.90	V	0.3	5.1	22.71	30.0	-7.3		1745.00	12.10	H	0.3	5.1	18.91	30.0	-13.1		High Ch									1770.00	14.90	V	0.3	4.9	19.51	30.0	-10.5		1770.00	11.80	H	0.3	4.9	16.41	30.0	-13.6		<p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/8/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_16QAM Band 66 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1717.50</td><td>12.00</td><td>V</td><td>0.3</td><td>5.6</td><td>17.33</td><td>30.0</td><td>-12.7</td><td></td></tr> <tr><td>1717.50</td><td>10.90</td><td>H</td><td>0.3</td><td>5.6</td><td>16.21</td><td>30.0</td><td>-13.8</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1745.00</td><td>16.50</td><td>V</td><td>0.3</td><td>5.1</td><td>21.31</td><td>30.0</td><td>-8.7</td><td></td></tr> <tr><td>1745.00</td><td>10.70</td><td>H</td><td>0.3</td><td>5.1</td><td>15.51</td><td>30.0</td><td>-14.5</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1772.50</td><td>16.20</td><td>V</td><td>0.3</td><td>4.9</td><td>20.81</td><td>30.0</td><td>-9.2</td><td></td></tr> <tr><td>1772.50</td><td>13.00</td><td>H</td><td>0.3</td><td>4.9</td><td>17.61</td><td>30.0</td><td>-12.4</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1717.50	12.00	V	0.3	5.6	17.33	30.0	-12.7		1717.50	10.90	H	0.3	5.6	16.21	30.0	-13.8		Mid Ch									1745.00	16.50	V	0.3	5.1	21.31	30.0	-8.7		1745.00	10.70	H	0.3	5.1	15.51	30.0	-14.5		High Ch									1772.50	16.20	V	0.3	4.9	20.81	30.0	-9.2		1772.50	13.00	H	0.3	4.9	17.61	30.0	-12.4	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1720.00	13.20	V	0.3	5.6	18.53	30.0	-11.5																																																																																																																																																																																																
1720.00	12.30	H	0.3	5.6	17.61	30.0	-12.4																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1745.00	17.90	V	0.3	5.1	22.71	30.0	-7.3																																																																																																																																																																																																
1745.00	12.10	H	0.3	5.1	18.91	30.0	-13.1																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1770.00	14.90	V	0.3	4.9	19.51	30.0	-10.5																																																																																																																																																																																																
1770.00	11.80	H	0.3	4.9	16.41	30.0	-13.6																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1717.50	12.00	V	0.3	5.6	17.33	30.0	-12.7																																																																																																																																																																																																
1717.50	10.90	H	0.3	5.6	16.21	30.0	-13.8																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1745.00	16.50	V	0.3	5.1	21.31	30.0	-8.7																																																																																																																																																																																																
1745.00	10.70	H	0.3	5.1	15.51	30.0	-14.5																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1772.50	16.20	V	0.3	4.9	20.81	30.0	-9.2																																																																																																																																																																																																
1772.50	13.00	H	0.3	4.9	17.61	30.0	-12.4																																																																																																																																																																																																
<p style="text-align: center;"><b>15MHz QPSK</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/8/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_QPSK Band 66 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1717.50</td><td>18.00</td><td>V</td><td>0.3</td><td>5.6</td><td>23.33</td><td>30.0</td><td>-8.7</td><td></td></tr> <tr><td>1717.50</td><td>13.30</td><td>H</td><td>0.3</td><td>5.6</td><td>18.61</td><td>30.0</td><td>-11.4</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1745.00</td><td>14.20</td><td>V</td><td>0.3</td><td>5.1</td><td>19.01</td><td>30.0</td><td>-11.0</td><td></td></tr> <tr><td>1745.00</td><td>14.70</td><td>H</td><td>0.3</td><td>5.1</td><td>19.51</td><td>30.0</td><td>-10.5</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1772.50</td><td>16.30</td><td>V</td><td>0.3</td><td>4.9</td><td>20.91</td><td>30.0</td><td>-9.1</td><td></td></tr> <tr><td>1772.50</td><td>14.10</td><td>H</td><td>0.3</td><td>4.9</td><td>18.71</td><td>30.0</td><td>-11.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1717.50	18.00	V	0.3	5.6	23.33	30.0	-8.7		1717.50	13.30	H	0.3	5.6	18.61	30.0	-11.4		Mid Ch									1745.00	14.20	V	0.3	5.1	19.01	30.0	-11.0		1745.00	14.70	H	0.3	5.1	19.51	30.0	-10.5		High Ch									1772.50	16.30	V	0.3	4.9	20.91	30.0	-9.1		1772.50	14.10	H	0.3	4.9	18.71	30.0	-11.3		<p style="text-align: center;"><b>15MHz 16QAM</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/8/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_16QAM Band 66 Fundamentals, 15MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1717.50</td><td>16.80</td><td>V</td><td>0.3</td><td>5.6</td><td>22.13</td><td>30.0</td><td>-7.9</td><td></td></tr> <tr><td>1717.50</td><td>12.00</td><td>H</td><td>0.3</td><td>5.6</td><td>17.31</td><td>30.0</td><td>-12.7</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1745.00</td><td>13.00</td><td>V</td><td>0.3</td><td>5.1</td><td>17.81</td><td>30.0</td><td>-12.2</td><td></td></tr> <tr><td>1745.00</td><td>13.50</td><td>H</td><td>0.3</td><td>5.1</td><td>18.31</td><td>30.0</td><td>-11.7</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1772.50</td><td>15.00</td><td>V</td><td>0.3</td><td>4.9</td><td>19.61</td><td>30.0</td><td>-10.4</td><td></td></tr> <tr><td>1772.50</td><td>12.80</td><td>H</td><td>0.3</td><td>4.9</td><td>17.41</td><td>30.0</td><td>-12.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1717.50	16.80	V	0.3	5.6	22.13	30.0	-7.9		1717.50	12.00	H	0.3	5.6	17.31	30.0	-12.7		Mid Ch									1745.00	13.00	V	0.3	5.1	17.81	30.0	-12.2		1745.00	13.50	H	0.3	5.1	18.31	30.0	-11.7		High Ch									1772.50	15.00	V	0.3	4.9	19.61	30.0	-10.4		1772.50	12.80	H	0.3	4.9	17.41	30.0	-12.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1717.50	18.00	V	0.3	5.6	23.33	30.0	-8.7																																																																																																																																																																																																
1717.50	13.30	H	0.3	5.6	18.61	30.0	-11.4																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1745.00	14.20	V	0.3	5.1	19.01	30.0	-11.0																																																																																																																																																																																																
1745.00	14.70	H	0.3	5.1	19.51	30.0	-10.5																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1772.50	16.30	V	0.3	4.9	20.91	30.0	-9.1																																																																																																																																																																																																
1772.50	14.10	H	0.3	4.9	18.71	30.0	-11.3																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1717.50	16.80	V	0.3	5.6	22.13	30.0	-7.9																																																																																																																																																																																																
1717.50	12.00	H	0.3	5.6	17.31	30.0	-12.7																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1745.00	13.00	V	0.3	5.1	17.81	30.0	-12.2																																																																																																																																																																																																
1745.00	13.50	H	0.3	5.1	18.31	30.0	-11.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1772.50	15.00	V	0.3	4.9	19.61	30.0	-10.4																																																																																																																																																																																																
1772.50	12.80	H	0.3	4.9	17.41	30.0	-12.6																																																																																																																																																																																																
<p style="text-align: center;"><b>10MHz QPSK</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/3/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_QPSK Band 66 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1715.00</td><td>13.70</td><td>V</td><td>0.3</td><td>5.6</td><td>19.03</td><td>30.0</td><td>-11.0</td><td></td></tr> <tr><td>1715.00</td><td>14.40</td><td>H</td><td>0.3</td><td>5.6</td><td>19.71</td><td>30.0</td><td>-10.3</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1745.00</td><td>14.30</td><td>V</td><td>0.3</td><td>5.1</td><td>19.11</td><td>30.0</td><td>-10.9</td><td></td></tr> <tr><td>1745.00</td><td>14.50</td><td>H</td><td>0.3</td><td>5.1</td><td>19.31</td><td>30.0</td><td>-10.7</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1775.00</td><td>16.70</td><td>V</td><td>0.3</td><td>4.9</td><td>21.31</td><td>30.0</td><td>-8.7</td><td></td></tr> <tr><td>1775.00</td><td>15.10</td><td>H</td><td>0.3</td><td>4.9</td><td>19.71</td><td>30.0</td><td>-10.3</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1715.00	13.70	V	0.3	5.6	19.03	30.0	-11.0		1715.00	14.40	H	0.3	5.6	19.71	30.0	-10.3		Mid Ch									1745.00	14.30	V	0.3	5.1	19.11	30.0	-10.9		1745.00	14.50	H	0.3	5.1	19.31	30.0	-10.7		High Ch									1775.00	16.70	V	0.3	4.9	21.31	30.0	-8.7		1775.00	15.10	H	0.3	4.9	19.71	30.0	-10.3		<p style="text-align: center;"><b>10MHz 16QAM</b></p> <p style="text-align: center;"><b>UL Verification Services, Inc.</b> High Frequency Substitution Measurement</p> <p><b>Company:</b> Samsung  <b>Project #:</b> 13171837  <b>Date:</b> 1/3/2020  <b>Test Engineer:</b> 19498 ER  <b>Configuration:</b> EUT Only  <b>Location:</b> Chamber J  <b>Mode:</b> LTE_16QAM Band 66 Fundamentals, 10MHz Bandwidth</p> <p><b>Test Equipment:</b>                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th>Notes</th> </tr> </thead> <tbody> <tr><td colspan="9">Low Ch</td></tr> <tr><td>1715.00</td><td>12.40</td><td>V</td><td>0.3</td><td>5.6</td><td>17.73</td><td>30.0</td><td>-12.3</td><td></td></tr> <tr><td>1715.00</td><td>13.10</td><td>H</td><td>0.3</td><td>5.6</td><td>18.41</td><td>30.0</td><td>-11.6</td><td></td></tr> <tr><td colspan="9">Mid Ch</td></tr> <tr><td>1745.00</td><td>13.30</td><td>V</td><td>0.3</td><td>5.1</td><td>18.11</td><td>30.0</td><td>-11.9</td><td></td></tr> <tr><td>1745.00</td><td>13.40</td><td>H</td><td>0.3</td><td>5.1</td><td>18.21</td><td>30.0</td><td>-11.8</td><td></td></tr> <tr><td colspan="9">High Ch</td></tr> <tr><td>1775.00</td><td>15.30</td><td>V</td><td>0.3</td><td>4.9</td><td>19.91</td><td>30.0</td><td>-10.1</td><td></td></tr> <tr><td>1775.00</td><td>13.80</td><td>H</td><td>0.3</td><td>4.9</td><td>18.41</td><td>30.0</td><td>-11.6</td><td></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1715.00	12.40	V	0.3	5.6	17.73	30.0	-12.3		1715.00	13.10	H	0.3	5.6	18.41	30.0	-11.6		Mid Ch									1745.00	13.30	V	0.3	5.1	18.11	30.0	-11.9		1745.00	13.40	H	0.3	5.1	18.21	30.0	-11.8		High Ch									1775.00	15.30	V	0.3	4.9	19.91	30.0	-10.1		1775.00	13.80	H	0.3	4.9	18.41	30.0	-11.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1715.00	13.70	V	0.3	5.6	19.03	30.0	-11.0																																																																																																																																																																																																
1715.00	14.40	H	0.3	5.6	19.71	30.0	-10.3																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1745.00	14.30	V	0.3	5.1	19.11	30.0	-10.9																																																																																																																																																																																																
1745.00	14.50	H	0.3	5.1	19.31	30.0	-10.7																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1775.00	16.70	V	0.3	4.9	21.31	30.0	-8.7																																																																																																																																																																																																
1775.00	15.10	H	0.3	4.9	19.71	30.0	-10.3																																																																																																																																																																																																
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																															
Low Ch																																																																																																																																																																																																							
1715.00	12.40	V	0.3	5.6	17.73	30.0	-12.3																																																																																																																																																																																																
1715.00	13.10	H	0.3	5.6	18.41	30.0	-11.6																																																																																																																																																																																																
Mid Ch																																																																																																																																																																																																							
1745.00	13.30	V	0.3	5.1	18.11	30.0	-11.9																																																																																																																																																																																																
1745.00	13.40	H	0.3	5.1	18.21	30.0	-11.8																																																																																																																																																																																																
High Ch																																																																																																																																																																																																							
1775.00	15.30	V	0.3	4.9	19.91	30.0	-10.1																																																																																																																																																																																																
1775.00	13.80	H	0.3	4.9	18.41	30.0	-11.6																																																																																																																																																																																																

5MHz QPSK										5MHz 16QAM																																																																																																																																																																																																																	
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_QPSK Band 66 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1712.50</td><td>13.00</td><td>V</td><td>0.3</td><td>5.6</td><td>18.33</td><td>30.0</td><td>-11.7</td><td colspan="2"></td></tr> <tr><td>1712.50</td><td>13.70</td><td>H</td><td>0.3</td><td>5.6</td><td>19.01</td><td>30.0</td><td>-11.0</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1745.00</td><td>14.50</td><td>V</td><td>0.3</td><td>5.1</td><td>19.31</td><td>30.0</td><td>-10.7</td><td colspan="2"></td></tr> <tr><td>1745.00</td><td>14.40</td><td>H</td><td>0.3</td><td>5.1</td><td>19.21</td><td>30.0</td><td>-10.8</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1777.50</td><td>16.00</td><td>V</td><td>0.3</td><td>4.9</td><td>20.61</td><td>30.0</td><td>-9.4</td><td colspan="2"></td></tr> <tr><td>1777.50</td><td>15.00</td><td>H</td><td>0.3</td><td>4.9</td><td>19.61</td><td>30.0</td><td>-10.4</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1712.50	13.00	V	0.3	5.6	18.33	30.0	-11.7			1712.50	13.70	H	0.3	5.6	19.01	30.0	-11.0			Mid Ch										1745.00	14.50	V	0.3	5.1	19.31	30.0	-10.7			1745.00	14.40	H	0.3	5.1	19.21	30.0	-10.8			High Ch										1777.50	16.00	V	0.3	4.9	20.61	30.0	-9.4			1777.50	15.00	H	0.3	4.9	19.61	30.0	-10.4			<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_16QAM Band 66 Fundamentals, 5MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1712.50</td><td>11.80</td><td>V</td><td>0.3</td><td>5.6</td><td>16.93</td><td>30.0</td><td>-13.1</td><td colspan="2"></td></tr> <tr><td>1712.50</td><td>12.40</td><td>H</td><td>0.3</td><td>5.6</td><td>17.71</td><td>30.0</td><td>-12.3</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1745.00</td><td>13.10</td><td>V</td><td>0.3</td><td>5.1</td><td>17.81</td><td>30.0</td><td>-12.1</td><td colspan="2"></td></tr> <tr><td>1745.00</td><td>13.00</td><td>H</td><td>0.3</td><td>5.1</td><td>17.81</td><td>30.0</td><td>-12.2</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1777.50</td><td>14.70</td><td>V</td><td>0.3</td><td>4.9</td><td>19.31</td><td>30.0</td><td>-10.7</td><td colspan="2"></td></tr> <tr><td>1777.50</td><td>13.70</td><td>H</td><td>0.3</td><td>4.9</td><td>18.31</td><td>30.0</td><td>-11.7</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1712.50	11.80	V	0.3	5.6	16.93	30.0	-13.1			1712.50	12.40	H	0.3	5.6	17.71	30.0	-12.3			Mid Ch										1745.00	13.10	V	0.3	5.1	17.81	30.0	-12.1			1745.00	13.00	H	0.3	5.1	17.81	30.0	-12.2			High Ch										1777.50	14.70	V	0.3	4.9	19.31	30.0	-10.7			1777.50	13.70	H	0.3	4.9	18.31	30.0	-11.7		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1712.50	13.00	V	0.3	5.6	18.33	30.0	-11.7																																																																																																																																																																																																																				
1712.50	13.70	H	0.3	5.6	19.01	30.0	-11.0																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1745.00	14.50	V	0.3	5.1	19.31	30.0	-10.7																																																																																																																																																																																																																				
1745.00	14.40	H	0.3	5.1	19.21	30.0	-10.8																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1777.50	16.00	V	0.3	4.9	20.61	30.0	-9.4																																																																																																																																																																																																																				
1777.50	15.00	H	0.3	4.9	19.61	30.0	-10.4																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1712.50	11.80	V	0.3	5.6	16.93	30.0	-13.1																																																																																																																																																																																																																				
1712.50	12.40	H	0.3	5.6	17.71	30.0	-12.3																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1745.00	13.10	V	0.3	5.1	17.81	30.0	-12.1																																																																																																																																																																																																																				
1745.00	13.00	H	0.3	5.1	17.81	30.0	-12.2																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1777.50	14.70	V	0.3	4.9	19.31	30.0	-10.7																																																																																																																																																																																																																				
1777.50	13.70	H	0.3	4.9	18.31	30.0	-11.7																																																																																																																																																																																																																				
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_QPSK Band 66 Fundamentals, 3MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1711.50</td><td>14.70</td><td>V</td><td>0.3</td><td>5.6</td><td>20.03</td><td>30.0</td><td>-10.0</td><td colspan="2"></td></tr> <tr><td>1711.50</td><td>14.10</td><td>H</td><td>0.3</td><td>5.6</td><td>19.41</td><td>30.0</td><td>-10.6</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1745.00</td><td>18.30</td><td>V</td><td>0.3</td><td>5.1</td><td>23.11</td><td>30.0</td><td>-6.9</td><td colspan="2"></td></tr> <tr><td>1745.00</td><td>13.50</td><td>H</td><td>0.3</td><td>5.1</td><td>18.31</td><td>30.0</td><td>-11.7</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1778.50</td><td>15.80</td><td>V</td><td>0.3</td><td>4.9</td><td>20.41</td><td>30.0</td><td>-9.6</td><td colspan="2"></td></tr> <tr><td>1778.50</td><td>15.00</td><td>H</td><td>0.3</td><td>4.9</td><td>19.61</td><td>30.0</td><td>-10.4</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1711.50	14.70	V	0.3	5.6	20.03	30.0	-10.0			1711.50	14.10	H	0.3	5.6	19.41	30.0	-10.6			Mid Ch										1745.00	18.30	V	0.3	5.1	23.11	30.0	-6.9			1745.00	13.50	H	0.3	5.1	18.31	30.0	-11.7			High Ch										1778.50	15.80	V	0.3	4.9	20.41	30.0	-9.6			1778.50	15.00	H	0.3	4.9	19.61	30.0	-10.4			<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_16QAM Band 66 Fundamentals, 3MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1711.50</td><td>13.40</td><td>V</td><td>0.3</td><td>5.6</td><td>18.73</td><td>30.0</td><td>-11.3</td><td colspan="2"></td></tr> <tr><td>1711.50</td><td>12.80</td><td>H</td><td>0.3</td><td>5.6</td><td>18.11</td><td>30.0</td><td>-11.9</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1745.00</td><td>17.30</td><td>V</td><td>0.3</td><td>5.1</td><td>22.11</td><td>30.0</td><td>-7.9</td><td colspan="2"></td></tr> <tr><td>1745.00</td><td>12.50</td><td>H</td><td>0.3</td><td>5.1</td><td>17.31</td><td>30.0</td><td>-12.7</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1778.50</td><td>14.60</td><td>V</td><td>0.3</td><td>4.9</td><td>19.21</td><td>30.0</td><td>-10.8</td><td colspan="2"></td></tr> <tr><td>1778.50</td><td>13.70</td><td>H</td><td>0.3</td><td>4.9</td><td>18.31</td><td>30.0</td><td>-11.7</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1711.50	13.40	V	0.3	5.6	18.73	30.0	-11.3			1711.50	12.80	H	0.3	5.6	18.11	30.0	-11.9			Mid Ch										1745.00	17.30	V	0.3	5.1	22.11	30.0	-7.9			1745.00	12.50	H	0.3	5.1	17.31	30.0	-12.7			High Ch										1778.50	14.60	V	0.3	4.9	19.21	30.0	-10.8			1778.50	13.70	H	0.3	4.9	18.31	30.0	-11.7		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1711.50	14.70	V	0.3	5.6	20.03	30.0	-10.0																																																																																																																																																																																																																				
1711.50	14.10	H	0.3	5.6	19.41	30.0	-10.6																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1745.00	18.30	V	0.3	5.1	23.11	30.0	-6.9																																																																																																																																																																																																																				
1745.00	13.50	H	0.3	5.1	18.31	30.0	-11.7																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1778.50	15.80	V	0.3	4.9	20.41	30.0	-9.6																																																																																																																																																																																																																				
1778.50	15.00	H	0.3	4.9	19.61	30.0	-10.4																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1711.50	13.40	V	0.3	5.6	18.73	30.0	-11.3																																																																																																																																																																																																																				
1711.50	12.80	H	0.3	5.6	18.11	30.0	-11.9																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1745.00	17.30	V	0.3	5.1	22.11	30.0	-7.9																																																																																																																																																																																																																				
1745.00	12.50	H	0.3	5.1	17.31	30.0	-12.7																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1778.50	14.60	V	0.3	4.9	19.21	30.0	-10.8																																																																																																																																																																																																																				
1778.50	13.70	H	0.3	4.9	18.31	30.0	-11.7																																																																																																																																																																																																																				
<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_QPSK Band 66 Fundamentals, 1.4MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn T344, and Chamber J SMA Cables                      Substitution: Horn T711, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1710.70</td><td>18.00</td><td>V</td><td>0.3</td><td>5.6</td><td>23.33</td><td>30.0</td><td>-6.7</td><td colspan="2"></td></tr> <tr><td>1710.70</td><td>13.80</td><td>H</td><td>0.3</td><td>5.6</td><td>19.11</td><td>30.0</td><td>-10.9</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1745.00</td><td>15.00</td><td>V</td><td>0.3</td><td>5.1</td><td>19.81</td><td>30.0</td><td>-10.2</td><td colspan="2"></td></tr> <tr><td>1745.00</td><td>13.70</td><td>H</td><td>0.3</td><td>5.1</td><td>18.61</td><td>30.0</td><td>-11.5</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1779.30</td><td>15.60</td><td>V</td><td>0.3</td><td>4.9</td><td>20.21</td><td>30.0</td><td>-9.8</td><td colspan="2"></td></tr> <tr><td>1779.30</td><td>14.70</td><td>H</td><td>0.3</td><td>4.9</td><td>19.31</td><td>30.0</td><td>-10.7</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1710.70	18.00	V	0.3	5.6	23.33	30.0	-6.7			1710.70	13.80	H	0.3	5.6	19.11	30.0	-10.9			Mid Ch										1745.00	15.00	V	0.3	5.1	19.81	30.0	-10.2			1745.00	13.70	H	0.3	5.1	18.61	30.0	-11.5			High Ch										1779.30	15.60	V	0.3	4.9	20.21	30.0	-9.8			1779.30	14.70	H	0.3	4.9	19.31	30.0	-10.7			<p>UL Verification Services, Inc.                      High Frequency Substitution Measurement</p> <p>Company: Samsung                      Project #: 13171837                      Date: 1/3/2020                      Test Engineer: 19498 ER                      Configuration: EUT Only                      Location: Chamber J                      Mode: LTE_16QAM Band 66 Fundamentals, 1.4MHz Bandwidth</p> <p>Test Equipment:                      Receiving: Horn PRE0199055, and Chamber J SMA Cables                      Substitution: Horn T73, Chamber J Passthrough Cables</p> <table border="1"> <thead> <tr> <th>f MHz</th> <th>SG reading (dBm)</th> <th>Ant. Pol. (H/V)</th> <th>Cable Loss (dB)</th> <th>Antenna Gain (dBi)</th> <th>ERP (dBm)</th> <th>Limit (dBm)</th> <th>Delta (dB)</th> <th colspan="2">Notes</th> </tr> </thead> <tbody> <tr><td colspan="10">Low Ch</td></tr> <tr><td>1710.70</td><td>17.50</td><td>V</td><td>0.3</td><td>5.6</td><td>22.83</td><td>30.0</td><td>-7.2</td><td colspan="2"></td></tr> <tr><td>1710.70</td><td>13.20</td><td>H</td><td>0.3</td><td>5.6</td><td>18.51</td><td>30.0</td><td>-11.5</td><td colspan="2"></td></tr> <tr><td colspan="10">Mid Ch</td></tr> <tr><td>1745.00</td><td>14.51</td><td>V</td><td>0.3</td><td>5.1</td><td>19.32</td><td>30.0</td><td>-10.7</td><td colspan="2"></td></tr> <tr><td>1745.00</td><td>13.50</td><td>H</td><td>0.3</td><td>5.1</td><td>18.31</td><td>30.0</td><td>-11.7</td><td colspan="2"></td></tr> <tr><td colspan="10">High Ch</td></tr> <tr><td>1779.30</td><td>15.10</td><td>V</td><td>0.3</td><td>4.9</td><td>19.71</td><td>30.0</td><td>-10.3</td><td colspan="2"></td></tr> <tr><td>1779.30</td><td>14.40</td><td>H</td><td>0.3</td><td>4.9</td><td>19.01</td><td>30.0</td><td>-11.0</td><td colspan="2"></td></tr> </tbody> </table>										f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		Low Ch										1710.70	17.50	V	0.3	5.6	22.83	30.0	-7.2			1710.70	13.20	H	0.3	5.6	18.51	30.0	-11.5			Mid Ch										1745.00	14.51	V	0.3	5.1	19.32	30.0	-10.7			1745.00	13.50	H	0.3	5.1	18.31	30.0	-11.7			High Ch										1779.30	15.10	V	0.3	4.9	19.71	30.0	-10.3			1779.30	14.40	H	0.3	4.9	19.01	30.0	-11.0		
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1710.70	18.00	V	0.3	5.6	23.33	30.0	-6.7																																																																																																																																																																																																																				
1710.70	13.80	H	0.3	5.6	19.11	30.0	-10.9																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1745.00	15.00	V	0.3	5.1	19.81	30.0	-10.2																																																																																																																																																																																																																				
1745.00	13.70	H	0.3	5.1	18.61	30.0	-11.5																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1779.30	15.60	V	0.3	4.9	20.21	30.0	-9.8																																																																																																																																																																																																																				
1779.30	14.70	H	0.3	4.9	19.31	30.0	-10.7																																																																																																																																																																																																																				
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																																																																																																																																																			
Low Ch																																																																																																																																																																																																																											
1710.70	17.50	V	0.3	5.6	22.83	30.0	-7.2																																																																																																																																																																																																																				
1710.70	13.20	H	0.3	5.6	18.51	30.0	-11.5																																																																																																																																																																																																																				
Mid Ch																																																																																																																																																																																																																											
1745.00	14.51	V	0.3	5.1	19.32	30.0	-10.7																																																																																																																																																																																																																				
1745.00	13.50	H	0.3	5.1	18.31	30.0	-11.7																																																																																																																																																																																																																				
High Ch																																																																																																																																																																																																																											
1779.30	15.10	V	0.3	4.9	19.71	30.0	-10.3																																																																																																																																																																																																																				
1779.30	14.40	H	0.3	4.9	19.01	30.0	-11.0																																																																																																																																																																																																																				

9.1.17. LTE Band 71

20MHz QPSK										20MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 71 Fundamentals, 20MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 71 Fundamentals, 20MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
673.00	9.64	V	3.7	1.1	7.07	34.8	-27.7			673.00	9.01	V	3.7	1.1	6.44	34.8	-28.3			
673.00	20.14	H	3.7	1.3	17.78	34.8	-17.0			673.00	19.51	H	3.7	1.3	17.15	34.8	-17.6			
Mid Ch										Mid Ch										
680.50	10.03	V	3.7	1.1	7.50	34.8	-27.3			680.50	8.83	V	3.7	1.1	6.30	34.8	-28.5			
680.50	21.78	H	3.7	1.3	19.43	34.8	-15.3			680.50	20.52	H	3.7	1.3	18.17	34.8	-16.6			
High Ch										High Ch										
688.00	9.23	V	3.7	1.2	6.74	34.8	-28.0			688.00	8.52	V	3.7	1.2	6.03	34.8	-28.7			
688.00	20.02	H	3.7	1.4	17.68	34.8	-17.1			688.00	19.33	H	3.7	1.4	16.99	34.8	-17.8			
15MHz QPSK										15MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 71 Fundamentals, 15MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 71 Fundamentals, 15MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
670.50	10.77	V	3.7	1.1	8.20	34.8	-26.6			670.50	10.07	V	3.7	1.1	7.50	34.8	-27.3			
670.50	20.39	H	3.7	1.3	18.04	34.8	-16.7			670.50	19.69	H	3.7	1.3	17.34	34.8	-17.4			
Mid Ch										Mid Ch										
680.50	12.40	V	3.7	1.1	9.87	34.8	-24.9			680.50	11.25	V	3.7	1.1	8.72	34.8	-26.1			
680.50	21.66	H	3.7	1.3	19.31	34.8	-15.5			680.50	20.47	H	3.7	1.3	18.12	34.8	-16.7			
High Ch										High Ch										
690.50	13.91	V	3.7	1.2	10.54	34.8	-24.2			690.50	12.02	V	3.7	1.2	9.55	34.8	-25.2			
690.50	21.40	H	3.7	1.4	19.06	34.8	-15.7			690.50	20.08	H	3.7	1.4	17.74	34.8	-17.0			
10MHz QPSK										10MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 71 Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 71 Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
668.00	11.57	V	3.6	1.1	9.00	34.8	-25.8			668.00	10.31	V	3.6	1.1	7.74	34.8	-27.0			
668.00	20.61	H	3.6	1.3	18.26	34.8	-16.5			668.00	19.37	H	3.6	1.3	17.02	34.8	-17.7			
Mid Ch										Mid Ch										
680.50	12.66	V	3.7	1.1	10.13	34.8	-24.6			680.50	11.24	V	3.7	1.1	8.71	34.8	-26.1			
680.50	21.82	H	3.7	1.3	19.47	34.8	-15.3			680.50	20.44	H	3.7	1.3	18.09	34.8	-16.7			
High Ch										High Ch										
693.00	13.42	V	3.7	1.2	10.96	34.8	-23.8			693.00	12.24	V	3.7	1.2	9.78	34.8	-25.0			
693.00	21.18	H	3.7	1.4	18.85	34.8	-15.9			693.00	20.00	H	3.7	1.4	17.67	34.8	-17.1			
5MHz QPSK										5MHz 16QAM										
UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_QPSK Band 71 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 13171837 Date: 2/11/2020 Test Engineer: 19480 BS Configuration: EUT Only Location: Chamber K Mode: LTE_16QAM Band 71 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Hybrid PRE0181574, and Chamber K SMA Cables Substitution: Dipole T416, Chamber K Passthrough Cables										
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes		
Low Ch										Low Ch										
665.50	11.46	V	3.6	1.1	8.88	34.8	-25.9			665.50	10.23	V	3.6	1.1	7.65	34.8	-27.1			
665.50	20.42	H	3.6	1.3	18.08	34.8	-16.7			665.50	19.21	H	3.6	1.3	16.87	34.8	-17.9			
Mid Ch										Mid Ch										
680.50	12.52	V	3.7	1.1	9.99	34.8	-24.8			680.50	11.30	V	3.7	1.1	8.77	34.8	-26.0			
680.50	21.49	H	3.7	1.3	19.14	34.8	-15.6			680.50	20.30	H	3.7	1.3	17.95	34.8	-16.8			
High Ch										High Ch										
695.50	13.29	V	3.7	1.3	10.84	34.8	-23.9			695.50	12.03	V	3.7	1.3	9.58	34.8	-25.2			
695.50	21.21	H	3.7	1.4	18.88	34.8	-15.9			695.50	20.00	H	3.7	1.4	17.67	34.8	-17.1			

## 9.2. FIELD STRENGTH OF SPURIOUS RADIATION

### RULE PART(S)

FCC: §2.1053, §22.917, §24.238, §27.53, §90.691, §90.543

ISED: RSS130§4.7, RSS132§5.5; RSS133§6.5, RSS139§6.6, RSS140§4.4 , RSS199§4.5.

### LIMITS

FCC: §22.917(a), §24.238(a), §27.53 (g), (h), §90.691

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

FCC: §27.53 (Band 13)

(c) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

(f) Emissions in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

FCC: §90.543 Emission Limitations. (Band 14)

(e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC: §27.53 (a) (Band 30)

For mobile and portable stations operating in the 2305-2315 MHz: by a factor of not less than  $43 + 10 \log (P)$  dB on all frequencies between 2360 and 2365 MHz, and not less than  $70 + 10 \log (P)$  dB above 2365 MHz.

FCC: §27.53 (m) (Band 7, 41)

At least  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.

RSS130§4.7

#### 4.7.1 General unwanted emissions limits

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least  $43 + 10 \log_{10} p$  (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

#### 4.7.2 Additional unwanted emissions limits

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

(a) the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:

- i.  $76 + 10 \log_{10} p$  (watts), dB, for base and fixed equipment and
- ii.  $65 + 10 \log_{10} p$  (watts), dB, for mobile and portable equipment

(b) the e.i.r.p. in the band 1559-1610 MHz shall not exceed  $-70$  dBW/MHz for wideband signal and  $-80$  dBW for discrete emission with bandwidth less than 700 Hz.

RSS132§5.5

Mobile and base station equipment shall comply with the limits in (i) and (ii) below.

- (iii) In the first 1.0 MHz band immediately outside and adjacent to each of the sub-bands specified in Section 5.1, the power of emissions per any 1% of the occupied bandwidth shall be attenuated (in dB) below the transmitter output power  $P$  (dBW) by at least  $43 + 10 \log_{10} p$  (watts).
- (iv) After the first 1.0 MHz immediately outside and adjacent to each of the sub-bands, the power of emissions in any 100 kHz bandwidth shall be attenuated (in dB) below the transmitter output power  $P$  (dBW) by at least  $43 + 10 \log_{10} p$  (watts). If the measurement is performed using 1% of the occupied bandwidth, power integration over 100 kHz is required.

#### RSS133§6.5

Equipment shall comply with the limits in (i) and (ii) below.

- (iii) In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power  $P$  (dBW) by at least  $43 + 10 \log_{10} p$  (watts).
- (iv) After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power  $P$  (dBW) by at least  $43 + 10 \log_{10} p$  (watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.

#### RSS139§6.6

- (iii) (i) In the first 1.0 MHz bands immediately outside and adjacent to the equipment's smallest operating frequency block, Footnote 2 which can contain the equipment's occupied bandwidth, the emission power per any 1% of the emission bandwidth shall be attenuated below the transmitter output power  $P$  (in dBW) by at least  $43 + 10 \log_{10} p$  (watts) dB.
- (iv) (ii) After the first 1.0 MHz outside the equipment's smallest operating frequency block, which can contain the equipment's occupied bandwidth, the emission power in any 1 MHz bandwidth shall be attenuated below the transmitter output power  $P$  (in dBW) by at least  $43 + 10 \log_{10} p$  (watts) dB.

#### RSS140§4.4 (Band 14)

The power of any unwanted emission outside the bands 758-768 MHz and 788-798 MHz shall be attenuated below the transmitter output power  $P$  in dBW as follows, where  $p$  is the transmitter output power in watts:

- a. For any frequency between 769-775 MHz and 799-806 MHz:
  - i.  $76 + 10 \log(p)$ , dB in a 6.25 kHz band for fixed and base station equipment
  - ii.  $65 + 10 \log(p)$ , dB in a 6.25 kHz band for mobile and portable/hand-held equipment
- b. For any frequency between 775-788 MHz, above 806 MHz, and below 758 MHz:  $43 + 10 \log(p)$ , dB in a bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency bands 758-768 MHz and 788-798 MHz, a resolution bandwidth of 30 kHz may be employed.

In addition, the equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed  $-70$  dBW/MHz for wideband emissions, and  $-80$  dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

#### RSS199§4.5

Equipment shall comply with the following unwanted emission limits:

- a. for base station and fixed subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power,  $P$  (dBW), by at least  $43 + 10 \log_{10} p$
- b. for mobile subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power,  $P$  (dBW), by at least:
  - i.  $40 + 10 \log_{10} p$  from the channel edges to 5 MHz away
  - ii.  $43 + 10 \log_{10} p$  between 5 MHz and  $X$  MHz from the channel edges, and



iii.  $55 + 10 \log_{10} p$  at X MHz and beyond from the channel edges

In addition, the attenuation shall not be less than  $43 + 10 \log_{10} p$  on all frequencies between 2490.5 MHz and 2496 MHz, and  $55 + 10 \log_{10} p$  at or below 2490.5 MHz.

In (a) and (b), **p** is the transmitter power measured in watts and **X** is 6 MHz or the equipment occupied bandwidth, whichever is greater.

### **TEST PROCEDURE**

KDB 971168 D01 v03r01/D02 v02/r01

All tests above 1GHz were done with a Resolution Bandwidth of 1MHz, and a Video Bandwidth of 3MHz.

### **RESULTS**

No spurious emissions were detected above system noise floor from 18-26GHz.

**9.2.1. GSM 850**

**GPRS MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	GPRS 850
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
824.2 MHz												
1	1.64813	-64.32	Pk	28.5	-31.7	12.5	-55.02	-13	-42.02	0-360	149	H
2	2.47263	-58.37	Pk	32.3	-30.4	11.3	-45.17	-13	-32.17	0-360	149	H
3	3.29978	-71.36	Pk	32.7	-29.2	11.7	-56.16	-13	-43.16	0-360	149	H
4	1.64759	-64.55	Pk	28.5	-31.7	11.4	-56.35	-13	-43.35	0-360	149	V
5	2.47263	-56.47	Pk	32.3	-30.4	11.6	-42.97	-13	-29.97	0-360	149	V
6	3.30084	-70.99	Pk	32.7	-29.3	12	-55.59	-13	-42.59	0-360	149	V
836.6 MHz												
1	1.67256	-57.02	Pk	28.8	-31.6	11.6	-48.22	-13	-35.22	0-360	149	H
2	2.50981	-58.07	Pk	32.3	-30.1	11.4	-44.47	-13	-31.47	0-360	149	H
3	3.34441	-71.78	Pk	32.7	-29.2	11.5	-56.78	-13	-43.78	0-360	149	H
4	1.67256	-59.2	Pk	28.8	-31.6	10.9	-51.1	-13	-38.1	0-360	149	V
5	2.50928	-61.85	Pk	32.3	-30.2	11.4	-48.35	-13	-35.35	0-360	149	V
6	3.34813	-71.32	Pk	32.7	-29.2	11.9	-55.92	-13	-42.92	0-360	149	V
848.8 MHz												
1	1.69753	-49.85	Pk	29.2	-31.5	11.2	-40.95	-13	-27.95	0-360	149	H
2	2.54647	-68.45	Pk	32.3	-30.1	12	-54.25	-13	-41.25	0-360	149	H
3	3.39966	-71.65	Pk	32.7	-29.2	11.9	-56.25	-13	-43.25	0-360	149	H
4	1.697	-59.62	Pk	29.2	-31.5	12.2	-49.72	-13	-36.72	0-360	149	V
5	2.54647	-65.67	Pk	32.3	-30.1	11.8	-51.67	-13	-38.67	0-360	149	V
6	3.40125	-71.55	Pk	32.7	-29.2	11.7	-56.35	-13	-43.35	0-360	149	V

**EGPRS MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	EGPRS 850
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
824.2 MHz												
1	1.64813	-54.23	Pk	28.5	-31.7	12.5	-44.93	-13	-31.93	0-360	149	H
2	2.47209	-59.3	Pk	32.3	-30.4	11.3	-46.1	-13	-33.1	0-360	149	H
3	3.29766	-70.73	Pk	32.7	-29.2	11.9	-55.33	-13	-42.33	0-360	149	H
4	1.64813	-58.87	Pk	28.5	-31.7	11.4	-50.67	-13	-37.67	0-360	149	V
5	2.47209	-58.09	Pk	32.3	-30.4	11.6	-44.59	-13	-31.59	0-360	149	V
6	3.29872	-70.55	Pk	32.7	-29.2	12	-55.05	-13	-42.05	0-360	149	V
836.6 MHz												
1	1.67309	-52.57	Pk	28.8	-31.6	11.6	-43.77	-13	-30.77	0-360	149	H
2	2.50981	-53.56	Pk	32.3	-30.1	11.4	-39.96	-13	-26.96	0-360	149	H
3	3.34972	-70.96	Pk	32.7	-29.2	11.4	-56.06	-13	-43.06	0-360	149	H
4	1.67256	-61.37	Pk	28.8	-31.6	10.9	-53.27	-13	-40.27	0-360	149	V
5	2.50981	-58.03	Pk	32.3	-30.1	11.4	-44.43	-13	-31.43	0-360	149	V
6	3.34919	-71.17	Pk	32.7	-29.2	11.9	-55.77	-13	-42.77	0-360	149	V
848.8 MHz												
1	1.69753	-64.84	Pk	29.2	-31.5	11.2	-55.94	-13	-42.94	0-360	149	H
2	2.54381	-73	Pk	32.2	-30.1	12.2	-58.7	-13	-45.7	0-360	149	H
3	3.39541	-71.28	Pk	32.6	-29.2	11.8	-56.08	-13	-43.08	0-360	149	H
4	1.697	-62.31	Pk	29.2	-31.5	12.2	-52.41	-13	-39.41	0-360	149	V
5	2.54488	-70.82	Pk	32.2	-30.1	11.8	-56.92	-13	-43.92	0-360	149	V
6	3.39806	-71.28	Pk	32.7	-29.2	11.7	-56.08	-13	-43.08	0-360	149	V

**9.2.2. GSM 1900**

**GPRS MODE**

Company:	Samsung
Project #:	13171837
Date:	12/28/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	GPRS 1900
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1850.2 MHz												
1	3.70034	-71.82	Pk	33	-28.7	11.9	-55.62	-13	-42.62	0-360	150	H
2	5.55016	-76.42	Pk	35.1	-26.8	12	-56.12	-13	-43.12	0-360	150	H
3	7.38297	-78.16	Pk	35.6	-24.2	12	-54.76	-13	-41.76	0-360	150	H
4	3.70034	-71.82	Pk	33	-28.7	11.9	-55.62	-13	-42.62	0-360	150	H
5	5.55016	-76.42	Pk	35.1	-26.8	12	-56.12	-13	-43.12	0-360	150	H
6	7.38297	-78.16	Pk	35.6	-24.2	12	-54.76	-13	-41.76	0-360	150	H
1880 MHz												
1	3.75878	-75.51	Pk	32.9	-28.4	11.8	-59.21	-13	-46.21	0-360	149	H
2	5.63409	-76.05	Pk	35	-26.6	11.7	-55.95	-13	-42.95	0-360	149	H
3	7.51153	-78.28	Pk	35.6	-23.8	12.1	-54.38	-13	-41.38	0-360	149	H
4	3.76091	-75.22	Pk	33	-28.4	11.8	-58.82	-13	-45.82	0-360	149	V
5	5.64259	-76.6	Pk	35.1	-26.6	11.9	-56.2	-13	-43.2	0-360	149	V
6	7.52641	-77.53	Pk	35.6	-23.9	11.7	-54.13	-13	-41.13	0-360	149	V
1909.8 MHz												
1	3.81669	-76.57	Pk	32.9	-28.3	11.7	-60.27	-13	-47.27	0-360	149	H
2	5.72813	-77.13	Pk	34.9	-26.6	11.8	-57.03	-13	-44.03	0-360	149	H
3	7.64647	-77.5	Pk	35.6	-24.1	11.6	-54.4	-13	-41.4	0-360	149	H
4	3.81456	-75.75	Pk	32.9	-28.4	11.4	-59.85	-13	-46.85	0-360	149	V
5	5.72441	-75.74	Pk	34.9	-26.7	11.8	-55.74	-13	-42.74	0-360	149	V
6	7.63903	-78.2	Pk	35.6	-24.1	11.8	-54.9	-13	-41.9	0-360	149	V

**EGPRS MODE**

Company:	Samsung
Project #:	13171837
Date:	12/28/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	EGPRS 1900
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1850.2 MHz												
1	3.70566	-75.05	Pk	33	-28.6	11.8	-58.85	-13	-45.85	0-360	149	H
2	5.55653	-76.3	Pk	35.1	-26.8	11.9	-56.1	-13	-43.1	0-360	149	H
3	7.40741	-77.83	Pk	35.5	-24.4	11.6	-55.13	-13	-42.13	0-360	149	H
4	3.69663	-75.23	Pk	33	-28.8	12.1	-58.93	-13	-45.93	0-360	149	V
5	5.55016	-75.7	Pk	35.1	-26.8	12.2	-55.2	-13	-42.2	0-360	149	V
6	7.39891	-78.3	Pk	35.6	-24.3	11.8	-55.2	-13	-42.2	0-360	149	V
1880 MHz												
1	3.75081	-75.08	Pk	33	-28.4	11.7	-58.78	-13	-45.78	0-360	149	H
2	5.62825	-76.16	Pk	35.2	-26.6	11.4	-56.16	-13	-43.16	0-360	149	H
3	7.51844	-77.87	Pk	35.5	-23.9	12	-54.27	-13	-41.27	0-360	149	H
4	3.76303	-76.48	Pk	33	-28.3	11.8	-59.98	-13	-46.98	0-360	149	V
5	5.64047	-76.64	Pk	35.1	-26.7	11.9	-56.34	-13	-43.34	0-360	149	V
6	7.51206	-78.64	Pk	35.6	-23.9	12.2	-54.74	-13	-41.74	0-360	149	V
1909.8 MHz												
1	3.82413	-75.52	Pk	32.9	-28.2	11.4	-59.42	-13	-46.42	0-360	149	H
2	5.72866	-76.71	Pk	34.9	-26.6	11.8	-56.61	-13	-43.61	0-360	149	H
3	7.65922	-78.53	Pk	35.7	-24	11.7	-55.13	-13	-42.13	0-360	149	H
4	3.82147	-76.62	Pk	32.9	-28.2	11.2	-60.72	-13	-47.72	0-360	149	V
5	5.72972	-76.46	Pk	34.9	-26.6	11.6	-56.56	-13	-43.56	0-360	149	V
6	7.63106	-78.71	Pk	35.6	-24.1	12	-55.21	-13	-42.21	0-360	149	V

**9.2.3. CDMA BC10**

**1xRTT MODE**

Company:	Samsung
Project #:	13171837
Date:	1/13/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	1xRTT BC10
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
817.25 MHz												
1	1.63431	-66.16	Pk	28.4	-31.6	12.2	-57.16	-13	-44.16	0-360	149	H
2	2.45084	-68.83	Pk	32.2	-30.4	11.4	-55.63	-13	-42.63	0-360	149	H
3	3.26791	-72.16	Pk	32.8	-29.2	12	-56.56	-13	-43.56	0-360	149	H
4	1.63378	-69.29	Pk	28.4	-31.6	11.4	-61.09	-13	-48.09	0-360	149	V
5	2.45138	-70.78	Pk	32.2	-30.4	11.5	-57.48	-13	-44.48	0-360	149	V
6	3.26738	-73.77	Pk	32.9	-29.2	11.7	-58.37	-13	-45.37	0-360	149	V
820 MHz												
1	1.63963	-67.57	Pk	28.4	-31.7	12.3	-58.57	-13	-45.57	0-360	149	H
2	2.45988	-71.06	Pk	32.3	-30.4	11.5	-57.66	-13	-44.66	0-360	149	H
3	3.28172	-73.34	Pk	32.8	-29.2	12.1	-57.64	-13	-44.64	0-360	149	H
4	1.63963	-68.24	Pk	28.4	-31.7	11.6	-59.94	-13	-46.94	0-360	149	V
5	2.45403	-70.81	Pk	32.2	-30.4	11.3	-57.71	-13	-44.71	0-360	149	V
6	3.28544	-70.27	Pk	32.8	-29.1	12	-54.57	-13	-41.57	0-360	149	V
822.75 MHz												
1	1.64547	-66.26	Pk	28.5	-31.7	12.4	-57.06	-13	-44.06	0-360	149	H
2	2.46731	-67.88	Pk	32.3	-30.4	11.3	-54.68	-13	-41.68	0-360	149	H
3	3.28916	-71.12	Pk	32.8	-29.2	12.2	-55.32	-13	-42.32	0-360	149	H
4	1.64547	-68.73	Pk	28.5	-31.7	11.4	-60.53	-13	-47.53	0-360	149	V
5	2.47103	-71.28	Pk	32.3	-30.4	11.6	-57.78	-13	-44.78	0-360	149	V
6	3.28916	-71.86	Pk	32.8	-29.2	12	-56.26	-13	-43.26	0-360	149	V

**1xEV-DO REV A MODE**

Company:	Samsung
Project #:	13171837
Date:	1/13/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	1xEV-DO REV A BC10
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
817.25 MHz												
1	1.63484	-61.86	Pk	28.4	-31.6	12.2	-52.86	-13	-39.86	0-360	149	H
2	2.45244	-68.56	Pk	32.2	-30.4	11.6	-55.16	-13	-42.16	0-360	149	H
3	3.26844	-71.21	Pk	32.8	-29.2	12	-55.61	-13	-42.61	0-360	149	H
4	1.63431	-66.03	Pk	28.4	-31.6	11.5	-57.73	-13	-44.73	0-360	149	V
5	2.45244	-67.71	Pk	32.2	-30.4	11.5	-54.41	-13	-41.41	0-360	149	V
6	3.26472	-71.28	Pk	32.9	-29.2	11.8	-55.78	-13	-42.78	0-360	149	V
820 MHz												
1	1.64016	-65.09	Pk	28.5	-31.8	12.3	-56.09	-13	-43.09	0-360	149	H
2	2.46041	-68.19	Pk	32.3	-30.4	11.5	-54.79	-13	-41.79	0-360	149	H
3	3.28013	-71.86	Pk	32.8	-29.2	12.1	-56.16	-13	-43.16	0-360	149	H
4	1.64069	-67.5	Pk	28.5	-31.8	11.5	-59.3	-13	-46.3	0-360	149	V
5	2.46094	-69.49	Pk	32.3	-30.4	11.1	-56.49	-13	-43.49	0-360	149	V
6	3.28172	-71.64	Pk	32.8	-29.2	11.9	-56.14	-13	-43.14	0-360	149	V
822.75 MHz												
1	1.64441	-63.57	Pk	28.5	-31.7	12.3	-54.47	-13	-41.47	0-360	149	H
2	2.46891	-67.25	Pk	32.3	-30.4	11.3	-54.05	-13	-41.05	0-360	149	H
3	3.29288	-72.11	Pk	32.8	-29.2	12.1	-56.41	-13	-43.41	0-360	149	H
4	1.64494	-68.68	Pk	28.5	-31.7	11.4	-60.48	-13	-47.48	0-360	149	V
5	2.46784	-70.1	Pk	32.3	-30.4	11.4	-56.8	-13	-43.8	0-360	149	V
6	3.29181	-73.08	Pk	32.8	-29.2	11.9	-57.58	-13	-44.58	0-360	149	V

**9.2.4. CDMA BC0**

**1xRTT MODE**

Company:	Samsung
Project #:	13171837
Date:	1/08/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	1xRTT BC0
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
824.7 MHz												
1	1.64441	-67.2	Pk	28.5	-31.7	12.3	-58.1	-13	-45.1	0-360	149	H
2	2.47422	-68.5	Pk	32.3	-30.4	11.3	-55.3	-13	-42.3	0-360	149	H
3	3.30456	-70.98	Pk	32.7	-29.3	11.6	-55.98	-13	-42.98	0-360	149	H
4	1.64228	-68.83	Pk	28.5	-31.7	11.5	-60.53	-13	-47.53	0-360	149	V
5	2.47422	-69.63	Pk	32.3	-30.4	11.5	-56.23	-13	-43.23	0-360	149	V
6	3.29925	-72.43	Pk	32.7	-29.2	12	-56.93	-13	-43.93	0-360	149	V
836.52 MHz												
1	1.67309	-68.73	Pk	28.8	-31.6	11.6	-59.93	-13	-46.93	0-360	149	H
2	2.50822	-69.62	Pk	32.3	-30.2	11.4	-56.12	-13	-43.12	0-360	149	H
3	3.34281	-69.52	Pk	32.7	-29.3	11.5	-54.62	-13	-41.62	0-360	149	H
4	1.67734	-69.53	Pk	28.9	-31.6	11	-61.23	-13	-48.23	0-360	149	V
5	2.51406	-70.75	Pk	32.3	-30.1	11.3	-57.25	-13	-44.25	0-360	149	V
6	3.35184	-70.17	Pk	32.6	-29.2	11.8	-54.97	-13	-41.97	0-360	149	V
848.3 MHz												
1	1.69647	-68.76	Pk	29.1	-31.5	11.2	-59.96	-13	-46.96	0-360	149	H
2	2.54222	-69.78	Pk	32.2	-30.1	12.3	-55.38	-13	-42.38	0-360	149	H
3	3.39169	-71.52	Pk	32.6	-29.2	11.7	-56.42	-13	-43.42	0-360	149	H
4	1.69913	-69.39	Pk	29.2	-31.6	12	-59.79	-13	-46.79	0-360	149	V
5	2.54966	-69.66	Pk	32.3	-30.1	11.7	-55.76	-13	-42.76	0-360	149	V
6	3.39222	-70.69	Pk	32.6	-29.2	11.9	-55.39	-13	-42.39	0-360	149	V



**1xEV-DO REV A MODE**

Company:	Samsung
Project #:	13171837
Date:	1/08/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	1xEV-DO REV A BC0
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
824.7 MHz												
1	1.64972	-68.52	Pk	28.5	-31.7	12.5	-59.22	-13	-46.22	0-360	149	H
2	2.47369	-69.04	Pk	32.3	-30.4	11.3	-55.84	-13	-42.84	0-360	149	H
3	3.29234	-71.48	Pk	32.8	-29.2	12.1	-55.78	-13	-42.78	0-360	149	H
4	1.64972	-69.62	Pk	28.5	-31.7	11.4	-61.42	-13	-48.42	0-360	149	V
5	2.47422	-69.44	Pk	32.3	-30.4	11.5	-56.04	-13	-43.04	0-360	149	V
6	3.29022	-71.43	Pk	32.8	-29.2	12	-55.83	-13	-42.83	0-360	149	V
836.52 MHz												
1	1.67203	-67.09	Pk	28.8	-31.5	11.6	-58.19	-13	-45.19	0-360	149	H
2	2.50822	-69.26	Pk	32.3	-30.2	11.4	-55.76	-13	-42.76	0-360	149	H
3	3.34759	-71.41	Pk	32.7	-29.2	11.4	-56.51	-13	-43.51	0-360	149	H
4	1.67256	-69.06	Pk	28.8	-31.6	10.9	-60.96	-13	-47.96	0-360	149	V
5	2.51034	-69.27	Pk	32.3	-30.1	11.4	-55.67	-13	-42.67	0-360	149	V
6	3.35291	-71.11	Pk	32.6	-29.2	11.8	-55.91	-13	-42.91	0-360	149	V
848.3 MHz												
1	1.697	-69.4	Pk	29.2	-31.5	11.2	-60.5	-13	-47.5	0-360	149	H
2	2.54647	-70.4	Pk	32.3	-30.1	12	-56.2	-13	-43.2	0-360	149	H
3	3.39169	-71.75	Pk	32.6	-29.2	11.7	-56.65	-13	-43.65	0-360	149	H
4	1.697	-70.31	Pk	29.2	-31.5	12.2	-60.41	-13	-47.41	0-360	149	V
5	2.547	-71.18	Pk	32.3	-30	11.8	-57.08	-13	-44.08	0-360	149	V
6	3.39275	-70.77	Pk	32.6	-29.3	11.8	-55.67	-13	-42.67	0-360	149	V

**9.2.5. CDMA BC1**

**1xRTT MODE**

Company:	Samsung
Project #:	13171837
Date:	1/09/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	1xRTT BC1
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1851.25 MHz												
1	3.69503	-75.96	Pk	33	-28.8	11.9	-59.86	-13	-46.86	0-360	149	H
2	5.55866	-76.52	Pk	35.1	-26.8	11.9	-56.32	-13	-43.32	0-360	149	H
3	7.39253	-78.85	Pk	35.5	-24.3	12.1	-55.55	-13	-42.55	0-360	149	H
4	3.70672	-75.62	Pk	33	-28.6	11.9	-59.32	-13	-46.32	0-360	149	V
5	5.55441	-77.69	Pk	35.1	-26.8	12.1	-57.29	-13	-44.29	0-360	149	V
6	7.39838	-77.98	Pk	35.5	-24.3	11.9	-54.88	-13	-41.88	0-360	149	V
1880 MHz												
1	3.74922	-76.4	Pk	33	-28.4	11.6	-60.2	-13	-47.2	0-360	149	H
2	5.64844	-76.13	Pk	35.1	-26.6	12	-55.63	-13	-42.63	0-360	149	H
3	7.50409	-78.81	Pk	35.5	-23.8	12.2	-54.91	-13	-41.91	0-360	149	H
4	3.74922	-76.39	Pk	33	-28.4	11.8	-59.99	-13	-46.99	0-360	149	V
5	5.64366	-77.38	Pk	35.1	-26.6	12	-56.88	-13	-43.88	0-360	149	V
6	7.51047	-78.67	Pk	35.6	-23.9	12.3	-54.67	-13	-41.67	0-360	149	V
1908.75 MHz												
1	3.81775	-76.78	Pk	32.9	-28.3	11.7	-60.48	-13	-47.48	0-360	149	H
2	5.72016	-76.71	Pk	35	-26.7	12	-56.41	-13	-43.41	0-360	149	H
3	7.64647	-77.52	Pk	35.6	-24.1	11.6	-54.42	-13	-41.42	0-360	149	H
4	3.82041	-76.2	Pk	32.9	-28.2	11.2	-60.3	-13	-47.3	0-360	149	V
5	5.73291	-77.38	Pk	35	-26.5	11.5	-57.38	-13	-44.38	0-360	149	V
6	7.6385	-78.57	Pk	35.6	-24.1	11.8	-55.27	-13	-42.27	0-360	149	V

**1xEV-DO REV A MODE**

Company:	Samsung
Project #:	13171837
Date:	1/09/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	1xEV-DO REV A BC1
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1851.25 MHz												
1	3.71097	-76.11	Pk	33	-28.5	11.7	-59.91	-13	-46.91	0-360	149	H
2	5.56609	-76.79	Pk	35.2	-26.7	11.6	-56.69	-13	-43.69	0-360	149	H
3	7.38775	-78.58	Pk	35.5	-24.2	12	-55.28	-13	-42.28	0-360	149	H
4	3.69716	-75.98	Pk	33	-28.8	12.1	-59.68	-13	-46.68	0-360	149	V
5	5.556	-76.27	Pk	35.1	-26.8	12	-55.97	-13	-42.97	0-360	149	V
6	7.39519	-78.8	Pk	35.5	-24.2	12	-55.5	-13	-42.5	0-360	149	V
1880 MHz												
1	3.75666	-76.29	Pk	32.9	-28.3	11.8	-59.89	-13	-46.89	0-360	149	H
2	5.64631	-76.13	Pk	35.1	-26.6	11.9	-55.73	-13	-42.73	0-360	149	H
3	7.49878	-78.77	Pk	35.5	-23.8	12.1	-54.97	-13	-41.97	0-360	149	H
4	3.75506	-76.69	Pk	32.9	-28.4	11.8	-60.39	-13	-47.39	0-360	149	V
5	5.64525	-77.03	Pk	35.1	-26.5	12	-56.43	-13	-43.43	0-360	149	V
6	7.5195	-77.08	Pk	35.5	-23.9	12	-53.48	-13	-40.48	0-360	149	V
1908.75 MHz												
1	3.82041	-76.58	Pk	32.9	-28.2	11.5	-60.38	-13	-47.38	0-360	149	H
2	5.71909	-77.73	Pk	35	-26.7	12	-57.43	-13	-44.43	0-360	149	H
3	7.63638	-78.18	Pk	35.6	-24.1	11.8	-54.88	-13	-41.88	0-360	149	H
4	3.81934	-76.78	Pk	32.9	-28.3	11.3	-60.88	-13	-47.88	0-360	149	V
5	5.71803	-77.72	Pk	35	-26.7	11.7	-57.72	-13	-44.72	0-360	149	V
6	7.63159	-78.57	Pk	35.6	-24.1	12	-55.07	-13	-42.07	0-360	149	V

**9.2.6. WCDMA BAND 5**

**REL 99 MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	REL 99 Band 5
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
826.4 MHz												
1	1.65344	-65.84	Pk	28.5	-31.7	12.2	-56.84	-13	-43.84	0-360	149	H
2	2.48059	-68.48	Pk	32.4	-30.5	11.3	-55.28	-13	-42.28	0-360	149	H
3	3.30456	-71.64	Pk	32.7	-29.3	11.6	-56.64	-13	-43.64	0-360	149	H
4	1.65131	-69.02	Pk	28.5	-31.7	11.3	-60.92	-13	-47.92	0-360	149	V
5	2.48113	-67.46	Pk	32.4	-30.5	11.3	-54.26	-13	-41.26	0-360	149	V
6	3.30563	-71.4	Pk	32.7	-29.3	11.9	-56.1	-13	-43.1	0-360	149	V
836.6 MHz												
1	1.67097	-69.5	Pk	28.8	-31.5	11.6	-60.6	-13	-47.6	0-360	149	H
2	2.50716	-70.42	Pk	32.3	-30.2	11.4	-56.92	-13	-43.92	0-360	149	H
3	3.34866	-71.53	Pk	32.7	-29.2	11.4	-56.63	-13	-43.63	0-360	149	H
4	1.67044	-70.29	Pk	28.8	-31.5	11.1	-61.89	-13	-48.89	0-360	149	V
5	2.50875	-70.65	Pk	32.3	-30.2	11.4	-57.15	-13	-44.15	0-360	149	V
6	3.34441	-72.13	Pk	32.7	-29.2	12	-56.63	-13	-43.63	0-360	149	V
846.6 MHz												
1	1.69434	-63.24	Pk	29.1	-31.6	11.4	-54.34	-13	-41.34	0-360	149	H
2	2.53531	-69.88	Pk	32.2	-30.2	12.7	-55.18	-13	-42.18	0-360	149	H
3	3.39063	-70.84	Pk	32.6	-29.3	11.6	-55.94	-13	-42.94	0-360	149	H
4	1.69488	-61.43	Pk	29.1	-31.6	12.4	-51.53	-13	-38.53	0-360	149	V
5	2.53691	-71.68	Pk	32.2	-30.1	11.5	-58.08	-13	-45.08	0-360	149	V
6	3.38691	-71.64	Pk	32.7	-29.2	12	-56.14	-13	-43.14	0-360	149	V

**HSDPA MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	HSDPA Band 5
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
826.4 MHz												
1	1.6545	-68.35	Pk	28.6	-31.7	12.2	-59.25	-13	-46.25	0-360	149	H
2	2.479	-70.91	Pk	32.3	-30.5	11.2	-57.91	-13	-44.91	0-360	149	H
3	3.30244	-71.96	Pk	32.7	-29.2	11.6	-56.86	-13	-43.86	0-360	149	H
4	1.65609	-69.7	Pk	28.6	-31.7	11.3	-61.5	-13	-48.5	0-360	149	V
5	2.47634	-71.17	Pk	32.3	-30.4	11.4	-57.87	-13	-44.87	0-360	149	V
6	3.30934	-72.23	Pk	32.7	-29.3	11.9	-56.93	-13	-43.93	0-360	149	V
836.6 MHz												
1	1.67681	-70.49	Pk	28.9	-31.6	11.8	-61.39	-13	-48.39	0-360	149	H
2	2.51247	-70.28	Pk	32.3	-30.1	11.5	-56.58	-13	-43.58	0-360	149	H
3	3.34175	-71.21	Pk	32.7	-29.2	11.6	-56.11	-13	-43.11	0-360	149	H
4	1.68213	-69.97	Pk	29	-31.5	11.6	-60.87	-13	-47.87	0-360	149	V
5	2.50928	-69.91	Pk	32.3	-30.2	11.4	-56.41	-13	-43.41	0-360	149	V
6	3.33697	-70.75	Pk	32.8	-29.2	12.1	-55.05	-13	-42.05	0-360	149	V
846.6 MHz												
1	1.69009	-66.9	Pk	29.2	-31.6	11.4	-57.9	-13	-44.9	0-360	149	H
2	2.53638	-70.19	Pk	32.2	-30.2	12.7	-55.49	-13	-42.49	0-360	149	H
3	3.39009	-70.73	Pk	32.6	-29.3	11.6	-55.83	-13	-42.83	0-360	149	H
4	1.69488	-64.64	Pk	29.1	-31.6	12.4	-54.74	-13	-41.74	0-360	149	V
5	2.54169	-71.06	Pk	32.2	-30.1	11.7	-57.26	-13	-44.26	0-360	149	V
6	3.38266	-71.45	Pk	32.7	-29.3	12.1	-55.95	-13	-42.95	0-360	149	V

**9.2.7. WCDMA BAND 2**

**REL 99 MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	REL 99 Band 2
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1852.4 MHz												
1	3.70619	-75.18	Pk	33	-28.6	11.8	-58.98	-13	-45.98	0-360	149	H
2	5.54909	-76.29	Pk	35.1	-26.8	12	-55.99	-13	-42.99	0-360	149	H
3	7.42388	-77.49	Pk	35.5	-24.3	11.7	-54.59	-13	-41.59	0-360	149	H
4	3.70884	-75.3	Pk	33	-28.5	11.9	-58.9	-13	-45.9	0-360	149	V
5	5.56131	-76.4	Pk	35.1	-26.8	12	-56.1	-13	-43.1	0-360	149	V
6	7.39838	-78.87	Pk	35.5	-24.3	11.9	-55.77	-13	-42.77	0-360	149	V
1880 MHz												
1	3.76569	-75.85	Pk	33	-28.2	11.6	-59.45	-13	-46.45	0-360	149	H
2	5.65588	-76.42	Pk	35	-26.7	12.2	-55.92	-13	-42.92	0-360	149	H
3	7.52109	-76.86	Pk	35.5	-23.9	11.9	-53.36	-13	-40.36	0-360	149	H
4	3.75931	-75.57	Pk	32.9	-28.3	11.8	-59.17	-13	-46.17	0-360	149	V
5	5.63409	-75.38	Pk	35	-26.6	12	-54.98	-13	-41.98	0-360	149	V
6	7.51047	-78	Pk	35.6	-23.9	12.3	-54	-13	-41	0-360	149	V
1907.6 MHz												
1	3.81403	-75.31	Pk	32.9	-28.4	11.8	-59.01	-13	-46.01	0-360	149	H
2	5.72866	-75.91	Pk	34.9	-26.6	11.8	-55.81	-13	-42.81	0-360	149	H
3	7.62363	-78.04	Pk	35.7	-24.1	11.9	-54.54	-13	-41.54	0-360	149	H
4	3.81403	-75.37	Pk	32.9	-28.4	11.4	-59.47	-13	-46.47	0-360	149	V
5	5.7175	-75.75	Pk	35	-26.7	11.7	-55.75	-13	-42.75	0-360	149	V
6	7.63531	-78.21	Pk	35.6	-24.1	12	-54.71	-13	-41.71	0-360	149	V

**HSDPA MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	HSDPA Band 2
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1852.4 MHz												
1	3.69769	-75.73	Pk	33	-28.8	11.9	-59.63	-13	-46.63	0-360	149	H
2	5.54697	-75.82	Pk	35.1	-26.9	12	-55.62	-13	-42.62	0-360	149	H
3	7.42122	-77.69	Pk	35.6	-24.4	11.6	-54.89	-13	-41.89	0-360	149	H
4	3.70141	-74.32	Pk	33	-28.7	12.1	-57.92	-13	-44.92	0-360	149	V
5	5.556	-77.04	Pk	35.1	-26.8	12	-56.74	-13	-43.74	0-360	149	V
6	7.41219	-77.35	Pk	35.5	-24.4	11.6	-54.65	-13	-41.65	0-360	149	V
1880 MHz												
1	3.76303	-75.16	Pk	33	-28.3	11.7	-58.76	-13	-45.76	0-360	149	H
2	5.65269	-76.28	Pk	35	-26.7	12.2	-55.78	-13	-42.78	0-360	149	H
3	7.50994	-77.78	Pk	35.6	-23.9	12.1	-53.98	-13	-40.98	0-360	149	H
4	3.75719	-76.5	Pk	32.9	-28.3	11.8	-60.1	-13	-47.1	0-360	149	V
5	5.6495	-75.96	Pk	35	-26.6	12.2	-55.36	-13	-42.36	0-360	149	V
6	7.51738	-78.73	Pk	35.5	-23.9	12.1	-55.03	-13	-42.03	0-360	149	V
1907.6 MHz												
1	3.82147	-75.2	Pk	32.9	-28.2	11.4	-59.1	-13	-46.1	0-360	149	H
2	5.72175	-76.24	Pk	35	-26.6	12	-55.84	-13	-42.84	0-360	149	H
3	7.65178	-77.88	Pk	35.6	-24.1	11.7	-54.68	-13	-41.68	0-360	149	H
4	3.81191	-76.14	Pk	32.9	-28.4	11.4	-60.24	-13	-47.24	0-360	149	V
5	5.71272	-77.29	Pk	34.9	-26.7	11.9	-57.19	-13	-44.19	0-360	149	V
6	7.63372	-78.11	Pk	35.6	-24.1	12	-54.61	-13	-41.61	0-360	149	V

**9.2.8. WCDMA BAND 4**

**REL 99 MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	REL 99 Band 4
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1712.4 MHz												
1	3.43419	-74.34	Pk	32.7	-29.3	11.9	-59.04	-13	-46.04	0-360	149	H
2	5.13313	-77.33	Pk	34.4	-26.9	11.8	-58.03	-13	-45.03	0-360	149	H
3	6.86234	-77.25	Pk	35.7	-25.2	11.8	-54.95	-13	-41.95	0-360	149	H
4	3.42834	-74.68	Pk	32.7	-29.3	11.7	-59.58	-13	-46.58	0-360	149	V
5	5.14056	-76.82	Pk	34.4	-27	12	-57.42	-13	-44.42	0-360	149	V
6	6.84747	-77.38	Pk	35.5	-25.3	11.6	-55.58	-13	-42.58	0-360	149	V
1732.6 MHz												
1	3.47191	-75.41	Pk	32.8	-29	11.8	-59.81	-13	-46.81	0-360	149	H
2	5.19422	-76.85	Pk	34.4	-26.9	12.1	-57.25	-13	-44.25	0-360	149	H
3	6.93194	-76.45	Pk	35.7	-24.7	11.7	-53.75	-13	-40.75	0-360	149	H
4	3.45863	-76.34	Pk	32.8	-29.1	11.5	-61.14	-13	-48.14	0-360	149	V
5	5.19741	-77.38	Pk	34.4	-27	12.4	-57.58	-13	-44.58	0-360	149	V
6	6.92769	-77.36	Pk	35.6	-24.8	12.1	-54.46	-13	-41.46	0-360	149	V
1752.6 MHz												
1	3.50006	-76.03	Pk	32.9	-28.8	12.1	-59.83	-13	-46.83	0-360	149	H
2	5.27284	-77.37	Pk	34.5	-26.7	12.1	-57.47	-13	-44.47	0-360	149	H
3	7.00047	-76.89	Pk	35.6	-24.7	11.7	-54.29	-13	-41.29	0-360	149	H
4	3.50963	-76.23	Pk	32.8	-28.7	11.8	-60.33	-13	-47.33	0-360	149	V
5	5.25691	-77.59	Pk	34.5	-26.7	12.3	-57.49	-13	-44.49	0-360	149	V
6	7.00259	-75.98	Pk	35.6	-24.8	11.8	-53.38	-13	-40.38	0-360	149	V



**HSDPA MODE**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	HSDPA Band 4
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1712.4 MHz												
1	3.43313	-74.73	Pk	32.7	-29.3	11.9	-59.43	-13	-46.43	0-360	149	H
2	5.14588	-76.75	Pk	34.3	-27	11.9	-57.55	-13	-44.55	0-360	149	H
3	6.82941	-76.86	Pk	35.5	-25.2	11.6	-54.96	-13	-41.96	0-360	149	H
4	3.42463	-75.52	Pk	32.7	-29.3	11.8	-60.32	-13	-47.32	0-360	149	V
5	5.14109	-77.03	Pk	34.4	-27	12	-57.63	-13	-44.63	0-360	149	V
6	6.84641	-77.79	Pk	35.5	-25.3	11.6	-55.99	-13	-42.99	0-360	149	V
1732.6 MHz												
1	3.46447	-76	Pk	32.8	-29.2	12	-60.4	-13	-47.4	0-360	149	H
2	5.19741	-77.17	Pk	34.4	-27	12.2	-57.57	-13	-44.57	0-360	149	H
3	6.91866	-77.42	Pk	35.6	-24.8	11.8	-54.82	-13	-41.82	0-360	149	H
4	3.46341	-75.39	Pk	32.8	-29.2	11.6	-60.19	-13	-47.19	0-360	149	V
5	5.19103	-77.1	Pk	34.4	-27	12.3	-57.4	-13	-44.4	0-360	149	V
6	6.93194	-77.37	Pk	35.7	-24.7	11.9	-54.47	-13	-41.47	0-360	149	V
1752.6 MHz												
1	3.50272	-76.73	Pk	32.9	-28.7	11.9	-60.63	-13	-47.63	0-360	152	H
2	5.26009	-76.71	Pk	34.5	-26.7	12	-56.91	-13	-43.91	0-360	152	H
3	6.99728	-78.29	Pk	35.6	-24.8	11.8	-55.69	-13	-42.69	0-360	152	H
4	3.50006	-76.11	Pk	32.9	-28.8	11.9	-60.11	-13	-47.11	0-360	152	V
5	5.25266	-76.87	Pk	34.5	-26.9	12.4	-56.87	-13	-43.87	0-360	152	V
6	6.99569	-77.05	Pk	35.6	-24.8	11.9	-54.35	-13	-41.35	0-360	152	V

### 9.2.9. LTE BAND 5

#### LIMITS

FCC: §22.917(a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

RSS132§5.5

Mobile and base station equipment shall comply with the limits in (i) and (ii) below.

- (i) In the first 1.0 MHz band immediately outside and adjacent to each of the sub-bands specified in Section 5.1, the power of emissions per any 1% of the occupied bandwidth shall be attenuated (in dB) below the transmitter output power P ( dBW) by at least 43 + 10 log10p (watts).
- (ii) After the first 1.0 MHz immediately outside and adjacent to each of the sub-bands, the power of emissions in any100 kHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least43 + 10 log10 p (watts). If the measurement is performed using 1% of the occupied bandwidth, power integration over 100 kHz is required.

#### QPSK LTE BAND 5 (10.0MHZ BANDWIDTH)

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 5 QPSK 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
829 MHz												
1	1.64919	-57.41	Pk	28.5	-31.7	12.5	-48.11	-13	-35.11	0-360	149	H
2	2.47369	-66.15	Pk	32.3	-30.4	11.3	-52.95	-13	-39.95	0-360	149	H
3	3.27056	-70.25	Pk	32.8	-29.1	12	-54.55	-13	-41.55	0-360	149	H
4	1.64919	-62.07	Pk	28.5	-31.7	11.4	-53.87	-13	-40.87	0-360	149	V
5	2.47369	-66.47	Pk	32.3	-30.4	11.5	-53.07	-13	-40.07	0-360	149	V
6	3.27906	-71.62	Pk	32.8	-29.2	11.9	-56.12	-13	-43.12	0-360	149	V
836.5 MHz												
1	1.66406	-66.54	Pk	28.7	-31.6	11.6	-57.84	-13	-44.84	0-360	149	H
2	2.496	-66.9	Pk	32.3	-30.3	11.3	-53.6	-13	-40.6	0-360	149	H
3	3.33219	-70.49	Pk	32.8	-29.1	11.6	-55.19	-13	-42.19	0-360	149	H
4	1.66406	-58.24	Pk	28.7	-31.6	11.3	-49.84	-13	-36.84	0-360	149	V
5	2.496	-66.86	Pk	32.3	-30.3	11.4	-53.46	-13	-40.46	0-360	149	V
6	3.33909	-70.92	Pk	32.7	-29.2	12.1	-55.32	-13	-42.32	0-360	149	V
844 MHz												
1	1.67894	-62.31	Pk	28.9	-31.6	12	-53.01	-13	-40.01	0-360	149	H
2	2.51831	-65.64	Pk	32.3	-30.2	11.9	-51.64	-13	-38.64	0-360	149	H
3	3.27269	-70.74	Pk	32.8	-29.2	12	-55.14	-13	-42.14	0-360	149	H
4	1.67947	-64.81	Pk	28.9	-31.6	11.3	-56.21	-13	-43.21	0-360	149	V
5	2.51884	-64.6	Pk	32.3	-30.2	11.6	-50.9	-13	-37.9	0-360	149	V
6	3.27959	-70.14	Pk	32.8	-29.2	11.9	-54.64	-13	-41.64	0-360	149	V

**16QAM LTE BAND 5 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 5 16QAM 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
829 MHz												
1	1.64919	-59.42	Pk	28.5	-31.7	12.5	-50.12	-13	-37.12	0-360	149	H
2	2.47369	-67.58	Pk	32.3	-30.4	11.3	-54.38	-13	-41.38	0-360	149	H
3	3.29766	-71.22	Pk	32.7	-29.2	11.9	-55.82	-13	-42.82	0-360	149	H
4	1.64919	-63.23	Pk	28.5	-31.7	11.4	-55.03	-13	-42.03	0-360	149	V
5	2.47369	-65.17	Pk	32.3	-30.4	11.5	-51.77	-13	-38.77	0-360	149	V
6	3.28809	-71.78	Pk	32.8	-29.1	12.1	-55.98	-13	-42.98	0-360	149	V
836.5 MHz												
1	1.66406	-66.52	Pk	28.7	-31.6	11.6	-57.82	-13	-44.82	0-360	149	H
2	2.49653	-66.93	Pk	32.3	-30.3	11.3	-53.63	-13	-40.63	0-360	149	H
3	3.33484	-70.96	Pk	32.8	-29.2	11.6	-55.76	-13	-42.76	0-360	149	H
4	1.66406	-56.69	Pk	28.7	-31.6	11.3	-48.29	-13	-35.29	0-360	149	V
5	2.496	-68.44	Pk	32.3	-30.3	11.4	-55.04	-13	-42.04	0-360	149	V
6	3.34813	-69.77	Pk	32.7	-29.2	11.9	-54.37	-13	-41.37	0-360	149	V
844 MHz												
1	1.67894	-62.63	Pk	28.9	-31.6	12	-53.33	-13	-40.33	0-360	149	H
2	2.51884	-67.43	Pk	32.3	-30.2	11.9	-53.43	-13	-40.43	0-360	149	H
3	3.3375	-70.09	Pk	32.8	-29.1	11.7	-54.69	-13	-41.69	0-360	149	H
4	1.67947	-63.24	Pk	28.9	-31.6	11.3	-54.64	-13	-41.64	0-360	149	V
5	2.51884	-65.57	Pk	32.3	-30.2	11.6	-51.87	-13	-38.87	0-360	149	V
6	3.33378	-71.2	Pk	32.8	-29.1	12	-55.5	-13	-42.5	0-360	149	V

**9.2.10. LTE BAND 7**

**LIMITS**

FCC: §27.53 (m)

At least 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.

RSS199§4.5

Equipment shall comply with the following unwanted emission limits:

- a. for base station and fixed subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least 43 + 10 log<sub>10</sub> p
- b. for mobile subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least:
  - i. 40 + 10 log<sub>10</sub> p from the channel edges to 5 MHz away
  - ii. 43 + 10 log<sub>10</sub> p between 5 MHz and X MHz from the channel edges, and
  - iii. 55 + 10 log<sub>10</sub> p at X MHz and beyond from the channel edges

In addition, the attenuation shall not be less than 43 + 10 log<sub>10</sub> p on all frequencies between 2490.5 MHz and 2496 MHz, and 55 + 10 log<sub>10</sub> p at or below 2490.5 MHz.

In (a) and (b), p is the transmitter power measured in watts and X is 6 MHz or the equipment occupied bandwidth, whichever is greater.

**QPSK LTE BAND 7 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/09/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 7 QPSK 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2510 MHz												
1	5.00031	-76.22	Pk	34.3	-27.2	11.5	-57.62	-25	-32.62	0-360	149	H
2	7.51684	-78.1	Pk	35.5	-23.9	12	-54.5	-25	-29.5	0-360	149	H
3	10.01744	-79.09	Pk	37	-20.8	12	-50.89	-25	-25.89	0-360	149	H
4	5.00403	-76.31	Pk	34.3	-27.2	11.9	-57.31	-25	-32.31	0-360	149	V
5	7.49878	-78.54	Pk	35.5	-23.8	12.2	-54.64	-25	-29.64	0-360	149	V
6	10.00469	-79.16	Pk	37	-20.8	11.7	-51.26	-25	-26.26	0-360	149	V
2535 MHz												
1	5.10391	-75.81	Pk	34.4	-26.9	11.7	-56.61	-25	-31.61	0-360	149	H
2	7.56147	-77.42	Pk	35.6	-23.8	12.2	-53.42	-25	-28.42	0-360	149	H
3	10.19966	-78.64	Pk	37.3	-20.1	12.3	-49.14	-25	-24.14	0-360	149	H
4	5.07256	-75.45	Pk	34.3	-27.1	11.9	-56.35	-25	-31.35	0-360	149	V
5	7.56678	-76.01	Pk	35.6	-23.9	12.2	-52.11	-25	-27.11	0-360	149	V
6	10.14388	-79.24	Pk	37.1	-20.2	12.4	-49.94	-25	-24.94	0-360	149	V
2560 MHz												
1	5.09647	-75.45	Pk	34.3	-26.8	11.9	-56.05	-25	-31.05	0-360	149	H
2	7.65603	-78.13	Pk	35.7	-24	11.7	-54.73	-25	-29.73	0-360	149	H
3	10.20178	-78.8	Pk	37.3	-20.1	12.3	-49.3	-25	-24.3	0-360	149	H
4	5.10391	-76.14	Pk	34.4	-26.9	11.7	-56.94	-25	-31.94	0-360	149	V
5	7.65391	-78.65	Pk	35.6	-24.1	11.7	-55.45	-25	-30.45	0-360	149	V
6	10.20391	-79.3	Pk	37.3	-20.1	12.3	-49.8	-25	-24.8	0-360	149	V

**16QAM LTE BAND 7 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/09/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 7 16QAM 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2510 MHz												
1	5.00775	-75.59	Pk	34.3	-27.2	11.7	-56.79	-25	-31.79	0-360	149	H
2	7.51313	-78.35	Pk	35.6	-23.9	12.1	-54.55	-25	-29.55	0-360	149	H
3	9.99884	-78.37	Pk	36.9	-20.9	11.6	-50.77	-25	-25.77	0-360	149	H
4	5.00084	-76.58	Pk	34.3	-27.3	11.8	-57.78	-25	-32.78	0-360	149	V
5	7.49825	-78.93	Pk	35.5	-23.9	12.2	-55.13	-25	-30.13	0-360	149	V
6	10.00841	-79.48	Pk	37	-20.8	11.9	-51.38	-25	-26.38	0-360	149	V
2535 MHz												
1	5.04866	-75.13	Pk	34.4	-27	11.4	-56.33	-25	-31.33	0-360	149	H
2	7.56519	-77.5	Pk	35.6	-23.9	12.2	-53.6	-25	-28.6	0-360	149	H
3	10.08225	-79.59	Pk	37.1	-20.8	12.1	-51.19	-25	-26.19	0-360	149	H
4	5.04813	-75.39	Pk	34.4	-27	11.7	-56.29	-25	-31.29	0-360	149	V
5	7.57847	-76.23	Pk	35.5	-24.1	12.1	-52.73	-25	-27.73	0-360	149	V
6	10.10456	-79.58	Pk	37.1	-20.7	11.8	-51.38	-25	-26.38	0-360	149	V
2560 MHz												
1	5.11134	-75.15	Pk	34.3	-26.9	11.7	-56.05	-25	-31.05	0-360	149	H
2	7.64009	-78.48	Pk	35.6	-24.1	11.7	-55.28	-25	-30.28	0-360	149	H
3	10.19859	-78.62	Pk	37.3	-20.1	12.3	-49.12	-25	-24.12	0-360	149	H
4	5.10338	-76.39	Pk	34.4	-26.9	11.7	-57.19	-25	-32.19	0-360	149	V
5	7.64913	-78.54	Pk	35.6	-24.2	11.6	-55.54	-25	-30.54	0-360	149	V
6	10.20444	-78.82	Pk	37.3	-20.2	12.3	-49.42	-25	-24.42	0-360	149	V

**9.2.11. LTE BAND 12**

**LIMITS**

FCC: §27.53 (g)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

RSS130§4.7

**4.7.1 General unwanted emissions limits**

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least 43 + 10 log<sub>10</sub> p (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

**4.7.2 Additional unwanted emissions limits**

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

- a. the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
  - iii. 76 + 10 log<sub>10</sub> p (watts), dB, for base and fixed equipment and
  - iv. 65 + 10 log<sub>10</sub> p (watts), dB, for mobile and portable equipment
- b. the e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

**QPSK LTE BAND 12 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/31/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 12 QPSK 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
704 MHz												
1	1.39897	-69.66	Pk	28.9	-32.2	10.4	-62.56	-13	-49.56	0-360	149	H
2	2.09863	-56.23	Pk	31.1	-30.9	11.8	-44.23	-13	-31.23	0-360	149	H
3	2.80731	-74.62	Pk	32.3	-29.8	11.9	-60.22	-13	-47.22	0-360	149	H
4	1.39897	-70.91	Pk	28.9	-32.2	10.3	-63.91	-13	-50.91	0-360	149	V
5	2.09916	-62.85	Pk	31.1	-30.9	11.4	-51.25	-13	-38.25	0-360	149	V
6	2.81847	-74.32	Pk	32.2	-29.8	11.9	-60.02	-13	-47.02	0-360	149	V
707.5 MHz												
1	1.40588	-67.35	Pk	28.8	-32.3	11.3	-59.55	-13	-46.55	0-360	149	H
2	2.10925	-53.96	Pk	31.1	-30.9	12.1	-41.66	-13	-28.66	0-360	149	H
3	2.80359	-74.5	Pk	32.3	-29.8	11.9	-60.1	-13	-47.1	0-360	149	H
4	1.40588	-69.01	Pk	28.8	-32.3	11	-61.51	-13	-48.51	0-360	149	V
5	2.10925	-57.42	Pk	31.1	-30.9	11.7	-45.52	-13	-32.52	0-360	149	V
6	2.79669	-74.62	Pk	32.4	-29.9	11.9	-60.22	-13	-47.22	0-360	149	V
711 MHz												
1	1.41331	-71.51	Pk	28.8	-32.2	12	-62.91	-13	-49.91	0-360	149	H
2	2.11934	-56.16	Pk	31.1	-31.1	12.3	-43.86	-13	-30.86	0-360	149	H
3	2.80041	-73.4	Pk	32.4	-29.8	11.8	-59	-13	-46	0-360	149	H
4	1.41756	-73.17	Pk	28.7	-32.1	12.2	-64.37	-13	-51.37	0-360	149	V
5	2.11988	-61.72	Pk	31.1	-31	11.6	-50.02	-13	-37.02	0-360	149	V
6	2.81316	-73.75	Pk	32.2	-29.8	11.7	-59.65	-13	-46.65	0-360	149	V

**16QAM LTE BAND 12 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/31/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 12 16QAM 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
704 MHz												
1	1.3995	-70.28	Pk	28.9	-32.2	10.4	-63.18	-13	-50.18	0-360	149	H
2	2.09916	-56.56	Pk	31.1	-30.9	11.8	-44.56	-13	-31.56	0-360	149	H
3	2.79084	-73.48	Pk	32.3	-29.9	11.9	-59.18	-13	-46.18	0-360	149	H
4	1.38622	-72.06	Pk	29.1	-32.3	10.5	-64.76	-13	-51.76	0-360	149	V
5	2.09916	-61.84	Pk	31.1	-30.9	11.4	-50.24	-13	-37.24	0-360	149	V
6	2.78925	-73.5	Pk	32.3	-30	11.9	-59.3	-13	-46.3	0-360	149	V
707.5 MHz												
1	1.42819	-72.77	Pk	28.6	-32.1	12.4	-63.87	-13	-50.87	0-360	149	H
2	2.10925	-56.04	Pk	31.1	-30.9	12.1	-43.74	-13	-30.74	0-360	149	H
3	2.78234	-72.83	Pk	32.3	-30	11.8	-58.73	-13	-45.73	0-360	149	H
4	1.42606	-72.07	Pk	28.6	-32.1	12.2	-63.37	-13	-50.37	0-360	149	V
5	2.10925	-61.1	Pk	31.1	-30.9	11.7	-49.2	-13	-36.2	0-360	149	V
6	2.80519	-73.89	Pk	32.3	-29.8	11.8	-59.59	-13	-46.59	0-360	149	V
711 MHz												
1	1.4335	-72.17	Pk	28.4	-32.1	12	-63.87	-13	-50.87	0-360	149	H
2	2.11988	-56.9	Pk	31.1	-31	12.3	-44.5	-13	-31.5	0-360	149	H
3	2.84397	-73.64	Pk	32.2	-30.1	11.4	-60.14	-13	-47.14	0-360	149	H
4	1.42288	-73.34	Pk	28.6	-32.1	12.4	-64.44	-13	-51.44	0-360	149	V
5	2.11988	-64.96	Pk	31.1	-31	11.6	-53.26	-13	-40.26	0-360	149	V
6	2.82378	-74.26	Pk	32.2	-29.9	12	-59.96	-13	-46.96	0-360	149	V

**9.2.12. LTE BAND 13**

**LIMITS**

FCC: §27.53

(c) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

(f) Emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

RSS130§4.7

**4.7.1 General unwanted emissions limits**

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least  $43 + 10 \log_{10} p$  (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

**4.7.2 Additional unwanted emissions limits**

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

- a. the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
  - i.  $76 + 10 \log_{10} p$  (watts), dB, for base and fixed equipment and
  - ii.  $65 + 10 \log_{10} p$  (watts), dB, for mobile and portable equipment
- b. the e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

**QPSK LTE BAND 13 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 13 QPSK 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
782MHz												
1	1.55993	-63.1	Pk	28.1	-31.8	11.5	-55.3	-40	-15.3	0-360	149	H
2	2.33238	-57.05	Pk	31.5	-30.6	12.1	-44.05	-13	-31.05	0-360	149	H
3	3.10906	-71.37	Pk	32.7	-29.3	11.6	-56.37	-13	-43.37	0-360	149	H
4	1.55994	-66.64	Pk	28	-31.8	12.1	-58.34	-40	-18.34	0-360	149	V
5	2.33238	-61.84	Pk	31.5	-30.6	11.8	-49.14	-13	-36.14	0-360	149	V
6	3.11013	-70.37	Pk	32.7	-29.3	12.2	-54.77	-13	-41.77	0-360	149	V



**16QAM LTE BAND 13 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 13 16QAM 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
782MHz												
1	1.55993	-67.34	Pk	28.1	-31.8	11.5	-59.54	-40	-19.54	0-360	149	H
2	2.33238	-59.44	Pk	31.5	-30.6	12.1	-46.44	-13	-33.44	0-360	149	H
3	3.11013	-70.62	Pk	32.7	-29.3	11.6	-55.62	-13	-42.62	0-360	149	H
4	1.55994	-70.06	Pk	28.1	-31.8	12.2	-61.56	-40	-21.56	0-360	149	V
5	2.33291	-63.17	Pk	31.5	-30.6	11.8	-50.47	-13	-37.47	0-360	149	V
6	3.11066	-70.17	Pk	32.7	-29.4	12.2	-54.67	-13	-41.67	0-360	149	V

**9.2.13. LTE BAND 14**

**LIMITS**

FCC: §90.543 Emission Limitations. (Band 14)

(e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation

**RSS140§4.4**

The power of any unwanted emission outside the bands 758-768 MHz and 788-798 MHz shall be attenuated below the transmitter output power P in dBW as follows, where p is the transmitter output power in watts:

a. For any frequency between 769-775 MHz and 799-806 MHz:

- i.  $76 + 10 \log (p)$ , dB in a 6.25 kHz band for fixed and base station equipment
- ii.  $65 + 10 \log (p)$ , dB in a 6.25 kHz band for mobile and portable/hand-held equipment

b. For any frequency between 775-788 MHz, above 806 MHz, and below 758 MHz:  $43 + 10 \log (p)$ , dB in a bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency bands 758-768 MHz and 788-798 MHz, a resolution bandwidth of 30 kHz may be employed.

In addition, the equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed -70 dBW/MHz for wideband emissions, and -80 dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

**QPSK LTE BAND 14 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/16/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 14 QPSK 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cpl (dB)	Amp/Cpl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
793MHz												
1	1.57694	-72.7	Pk	28	-31.8	10.8	-65.7	-40	-25.7	0-360	149	H
2	2.36531	-58.5	Pk	31.8	-30.6	12.6	-44.7	-13	-31.7	0-360	149	H
3	3.15422	-75.08	Pk	32.7	-28.9	12	-59.28	-13	-46.28	0-360	149	H
4	1.57694	-72.14	Pk	28	-31.8	11.1	-64.84	-40	-24.84	0-360	149	V
5	2.36584	-66.96	Pk	31.8	-30.6	13.1	-52.66	-13	-39.66	0-360	149	V
6	3.15422	-72.61	Pk	32.7	-28.9	12	-56.81	-13	-43.81	0-360	149	V

**16QAM LTE BAND 14 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/16/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 14 16QAM 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
793MHz												
1	1.57694	-70.43	Pk	28	-31.8	10.8	-63.43	-40	-23.43	0-360	149	H
2	2.36531	-59.98	Pk	31.8	-30.6	12.6	-46.18	-13	-33.18	0-360	149	H
3	3.15263	-75.67	Pk	32.7	-28.9	12	-59.87	-13	-46.87	0-360	149	H
4	1.57428	-72.43	Pk	28	-31.8	11	-65.23	-40	-25.23	0-360	149	V
5	2.36531	-69.72	Pk	31.8	-30.6	13.2	-55.32	-13	-42.32	0-360	149	V
6	3.15475	-74.96	Pk	32.7	-28.9	12	-59.16	-13	-46.16	0-360	149	V

**9.2.14. LTE BAND 25**

**LIMITS**

FCC: §24.238(a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

RSS133§6.5.1

Equipment shall comply with the limits in (i) and (ii) below.

- (i) In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log10p(watts).
- (ii) After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least 43 + 10 log10p(watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.

**QPSK LTE BAND 25 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 25 QPSK 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1860 MHz												
1	3.70141	-75.41	Pk	33	-28.7	11.9	-59.21	-13	-46.21	0-360	149	H
2	5.54431	-76.04	Pk	35.1	-26.8	12.1	-55.64	-13	-42.64	0-360	149	H
3	7.42388	-77.59	Pk	35.5	-24.3	11.7	-54.69	-13	-41.69	0-360	149	H
4	3.70725	-75.3	Pk	33	-28.6	11.9	-59	-13	-46	0-360	149	V
5	5.55228	-75.7	Pk	35.1	-26.8	12.1	-55.3	-13	-42.3	0-360	149	V
6	7.40741	-78.55	Pk	35.5	-24.4	11.7	-55.75	-13	-42.75	0-360	149	V
1882.5 MHz												
1	3.75134	-76.39	Pk	33	-28.4	11.7	-60.09	-13	-47.09	0-360	149	H
2	5.61497	-77.22	Pk	35.2	-26.8	11.9	-56.92	-13	-43.92	0-360	149	H
3	7.49666	-77.68	Pk	35.5	-24	12	-54.18	-13	-41.18	0-360	149	H
4	3.74603	-75.81	Pk	32.9	-28.4	11.9	-59.41	-13	-46.41	0-360	149	V
5	5.61975	-76.97	Pk	35.1	-26.7	12.1	-56.47	-13	-43.47	0-360	149	V
6	7.49453	-78.29	Pk	35.6	-24	12.1	-54.59	-13	-41.59	0-360	149	V
1905 MHz												
1	3.80181	-75.11	Pk	32.9	-28.3	11.5	-59.01	-13	-46.01	0-360	149	H
2	5.70156	-75.74	Pk	35	-26.6	11.9	-55.44	-13	-42.44	0-360	149	H
3	7.60238	-77.65	Pk	35.6	-24.1	11.9	-54.25	-13	-41.25	0-360	149	H
4	3.79172	-76.06	Pk	32.9	-28.3	11.4	-60.06	-13	-47.06	0-360	149	V
5	5.69519	-76.75	Pk	34.9	-26.6	11.7	-56.75	-13	-43.75	0-360	149	V
6	7.57369	-78.72	Pk	35.6	-23.9	12.2	-54.82	-13	-41.82	0-360	149	V

**16QAM LTE BAND 25 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/27/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 25 16QAM 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1860 MHz												
1	3.70672	-75.31	Pk	33	-28.6	11.8	-59.11	-13	-46.11	0-360	149	H
2	5.55069	-76.94	Pk	35.1	-26.8	12	-56.64	-13	-43.64	0-360	149	H
3	7.38244	-78.28	Pk	35.6	-24.2	12	-54.88	-13	-41.88	0-360	149	H
4	3.70088	-75.05	Pk	33	-28.7	12.1	-58.65	-13	-45.65	0-360	149	V
5	5.55706	-76.54	Pk	35.1	-26.8	12	-56.24	-13	-43.24	0-360	149	V
6	7.41059	-78.45	Pk	35.5	-24.4	11.6	-55.75	-13	-42.75	0-360	149	V
1882.5 MHz												
1	3.75188	-75.86	Pk	33	-28.3	11.7	-59.46	-13	-46.46	0-360	150	H
2	5.63356	-75.21	Pk	35.1	-26.6	11.7	-55.01	-13	-42.01	0-360	150	H
3	7.494	-77.38	Pk	35.6	-24	11.9	-53.88	-13	-40.88	0-360	150	H
4	3.75081	-76.09	Pk	33	-28.4	11.8	-59.69	-13	-46.69	0-360	150	V
5	5.62719	-75.87	Pk	35.2	-26.6	11.9	-55.37	-13	-42.37	0-360	150	V
6	7.49878	-77.77	Pk	35.5	-23.8	12.2	-53.87	-13	-40.87	0-360	150	V
1905 MHz												
1	3.78534	-75.06	Pk	33	-28.3	11.3	-59.06	-13	-46.06	0-360	149	H
2	5.69891	-76.63	Pk	35	-26.6	11.9	-56.33	-13	-43.33	0-360	149	H
3	7.60344	-77.84	Pk	35.7	-24.2	11.9	-54.44	-13	-41.44	0-360	149	H
4	3.79544	-75.92	Pk	32.9	-28.3	11.4	-59.92	-13	-46.92	0-360	149	V
5	5.68616	-74.56	Pk	35	-26.7	11.6	-54.66	-13	-41.66	0-360	149	V
6	7.58803	-76.54	Pk	35.6	-24.1	11.8	-53.24	-13	-40.24	0-360	149	V

**9.2.15. LTE BAND 26 (FCC PART 90S)**

**LIMITS**

FCC: §90.691

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

**QPSK LTE BAND 26 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 26 QPSK 15MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
821.5 MHz												
1	1.62953	-61.87	Pk	28.4	-31.7	12.3	-52.87	-13	-39.87	0-360	149	H
2	2.44394	-63.81	Pk	32.2	-30.4	10.6	-51.41	-13	-38.41	0-360	149	H
3	3.23603	-71.31	Pk	33	-29.1	12	-55.41	-13	-42.41	0-360	149	H
4	1.629	-66.28	Pk	28.4	-31.7	11.5	-58.08	-13	-45.08	0-360	149	V
5	2.44394	-68.42	Pk	32.2	-30.4	11.3	-55.32	-13	-42.32	0-360	149	V
6	3.23178	-70.24	Pk	33.1	-29	11.6	-54.54	-13	-41.54	0-360	149	V

**16QAM LTE BAND 26 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 26 16QAM 15MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
821.5 MHz												
1	1.62953	-65.32	Pk	28.4	-31.7	12.3	-56.32	-13	-43.32	0-360	149	H
2	2.44394	-68.14	Pk	32.2	-30.4	10.6	-55.74	-13	-42.74	0-360	149	H
3	3.24134	-71.18	Pk	32.9	-29.1	11.8	-55.58	-13	-42.58	0-360	149	H
4	1.629	-67.8	Pk	28.4	-31.7	11.5	-59.6	-13	-46.6	0-360	149	V
5	2.44447	-70.23	Pk	32.2	-30.4	11.3	-57.13	-13	-44.13	0-360	149	V
6	3.24984	-70.4	Pk	32.9	-29.3	11.6	-55.2	-13	-42.2	0-360	149	V

**9.2.16. LTE BAND 26 (FCC PART 22)**

**LIMITS**

FCC: §22.917(a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

**QPSK LTE BAND 26 (15.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/28/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 26 QPSK 15MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
831.5 MHz												
1	1.64972	-66.72	Pk	28.5	-31.7	12.5	-57.42	-13	-44.42	0-360	149	H
2	2.47422	-66.14	Pk	32.3	-30.4	11.3	-52.94	-13	-39.94	0-360	149	H
3	3.29659	-74.22	Pk	32.7	-29.2	12	-58.72	-13	-45.72	0-360	149	H
4	1.65291	-71.57	Pk	28.5	-31.7	11.3	-63.47	-13	-50.47	0-360	149	V
5	2.47369	-69.52	Pk	32.3	-30.4	11.5	-56.12	-13	-43.12	0-360	149	V
6	3.29819	-73.76	Pk	32.7	-29.2	12	-58.26	-13	-45.26	0-360	149	V
836.5 MHz												
1	1.6545	-70.61	Pk	28.6	-31.7	12.2	-61.51	-13	-48.51	0-360	149	H
2	2.48909	-70.92	Pk	32.3	-30.4	11.4	-57.62	-13	-44.62	0-360	149	H
3	3.312	-73.29	Pk	32.7	-29.3	11.4	-58.49	-13	-45.49	0-360	149	H
4	1.65928	-71.3	Pk	28.7	-31.6	11.4	-62.8	-13	-49.8	0-360	149	V
5	2.48697	-72.67	Pk	32.3	-30.4	11.6	-59.17	-13	-46.17	0-360	149	V
6	3.30934	-73.72	Pk	32.7	-29.3	11.9	-58.42	-13	-45.42	0-360	149	V
841.5 MHz												
1	1.67203	-71.66	Pk	28.8	-31.5	11.6	-62.76	-13	-49.76	0-360	149	H
2	2.50238	-72.28	Pk	32.3	-30.2	11.4	-58.78	-13	-45.78	0-360	149	H
3	3.33378	-73.01	Pk	32.8	-29.1	11.6	-57.71	-13	-44.71	0-360	149	H
4	1.66938	-69.02	Pk	28.7	-31.5	11.2	-60.62	-13	-47.62	0-360	149	V
5	2.5045	-70.81	Pk	32.3	-30.2	11.6	-57.11	-13	-44.11	0-360	149	V
6	3.33113	-73.05	Pk	32.8	-29.2	11.9	-57.55	-13	-44.55	0-360	149	V



**16QAM LTE BAND 26 (15.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/28/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 26 16QAM 15MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
831.5 MHz												
1	1.64919	-68.54	Pk	28.5	-31.7	12.5	-59.24	-13	-46.24	0-360	149	H
2	2.47475	-68.21	Pk	32.3	-30.4	11.3	-55.01	-13	-42.01	0-360	149	H
3	3.29394	-73.58	Pk	32.8	-29.2	12.1	-57.88	-13	-44.88	0-360	149	H
4	1.64866	-71.65	Pk	28.5	-31.7	11.4	-63.45	-13	-50.45	0-360	149	V
5	2.47422	-70.54	Pk	32.3	-30.4	11.5	-57.14	-13	-44.14	0-360	149	V
6	3.29341	-72.32	Pk	32.8	-29.2	11.9	-56.82	-13	-43.82	0-360	149	V
836.5 MHz												
1	1.65875	-70.9	Pk	28.7	-31.6	11.9	-61.9	-13	-48.9	0-360	149	H
2	2.48909	-70.25	Pk	32.3	-30.4	11.4	-56.95	-13	-43.95	0-360	149	H
3	3.31944	-74.17	Pk	32.7	-29.3	11.3	-59.47	-13	-46.47	0-360	149	H
4	1.65928	-70.87	Pk	28.7	-31.6	11.4	-62.37	-13	-49.37	0-360	149	V
5	2.48856	-70.48	Pk	32.3	-30.4	11.6	-56.98	-13	-43.98	0-360	149	V
6	3.3205	-73.47	Pk	32.7	-29.3	11.6	-58.47	-13	-45.47	0-360	149	V
841.5 MHz												
1	1.66991	-71.87	Pk	28.8	-31.5	11.6	-62.97	-13	-49.97	0-360	149	H
2	2.50238	-72.02	Pk	32.3	-30.2	11.4	-58.52	-13	-45.52	0-360	149	H
3	3.33219	-73.38	Pk	32.8	-29.1	11.6	-58.08	-13	-45.08	0-360	149	H
4	1.66938	-67.26	Pk	28.7	-31.5	11.2	-58.86	-13	-45.86	0-360	149	V
5	2.50397	-71.55	Pk	32.3	-30.2	11.6	-57.85	-13	-44.85	0-360	149	V
6	3.33113	-74.35	Pk	32.8	-29.2	11.9	-58.85	-13	-45.85	0-360	149	V

**9.2.17. LTE BAND 30**

**LIMITS**

FCC: §27.53 (a)

For mobile and portable stations operating in the 2305-2315 MHz: by a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

RSS195§5.6

The transmitter unwanted emissions shall be measured with a resolution bandwidth of 1 MHz. A smaller resolution bandwidth is permitted provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz. However, in the 1 MHz bands immediately adjacent to the edges of the frequency range(s) in which the equipment is allowed to operate, a resolution bandwidth of as close as possible to, without being less than 1% of the occupied bandwidth, shall be employed provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz.

RSS195§5.6.2 Mobile, Portable and Low-Power Fixed Subscriber Equipment

The power of any emission outside the frequency range(s) in which the equipment operates shall be attenuated below the transmitter power, P(dBW), by the amount indicated in Table 2 and graphically represented in Figure 2, where p is the transmitter output power measured in watts.

**QPSK LTE BAND 30 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/23/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 30 QPSK 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbi (dB)	Amp/Cbi (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2310 MHz												
1	4.621	-74.75	Pk	33.9	-27.6	11.7	-56.75	-40	-16.75	0-360	149	H
2	6.92131	-75.33	Pk	35.5	-24.8	11.8	-52.83	-40	-12.83	0-360	149	H
3	9.20675	-77.43	Pk	36.3	-21.4	12.1	-50.43	-40	-10.43	0-360	149	H
4	2.30528	-63.05	Pk	31.4	-30.8	11.4	-51.05	-40	-11.05	0-360	149	V
5	4.61144	-75.29	Pk	33.9	-27.7	11.8	-57.29	-40	-17.29	0-360	149	V
6	6.92397	-76.56	Pk	35.6	-24.8	12.1	-53.66	-40	-13.66	0-360	149	V

**16QAM LTE BAND 30 (10.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/23/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 30 16QAM 10MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2310 MHz												
1	4.60347	-74.76	Pk	33.9	-27.8	11.4	-57.26	-40	-17.26	0-360	149	H
2	6.91972	-76.39	Pk	35.6	-24.8	11.8	-53.79	-40	-13.79	0-360	149	H
3	9.22641	-76.78	Pk	36.3	-21.4	11.8	-50.08	-40	-10.08	0-360	149	H
4	4.61144	-74.09	Pk	33.9	-27.7	11.8	-56.09	-40	-16.09	0-360	149	V
5	6.91706	-76.47	Pk	35.6	-24.9	12.1	-53.67	-40	-13.67	0-360	149	V
6	9.21259	-78.5	Pk	36.4	-21.3	12	-51.4	-40	-11.4	0-360	149	V

**9.2.18. LTE BAND 38 (IC)**

**LIMITS**

**RSS199§4.5**

Equipment shall comply with the following unwanted emission limits:

- a. for base station and fixed subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least  $43 + 10 \log_{10} p$
- b. for mobile subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least:
  - i.  $40 + 10 \log_{10} p$  from the channel edges to 5 MHz away
  - ii.  $43 + 10 \log_{10} p$  between 5 MHz and X MHz from the channel edges, and
  - iii.  $55 + 10 \log_{10} p$  at X MHz and beyond from the channel edges

In addition, the attenuation shall not be less than  $43 + 10 \log_{10} p$  on all frequencies between 2490.5 MHz and 2496 MHz, and  $55 + 10 \log_{10} p$  at or below 2490.5 MHz.

In (a) and (b), p is the transmitter power measured in watts and X is 6 MHz or the equipment occupied bandwidth, whichever is greater.

**QPSK LTE BAND 38 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/10/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 38 QPSK 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2580 MHz												
1	5.14109	-76.11	Pk	34.4	-27	11.8	-56.91	-25	-31.91	0-360	149	H
2	7.72456	-76.94	Pk	35.7	-23.6	12	-52.84	-25	-27.84	0-360	149	H
3	10.28359	-76.07	Pk	37.4	-20.5	11.8	-47.37	-25	-22.37	0-360	149	H
4	5.14375	-76.13	Pk	34.4	-27	12	-56.73	-25	-31.73	0-360	149	V
5	7.70491	-79.24	Pk	35.7	-23.8	11.6	-55.74	-25	-30.74	0-360	149	V
6	10.28413	-76.08	Pk	37.4	-20.6	11.8	-47.48	-25	-22.48	0-360	149	V
2595 MHz												
1	5.19847	-75.89	Pk	34.4	-26.9	12.2	-56.19	-25	-31.19	0-360	149	H
2	7.78088	-77.55	Pk	35.6	-23.7	12.1	-53.55	-25	-28.55	0-360	149	H
3	10.34416	-76.08	Pk	37.5	-20.3	11.8	-47.08	-25	-22.08	0-360	149	H
4	5.19528	-76.61	Pk	34.4	-27	12.4	-56.81	-25	-31.81	0-360	149	V
5	7.7915	-77.91	Pk	35.7	-23.7	12.4	-53.51	-25	-28.51	0-360	149	V
6	10.34469	-77.05	Pk	37.5	-20.3	11.7	-48.15	-25	-23.15	0-360	149	V
2610 MHz												
1	5.199	-76.54	Pk	34.4	-26.9	12.2	-56.84	-25	-31.84	0-360	149	H
2	7.79947	-78.17	Pk	35.7	-23.6	12.2	-53.87	-25	-28.87	0-360	149	H
3	10.41747	-78.85	Pk	37.6	-20.8	11.7	-50.35	-25	-25.35	0-360	149	H
4	5.19688	-76.96	Pk	34.4	-27	12.4	-57.16	-25	-32.16	0-360	149	V
5	7.8	-78.04	Pk	35.7	-23.6	12.4	-53.54	-25	-28.54	0-360	149	V
6	10.40472	-79.29	Pk	37.5	-20.7	11.7	-50.79	-25	-25.79	0-360	149	V

**16QAM LTE BAND 38 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	1/10/20
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 38 16QAM 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2580 MHz												
1	5.15172	-77.54	Pk	34.4	-26.9	11.9	-58.14	-25	-33.14	0-360	149	H
2	7.71288	-77.53	Pk	35.6	-23.7	11.8	-53.83	-25	-28.83	0-360	149	H
3	10.28466	-76.55	Pk	37.4	-20.5	11.8	-47.85	-25	-22.85	0-360	149	H
4	5.13844	-75.92	Pk	34.5	-27.1	12	-56.52	-25	-31.52	0-360	149	V
5	7.71288	-79.16	Pk	35.6	-23.7	11.7	-55.56	-25	-30.56	0-360	149	V
6	10.28466	-78.96	Pk	37.4	-20.5	11.8	-50.26	-25	-25.26	0-360	149	V
2595 MHz												
1	5.17775	-76.43	Pk	34.4	-27.1	11.6	-57.53	-25	-32.53	0-360	149	H
2	7.76388	-78	Pk	35.7	-23.8	11.9	-54.2	-25	-29.2	0-360	149	H
3	10.34416	-75.43	Pk	37.5	-20.3	11.8	-46.43	-25	-21.43	0-360	149	H
4	5.17084	-76.76	Pk	34.4	-27	11.8	-57.56	-25	-32.56	0-360	149	V
5	7.75272	-78.56	Pk	35.7	-23.6	11.9	-54.56	-25	-29.56	0-360	149	V
6	10.35319	-78.74	Pk	37.4	-20.2	11.9	-49.64	-25	-24.64	0-360	149	V
2610 MHz												
1	5.20644	-77.11	Pk	34.4	-26.7	12.2	-57.21	-25	-32.21	0-360	149	H
2	7.79681	-77.48	Pk	35.7	-23.7	12.2	-53.28	-25	-28.28	0-360	149	H
3	10.40419	-77.1	Pk	37.5	-20.7	11.7	-48.6	-25	-23.6	0-360	149	H
4	5.20219	-76.49	Pk	34.3	-26.9	12.4	-56.69	-25	-31.69	0-360	149	V
5	7.80744	-76.66	Pk	35.8	-23.7	12.2	-52.36	-25	-27.36	0-360	149	V
6	10.40366	-78.36	Pk	37.5	-20.7	11.8	-49.76	-25	-24.76	0-360	149	V

**9.2.20. LTE BAND 41 (FCC) HPUE**

**LIMITS**

FCC: §27.53 (m)

At least 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.

**QPSK LTE BAND 41 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/31/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 41 QPSK 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2506 MHz												
1	4.97534	-76.51	Pk	34.2	-27	12	-57.31	-25	-32.31	0-360	149	H
2	7.46478	-76.75	Pk	35.5	-24.3	11.8	-53.75	-25	-28.75	0-360	149	H
3	10.02009	-78.53	Pk	37	-20.8	12.1	-50.23	-25	-25.23	0-360	149	H
4	4.99872	-74.77	Pk	34.3	-27.2	11.8	-55.87	-25	-30.87	0-360	149	V
5	7.46744	-77.24	Pk	35.5	-24.2	11.8	-54.14	-25	-29.14	0-360	149	V
6	9.94997	-77.9	Pk	37	-20.6	12	-49.5	-25	-24.5	0-360	149	V
2593 MHz												
1	5.17084	-76.39	Pk	34.4	-27	11.6	-57.39	-25	-32.39	0-360	149	H
2	7.75272	-77.63	Pk	35.7	-23.6	11.8	-53.73	-25	-28.73	0-360	149	H
3	10.33725	-73.11	Pk	37.4	-20.2	11.8	-44.11	-25	-19.11	0-360	149	H
4	5.14163	-75.92	Pk	34.4	-27	12	-56.52	-25	-31.52	0-360	149	V
5	7.75219	-76.81	Pk	35.7	-23.6	11.9	-52.81	-25	-27.81	0-360	149	V
6	10.33672	-72.8	Pk	37.4	-20.3	11.9	-43.8	-25	-18.8	0-360	149	V
2680 MHz												
1	5.34934	-76.27	Pk	34.6	-26.7	12	-56.37	-25	-31.37	0-360	149	H
2	8.01356	-73.26	Pk	35.8	-23.3	11.9	-48.86	-25	-23.86	0-360	149	H
3	10.68522	-71.51	Pk	37.9	-20.3	11.5	-42.41	-25	-17.41	0-360	149	H
4	5.34456	-75.72	Pk	34.6	-26.7	12	-55.82	-25	-30.82	0-360	149	V
5	8.01356	-71.42	Pk	35.8	-23.3	11.9	-47.02	-25	-22.02	0-360	149	V
6	10.68469	-75.35	Pk	37.9	-20.3	11.5	-46.25	-25	-21.25	0-360	149	V

**16QAM LTE BAND 41 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/31/19
Test Engineer:	19498
Configuration:	EUT + Support Equipment
Mode:	LTE 41 16QAM 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2506 MHz												
1	5.01838	-75.22	Pk	34.3	-27.1	12	-56.02	-25	-31.02	0-360	149	H
2	7.49081	-76.71	Pk	35.6	-24	11.9	-53.21	-25	-28.21	0-360	149	H
3	9.97122	-78.34	Pk	37	-20.6	12	-49.94	-25	-24.94	0-360	149	H
4	5.01519	-75.41	Pk	34.3	-27.1	12.2	-56.01	-25	-31.01	0-360	149	V
5	7.44619	-75.89	Pk	35.5	-24.3	12	-52.69	-25	-27.69	0-360	149	V
6	9.98875	-77.01	Pk	37	-20.8	11.7	-49.11	-25	-24.11	0-360	149	V
2593 MHz												
1	5.11825	-74.95	Pk	34.4	-27	11.5	-56.05	-25	-31.05	0-360	149	H
2	7.81009	-77.01	Pk	35.8	-23.7	12	-52.91	-25	-27.91	0-360	149	H
3	10.33672	-71.76	Pk	37.4	-20.3	11.8	-42.86	-25	-17.86	0-360	149	H
4	5.19209	-76.48	Pk	34.4	-26.9	12.3	-56.68	-25	-31.68	0-360	149	V
5	7.78513	-77.04	Pk	35.6	-23.8	12.3	-52.94	-25	-27.94	0-360	149	V
6	10.33725	-75.68	Pk	37.4	-20.2	11.8	-46.68	-25	-21.68	0-360	149	V
2680 MHz												
1	5.34244	-76.35	Pk	34.6	-26.7	11.7	-56.75	-25	-31.75	0-360	149	H
2	8.01356	-73.57	Pk	35.8	-23.3	11.9	-49.17	-25	-24.17	0-360	149	H
3	10.68469	-71.41	Pk	37.9	-20.3	11.5	-42.31	-25	-17.31	0-360	149	H
4	5.34244	-75.32	Pk	34.6	-26.7	11.9	-55.52	-25	-30.52	0-360	149	V
5	8.01303	-72.75	Pk	35.8	-23.4	11.9	-48.45	-25	-23.45	0-360	149	V
6	10.68469	-69.89	Pk	37.9	-20.3	11.5	-40.79	-25	-15.79	0-360	149	V

**9.2.21. LTE BAND 41 (IC)**

**LIMITS**

RSS199§4.5

Equipment shall comply with the following unwanted emission limits:

- a. for base station and fixed subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least  $43 + 10 \log_{10} p$
- b. for mobile subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least:
  - i.  $40 + 10 \log_{10} p$  from the channel edges to 5 MHz away
  - ii.  $43 + 10 \log_{10} p$  between 5 MHz and X MHz from the channel edges, and
  - iii.  $55 + 10 \log_{10} p$  at X MHz and beyond from the channel edges

In addition, the attenuation shall not be less than  $43 + 10 \log_{10} p$  on all frequencies between 2490.5 MHz and 2496 MHz, and  $55 + 10 \log_{10} p$  at or below 2490.5 MHz.

In (a) and (b), p is the transmitter power measured in watts and X is 6 MHz or the equipment occupied bandwidth, whichever is greater.

**QPSK LTE BAND 41 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	02/27/20
Test Engineer:	19497
Configuration:	EUT + Support Equipment
Mode:	LTE 41 QPSK 20MHz
Chamber #:	Chamber J

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2510 MHz												
1	5.04866	-68.68	Pk	34.3	-31	12.1	-53.28	-25	-28.28	0-360	149	H
2	7.50303	-70.54	Pk	35.6	-27.9	12.1	-50.74	-25	-25.74	0-360	149	H
3	10.00363	-69.95	Pk	37.1	-25.1	12.4	-45.55	-25	-20.55	0-360	149	H
4	5.00138	-69.03	Pk	34.1	-31.3	11.8	-54.43	-25	-29.43	0-360	149	V
5	7.50356	-67	Pk	35.6	-27.9	11.9	-47.4	-25	-22.4	0-360	149	V
6	10.00469	-67.27	Pk	37.1	-25.1	12.2	-43.07	-25	-18.07	0-360	149	V
2595 MHz												
1	5.17138	-68.04	Pk	34.2	-31	12.2	-52.64	-25	-27.64	0-360	149	H
2	7.8085	-71.7	Pk	35.8	-27.6	12.2	-51.3	-25	-26.3	0-360	149	H
3	10.34416	-67.5	Pk	37.5	-25.4	12.4	-43	-25	-18	0-360	149	H
4	5.17297	-68.56	Pk	34.2	-31	12.2	-53.16	-25	-28.16	0-360	149	V
5	7.74581	-71.85	Pk	35.8	-27.6	12.2	-51.45	-25	-26.45	0-360	149	V
6	10.34416	-68.83	Pk	37.5	-25.4	12.1	-44.63	-25	-19.63	0-360	149	V
2680 MHz												
1	5.33341	-68.21	Pk	34.5	-31.1	12.2	-52.61	-25	-27.61	0-360	149	H
2	8.01303	-69.1	Pk	35.7	-27.4	12	-48.8	-25	-23.8	0-360	149	H
3	10.68416	-67.74	Pk	37.9	-24.8	12.4	-42.24	-25	-17.24	0-360	149	H
4	5.33606	-68.81	Pk	34.5	-31	12	-53.31	-25	-28.31	0-360	149	V
5	8.01303	-68.76	Pk	35.7	-27.4	11.9	-48.56	-25	-23.56	0-360	149	V
6	10.68416	-59.94	Pk	37.9	-24.8	12.4	-34.44	-25	-9.44	0-360	149	V



**16QAM LTE BAND 41 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	02/27/20
Test Engineer:	19497
Configuration:	EUT + Support Equipment
Mode:	LTE 41 16QAM 20MHz
Chamber #:	Chamber J

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2510 MHz												
1	4.99447	-68.74	Pk	34.1	-31.3	12.3	-53.64	-25	-28.64	0-360	149	H
2	7.50303	-70.93	Pk	35.6	-27.9	12.1	-51.13	-25	-26.13	0-360	149	H
3	10.07588	-72.73	Pk	37.2	-25.2	12.5	-48.23	-25	-23.23	0-360	149	H
4	4.99288	-68.63	Pk	34.1	-31.2	11.7	-54.03	-25	-29.03	0-360	149	V
5	7.50303	-68.61	Pk	35.6	-27.9	11.9	-49.01	-25	-24.01	0-360	149	V
6	10.00416	-67.79	Pk	37.1	-25.1	12.2	-43.59	-25	-18.59	0-360	149	V
2595 MHz												
1	5.20059	-68.46	Pk	34.2	-31.1	12.1	-53.26	-25	-28.26	0-360	149	H
2	7.69588	-70.79	Pk	35.8	-27.6	12.3	-50.29	-25	-25.29	0-360	149	H
3	10.34416	-68.2	Pk	37.5	-25.4	12.4	-43.7	-25	-18.7	0-360	149	H
4	5.16819	-68.35	Pk	34.3	-31	12	-53.05	-25	-28.05	0-360	149	V
5	7.73784	-71.83	Pk	35.8	-27.6	12.1	-51.53	-25	-26.53	0-360	149	V
6	10.34416	-67.51	Pk	37.5	-25.4	12.1	-43.31	-25	-18.31	0-360	149	V
2680 MHz												
1	5.34244	-69.1	Pk	34.4	-31	12.3	-53.4	-25	-28.4	0-360	149	H
2	8.01303	-68.17	Pk	35.7	-27.4	12	-47.87	-25	-22.87	0-360	149	H
3	10.68469	-68.56	Pk	37.9	-24.7	12.4	-42.96	-25	-17.96	0-360	149	H
4	5.34775	-69.73	Pk	34.5	-30.9	12.2	-53.93	-25	-28.93	0-360	149	V
5	8.01303	-67.41	Pk	35.7	-27.4	11.9	-47.21	-25	-22.21	0-360	149	V
6	10.68416	-62.62	Pk	37.9	-24.8	12.4	-37.12	-25	-12.12	0-360	149	V

**9.2.22. LTE BAND 66**

**LIMITS**

FCC: §27.53 (h)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

RSS139§6.6

- (i) In the first 1.0 MHz bands immediately outside and adjacent to the equipment's smallest operating frequency block, Footnote 2 which can contain the equipment's occupied bandwidth, the emission power per any 1% of the emission bandwidth shall be attenuated below the transmitter output power P (in dBW) by at least 43 + 10 log 10 p (watts) dB.
- (ii) After the first 1.0 MHz outside the equipment's smallest operating frequency block, which can contain the equipment's occupied bandwidth, the emission power in any 1 MHz bandwidth shall be attenuated below the transmitter output power P (in dBW) by at least 43 + 10 log 10 p (watts) dB.

**QPSK LTE BAND 66 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/31/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 66 QPSK 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1720 MHz												
1	3.41294	-74.63	Pk	32.7	-29.2	12.1	-59.03	-13	-46.03	0-360	149	H
2	5.13313	-77.29	Pk	34.4	-26.9	11.8	-57.99	-13	-44.99	0-360	149	H
3	6.85863	-77.12	Pk	35.6	-25.2	11.7	-55.02	-13	-42.02	0-360	149	H
4	3.4225	-75.86	Pk	32.7	-29.3	11.8	-60.66	-13	-47.66	0-360	149	V
5	5.13844	-77.14	Pk	34.5	-27.1	12	-57.74	-13	-44.74	0-360	149	V
6	6.83419	-77.45	Pk	35.5	-25.1	11.5	-55.55	-13	-42.55	0-360	149	V
1745 MHz												
1	3.47456	-75.3	Pk	32.8	-29	11.7	-59.8	-13	-46.8	0-360	149	H
2	5.21016	-77.74	Pk	34.4	-26.8	12.1	-58.04	-13	-45.04	0-360	149	H
3	6.93566	-77.8	Pk	35.7	-24.7	11.7	-55.1	-13	-42.1	0-360	149	H
4	3.47616	-75.71	Pk	32.8	-29	11.6	-60.31	-13	-47.31	0-360	149	V
5	5.20591	-77.57	Pk	34.3	-26.7	12.3	-57.67	-13	-44.67	0-360	149	V
6	6.95159	-76.75	Pk	35.7	-24.7	11.7	-54.05	-13	-41.05	0-360	149	V
1770 MHz												
1	3.52928	-75.44	Pk	32.9	-28.4	11.5	-59.44	-13	-46.44	0-360	149	H
2	5.28559	-75.61	Pk	34.6	-26.7	11.7	-56.01	-13	-43.01	0-360	149	H
3	7.04669	-77.86	Pk	35.7	-24.9	11.8	-55.26	-13	-42.26	0-360	149	H
4	3.52184	-75.33	Pk	32.9	-28.6	11.9	-59.13	-13	-46.13	0-360	149	V
5	5.28028	-77.16	Pk	34.6	-26.7	12.1	-57.16	-13	-44.16	0-360	149	V
6	7.04616	-78.21	Pk	35.7	-24.8	11.9	-55.41	-13	-42.41	0-360	149	V

**16QAM LTE BAND 66 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/31/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 66 16QAM 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1720 MHz												
1	3.41134	-74.93	Pk	32.7	-29.2	12.1	-59.33	-13	-46.33	0-360	149	H
2	5.12038	-76.85	Pk	34.4	-27	11.5	-57.95	-13	-44.95	0-360	149	H
3	6.84216	-77	Pk	35.6	-25.3	11.4	-55.3	-13	-42.3	0-360	149	H
4	3.42303	-75.38	Pk	32.7	-29.2	11.8	-60.08	-13	-47.08	0-360	149	V
5	5.13259	-77.09	Pk	34.4	-27	11.9	-57.79	-13	-44.79	0-360	149	V
6	6.83419	-77	Pk	35.5	-25.1	11.5	-55.1	-13	-42.1	0-360	149	V
1745 MHz												
1	3.47669	-74.11	Pk	32.8	-29	11.6	-58.71	-13	-45.71	0-360	149	H
2	5.21334	-76.91	Pk	34.4	-26.7	12	-57.21	-13	-44.21	0-360	149	H
3	6.93831	-77.78	Pk	35.6	-24.6	11.7	-55.08	-13	-42.08	0-360	149	H
4	3.46659	-76.09	Pk	32.8	-29.1	11.6	-60.79	-13	-47.79	0-360	149	V
5	5.21388	-76.5	Pk	34.4	-26.7	12.2	-56.6	-13	-43.6	0-360	149	V
6	6.95319	-76.92	Pk	35.7	-24.6	11.7	-54.12	-13	-41.12	0-360	149	V
1770 MHz												
1	3.52981	-75.09	Pk	32.9	-28.4	11.5	-59.09	-13	-46.09	0-360	149	H
2	5.27763	-77.15	Pk	34.6	-26.7	11.9	-57.35	-13	-44.35	0-360	149	H
3	7.05625	-77.38	Pk	35.6	-24.7	11.8	-54.68	-13	-41.68	0-360	149	H
4	3.52184	-74.28	Pk	32.9	-28.6	11.9	-58.08	-13	-45.08	0-360	149	V
5	5.28825	-76.31	Pk	34.6	-26.7	11.9	-56.51	-13	-43.51	0-360	149	V
6	7.04456	-77.89	Pk	35.7	-24.9	11.8	-55.29	-13	-42.29	0-360	149	V

**9.2.23. LTE BAND 71**

**LIMITS**

FCC: §27.53 (g)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

RSS130§4.7

**4.7.1 General unwanted emissions limits**

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least 43 + 10 log<sub>10</sub> p (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

**4.7.2 Additional unwanted emissions limits**

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

- a. the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
  - i. 76 + 10 log<sub>10</sub> p (watts), dB, for base and fixed equipment and
  - ii. 65 + 10 log<sub>10</sub> p (watts), dB, for mobile and portable equipment
- b. the e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

**QPSK LTE BAND 71 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 71 QPSK 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
673 MHz												
1	1.32406	-72.9	Pk	29.4	-32.3	13.8	-62	-13	-49	0-360	149	H
2	1.99184	-69.73	Pk	30.9	-31	11.3	-58.53	-13	-45.53	0-360	149	H
3	2.65059	-75.76	Pk	32.4	-29.9	11.7	-61.56	-13	-48.56	0-360	149	H
4	1.32034	-73.9	Pk	29.3	-32.3	13.1	-63.8	-13	-50.8	0-360	149	V
5	1.99184	-71.77	Pk	30.9	-31	11.6	-60.27	-13	-47.27	0-360	149	V
6	2.649	-74.98	Pk	32.4	-29.9	11.9	-60.58	-13	-47.58	0-360	149	V
680.5 MHz												
1	1.34266	-72.26	Pk	29.5	-32.3	10.8	-64.26	-13	-51.26	0-360	149	H
2	2.01416	-66.47	Pk	30.9	-31.1	11.4	-55.27	-13	-42.27	0-360	149	H
3	2.68406	-74.59	Pk	32.4	-29.9	11.5	-60.59	-13	-47.59	0-360	149	H
4	1.34266	-71.91	Pk	29.5	-32.3	10.1	-64.61	-13	-51.61	0-360	149	V
5	2.01469	-71.3	Pk	30.8	-31.1	12.2	-59.4	-13	-46.4	0-360	149	V
6	2.68513	-74.78	Pk	32.4	-29.9	11.3	-60.98	-13	-47.98	0-360	149	V
688 MHz												
1	1.35753	-73.91	Pk	29.7	-32.3	11.4	-65.11	-13	-52.11	0-360	149	H
2	2.037	-66.48	Pk	31	-31	10	-56.48	-13	-43.48	0-360	149	H
3	2.71169	-75.04	Pk	32.4	-30.1	11.6	-61.14	-13	-48.14	0-360	149	H
4	1.36231	-74.14	Pk	29.6	-32.2	11.4	-65.34	-13	-52.34	0-360	149	V
5	2.037	-68.69	Pk	31	-31	10.7	-57.99	-13	-44.99	0-360	149	V
6	2.70797	-75.59	Pk	32.4	-30	11.7	-61.49	-13	-48.49	0-360	149	V

**16QAM LTE BAND 71 (20.0MHZ BANDWIDTH)**

Company:	Samsung
Project #:	13171837
Date:	12/30/19
Test Engineer:	19480
Configuration:	EUT + Support Equipment
Mode:	LTE 71 16QAM 20MHz
Chamber #:	Chamber I

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	AF T862 (dB/m)	Amp/Cbl (dB)	Amp/Cbl (dB)	Corrected Reading (dBm)	WWAN Harmonics Limit	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
673 MHz												
1	1.32831	-70.96	Pk	29.3	-32.4	13.5	-60.56	-13	-47.56	0-360	149	H
2	1.99184	-65.37	Pk	30.9	-31	11.3	-54.17	-13	-41.17	0-360	149	H
3	2.65484	-74.88	Pk	32.4	-29.9	11.7	-60.68	-13	-47.68	0-360	149	H
4	1.32406	-74.35	Pk	29.4	-32.3	12.5	-64.75	-13	-51.75	0-360	149	V
5	1.99184	-70.8	Pk	30.9	-31	11.6	-59.3	-13	-46.3	0-360	149	V
6	2.65431	-75.16	Pk	32.4	-29.9	11.9	-60.76	-13	-47.76	0-360	149	V
680.5 MHz												
1	1.34266	-68.98	Pk	29.5	-32.3	10.8	-60.98	-13	-47.98	0-360	149	H
2	2.01469	-65.37	Pk	30.8	-31.1	11.4	-54.27	-13	-41.27	0-360	149	H
3	2.68778	-73.89	Pk	32.4	-29.8	11.3	-59.99	-13	-46.99	0-360	149	H
4	1.34266	-71.52	Pk	29.5	-32.3	10.1	-64.22	-13	-51.22	0-360	149	V
5	2.01469	-69.01	Pk	30.8	-31.1	12.2	-57.11	-13	-44.11	0-360	149	V
6	2.68247	-74.58	Pk	32.4	-29.9	11.2	-60.88	-13	-47.88	0-360	149	V
688 MHz												
1	1.35434	-73.62	Pk	29.7	-32.3	11	-65.22	-13	-52.22	0-360	149	H
2	2.037	-62.76	Pk	31	-31	10	-52.76	-13	-39.76	0-360	149	H
3	2.71647	-75.66	Pk	32.4	-30.1	11.8	-61.56	-13	-48.56	0-360	149	H
4	1.35275	-73.28	Pk	29.7	-32.3	10.7	-65.18	-13	-52.18	0-360	149	V
5	2.037	-66.34	Pk	31	-31	10.7	-55.64	-13	-42.64	0-360	149	V
6	2.71541	-75.62	Pk	32.4	-30.1	11.8	-61.52	-13	-48.52	0-360	149	V