

FCC ANT+ REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
16677, Rep. of Korea

Date of Issue:
June 25, 2020

Test Site/Location:
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-
si, Gyeonggi-do, 17383 KOREA

Report No.: HCT-RF-2006-FC027-R1

FCC ID:	A3LSMA516V
APPLICANT:	SAMSUNG Electronics Co., Ltd.

Model: SM-A516V
EUT Type: Mobile Phone
Max. RF Output Power: 92.50 dBuV/m @3 m
Frequency Range: 2402 MHz -2480 MHz
Modulation type GFSK
FCC Classification: Low Power communication Device Transmitter(DXX)
FCC Rule Part(s): Part 15 subpart C 15.249

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

Report No.: HCT-RF-2006-FC027-R1

REVIEWED BY



Report prepared by : Jin Gwan Lee
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2006-FC027	June 18, 2020	- First Approval Report
HCT-RF-2006-FC027-R1	June 25, 2020	- On Page 12, 26, 31, Typo correction

Table of Contents

REVIEWED BY	2
1. EUT DESCRIPTION	5
2. TEST METHODOLOGY	6
EUT CONFIGURATION	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES	7
3. INSTRUMENT CALIBRATION	7
4. FACILITIES AND ACCREDITATIONS	7
FACILITIES	7
EQUIPMENT	7
5. ANTENNA REQUIREMENTS.....	7
6. MEASUREMENT UNCERTAINTY	8
7. DESCRIPTION OF TESTS.....	9
8. SUMMARY TEST OF RESULTS	22
9. TEST RESULT	23
9.1 DUTY CYCLE.....	23
9.2 OCCUPIED BANDWIDTH	24
9.3 RADIATED MEASUREMENT.....	26
9.3.1 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT	26
9.3.2 RADIATED SPURIOUS EMISSIONS.....	28
9.3.3 RADIATED BAND EDGES MEASUREMENTS.....	31
9.4 POWERLINE CONDUCTED EMISSIONS	33
10. LIST OF TEST EQUIPMENT	37
11. ANNEX A_ TEST SETUP PHOTO	39

1. EUT DESCRIPTION

Model	SM-A516V
Additional Model	-
EUT Type	Mobile Phone
Power Supply	DC 3.88 V
Battery Information	Model: EB-BA516AMY Type: Li-ion Battery
Travel Adapter Information	Model : EP-TA200 Manufacture: DONG YANG E&P
Data Cable Information	Model : EP-DR140ABZ Manufacture: RFTech
Ear-jack Information	Model : EHS64AVFWE Manufacture: ALMUS
Frequency Range	2402 MHz - 2480 MHz
Max. RF Output Power	Peak : 92.50 dBuV/m @3 m Average : 60.62 dBuV/m @3 m
Modulation Type	GFSK
Number of Channels	79 Channels
Antenna Specification	Antenna type: Metal + LDS Peak Gain : -0.10 dBi
Date(s) of Tests	May 12, 2020 ~ June 02, 2020

2. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) Operating Under §15.249” were used in the measurement.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.249 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1 GHz. For average measurements above 1 GHz, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in section 9.1

- DCCF = $20\log_{10}(\text{Pulse width} / \text{Period of the pulse train})$, (RBW = 1 MHz, VBW = 3 MHz)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test overview


§15.35(c)

: Unless otherwise specified, e.g. § 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification

Test Configuration




7.2. Occupied Bandwidth

Test overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.


- 1) RBW = 1% to 3% of the 99% bandwidth.
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize

Note :

We tested Occupied Bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. 20dB Bandwidth

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

- 1) RBW = 1% to 5% of the 20dB bandwidth.
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize

Note :

We tested 20dB Bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer.

7.4. Fundamental Field Strength Level

Limit

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
2400-2483.5 MHz	50	500


§15.249(e):

The peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

The maximum permissible average field strength of fundamental level is 50 mV/m (93.98 dBuV/m).

The maximum permissible peak field strength of fundamental level is 500 mV/m (113.98 dBuV/m).

Test Configuration



Test Procedure

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. The unit was tested with its standard battery.
7. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency : 2402MHz, 2441MHz, 2480MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - (2) Measurement Type(Average):
 - Average value of pulsed emissions
 - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in section 9.1.
 - DCCF = $20\log_{10}(\text{Pulse width} / \text{Period of the pulse train})$
8. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
9. Total(Peak) = Peak Reading Value + Antenna Factor(A.F) - Amp Gain(A.G) + Cable Loss(C.L)
+ Distance Factor(D.F)
Total(Average) = Peak Reading Value + Antenna Factor(A.F) - Amp Gain(A.G) + Cable Loss(C.L)
+ Distance Factor(D.F) + Duty Cycle Correction Factor

7.5. Radiated Test

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

§15.249(d):
Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.


§15.249(e):
The peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40\log(3\text{ m}/300\text{ m}) = - 80\text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40\log(3\text{ m}/30\text{ m}) = - 40\text{ dB}$
Measurement Distance : 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 9 kHz
 - VBW \geq 3RBW
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. The Hybrid antenna was placed at a location 3m from the EUT, which is varied from 1m to 4m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 100 kHz
 - VBW \geq 3 x RBW
 - (2) Measurement Type(Quasi-peak):
 - Measured Frequency Range : 30 MHz – 1 GHz
 - Detector = Quasi-Peak
 - RBW = 120 kHz
- ※ In general, (1) is used mainly
7. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW \geq 3x RBW

(2) Measurement Type(Average):

- Average value of pulsed emissions
- Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in section 9.1.
- $DCCF = 20\log_{10}(\text{Pulse width} / \text{Period of the pulse train})$

9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

10. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)

11. Total(Peak) = Peak Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) – Amp Gain(A.G)
+ Distance Factor(D.F)

Total(Average) = Peak Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) – Amp Gain(A.G)
+ Distance Factor(D.F) + Duty Cycle Correction Factor

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. The unit was tested with its standard battery.
7. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range = 2310 MHz ~ 2400 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW \geq 3 x RBW

(2) Measurement Type(Average):

- Measured Frequency Range = 2310 MHz ~ 2400 MHz/ 2483.5 MHz ~ 2500 MHz
- Average value of pulsed emissions
- Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in section 9.1.
- DCCF = $20\log_{10}(\text{Pulse width} / \text{Period of the pulse train})$

8. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
9. Total(Peak) = Peak Reading Value + Antenna Factor(A.F) - Amp Gain(A.G) + Cable Loss(C.L)
+ Distance Factor(D.F)

$$\text{Total(Average)} = \text{Peak Reading Value} + \text{Antenna Factor(A.F)} - \text{Amp Gain(A.G)} + \text{Cable Loss(C.L)} \\ + \text{Distance Factor(D.F)} + \text{Duty Cycle Correction Factor}$$

7.6. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

7.7. Worst case configuration and mode

Fundamental Field Strength Level & Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Fundamental Field Strength Level : X
 - Radiated test : X
3. All period were investigated and the worst case period results are reported.
 - All period : Period 256, Period 128, Period 64, Period 32, Period 16, Period 8, Period 4, Period 1
 - Worstcase : Period 128
4. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Earphone, etc)+Travel Adapter
Stand alone + Travel Adapter
 - Worstcase : Stand alone + Travel Adapter

Duty Cycle & Occupied Bandwidth

1. All period were investigated and the worst case period results are reported.
 - All period : Period 256, Period 128, Period 64, Period 32, Period 16, Period 8, Period 4, Period 1
 - Worstcase : Period 128

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
Occupied Bandwidth	§2.1049	N/A	Conducted	PASS
20dB Bandwidth	§15.215	N/A		PASS
Duty Cycle	§15.35(c)	N/A		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.5		PASS
Fundamental Field Strength Level	§15.249(a)(e)	< 50 mV/m	Radiated	PASS
Harmonic Field Strength Level	§15.249(a)(e)	< 500 uV/m		PASS
General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	§15.205, §15.209, §15.249(d)(e)	< 15.209 limits or 50dB below the level of the fundamental		PASS

9. TEST RESULT


9.1 DUTY CYCLE

DCCF = $20\log_{10}(\text{Pulse width} / \text{Period of the pulse train})$


= $20\log_{10}(13 \times 0.1959 \text{ ms} / 100 \text{ ms}) = -31.88 \text{ dB}$

■ Test Plots

Pulse Width Plot



Period of the Pulse Train




9.2 OCCUPIED BANDWIDTH


Frequency[MHz]	99% Bandwidth[kHz]	20dB Bandwidth[kHz]
2402	754.30	698.1
2441	742.94	682.5
2480	756.62	747.0

■ Test Plots


Occupied Bandwidth plot (Low)



Occupied Bandwidth plot (Mid)



Occupied Bandwidth plot (High)




9.3 RADIATED MEASUREMENT.

9.3.1 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT

Frequency [MHz]	Reading [dBuV/m]	A.F.+C.L. +D.F+ATT. [dB]	Ant. Pol. [H/V]	D.C.C.F [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2402	54.56	35.61	V	0.00	90.17	113.98	23.81	PK
2402	54.56	35.61	V	-31.88	58.29	93.98	35.69	AV
2402	56.89	35.61	H	0.00	92.50	113.98	21.48	PK
2402	56.89	35.61	H	-31.88	60.62	93.98	33.36	AV
2441	55.98	35.67	V	0.00	91.65	113.98	22.33	PK
2441	55.98	35.67	V	-31.88	59.77	93.98	34.21	AV
2441	56.04	35.67	H	0.00	91.71	113.98	22.27	PK
2441	56.04	35.67	H	-31.88	59.83	93.98	34.15	AV
2480	56.19	36.01	V	0.00	92.20	113.98	21.78	PK
2480	56.19	36.01	V	-31.88	60.32	93.98	33.66	AV
2480	55.96	36.01	H	0.00	91.97	113.98	22.01	PK
2480	55.96	36.01	H	-31.88	60.09	93.98	33.89	AV

■ Test Plots (Worst case : X-H)

Fundamental Field Strength plot (Ch.0)



Date: 27.MAY.2020 02:46:45

Note:

Plot of worst case are only reported.

9.3.2 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40\log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Operation Frequency: 2402 MHz

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Duty Cycle Correction [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	44.08	2.36	0.00	V	46.44	73.98	27.54	PK
4804	44.08	2.36	-31.88	V	46.44	53.98	7.54	AV
7206	40.28	8.66	0.00	V	48.94	73.98	25.04	PK
7206	40.28	8.66	-31.88	V	48.94	53.98	5.04	AV
4804	44.16	2.36	0.00	H	46.52	73.98	27.46	PK
4804	44.16	2.36	-31.88	H	46.52	53.98	7.46	AV
7206	40.57	8.66	0.00	H	49.23	73.98	24.75	PK
7206	40.57	8.66	-31.88	H	49.23	53.98	4.75	AV


Operation Frequency: 2441 MHz

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Duty Cycle Correction [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	42.12	2.84	0.00	V	44.96	73.98	29.02	PK
4882	42.12	2.84	-31.88	V	44.96	53.98	9.02	AV
7323	40.27	9.27	0.00	V	49.54	73.98	24.44	PK
7323	40.27	9.27	-31.88	V	49.54	53.98	4.44	AV
4882	42.56	2.84	0.00	H	45.40	73.98	28.58	PK
4882	42.56	2.84	-31.88	H	45.40	53.98	8.58	AV
7323	40.46	9.27	0.00	H	49.73	73.98	24.25	PK
7323	40.46	9.27	-31.88	H	49.73	53.98	4.25	AV

Operation Frequency: 2480 MHz

Frequency [MHz]	Reading [dBuV]	A.F + C.L - A.G + D.F [dB]	Duty Cycle Correction [dB]	Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	42.06	2.14	0.00	V	44.20	73.98	29.78	PK
4960	42.06	2.14	-31.88	V	44.20	53.98	9.78	AV
7440	39.77	10.06	0.00	V	49.83	73.98	24.15	PK
7440	39.77	10.06	-31.88	V	49.83	53.98	4.15	AV
4960	42.11	2.14	0.00	H	44.25	73.98	29.73	PK
4960	42.11	2.14	-31.88	H	44.25	53.98	9.73	AV
7440	39.93	10.06	0.00	H	49.99	73.98	23.99	PK
7440	39.93	10.06	-31.88	H	49.99	53.98	3.99	AV

■ Test Plots (Worst case : X-H)



Date: 27.MAY.2020 03:14:18

Note:

Plot of worst case are only reported.

9.3.3 RADIATED BAND EDGES MEASUREMENTS

Operating Mode ANT+
 Test Frequency 2402 MHz


Frequency [MHz]	Reading [dBuV]	A.F+C.L +D.F+ATT [dB]	Pol. [H/V]	D.C.C.F [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2400.0	27.41	35.60	H	0	63.01	73.98	10.97	PK
2400.0	27.41	35.60	H	-31.88	31.13	53.98	22.85	AV
2400.0	27.34	35.60	V	0	62.94	73.98	11.04	PK
2400.0	27.34	35.60	V	-31.88	31.06	53.98	22.92	AV

Operating Mode ANT+
 Test Frequency 2480 MHz

Frequency [MHz]	Reading [dBuV]	A.F+C.L +D.F+ATT [dB]	Pol. [H/V]	D.C.C.F [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	27.54	35.96	H	0	63.50	73.98	10.48	PK
2483.5	27.54	35.96	H	-31.88	31.62	53.98	22.36	AV
2483.5	27.66	35.96	V	0	63.62	73.98	10.36	PK
2483.5	27.66	35.96	V	-31.88	31.74	53.98	22.24	AV

■ Test Plots (Worst case : Z-V)

Radiated Band Edges plot – Ch.78



Date: 27.MAY.2020 02:57:35

Note:

Plot of worst case are only reported.

9.4 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

ANT MODE_L1


1 / 2

HCT TEST Report

Common Information

EUT: SM-A516V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: ANT MODE_L1

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG x Final Result 1-QPK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	40.8	9.000	Off	L1	9.8	25.1	65.9
0.156000	38.1	9.000	Off	L1	9.8	27.6	65.7
0.226000	34.8	9.000	Off	L1	9.8	27.8	62.6
0.230000	34.6	9.000	Off	L1	9.8	27.9	62.4
0.750000	32.8	9.000	Off	L1	9.8	23.2	56.0
0.754000	33.3	9.000	Off	L1	9.8	22.7	56.0
2.906000	24.8	9.000	Off	L1	9.9	31.2	56.0
2.930000	25.3	9.000	Off	L1	9.9	30.7	56.0
3.128000	25.2	9.000	Off	L1	9.9	30.8	56.0
3.216000	25.3	9.000	Off	L1	9.9	30.7	56.0
3.248000	25.0	9.000	Off	L1	9.9	31.0	56.0
3.364000	24.5	9.000	Off	L1	9.9	31.5	56.0
8.830000	27.9	9.000	Off	L1	10.2	32.1	60.0
8.936000	29.0	9.000	Off	L1	10.2	31.0	60.0
9.010000	28.9	9.000	Off	L1	10.2	31.1	60.0
9.020000	28.9	9.000	Off	L1	10.2	31.1	60.0
9.076000	28.9	9.000	Off	L1	10.2	31.1	60.0
9.244000	29.0	9.000	Off	L1	10.2	31.0	60.0

2020-06-02

오전 11:16:46

ANT MODE_L1

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.0	9.000	Off	L1	9.8	28.0	56.0
0.226000	21.2	9.000	Off	L1	9.8	31.4	52.6
0.614000	26.1	9.000	Off	L1	9.8	19.9	46.0
0.686000	24.0	9.000	Off	L1	9.8	22.0	46.0
0.754000	24.6	9.000	Off	L1	9.8	21.4	46.0
0.760000	25.3	9.000	Off	L1	9.8	20.7	46.0
2.540000	17.0	9.000	Off	L1	9.9	29.0	46.0
2.650000	16.6	9.000	Off	L1	9.9	29.4	46.0
2.692000	16.5	9.000	Off	L1	9.9	29.5	46.0
2.930000	17.3	9.000	Off	L1	9.9	28.7	46.0
3.216000	17.1	9.000	Off	L1	9.9	28.9	46.0
3.248000	16.9	9.000	Off	L1	9.9	29.1	46.0
8.906000	20.5	9.000	Off	L1	10.2	29.5	50.0
8.936000	20.9	9.000	Off	L1	10.2	29.1	50.0
8.988000	20.8	9.000	Off	L1	10.2	29.2	50.0
9.038000	21.1	9.000	Off	L1	10.2	28.9	50.0
9.144000	21.1	9.000	Off	L1	10.2	28.9	50.0
9.236000	21.0	9.000	Off	L1	10.2	29.0	50.0

2020-06-02

오전 11:16:46

Conducted Emissions (Line 2)

ANT MODE_N


1 / 2

HCT TEST Report

Common Information

EUT: SM-A516V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: ANT MODE_N

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG x Final Result 1-QPK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154000	41.9	9.000	Off	N	9.8	23.9	65.8
0.168000	30.3	9.000	Off	N	9.8	34.8	65.1
0.212000	31.6	9.000	Off	N	9.8	31.5	63.1
0.218000	33.3	9.000	Off	N	9.8	29.6	62.9
0.226000	35.9	9.000	Off	N	9.8	26.7	62.6
0.232000	35.0	9.000	Off	N	9.8	27.4	62.4
1.928000	24.0	9.000	Off	N	9.9	32.0	56.0
2.158000	24.3	9.000	Off	N	9.9	31.7	56.0
2.358000	24.3	9.000	Off	N	9.9	31.7	56.0
2.414000	23.7	9.000	Off	N	9.9	32.3	56.0
2.556000	24.9	9.000	Off	N	9.9	31.1	56.0
2.568000	24.6	9.000	Off	N	9.9	31.4	56.0
15.684000	27.0	9.000	Off	N	10.5	33.0	60.0
15.928000	27.7	9.000	Off	N	10.5	32.3	60.0
16.016000	27.8	9.000	Off	N	10.5	32.2	60.0
16.070000	28.1	9.000	Off	N	10.5	31.9	60.0
16.116000	27.7	9.000	Off	N	10.5	32.3	60.0
16.542000	27.0	9.000	Off	N	10.5	33.0	60.0

2020-06-02

오전 11:02:30

ANT MODE_N

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	28.6	9.000	Off	N	9.8	27.4	56.0
0.154000	27.4	9.000	Off	N	9.8	28.4	55.8
0.168000	20.7	9.000	Off	N	9.8	34.4	55.1
0.218000	19.2	9.000	Off	N	9.8	33.7	52.9
0.224000	21.2	9.000	Off	N	9.8	31.5	52.7
0.230000	21.2	9.000	Off	N	9.8	31.2	52.4
1.882000	15.3	9.000	Off	N	9.9	30.7	46.0
1.928000	14.3	9.000	Off	N	9.9	31.7	46.0
2.048000	14.9	9.000	Off	N	9.9	31.1	46.0
2.158000	15.8	9.000	Off	N	9.9	30.2	46.0
2.414000	14.9	9.000	Off	N	9.9	31.1	46.0
2.556000	16.3	9.000	Off	N	9.9	29.7	46.0
15.684000	15.9	9.000	Off	N	10.5	34.1	50.0
15.868000	16.1	9.000	Off	N	10.5	33.9	50.0
16.016000	16.3	9.000	Off	N	10.5	33.7	50.0
16.080000	16.3	9.000	Off	N	10.5	33.7	50.0
16.216000	16.1	9.000	Off	N	10.5	33.9	50.0
16.542000	15.5	9.000	Off	N	10.5	34.5	50.0

2020-06-02

오전 11:02:30

10. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	09/11/2019	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/18/2019	Annual	100033
ESPAC	SU-642 / Temperature Chamber	03/18/2020	Annual	0093008124
Agilent	N9020A / Signal Analyzer	05/11/2020	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	05/06/2020	Annual	MY53310623
Agilent	N1911A / Power Meter	04/07/2020	Annual	MY45101406
Agilent	N1921A / Power Sensor	03/23/2020	Annual	MY55220026
Agilent	87300B / Directional Coupler	11/11/2019	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	05/25/2020	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/18/2019	Annual	KR75303960
Weinschel	2-20 / Attenuator(20 dB)	07/02/2019	Annual	BR0592
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/16/2019	Annual	100422

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Emco	2090 / Controller	N/A	N/A	060520
Ets	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	05/18/2020	Biennial	1513-175
Schwarzbeck	VULB 9160 / Hybrid Antenna	08/09/2018	Biennial	3368
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/31/2018	Biennial	00895
Schwarzbeck	BBHA 9120D / Horn Antenna	11/18/2019	Biennial	9120D-1191
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	11/29/2019	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/11/2019	Annual	836650/016
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/26/2019	Annual	101068-SZ
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	01/21/2020	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	02/10/2020	Annual	1
CERNEX WEINSCHTEL	CBLU1183540B-01/Broadband Bench Top LNA 56-10 / Attenuator(10 dB)	12/24/2019	Annual	N/A
CERNEX Api tech.	CBL06185030 / Broadband Low Noise Amplifier 18B-03 / Attenuator (3 dB)	12/24/2019	Annual	N/A
Wainwright Instruments	WHKX10-2700-3000-18000-40SS / High Pass Filter	12/24/2019	Annual	N/A
Wainwright Instruments	WHKX8-6090-7000-18000-40SS / High Pass Filter	12/24/2019	Annual	N/A
T&M SYSTEM	COAXIAL ATTENUATOR / Thru	12/24/2019	Annual	N/A
CERNEX	CBL18265035 / Power Amplifier	12/26/2019	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	03/23/2020	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/18/2020	Annual	3000C000276

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2006-FC027-P