

HAC T-COIL Test Report

Applicant Name: SAMSUNG Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-Si, Gyeonggi-do, 16677 Rep. of Korea	Date of Issue: Jul. 02, 2020 Test Report No.: HCT-SR-2006-FC003-R1 Test Site: HCT CO., LTD.
---	--

Equipment Type:	Mobile Phone
Application Type	Certification
FCC Rule Part(s):	CFR §20.19 , ANSI C63.19-2011
Model Name:	SM-A516V
Date of Test:	05/07/2020 ~ 05/21/2020,07/01/2020~07/02/2020

C63.19-2011 HAC Category	T3 (T-COIL CATEGORY)
-------------------------------------	-----------------------------

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and had been tested in accordance with the specified measurement procedures. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested By



Yoon Ho, Choi
Test Engineer
SAR Team
Certification Division

Reviewed By



Yun-jeang, Heo
Technical Manager
SAR Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	Jun. 18, 2020	Initial Release
R1	Jul. 02, 2020	Revised Sec.12.8

This test results were applied only to the test methods required by the standard.

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.

Table of Contents

1. Test Regulations	4
2. ATTESTATION OF TEST RESULT OF DEVICE UNDER TEST	5
3. DEVICE UNDER TEST DESCRIPTION.....	6
4. Test Methodology	7
5. Measuring Instrument Calibraion	8
6. Measurement Uncertainty.....	9
7. Test Procedures for all Technologies	10
8. Audio Level and Gain Measurements.....	14
9 T-coil Measurement Criteria	16
10. Device Under Test.....	18
12. HAC (T-coil) Test Results	20
Attachment 1. HAC T-COIL Test Plots	39
Attachment 2. HAC T-Coil Probe Certificates.....	153

1. Test Regulations

The tests were performed according to the following regulations:

Test Standard	FCC 47 CFR §20.19 ANSI C63.19-2011
Test Method	<ul style="list-style-type: none">• FCC CFR47 Part 20.19• ANSI C63.19 2011-version• FCC KDB 285076 D01 HAC Guidance v05• FCC KDB 285076 D02 T Coil testing v03

2. ATTESTATION OF TEST RESULT OF DEVICE UNDER TEST

Test Laboratory	
Company Name:	HCT Co., LTD
Address:	74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of Korea
Telephone:	+82 31 645 6300
Fax.:	+82 31 645 6401

Attestation of SAR test result	
Applicant Name:	SAMSUNG Electronics Co., Ltd.
Model:	SM-A516V
EUT Type:	Mobile Phone
Application Type:	Certification

2.1 Test Methodology

The Tests document in this report were performed in accordance with ANSI C63.19-2011 method of Measurement of Compatibility between Wireless Communication Devices and Hearing Aids, FCC published KDB 285076 D01 HAC Guidance v05, FCC Published KDB285076 D03 HAC FAQ v01 and TCB Workshop updates .

3. DEVICE UNDER TEST DESCRIPTION

3.1 DUT specification

Device Wireless specification overview		
Band & Mode	Operating Mode	Tx Frequency
GSM850	Voice / Data	824.2 MHz ~ 848.8 MHz
GSM1900	Voice / Data	1 850.2 MHz ~ 1 909.8 MHz
WCDMA 850	Voice / Data	826.4 MHz ~ 846.6 MHz
WCDMA 1900	Voice / Data	1 852.4 MHz ~ 1 907.6 MHz
LTE Band 2 (PCS)	Voice / Data	1 850.7 MHz ~ 1 909.3 MHz
LTE Band 4 (AWS)	Voice / Data	1 710.7 MHz ~ 1 754.3 MHz
LTE Band 5 (Cell)	Voice / Data	824.7 MHz ~ 848.3 MHz
LTE Band 7	Voice / Data	2 502.5 MHz ~ 2 567.5 MHz
LTE Band 12	Voice / Data	699.7 MHz ~ 715.3 MHz
LTE Band 13	Voice / Data	779.5 MHz ~ 784.5 MHz
LTE Band 66 (AWS)	Voice / Data	1 710.7 MHz ~ 1 779.3 MHz
NR Band n2 (PCS)*	Data	1 852.5 MHz ~ 1 907.5 MHz
NR Band n5 (Cell)*	Data	826.5 MHz ~ 846.5 MHz
NR Band n66*	Data	1 712.5 MHz ~ 1 777.5 MHz
NR Band n260*	Data	37000 - 40000 MHz
NR Band n261*	Data	27500 - 28350 MHz
U-NII-1	Voice / Data	5 180 MHz ~ 5 240 MHz
U-NII-2A	Voice / Data	5 260 MHz ~ 5 320 MHz
U-NII-2C	Voice / Data	5 500 MHz ~ 5 720 MHz
U-NII-3	Voice / Data	5 745 MHz ~ 5 825 MHz
2.4 GHz WLAN	Voice / Data	2 412 MHz ~ 2 472 MHz
Bluetooth / LE 5.0	Data	2 402 MHz ~ 2 480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 MHz~ 2480 MHz MHz
Device Description		
Device Dimension	Overall (Length x Width): 156 mm x 71mm Overall Diagonal: 165 mm Display Diagonal: 161 mm	
Battery Information	Standard (Li-ion Polymer Battery) Battery Model Name: EB-BA516AMY (Samsung SDI)	
HW version	REV1.0	
SW version	A516V.001	

4. Test Methodology

The tests documented in this report were performed in accordance with ANSI C63.19-2011 Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids and FCC published procedure

KDB 285076 D01 HAC Guidance v05 IP

v03 KDB 285076 D03 HAC FAQ v01

TCB workshop updates

KDB 285076 D02 T-Coil testing for CMRS

5. Measuring Instrument Calibraion

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations and is traceable to recognized national standards.

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
ABM Probe	SPEAG	AM1DV3	3050	11/20/2020
ABM Probe	SPEAG	AM1DV3	3049	05/26/2021
Data Acquisition Electronics	SPEAG	DAE4	868	09/04/2020
Data Acquisition Electronics	SPEAG	DAE3	504	02/26/2021
DAC	Sound Devices	USBPre 2	HB1319212059	N/A
Radio Communication Tester	R & S	CMW 500	167916	10/23/2020

6. Measurement Uncertainty

Measurement Uncertainty for Audio Band Magnetic Measurement

Error Description	Uncertainty values (±%)	Probe Dist.	Div.	C _i ABM1	C _i ABM2	Std. Unc.	
						ABM1 (±%)	ABM2 (±%)
Probe Sensitivity							
ReFERENCE Level	3.00	N	1	1	1	3.00	3.00
AMCC Geometry	0.40	R	1.73	1	1	0.23	0.23
AMCC Current	1.00	R	1.73	1	1	0.58	0.58
Probe Positioning during Calibr.	0.10	R	1.73	1	1	0.06	0.06
Noise Contribution	0.70	R	1.73	0.0143	1	0.01	0.40
Frequency Slope	5.90	R	1.73	0.1	1	0.34	3.41
Probe System							
Repeatability / Drift	1.00	R	1.73	1	1	0.58	0.58
Linearity / Dynamic Range	0.60	R	1.73	1	1	0.35	0.35
Acoustic Noise	1.00	R	1.73	0.1	1	0.06	0.58
Probe Angle	2.30	R	1.73	1	1	1.33	1.33
Spectral Processing	0.90	R	1.73	1	1	0.52	0.52
Integration Time	0.60	N	1.00	1	5	0.60	3.00
Field Disturbation	0.20	R	1.73	1	1	0.12	0.12
Test Signal							
Ref. Signal Spectral Response	0.60	R	1.73	0	1	0.00	0.35
Positioning							
Probe Positioning	1.90	R	1.73	1	1	1.10	1.10
Phantom Thickness	0.90	R	1.73	1	1	0.52	0.52
DUT Positioning	1.90	R	1.73	1	1	1.10	1.10
External Contributions							
RF Interference	0.00	R	1.73	1	0.3	0.00	0.00
Test Signal Variation	2.00	R	1.73	1	1	1.2	1.2
Combined Std. Uncertainty (ABM field)						4.1	6.1
Expanded Std. Uncertainty (%)						8.1	12.3
Notes for table N - Nomal R - Rectangular Div. - Divisor used to obtain standard uncertainty							

7. Test Procedures for all Technologies

7.1 General Procedures C63.19-2011, Section 7

ANSI C63.19-2011, Section 7

This document describes the procedures used to measure the ABM (T-Coil) performance of the WD. In addition to measuring the absolute signal levels, the A-weighted magnitude of the unintended signal shall also be determined. In order to assure that the required signal quality is measured, the measurement of the intended signal and the measurement of the unintended signal must be made at the same location for all measurement positions. In addition, the RF field strength at each measurement location must be at or below that required for the assigned category.

Measurements shall not include undesired properties from the WD's RF field; therefore, use of a coaxial connection to a base station simulator or non-radiating load may be necessary. However, even then with a coaxial connection to a base station simulator or non-radiating load there may still be RF leakage from the WD, which may interfere with the desired measurement. Pre-measurement checks should be made to avoid this possibility. All measurements shall be done with the WD operating on battery power with an appropriate normal speech audio signal input level given in Table 7.1. If the device display can be turned off during a phone call then that may be done during the measurement as well.

Measurements shall be performed at two locations specified in A.3, with the correct probe orientation for a particular location, in a multistage sequence by first measuring the field intensity of the desired T-Coil signal (ABM1) that is useful to a hearing aid T-Coil. The undesired magnetic components (ABM2) must be measured at the same location as the desired ABM or T-Coil signal (ABM1), and the ratio of desired to undesired ABM signals must be calculated. For the perpendicular field location, only the ABM1 frequency response shall be determined in a third measurement stage. The flow chart in Figure 7.3 illustrates this three-stage, two orientation process.

The following steps summarize the basic test flow for determining ABM1 and ABM2. These steps assume that a sine wave or narrowband 1/3 octave signal can be used for the measurement of ABM1.

A validation of the test setup and instrumentation may be performed using a TMFS or Helmholtz coil. Measure the emissions and confirm that they are within the specified tolerance.

Position the WD in the test setup and connect the WD RF connector to a base station simulator or a non-radiating load as shown in Figure 7.1 or Figure 7.2. Confirm that equipment that requires calibration has been calibrated, and that the noise level meets the requirements given in 7.3.1.

The drive level to the WD is set such that the reference input level specified in Table 7.1 is input to the base station simulator (or manufacturer's test mode equivalent) in the 1 kHz, 1/3 octave band. This drive level shall be used for the T-Coil signal test (ABM1) at $f = 1$ kHz. Either a sine wave at 1025 Hz or a voice-like signal, band-limited to the 1 kHz 1/3 octave, as defined in 7.4.2, shall be used for the reference audio signal. If interference is found at 1025 Hz an alternative nearby reference audio signal frequency may be used.⁴⁶ The same drive level will be used for the ABM1 frequency response measurements at each 1/3 octave band center frequency. The WD volume control may be set at any level up to maximum, provided that a signal at any frequency at maximum modulation would not result in clipping or signal overload.

Determine the magnetic measurement locations for the WD device (A.3), if not already specified by the manufacturer, as described in 7.4.4.1.1 and 7.4.4.2.

At each measurement location, measure and record the desired T-Coil magnetic signals (ABM1 at f_i) as described in 7.4.4.2 in each individual ISO 266-1975 R10 standard 1/3 octave band. The desired audio band input frequency (f_i) shall be centered in each 1/3 octave band maintaining the same drive level as determined in item c) and the reading taken for that band.


Equivalent methods of determining the frequency response may also be employed, such as fast Fourier transform (FFT) analysis using noise excitation or input-output comparison using simulated speech. The full-band integrated or half-band integrated probe output, as specified in D.9, may be used, as long as the appropriate calibration curve is applied to the measured result, so as to yield an accurate measurement of the field magnitude. (The resulting measurement shall be an accurate measurement in dB A/m.)

All measurements of the desired signal shall be shown to be of the desired signal and not of an undesired signal. This may be shown by turning the desired signal ON and OFF with the probe measuring the same

location. If the scanning method is used the scans shall show that all measurement points selected for the ABM1 measurement meet the ambient and test system noise criteria in 7.3.1.

At the measurement location for each orientation, measure and record the undesired broadband audio magnetic signal (ABM2) as specified in 7.4.4.4 with no audio signal applied (or digital zero applied, if appropriate) using A-weighting and the half-band integrator. Calculate the ratio of the desired to undesired signal strength (i.e., signal quality). Obtain the data from the postprocessor, SEMCAD, and determine the category that properly classifies the signal quality based on Table 8.5.

Test Setup Diagram



7.2 VoWiFi – For PAG REUSE

This device supports Wi-Fi calling (aka Voice over Wi-Fi or VoWiFi) which is an extended feature of the carriers CMRS service to offload VoLTE calls onto local area networks over WI-FI via the internet and subject to HAC assessment for phones with a HAC rating. HAC assessment for this feature is subject to Pre Approval Guidance.

The set up for VoWiFi uses the Base station as described in section 7.1 with the exception that the reference audio level is set at -20dBm0. The reference level is calibrated using the standard call box calibration procedures with the exception of the -20dBm0 reference level being used (refer to section 8.4).


An investigation was performed to determine worst case codec, bit rate and air interface configuration (refer to sections 12.5 and 12.6).

7.3 Over the Top(OTT) – For PAG REUSE

This device supports VoIP via a preinstalled application that uses the **Google Duo** service, using **OPUS** as its only codec (refer to §11 for air interface details and §12.7 for codec bit rates). VoIP capabilities require HAC assessment when voice calls are supported over the cellular data connection via pre-installed VoIP applications and the assessment is subject to Pre-Approval Guidance procedures.


The equipment is set up as shown below with a support device used to originate the call using the IP transport. The support device connects to the cloud-based **Google Duo** service via Wi-Fi access point and router, or RJ45. The DUT connects to the VoIP service via a cellular/unlicensed air interface to the call box and an Ethernet connection from call box to Internet. The various codec bit rate and air interface configurations are evaluated to determine the worst-case configuration (refer to §12.7).

Test Setup configuration for OTT calls



For the OTT call, the calibrated audio card within the CMW500 cannot be used so the AMMI is connected to an external Digital-Analog Converter (DAC) and the DAC is connected to the Support Device via USB. The test signal is sent from the DASY PC to the AMMI, from the AMMI to the DAC, from the DAC to the Support Device, and, via the VoIP call, to the DUT.

As this test set up uses an external DAC between the AMMI's audio output and support device, the appropriate gain factor for the OTT call needs be determined. This is done by connecting the DAC between the AMMI Audio output and Coil input as shown below.



Using the metering function on the DAC, the DAC gain is adjusted until the volume reaches 0 dBFS (3.14 dBm0 based on TIA/EIA 810-A). SPEAG's "TN-LK-05042018-C-T-Coil_Levels" document (Appendix E) steps E through H are then followed to determine the adjusted gain values as detailed in §8.5 so that the reference level is set to 23.14dB below full scale, i.e. at -20dBm0. A verification of the DAC's output is performed prior to testing.

8. Audio Level and Gain Measurements

8.1 GSM

Refer to the below table for the gains used to measure GSM.

Signal Type	Audio Level [dBm]	Gain [dB]	Gain [linear]
Voice 1 kHz	-16.00	27.91	24.86
Voice 300 - 3 kHz	-16.00	37.62	75.5

8.2 W-CDMA

Refer to the below table for the gains used to measure W-CDMA.

Signal Type	Audio Level [dBm]	Gain [dB]	Gain [linear]
Voice 1 kHz	-16.00	27.91	24.86
Voice 300 - 3 kHz	-16.00	37.62	75.5

8.3 VOLTE

Refer to the below table for the gains used to measure VoLTE.

The following software/firmware was used to simulate the VoLTE server for testing:

Firmware	License Keys	Software Name
V3.7.30 for LTE	KS500	LTE FDD R8 SIG BASIC
	KS550	LTE TDD R8 SIG BASIC
V3.7.20 for Audio	KA100	IP APPL ENABLING IPv4
	KA150	IP APPL ENABLING IPv6
	KAA20	IP APPL IMS BASIC
	KM050	DATA APPL MEAS
	KS104	EVS SPEECH CODEC

Signal Type	Audio Level [dBm]	Gain [dB]	Gain [linear]
Voice 1 kHz	-16.00	27.91	24.86
Voice 300 - 3 kHz	-16.00	37.62	75.5

8.4 VOWi-Fi

Refer to the below table for the gains used to measure VoWi-Fi.

Firmware	License Keys	Software Name
V3.7.40 for WLAN	KS650	WLAN A/B/G SIG BASIC
	KS651	WLAN N SIG BASIC
	KS656	WLAN IEEE 802.11ac
	KS657	WLAN IEEE 802.11ax
V3.7.20 for Audio	KA100	IP APPL ENABLING IPv4
	KA150	IP APPL ENABLING IPv4
	KAA20	IP APPL IMS BASIC
	KM050	DATA APPL MEAS
	KS104	EVS SPEECH CODEC

Signal Type	Audio Level [dBm]	Gain [dB]	Gain [linear]
Voice 1 kHz	-20.00	23.89	15.65
Voice 300 - 3 kHz	-20.00	33.60	47.45

8.5 Over the Top(OTT) – For PAG REUSE

For EDGE, HSPA, LTE and Wi-Fi the linear gain levels listed below were used. The results below are based on a reference input level of -20 dBm.

To calibrate the DAC (refer §7.3), three. Way audio files (sine wave, 1kHz voice, and 300 to 3 kHz voice) are sent from the DASY5 PC to the AMMI, then to the DAC. The Helmholtz resonator measures the field strength, which represents the AMMI to DAC input sensitivity. After determining the input sensitivity, the adjusted linear gain values can then be calculated.


Signal Type	Audio Level [dBm]	Gain [dB]	Gain [linear]
Voice 1 kHz	-20.00	25.87	19.66
Voice 300-3kHz	-20.00	35.58	59.83

9 T-coil Measurement Criteria

9.1 Frequency Responses


The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the response curve, over the frequency range 300 Hz to 3000 Hz.

Figure 8.1 and Figure 8.2 provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.



NOTE—The frequency response is between 300 Hz and 3000 Hz.

Figure 8.1—Magnetic field frequency response for WDs with field strength ≤ -15 dB (A/m) at 1 kHz



NOTE—The frequency response is between 300 Hz and 3000 Hz.

Figure 8.2—Magnetic field frequency response for WDs with a field that exceeds -15 dB(A/m) at 1 kHz

9.2 Signal to Noise


This specifies the signal-to-noise quality requirement for the intended T-Coil signal from a WD. The worst signal to noise of the two T-Coil signal measurements, as determined in Clause 7, shall be used to determine the T-Coil mode category per Table 8.5.

Only the RF immunity of the hearing aid is measured in T-Coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. So, the only criterion that can be measured is the RF immunity in T-Coil Mode. This is measured using the same procedure as for the audio coupling mode and at the same levels as specified in 6.4.

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Table 8.5- T-Coil signal-to-noise categories

Measurement locations and reference plane to be used for the T-coil measurements.



10. Device Under Test

Normal operation	Held to head	
Back Cover	The Back Cover is not removable	
Test sample information	S/N	Notes
	TDS0133H	T-coil Test
	TDS0089H	T-coil Test
	TDS0106H	T-coil Test
	TDS0158H	T-coil Test

11. Air Interfaces and Operating Mode

Air Interface	Bands (MHz)	Type	C63.19 Tested	Simultaneous Transmitter	Audio Codecs Evaluated
GSM	850	VO	Yes	Wi-Fi, BT	EFR
	1900				
	GPRS/EDGE	DT	Yes ³	Wi-Fi, BT	OPUS ²
W-CDMA (UMTS)	850	VO	Yes	Wi-Fi, BT	AMR-NB & AMR-WB
	1700				
	1900				
	HSPA	VD	Yes ³	Wi-Fi, BT	OPUS ²
LTE - FDD	700 (B12/13/17)	VD	Yes ^{1,3}	Wi-Fi, BT	AMR-NB, AMR- WB, EVS-NB, EVS-WB, EVS-SWB & OPUS ²
	850 (B5/26)				
	1700 (B4/66)				
	1900 (B2/25)				
	2300 (B30)				
	2500 (B7)				
NR -FDD	835 (n5)	VD	Yes ⁴	Wi-Fi, BT	OPUS ²
	1700 (n66)				
	1900 (n2)				
NR -TDD	38500(n260)	VD	No ⁴	Wi-Fi, BT	OPUS ²
	28000(n261)				
Wi-Fi	2450	VD	Yes	WWAN	AMR-NB, AMR- WB, EVS-NB, EVS-WB, EVS-SWB & OPUS ²
	5200 (U-NII-1)				
	5300 (U-NII-2A)				
	5500 (U-NII-2C)				
	5800 (U-NII-3)				
BT	2450	DT	NA	WWAN	N/A
Type: VO: Legacy Cellular Voice Service DT: Digital Transport only (no voice) VD :CMRS and /or IP Voice over data Transport.				Note: 1. Ref Lev in accordance with the July 2012 C63 VoLTE interpretation 2. Ref Lev -20 dBm0 3. For PAG REUSE 4. n260,n261 are currently outsided the scope of ANSI C63.9 and FCC HAC regulations.	

12. HAC (T-coil) Test Results

12.1 Codec Investigation

An investigation between the various codec configurations (Low/High bit rates for Narrowband, Wideband) and specific parameters are documented (ABM1, ABM2, S+N/N, frequency response) to determine the worst-case bit rates for each voice service type. The table below compares the varying codec configurations. A codec investigation was performed on one band of each GSM, W-CDMA, LTE FDD/TDD.

The highlighted results below were determined to be the worst case codec configuration(s) for GSM, W- CDMA and LTE.

Codec Investigation				
Codec State	AMR-NB (kbit/s)		Orientation	Band/ Channel
	FR V1	HR V1		
ABM1 (dB/m)	-5.45	-4.74	z (Axial)	GSM 850 CH.190
ABM2 (dBA/m)	-44.08	-44.42		
S+N/N (dB)	38.63	39.68		
Freq. Resposne (dB)	2.0	1.03		
ABM1 (dB/m)	-9.71	-9.61	y (Transversal)	
ABM2 (dBA/m)	-46.47	-47.50		
S+N/N (dB)	36.75	37.89		

Codec Investigation								
Codec State	AMR-NB (kbit/s)			AMR-WB (kbit/s)			Orientation	Band/ Bandwidth/ Channel
	4.75	7.4	12.2	6.6	15.85	23.85		
ABM1 (dB/m)	1.46	0.60	5.19	3.29	0.76	-8.36	z (Axial)	WCDMA Band II Rel.99 CH.9400
ABM2 (dBA/m)	-34.79	-35.76	-30.51	-35.56	-37.82	-47.03		
S+N/N (dB)	36.25	36.36	35.70	38.85	38.57	38.67		
Freq. Resposne (dB)	1.73	1.58	1.40	1.95	2.0	2.0		
ABM1 (dB/m)	-4.73	-1.81	-2.84	-5.00	-3.34	-17.09	y (Transversal)	
ABM2 (dBA/m)	-40.74	-38.08	-38.43	-43.58	-41.74	-52.50		
S+N/N (dB)	36.00	36.27	35.59	38.57	38.40	35.41		

Codec Investigation								
Codec State	AMR-NB (kbit/s)			AMR-WB (kbit/s)			Orientation	Band/ Bandwidth/ Channel
	4.75	7.4	12.2	6.6	15.85	23.85		
ABM1 (dB/m)	-0.60	0.93	2.07	-1.17	-1.90	2.10	z (Axial)	LTE Band 2 CH.18900 20 MHz BW QPSK RB 1/0
ABM2 (dBA/m)	-36.79	-35.37	-33.70	-39.68	-40.43	-36.25		
S+N/N (dB)	36.20	36.30	35.77	38.51	38.53	38.35		
Freq. Resposne(dB)	1.61	1.48	1.61	2.0	2.0	2.0		
ABM1 (dB/m)	-5.57	-1.81	-1.67	-5.94	-5.50	-5.12	y (Transversal)	
ABM2 (dBA/m)	-41.68	-38.07	-37.36	-44.20	-43.84	-43.30		
S+N/N (dB)	36.11	36.26	35.70	38.26	38.35	38.18		

Codec Investigation											
Codec State	EVS-NB (kbit/s)			EVS-WB (kbit/s)			EVS-SWB (kbit/s)			Orientation	Band/ BandWidt/ Channel
	5.9	13.2	24.4	5.9	13.2	24.4	9.6	16.4	24.4		
ABM1 (dB/m)	2.71	3.75	3.43	-2.81	1.17	3.95	-3.46	-4.68	-4.34	z (Axial)	LTE Band 2 CH.18900 20 MHz BW QPSK RB 1/0
ABM2 (dBA/m)	-32.08	-32.58	-32.81	-40.41	-37.98	-35.54	-52.08	-51.84	-51.28		
S+N/N (dB)	34.79	36.33	36.24	37.60	39.15	39.50	48.62	47.17	46.94		
Freq.Resposne(dB)	1.59	1.65	1.61	2.0	2.0	2.0	1.79	2	2		
ABM1 (dB/m)	-5.78	-4.45	-3.09	-7.96	-4.63	-4.02	-9.39	-9.85	-11.81	y (Transversal)	
ABM2 (dBA/m)	-40.43	-40.68	-39.24	-45.59	-43.40	-42.92	-52.07	-51.79	-53.69		
S+N/N (dB)	34.64	36.23	36.15	37.63	38.76	38.90	42.68	41.94	41.88		

12.3 Air Interface Investigation

Use the worst-case codec test and document a limited set of bands/modulations/channels/bandwidth. Observe the effect of changing the band and bandwidth to ensure that there are no unexpected variations.

GSM / W-CDMA (UMTS)

Mode	Ch. Freq.	Orientation	ABM1 dB (A/m)	ABM2 dB (A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABMSNR (dB)	T-Rating	Plot No.
GSM 850 Voice Coder Speech Codec: FR V1	CH.190 836.6 MHz	z(Axial)	-5.45	-44.08	-55.41	2.0	38.63	T4	1/ 2
		y(Transversal)	-9.71	-46.47	-55.84		36.75	T4	3
GSM 1900 Voice Coder Speech Codec: FR V1	CH.661 1880.0 MHz	z(Axial)	-2.57	-41.85	-55.41	1.92	39.28	T4	4/ 5
		y(Transversal)	-12.09	-49.79	-55.84		37.69	T4	6
GSM 850 Voice Coder Speech Codec: FR V1	CH.128 824.2 MHz	z(Axial)	-2.72	-41.44	-55.41	1.95	38.72	T4	
		y(Transversal)	-9.77	-47.14	-55.84		37.37	T4	
	CH.251 848.8 MHz	z(Axial)	-2.76	-41.31	-55.41	1.95	38.56	T4	
		y(Transversal)	-9.82	-46.89	-55.84		37.07	T4	
W-CDMA Band II Voice WB AMR Codec:23.85 kbit/s	CH.9400 1880.0 MHz	z(Axial)	-8.36	-47.03	-55.41	2.0	38.67	T4	7/ 8
		y(Transversal)	-17.09	-52.50	-55.84		35.41	T4	9
W-CDMA Band V Voice WB AMR Codec:23.85 kbit/s	CH.4183 836.6 MHz	z(Axial)	-1.02	-39.64	-55.41	2.00	38.62	T4	10/ 11
		y(Transversal)	-4.03	-42.54	-55.84		38.50	T4	12
W-CDMA Band II Voice WB AMR Codec:23.85 kbit/s	CH.9262 1852.4 MHz	z(Axial)	1.32	-37.33	-55.41	2.0	38.66	T4	
		y(Transversal)	-2.33	-40.93	-55.84		38.59	T4	
	CH.9538 1907.6 MHz	z(Axial)	-0.94	-39.55	-55.41	2.0	38.61	T4	
		y(Transversal)	-2.44	-40.92	-55.84		38.48	T4	

Air Interface Investigation(Contiued)

LTE-FDD

Mode:	Ch. Freq.	BW	BW/ Modulation	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T-Rating	Plot No.	
LTE Band 2 Voice EVS- NB Codec: 5.9 kbit/s	CH.18900 1880 MHz	20MHz	QPSK	1/0	z(Axial)	2.71	-32.08	-55.46	1.59	34.79	T4	13/ 14	
					y(Transversal)	-5.78	-40.43	-55.77		34.64	T4	15	
				1/49	z(Axial)	3.75	-32.09	-55.66	1.69	35.85	T4		
					y(Transversal)	-3.81	-39.39	-55.88		35.59	T4		
				1/99	z(Axial)	3.69	-32.17	-55.66	1.88	35.87	T4		
					y(Transversal)	-2.44	-38.12	-55.88		35.68	T4		
				50/0	z(Axial)	-0.60	-36.42	-55.66	1.82	35.82	T4		
					y(Transversal)	-3.59	-39.25	-55.88		35.67	T4		
				50/25	z(Axial)	0.64	-35.13	-55.66	1.71	35.77	T4		
					y(Transversal)	-2.75	-38.39	-55.88		35.64	T4		
				50/49	z(Axial)	4.84	-30.94	-55.66	1.83	35.77	T4		
					y(Transversal)	-2.55	-38.20	-55.88		35.64	T4		
				100/0	z(Axial)	3.22	-32.47	-55.66	1.73	35.69	T4		
					y(Transversal)	-5.27	-40.81	-55.88		35.54	T4		
				16QAM	1/0	z(Axial)	4.91	-30.99	-55.66	1.69	35.90	T4	
						y(Transversal)	-2.72	-38.49	-55.88		35.77	T4	
				64QAM	1/0	z(Axial)	5.52	-30.34	-55.66	1.59	35.87	T4	
						y(Transversal)	-2.83	-38.46	-55.88		35.64	T4	
		15 MHz	QPSK	1/0	z(Axial)	-4.21	-40.15	-55.66	1.66	35.94	T4		
					y(Transversal)	-2.81	-38.65	-55.88		35.84	T4		
				1/0	z(Axial)	0.06	-35.86	-55.66	1.77	35.92	T4		
					y(Transversal)	-2.65	-38.40	-55.88		35.75	T4		
				1/0	z(Axial)	3.23	-32.30	-55.66	2.00	35.53	T4		
					y(Transversal)	-4.03	-39.68	-55.88		35.65	T4		
		3 MHz	1/0	z(Axial)	4.85	-30.93	-55.66	1.88	35.77	T4			
				y(Transversal)	-5.03	-40.62	-55.88		35.59	T4			
		1.4 MHz	1/0	z(Axial)	3.22	-32.49	-55.66	1.61	35.72	T4			
				y(Transversal)	-4.04	-39.61	-55.88		35.57	T4			

Air Interface Investigation(Contiued)

LTE-FDD

Mode	Ch. Freq.	Band width	BW/ Mode	RB Config	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T- Rating	Plot No.
LTE Band 5 Voice EVS-NB Codec: 5.9 kbit/s	CH.20525 836.5 MHz	10 MHz	QPSK	1/0	z(Axial)	3.58	-32.10	-55.66	1.59	35.68	T4	16/ 17
					y(Transversal)	-2.74	-38.32	-55.88		35.58	T4	18
LTE Band 7 Voice EVS-NB Codec: 5.9 kbit/s	CH.21100 2535 MHz	20 MHz	QPSK	1/0	z(Axial)	4.58	-31.16	-55.66	1.74	35.74	T4	19/ 20
					y(Transversal)	-4.66	-40.20	-55.88		35.53	T4	21
LTE Band 12 Voice EVS-NB Codec: 5.9 kbit/s	CH.23095 707.5 MHz	10 MHz	QPSK	1/0	z(Axial)	3.56	-32.13	-55.66	1.73	35.70	T4	22/ 23
					y(Transversal)	-4.54	-40.12	-55.88		35.58	T4	24
LTE Band 13 Voice EVS-NB Codec: 5.9 kbit/s	CH.23230 782 MHz	10 MHz	QPSK	1/0	z(Axial)	-5.44	-42.04	-55.66	2.00	36.60	T4	25/ 26
					y(Transversal)	-5.80	-42.56	-55.88		36.76	T4	27
LTE Band 66 Voice EVS-NB Codec: 5.9 kbits	CH.132322 1745 MHz	20 MHz	QPSK	1/0	z(Axial)	4.22	-31.46	-55.66	1.59	35.68	T4	28/ 29
					y(Transversal)	-3.79	-39.31	-55.88		35.53	T4	30
LTE Band 2 Voice EVS-NB Codec: 5.9 kbit/s	CH.18700 1860 MHz	20 MHz	QPSK	1/0	z(Axial)	-1.79	-38.70	-55.66	2.00	36.91	T4	
					y(Transversal)	-3.46	-39.97	-55.88		36.51	T4	
LTE Band 2 Voice EVS-NB Codec: 5.9 kbit/s	CH.19100 1900 MHz	20 MHz	QPSK	1/0	z(Axial)	-5.22	-41.66	-55.66	2.00	36.44	T4	
					y(Transversal)	-5.70	-42.49	-55.88		36.79	T4	

12.4 VoWi-Fi Codec Investigation

An investigation between the various codec configurations (Low/High bit rates for Narrowband, Wideband) and specific parameters are documented (ABM1, ABM2, S+N/N, frequency response) to determine the worst-case bit rates for each voice service type. The table below compares the varying codec configurations. A codec investigation was performed for each Wi-Fi 2.4GHz and 5GHz.

The highlighted results below were determined to be the worst case codec configuration(s) for Wi-Fi 2.4 GHz and 5 GHz.

Codec State	AMR-NB (kbit/s)			AMR-WB (kbit/s)			Orientation	Band/ BandWidth/ Channel
	4.75	7.4	12.2	6.6	15.85	23.85		
ABM1 (dB/m)	-2.39	0.30	3.38	-2.83	-1.58	-1.64	z (Axial)	802.11b CH.6 2437 MHz DSSS 1 Mbps
ABM2 (dBA/m)	-34.65	-32.31	-28.87	-45.87	-45.02	-45.90		
S+N/N (dB)	32.26	32.61	32.24	43.04	43.44	44.26		
Freq.Resposne(dB)	1.93	1.92	1.71	2.0	2.0	2.0		
ABM1 (dB/m)	-4.44	-7.22	-5.81	-8.97	-8.99	-8.95	y (Transversal)	
ABM2 (dBA/m)	-36.67	-39.51	37.90	-50.11	-50.31	-51.49		
S+N/N (dB)	32.23	32.28	32.09	41.14	41.32	42.55		

Codec Investigation											
Codec State	EVS-NB (kbit/s)			EVS-WB (kbit/s)			EVS-SWB (kbit/s)			Orientation	Band/ BandWidth/ Channel
	5.9	13.2	24.4	5.9	13.2	24.4	9.6	16.4	24.4		
ABM1 (dB/m)	0.17	-1.64	0.24	-3.55	2.37	-1.01	-8.55	-6.51	-8.83	z (Axial)	802.11b CH.6 2437 MHz DSSS 1 Mbps
ABM2 (dBA/m)	-31.96	-33.49	-31.76	-36.19	-32.46	-35.20	-43.90	-40.30	-42.11		
S+N/N (dB)	32.13	31.85	32.01	32.65	34.83	34.19	35.35	33.79	33.28		
Freq.Resposne(dB)	2.0	1.75	1.87	2.0	2.0	2.0	2.0	2.0	2.0		
ABM1 (dB/m)	-7.15	-6.95	-9.45	-11.90	-8.05	-6.79	-15.82	-16.80	-16.37	y (Transversal)	
ABM2 (dBA/m)	-39.11	-38.72	-41.51	-43.06	-42.37	-41.06	-47.76	-49.02	-47.70		
S+N/N (dB)	31.96	31.77	32.06	31.16	34.32	34.27	31.94	32.22	31.32		

Codec Investigation								
Codec State	AMR-NB (kbit/s)			AMR-WB (kbit/s)			Orientation	Band/ BandWidth/ Channel
	4.75	7.4	12.2	6.6	15.85	23.85		
ABM1 (dB/m)	1.41	-1.29	-6.82	-1.54	-1.47	-0.12	z (Axial)	802.11a CH.40 5200 MHz BPSK 6 Mbps
ABM2 (dBA/m)	-30.81	-33.70	-39.10	-41.20	-42.06	-41.03		
S+N/N (dB)	32.22	32.40	32.27	39.65	40.59	40.91		
Freq.Resposne(dB)	1.64	1.91	1.72	2.0	2.0	2.0		
ABM1 (dB/m)	-9.91	-11.75	-4.74	-8.83	-7.44	-7.32	y (Transversal)	
ABM2 (dBA/m)	-42.02	-44.05	-36.60	-47.93	-47.83	-47.59		
S+N/N (dB)	32.11	32.30	31.86	39.09	40.39	40.27		

Codec Investigation											
Codec State	EVS-NB (kbit/s)			EVS-WB (kbit/s)			EVS-SWB (kbit/s)			Orientation	Band/ BandWidth/ Channel
	5.9	13.2	24.4	5.9	13.2	24.4	9.6	16.4	24.4		
ABM1 (dB/m)	3.41	0.45	1.48	-0.60	-1.21	1.66	-5.76	-6.83	-11.53	z (Axial)	802.11a CH.40 5200 MHz BPSK 6 Mbps
ABM2 (dBA/m)	-28.51	-31.43	-30.40	-32.67	-35.61	-32.36	-38.98	-39.28	-44.04		
S+N/N (dB)	31.92	31.88	31.88	32.07	34.40	34.02	33.21	32.46	32.51		
Freq.Resposne(dB)	2.0	1.70	1.88	2.0	2.0	2.0	1.93	2.0	2.0		
ABM1 (dB/m)	-5.40	-9.41	-6.45	-9.10	-8.34	-11.34	-14.46	-16.21	-15.85	y (Transversal)	
ABM2 (dBA/m)	-37.43	-41.04	-38.09	-41.06	-41.96	-45.02	-47.02	-47.14	-46.74		
S+N/N (dB)	32.02	31.63	31.64	31.95	33.62	33.69	32.56	30.93	30.89		

12.5 VoWi-Fi Air Interface Investigation

Using the data from §9.4, further testing was performed on the remaining 802.11 modes. The objective of these measurements is to ensure that changing the modulation, bandwidth, and data rate, whilst using the worst case codec configuration measured in §9.4, yields no unexpected variations.

Moe	Ch. Freq.	BW	BW/ Modeulation	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB (A/m)	Freq. Response (dB)	ABM SNR (dB)	T-Rating	Plot No.
802.11b Voice EVS-WB Codec: 5.9 kbit/s	CH.6 2437 MHz	20 MHz	DSSS 1 Mbps	z(Axial)	-3.55	-36.19	-55.66	2.00	32.65	T4	
				y(Transversal)	-11.90	-43.06	-55.82		31.16	T4	
			CCK 5.5 Mbps	z(Axial)	-9.44	-39.68	-55.73	2.00	30.23	T4	
				y(Transversal)	-11.03	-42.66	-55.93		31.63	T4	
	CCK 11 Mbps		z(Axial)	-9.94	-40.11	-55.73	2.00	30.17	T4		
			y(Transversal)	-6.75	-38.26	-55.93		31.51	T4		
	CH.1 2412 MHz		DSSS 11 Mbps	z(Axial)	-13.32	-45.67	-55.73	2.00	32.35	T4	
				y(Transversal)	-6.54	-39.21	-55.93		32.67	T4	
CH.11 2462 MHz	DSSS 11 Mbps	z(Axial)	-19.41	-49.19	-55.73	2.00	29.78	T3	31/ 32		
		y(Transversal)	-19.50	-50.72	-55.93		31.22	T4	33		
802.11g Voice EVS-WB Codec: 5.9 kbit/s	CH.6 2437 MHz	20 MHz	QPSK 18 Mbps	z(Axial)	-4.49	-35.75	-55.73	2.00	31.26	T4	
				y(Transversal)	-5.09	-36.81	-55.93		31.71	T4	
802.11n HT20 Voice AMR-WB Codec: 5.9 kbit/s	CH.6 2437 MHz	20 MHz	MCS 0	z(Axial)	-7.96	-41.51	-55.73	2.00	33.55	T4	
				y(Transversal)	-5.86	-38.72	-55.93		32.85	T4	

VoWi-Fi Air Interface Investigation (Continued)

Mode	Ch. Freq.	BW	BW /Modulation	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T-Rating	Plot No.
802.11a Voice EVS-SWB Codec: 24.4 kbit/s	CH.40 5200 MHz	20 MHz	BPSK 6 Mbps	z(Axial)	-11.53	-44.04	-55.55	2.0	32.51	T4	
				y(Transversal)	-15.85	-46.74	-55.81		30.89	T4	
			QPSK 18 Mbps	z(Axial)	-13.07	-43.07	-55.55	2.0	30.00	T3	
				y(Transversal)	-16.93	-50.76	-55.81		33.83	T4	
			64QAM 54 Mbps	z(Axial)	-16.26	-48.78	-55.55	2.0	32.52	T4	
				y(Transversal)	-11.14	-45.93	-55.81		34.80	T4	
802.11n HT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.40 5200 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-13.59	-41.66	-55.55	2.0	28.06	T3	34/ 35
				y(Transversal)	-13.67	-46.57	-55.81		32.90	T4	36
			MCS 3 26 Mbps	z(Axial)	-13.93	-42.98	-55.55	2.0	29.05	T3	
				y(Transversal)	-13.71	-47.08	-55.81		33.37	T4	
			MCS 7 65 Mbps	z(Axial)	-13.52	-45.72	-55.55	2.0	32.20	T4	
				y(Transversal)	-13.61	-48.25	-55.81		34.64	T4	
802.11n HT40 Voice EVS-SWB Codec: 24.4 kbit/s	CH.38 5190 MHz	40 MHz	MCS 0 13.5 Mbps	z(Axial)	-13.22	-42.97	-55.55	2.0	29.75	T3	
				y(Transversal)	-16.62	-50.68	-55.81		34.06	T4	
			MCS 3 54 Mbps	z(Axial)	-12.55	-48.89	-55.55	2.0	36.34	T4	
				y(Transversal)	-16.45	-53.18	-55.81		36.74	T4	
			MCS 7 135 Mbps	z(Axial)	-16.72	-47.40	-55.55	2.0	30.69	T4	
				y(Transversal)	-13.97	-48.17	-55.81		34.20	T4	
802.11ac VHT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.40 5200 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-13.64	-44.73	-55.55	2.0	31.09	T4	
				y(Transversal)	-14.14	-49.45	-55.81		35.30	T4	
			MCS 4 39 Mbps	z(Axial)	-13.54	-44.83	-55.55	2.0	31.29	T4	
				y(Transversal)	-15.14	-48.75	-55.81		33.61	T4	
			MCS 8 78 Mbps	z(Axial)	-11.22	-47.59	-55.55	2.0	36.37	T4	
				y(Transversal)	-13.68	-49.22	-55.81		35.54	T4	
802.11ac VHT40 Voice EVS-SWB Codec: 24.4 kbit/s	CH.38 5190 MHz	40 MHz	MCS 0 13.5 Mbps	z(Axial)	-12.64	-44.59	-55.55	2.0	31.94	T4	
				y(Transversal)	-18.29	-50.69	-55.81		32.40	T4	
			MCS 4 81 Mbps	z(Axial)	-12.94	-49.73	-55.55	2.0	36.80	T4	
				y(Transversal)	-14.06	-51.84	-55.81		37.79	T4	
			MCS 9 180 Mbps	z(Axial)	-14.16	-45.25	-55.55	2.0	31.09	T4	
				y(Transversal)	-15.52	-48.65	-55.81		33.13	T4	
802.11ac VHT80 Voice EVS-SWB Codec: 24.4 kbit/s	CH.42 5210 MHz	80 MHz	MCS 0 29.3 Mbps	z(Axial)	-14.02	-47.49	-43.10	2.0	33.47	T4	
				y(Transversal)	-12.10	-46.67	-48.63		34.57	T4	
			MCS 4 175.5 Mbps	z(Axial)	-10.72	-47.87	-43.10	2.0	37.15	T4	
				y(Transversal)	-14.21	-48.91	-48.63		34.70	T4	
			MCS 9 390 Mbps	z(Axial)	-12.13	-49.56	-43.10	2.0	37.43	T4	
				y(Transversal)	-14.45	-49.57	-48.63		35.12	T4	

Mode	Ch. Freq.	BW	BW /Mode	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T-Rating	Plot No.
802.11n HT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.56 5280 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-10.28	-41.60	-43.10	2.0	31.32	T4	37/ 38
				y(Transversal)	-12.86	-45.27	-48.63		32.41	T4	39
802.11n HT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.120 5600 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-12.16	-44.35	-43.10	2.0	32.18	T4	40/ 41
				y(Transversal)	-15.40	-47.99	-48.63		32.59	T4	42
802.11n HT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.157 5785 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-12.30	-44.42	-43.10	2.0	32.12	T4	43/ 44
				y(Transversal)	-14.83	-48.08	-48.63		33.25	T4	45
802.11n HT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.36 5180 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-12.54	-42.49	-43.10	2.0	29.95	T3	46/ 47
				y(Transversal)	-12.21	-44.48	-48.63		32.27	T4	48
802.11n HT20 Voice EVS-SWB Codec: 24.4 kbit/s	CH.48 5240 MHz	20 MHz	MCS 0 6.5 Mbps	z(Axial)	-10.72	-40.72	-43.10	2.0	29.99	T3	49/ 50
				y(Transversal)	-14.50	-47.08	-48.63		32.58	T4	51

12.6 OTT Coec Investigation

The DUT's nested OTT application supports range of codec bit rate 6 – 75 kbit/s, thus an investigation between the various codec configurations (6/75 as Low/High bit rates) and specific parameters are documented (ABM1, ABM2, S+N/N, frequency response) to determine the worst-case bit rates for each service type.

The table below compares the varying codec configurations.

Codec Investigation					
Codec State	codec bit rate (kbit/s)			Orientation	Band/ BandWidth/ Channel
	6	40	75		
ABM1 (dB/m)	-3.83	-4.35	-4.69	z (Axial)	GSM 850 EDGE 2 slots CH.190 836.6 MHz
ABM2 (dBA/m)	-41.50	-41.67	-44.52		
S+N/N (dB)	37.68	37.32	39.83		
Freq.Resposne (dB)	2.0	2.0	2.0		
ABM1 (dB/m)	-12.87	-12.91	-13.97	y(Transversal)	
ABM2 (dBA/m)	-50.23	-49.44	-50.95		
S+N/N (dB)	37.36	36.53	36.98		
ABM1 (dB/m)	-7.33	-7.11	-7.42	z (Axial)	
ABM2 (dBA/m)	-52.96	-53.23	-53.31		
S+N/N (dB)	45.63	46.12	45.89		
Freq.Resposne (dB)	2.0	2.0	2.0		
ABM1 (dB/m)	-11.65	-11.66	-11.32	y(Transversal)	
ABM2 (dBA/m)	-52.82	-53.01	-52.78		
S+N/N (dB)	41.17	41.35	41.46		
ABM1 (dB/m)	-4.45	-2.42	-4.46	z (Axial)	LTE Band 2 20 MHz QPSK RB 1/0 CH.18900 1880MHz
ABM2 (dBA/m)	-52.20	-48.91	-51.51		
S+N/N (dB)	47.75	46.49	47.05		
Freq.Resposne (dB)	2.0	2.0	2.0		
ABM1 (dB/m)	-8.47	-8.36	-6.93	y(Transversal)	
ABM2 (dBA/m)	-51.72	-51.89	-50.37		
S+N/N (dB)	43.25	43.53	43.45		

Codec Investigation					
Codec State	codec bit rate (kbit/s)			Orientation	Band/ BandWidth/ Channel
	6	40	75		
ABM1 (dB/m)	-5.60	-5.69	-5.62	z (Axial)	802.11b CH.11 2462 MHz 11Mbps
ABM2 (dBA/m)	-38.78	-38.59	-38.60		
S+N/N (dB)	33.19	32.90	32.97		
Freq.Resposne (dB)	2.0	2.0	2.0		
ABM1 (dB/m)	-14.63	-14.99	-14.65	y(Transversal)	
ABM2 (dBA/m)	-51.66	-51.58	-51.65		
S+N/N (dB)	37.04	36.58	37.01		
ABM1 (dB/m)	-6.30	-6.07	-5.50	z (Axial)	
ABM2 (dBA/m)	-47.72	-47.92	-48.82		
S+N/N (dB)	41.43	41.85	43.32		
Freq.Resposne (dB)	2.0	2.0	2.0		
ABM1 (dB/m)	-8.67	-10.16	-11.29	y(Transversal)	
ABM2 (dBA/m)	-49.51	-49.36	-50.73		
S+N/N (dB)	40.84	39.20	39.44		

12.7 OTT Air Interface Investigation

Mode	Ch. Freq.	BW	BW/ Mode	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T- Rating	Plot No.
GSM850 EDGE 2 slots Duo Codec: 40 kbit/s	CH.190 836.6 MHz				z(Axial)	-4.35	-41.67	-52.72	2.0	37.32	T4	52/ 53
					y(Transversal)	-12.91	-49.44	-53.67		36.53	T4	54
GSM1900 EDGE 2 slots Duo Codec: 40 kbit/s	CH.661 1880 MHz				z(Axial)	-1.24	-45.52	-52.72	2.0	44.28	T4	55/ 56
					y(Transversal)	-11.48	-50.87	-53.67		39.39	T4	57
WCDMA Band II HSUPA subtest1 Duo Codec: 6 kbit/s	CH.9400 1800 MHz				z(Axial)	-7.33	-52.96	-52.72	2.0	45.63	T4	58/ 59
					y(Transversal)	-11.65	-52.82	-53.67		41.17	T4	60
WCDMA Band V HSUPA subtest1 Duo Codec: 6 kbit/s	CH.4183 836.6 MHz				z(Axial)	-0.75	-51.79	-52.72	2.0	51.04	T4	61/ 62
					y(Transversal)	-7.84	-51.19	-53.67		43.35	T4	63
LTE Band 2 Google Duo Codec: 6 kbit/s	CH.18900 1880 MHz	20 MHz	QPSK	1/0	z(Axial)	-4.45	-52.20	-52.72	2.0	47.75	T4	64/ 65
					y(Transversal)	-8.47	-51.72	-53.67		43.25	T4	66
LTE Band 5 Google Duo Codec: 6 kbit/s	CH.20525 836.5 MHz	10 MHz	QPSK	1/0	z(Axial)	-0.36	-50.64	-51.29	2.0	50.28	T4	67/ 68
					y(Transversal)	-10.14	-53.46	-54.07		43.32	T4	69
LTE Band 7 Google Duo Codec: 6 kbit/s	CH.21100 2535 MHz	20 MHz	QPSK	1/0	z(Axial)	-0.52	-49.82	-51.29	2.0	49.30	T4	70/ 71
					y(Transversal)	-7.23	-49.94	-54.07		42.71	T4	72
LTE Band 12 Google Duo Codec: 6 kbit/s	CH.23095 707.5 MHz	10 MHz	QPSK	1/0	z(Axial)	-0.47	-50.82	-51.29	2.0	50.34	T4	73/ 74
					y(Transversal)	-7.50	-50.72	-54.07		43.23	T4	75
LTE Band 13 Google Duo Codec: 6 kbit/s	CH.23230 782 MHz	10 MHz	QPSK	1/0	z(Axial)	-0.36	-50.14	-51.29	2.0	49.78	T4	76/ 77
					y(Transversal)	-7.64	-49.91	-54.07		42.27	T4	78
LTE Band 66 Google Duo Codec: 6 kbit/s	CH.132322 1745 MHz	20 MHz	QPSK	1/0	z(Axial)	-0.54	-50.55	-51.29	2.0	50.01	T4	79/ 80
					y(Transversal)	-7.18	-49.99	-54.07		42.81	T4	81

Mode:	Ch./ Freq.	BW/ Data Rate	BW/ Modulation	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T-Rating	Plot No.
Wi-Fi 2.4 GHz 802.11b Google Duo Codec: 40 kbit/s	CH.11 2462 MHz	20MHz	11Mbps		z(Axial)	-5.69	-38.59	-52.72	2.0	32.90	T4	
					y(Transversal)	-14.99	-51.58	-53.67		36.58	T4	
U-NII 5.2 GHz 802.11n HT20 Google Duo Codec: 40 kbit/s	CH.40 5200 MHz	20MHz	MCS0		z(Axial)	-6.07	-47.92	-52.72	2.0	41.85	T4	82/ 83
					y(Transversal)	-10.16	-49.36	-53.67		39.20	T4	84
U-NII 5.3 GHz 802.11n HT20 Google Duo Codec: 40 kbit/s	CH.56 5280 MHz	20MHz	MCS0		z(Axial)	-3.40	-42.78	-52.72	2.0	39.38	T4	85/ 86
					y(Transversal)	-13.94	-50.93	-53.67		36.99	T4	87
U-NII 5.6 GHz 802.11n HT20 Google Duo Codec: 40 kbit/s	CH.120 5600 MHz	20MHz	MCS0		z(Axial)	-3.69	-41.47	-52.72	2.0	37.78	T4	88/ 89
					y(Transversal)	-14.61	-51.13	-53.67		36.52	T4	90
U-NII 5.8 GHz 802.11n HT20 Google Duo Codec: 40 kbit/s	CH.157 5785 MHz	20MHz	MCS0		z(Axial)	-5.27	-41.67	-52.72	2.0	36.40	T4	91/ 92
					y(Transversal)	-16.67	-52.93	-53.67		36.26	T4	93
Wi-Fi 2.4 GHz 802.11b Google Duo Codec: 40 kbit/s	CH.1 2412 MHz	20MHz	11Mbps		z(Axial)	-5.47	-37.95	-52.72	2.0	32.48	T4	
					y(Transversal)	-15.69	-51.10	-53.67		35.41	T4	
Wi-Fi 2.4 GHz 802.11b Google Duo Codec: 40 kbit/s	CH.6 2437 MHz	20MHz	11Mbps		z(Axial)	-5.40	-37.85	-52.72	2.0	32.45	T4	94/ 95
					y(Transversal)	-15.73	-51.51	-53.67		35.78	T4	96

12.8 Radio Configuration for OTT VoIP (NR)

An investigation was performed to determine the waveform, modulation, and RB configuration to be used for testing. Due to equipment limitations, the worst-case ABM1 from OTT VoIP was used with the ABM2 measured for each NR radio configuration. DFT-s-OFDM BPSK, 1RB, 99%RB offset was determined to be the worst-case configuration for the handset and will be used for full testing. Frequency Response measurements were not possible due to equipment limitations

NR OTT VoIP SNNR by Radio Configuration (CP-OFDM)

Mode:	Ch./ Freq.	BW	BW/ Mode	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T- Rating	Plot No.
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	1/1	z(Axial)	-4.45	-44.97	-55.01		40.52	T4	
					y(Transversal)	-10.14	-47.87	-55.94		37.73	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	1/53	z(Axial)	-4.45	-44.70	-55.01		40.25	T4	
					y(Transversal)	-10.14	-50.98	-55.94		40.84	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	1/104	z(Axial)	-4.45	-43.54	-55.01		39.09	T4	
					y(Transversal)	-10.14	-50.49	-55.94		40.35	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	53/0	z(Axial)	-4.45	-48.63	-55.01		44.18	T4	
					y(Transversal)	-10.14	-53.30	-55.94		43.16	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	53/26	z(Axial)	-4.45	-52.04	-55.01		47.59	T4	
					y(Transversal)	-10.14	-52.48	-55.94		42.34	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	53/53	z(Axial)	-4.45	-51.87	-55.01		47.42	T4	
					y(Transversal)	-10.14	-52.89	-55.94		42.75	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	QPSK	106/0	z(Axial)	-4.45	-51.95	-55.01		47.5	T4	
					y(Transversal)	-10.14	-53.35	-55.94		43.21	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	1/1	z(Axial)	-4.45	-44.27	-55.01		39.82	T4	
					y(Transversal)	-10.14	-50.21	-55.94		40.07	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	1/53	z(Axial)	-4.45	-45.21	-55.01		40.76	T4	
					y(Transversal)	-10.14	-51.25	-55.94		41.11	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	1/104	z(Axial)	-4.45	-46.71	-55.01		42.26	T4	
					y(Transversal)	-10.14	-50.64	-55.94		40.50	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	53/0	z(Axial)	-4.45	-46.20	-55.01		41.75	T4	
					y(Transversal)	-10.14	-52.08	-55.94		41.94	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	53/26	z(Axial)	-4.45	-45.48	-55.01		41.03	T4	
					y(Transversal)	-10.14	-51.08	-55.94		40.94	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	53/53	z(Axial)	-4.45	-44.27	-55.01		39.82	T4	
					y(Transversal)	-10.14	-50.98	-55.94		40.84	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	16QAM	106/0	z(Axial)	-4.45	-50.01	-55.01		45.56	T4	
					y(Transversal)	-10.14	-53.62	-55.94		43.48	T4	

n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	1/1	z(Axial)	-4.45	-46.13	-55.01		41.68	T4	
					y(Transversal)	-10.14	-51.09	-55.94		40.95	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	1/53	z(Axial)	-4.45	-45.31	-55.01		40.86	T4	
					y(Transversal)	-10.14	-51.08	-55.94		40.94	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	1/104	z(Axial)	-4.45	-43.75	-55.01		39.30	T4	
					y(Transversal)	-10.14	-49.91	-55.94		39.77	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	53/0	z(Axial)	-4.45	-49.87	-55.01		45.42	T4	
					y(Transversal)	-10.14	-50.97	-55.94		40.83	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	53/26	z(Axial)	-4.45	-48.95	-55.01		44.50	T4	
					y(Transversal)	-10.14	-50.82	-55.94		40.68	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	53/53	z(Axial)	-4.45	-50.04	-55.01		45.59	T4	
					y(Transversal)	-10.14	-51.25	-55.94		41.11	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	64QAM	106/0	z(Axial)	-4.45	-49.63	-55.01		45.18	T4	
					y(Transversal)	-10.14	-54.24	-55.94		44.10	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	1/1	z(Axial)	-4.45	-44.66	-55.01		40.21	T4	
					y(Transversal)	-10.14	-52.05	-55.94		41.91	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	1/53	z(Axial)	-4.45	-49.72	-55.01		45.27	T4	
					y(Transversal)	-10.14	-52.52	-55.94		42.38	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	1/104	z(Axial)	-4.45	-48.98	-55.01		44.53	T4	
					y(Transversal)	-10.14	-44.30	-55.94		34.16	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	53/0	z(Axial)	-4.45	-50.03	-55.01		45.58	T4	
					y(Transversal)	-10.14	-51.79	-55.94		41.65	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	53/26	z(Axial)	-4.45	-51.04	-55.01		46.59	T4	
					y(Transversal)	-10.14	-50.88	-55.94		40.74	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	53/53	z(Axial)	-4.45	-51.85	-55.01		47.40	T4	
					y(Transversal)	-10.14	-51.35	-55.94		41.21	T4	
n2 CP-OFDM	CH.376000 1880 MHz	20MHz	256QAM	106/0	z(Axial)	-4.45	-51.25	-55.01		46.80	T4	
					y(Transversal)	-10.14	-52.50	-55.94		42.36	T4	

NR OTT VoIP SNNR by Radio Configuration (DFT-s-OFDM)

Mode:	Ch./ Freq.	BW	BW/ Mode	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T- Rating	Plot No.
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	1/1	z(Axial)	-4.45	-44.18	-49.96		39.73	T4	
					y(Transversal)	-10.14	-41.75	-46.62		31.61	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	1/53	z(Axial)	-4.45	-45.89	-49.96		41.44	T4	
					y(Transversal)	-10.14	-46.32	-46.62		36.18	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-44.10	-49.96		39.65	T4	
					y(Transversal)	-10.14	-40.46	-46.62		30.32	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	50/0	z(Axial)	-4.45	-46.24	-49.96		41.79	T4	
					y(Transversal)	-10.14	-47.05	-46.62		36.91	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	50/28	z(Axial)	-4.45	-46.28	-49.96		41.83	T4	
					y(Transversal)	-10.14	-45.81	-46.62		35.67	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	50/56	z(Axial)	-4.45	-46.60	-49.96		42.15	T4	
					y(Transversal)	-10.14	-46.02	-46.62		35.67	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	100/0	z(Axial)	-4.45	-46.67	-49.96		42.22	T4	
					y(Transversal)	-10.14	-46.53	-46.62		36.39	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	1/1	z(Axial)	-4.45	-45.08	-49.96		40.63	T4	
					y(Transversal)	-10.14	-45.92	-46.62		35.78	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	1/53	z(Axial)	-4.45	-45.84	-49.96		41.39	T4	
					y(Transversal)	-10.14	-45.82	-46.62		35.88	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	1/104	z(Axial)	-4.45	-45.44	-49.96		40.99	T4	
					y(Transversal)	-10.14	-46.23	-46.62		36.09	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	50/0	z(Axial)	-4.45	-45.02	-49.96		40.57	T4	
					y(Transversal)	-10.14	-46.03	-46.62		35.89	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	50/28	z(Axial)	-4.45	-45.31	-49.96		40.86	T4	
					y(Transversal)	-10.14	-45.98	-46.62		35.84	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	50/56	z(Axial)	-4.45	-44.82	-49.96		40.37	T4	
					y(Transversal)	-10.14	-46.05	-46.62		35.91	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	QPSK	100/0	z(Axial)	-4.45	-46.35	-49.96		41.90	T4	
					y(Transversal)	-10.14	-46.49	-46.62		36.35	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	1/1	z(Axial)	-4.45	-41.95	-49.96		37.50	T4	
					y(Transversal)	-10.14	-45.91	-46.62		35.77	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	1/53	z(Axial)	-4.45	-45.38	-49.96		40.93	T4	
					y(Transversal)	-10.14	-46.42	-46.62		36.28	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	1/104	z(Axial)	-4.45	-43.40	-49.96		38.95	T4	
					y(Transversal)	-10.14	-45.67	-46.62		35.53	T4	

n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	50/0	z(Axial)	-4.45	-46.20	-49.96		41.75	T4	
					y(Transversal)	-10.14	-46.05	-46.62		35.91	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	50/28	z(Axial)	-4.45	-46.72	-49.96		42.27	T4	
					y(Transversal)	-10.14	-46.31	-46.62		36.17	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	50/56	z(Axial)	-4.45	-46.84	-49.96		42.39	T4	
					y(Transversal)	-10.14	-46.41	-46.62		36.27	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	16QAM	100/0	z(Axial)	-4.45	-46.33	-49.96		41.88	T4	
					y(Transversal)	-10.14	-46.36	-46.62		36.22	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	1/1	z(Axial)	-4.45	-43.54	-49.96		39.09	T4	
					y(Transversal)	-10.14	-45.65	-46.62		35.51	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	1/53	z(Axial)	-4.45	-45.52	-49.96		41.07	T4	
					y(Transversal)	-10.14	-46.18	-46.62		36.04	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	1/104	z(Axial)	-4.45	-43.84	-49.96		39.39	T4	
					y(Transversal)	-10.14	-45.59	-46.62		35.45	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	50/0	z(Axial)	-4.45	-46.20	-49.96		41.75	T4	
					y(Transversal)	-10.14	-45.88	-46.62		35.74	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	50/28	z(Axial)	-4.45	-46.72	-49.96		42.27	T4	
					y(Transversal)	-10.14	-46.53	-46.62		36.39	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	50/56	z(Axial)	-4.45	-46.38	-49.96		41.93	T4	
					y(Transversal)	-10.14	-45.76	-46.62		35.62	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	64QAM	100/0	z(Axial)	-4.45	-46.51	-49.96		42.06	T4	
					y(Transversal)	-10.14	-46.21	-46.62		36.07	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	1/1	z(Axial)	-4.45	-44.69	-49.96		40.24	T4	
					y(Transversal)	-10.14	-46.07	-46.62		35.93	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	1/53	z(Axial)	-4.45	-46.51	-49.96		42.06	T4	
					y(Transversal)	-10.14	-46.21	-46.62		36.07	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	1/104	z(Axial)	-4.45	-44.80	-49.96		40.35	T4	
					y(Transversal)	-10.14	-46.27	-46.62		36.13	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	50/0	z(Axial)	-4.45	-46.34	-49.96		41.89	T4	
					y(Transversal)	-10.14	-46.31	-46.62		36.17	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	50/28	z(Axial)	-4.45	-46.27	-49.96		41.82	T4	
					y(Transversal)	-10.14	-45.75	-46.62		35.61	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	50/56	z(Axial)	-4.45	-46.70	-49.96		42.25	T4	
					y(Transversal)	-10.14	-46.15	-46.62		36.01	T4	
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	256QAM	100/0	z(Axial)	-4.45	-46.60	-49.96		42.15	T4	
					y(Transversal)	-10.14	-46.52	-46.62		36.38	T4	

An investigation was performed to determine the worst-case NR band to be used for OTT VoIP testing. NR n2 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different NR bands

OTT VoIP (NR) SNNR by Band

Mode:	Ch./ Freq.	BW	BW/ Mode	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T- Rating	Plot No.
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-44.10	-49.96		39.65	T4	97
					y(Transversal)	-10.14	-40.46	-46.62		30.32	T4	98
n5 DFT-s-OFDM	CH.167300 836.5 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-46.94	-46.80		42.49	T4	99
					y(Transversal)	-10.14	-50.80	-42.36		40.66	T4	100
n66 DFT-s-OFDM	CH.349000 1745 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-47.38	-46.80		42.93	T4	101
					y(Transversal)	-10.14	-44.12	-42.36		33.98	T4	102

Raw Data Results for NR n2 (OTT VoIP)

Mode:	Ch./ Freq.	BW	BW/ Mode	RB Config.	Orientation	ABM1 dB(A/m)	ABM2 dB(A/m)	Ambient Noise dB(A/m)	Freq. Response (dB)	ABM SNR (dB)	T- Rating	Plot No.
n2 DFT-s-OFDM	CH.376000 1880 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-44.10	-49.96		39.65	T4	97
					y(Transversal)	-10.14	-40.46	-46.62		30.32	T4	98
n2 DFT-s-OFDM	CH.376000 1880 MHz	15MHz	BPSK	1/104	z(Axial)	-4.45	-47.03	-46.80		42.58	T4	103
					y(Transversal)	-10.14	-51.73	-42.36		41.59	T4	104
n2 DFT-s-OFDM	CH.376000 1880 MHz	10MHz	BPSK	1/104	z(Axial)	-4.45	-46.76	-46.80		42.31	T4	105
					y(Transversal)	-10.14	-42.01	-42.36		31.87	T4	106
n2 DFT-s-OFDM	CH.376000 1880 MHz	5MHz	BPSK	1/104	z(Axial)	-4.45	-52.68	-46.80		48.23	T4	107
					y(Transversal)	-10.14	-54.42	-42.36		44.28	T4	108
n2 DFT-s-OFDM	CH.372000 1860 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-44.62	-46.80		40.17	T4	109
					y(Transversal)	-10.14	-40.51	-42.36		30.37	T4	110
n2 DFT-s-OFDM	CH.380000 1900 MHz	20MHz	BPSK	1/104	z(Axial)	-4.45	-46.62	-46.80		42.17	T4	111
					y(Transversal)	-10.14	-51.65	-42.36		41.51	T4	112

Attachment 1. HAC T-COIL Test Plots

Plot No.1

GSM850 AMR-NB FR V1 190ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:8.30042
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -5.45 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 8.3, 3.7 mm

Cursor:

ABM2 = -44.08 dBA/m
 Location: 0, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 38.63 dB
 ABM1 comp = -5.45 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No. 2

GSM850 AMR-NB FR V1 190ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:8.30042
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 75.5
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.47 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
 BWC Factor = 9.47 dB
 Location: 2.3, 10.1, 3.7 mm



Plot No.3

GSM850 AMR-NB FR V1 190ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:8.30042
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -9.71 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm

Cursor:

ABM2 = -46.47 dBA/m

Location: 4.2, 0, 3.7 mm


Cursor:

ABM1/ABM2 = 36.75 dB

ABM1 comp = -9.71 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.4
GSM1900 661ch FR V1 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -2.57 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -41.85 dBA/m

Location: 4.2, 8.3, 3.7 mm


Cursor:

ABM1/ABM2 = 39.28 dB

ABM1 comp = -2.57 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.5
GSM1900 661ch FR V1 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 1.92 dB

BWC Factor = 9.47 dB

Location: 4, 8.7, 3.7 mm



Plot No.6
GSM1900 661ch FR V1 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:8.30042
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.09 dBA/m

BWC Factor = 0.16 dB

Location: 0, 0, 3.7 mm

Cursor:

ABM2 = -49.79 dBA/m

Location: 0, 0, 3.7 mm


Cursor:

ABM1/ABM2 = 37.69 dB

ABM1 comp = -12.09 dBA/m

BWC Factor = 0.16 dB

Location: 0, 0, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.7
WCDMA2 AMR-WB 23_85 9400ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 24.86
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -8.36 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -47.03 dBA/m
Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 38.67 dB
ABM1 comp = -8.36 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.8
WCDMA2 AMR-WB 23_85 9400ch Freq. Response


DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
Output Gain: 75.5
Measure Window Start: 300ms
Measure Window Length: 51000ms
BWC applied: 9.47 dB
Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
Diff = 2.00 dB
BWC Factor = 9.47 dB
Location: 2.8, 8.7, 3.7 mm



Plot No.9
WCDMA2 AMR-WB 23_85 9400ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 24.86
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -17.09 dBA/m
BWC Factor = 0.16 dB
Location: 0, 16.7, 3.7 mm

Cursor:

ABM2 = -52.50 dBA/m
Location: 0, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 35.41 dB
ABM1 comp = -17.09 dBA/m
BWC Factor = 0.16 dB
Location: 0, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.10
WCDMA5 AMR-WB 23_85 4183ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 24.86
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -1.02 dBA/m
BWC Factor = 0.16 dB
Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -39.64 dBA/m
Location: 0, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 38.62 dB
ABM1 comp = -1.02 dBA/m
BWC Factor = 0.16 dB
Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.11
WCDMA5 AMR-WB 23_85 4183ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.48 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB

BWC Factor = 9.48 dB

Location: 1.9, 12.4, 3.7 mm



Plot No.12

WCDMA5 AMR-WB 23_85 4183ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 2019-11-20
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -4.03 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 16.7, 3.7 mm

Cursor:

ABM2 = -42.54 dBA/m
 Location: 0, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 38.50 dB
 ABM1 comp = -4.03 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.13
LTE 2 EVS nb 5_9 QPSK 20MHz 1RB 0offset 18900ch (axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 2.71 dBA/m

BWC Factor = 0.15 dB

Location: 4.2, 12.5, 3.7 mm

Cursor:

ABM2 = -32.08 dBA/m

Location: 4.2, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 34.79 dB

ABM1 comp = 2.71 dBA/m

BWC Factor = 0.15 dB

Location: 4. 2, 12.5, 3.7 mm



Plot No.14
LTE 2 EVS nb 5_9 QPSK 20MHz 1RB 0offset 18900ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM

Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 1.59 dB

BWC Factor = 9.47 dB

Location: 4, 14.1, 3.7 mm



Plot No.15
LTE 2 EVS nb 5_9 QPSK 20MHz 1RB 0offset 18900ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.15 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -5.78 dBA/m
 BWC Factor = 0.15 dB
 Location: 4.2, -8.3, 3.7 mm

Cursor:

ABM2 = -40.43 dBA/m
 Location: 4.2, -8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 34.64 dB
 ABM1 comp = -5.78 dBA/m
 BWC Factor = 0.15 dB
 Location: 4.2, -8.3, 3.7 mm



Plot No.16
LTE 5 EVS nb 5_9 QPSK 10MHz 1RB 0offset 20525ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = 3.58 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 12.5, 3.7 mm

Cursor:

ABM2 = -32.10 dBA/m
 Location: 4.2, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 35.68 dB
 ABM1 comp = 3.58 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 12.5, 3.7 mm



Plot No.17

LTE 5 EVS nb 5_9 QPSK 10MHz 1RB 0offset 20525ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM

Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.45 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 1.59 dB

BWC Factor = 9.45 dB

Location: 5.9, 14.5, 3.7 mm



Plot No.18
LTE 5 EVS nb 5_9 QPSK 10MHz 1RB 0offset 20525ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -2.74 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM2 = -38.32 dBA/m
 Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 35.58 dB
 ABM1 comp = -2.74 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 16.7, 3.7 mm



Plot No.19
LTE 7 EVS nb 5_9 QPSK 20MHz 1RB 0offset 21100ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = 4.58 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -31.16 dBA/m
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 35.74 dB
 ABM1 comp = 4.58 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm



Plot No.20

LTE 7 EVS nb 5_9 QPSK 20MHz 1RB 0offset 21100ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM

Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 1.74 dB

BWC Factor = 9.47 dB

Location: 2.5, 8, 3.7 mm



Plot No.21
LTE 7 EVS nb 5_9 QPSK 20MHz 1RB 0offset 21100ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -4.66 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 0, 3.7 mm

Cursor:

ABM2 = -40.20 dBA/m
 Location: 0, 0, 3.7 mm

Cursor:

ABM1/ABM2 = 35.53 dB
 ABM1 comp = -4.66 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 0, 3.7 mm



Plot No.22
LTE 12 EVS nb 5_9 QPSK 10MHz 1RB 0offset 23095ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = 3.56 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 12.5, 3.7 mm

Cursor:

ABM2 = -32.13 dBA/m

Location: 4.2, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 35.70 dB

ABM1 comp = 3.56 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 12.5, 3.7 mm



Plot No.23

LTE 12 EVS nb 5_9 QPSK 10MHz 1RB 0offset 23095ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM

Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 1.73 dB

BWC Factor = 9.47 dB

Location: 5, 19, 3.7 mm



Plot No.24
LTE 12 EVS nb 5_9 QPSK 10MHz 1RB 0offset 23095ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -4.54 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 0, 3.7 mm

Cursor:

ABM2 = -40.12 dBA/m
 Location: 0, 0, 3.7 mm

Cursor:

ABM1/ABM2 = 35.58 dB
 ABM1 comp = -4.54 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 0, 3.7 mm



Plot No.25
LTE 13 EVS nb 5_9 QPSK 10MHz 1RB 0offset 23230ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -5.44 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, 12.5, 3.7 mm

Cursor:

ABM2 = -42.04 dBA/m

Location: -4.2, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 36.60 dB

ABM1 comp = -5.44 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, 12.5, 3.7 mm



Plot No.26

LTE 13 EVS nb 5_9 QPSK 10MHz 1RB 0offset 23230ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM

Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB

BWC Factor = 9.47 dB

Location: -0.3, 5.1, 3.7 mm



Plot No.27
LTE 13 EVS nb 5_9 QPSK 10MHz 1RB 0offset 23230ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 24.86

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -5.80 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, 16.7, 3.7 mm

Cursor:

ABM2 = -42.56 dBA/m

Location: -4.2, 16.7, 3.7 mm


Cursor:

ABM1/ABM2 = 36.76 dB

ABM1 comp = -5.80 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, 16.7, 3.7 mm



Plot No.28
LTE 66 EVS nb 5_9 QPSK 20MHz 1RB 0offset 132322ch z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = 4.22 dBA/m
 BWC Factor = 0.16 dB
 Location: 8.3, 12.5, 3.7 mm

Cursor:

ABM2 = -31.46 dBA/m
 Location: 8.3, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 35.68 dB
 ABM1 comp = 4.22 dBA/m
 BWC Factor = 0.16 dB
 Location: 8.3, 12.5, 3.7 mm



Plot No.29

LTE 66 EVS nb 5_9 QPSK 20MHz 1RB 0offset 132322ch Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM

Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 75.5

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 1.59 dB

BWC Factor = 9.47 dB

Location: 10.2, 12.6, 3.7 mm



Plot No.30
LTE 66 EVS nb 5_9 QPSK 20MHz 1RB 0offset 132322ch y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM

Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 24.86
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -3.79 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 20.8, 3.7 mm

Cursor:

ABM2 = -39.31 dBA/m
 Location: 4.2, 20.8, 3.7 mm

Cursor:

ABM1/ABM2 = 35.53 dB
 ABM1 comp = -3.79 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 20.8, 3.7 mm



Plot No.31
802_11b 11Mbps 11ch EVS-WB 5_9 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, 2450MHz FCC (0); Frequency: 2462 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:


- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 15.65
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.15 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:
 ABM1 comp = -19.41 dBA/m
 BWC Factor = 0.15 dB
 Location: -8.3, 12.5, 3.7 mm

Cursor:
 ABM2 = -49.19 dBA/m
 Location: -8.3, 12.5, 3.7 mm

Cursor:
 ABM1/ABM2 = 29.78 dB
 ABM1 comp = -19.41 dBA/m
 BWC Factor = 0.15 dB
 Location: -8.3, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.32
802_11b 11Mbps 11ch EVS-WB 5_9 Freq. Response


DUT: SM-A516V; Type: Bar

Communication System: UID 0, 2450MHz FCC (0); Frequency: 2462 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
Output Gain: 47.45
Measure Window Start: 300ms
Measure Window Length: 51000ms
BWC applied: 9.47 dB
Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
Diff = 2.00 dB
BWC Factor = 9.47 dB
Location: -8.6, 12.3, 3.7 mm



Plot No.33
802_11b 11Mbps 11ch EVS-WB 5_9 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, 2450MHz FCC (0); Frequency: 2462 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -19.50 dBA/m

BWC Factor = 0.15 dB

Location: -8.3, 20.8, 3.7 mm

Cursor:

ABM2 = -50.72 dBA/m

Location: -8.3, 20.8, 3.7 mm


Cursor:

ABM1/ABM2 = 31.22 dB

ABM1 comp = -19.50 dBA/m

BWC Factor = 0.15 dB

Location: -8.3, 20.8, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.34
802_11n20 MCS0 40ch EVS SWB 24_4 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5200 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 15.65
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -13.59 dBA/m
BWC Factor = 0.16 dB
Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -41.66 dBA/m
Location: 0, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 28.06 dB
ABM1 comp = -13.59 dBA/m
BWC Factor = 0.16 dB
Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.35
802_11n20 MCS0 40ch EVS SWB 24_4 Freq. Response


DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5200 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Pantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
Output Gain: 47.45
Measure Window Start: 300ms
Measure Window Length: 51000ms
BWC applied: 9.48 dB
Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: -1.9, 12.4, 3.7 mm



Plot No.36
802_11n20 MCS0 40ch EVS SWB 24_4 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5200 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -13.67 dBA/m

BWC Factor = 0.16 dB

Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -46.57 dBA/m

Location: 0, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 32.90 dB

ABM1 comp = -13.67 dBA/m

BWC Factor = 0.16 dB

Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.37

802_11n20 MCS0 56ch EVS SWB 24_4 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5280 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 15.65
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -10.28 dBA/m
BWC Factor = 0.16 dB
Location: 0, 8.3, 3.7 mm

Cursor:

ABM2 = -41.60 dBA/m
Location: 0, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 31.32 dB
ABM1 comp = -10.28 dBA/m
BWC Factor = 0.16 dB
Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.38
802_11n20 MCS0 56ch EVS SWB 24_4 Freq. Response


DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5280 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 47.45
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.47 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
 Diff = 2.00 dB
 BWC Factor = 9.47 dB
 Location: 0.3, 8.8, 3.7 mm



Plot No.39
802_11n20 MCS0 56ch EVS SWB 24_4 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5280 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.86 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 16.7, 3.7 mm


Cursor:

ABM2 = -45.27 dBA/m

Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 32.41 dB
 ABM1 comp = -12.86 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.40

802_11n20 MCS0 120ch EVS SWB 24_4 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5600 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.16 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 12.5, 3.7 mm


Cursor:

ABM2 = -44.35 dBA/m

Location: 0, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 32.18 dB
 ABM1 comp = -12.16 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.41

802_11n20 MCS0 120ch EVS SWB 24_4 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5600 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 47.45

Measure Window Start: 300ms

Measure Window Length: 51000ms


BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
 BWC Factor = 9.47 dB
 Location: 0.2, 11.8, 3.7 mm



Plot No.42
802_11n20 MCS0 120ch EVS SWB 24_4 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5600 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 15.65
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm


Cursor:
ABM1 comp = -15.40 dBA/m
BWC Factor = 0.16 dB
Location: 0, 16.7, 3.7 mm

Cursor:
ABM2 = -47.99 dBA/m

Location: 0, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 32.59 dB
 ABM1 comp = -15.40 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.43

802_11n20 MCS0 157ch EVS SWB 24_ z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5785 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.30 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 12.5, 3.7 mm


Cursor:

ABM2 = -44.42 dBA/m

Location: 0, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 32.12 dB
 ABM1 comp = -12.30 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.44

802_11n20 MCS0 157ch EVS SWB 24_4 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5785 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 47.45

Measure Window Start: 300ms

Measure Window Length: 51000ms


BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
 BWC Factor = 9.47 dB
 Location: 0, 11.6, 3.7 mm



Plot No.45

802_11n20 MCS0 157ch EVS SWB 24_4 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5785 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -14.83 dBA/m

BWC Factor = 0.16 dB

Location: 0, 16.7, 3.7 mm


Cursor:

ABM2 = -48.08 dBA/m

Location: 0, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 33.25 dB
 ABM1 comp = -14.83 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.46

802_11n20 MCS0 36ch EVS SWB 24_4 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5180 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.54 dBA/m
 BWC Factor = 0.15 dB
 Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -42.49 dBA/m

Location: 0, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 29.95 dB

ABM1 comp = -12.54 dBA/m

BWC Factor = 0.15 dB

Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.47

802_11n20 MCS0 36ch EVS SWB 24_4 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5180 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 47.45

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.47 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB

BWC Factor = 9.47 dB

Location: 0.2, 11.3, 3.7 mm



Plot No.48

802_11n20 MCS0 36ch EVS SWB 24_4 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5180 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.15 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.21 dBA/m

BWC Factor = 0.15 dB

Location: 4.2, 16.7, 3.7 mm


Cursor:

ABM2 = -44.48 dBA/m

Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 32.27 dB
 ABM1 comp = -12.21 dBA/m
 BWC Factor = 0.15 dB
 Location: 4.2, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.49

802_11n20 MCS0 48ch EVS SWB 24_4 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5240 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -10.72 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 8.3, 3.7 mm


Cursor:

ABM2 = -40.72 dBA/m

Location: 0, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 29.99 dB
 ABM1 comp = -10.72 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.50

802_11n20 MCS0 48ch EVS SWB 24_4 Freq. Response

DUT: SM-A516V; Type: Bar


Communication System: UID 0, WIFI 5GHz (0); Frequency: 5240 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 47.45
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.47 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
 BWC Factor = 9.47 dB
 Location: 0.1, 9, 3.7 mm



Plot No.51

802_11n20 MCS0 48ch EVS SWB 24_4 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5240 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 15.65

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -14.50 dBA/m

BWC Factor = 0.16 dB


Location: 0, 16.7, 3.7 mm

Cursor:

ABM2 = -47.08 dBA/m

Cursor:

ABM1/ABM2 = 32.58 dB
 ABM1 comp = -14.50 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.52

001_GSM850 EDGE 2Slots 190ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM850 2TX (0); Frequency: 836.6 MHz;Duty Cycle: 1:4.14954
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -4.35 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 12.5, 3.7 mm


Cursor:

ABM2 = -41.67 dBA/m

Location: 4.2, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 37.32 dB
 ABM1 comp = -4.35 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.53

GSM850 EDGE 2Slots 190ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar


Communication System: UID 0, GSM850 2TX (0); Frequency: 836.6 MHz;Duty Cycle: 1:4.14954
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 59.83
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.48 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
 BWC Factor = 9.48 dB
 Location: 4, 11.5, 3.7 mm



Plot No.54

GSM850 EDGE 2Slots 190ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM850 2TX (0); Frequency: 836.6 MHz;Duty Cycle: 1:4.14954
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -12.91 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -4.2, 3.7 mm


Cursor:

ABM2 = -49.44 dBA/m

Location: -4.2, -4.2, 3.7 mm

Cursor:

ABM1/ABM2 = 36.53 dB
 ABM1 comp = -12.91 dBA/m
 BWC Factor = 0.16 dB
 Location: -4.2, -4.2, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.55

GSM1900 EDGE 2Slots 661ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 1900 2TX (0); Frequency: 1880 MHz;Duty Cycle: 1:4.14954
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -1.24 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -45.52 dBA/m

Location: 4.2, 8.3, 3.7 mm


Cursor:

ABM1/ABM2 = 44.28 dB

ABM1 comp = -1.24 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.56

GSM1900 EDGE 2Slots 661ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.48 dB

Device Reference Point: 0, 0, -6.3 mm


Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB

BWC Factor = 9.48 dB

Location: 4.6, 8, 3.7 mm



Plot No.57

GSM1900 EDGE 2Slots 661ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, GSM 1900 2TX (0); Frequency: 1880 MHz;Duty Cycle: 1:4.14954
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 19.66
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -11.48 dBA/m
BWC Factor = 0.16 dB


Location: 0, -4.2, 3.7 mm

Cursor:

ABM2 = -50.87 dBA/m
Location: 0, -4.2, 3.7 mm

Cursor:

ABM1/ABM2 = 39.39 dB
ABM1 comp = -11.48 dBA/m
BWC Factor = 0.16 dB
Location: 0, -4.2, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.58

WCDMA2 AMR-WB 23_85 9400ch Bitrate 6 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -7.33 dBA/m
BWC Factor = 0.17 dB


Location: 0, 8.3, 3.7 mm

Cursor:

ABM2 = -52.96 dBA/m
Location: 0, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 45.63 dB
ABM1 comp = -7.33 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.59

WCDMA2 AMR-WB 23_85 9400ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms


BWC applied: 9.48 dB

Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 2, 9, 3.7 mm



Plot No.60
WCDMA2 AMR-WB 23_85 9400ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 19.66
Measure Window Start: 300ms
Measure Window Length: 1000ms
BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -11.65 dBA/m
BWC Factor = 0.17 dB
Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -52.82 dBA/m
Location: 0, 12.5, 3.7 mm

Cursor:

ABM1/ABM2 = 41.17 dB
ABM1 comp = -11.65 dBA/m
BWC Factor = 0.17 dB
Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.61

WCDMA5 AMR-WB 23_85 4183ch Bitrate 6 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -0.75 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -51.79 dBA/m
Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 51.04 dB
ABM1 comp = -0.75 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.62

WCDMA5 AMR-WB 23_85 4183ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Ba

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.48 dB


Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB

Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
 BWC Factor = 9.48 dB
 Location: 3.6, 8.5, 3.7 mm



Plot No.63
WCDMA5 AMR-WB 23_85 4183ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms

BWC applied: 0.16 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -7.84 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM2 = -51.19 dBA/m
Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 43.35 dB
ABM1 comp = -7.84 dBA/m
BWC Factor = 0.16 dB
Location: 4.2, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.64

LTE 2 20MHz QPSK 1RB 0offset 18900ch Bitrate 6 z(axial)

DT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB
Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -4.45 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm

Cursor:

ABM2 = -52.20 dBA/m
Location: 0, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 47.75 dB
ABM1 comp = -4.45 dBA/m
BWC Factor = 0.17 dB
Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.65

LTE 2 20MHz QPSK 1RB 0offset 18900ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.48 dB


Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB

Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 0.8, 8.4, 3.7 mm



Plot No.66

LTE 2 20MHz QPSK 1RB 0offset 18900ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms
 BWC applied: 0.17 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -8.47 dBA/m
 BWC Factor = 0.17 dB
 Location: 0, 16.7, 3.7 mm

Cursor:

ABM2 = -51.72 dBA/m
 Location: 0, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 43.25 dB
 ABM1 comp = -8.47 dBA/m
 BWC Factor = 0.17 dB
 Location: 0, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.67

LTE 5 10MHz QPSK 1RB 0offset 20525ch Bitrate 6 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -0.36 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -50.64 dBA/m
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 50.28 dB
 ABM1 comp = -0.36 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.68

LTE 5 10MHz QPSK 1RB 0offset 20525ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms

BWC applied: 9.48 dB


Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
----------	---

Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 3.7, 8.2, 3.7 mm



Plot No.69
LTE 5 10MHz QPSK 1RB 0offset 20525ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -10.14 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 0, 3.7 mm

Cursor:

ABM2 = -53.46 dBA/m
 Location: 0, 0, 3.7 mm

Cursor:

ABM1/ABM2 = 43.32 dB
 ABM1 comp = -10.14 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 0, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.70

LTE 7 20MHz QPSK 1RB 0offset 21100ch Bitrate 6 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -0.52 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -49.82 dBA/m
 Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 49.30 dB
 ABM1 comp = -0.52 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.71

LTE 7 20MHz QPSK 1RB 0offset 21100ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms


BWC applied: 9.48 dB

Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 3.2, 8.3, 3.7 mm



Plot No.72

LTE 7 20MHz QPSK 1RB 0offset 21100ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -7.23 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM2 = -49.94 dBA/m
 Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM1/ABM2 = 42.71 dB
 ABM1 comp = -7.23 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.73

LTE 12 10MHz QPSK 1RB 0offset 23095ch Bitrate 6 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -0.47 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 8.3, 3.7 mm

Cursor:

ABM2 = -50.82 dBA/m

Location: 4.2, 8.3, 3.7 mm


Cursor:

ABM1/ABM2 = 50.34 dB

ABM1 comp = -0.47 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.74

LTE 12 10MHz QPSK 1RB 0offset 23095ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms

Measure Window Length: 51000ms


BWC applied: 9.48 dB

Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 3.6, 8, 3.7 mm



Plot No.75

LTE 12 10MHz QPSK 1RB 0offset 23095ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50**x 50/ABM Signal(x,y,z) (13x13x1):** Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -7.50 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm

Cursor:

ABM2 = -50.72 dBA/m

Location: 4.2, 0, 3.7 mm


Cursor:

ABM1/ABM2 = 43.23 dB

ABM1 comp = -7.50 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.76**LTE 13 10MHz QPSK 1RB 0offset 23230ch Bitrate 6 z(axial)****DUT: SM-A516V; Type: Bar**

Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:


- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:
 ABM1 comp = -0.36 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm

Cursor:
 ABM2 = -50.14 dBA/m
 Location: 4.2, 8.3, 3.7 mm

Cursor:
 ABM1/ABM2 = 49.78 dB
 ABM1 comp = -0.36 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.77

LTE 13 10MHz QPSK 1RB 0offset 23230ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar


Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 59.83
 Measure Window Start: 300ms
 Measure Window Length: 51000ms

BWC applied: 9.48 dB
Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 4, 8.1, 3.7 mm



Plot No.78
LTE 13 10MHz QPSK 1RB 0offset 23230ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC

- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -7.64 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm

Cursor:

ABM2 = -49.91 dBA/m

Location: 4.2, 0, 3.7 mm


Cursor:

ABM1/ABM2 = 42.27 dB

ABM1 comp = -7.64 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 0, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.79

LTE 66 20MHz QPSK 1RB 0offset 132322ch Bitrate 6 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC


- Measurement SW: DASYS2, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:
 ABM1 comp = -0.54 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm

Cursor:
 ABM2 = -50.55 dBA/m
 Location: 4.2, 8.3, 3.7 mm

Cursor:
 ABM1/ABM2 = 50.01 dB
 ABM1 comp = -0.54 dBA/m
 BWC Factor = 0.16 dB
 Location: 4.2, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.80

LTE 66 20MHz QPSK 1RB 0offset 132322ch Bitrate 6 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 59.83
 Measure Window Start: 300ms

Measure Window Length: 51000ms
BWC applied: 9.48 dB
Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:

Diff = 2.00 dB
BWC Factor = 9.48 dB
Location: 3.6, 8.2, 3.7 mm



Plot No.81
LTE 66 20MHz QPSK 1RB 0offset 132322ch Bitrate 6 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26

- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASYS2, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -7.18 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 16.7, 3.7 mm

Cursor:

ABM2 = -49.99 dBA/m

Location: 4.2, 16.7, 3.7 mm


Cursor:

ABM1/ABM2 = 42.81 dB

ABM1 comp = -7.18 dBA/m

BWC Factor = 0.16 dB

Location: 4.2, 16.7, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.82

802_11n20 MCS0 40ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5200 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019

- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.17 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -6.07 dBA/m

BWC Factor = 0.17 dB

Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -47.92 dBA/m

Location: 0, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 41.85 dB

ABM1 comp = -6.07 dBA/m

BWC Factor = 0.17 dB

Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.83

802_11n20 MCS0 40ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5200 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best

S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm


Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83

Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.48 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
 Diff = 2.00 dB
 BWC Factor = 9.48 dB
 Location: 0, 11.3, 3.7 mm



Plot No.84
802_11n20 MCS0 40ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5200 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019

- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASYS2, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.17 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:


ABM1 comp = -10.16 dBA/m
 BWC Factor = 0.17 dB
 Location: 0, 0, 3.7 mm

Cursor:

ABM2 = -49.36 dBA/m
 Location: 0, 0, 3.7 mm

Cursor:

ABM1/ABM2 = 39.20 dB
 ABM1 comp = -10.16 dBA/m
 BWC Factor = 0.17 dB
 Location: 0, 0, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.85

802_11n20 MCS0 56ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5280 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019

- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DAS52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 BWC applied: 0.16 dB
 Device Reference Point: 0, 0, -6.3 mm

Cursor:



ABM1 comp = -3.40 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 8.3, 3.7 mm

Cursor:

ABM2 = -42.78 dBA/m
 Location: 0, 8.3, 3.7 mm

Cursor:

ABM1/ABM2 = 39.38 dB
 ABM1 comp = -3.40 dBA/m
 BWC Factor = 0.16 dB
 Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.86

802_11n20 MCS0 56ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar


Communication System: UID 0, WIFI 5GHz (0); Frequency: 5280 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_Normal_51s new.wav

Output Gain: 59.83
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.48 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
 Diff = 2.00 dB
 BWC Factor = 9.48 dB
 Location: 0.3, 10.3, 3.7 mm



Plot No.87
802_11n20 MCS0 56ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5280 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -13.94 dBA/m

BWC Factor = 0.16 dB

Location: 0, -8.3, 3.7 mm

Cursor:

ABM2 = -50.93 dBA/m

Location: 0, -8.3, 3.7 mm


Cursor:

ABM1/ABM2 = 36.99 dB

ABM1 comp = -13.94 dBA/m

BWC Factor = 0.16 dB

Location: 0, -8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.88

802_11n20 MCS0 120ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5600 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -3.69 dBA/m

BWC Factor = 0.16 dB

Location: 0, 8.3, 3.7 mm

Cursor:

ABM2 = -41.47 dBA/m

Location: 0, 8.3, 3.7 mm


Cursor:

ABM1/ABM2 = 37.78 dB

ABM1 comp = -3.69 dBA/m

BWC Factor = 0.16 dB

Location: 0, 8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.89

802_11n20 MCS0 120ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5600 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³


Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 59.83
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.48 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
 Diff = 2.00 dB
 BWC Factor = 9.48 dB
 Location: 1.1, 10.2, 3.7 mm



Plot No.90
802_11n20 MCS0 120ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5600 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -14.61 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -4.2, 3.7 mm

Cursor:

ABM2 = -51.13 dBA/m

Location: -4.2, -4.2, 3.7 mm


Cursor:

ABM1/ABM2 = 36.52 dB

ABM1 comp = -14.61 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -4.2, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.91

802_11n20 MCS0 157ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5785 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -5.27 dBA/m

BWC Factor = 0.16 dB

Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -41.67 dBA/m

Location: 0, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 36.40 dB

ABM1 comp = -5.27 dBA/m

BWC Factor = 0.16 dB

Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.92

802_11n20 MCS0 157ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5785 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³


Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 59.83
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.48 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
 Diff = 2.00 dB
 BWC Factor = 9.48 dB
 Location: 0.7, 10.7, 3.7 mm



Plot No.93
802_11n20 MCS0 157ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5785 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -16.67 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -8.3, 3.7 mm

Cursor:

ABM2 = -52.93 dBA/m

Location: -4.2, -8.3, 3.7 mm


Cursor:

ABM1/ABM2 = 36.26 dB

ABM1 comp = -16.67 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -8.3, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.94

802_11b 11Mbps 1ch Bitrate 40 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, 2450MHz FCC (0); Frequency: 2437 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -5.40 dBA/m

BWC Factor = 0.16 dB

Location: 0, 12.5, 3.7 mm

Cursor:

ABM2 = -37.85 dBA/m

Location: 0, 12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 32.45 dB

ABM1 comp = -5.40 dBA/m

BWC Factor = 0.16 dB

Location: 0, 12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.95

802_11b 11Mbps 1ch Bitrate 40 Freq. Response

DUT: SM-A516V; Type: Bar

Communication System: UID 0, 2450MHz FCC (0); Frequency: 2437 MHz;Duty Cycle: 1:1

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³


Phantom section: TCoil Section

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) wideband at best S/N/ABM Freq Resp(x,y,z,f) (1x1x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_Normal_51s new.wav
 Output Gain: 59.83
 Measure Window Start: 300ms
 Measure Window Length: 51000ms
 BWC applied: 9.47 dB
 Device Reference Point: 0, 0, -6.3 mm

Category	Telephone parameters WD signal quality [(signal+noise)-to-noise ratio in decibels]
Category T1	0 dB to 10 dB
Category T2	10 dB to 20 dB
Category T3	20 dB to 30 dB
Category T4	> 30 dB

Cursor:
 Diff = 2.00 dB
 BWC Factor = 9.47 dB
 Location: -0.8, 12.1, 3.7 mm



Plot No.96
802_11b 11Mbps 1ch Bitrate 40 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, 2450MHz FCC (0); Frequency: 2437 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2020-02-26
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Signal(x,y,z) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms

Measure Window Length: 1000ms

BWC applied: 0.16 dB

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM1 comp = -15.73 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -12.5, 3.7 mm

Cursor:

ABM2 = -51.51 dBA/m

Location: -4.2, -12.5, 3.7 mm


Cursor:

ABM1/ABM2 = 35.78 dB

ABM1 comp = -15.73 dBA/m

BWC Factor = 0.16 dB

Location: -4.2, -12.5, 3.7 mm



0 dB = 1.000 A/m = 0.00 dBA/m

Plot No.97

NR Band2 DFTS-OFDM BPSK 20MHz 1RB 104offset 376000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3049; ; Calibrated: 2020-05-26
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn868; Calibrated: 2019-09-04
- Phantom: HAC Test Arch with AMCC TCOIL
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
Output Gain: 19.66
Measure Window Start: 300ms
Measure Window Length: 1000ms
Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -44.10 dBA/m
Location: 0, 8.3, 3.7 mm



Plot No.98

NR Band2 DFTS-OFDM BPSK 20MHz 1RB 104offset 376000 y(transversal)

UT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3049; ; Calibrated: 2020-05-26
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn868; Calibrated: 2019-09-04
- Phantom: HAC Test Arch with AMCC TCOIL
- Measurement SW: DASY52, Version 52.10 (4);

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -40.46 dBA/m
 Location: 0, 0, 3.7 mm



Plot No.99

NR Band5 DFTS-OFDM BPSK 20MHz 1RB 104offset 167300z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms


Measure Window Length: 1000ms

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -46.94 dBA/m

Location: 0, 8.3, 3.7 mm



Plot No.100

NR Band5 DFTS-OFDM BPSK 20MHz 1RB 104offset 167300 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -50.80 dBA/m
 Location: 0, 0, 3.7 mm



Plot No.101

NR Band66 DFTS-OFDM BPSK 20MHz 1RB 104offset 349000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -47.38 dBA/m
 Location: 0, 8.3, 3.7 mm



Plot No.102

NR Band66 DFTS-OFDM BPSK 20MHz 1RB 104offset 349000 y(transveral)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band66 (0); Frequency: 1745 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms


Measure Window Length: 1000ms

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -44.12 dBA/m

Location: 0, 0, 3.7 mm



Plot No.103

NR Band2 DFTS-OFDM BPSK 15MHz 1RB 104offset 376000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms


Measure Window Length: 1000ms

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -47.03 dBA/m

Location: 0, 8.3, 3.7 mm



Plot No.104

NR Band2 DFTS-OFDM BPSK 15MHz 1RB 104offset 376000 y(transveral)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transveral) 4.2mm 50

x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms


Measure Window Length: 1000ms

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -51.73 dBA/m

Location: 0, 0, 3.7 mm



Plot No.105

NR Band2 DFTS-OFDM BPSK 10MHz 1RB 104offset 376000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -46.76 dBA/m
 Location: 0, 8.3, 3.7 mm



Plot No.106

NR Band2 DFTS-OFDM BPSK 10MHz 1RB 104offset 376000 y(transveral)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transveral) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -42.01 dBA/m
 Location: 0, 0, 3.7 mm



Plot No.107

NR Band2 DFTS-OFDM BPSK 5MHz 1RB 104offset 376000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x

50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm

Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav

Output Gain: 19.66

Measure Window Start: 300ms


Measure Window Length: 1000ms

Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -52.68 dBA/m

Location: 0, 8.3, 3.7 mm



Plot No.108

NR Band2 DFTS-OFDM BPSK 5MHz 1RB 104offset 376000 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, NR Band2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section

DASY5 Configuration:


- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50

x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -54.42 dBA/m
 Location: 0, 0, 3.7 mm



Plot No.109

NR Band2 DFTS-OFDM BPSK 20MHz 1RB 104offset 372000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band2 (0); Frequency: 1860 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -44.62 dBA/m
 Location: 0, 8.3, 3.7 mm



Plot No.110

NR Band2 DFTS-OFDM BPSK 20MHz 1RB 104offset 372000 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band2 (0); Frequency: 1860 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -40.51 dBA/m
 Location: 0, 0, 3.7 mm



Plot No.111

NR Band2 DFTS-OFDM BPSK 20MHz 1RB 104offset 380000 z(axial)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band2 (0); Frequency: 1900 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/z (axial) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -46.62 dBA/m
 Location: 0, 8.3, 3.7 mm



Plot No.112

NR Band2 DFTS-OFDM BPSK 20MHz 1RB 104offset 380000 y(transversal)

DUT: SM-A516V; Type: Bar

Communication System: UID 0, LTE Band2 (0); Frequency: 1900 MHz;Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³
 Phantom section: TCoil Section


DASY5 Configuration:

- Probe: AM1DV3 - 3050; ; Calibrated: 11/20/2019
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn504; Calibrated: 2/26/2020
- Phantom: HAC Test Arch with AMCC
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

T-Coil scan (scan for ANSI C63.19-2007 & 2011 compliance)/General Scans/y (transversal) 4.2mm 50 x 50/ABM Noise Spectrum(x,y,z,f) (13x13x1): Measurement grid: dx=10mm, dy=10mm
 Signal Type: Audio File (.wav) 48k_voice_1kHz_1s.wav
 Output Gain: 19.66
 Measure Window Start: 300ms
 Measure Window Length: 1000ms
 Device Reference Point: 0, 0, -6.3 mm

Cursor:

ABM = -51.65 dBA/m
 Location: 0, 0, 3.7 mm



Attachment 2. HAC T-Coil Probe Certificates

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **HCT (Dymstec)**

Certificate No: **AM1DV3-3049_May20**

CALIBRATION CERTIFICATE

Object **AM1DV3 - SN: 3049**

Calibration procedure(s) **QA CAL-24.v4
Calibration procedure for AM1D magnetic field probes and TMFS in the
audio range**

Calibration date: **May 26, 2020**

결	담당자	화인자
재	<i>[Signature]</i>	<i>[Signature]</i>
직원/성명	SW 12월 9	HS 1 2020
일 차	2020 6.16	2020 6.16

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Kelthley Multimeter Type 2001	SN: 0810278	03-Sep-19 (No. 25949)	Sep-20
Reference Probe AM1DV2	SN: 1008	10-Dec-19 (No. AM1DV2-1008_Dec19)	Dec-20
DAE4	SN: 781	27-Dec-19 (No. DAE4-781_Dec19)	Dec-20
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
AMCC	SN: 1050	01-Oct-13 (in house check Oct-17)	Oct-20
AMMI Audio Measuring Instrument	SN: 1062	26-Sep-12 (in house check Oct-17)	Oct-20

Calibrated by:	Name Leif Klysner	Function Laboratory Technician	Signature <i>[Signature]</i>
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature <i>[Signature]</i>

Issued: May 27, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

References

- [1] ANSI-C63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] ANSI-C63.19-2011
American National Standard, Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [3] DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.

The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to "southwest" orientation.
- *Functional Test:* The functional test preceding calibration includes test of Noise level RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected. Frequency response verification from 100 Hz to 10 kHz.
- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.
- *Sensitivity:* With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

AM1D probe identification and configuration data

Item	AM1DV3 Audio Magnetic 1D Field Probe
Type No	SP AM1 001 BA
Serial No	3049

Overall length	296 mm
Tip diameter	6.0 mm (at the tip)
Sensor offset	3.0 mm (centre of sensor from tip)
Internal Amplifier	20 dB

Manufacturer / Origin	Schmid & Partner Engineering AG, Zurich, Switzerland
-----------------------	--

Calibration data

Connector rotation angle	(in DASY system)	279.8 °	+/- 3.6 ° (k=2)
Sensor angle	(in DASY system)	-0.49 °	+/- 0.5 ° (k=2)
Sensitivity at 1 kHz	(in DASY system)	0.00746 V/(A/m)	+/- 2.2 % (k=2)

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **HCT (Dymstec)**

Certificate No: **AM1DV3-3050_Nov19**

CALIBRATION CERTIFICATE															
Object	AM1DV3 - SN: 3050														
Calibration procedure(s)	QA CAL-24.v4 Calibration procedure for AM1D magnetic field probes and TMFS in the audio range														
Calibration date:	November 20, 2019	<table border="1"> <tr> <td>결재</td> <td>담당자</td> <td>확인자</td> </tr> <tr> <td></td> <td><i>Jung</i></td> <td><i>[Signature]</i></td> </tr> <tr> <td>직위/성명</td> <td>SA / 김민영</td> <td>CAJ / 김민영</td> </tr> <tr> <td>일 자</td> <td>2019 / 11 / 19</td> <td>2019 / 11 / 19</td> </tr> </table>		결재	담당자	확인자		<i>Jung</i>	<i>[Signature]</i>	직위/성명	SA / 김민영	CAJ / 김민영	일 자	2019 / 11 / 19	2019 / 11 / 19
결재	담당자	확인자													
	<i>Jung</i>	<i>[Signature]</i>													
직위/성명	SA / 김민영	CAJ / 김민영													
일 자	2019 / 11 / 19	2019 / 11 / 19													
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.															
All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.															
Calibration Equipment used (M&TE critical for calibration)															
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration												
Keithley Multimeter Type 2001	SN: 0810278	03-Sep-19 (No. 25949)	Sep-20												
Reference Probe AM1DV2	SN: 1008	20-Dec-18 (No. AM1DV2-1008_Dec18)	Dec-19												
DAE4	SN: 781	09-Jan-19 (No. DAE4-781_Jan19)	Jan-20												
Secondary Standards	ID #	Check Date (In house)	Scheduled Check												
AMCC	SN: 1050	01-Oct-13 (in house check Oct-17)	Oct-20												
AMMI Audio Measuring Instrument	SN: 1062	26-Sep-12 (in house check Oct-17)	Oct-20												
Calibrated by:	Name Leif Klyaner	Function Laboratory Technician	Signature <i>[Signature]</i>												
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature <i>[Signature]</i>												
			Issued: November 20, 2019												
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.															

[References

- [1] ANSI-C63.19-2007
American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [2] ANSI-C63.19-2011
American National Standard, Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids.
- [3] DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.

The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to "southwest" orientation.
- *Functional Test:* The functional test preceding calibration includes test of Noise level RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected. Frequency response verification from 100 Hz to 10 kHz.
- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and -120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.
- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and -120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.
- *Sensitivity:* With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

AM1D probe identification and configuration data

Item	AM1DV3 Audio Magnetic 1D Field Probe
Type No	SP AM1 001 BA
Serial No	3050

Overall length	296 mm
Tip diameter	6.0 mm (at the tip)
Sensor offset	3.0 mm (centre of sensor from tip)
Internal Amplifier	20 dB

Manufacturer / Origin	Schmid & Partner Engineering AG, Zurich, Switzerland
-----------------------	--

Calibration data

Connector rotation angle	(in DASY system)	214.5 °	+/- 3.6 ° (k=2)
Sensor angle	(in DASY system)	0.20 °	+/- 0.5 ° (k=2)
Sensitivity at 1 kHz	(in DASY system)	0.00752 V/(A/m)	+/- 2.2 % (k=2)

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.