



**PART 22 MEASUREMENT REPORT**

**Applicant Name:**  
 Samsung Electronics Co., Ltd.  
 129, Samsung-ro,  
 Yeongtong-gu, Suwon-si  
 Gyeonggi-do, 16677, Korea


**Date of Testing:**  
 2/11/2021 - 2/24/2021  
**Test Site/Location:**  
 PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
 1M2102110010-02.A3L

<b>FCC ID:</b>	<b>A3LSMA526JPN</b>
<b>Applicant Name:</b>	<b>Samsung Electronics Co., Ltd.</b>

**Application Type:** Certification  
**Model:** SC-53B  
**EUT Type:** Portable Handset  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part:** 22  
**Test Procedure(s):** ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
 Randy Ortanez  
 President




<b>FCC ID:</b> A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 	<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset
		Page 1 of 62


## TABLE OF CONTENTS

1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities.....	5
2.3	Test Configuration .....	5
2.4	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Cellular - Base Frequency Blocks .....	6
3.3	Cellular - Mobile Frequency Blocks .....	6
3.4	Radiated Power and Radiated Spurious Emissions .....	7
4.0	MEASUREMENT UNCERTAINTY .....	8
5.0	TEST EQUIPMENT CALIBRATION DATA .....	9
6.0	SAMPLE CALCULATIONS .....	10
7.0	TEST RESULTS .....	12
7.1	Summary .....	12
7.2	Occupied Bandwidth .....	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	22
7.4	Band Edge Emissions at Antenna Terminal .....	38
7.5	Radiated Power (ERP) .....	46
7.6	Radiated Spurious Emissions Measurements .....	49
7.7	Frequency Stability / Temperature Variation .....	58
8.0	CONCLUSION.....	62

<b>FCC ID:</b> A3LSMA526JPN		<b>PART 22 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset		Page 2 of 62



## PART 22 MEASUREMENT REPORT



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	ERP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	
LTE Band 5	10 MHz	QPSK	829.0 - 844.0	0.063	18.03	9M04G7D
		16QAM	829.0 - 844.0	0.052	17.16	9M04W7D
		64QAM	829.0 - 844.0	0.040	15.98	9M01W7D
	5 MHz	QPSK	826.5 - 846.5	0.063	17.99	4M52G7D
		16QAM	826.5 - 846.5	0.050	17.02	4M52W7D
		64QAM	826.5 - 846.5	0.040	16.01	4M53W7D
	3 MHz	QPSK	825.5 - 847.5	0.064	18.08	2M71G7D
		16QAM	825.5 - 847.5	0.054	17.36	2M71W7D
		64QAM	825.5 - 847.5	0.043	16.30	2M71W7D
	1.4 MHz	QPSK	824.7 - 848.3	0.066	18.18	1M09G7D
		16QAM	824.7 - 848.3	0.056	17.45	1M11W7D
		64QAM	824.7 - 848.3	0.041	16.16	1M09W7D

Mode	Modulation	Tx Frequency Range [MHz]	ERP		Emission Designator
			Max. Power [W]	Max. Power [dBm]	
GSM/GPRS	GMSK	824.2 - 848.8	0.312	24.95	244KGXW
EDGE	8-PSK	824.2 - 848.8	0.076	18.83	240KG7W
WCDMA	Spread Spectrum	826.4 - 846.6	0.094	19.73	4M19F9W

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 3 of 62

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 4 of 62

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA526JPN**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 22.

**Test Device Serial No.:** 01192, 01069, 01127, 01200

### 2.2 Device Capabilities

This device contains the following capabilities:

GSM/GPRS/EDGE, WCDMA/HSPA, Multi-band LTE, WLAN, UNII, Bluetooth (1x, EDR, LE), NFC

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 3.4 of this test report for a description of the radiated and antenna port conducted emissions tests.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

<b>FCC ID:</b> A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 5 of 62


## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

### 3.2 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A\* Low + A)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A\* High)

BLOCK 4: 891.5 – 894 MHz (B\*)

### 3.3 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A\* Low + A)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A\* High)

BLOCK 4: 846.5 – 849 MHz (B\*)

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 6 of 62

### 3.4 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI/TIA-603-E-2016. A half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [dBm] = P_g [dBm] - \text{cable loss} [dB] + \text{antenna gain} [dBd/dBi];$$

where  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g [dBm] - \text{cable loss} [dB]$ .

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[dB\mu V/m]} = \text{Measured amplitude level}_{[dBm]} + 107 + \text{Cable Loss}_{[dB]} + \text{Antenna Factor}_{[dB/m]}$$

And

$$\text{EIRP}_{[dBm]} = E_{[dB\mu V/m]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 7 of 62

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 8 of 62

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	AP2	EMC Cable and Switch System	9/9/2020	Annual	9/9/2021	AP2
-	AP1	EMC Cable and Switch System	9/10/2020	Annual	9/10/2021	AP1
-	LTx1	Licensed Transmitter Cable Set	5/1/2020	Annual	5/1/2021	LTx1
-	LTx4	Licensed Transmitter Cable Set	9/16/2020	Annual	9/16/2021	LTx4
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	8/17/2021	MY52350166
Agilent	E5515C	Wireless Communications Test Set	N/A			GB46310798
Anritsu	MT8821C	Radio Communication Analyzer	N/A			6201381794
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2019	Biennial	10/10/2021	121034
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/12/2020	Biennial	3/12/2022	128337
Keysight Technologies	N9020A	MXA Signal Analyzer	9/22/2020	Annual	9/22/2021	MY54500644
Keysight Technologies	N9030B	PXA Signal Analyzer, Multi-touch	9/17/2020	Annual	9/17/2021	MY57141001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			112347
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/9/2020	Annual	9/9/2021	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/10/2020	Annual	8/10/2021	103200
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/21/2020	Annual	2/21/2021	102133
Sunol	DRH-118	Horn Antenna (1-18GHz)	10/3/2019	Biennial	10/3/2021	A050307
Sunol	DRH-118	Horn Antenna (1-18 GHz)	8/27/2019	Biennial	8/27/2021	A042511
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107

**Table 5-1. Test Equipment**

**Notes:**

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 9 of 62

## 6.0 SAMPLE CALCULATIONS

### GSM Emission Designator

#### **Emission Designator = 250KGXW**

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### EDGE Emission Designator

#### **Emission Designator = 250KG7W**

EDGE BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

### WCDMA Emission Designator

#### **Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

### QPSK Modulation

#### **Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### QAM Modulation

#### **Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 10 of 62

## Spurious Radiated Emission

### Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is  $8.1$  dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is  $2.0$  dB at  $3700.40$  MHz. So  $6.1$  dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was  $25.50$  dBm so this harmonic was  $25.50$  dBm  $- (-24.80) = 50.3$  dBc.

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 11 of 62

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LSMA526JPN  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): GSM/GPRS/WCDMA/LTE

Test Condition	Test Description	FCC Part Section(s)	RSS Section(s)	Test Limit	Test Result	Reference
<b>CONDUCTED</b>	Transmitter Conducted Output Power	2.1046	RSS-132(5.4)	N/A	<b>PASS</b>	See RF Exposure Report
	Occupied Bandwidth	2.1049	RSS-Gen(6.7)	N/A	<b>PASS</b>	Section 7.2
	Conducted Band Edge / Spurious Emissions	2.1051, 22.917(a)	RSS-132(5.5)	> 43 + 10log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions	<b>PASS</b>	Sections 7.3, 7.4
	Frequency Stability	2.1055, 22.355	RSS-132(5.3)	Fundamental emissions stay within authorized frequency block	<b>PASS</b>	Section 7.8
<b>RADIATED</b>	Effective Radiated Power / Equivalent Isotropic Radiated Power	22.913(a)(5)	RSS-132(5.4)	< 7 Watts max. ERP	<b>PASS</b>	Section 7.6
	Radiated Spurious Emissions	2.1053, 22.917(a)	RSS-132(5.5)	> 43 + 10 log <sub>10</sub> (P[Watts]) for all out-of-band emissions	<b>PASS</b>	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST 2G/3G Automation Version 4.5, LTE Automation Version 5.3.

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 12 of 62

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


KDB 971168 D01 v03r01 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 13 of 62

# LTE Band 5



Plot 7-1. Occupied Bandwidth Plot (LTE Band 5 - 10MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 5 - 10MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA526JPN		PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 14 of 62




Plot 7-3. Occupied Bandwidth Plot (LTE Band 5 - 10MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 5 - 5MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	<b>PART 22 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 15 of 62




Plot 7-5. Occupied Bandwidth Plot (LTE Band 5 - 5MHz 16-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 5 - 5MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	<b>PART 22 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 16 of 62




Plot 7-7. Occupied Bandwidth Plot (LTE Band 5 - 3MHz QPSK - Full RB Configuration)



Plot 7-8. Occupied Bandwidth Plot (LTE Band 5 - 3MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	<b>PART 22 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 17 of 62




**Plot 7-9. Occupied Bandwidth Plot (LTE Band 5 - 3MHz 64-QAM - Full RB Configuration)**



**Plot 7-10. Occupied Bandwidth Plot (LTE Band 5 - 1.4MHz QPSK - Full RB Configuration)**

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 18 of 62




Plot 7-11. Occupied Bandwidth Plot (LTE Band 5 - 1.4MHz 16-QAM - Full RB Configuration)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 5 - 1.4MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> Proud to be part of	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 19 of 62

## GPRS Cell



Plot 7-13. Occupied Bandwidth Plot (GPRS, Ch. 190)



Plot 7-14. Occupied Bandwidth Plot (EDGE, Ch. 190)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	<b>PART 22 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 20 of 62

# WCDMA Cell



Plot 7-15. Occupied Bandwidth Plot (WCDMA, Ch. 4183)

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 21 of 62

## 7.3 Spurious and Harmonic Emissions at Antenna Terminal

### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + 10 \log_{10}(P_{[Watts]})$ , where P is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 D01 v03r01 – Section 6.0

### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**

### Test Notes


Per Part 22 and RSS-132, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100 kHz or greater for measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 22 of 62

### LTE Band 5



Plot 7-16. Conducted Spurious Plot (LTE Band 5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)



Plot 7-17. Conducted Spurious Plot (LTE Band 5 - 10MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 23 of 62





















## WCDMA Cell




Plot 7-34. Conducted Spurious Plot (WCDMA Ch. 4132)




Plot 7-35. Conducted Spurious Plot (WCDMA Ch. 4132)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 33 of 62




Plot 7-36. Conducted Spurious Plot (WCDMA Ch. 4132)



Plot 7-37. Conducted Spurious Plot (WCDMA Ch. 4183)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 34 of 62




Plot 7-38. Conducted Spurious Plot (WCDMA Ch. 4183)




Plot 7-39. Conducted Spurious Plot (WCDMA Ch. 4183)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 35 of 62




Plot 7-40. Conducted Spurious Plot (WCDMA Ch. 4233)



Plot 7-41. Conducted Spurious Plot (WCDMA Ch. 4233)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 36 of 62



Plot 7 42. Conducted Spurious Plot (WCDMA Ch. 4233)

FCC ID: A3LSMA526JPN	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 37 of 62

## 7.4 Band Edge Emissions at Antenna Terminal

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

***The minimum permissible attenuation level of any spurious emission is  $43 + 10 \log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.***

### Test Procedure Used


KDB 971168 D01 v03r01 – Section 6.0

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3.  $RBW \geq 1\%$  of the emission bandwidth
4.  $VBW \geq 3 \times RBW$
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span}/RBW$
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-3. Test Instrument & Measurement Setup**

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 38 of 62


## Test Notes

Per 22.917(b) and RSS-132(5.5), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.


<b>FCC ID:</b> A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 39 of 62







Plot 7-46. Lower Band Edge Plot (LTE Band 5 - 3MHz QPSK – Full RB Configuration)



Plot 7-47. Upper Band Edge Plot (LTE Band 5 - 3MHz QPSK – Full RB Configuration)

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	PART 22 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 42 of 62





# WCDMA Cell



Plot 7-52. Lower Band Edge Plot (WCDMA Cell – Ch. 4132)



Plot 7-53. Upper Band Edge Plot (WCDMA Cell – Ch. 4233)

FCC ID: A3LSMA526JPN		PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 45 of 62

## 7.5 Radiated Power (ERP)

### Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto". Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 46 of 62

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Radiated Test Setup <1GHz**

**Test Notes**

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest powers is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1".
- 3) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 4) This unit was tested with its standard battery.
- 5) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: A3LSMA526JPN	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 47 of 62

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
10 MHz	QPSK	829.0	V	145.0	223.0	6.40	1 / 49	13.37	17.62	0.058	38.45	-20.83	19.77	0.095	40.61	-20.84
		836.5	V	131.0	225.0	6.38	1 / 25	13.68	17.91	0.062	38.45	-20.54	20.06	0.101	40.61	-20.55
		844.0	V	142.0	228.0	6.46	1 / 0	13.72	<b>18.03</b>	0.063	38.45	-20.42	<b>20.18</b>	0.104	40.61	-20.43
	16-QAM	844.0	V	142.0	228.0	6.46	1 / 25	12.85	17.16	0.052	38.45	-21.29	19.31	0.085	40.61	-21.30
	64-QAM	844.0	V	142.0	228.0	6.46	1 / 25	11.67	15.98	0.040	38.45	-22.47	18.13	0.065	40.61	-22.48
5 MHz	QPSK	829.0	V	145.0	223.0	6.40	1/12	13.33	17.58	0.057	38.45	-20.87	19.73	0.094	40.61	-20.88
		836.5	V	131.0	225.0	6.38	1/12	13.66	17.89	0.061	38.45	-20.56	20.04	0.101	40.61	-20.57
		844.0	V	142.0	228.0	6.46	1/24	13.68	<b>17.99</b>	0.063	38.45	-20.46	<b>20.14</b>	0.103	40.61	-20.47
	16-QAM	829.0	V	145.0	223.0	6.40	1/0	12.77	17.02	0.050	38.45	-21.43	19.17	0.083	40.61	-21.44
	64-QAM	829.0	V	145.0	223.0	6.40	1/12	11.76	16.01	0.040	38.45	-22.44	18.16	0.065	40.61	-22.45
3 MHz	QPSK	829.0	V	145.0	223.0	6.40	1/14	13.42	17.67	0.058	38.45	-20.78	19.82	0.096	40.61	-20.79
		836.5	V	131.0	225.0	6.38	1/14	13.57	17.80	0.060	38.45	-20.65	19.95	0.099	40.61	-20.66
		844.0	V	142.0	228.0	6.46	1/14	13.77	<b>18.08</b>	0.064	38.45	-20.37	<b>20.23</b>	0.105	40.61	-20.38
	16-QAM	829.0	V	145.0	223.0	6.40	1/14	13.11	17.36	0.054	38.45	-21.09	19.51	0.089	40.61	-21.10
	64-QAM	844.0	V	142.0	228.0	6.46	1/14	11.99	16.30	0.043	38.45	-22.15	18.45	0.070	40.61	-22.16
1.4 MHz	QPSK	829.0	V	145.0	223.0	6.40	1/2	13.36	17.61	0.058	38.45	-20.84	19.76	0.095	40.61	-20.85
		836.5	V	131.0	225.0	6.38	1/2	13.54	17.77	0.060	38.45	-20.68	19.92	0.098	40.61	-20.69
		844.0	V	142.0	228.0	6.46	1/2	13.87	<b>18.18</b>	0.066	38.45	-20.27	<b>20.33</b>	0.108	40.61	-20.28
	16-QAM	829.0	V	145.0	223.0	6.40	1/2	13.20	17.45	0.056	38.45	-21.00	19.60	0.091	40.61	-21.01
	64-QAM	844.0	V	142.0	228.0	6.46	1/2	11.85	16.16	0.041	38.45	-22.29	18.31	0.068	40.61	-22.30
10 MHz	Opposite Pol.	844.0	H	207.0	284.0	6.66	1 / 0	10.90	17.56	0.057	38.45	-20.89	19.71	0.093	40.61	-20.90

Table 7-2. ERP Data (LTE Band 5)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.20	GPRS850	V	149	179	19.62	6.35	23.82	0.241	38.45	-14.63
836.60	GPRS850	V	147	186	20.10	6.38	24.33	0.271	38.45	-14.12
848.80	GPRS850	V	155	194	20.59	6.51	<b>24.95</b>	<b>0.312</b>	38.45	-13.51
848.80	GPRS850	H	100	305	19.43	6.71	23.99	0.250	38.45	-14.47
848.80	EDGE850	V	155	194	14.47	6.51	<b>18.83</b>	0.076	38.45	-19.62

Table 7-3. ERP Data (GPRS Cell)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
826.40	WCDMA850	V	143	192	15.03	6.37	19.25	0.084	38.45	-19.20
836.60	WCDMA850	V	133	226	15.20	6.38	19.43	0.088	38.45	-19.02
846.60	WCDMA850	V	143	227	15.40	6.48	<b>19.73</b>	<b>0.094</b>	38.45	-18.72
846.60	WCDMA850	H	107	303	12.92	6.48	17.25	0.053	38.45	-21.20

Table 7-4. ERP Data (WCDMA Cell)

FCC ID: A3LSMA526JPN		PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 48 of 62

## 7.6 Radiated Spurious Emissions Measurements

### Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in KDB 971168 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize


FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 49 of 62

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Test Instrument & Measurement Setup < 1GHz**



**Figure 7-6. Test Instrument & Measurement Setup >1 GHz**


FCC ID: A3LSMA526JPN	PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 50 of 62

## Test Notes

- 1) Field strengths are calculated using the Measurement quantity conversions in KDB 971168 Section 5.8.4.
  - a)  $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
  - b)  $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$ ; where D is the measurement distance in meters.
- 2) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest powers is reported in GPRS mode while transmitting with one slot active.
- 3) This device employs UMTS technology with WCDMA (AMR/RMC) and HSDPA capabilities. The EUT was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1".
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 5) This unit was tested with its standard battery.
- 6) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 7) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 8) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 9) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 51 of 62

# LTE Band 5



**Plot 7-54. Radiated Spurious Plot (LTE Band 5)**

Bandwidth (MHz):	10
Frequency (MHz):	829.0
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1658.0	H	-	-	-77.44	-0.53	29.03	-66.23	-13.00	-53.23
2487.0	H	215	8	-76.88	3.45	33.57	-61.69	-13.00	-48.69
3316.0	H	104	34	-75.43	4.77	36.34	-58.92	-13.00	-45.92
4145.0	H	-	-	-78.42	6.17	34.75	-60.51	-13.00	-47.51
4974.0	H	-	-	-78.98	7.16	35.18	-60.08	-13.00	-47.08

**Table 7-5. Radiated Spurious Data (LTE Band 5 – Low Channel)**

Bandwidth (MHz):	10
Frequency (MHz):	836.5
RB / Offset:	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.0	H	-	-	-77.33	-0.56	29.11	-66.15	-13.00	-53.15
2509.5	H	155	312	-69.49	3.53	41.04	-54.21	-13.00	-41.21
3346.0	H	125	38	-75.90	5.20	36.30	-58.96	-13.00	-45.96
4182.5	H	-	-	-78.33	6.15	34.82	-60.44	-13.00	-47.44
5019.0	H	-	-	-78.82	6.52	34.70	-60.56	-13.00	-47.56

**Table 7-6. Radiated Spurious Data (LTE Band 5 – Mid Channel)**

FCC ID: A3LSMA526JPN		<b>PART 22 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 52 of 62


<b>Bandwidth (MHz):</b>	10
<b>Frequency (MHz):</b>	844.0
<b>RB / Offset:</b>	1 / 25

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1688.00	H	-	-	-77.43	-0.71	28.86	-66.40	-13.00	-53.40
2532.00	H	150	305	-77.30	3.43	33.13	-62.12	-13.00	-49.12
3376.00	H	112	46	-75.36	5.19	36.83	-58.42	-13.00	-45.42
4220.00	H	-	-	-78.06	5.69	34.63	-60.63	-13.00	-47.63
5064.00	H	-	-	-78.95	7.04	35.09	-60.17	-13.00	-47.17

**Table 7-7. Radiated Spurious Data (LTE Band 5 – High Channel)**

<b>FCC ID:</b> A3LSMA526JPN	 <b>PCTEST</b> <small>Proved to be part of</small>	<b>PART 22 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset		Page 53 of 62

# GSM/GPRS Cell



**Plot 7-55. Radiated Spurious Plot (GPRS Cell)**

<b>Mode:</b>	GPRS 1 Tx Slot
<b>Channel:</b>	128
<b>Frequency (MHz):</b>	824.2

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1648.4	H	-	-	-68.10	0.55	39.45	-55.80	-13.00	-42.80
2472.6	H	151	319	-66.01	5.17	46.16	-49.10	-13.00	-36.10
3296.8	H	-	-	-69.62	7.01	44.39	-50.87	-13.00	-37.87
4121.0	H	-	-	-70.04	8.07	45.03	-50.23	-13.00	-37.23
4945.2	H	-	-	-69.02	9.88	47.86	-47.39	-13.00	-34.39

**Table 7-8. Radiated Spurious Data (GPRS Cell – Low Channel)**

<b>Mode:</b>	GPRS 1 Tx Slot
<b>Channel:</b>	190
<b>Frequency (MHz):</b>	836.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.2	H	102	321	-68.83	1.02	39.19	-56.06	-13.00	-43.06
2509.8	H	116	317	-62.26	5.18	49.92	-45.34	-13.00	-32.34
3346.4	H	-	-	-69.88	6.76	43.88	-51.38	-13.00	-38.38
4183.0	H	-	-	-70.53	8.61	45.08	-50.18	-13.00	-37.18
5019.6	H	-	-	-69.14	10.78	48.64	-46.62	-13.00	-33.62

**Table 7-9. Radiated Spurious Data (GPRS Cell – Mid Channel)**

<b>FCC ID:</b> A3LSMA526JPN		<b>PART 22 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 54 of 62	


<b>Mode:</b>	GPRS 1 Tx Slot
<b>Channel:</b>	251
<b>Frequency (MHz):</b>	848.8

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1697.6	H	-	-	-70.41	1.46	38.05	-57.21	-13.00	-44.21
2546.4	H	107	319	-61.46	5.44	50.98	-44.27	-13.00	-31.27
3395.2	H	-	-	-70.68	7.36	43.68	-51.58	-13.00	-38.58
4244.0	H	-	-	-70.28	8.12	44.84	-50.42	-13.00	-37.42
5092.8	H	-	-	-69.21	10.31	48.10	-47.16	-13.00	-34.16

**Table 7-10. Radiated Spurious Data (GPRS Cell – High Channel)**

<b>FCC ID:</b> A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 	<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset
		Page 55 of 62

# WCDMA Cell



**Plot 7-56. Radiated Spurious Plot (WCDMA Cell)**

<b>Mode:</b>	WCDMA RMC
<b>Channel:</b>	4132
<b>Frequency (MHz):</b>	826.4

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1652.8	H	-	-	-70.09	0.64	37.55	-57.71	-13.00	-44.71
2479.2	H	100	358	-59.40	5.17	52.77	-42.49	-13.00	-29.49
3305.6	H	-	-	-71.78	6.91	42.13	-53.13	-13.00	-40.13
4132.0	H	-	-	-72.62	8.19	42.57	-52.69	-13.00	-39.69
4958.4	H	-	-	-73.73	10.17	43.44	-51.81	-13.00	-38.81

**Table 7-11. Radiated Spurious Data (WCDMA Cell – Low Channel)**

<b>Mode:</b>	WCDMA RMC
<b>Channel:</b>	4183
<b>Frequency (MHz):</b>	836.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1673.2	H	-	-	-70.42	1.02	37.60	-57.65	-13.00	-44.65
2509.8	H	-	-	-69.62	5.18	42.56	-52.70	-13.00	-39.70
3346.4	H	-	-	-72.37	6.76	41.39	-53.87	-13.00	-40.87

**Table 7-12. Radiated Spurious Data (WCDMA Cell – Mid Channel)**

<b>FCC ID:</b> A3LSMA526JPN		<b>PART 22 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 56 of 62	

<b>Mode:</b>	WCDMA RMC
<b>Channel:</b>	4233
<b>Frequency (MHz):</b>	846.6

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1693.2	H	-	-	-70.37	1.36	37.99	-57.27	-13.00	-44.27
2539.8	H	101	226	-44.76	5.51	67.75	-27.51	-13.00	-14.51
3386.4	H	-	-	-72.52	7.25	41.73	-53.52	-13.00	-40.52
4233.0	H	-	-	-72.43	8.17	42.74	-52.52	-13.00	-39.52
5079.6	H	-	-	-72.82	9.93	44.11	-51.15	-13.00	-38.15

**Table 7-13. Radiated Spurious Data (WCDMA Cell –High Channel)**

<b>FCC ID:</b> A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 57 of 62

## 7.7 Frequency Stability / Temperature Variation

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 22 and RSS-132, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency.***

### Test Procedure Used

ANSI/TIA-603-E-2016

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.


### Test Notes

None

FCC ID: A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset	Page 58 of 62

LTE Band 5					
Operating Frequency (Hz):		836,500,000			
Ref. Voltage (VDC):		4.38			
Deviation Limit:		± 0.00025% or 2.5 ppm			
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.38	- 30	836,500,054	54	0.0000065
		- 20	836,500,085	85	0.0000102
		- 10	836,499,870	-130	-0.0000155
		0	836,500,147	147	0.0000176
		+ 10	836,499,886	-114	-0.0000136
		+ 20 (Ref)	836,499,978	0	0.0000000
		+ 30	836,499,801	-199	-0.0000238
		+ 40	836,500,226	226	0.0000270
Battery Endpoint	3.41	+ 20	836,499,966	-34	-0.0000041

Table 7-14. LTE Band 5 Frequency Stability Data




Plot 7-57. LTE Band 5 Frequency Stability Chart

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 59 of 62

GSM/GPRS Cellular					
Operating Frequency (Hz):		836,600,000			
Ref. Voltage (VDC):		4.38			
Deviation Limit:		± 0.00025% or 2.5 ppm			
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.38	- 30	836,600,080	80	0.0000096
		- 20	836,600,282	282	0.0000337
		- 10	836,600,207	207	0.0000247
		0	836,600,169	169	0.0000202
		+ 10	836,600,242	242	0.0000289
		+ 20 (Ref)	836,600,063	0	0.0000000
		+ 30	836,599,778	-222	-0.0000265
		+ 40	836,599,840	-160	-0.0000191
Battery Endpoint	3.41	+ 20	836,600,227	227	0.0000271

Table 7-15. GSM/GPRS Cell Frequency Stability Data




Plot 7-58. GSM/GPRS Cell Frequency Stability Chart

FCC ID: A3LSMA526JPN	 PART 22 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset	Page 60 of 62

<b>WCDMA Cellular</b>					
Operating Frequency (Hz):		836,600,000			
Ref. Voltage (VDC):		4.38			
Deviation Limit:		± 0.00025% or 2.5 ppm			
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.38	- 30	836,599,888	-112	-0.0000134
		- 20	836,599,952	-48	-0.0000057
		- 10	836,599,966	-34	-0.0000041
		0	836,599,943	-57	-0.0000068
		+ 10	836,600,127	127	0.0000152
		+ 20 (Ref)	836,600,172	0	0.0000000
		+ 30	836,600,069	69	0.0000082
		+ 40	836,600,020	20	0.0000024
Battery Endpoint	3.41	+ 20	836,600,223	223	0.0000267

**Table 7-16. WCDMA Cell Frequency Stability Data**



**Plot 7-59. WCDMA Cell Frequency Stability Chart**

FCC ID: A3LSMA526JPN	<b>PCTEST</b> <small>Proved to be part of</small>	<b>PART 22 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2102110010-02.A3L	Test Dates: 2/11/2021 - 2/24/2021	EUT Type: Portable Handset		Page 61 of 62

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the Samsung **Portable Handset** **FCC ID: A3LSMA526JPN** complies with all the requirements of Part 22 of the FCC rules.

<b>FCC ID:</b> A3LSMA526JPN	 <b>PART 22 MEASUREMENT REPORT</b> 	<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2102110010-02.A3L	<b>Test Dates:</b> 2/11/2021 - 2/24/2021	<b>EUT Type:</b> Portable Handset
Page 62 of 62		