




# TEST REPORT

<b>KCTL Inc.</b> 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a>	Report No.: KR22-SRF0035-A Page (1) of (69)	   <b>KCTL</b>
---	---	---

## 1. Client

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2022-02-03

2. Use of Report : Certification

3. Name of Product / Model : Mobile phone / SC-53C, SCG15

4. Manufacturer / Country of Origin : Samsung Electronics Co., Ltd. / Vietnam



5. FCC ID : A3LSMA536JPN

6. Date of Test : 2022-02-17 to 2022-03-23

7. Location of Test :  Permanent Testing Lab  On Site Testing  
 (Address:65,Sinwon-roYeongtong-gu,Suwon-si,Gyeonggi-do,16677, Korea)

8. Test method used : FCC Part 15 Subpart C, 15.247

9. Test Result : Refer to the test result in the test report

Affirmation	Tested by  Name : Kwonse Kim (Signature) 	Technical Manager  Name : Seungyong Kim (Signature) 
-------------	--	---

2022-03-24

## KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

**REPORT REVISION HISTORY**

Date	Revision	Page No
2022-03-21	Originally issued	-
2022-03-24	Retest the 6dB BW and PSD	17~20, 22~25

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

Note. The report No. KR22-SRF0035 is superseded by the report No. KR22-SRF0035-A.

**General remarks for test reports**

**Statement concerning the uncertainty of the measurement systems used for the tests**

(may be required by the product standard or client)

Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

**Procedure number, issue date and title:**

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

Statement not required by the standard or client used for type testing

## CONTENTS

1.	General information .....	4
2.	Device information .....	4
2.1.	Frequency/channel operations.....	5
2.2.	Duty Cycle Factor .....	7
3.	Antenna requirement .....	8
4.	Summary of tests .....	9
5.	Measurement uncertainty .....	10
6.	Measurement results explanation example .....	11
7.	Test results .....	12
7.1.	Maximum peak output power .....	12
7.2.	Peak Power Spectral Density .....	16
7.3.	6 dB Bandwidth(DTS Channel Bandwidth) .....	21
7.4.	Spurious Emission, Band Edge and Restricted bands.....	26
7.5.	Conducted Spurious Emission.....	60
7.6.	AC Conducted emission .....	67
8.	Measurement equipment .....	69

## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (4) of (69)



KCTL

### 1. General information

Client : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,  
Rep. of Korea  
Manufacturer : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,  
Rep. of Korea  
Factory : Samsung Electronics Vietnam Thai Nguyen Co., Ltd.  
Address : Yen Binh Industrial Park, Dong Tien Ward, Pho Yen Town, Thai Nguyen  
Province, Vietnam  
Laboratory : KCTL Inc.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
CAB Identifier: KR0040  
ISED Number: 8035A  
KOLAS No.: KT231

### 2. Device information

Equipment under test : Mobile phone  
Model : SC-53C, SCG15  
Modulation technique : Bluetooth(BDR/EDR)\_GFSK,  $\pi/4$ DQPSK, 8DPSK  
Bluetooth(BLE)\_GFSK  
WIFI(802.11a/b/g/n/ac)\_DSSS, OFDM  
LTE\_QPSK, 16QAM, 64QAM  
WCDMA\_QPSK  
GSM\_GMSK, 8-PSK  
NFC\_ASK  
Number of channels : Bluetooth(BDR/EDR)\_79 ch / Bluetooth(BLE)\_40 ch  
802.11b/g/n\_HT20 : 13 ch  
UNII-1: 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
UNII-2A: 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
UNII-2C: 12 ch (20 MHz), 6 ch (40 MHz), 3 ch (80 MHz)  
UNII-3: 5 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
NFC: 1 ch  
Power source : DC 3.88 V  
Antenna specification : LTE/WCDMA/GSM\_Metal Antenna  
WIFI(2.4G)/Bluetooth(BDR/EDR/BLE)\_Metal Antenna  
WIFI(5G)/NFC\_LDS Antenna

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (5) of (69)



KCTL

Antenna gain : WIFI/Bluetooth(BDR/EDR/BLE)\_-7.11 dBi  
UNII-1 : -9.23 dBi  
UNII-2A : -9.29 dBi  
UNII-2C : -9.01 dBi  
UNII-3 : -9.12 dBi

Frequency range : Bluetooth(BDR/EDR/BLE)\_2 402 MHz ~ 2 480 MHz  
2 412 MHz ~ 2 472 MHz (802.11b/g/n\_HT20)  
UNII-1: 5 180 MHz ~ 5 240 MHz (802.11a/n/ac\_HT20/VHT20)  
UNII-1: 5 190 MHz ~ 5 230 MHz (802.11n/ac\_HT40/VHT40)  
UNII-1: 5 210 MHz (802.11ac\_VHT80)  
UNII-2A: 5 260 MHz ~ 5 320 MHz (802.11a/n/ac\_HT20/VHT20)  
UNII-2A: 5 270 MHz ~ 5 310 MHz (802.11n/ac\_HT40/VHT40)  
UNII-2A: 5 290 MHz (802.11ac\_VHT80)  
UNII-2C: 5 500 MHz ~ 5 720 MHz (802.11a/n/ac\_HT20/VHT20)  
UNII-2C: 5 510 MHz ~ 5 710 MHz (802.11n/ac\_HT40/VHT40)  
UNII-2C: 5 530 MHz ~ 5 690 MHz (802.11ac\_VHT80)  
UNII-3: 5 745 MHz ~ 5 825 MHz (802.11a/n/ac\_HT20/VHT20)  
UNII-3: 5 755 MHz ~ 5 795 MHz (802.11n/ac\_HT40/VHT40)  
UNII-3: 5 775 MHz (802.11ac\_VHT80)  
LTE Band 5\_824.7 MHz ~ 848.3 MHz  
LTE Band 12\_699.7 MHz ~ 715.3 MHz  
LTE Band 41\_2 498.5 MHz ~ 2 687.5 MHz  
GSM 850\_824.2 MHz ~ 848.8 MHz  
GSM 1900\_1 850.2 MHz ~ 1 909.8 MHz  
WCDMA 850\_826.4 MHz ~ 846.6 MHz  
NFC\_13.56 MHz

Software version : SC-53C(A536D.001) / SCG15(A536J.001)  
Hardware version : REV1.0  
Test device serial No. : Conducted(5bd4ab7193207ece)  
Radiated(R3CRC0HRF7K)

Operation temperature : -30 °C ~ 50 °C

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (6) of (69)

**2.1. Frequency/channel operations**

This device contains the following capabilities:

WiFi (802.11a/b/g/n/ac), Bluetooth (BDR/EDR/BLE), NFC, LTE Band 5, LTE Band 12, LTE Band 41  
GSM 850, GSM 1900, WCDMA 850

Ch.	Frequency (MHz)
01	2 412
.	.
06	2 437
.	.
11	2 462
12	2 467
13	2 472

Table 2.1.1. 802.11b/g/n\_HT20 mode

# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (7) of (69)




## 2.2. Duty Cycle Factor

Test mode	Period (ms)	On time (ms)	Duty cycle		Duty Cycle Factor (dB)
			(Linear)	(%)	
802.11b	8.678 0	8.608 5	0.992 0	99.20	0.03
802.11g	1.542 1	1.425 2	0.924 2	92.42	0.34
802.11n_HT20	1.450 8	1.333 2	0.918 9	91.89	0.37

### Notes.

1. Duty cycle (Linear) = Ton time / Period
2. DCF(Duty cycle factor) =  $10\log(1/\text{duty cycle})$
3. DCF is not compensated to Average result if duty cycle is more than 98%



## KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (8) of (69)



### 3. Antenna requirement

Requirement of FCC part section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- The transmitter has permanently attached Metal Antenna (Internal antenna) on board.





#### 4. Summary of tests

FCC Part section(s)	Parameter	Test Condition	Test results
15.247(b)(3)	Maximum peak output power	Conducted	Pass
15.247(e)	Peak power spectral density		Pass
15.247(a)(2)	6 dB channel bandwidth		Pass
15.207(a)	AC Conducted Emissions		Pass
15.247(d)	Conducted Spurious Emissions		Pass
15.205(a), 15.209(a)	Spurious emission	Radiated	Pass
	Band-edge, restricted band		Pass

**Notes:**

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
3. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **X** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **X** orientation.
4. All the radiated tests have been performed several case.  
(Stand-alone, with accessories (TA etc.))  
Worst case: Stand-alone
5. The test procedure(s) in this report were performed in accordance as following.
  - ◆ ANSI C63.10-2013
  - ◆ KDB 558074 D01 V05r02
6. The worst-case data rate were:
  - 802.11b mode: 1Mbps
  - 802.11g mode: 6Mbps
  - 802.11n\_HT20 mode: MCS0

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (10) of (69)

**5. Measurement uncertainty**

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ( $\pm$ )	
Conducted RF power	0.9 dB	
Conducted spurious emissions	1.1 dB	
Radiated spurious emissions	9 kHz ~ 30 MHz:	2.4 dB
	30 MHz ~ 1 000 MHz	2.3 dB
	1 000 MHz ~ 18 000 MHz	5.6 dB
	Above 18 000 MHz	5.7 dB
Conducted emissions	9 kHz ~ 150 kHz	1.6 dB
	150 kHz ~ 30 MHz	1.7 dB

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (11) of (69)

**6. Measurement results explanation example**

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.


Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	9.86	9000	12.58
50	10.08	10000	13.03
100	10.20	11000	13.23
200	10.30	12000	13.29
300	10.37	13000	13.47
400	10.49	14000	13.42
500	10.52	15000	14.03
600	10.60	16000	13.45
700	10.68	17000	13.84
800	10.77	18000	13.77
900	10.83	19000	13.57
1000	10.84	20000	14.59
2000	11.22	21000	14.17
3000	11.47	22000	14.41
4000	11.72	23000	14.02
5000	11.89	24000	14.24
6000	12.10	25000	14.44
7000	11.91	26000	14.61
8000	12.45	26500	14.51

**Note :** Offset(dB) = RF cable loss(dB) + Attenuator(dB)

## 7. Test results

### 7.1. Maximum peak output power

#### Test setup



#### Limit

According to §15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test procedure

ANSI C63.10 - Section 11.9

Used test method is section 11.9.1.3 and 11.9.2.3.1

## **Test settings**

### **General**

Section 15.247 permits the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for demonstrating compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth (see ANSI C63.10 for measurement guidance).

When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW to set a bin-to-bin spacing of  $\leq$  RBW/2 so that narrowband signals are not lost between frequency bins.

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level. The intent is to test at 100 % duty cycle; however a small reduction in duty cycle (to no lower than 98 %) is permitted, if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

If continuous transmission (or at least 98 % duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

### **11.9.1. Maximum peak conducted output power**

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

#### **11.9.1.1. RBW $\geq$ DTS bandwidth**

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq$  [3  $\times$  RBW].
- c) Set span  $\geq$  [3  $\times$  RBW].
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### **11.9.1.3. PKPM1 Peak power meter method**

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

**11.9.2.3.1. Measurement using a power meter (PM)**

Method AVGPM is a measurement using an RF average power meter, as follows:

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:
  - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
  - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
  - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle,  $D$ , of the transmitter output signal as described in 11.6.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Adjust the measurement in  $\text{dBm}$  by adding  $[10 \log(1/D)]$ , where  $D$  is the duty cycle

**Notes:**

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (15) of (69)



KCTL

**Test results**


Test mode	Frequency (MHz)	Measured output power				Limit (dBm)
		Reading (dBm)		DCF (dB)	Result (dBm)	
		Peak	Average		Average	
802.11b	2 412	20.48	18.24	-	18.24	30
	2 437	20.40	18.26	-	18.26	
	2 462	20.25	18.02	-	18.02	
	2 467	9.72	7.40	-	7.40	
	2 472	9.44	7.21	-	7.21	
802.11g	2 412	26.16	17.53	0.34	17.87	
	2 437	26.34	16.54		16.88	
	2 462	26.46	17.18		17.52	
	2 467	17.12	7.04		7.38	
	2 472	14.39	4.51		4.85	
802.11n HT20	2 412	26.67	16.87	0.37	17.24	
	2 437	26.96	16.08		16.45	
	2 462	26.80	15.78		16.15	
	2 467	15.92	4.42		4.79	
	2 472	13.69	2.24		2.61	

**Notes:**

1. Average result(dB m) = Average Reading (dB m) + DCF(dB)

## 7.2. Peak Power Spectral Density

### Test setup



### Limit

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test procedure

ANSI C63.10 - Section 11.10.2

### Test settings

#### Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- 4) Set the VBW  $\geq 3 \times \text{RBW}$ .
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (17) of (69)

**Test results**

Test mode	Frequency (MHz)	Reading (dBm/ 3kHz)	Limit (dBm/ 3kHz)
802.11b	2 412	-4.83	8.00
	2 437	-4.41	
	2 462	-6.13	
	2 467	-16.22	
	2 472	-17.04	
802.11g	2 412	-8.67	
	2 437	-9.19	
	2 462	-8.93	
	2 467	-19.85	
	2 472	-22.26	
802.11n HT20	2 412	-9.33	
	2 437	-9.47	
	2 462	-9.54	
	2 467	-21.17	
	2 472	-23.34	


# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR22-SRF0035-A  
Page (18) of (69)




## 802.11b / 2 412 MHz




## 802.11b / 2 467 MHz




## 802.11b / 2 437 MHz



## 802.11b / 2 472 MHz



## 802.11b / 2 462 MHz



Blank

# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (19) of (69)




KCTL


## 802.11g / 2 412 MHz




## 802.11g / 2 467 MHz




## 802.11g / 2 437 MHz



## 802.11g / 2 472 MHz



## 802.11g / 2 462 MHz



Blank

# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (20) of (69)




KCTL


## 802.11n HT20 / 2 412 MHz




## 802.11n HT20 / 2 467 MHz




## 802.11n HT20 / 2 437 MHz



## 802.11n HT20 / 2 472 MHz




## 802.11n HT20 / 2 462 MHz



Blank

### 7.3. 6 dB Bandwidth(DTS Channel Bandwidth)

#### Test setup



#### Limit

According to §15.247(a)(2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2 400–2 483.5 MHz, and 5 725–5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### Test procedure

ANSI C63.10 - Section 11.8.2

#### Test settings

##### DTS bandwidth

One of the following procedures may be used to determine the modulated DTS bandwidth.

##### Option 1

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

##### Option 2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0035-A  
Page (22) of (69)

**Test results**

Test mode	Frequency(MHz)	6 dB bandwidth(MHz)
802.11b	2 412	8.64
	2 437	10.14
	2 462	10.14
	2 467	8.69
	2 472	9.64
802.11g	2 412	16.38
	2 437	16.38
	2 462	16.38
	2 467	16.13
	2 472	15.78
802.11n HT20	2 412	16.78
	2 437	17.38
	2 462	17.43
	2 467	16.43
	2 472	16.13