



FCC CFR47 PART 15 SUBPART C

NFC

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n, ANT+ and NFC

MODEL NUMBER : SM-A600GN/DS, SM-A600GN

FCC ID: A3LSMA600GN

REPORT NUMBER: 4788371667-E6V2

ISSUE DATE: APR 07, 2018

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Testing
Laboratory

TL-637

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	03/30/18	Initial issue	Junwhan Lee
V2	04/07/18	Updated to address TCB's question	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
1.1. INTRODUCTION OF TEST DATA REUSE.....	5
1.2. DIFFERENCE.....	5
1.3. SPOT CHECK VERIFICATION DATA	5
1.4. REFERENCE DETAIL	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM E-FIELD STRENGTH	8
5.3. WORST-CASE CONFIGURATION AND MODE.....	8
5.4. DESCRIPTION OF TEST SETUP.....	9
6. TEST AND MEASUREMENT EQUIPMENT	12
7. 20dB BANDWIDTH	13
8. RADIATED EMISSION TEST RESULTS.....	14
8.1. LIMITS AND PROCEDURE.....	14
8.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)	16
8.1.2. SPURIOUS EMISSION 0.09 TO 30 MHz.....	18
8.1.3. TX SPURIOUS EMISSION 30 TO 1000 MHz	20
9. AC MAINS LINE CONDUCTED EMISSIONS.....	22
10. FREQUENCY STABILITY.....	27
11. SETUP PHOTOS	28

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n, ANT+ and NFC
MODEL NUMBER: SM-A600GN/DS, SM-A600GN
SERIAL NUMBER: R38K108GVGN (RADIATED, CONDUCTED, Original);
R38K108NTAW (RADIATED, Spot check & Additional test);
DATE TESTED: FEB 24, 2018 - MAR 09, 2018 (Original)
MAR 23, 2018 - MAR 29, 2018 (Spot check & Additional test)

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

1.1. INTRODUCTION OF TEST DATA REUSE

This report referenced from the FCC ID: A3LSMA600FN NFC(FCC CFR 47 Part 15C). And the applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID.

1.2. DIFFERENCE

The FCC ID: A3LSMA600GN shares the same enclosure and circuit board as FCC ID: A3LSMA600FN. The NFC antennas and surrounding circuitry and layout are identical between these two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMA600FN remains representative of FCC ID: A3LSMA600GN. The test data of FCC ID: A3LSMA600FN being submitted for this application to cover NFC features.

Due to difference of charger, radiated emission under 1GHz and AC line conducted test were performed newly.

1.3. SPOT CHECK VERIFICATION DATA

Mode	Test Item	Frequency	Test Limit	Original model	Spot check model	Deviation	Remark
				SM-A600FN/DS Results	SM-A600GN/DS Results		
				FCC ID : A3LSMA600FN	FCC ID : A3LSMA600GN		
NFC	Fundamental	13.55925 MHz	84.00 dBuV/m	23.01 dBuV/m	23.22 dBuV/m	0.21 dB	Loop antenna Face on
	Emission	4.0625 MHz	29.50 dBuV/m	11.73 dBuV/m	9.74 dBuV/m	-1.99 dB	Loop antenna Face on

Comparison of two models, upper deviation is within 3dB range and all test results are under FCC Technical Limits.

1.4. REFERENCE DETAIL

Reference application that contains the reused reference data.

Equipment Class	Reference FCC ID	Type Grant/Permissive Change	Reference Application	Folder Test/RF Exposure	Report Title / Section
DTS	A3LSMA600FN	Grant	4788371662-E1V2	Test	FCC Report DTS WLAN / All sections (Except section 11.3 and 12)
			4788371662-E2V2	Test	FCC Report BLE All sections (Except section 11.3 and 12)
DSS	A3LSMA600FN	Grant	4788371662-E3V2	Test	FCC Report BT / All sections (Except section 11.3 and 12)
NII	A3LSMA600FN	Grant	4788371662-E4V2	Test	FCC Report UNII WALN / All sections (Except section 12 and 13)
DXX	A3LSMA600FN	Grant	4788371662-E5V2	Test	FCC Report ANT+ / All sections (Except section 7.2.5 and 8)
			4788371662-E6V2	Test	FCC Report NFC / All sections (Except section 8.1.3 and 9)
PCE	A3LSMA600FN	Grant	4788371662-E7V3	Test	FCC Report WWAN / All sections (Except Conducted Output Power)

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. ANSI C63.10-2013.
4. KDB 484596 D01 Referencing Test Data DR01-42712

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n, ANT+ and NFC.
This test report addresses the DXX (NFC) operational mode.

5.2. MAXIMUM E-FIELD STRENGTH

The testing was performed at 3 meter. The transmitter maximum E-field at 30m distance is 23.01 dBuV/m which convert from 3 meter data.

5.3. WORST-CASE CONFIGURATION AND MODE

The NFC function was tested at its' fundamental and only operational frequency of 13.56 MHz. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that the Z orientation was the worst-case orientation; therefore all final radiated testing was performed with the EUT in the Z orientation while generating continuous emissions.

The fundamental level of the EUT was investigated each type and bitrate.
All test was performed worst case condition(type A and bit rate 106 kbps).

5.4. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50JWS	DK6K104VS/A- E	N/A
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A

I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A


TEST SETUP

The EUT is a stand-alone device configured and tested in a worst-case setup.


Note: Worst case is using worst case orientation with AC charger attached to the EUT with NFC signal continuously transmitting.

SETUP DIAGRAM FOR TESTS

Radiated Emissions Below 30 MHz:



Radiated Emissions Above 30 MHz, AC Line Conducted Emissions:



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-31-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	09-14-19
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-26-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-08-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY54200580	08-07-18
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-09-18
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-07-18
DC Power Supply	Agilent / HP	E3640A	MY54226395	08-07-18
Temperature Chamber	ESPEC	SH-642	93001109	08-08-18
LISN	R&S	ENV216	101837	08-09-18
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. 20dB BANDWIDTH

LIMITS

§15.215

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated

§15.225

Operation within the band 13.110 – 14.010MHz

TEST PROCEDURE

The spectrum analyzer connected receive antenna and the EUT placed on near the receive antenna. The RBW is set to 10KHz. The VBW is set to 3 times the RBW. The sweep time is coupled.

RESULTS

Frequency [MHz]	20dB Bandwidth [KHz]
13.56	435.10

Note : Because the intentional signal is very narrowband (almost CW) adjusting the RBW per RSS-GEN/ANSI C63.10:2013 to be a value between 1-5% of the OBW is impractical. Measurements were made to show the emissions were fully contained within the frequency band designated in the rule section under which the equipment is operated.

20dB Bandwidth Plot



8. RADIATED EMISSION TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMIT

§15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the filed strength from uV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (uV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE


ANSI C63.10-2013

The EUT is an intentional radiator that incorporates a digital device. The highest fundamental frequency generated or used in the device is 13.56 MHz. The frequency range was investigated from 0.15 MHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater (1000MHz)

RESULTS

No non-compliance noted:

8.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)



Trace Markers

[Face-On]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna	Dist Corr 30m	Cable Loss	Corrected Reading dB(uVolts/meter)	FCC 15.225 Limit	PK Margin (dB)	Azimuth (Degs)
1	13.55925	42.61	PK	19.9	-40	.5	23.01	84	-60.99	0-360
2	13.4395	24.39	PK	19.9	-40	.5	4.79	50.5	-45.71	0-360
3	13.66	22.66	PK	19.9	-40	.6	3.16	50.5	-47.34	0-360
4	13.26075	25.02	PK	19.9	-40	.5	5.42	40.51	-35.09	0-360
5	13.8665	23.24	PK	19.8	-40	.6	3.64	40.51	-36.87	0-360
6	13.015	24.19	PK	19.9	-40	.5	4.59	29.54	-24.95	0-360
7	14.159	23	PK	19.8	-40	.6	3.4	29.54	-26.14	0-360

PK – Peak Detector


[Face-Off]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna	Dist Corr 30m	Cable Loss	Corrected Reading dB(uVolts/meter)	FCC 15.225 Limit	PK Margin (dB)	Azimuth (Degs)
8	13.56025	37.12	PK	19.9	-40	.5	17.52	84	-66.48	0-360
9	13.4385	22.37	PK	19.9	-40	.5	2.77	50.5	-47.73	0-360
10	13.66225	23.31	PK	19.9	-40	.6	3.81	50.5	-46.69	0-360
11	13.248	24.4	PK	19.9	-40	.5	4.8	40.51	-35.71	0-360
12	13.86425	23.05	PK	19.8	-40	.6	3.45	40.51	-37.06	0-360
13	13.011	25.6	PK	19.9	-40	.5	6	29.54	-23.54	0-360
14	14.15975	22.98	PK	19.8	-40	.6	3.38	29.54	-26.16	0-360

PK – Peak Detector

Note : Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

8.1.2. SPURIOUS EMISSION 0.09 TO 30 MHz



Trace Markers

[Face-On]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna	Cable Loss	Dist Corr 30m	Corrected Reading (dBuVolts)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	QP Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Asimuth (Degs)
1	.01823	49.88	Pk	20	.1	-80	-10.02	62.37	-72.39	42.37	-52.39	-	-	-	-	-	-	0-360
2	.06563	37.62	Pk	19.8	.1	-80	-22.48	51.24	-73.72	31.24	-53.72	-	-	-	-	-	-	0-360
3	.26667	30.87	Pk	19.5	.1	-80	-29.53	-	-	-	-	-	-	39.09	-68.62	19.09	-48.62	0-360
4	.91245	18.06	Pk	19.7	.2	-40	-2.04	-	-	-	-	28.41	-30.45	-	-	-	-	0-360
5	4.06125	31.63	Pk	19.8	.3	-40	11.73	-	-	-	-	29.5	-17.77	-	-	-	-	0-360
6	13.56165	41.26	Pk	19.9	.5	-40	21.66	-	-	-	-	29.5	-7.84	-	-	-	-	0-360


Pk - Peak detector

[Face-Off]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna	Cable Loss	Dist Corr 30m	Corrected Reading (dBuVolts)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	QP Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Asimuth (Degs)
7	.01825	52.95	Pk	20	.1	-80	-6.95	62.36	-69.31	42.36	-49.31	-	-	-	-	-	-	0-360
8	.06437	38.01	Pk	19.8	.1	-80	-22.09	51.41	-73.5	31.41	-53.5	-	-	-	-	-	-	0-360
9	.24243	32.99	Pk	19.6	.1	-80	-27.31	-	-	-	-	-	-	39.92	-67.23	19.92	-47.23	0-360
10	.8977	19.2	Pk	19.7	.2	-40	-.9	-	-	-	-	28.56	-29.46	-	-	-	-	0-360
11	4.1178	28.82	Pk	19.8	.3	-40	8.92	-	-	-	-	29.5	-20.58	-	-	-	-	0-360
12	13.56165	37.32	Pk	19.9	.5	-40	17.72	-	-	-	-	29.5	-11.78	-	-	-	-	0-360

Pk - Peak detector

8.1.3. TX SPURIOUS EMISSION 30 TO 1000 MHz



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	48.721	31.86	Pk	19.8	-29.6	0	22.06	40	-17.94	0-360	400	H
2	98.773	46.05	Pk	17.2	-28.5	0	34.75	43.52	-8.77	0-360	300	H
3	225.94	37.12	Pk	17.6	-27.4	0	27.32	46.02	-18.7	0-360	200	H
4	50.079	40.79	Pk	19.9	-29.3	0	31.39	40	-8.61	0-360	200	V
5	59.585	41.23	Pk	18.5	-29.1	0	30.63	40	-9.37	0-360	100	V
6	222.739	38.44	Pk	17.4	-27.4	0	28.44	46.02	-17.58	0-360	100	V

Pk - Peak detector

9. AC MAINS LINE CONDUCTED EMISSIONS

LIMITS

§15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Notes:
1. The lower limit shall apply at the transition frequencies
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.


Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

No non-compliance noted:

WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.159	37.3	Pk	10	.1	47.4	65.52	-18.12	-	-
2	.159	20.53	Av	10	.1	30.63	-	-	55.52	-24.89
3	.195	36.6	Pk	9.8	.2	46.6	63.82	-17.22	-	-
4	.201	20.01	Av	9.8	.2	30.01	-	-	53.57	-23.56
5	.24	31.52	Pk	9.6	.2	41.32	62.1	-20.78	-	-
6	.24	14.62	Av	9.6	.2	24.42	-	-	52.1	-27.68
7	.501	28.24	Pk	9.7	.2	38.14	56	-17.86	-	-
8	.504	16.49	Av	9.7	.2	26.39	-	-	46	-19.61
9	3.273	27.38	Pk	9.8	.3	37.48	56	-18.52	-	-
10	3.279	14.4	Av	9.8	.3	24.5	-	-	46	-21.5
11	13.569	46.39	Pk	9.8	.4	56.59	60	-3.41	-	-
12	13.569	27.37	Av	9.8	.4	37.57	-	-	50	-12.43

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Range 1: Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13.5683	46.65	Qp	9.8	.4	56.85	60	-3.15	-	-

Qp - Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.159	41.18	Pk	10	.1	51.28	65.52	-14.24	-	-
14	.159	25.31	Av	10	.1	35.41	-	-	55.52	-20.11
15	.198	35.68	Pk	9.9	.2	45.78	63.69	-17.91	-	-
16	.204	17.98	Av	9.8	.2	27.98	-	-	53.45	-25.47
17	1.611	25.75	Pk	9.9	.3	35.95	56	-20.05	-	-
18	1.605	15.94	Av	9.9	.3	26.14	-	-	46	-19.86
19	2.397	23.83	Pk	9.9	.3	34.03	56	-21.97	-	-
20	2.397	12.1	Av	9.9	.3	22.3	-	-	46	-23.7
21	14.997	35.32	Pk	9.9	.4	45.62	60	-14.38	-	-
22	14.979	24.34	Av	9.9	.4	34.64	-	-	50	-15.36
23	20.526	33.09	Pk	10.1	.4	43.59	60	-16.41	-	-
24	20.544	16.28	Av	10.1	.4	26.78	-	-	50	-23.22

Pk - Peak detector
 Av - Average detection

10. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

TEST PROCEDURE

ANSI C63.10 §6.8

RESULTS

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply (Vdc)	Envir. Temp (°C)	Frequency Deviation Measured with Time Elapse								
		Start up (MHz)	Delta (ppm)	@ 2mins (MHz)	Delta (ppm)	@ 5mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.85	50	13.559970631	5.024	13.559957786	5.971	13.559958256	5.936	13.559955848	6.114	100
3.85	40	13.559982649	4.138	13.559981448	4.226	13.559980725	4.279	13.559977234	4.537	100
3.85	30	13.560011549	2.006	13.560011272	2.027	13.560010446	2.088	13.560009859	2.131	100
3.85	20	13.560038754	0	13.560037119	0.121	13.560037879	0.065	13.560038125	0.046	100
3.85	10	13.560030595	0.602	13.560030129	0.636	13.560029852	0.656	13.560029494	0.683	100
3.85	0	13.560079995	-3.041	13.560079256	-2.987	13.560078422	-2.925	13.560076429	-2.778	100
3.85	-10	13.560094289	-4.095	13.560095172	-4.161	13.560095725	-4.201	13.560096142	-4.232	100
3.85	-20	13.560088425	-3.663	13.560089146	-3.716	13.560089954	-3.776	13.560090433	-3.811	100
3.85	-30	13.560030573	0.603	13.560007445	2.309	13.559995868	3.163	13.559994731	3.247	100

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply (Vdc)	Envir. Temp (°C)	Frequency Deviation Measured with Time Elapse								
		Start up (MHz)	Delta (ppm)	@ 2mins (MHz)	Delta (ppm)	@ 5mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.85	20	13.560038754	0	13.560037119	0.121	13.560037879	0.065	13.560038125	0.046	100
4.40	20	13.560037285	0.108	13.560037596	0.085	13.560037869	0.001	13.560038484	0.020	100
3.60	20	13.560037459	0.096	13.560037216	0.113	13.560036709	0.086	13.560036115	0.195	100

No non-compliance noted.