



FCC 47 CFR PART 15 SUBPART E

UNII

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n, ANT+ and NFC

MODEL NUMBER : SM-A600GN/DS, SM-A600GN

FCC ID: A3LSMA600GN

REPORT NUMBER: 4788371667-E4V2

ISSUE DATE: APR 07, 2018

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



ACCREDITED*

Testing
Laboratory

TL-637

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	03/30/18	Initial issue	Junwhan Lee
V2	04/07/18	Updated to address TCB's question	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
1.1. INTRODUCTION OF TEST DATA REUSE.....	7
1.2. DIFFERENCE.....	7
1.3. SPOT CHECK VERIFICATION DATA	7
1.4. REFERENCE DETAIL	8
2. TEST METHODOLOGY	9
3. FACILITIES AND ACCREDITATION	9
4. CALIBRATION AND UNCERTAINTY	9
4.1. MEASURING INSTRUMENT CALIBRATION	9
4.2. SAMPLE CALCULATION	9
4.3. MEASUREMENT UNCERTAINTY.....	10
5. EQUIPMENT UNDER TEST	11
5.1. DESCRIPTION OF EUT	11
5.2. MAXIMUM OUTPUT POWER.....	11
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.4. WORST-CASE CONFIGURATION AND MODE.....	12
5.5. DESCRIPTION OF TEST SETUP.....	13
6. TEST AND MEASUREMENT EQUIPMENT	15
7. SUMMARY TABLE	16
8. MEASUREMENT METHODS	17
9. REFERENCE MEASUREMENTS RESULTS	18
9.1. ON TIME AND DUTY CYCLE RESULTS.....	18
9.2. DUTY CYCLE PLOTS	18
9.3. 26 dB BANDWIDTH.....	20
9.3.1. 802.11a MODE IN THE 5.2 GHz BAND.....	21
9.3.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND	21
9.3.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND	21
9.3.4. 802.11a MODE IN THE 5.3 GHz BAND	21
9.3.5. 802.11n HT20 MODE IN THE 5.3 GHz BAND	22
9.3.6. 802.11n HT40 MODE IN THE 5.3 GHz BAND	22
9.3.7. 802.11a MODE IN THE 5.5 GHz BAND.....	22
9.3.8. 802.11n HT20 MODE IN THE 5.5 GHz BAND	22

9.3.9.	802.11n HT40 MODE IN THE 5.5 GHz BAND	23
9.3.10.	802.11a MODE IN THE 5.8 GHz BAND	23
9.3.11.	802.11n HT20 MODE IN THE 5.8 GHz BAND	23
9.3.12.	802.11n HT40 MODE IN THE 5.8 GHz BAND	23
9.3.13.	26 dB BANDWIDTH PLOTS	24
9.4.	99% BANDWIDTH	36
9.4.1.	802.11a MODE IN THE 5.2 GHz BAND	37
9.4.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	37
9.4.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	37
9.4.4.	802.11a MODE IN THE 5.3 GHz BAND	37
9.4.5.	802.11n HT20 MODE IN THE 5.3 GHz BAND	38
9.4.6.	802.11n HT40 MODE IN THE 5.3 GHz BAND	38
9.4.7.	802.11a MODE IN THE 5.5 GHz BAND	38
9.4.8.	802.11n HT20 MODE IN THE 5.5 GHz BAND	38
9.4.9.	802.11n HT40 MODE IN THE 5.5 GHz BAND	39
9.4.10.	802.11a MODE IN THE 5.8 GHz BAND	39
9.4.11.	802.11n HT20 MODE IN THE 5.8 GHz BAND	39
9.4.12.	802.11n HT40 MODE IN THE 5.8 GHz BAND	39
9.4.13.	99% BANDWIDTH PLOTS	40
10.	ANTENNA PORT TEST RESULTS	52
10.1.	6 dB BANDWIDTH	52
10.1.1.	802.11a MODE IN THE 5.8 GHz BAND	53
10.1.2.	802.11n HT20 MODE IN THE 5.8 GHz BAND	53
10.1.3.	802.11n HT40 MODE IN THE 5.8 GHz BAND	53
10.1.4.	6 dB BANDWIDTH PLOTS	54
10.2.	OUTPUT POWER AND PPSD	57
10.2.1.	802.11a MODE IN THE 5.2 GHz BAND	58
10.2.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	59
10.2.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	60
10.2.4.	802.11a MODE IN THE 5.3 GHz BAND	61
10.2.5.	802.11n HT20 MODE IN THE 5.3 GHz BAND	62
10.2.6.	802.11n HT40 MODE IN THE 5.3 GHz BAND	63
10.2.7.	802.11a MODE IN THE 5.5 GHz BAND	64
10.2.8.	802.11n HT20 MODE IN THE 5.5 GHz BAND	65
10.2.9.	802.11n HT40 MODE IN THE 5.5 GHz BAND	66
10.2.10.	802.11a MODE IN THE 5.8 GHz BAND	67
10.2.11.	802.11n HT20 MODE IN THE 5.8 GHz BAND	68
10.2.12.	802.11n HT40 MODE IN THE 5.8 GHz BAND	69
10.2.13.	802.11a MODE AT STRADDLE CHANNEL	70
10.2.14.	802.11n HT20 MODE AT STRADDLE CHANNEL	71
10.2.15.	802.11n HT40 MODE AT STRADDLE CHANNEL	72
10.2.16.	OUTPUT POWER AND PPSD PLOTS	73
11.	TRANSMITTER ABOVE 1 GHz.....	88
11.1.	5.2 GHz	90
11.1.1.	TX Above 1GHz 802.11a MODE IN THE 5.2GHz BAND	90
11.1.2.	TX Above 1GHz 802.11n HT20 MODE IN THE 5.2GHz BAND	98
11.1.3.	TX Above 1GHz 802.11n HT40 MODE IN THE 5.2GHz BAND	106

11.2.	5.3 GHz.....	112
11.2.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.3 GHz BAND	112
11.2.2.	TX ABOVE 1GHz 802.11n HT20 MODE IN THE 5.3GHz BAND.....	120
11.2.3.	TX ABOVE 1GHz 802.11n HT40 MODE IN THE 5.3GHz BAND.....	128
11.3.	5.5-5.6 GHz.....	134
11.3.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.5 GHz BAND	134
11.3.2.	TX ABOVE 1GHz 802.11n HT20 MODE IN THE 5.5GHz BAND.....	146
11.3.3.	TX ABOVE 1GHz 802.11n HT40 MODE IN THE 5.5GHz BAND.....	158
11.4.	5.8 GHz.....	170
11.4.1.	TX ABOVE 1GHz 802.11a MODE IN THE 5.8GHz BAND	170
11.4.2.	TX ABOVE 1GHz 802.11n HT20 MODE IN THE 5.8GHz BAND.....	180
11.4.3.	TX ABOVE 1GHz 802.11n HT40 MODE IN THE 5.8GHz BAND.....	190
12.	WORST-CASE BELOW 1 GHz	198
13.	AC POWER LINE CONDUCTED EMISSIONS.....	200
14.	DYNAMIC FREQUENCY SELECTION.....	205
14.1.	OVERVIEW.....	205
14.1.1.	LIMITS.....	205
14.1.1.	TEST AND MEASUREMENT SYSTEM.....	209
14.1.2.	SETUP OF EUT.....	212
14.1.3.	DESCRIPTION OF EUT	213
14.2.	RESULTS FOR 20 MHz BANDWIDTH.....	214
14.2.1.	TEST CHANNEL	214
14.2.2.	RADAR WAVEFORM AND TRAFFIC.....	214
14.2.3.	OVERLAPPING CHANNEL TESTS.....	216
14.2.4.	MOVE AND CLOSING TIME	216
14.3.	RESULTS FOR 40 MHz BANDWIDTH.....	219
14.3.1.	TEST CHANNEL	219
14.3.2.	RADAR WAVEFORM AND TRAFFIC.....	219
14.3.3.	OVERLAPPING CHANNEL TESTS.....	221
14.3.4.	MOVE AND CLOSING TIME	221
15.	SETUP PHOTOS.....	224

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n, ANT+ and NFC

MODEL NUMBER: SM-A600GN/DS, SM-A600GN

SERIAL NUMBER: R38K108GLMR, R38K108GVGN (RADIATED, Original);
R38K10BCS5W (CONDUCTED, Original);
R38K108NTAW, R38K108M8ZJ
(RADIATED, Spot check & Additional test);

DATE TESTED: FEB 22, 2018 - MAR 09, 2018 (Original)
MAR 12, 2018 - MAR 29, 2018 (Spot check & Additional test)

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

1.1. INTRODUCTION OF TEST DATA REUSE

This report referenced from the FCC ID: A3LSMA600FN UNII WLAN(FCC CFR 47 Part 15E). And the applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID.

1.2. DIFFERENCE

The FCC ID: A3LSMA600GN shares the same enclosure and circuit board as FCC ID: A3LSMA600FN. The WLAN antennas and surrounding circuitry and layout are identical between these two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMA600FN remains representative of FCC ID: A3LSMA600GN. The test data of FCC ID: A3LSMA600FN being submitted for this application to cover WLAN features.

Due to difference of charger, radiated emission under 1GHz and AC line conducted test were performed newly.

1.3. SPOT CHECK VERIFICATION DATA

Band	Test Item	Mode	Frequency	Test Limit	Original model	Spot check model	Deviation	Remark
					SM-A600FN/DS Results	SM-A600GN/DS Results		
					FCC ID : A3LSMA600FN	FCC ID : A3LSMA600GN		
UNII WLAN (5GHz)	Band Edge	802.11n HT40	5190 MHz	54 dBuV/m	51.12 dBuV/m	50.48 dBuV/m	-0.64 dB	
	RSE	802.11 a	5200 MHz	68.2 dBuV/m	58.25 dBuV/m	56.88 dBuV/m	-1.37 dB	
	Band Edge	802.11 n HT40	5310 MHz	54 dBuV/m	48.90 dBuV/m	49.31 dBuV/m	0.41 dB	
	RSE	802.11 a	5260 MHz	68.2 dBuV/m	58.32 dBuV/m	57.86 dBuV/m	-0.46 dB	
	Band Edge	802.11n HT20	5500 MHz	68.2 dBuV/m	65.83 dBuV/m	65.87 dBuV/m	0.04 dB	
	RSE	802.11 a	5500 MHz	54 dBuV/m	44.16 dBuV/m	44.04 dBuV/m	-0.12 dB	
	Band Edge	802.11 a	5745 MHz	-27 dBm	-32.56 dBm	-31.46 dBm	1.10 dB	
	RSE	802.11 a	5785 MHz	54 dBuV/m	47.05 dBuV/m	45.76 dBuV/m	-1.29 dB	

Comparison of two models, upper deviation is within 3dB range and all test results are under FCC Technical Limits.

1.4. REFERENCE DETAIL

Reference application that contains the reused reference data.

Equipment Class	Reference FCC ID	Type Grant/Permissive Change	Reference Application	Folder Test/RF Exposure	Report Title / Section
DTS	A3LSMA600FN	Grant	4788371662-E1V2	Test	FCC Report DTS WLAN / All sections (Except section 11.3 and 12)
			4788371662-E2V2	Test	FCC Report BLE All sections (Except section 11.3 and 12)
DSS	A3LSMA600FN	Grant	4788371662-E3V2	Test	FCC Report BT / All sections (Except section 11.3 and 12)
NII	A3LSMA600FN	Grant	4788371662-E4V2	Test	FCC Report UNII WALN / All sections (Except section 12 and 13)
DXX	A3LSMA600FN	Grant	4788371662-E5V2	Test	FCC Report ANT+ / All sections (Except section 7.2.5 and 8)
			4788371662-E6V2	Test	FCC Report NFC / All sections (Except section 8.1.3 and 9)
PCE	A3LSMA600FN	Grant	4788371662-E7V3	Test	FCC Report WWAN / All sections (Except Conducted Output Power)

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 789033 D02 General UNII Test Procedures New Rules v02r01
4. KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
5. KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02
6. KDB 484596 D01 Referencing Test Data DR01-42712
7. ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
<input checked="" type="checkbox"/> Chamber 1
<input checked="" type="checkbox"/> Chamber 2
<input checked="" type="checkbox"/> Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n, ANT+ and NFC.
 This test report addresses the NII (UNII) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted average output power as follows:

Frequency Range [MHz]	Mode	Output Power [dBm]	Output Power [mW]
5180 - 5240	802.11a	16.01	39.90
	802.11n HT20	15.57	36.09
5190 - 5230	802.11n HT40	14.21	26.36
5260 - 5320	802.11a	15.85	38.45
	802.11n HT20	16.40	43.60
5270 - 5310	802.11n HT40	14.31	26.97
5500 - 5720	802.11a	16.29	42.60
	802.11n HT20	16.00	39.84
5510 - 5710	802.11n HT40	13.76	23.78
5745 - 5825	802.11a	16.19	41.57
	802.11n HT20	15.76	37.69
5755 - 5795	802.11n HT40	13.73	23.58

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal antenna, with a maximum gain of:

Frequency Range [MHz]	Antenna Gain [dBi]
UNII 1 5150 – 5250	-1.17
UNII 2A 5250 – 5350	-1.74
UNII 2C 5470 – 5725	-1.74
UNII 3 5725 – 5850	-2.12

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that the Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the Y orientation.

Based on the baseline scan, the worst-case data rates were:

802.11a mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0

Note : All radiated and power line conducted tests were performed connected with earphone and charger for evaluation of worst case mode.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA50JWS	DK6K104VS/A- E	N/A
Data Cable	SAMSUNG	ECB-DU68WE	N/A	N/A
Earphone	SAMSUNG	EHS61ASFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A


TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software in hidden menu exercised the EUT to enable NII mode.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	09-14-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-31-19
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3115	00161451	03-10-19
Antenna, Horn, 18 GHz	ETS	3117	00168724	05-31-19
Antenna, Horn, 18 GHz	ETS	3117	00168717	05-31-19
Antenna, Horn, 18 GHz	ETS	3117	00205959	11-29-18
Antenna, Horn, 40 GHz	ETS	3116C	00166155	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C	00168645	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	11-13-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-11-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-08-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-08-18
Attenuator	PASTERNAK	PE7087-10	A001	08-08-18
Attenuator	PASTERNAK	PE7087-10	A008	08-08-18
Attenuator	PASTERNAK	PE7087-10	2	08-10-18
Attenuator	PASTERNAK	PE7087-10	A009	08-08-18
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-09-18
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-07-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-11-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-11-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-11-18
LISN	R&S	ENV-216	101837	08-09-18
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
15.407(e)	6dB Band width (5.8Ghz)	500KHz	Condcuted	PASS
15.407 (a)(2)	TX Cond. Power 5.15-2.25, 5.25-5.35 & 5.47-5.725	<24dBm or 11+10Log(OBW)		PASS
15.407 (a)(3)	TX Cond. Power 5.725-5.825	< 30dBm or 17+10Log(OBW)		PASS
15.407 (a)(5)	PSD (5.2,5.3,5.5GHz)	<11dBm		PASS
15.407 (a)(5)	PSD (5.8GHz)	30dBm per 500kHz		PASS
15.207 (a)	AC Power Line conducted emissions	Section 10		Radiated
15.407 (b) & 15.209	Radiated Spurious Emission	< 54dBuV/m	PASS	
15.407 (h)(2)	Dynamic Frequency Selection	N/A	Condcuted	PASS

8. MEASUREMENT METHODS

On-Time and Duty Cycle : KDB 789033 D02 v02r01, Section B.

6dB Emission BW : KDB 789033 D02 v02r01, Section C.2.

26dB Emission BW : KDB 789033 D02 v02r01, Section C.1.

99% Occupied BW : KDB 789033 D02 v02r01, Section D.



Conducted Output Power : KDB 789033 D02 v02r01, Section E.2.d(Method SA-2)

Power Spectral Density : KDB 789033 D02 v02r01, Section F.

Unwanted emissions in restricted bands : KDB 789033 D02 v02r01, Section G.

Unwanted emissions in non-restricted bands : KDB 789033 D02 v02r01, Section G.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.



9.3. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v02r01: The transmitter output is connected to a spectrum analyzer with the RBW set to approximately 1% of EBW, the VBW > RBW, peak detector and max hold.

NOTE

- Calculation for 26dB Bandwidth of UNII-2C and UNII-3 Straddle Channel

ex) Fundamental frequency : 5720MHz

- 26dB BW : 21.00MHz
- Turning Frequency : 5725MHz
- 26dB Bandwidth of UNII-2C band Portion
= $(5725 - (5720 - (21.00 / 2))) = 15.50 \text{ MHz}$
- 26dB Bandwidth of UNII-3 band Portion
= $(5720 + (21.00 / 2) - 5725) = 5.50 \text{ MHz}$

RESULTS

9.3.1. 802.11a MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5180	21.07
Mid	5200	20.98
High	5240	21.35
Worst		21.35

9.3.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5180	21.43
Mid	5200	21.31
High	5240	21.19
Worst		21.43

9.3.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5190	39.41
High	5230	39.45
Worst		39.45

9.3.4. 802.11a MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5260	21.06
Mid	5300	21.04
High	5320	20.87
Worst		21.06

9.3.5. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5260	22.56
Mid	5300	21.86
High	5320	21.86
Worst		22.56

9.3.6. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5270	39.66
High	5310	39.81
Worst		39.81

9.3.7. 802.11a MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5500	21.22
Mid	5580	20.99
High	5700	21.05
Straddle	5720	15.58
Worst		21.22

9.3.8. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5500	21.08
Mid	5580	21.36
High	5700	21.23
Straddle	5720	15.70
Worst		21.36

9.3.9. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Low	5510	39.56
Mid	5590	39.65
High	5670	39.82
Straddle	5710	34.68
Worst		39.82

9.3.10. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Straddle	5720	5.58
Low	5745	21.28
Mid	5785	21.03
High	5825	21.16
Worst		21.28

9.3.11. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Straddle	5720	5.70
Low	5745	21.07
Mid	5785	21.30
High	5825	21.24
Worst		21.30

9.3.12. 802.11n HT40 MODE IN THE 5.8 GHz BAND


Channel	Frequency [MHz]	26 dB Bandwidth [MHz]
Straddle	5710	4.68
Low	5755	39.58
High	5795	39.80
Worst		39.80

9.3.13. 26 dB BANDWIDTH PLOTS


UNII 5.2 GHz IEEE 802.11a mode



UNII 5.2 GHz IEEE 802.11n HT20 mode



UNII 5.2 GHz IEEE 802.11n HT40 mode




UNII 5.3 GHz IEEE 802.11a mode




UNII 5.3 GHz IEEE 802.11n HT20 mode


11n HT20 Mode Low Channel




11n HT20 Mode Middle Channel



11n HT20 Mode High Channel



UNII 5.3 GHz IEEE 802.11n HT40 mode



UNII 5.5 GHz IEEE 802.11a mode




UNII 5.5 GHz IEEE 802.11n HT20 mode



UNII 5.5 GHz IEEE 802.11n HT40 mode



UNII 5.8 GHz IEEE 802.11a mode




UNII 5.8 GHz IEEE 802.11n HT20 mode




UNII 5.8 GHz IEEE 802.11n HT40 mode


11n HT40 Mode Straddle Channel



11n HT40 Mode Low Channel



11n HT40 Mode High Channel



9.4. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v02r01: The transmitter output is connected to a spectrum analyzer with the RBW set to approximately 1% of EBW, the VBW > RBW, peak detector and max hold.

NOTE

- Calculation for 99% Bandwidth of UNII-2C and UNII-3 Straddle Channel

ex) Fundamental frequency : 5720MHz

- 99% BW : 21.00MHz
- Turning Frequency : 5725MHz
- 99% Bandwidth of UNII-2C band Portion
= $(5725 - (5720 - (21.00 / 2))) = 15.50$ MHz
- 99% Bandwidth of UNII-3 band Portion
= $(5720 + (21.00 / 2) - 5725) = 5.50$ MHz

RESULTS

9.4.1. 802.11a MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5180	16.49
Mid	5200	16.48
High	5240	16.51
Worst		16.51

9.4.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5180	17.67
Mid	5200	17.67
High	5240	17.68
Worst		17.68

9.4.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5190	36.14
High	5230	36.14
Worst		36.14

9.4.4. 802.11a MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5260	16.47
Mid	5300	16.50
High	5320	16.50
Worst		16.50

9.4.5. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5260	17.70
Mid	5300	17.72
High	5320	17.72
Worst		17.72

9.4.6. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5270	36.13
High	5310	36.15
Worst		36.15

9.4.7. 802.11a MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5500	16.48
Mid	5580	16.49
High	5700	16.48
Straddle	5720	13.25
Worst		16.49

9.4.8. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5500	17.68
Mid	5580	17.70
High	5700	17.70
Straddle	5720	13.86
Worst		17.70

9.4.9. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	5510	36.16
Mid	5590	36.12
High	5670	36.17
Straddle	5710	33.11
Worst		36.17

9.4.10. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Straddle	5720	3.25
Low	5745	16.49
Mid	5785	16.46
High	5825	16.48
Worst		16.49

9.4.11. 802.11n HT20 MODE IN THE 5.8 GHz BAND


Channel	Frequency [MHz]	99% Bandwidth [MHz]
Straddle	5720	3.86
Low	5745	17.72
Mid	5785	17.69
High	5825	17.66
Worst		17.72

9.4.12. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Straddle	5710	3.11
Low	5755	36.15
High	5795	36.21
Worst		36.21


9.4.13. 99% BANDWIDTH PLOTS

UNII 5.2 GHz IEEE 802.11a mode




UNII 5.2 GHz IEEE 802.11n HT20 mode


11n HT20 Mode Low Channel




11n HT20 Mode Middle Channel




11n HT20 Mode High Channel



UNII 5.2 GHz IEEE 802.11n HT40 mode




UNII 5.3 GHz IEEE 802.11a mode




UNII 5.3 GHz IEEE 802.11n HT20 mode


11n HT20 Mode Low Channel




11n HT20 Mode Middle Channel




11n HT20 Mode High Channel




UNII 5.3 GHz IEEE 802.11n HT40 mode



UNII 5.5 GHz IEEE 802.11a mode




UNII 5.5 GHz IEEE 802.11n HT20 mode



UNII 5.5 GHz IEEE 802.11n HT40 mode



UNII 5.8 GHz IEEE 802.11a mode



UNII 5.8 GHz IEEE 802.11n HT20 mode

