

# FCC LTE REPORT

## Certification

**Applicant Name:**  
SAMSUNG Electronics Co., Ltd.

**Date of Issue:**  
March 13, 2019

**Address:**  
129, Samsung-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Location:**  
HCT CO., LTD.,  
74, Seoicheon-ro 578beon-gil, Majang-myeon,  
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-RF-1903-FC018

**FCC ID:** A3LSMA6060

**APPLICANT:** SAMSUNG Electronics Co., Ltd.

Model(s): SM-A6060  
 EUT Type: Mobile Phone  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 41 (5)	2557.5 – 2652.5	4M50G7D	QPSK	0.198	22.97
		4M51W7D	16QAM	0.158	21.98
		4M48W7D	64QAM	0.124	20.94
LTE – Band 41 (10)	2560.0 – 2650.0	8M96G7D	QPSK	0.194	22.87
		8M97W7D	16QAM	0.154	21.86
		8M94W7D	64QAM	0.120	20.79
LTE – Band 41 (15)	2562.5 – 2647.5	13M4G7D	QPSK	0.204	23.09
		13M5W7D	16QAM	0.172	22.36
		13M5W7D	64QAM	0.136	21.32
LTE – Band 41 (20)	2565.0 – 2645.0	17M9G7D	QPSK	0.200	23.01
		17M9W7D	16QAM	0.169	22.28
		17M9W7D	64QAM	0.132	21.20

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



**Report prepared by : Jae Ryang Do**  
**Engineer of Telecommunication Testing Center**



**Report approved by : Kwon Jeong**  
**Manager of Telecommunication Testing Center**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1903-FC018	March 13, 2019	- First Approval Report

# Table of Contents

1. GENERAL INFORMATION .....	4
2. INTRODUCTION.....	5
2.1. DESCRIPTION OF EUT .....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY.....	5
3. DESCRIPTION OF TESTS .....	6
3.1 TEST PROCEDURE.....	6
3.2 RADIATED POWER.....	7
3.3 RADIATED SPURIOUS EMISSIONS.....	8
3.4 OCCUPIED BANDWIDTH.....	9
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	10
3.6 CHANNEL EDGE .....	11
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	12
3.8 WORST CASE(RADIATED TEST).....	13
3.9 WORST CASE(CONDUCTED TEST).....	14
4. LIST OF TEST EQUIPMENT.....	15
5. MEASUREMENT UNCERTAINTY .....	16
6. SUMMARY OF TEST RESULTS .....	17
7. SAMPLE CALCULATION .....	18
8. TEST DATA .....	20
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	20
8.2 RADIATED SPURIOUS EMISSIONS.....	22
8.3 OCCUPIED BANDWIDTH.....	26
8.4 CONDUCTED SPURIOUS EMISSIONS .....	27
8.5 CHANNEL EDGE .....	28
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	29
8.7 GEO-LOCATION MECHANISM .....	41
9. TEST PLOTS.....	50
10. ANNEX A_ TEST SETUP PHOTO .....	111

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

<b>Applicant Name:</b>	SAMSUNG Electronics Co., Ltd.
<b>Address:</b>	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
<b>FCC ID:</b>	A3LSMA6060
<b>Application Type:</b>	Certification
<b>FCC Classification:</b>	PCS Licensed Transmitter Held to Ear (PCE)
<b>FCC Rule Part(s):</b>	§27, §2
<b>EUT Type:</b>	Mobile Phone
<b>Model(s):</b>	SM-A6060
<b>Tx Frequency:</b>	2557.5 – 2652.5 : 5 MHz 2560.0 – 2650.0 : 10 MHz 2562.5 – 2647.5 : 15 MHz 2565.0 – 2645.0 : 20 MHz
<b>Date(s) of Tests:</b>	February 18, 2019 ~ March 05, 2019

## **2. INTRODUCTION**

### **2.1. DESCRIPTION OF EUT**

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE.  
It also supports IEEE 802.11 a/b/g/n/ac, Bluetooth, BTLE, NFC & ANT+.

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

### **3. DESCRIPTION OF TESTS**

#### **3.1 TEST PROCEDURE**

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI C63.26-2015 – Section 5.2 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

## 3.2 RADIATED POWER

### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

#### Test Settings


1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $> 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin  $> 20$  dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.  
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data



### 3.4 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Settings

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep  $\geq$  2 \* Span / RBW

### 3.6 CHANNEL EDGE



Test setup

#### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.


#### Test Settings

1. Start and stop frequency were set such that the channel edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 2% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

#### Test Notes

1. The attenuation factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge. In addition, the attenuation factor shall not be less than  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log (P)$  dB at or below 2490.5 MHz.
2. All measurements were done at 3 channels.
3. The channel edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

### 3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



**Test setup**

#### **Test Overview**

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

#### **Test Settings**

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### 3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM	1	0	Y
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Y

**3.9 WORST CASE(CONDUCTED TEST)**

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.  
 Conducted Output Power value can be confirmed on the SAR report.

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset		
Occupied Bandwidth	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0		
Channel Edge	QPSK	5	Low	1	0		
			High	1	24		
		10	Low	1	0		
			High	1	49		
		15	Low	1	0		
			High	1	74		
		20	Low	1	0		
			High	1	99		
				5, 10, 15, 20	Low, Mid, High	Full RB	0
		Spurious and Harmonic Emissions at Antenna Terminal	QPSK	5, 10, 15, 20	Low, Mid, High	1	0

## 4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/17/2018	Annual	04/17/2019
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/04/2018	Annual	04/04/2019
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/04/2018	Annual	04/04/2019
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	5001	06/07/2018	Annual	06/07/2019
Agilent	E3632A/DC Power Supply	KR75303243	05/09/2018	Annual	05/09/2019
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	93000718	08/07/2018	Annual	08/07/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/14/2018	Annual	09/14/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	10/04/2018	Annual	10/04/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY52090906	06/08/2018	Annual	06/08/2019
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/21/2018	Annual	06/21/2019
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/22/2018	Annual	10/22/2019
Agilent	8960 (E5515C)/ Base Station	MY48360800	09/27/2018	Annual	09/27/2019
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	04/06/2017	Biennial	04/06/2019
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/13/2018	Annual	08/13/2019
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/19/2018	Annual	07/19/2019
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	07/27/2018	Annual	07/27/2019
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

**Note:**

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

## **5. MEASUREMENT UNCERTAINTY**

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

<b>Parameter</b>	<b>Expanded Uncertainty (<math>\pm</math>dB)</b>
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71



## 6. SUMMARY OF TEST RESULTS

### 6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(m)(4)	<ul style="list-style-type: none"> <li>■ <math>&lt; 40 + 10\log_{10} (P[\text{Watts}])</math> at Channel edges</li> <li>■ <math>&lt; 43 + 10\log_{10} (P[\text{Watts}])</math> between 5 and X MHz from Channel edges</li> <li>■ <math>&lt; 55 + 10\log_{10} (P[\text{Watts}])</math> beyond X MHz beyond from Channel edges</li> <li>■ <math>&lt; 43 + 10 \log (P)</math> dB on all frequencies between 2490.5 MHz and 2496 MHz</li> </ul>	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

**Note:**

1. See SAR Report

### 6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§27.50(h)(2)	$< 2$ Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(m)(4)	$< 55 + 10\log_{10} (P[\text{Watts}])$	PASS

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

#### ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
40620	2593.0	-15.75	18.45	9.90	1.76	H	0.456	26.59

#### EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

### 7.3. Emission Designator

#### GSM Emission Designator

**Emission Designator = 249KGXW**

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

#### EDGE Emission Designator

**Emission Designator = 249KG7W**

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

#### WCDMA Emission Designator

**Emission Designator = 4M17F9W**

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

#### QPSK Modulation

**Emission Designator = 4M48G7D**

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

#### 16QAM Modulation

**Emission Designator = 4M48W7D**

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

#### 64QAM Modulation

**Emission Designator = 4M48W7D**

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

## 8. TEST DATA

### 8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2557.5	LTE B41/ 5 MHz	QPSK	-21.27	13.57	11.02	1.62	H	< 2.00	0.198	22.97
		16-QAM	-22.26	12.58	11.02	1.62	H		0.158	21.98
		64-QAM	-23.30	11.54	11.02	1.62	H		0.124	20.94
2605.0		QPSK	-23.04	11.78	11.07	1.64	H		0.132	21.21
		16-QAM	-23.66	11.16	11.07	1.64	H		0.115	20.59
		64-QAM	-24.70	10.12	11.07	1.64	H		0.090	19.55
2652.5		QPSK	-25.90	8.95	11.15	1.66	H		0.070	18.44
		16-QAM	-26.25	8.60	11.15	1.66	H		0.064	18.09
		64-QAM	-27.26	7.59	11.15	1.66	H		0.051	17.08

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2560.0	LTE B41/ 10 MHz	QPSK	-21.37	13.47	11.02	1.62	H	< 2.00	0.194	22.87
		16-QAM	-22.38	12.46	11.02	1.62	H		0.154	21.86
		64-QAM	-23.45	11.39	11.02	1.62	H		0.120	20.79
2605.0		QPSK	-22.67	12.15	11.07	1.64	H		0.144	21.58
		16-QAM	-23.32	11.50	11.07	1.64	H		0.124	20.93
		64-QAM	-24.41	10.41	11.07	1.64	H		0.096	19.84
2650.0		QPSK	-25.42	9.43	11.15	1.66	H		0.078	18.92
		16-QAM	-25.87	8.98	11.15	1.66	H		0.070	18.47
		64-QAM	-26.88	7.97	11.15	1.66	H		0.056	17.46

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
									W	W
2562.5	LTE B41/ 15 MHz	QPSK	-21.15	13.69	11.02	1.62	H	< 2.00	0.204	23.09
		16-QAM	-21.88	12.96	11.02	1.62	H		0.172	22.36
		64-QAM	-22.92	11.92	11.02	1.62	H		0.136	21.32
2605.0		QPSK	-22.95	11.86	11.07	1.64	H		0.135	21.29
		16-QAM	-23.58	11.23	11.07	1.64	H		0.116	20.66
		64-QAM	-24.62	10.19	11.07	1.64	H		0.092	19.62
2647.5		QPSK	-25.37	9.48	11.15	1.66	H		0.079	18.97
		16-QAM	-25.81	9.04	11.15	1.66	H		0.071	18.53
		64-QAM	-26.80	8.05	11.15	1.66	H		0.057	17.54

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
									W	W
2565.0	LTE B41/ 20 MHz	QPSK	-21.22	13.62	11.02	1.63	H	< 2.00	0.200	23.01
		16-QAM	-21.95	12.89	11.02	1.63	H		0.169	22.28
		64-QAM	-23.03	11.81	11.02	1.63	H		0.132	21.20
2605.0		QPSK	-23.12	11.69	11.07	1.64	H		0.129	21.12
		16-QAM	-23.77	11.04	11.07	1.64	H		0.111	20.47
		64-QAM	-24.86	9.95	11.07	1.64	H		0.087	19.38
2645.0		QPSK	-24.89	10.01	11.13	1.65	H		0.089	19.49
		16-QAM	-25.41	9.49	11.13	1.65	H		0.079	18.97
		64-QAM	-26.40	8.50	11.13	1.65	H		0.063	17.98

**8.2 RADIATED SPURIOUS EMISSIONS**

- ▣ OPERATING FREQUENCY : 2557.50 MHz
- ▣ MEASURED OUTPUT POWER: 22.97 dBm = 0.198 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10}(W) =$  47.97 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40265 (2557.5)	5,115.00	-37.52	12.58	-50.83	2.55	V	-40.80	63.77
	7,672.50	-39.87	12.04	-47.42	2.95	V	-38.33	61.31
	10,230.00	-43.69	11.19	-46.85	3.60	H	-39.26	62.23
	12,787.50	-53.63	13.71	-57.57	4.27	V	-48.13	71.10
40740 (2605.0)	5,210.00	-42.98	13.21	-56.89	2.55	V	-46.23	69.20
	7,815.00	-39.62	11.93	-45.49	2.99	H	-36.55	59.53
	10,420.00	-44.52	10.92	-46.20	3.58	H	-38.86	61.83
	13,025.00	-54.42	13.73	-58.08	4.15	V	-48.49	71.46
41215 (2652.5)	5,305.00	-38.80	13.58	-52.65	2.63	V	-41.70	64.67
	7,957.50	-39.02	11.57	-44.79	3.00	V	-36.22	59.19
	10,610.00	-41.27	10.74	-43.44	3.58	V	-36.28	59.25
	13,262.50	-52.53	13.49	-54.93	3.89	H	-45.33	68.30

- ▣ OPERATING FREQUENCY : 2560.00 MHz
- ▣ MEASURED OUTPUT POWER: 22.87 dBm = 0.194 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10}(W) =$  47.87 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40290 (2560.0)	5,120.00	-39.30	12.60	-52.84	2.54	V	-42.78	65.65
	7,680.00	-39.46	12.04	-47.49	2.94	V	-38.39	61.26
	10,240.00	-47.76	11.13	-50.96	3.59	V	-43.42	66.29
	12,800.00	-54.61	13.73	-58.54	4.23	V	-49.04	71.91
40740 (2605.0)	5,210.00	-42.11	13.21	-56.02	2.55	V	-45.36	68.23
	7,815.00	-40.29	11.93	-46.16	2.99	V	-37.22	60.10
	10,420.00	-48.02	10.92	-49.70	3.58	V	-42.36	65.23
	13,025.00	-54.15	13.73	-57.81	4.15	V	-48.22	71.09
41190 (2650.0)	5,300.00	-39.05	13.58	-52.89	2.61	V	-41.92	64.79
	7,950.00	-38.23	11.58	-43.22	3.01	V	-34.65	57.52
	10,600.00	-41.80	10.73	-44.69	3.58	V	-37.54	60.41
	13,250.00	-53.88	13.50	-56.41	3.79	V	-46.70	69.58
	15,900.00	-53.87	17.33	-59.12	4.44	V	-46.23	69.10

- OPERATING FREQUENCY : 2562.50 MHz
- MEASURED OUTPUT POWER: 23.09 dBm = 0.204 W
- MODE: LTE B41
- MODULATION SIGNAL: 15 MHz QPSK
- DISTANCE: 1 meters
- LIMIT:  $55 + 10 \log_{10}(W) =$  48.09 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40315 (2562.5)	5,125.00	-38.10	12.64	-51.72	2.53	V	-41.61	64.70
	7,687.50	-39.17	12.04	-47.10	2.98	V	-38.04	61.13
	10,250.00	-48.34	11.06	-51.58	3.58	V	-44.10	67.19
	12,812.50	-52.67	13.71	-56.71	4.26	V	-47.26	70.35
40740 (2605.0)	5,210.00	-42.66	13.21	-56.57	2.55	V	-45.91	69.00
	7,815.00	-40.39	11.93	-46.26	2.99	V	-37.32	60.42
	10,420.00	-49.87	10.92	-51.55	3.58	V	-44.21	67.30
	13,025.00	-55.63	13.73	-59.29	4.15	V	-49.70	72.79
41165 (2647.5)	5,295.00	-37.74	13.57	-51.46	2.61	V	-40.50	63.59
	7,942.50	-38.21	11.62	-43.60	2.98	V	-34.96	58.05
	10,590.00	-39.77	10.73	-42.93	3.58	V	-35.78	58.87
	13,237.50	-52.54	13.54	-55.44	3.92	V	-45.82	68.92
	15,885.00	-53.57	17.35	-58.80	4.54	V	-45.99	69.08



- ▣ OPERATING FREQUENCY : 2565.00 MHz
- ▣ MEASURED OUTPUT POWER: 23.01 dBm = 0.200 W
- ▣ MODE: LTE B41
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT:  $55 + 10 \log_{10}(W) =$  48.01 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40340 (2565.0)	5,130.00	-37.63	12.68	-51.34	2.52	V	-41.18	64.19
	7,695.00	-38.49	12.04	-46.00	3.00	V	-36.95	59.96
	10,260.00	-47.86	11.06	-51.23	3.53	V	-43.70	66.71
	12,825.00	-52.80	13.67	-56.97	4.24	V	-47.54	70.55
40740 (2605.0)	5,210.00	-41.86	13.21	-55.77	2.55	V	-45.11	68.12
	7,815.00	-41.86	11.93	-47.73	2.99	V	-38.79	61.81
	10,420.00	-48.27	10.92	-49.95	3.58	V	-42.61	65.62
	13,025.00	-55.51	13.73	-59.17	4.15	V	-49.58	72.59
41140 (2645.0)	5,290.00	-38.77	13.55	-52.37	2.60	V	-41.42	64.43
	7,935.00	-37.58	11.65	-42.89	2.99	V	-34.24	57.25
	10,580.00	-40.23	10.72	-43.04	3.60	V	-35.92	58.93
	13,225.00	-52.44	13.59	-55.41	4.10	V	-45.91	68.92
	15,870.00	-53.80	17.35	-58.77	4.55	V	-45.97	68.98

**8.3 OCCUPIED BANDWIDTH**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )
41	5 MHz	2605.0	QPSK	25	0	4.4983
			16-QAM			4.5069
			64-QAM			4.4815
	10 MHz		QPSK	50		8.9611
			16-QAM			8.9657
			64-QAM			8.9411
	15 MHz		QPSK	75		13.409
			16-QAM			13.453
			64-QAM			13.447
	20 MHz		QPSK	100		17.924
			16-QAM			17.852
			64-QAM			17.884

**Note:**

1. Plots of the EUT's Occupied Bandwidth are shown Page 51 ~ 62.

**8.4 CONDUCTED SPURIOUS EMISSIONS**

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
41	5	2557.5	7.6665	28.591	-66.207	-37.616	-25.00
		2605.0	7.8091	28.591	-65.514	-36.923	
		2652.5	7.9646	28.591	-66.001	-37.410	
	10	2560.0	26.1226	30.131	-66.330	-36.199	
		2605.0	7.8011	28.591	-66.599	-38.008	
		2650.0	26.3787	30.131	-66.961	-36.830	
	15	2562.5	7.6685	28.591	-66.015	-37.424	
		2605.0	26.1688	30.131	-66.272	-36.141	
		2647.5	25.8260	30.131	-66.850	-36.719	
	20	2565.0	7.6690	28.591	-66.134	-37.543	
		2605.0	7.7887	28.591	-66.131	-37.540	
		2645.0	26.1683	30.131	-66.403	-36.272	

**Note:**

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 83 ~ 110.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

**8.5 CHANNEL EDGE**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
Band 41	5 MHz	2557.5	QPSK	25	0	-24.84	-24.75	-23.49	-22.45
		2605.0	QPSK	25	0	-25.78	-25.68	-22.34	-21.80
		2652.5	QPSK	25	0	-25.60	-25.84	-24.97	-23.66
	10 MHz	2560.0	QPSK	50	0	-26.72	-24.85	-27.01	-26.07
		2605.0	QPSK	50	0	-27.06	-27.44	-27.85	-26.44
		2650.0	QPSK	50	0	-27.06	-25.85	-26.13	-24.31
	15 MHz	2562.5	QPSK	75	0	-25.43	-24.96	-25.58	-24.79
		2605.0	QPSK	75	0	-28.31	-28.41	-27.45	-26.18
		2647.5	QPSK	75	0	-29.13	-28.25	-28.64	-27.16
	20 MHz	2565.0	QPSK	100	0	-25.32	-25.34	-27.37	-25.63
		2605.0	QPSK	100	0	-28.64	-28.29	-27.74	-27.05
		2645.0	QPSK	100	0	-30.01	-28.51	-29.04	-27.93
Limit						-10.0		-10.0	
Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
						Lower	Upper	Lower	Upper
Band 41	5 MHz	2557.5	QPSK	25	0	-33.14	-34.62	-33.30	-34.96
		2605.0	QPSK	25	0	-32.10	-31.72	-32.23	-31.64
		2652.5	QPSK	25	0	-30.63	-29.81	-33.71	-32.80
	10 MHz	2560.0	QPSK	50	0	-29.41	-30.92	-36.43	-39.08
		2605.0	QPSK	50	0	-29.13	-26.22	-36.61	-33.79
		2650.0	QPSK	50	0	-30.15	-26.41	-35.96	-33.65
	15 MHz	2562.5	QPSK	75	0	-28.05	-27.95	-34.55	-35.80
		2605.0	QPSK	75	0	-29.57	-26.79	-38.97	-35.57
		2647.5	QPSK	75	0	-30.88	-26.95	-38.46	-34.89
	20 MHz	2565.0	QPSK	100	0	-30.08	-28.99	-36.94	-37.98
		2605.0	QPSK	100	0	-30.51	-27.82	-39.58	-36.12
		2645.0	QPSK	100	0	-31.18	-28.14	-40.80	-36.68
Limit						-13.0		-25.0	


**Note:**

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth.
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. Plots of the EUT's Channel Edge are shown Page 63 ~ 82. (1RB & Full RB)

**8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE**


- MODE: LTE 41
- OPERATING FREQUENCY: 2557,500,000 Hz
- BANDWIDTH: 40265 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2557 499 902	0.0	0.000 000	0.000
100%		-30	2557 499 787	-114.5	-0.000 004	-0.045
100%		-20	2557 500 034	132.8	0.000 005	0.052
100%		-10	2557 500 061	159.8	0.000 006	0.062
100%		0	2557 499 783	-118.2	-0.000 005	-0.046
100%		+10	2557 500 054	152.6	0.000 006	0.060
100%		+30	2557 500 043	141.4	0.000 006	0.055
100%		+40	2557 500 046	144.3	0.000 006	0.056
100%		+50	2557 499 790	-111.9	-0.000 004	-0.044
Batt. Endpoint		3.600	+20	2557 499 794	-107.7	-0.000 004




- MODE: LTE 41
- OPERATING FREQUENCY: 2560,000,000 Hz
- BANDWIDTH: 40290 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2560 000 109	0.0	0.000 000	0.000
100%		-30	2560 000 271	161.4	0.000 006	0.063
100%		-20	2559 999 990	-118.7	-0.000 005	-0.046
100%		-10	2559 999 992	-117.4	-0.000 005	-0.046
100%		0	2560 000 262	153.0	0.000 006	0.060
100%		+10	2560 000 248	138.4	0.000 005	0.054
100%		+30	2560 000 273	164.0	0.000 006	0.064
100%		+40	2560 000 240	131.3	0.000 005	0.051
100%		+50	2560 000 282	173.0	0.000 007	0.068
Batt. Endpoint	3.600	+20	2560 000 275	166.0	0.000 006	0.065




- MODE: LTE 41
- OPERATING FREQUENCY: 2562,500,000 Hz
- BANDWIDTH: 40315 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2562 500 143	0.0	0.000 000	0.000
100%		-30	2562 500 315	171.9	0.000 007	0.067
100%		-20	2562 499 992	-151.6	-0.000 006	-0.059
100%		-10	2562 499 992	-151.8	-0.000 006	-0.059
100%		0	2562 500 004	-139.4	-0.000 005	-0.054
100%		+10	2562 499 996	-147.1	-0.000 006	-0.057
100%		+30	2562 499 999	-144.1	-0.000 006	-0.056
100%		+40	2562 500 332	188.8	0.000 007	0.074
100%		+50	2562 500 002	-141.7	-0.000 006	-0.055
Batt. Endpoint	3.600	+20	2562 500 003	-140.6	-0.000 005	-0.055



- MODE: LTE 41
- OPERATING FREQUENCY: 2565,000,000 Hz
- BANDWIDTH: 40340 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2565 000 192	0.0	0.000 000	0.000
100%		-30	2565 000 381	189.1	0.000 007	0.074
100%		-20	2565 000 348	155.3	0.000 006	0.061
100%		-10	2565 000 405	212.4	0.000 008	0.083
100%		0	2565 000 384	191.4	0.000 007	0.075
100%		+10	2565 000 373	180.3	0.000 007	0.070
100%		+30	2565 000 058	-134.0	-0.000 005	-0.052
100%		+40	2565 000 379	187.0	0.000 007	0.073
100%		+50	2565 000 377	185.0	0.000 007	0.072
Batt. Endpoint	3.600	+20	2565 000 369	176.5	0.000 007	0.069






- MODE: LTE 41
- OPERATING FREQUENCY: 2605,000,000 Hz
- BANDWIDTH: 40740 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2605 000 147	0.0	0.000 000	0.000
100%		-30	2605 000 248	100.6	0.000 004	0.039
100%		-20	2605 000 306	158.2	0.000 006	0.061
100%		-10	2605 000 276	128.4	0.000 005	0.049
100%		0	2605 000 302	154.2	0.000 006	0.059
100%		+10	2605 000 250	102.9	0.000 004	0.040
100%		+30	2605 000 312	164.9	0.000 006	0.063
100%		+40	2605 000 274	126.2	0.000 005	0.048
100%		+50	2605 000 057	2605 000 057	-89.9	-0.000 003
Batt. Endpoint	3.600	+20	2605 000 306	158.5	0.000 006	0.061




- MODE: LTE 41
- OPERATING FREQUENCY: 2605,000,000 Hz
- BANDWIDTH: 40740 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2605 000 142	0.0	0.000 000	0.000
100%		-30	2605 000 274	132.0	0.000 005	0.051
100%		-20	2605 000 041	-100.5	-0.000 004	-0.039
100%		-10	2605 000 302	160.6	0.000 006	0.062
100%		0	2605 000 299	157.5	0.000 006	0.060
100%		+10	2605 000 308	166.9	0.000 006	0.064
100%		+30	2605 000 291	149.0	0.000 006	0.057
100%		+40	2605 000 026	-115.9	-0.000 004	-0.044
100%		+50	2605 000 021	-120.9	-0.000 005	-0.046
Batt. Endpoint	3.600	+20	2605 000 274	132.0	0.000 005	0.051




- MODE: LTE 41
- OPERATING FREQUENCY: 2605,000,000 Hz
- BANDWIDTH: 40740 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2605 000 166	0.0	0.000 000	0.000
100%		-30	2605 000 343	176.8	0.000 007	0.068
100%		-20	2605 000 345	178.7	0.000 007	0.069
100%		-10	2605 000 316	149.8	0.000 006	0.058
100%		0	2605 000 353	186.2	0.000 007	0.071
100%		+10	2605 000 341	174.2	0.000 007	0.067
100%		+30	2605 000 354	187.6	0.000 007	0.072
100%		+40	2605 000 273	107.0	0.000 004	0.041
100%		+50	2605 000 352	186.1	0.000 007	0.071
Batt. Endpoint	3.600	+20	2605 000 326	159.8	0.000 006	0.061




- MODE: LTE 41
- OPERATING FREQUENCY: 2605,000,000 Hz
- BANDWIDTH: 40740 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2605 000 185	0.0	0.000 000	0.000
100%		-30	2605 000 315	130.3	0.000 005	0.050
100%		-20	2605 000 368	182.8	0.000 007	0.070
100%		-10	2605 000 370	184.9	0.000 007	0.071
100%		0	2605 000 377	192.2	0.000 007	0.074
100%		+10	2605 000 357	171.7	0.000 007	0.066
100%		+30	2605 000 371	185.7	0.000 007	0.071
100%		+40	2605 000 361	175.5	0.000 007	0.067
100%		+50	2605 000 374	188.8	0.000 007	0.072
Batt. Endpoint	3.600	+20	2605 000 364	179.3	0.000 007	0.069




- MODE: LTE 41
- OPERATING FREQUENCY: 2652,500,000 Hz
- BANDWIDTH: 41215 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2652 499 887	0.0	0.000 000	0.000
100%		-30	2652 499 776	-110.5	-0.000 004	-0.042
100%		-20	2652 499 788	-99.2	-0.000 004	-0.037
100%		-10	2652 499 777	-109.4	-0.000 004	-0.041
100%		0	2652 499 784	-102.8	-0.000 004	-0.039
100%		+10	2652 500 016	129.6	0.000 005	0.049
100%		+30	2652 499 778	-108.9	-0.000 004	-0.041
100%		+40	2652 499 986	99.2	0.000 004	0.037
100%		+50	2652 499 975	87.9	0.000 003	0.033
Batt. Endpoint	3.600	+20	2652 499 975	88.7	0.000 003	0.033




- MODE: LTE 41
- OPERATING FREQUENCY: 2650,000,000 Hz
- BANDWIDTH: 41190 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2650 000 128	0.0	0.000 000	0.000
100%		-30	2650 000 060	-67.8	-0.000 003	-0.026
100%		-20	2650 000 241	112.5	0.000 004	0.042
100%		-10	2650 000 232	104.1	0.000 004	0.039
100%		0	2650 000 056	-72.4	-0.000 003	-0.027
100%		+10	2650 000 221	93.1	0.000 004	0.035
100%		+30	2650 000 257	128.5	0.000 005	0.048
100%		+40	2650 000 063	-64.6	-0.000 002	-0.024
100%		+50	2650 000 236	107.6	0.000 004	0.041
Batt. Endpoint	3.600	+20	2650 000 212	83.9	0.000 003	0.032




- MODE: LTE 41
- OPERATING FREQUENCY: 2647,500,000 Hz
- BANDWIDTH: 41165 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2647 500 087	0.0	0.000 000	0.000
100%		-30	2647 500 156	68.9	0.000 003	0.026
100%		-20	2647 500 005	-81.7	-0.000 003	-0.031
100%		-10	2647 500 183	96.0	0.000 004	0.036
100%		0	2647 500 175	87.8	0.000 003	0.033
100%		+10	2647 500 002	-85.5	-0.000 003	-0.032
100%		+30	2647 500 006	-80.8	-0.000 003	-0.031
100%		+40	2647 500 165	78.1	0.000 003	0.029
100%		+50	2647 500 182	94.7	0.000 004	0.036
Batt. Endpoint	3.600	+20	2647 500 014	-73.0	-0.000 003	-0.028



- MODE: LTE 41
- OPERATING FREQUENCY: 2645,000,000 Hz
- BANDWIDTH: 41140 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2644 999 936	0.0	0.000 000	0.000
100%		-30	2645 000 010	74.4	0.000 003	0.028
100%		-20	2644 999 868	-67.7	-0.000 003	-0.026
100%		-10	2644 999 864	-71.7	-0.000 003	-0.027
100%		0	2644 999 859	-76.9	-0.000 003	-0.029
100%		+10	2644 999 864	-71.6	-0.000 003	-0.027
100%		+30	2644 999 867	-69.0	-0.000 003	-0.026
100%		+40	2645 000 019	82.7	0.000 003	0.031
100%		+50	2644 999 879	-56.6	-0.000 002	-0.021
Batt. Endpoint		3.600	+20	2645 000 005	69.0	0.000 003





## 8.7 GEO-LOCATION MECHANISM

The device uses a geo-location mechanism based on the cellular MCC codes in order to only enable certain LTE bands when the device is not in the USA.


The validation of this mechanism is provided below. The device was configured for cellular communications to a test set and the MCC code was adjusted on the test set between the US MCC and then an MCC code valid for a country where the LTE band is supported.


Band	MCC = USA	MCC = non US
7	Did not connect	Connected (Canada)
38	Did not connect	Connected (Canada)
40	Did not connect	Connected (Canada)
41	Connected	Connected (Canada)


The verification tests confirmed the operational of the geo-location mechanism.

**Verification test**









**Connected(LTE B41)**  
**(MCC = US)**

---

2019/02/28 10:08
Connected
Phone-2
Phone-1

<Fundamental Measurement> Output Main
Continuous
---
LTE

Parameter
Fundamental
UE Report
Band Cal.

Measuring (Spectrum)
UE Power : 25.9 dBm
Parameter

Modulation Analysis View
(Meas. Count : 10 / 10)

Carrier Frequency
Avg.
2605.000000 MHz

Carrier Frequency Error

Avg.	Max.	Min.	Limit
0.0000	0.0051	-0.0055	
0.00	0.00	0.00	ppm

DCNG (Connected)
On

DCNG Power
(RA : 0.0dB, RB : 0.0dB)

0.0 dB

Call Processing Parameter

Base Station Identity

Cell ID
0

MCC
311

MNC
01

TAC
0001 H

Mobile Station Identity


IMSI
001010123456789

Paging IMSI
Auto

C-RNTI
AAAA H

1 | 2 | 3 | 4 |

Normal Test Parameter
Idle/Call \* Test Parameter
TX-1 \* Test Parameter
TX-2 \* Test Parameter
TX-3 \* Test Parameter
RX \* Test Parameter



**Did not connect (LTE B38)**  
**(MCC = US)**

---

2019/02/28 16:41      Idle      Phone-2      Phone-1  
 <Fundamental Measurement> Output Main      Continuous      ---      LTE

Parameter      Fundamental      UE Report      Band Cal.

Reference Signal not found      UE Power :      -16.9 dBm

Modulation Analysis      View      (Meas. Count :      1/ 10)

Carrier Frequency      Avg.      \*\*\*\*\* MHz

	Avg.	Max.	Min.	Limit
Carrier Frequency Error	*****	*****	*****	kHz
	*****	*****	*****	mm

OCNG (Connected)      On

OCNG Power      (RA :      0.0dB, RB :      0.0dB)  
 0.0 dB

**Call Processing Parameter**

Base Station Identity

Cell ID	0
MCC	311
MNC	01
TAC	0001 H

Mobile Station Identity

IMSI	001010123456789
Paging IMSI	Auto
C-RNTI	AAAA H

Parameter

Normal Test Parameter

Idle/Call \* Test Parameter

TX-1 \* Test Parameter


TX-2 \* Test Parameter

TX-3 \* Test Parameter

RX \* Test Parameter


1 | 2 | 3 | 4






## **9. TEST PLOTS**


BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40740 QPSK RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40740 16-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40740 64-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40740 QPSK RB 50)



BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40740 16-QAM RB 50)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40740 64-QAM RB 50)







BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40740 QPSK RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40740 16-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40740 64-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40740 QPSK RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40740 16-QAM RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40740 64-QAM RB 100)



BAND 41. Low Channel Edge Plot (5 MHz Ch.40265 QPSK RB 1, Offset 0)-1




BAND 41. Low Channel Edge Plot (5 MHz Ch.40265 QPSK\_RB25\_Offset 0)-2






BAND 41. Mid Channel Edge Plot (5 MHz Ch.40740 QPSK RB 25)



BAND 41. High Channel Edge Plot (5 MHz Ch.41215 QPSK RB 1, Offset 0)-1



BAND 41. High Channel Edge Plot (5 MHz Ch.41215 QPSK\_RB25\_Offset 0)-2

