

# **CERTIFICATION TEST REPORT**

# **Report Number. :** 12726913-E7V1

- Applicant : Samsung Electronics Co., Ltd. 129 Samsung-Ro, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do, 16677, Korea
  - Model : SM-A705GM/DS
  - FCC ID : A3LSMA705GM
- **EUT Description :** GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, ANT+, NFC and MST
- Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue: April 05, 2019

Prepared by: UL Verification Services Inc. 47173 Benicia Street Fremont, CA 94538 U.S.A. TEL: (510) 771-1000 FAX: (510) 661-0888



# **Revision History**

Rev.	lssue Date	Revisions	Revised By
V1	4/5/2019	Initial Issue	

Page 2 of 33

# TABLE OF CONTENTS

1.	AT	TESTATION OF TEST RESULTS	4
2.	TES	ST METHODOLOGY	.5
3.	FAG	CILITIES AND ACCREDITATION	.5
4.	CAI	LIBRATION AND UNCERTAINTY	.6
4	.1.	MEASURING INSTRUMENT CALIBRATION	.6
4	.2.	SAMPLE CALCULATION	.6
4	.3.	MEASUREMENT UNCERTAINTY	.6
5.	EQ	UIPMENT UNDER TEST	.7
5	.1.	DESCRIPTION OF EUT	.7
5	.2.	MAXIMUM FIELD STRENGTH	.7
5	.3.	DESCRIPTION OF AVAILABLE ANTENNAS	.7
5	.4.	SOFTWARE AND FIRMWARE	.7
5	.5.	WORST-CASE CONFIGURATION AND MODE	.7
5	.6.	DESCRIPTION OF TEST SETUP	.8
6.	TES	ST AND MEASUREMENT EQUIPMENT1	0
6. 7.		ST AND MEASUREMENT EQUIPMENT1 CUPIED BANDWIDTH	0 1
6. 7. 7	TES OC	ST AND MEASUREMENT EQUIPMENT1 CUPIED BANDWIDTH	0 1 2
6. 7. 7 7	TES OC .1. .2.	ST AND MEASUREMENT EQUIPMENT	0 1 2 4
6. 7. 7 7 7	TES OC 7.1. 7.2. 7.3.	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1	0 1 2 4 6
<ol> <li>6.</li> <li>7.</li> <li>7</li> <li>7</li> <li>7</li> <li>8.</li> </ol>	TES OC .1. .2. .3. RAI	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS.       1	<b>0</b> 1 12 14 16 <b>7</b>
<ol> <li>6.</li> <li>7.</li> <li>7</li> <li>7</li> <li>8.</li> <li>8</li> </ol>	TES OC 2.1. 2.2. 2.3. RAI 2.1.	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS       1         LIMITS AND PROCEDURE       1	0 1 12 14 16 7
<ol> <li>6.</li> <li>7.</li> <li>7</li> <li>7</li> <li>8.</li> <li>8</li> <li>8</li> </ol>	TES OC .1. .2. .3. RAI .1. .2.	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS       1         LIMITS AND PROCEDURE       1         FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)       1	0 1 12 14 16 7 7 17
6. 7. 7 7 8. 8 8 8	TES OC .1. .2. .3. RAI .1. .2. .3.	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS       1         LIMITS AND PROCEDURE       1         FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)       1         TX SPURIOUS EMISSION 30 TO 1000 MHz       2	0 1 12 14 16 7 17 19 22
6. 7. 7 8. 8. 8 8 9.	TES OC .1. .2. .3. RAI .1. .2. .3. FRE	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS       1         LIMITS AND PROCEDURE       1         FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)       1         TX SPURIOUS EMISSION 30 TO 1000 MHz       2         EQUENCY STABILITY       2	0 1 12 14 16 7 17 19 22 24
<ol> <li>6.</li> <li>7.</li> <li>7</li> <li>8.</li> <li>8</li> <li>8</li> <li>8</li> <li>9.</li> <li>10.</li> </ol>	TES OC .1. .2. .3. RAI .2. .3. FRI A	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS       1         LIMITS AND PROCEDURE       1         FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)       1         TX SPURIOUS EMISSION 30 TO 1000 MHz       2         EQUENCY STABILITY       2         C MAINS LINE CONDUCTED EMISSIONS       2	0 1 2 4 6 7 7 9 2 2 4 8 6
6. 7. 7 8. 8 8 9. 10.	TES OC .1. .2. .3. RAI .1. .2. .3. FRE 10. .10.	ST AND MEASUREMENT EQUIPMENT       1         CUPIED BANDWIDTH       1         Type A       1         Type B       1         Type F       1         DIATED EMISSION TEST RESULTS       1         LIMITS AND PROCEDURE       1         FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)       1         TX SPURIOUS EMISSION 30 TO 1000 MHz       2         EQUENCY STABILITY       2         I.1       NORMAL OPERATION with ANTENNA         1.2       NORMAL OPERATION with ANTENNA TERMINATED	0 1 2 4 6 7 7 9 22 4 29

# **1. ATTESTATION OF TEST RESULTS**

COMPANY NAME:	Samsung Electronics Co., Ltd. 129 Samsung-Ro, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do, 16677, Korea
EUT DESCRIPTION:	GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, ANT+, NFC and MST
MODEL:	SM-A705GM/DS
SERIAL NUMBER:	Radiated: R38M208LZKY and R38M208M5YB
DATE TESTED:	March 13 – April 04, 2019

APPLICABLE STANDARDS				
STANDARD	TEST RESULTS			
FCC PART 15 SUBPART C Complies				

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For UL Verification Services Inc. By:

Reviewed By:

Dan Coronia Operations Leader Consumer Technology Division UL Verification Services Inc.

Kiya Kedida Project Engineer Consumer Technology Division UL Verification Services Inc.

Page 4 of 33

# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, and FCC CFR 47 Part 15.

# 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd
Chamber A (ISED:2324B-1)	Chamber D (ISED:22541-1)	Chamber I (ISED:2324A-5)
Chamber B (ISED:2324B-2)	Chamber E (ISED:22541-2)	Chamber J (ISED:2324A-6)
Chamber C (ISED:2324B-3)	Chamber F (ISED:22541-3)	Chamber K (ISED:2324A-1)
	Chamber G (ISED:22541-4)	Chamber L (ISED:2324A-3)
	Chamber H (ISED:22541-5)	

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers above are covered under Industry Canada company address and respective code

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0

Page 5 of 33

# 4. CALIBRATION AND UNCERTAINTY

# 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

# 4.2. SAMPLE CALCULATION

# RADIATED EMISSIONS

Where relevant, the following sample calculation is provided: Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB - 26.9 dB = 28.9 dBuV/m

# MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided: Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss. 36.5 dBuV + 0 dB + 10.1 dB + 0 dB = 46.6 dBuV

# 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

Page 6 of 33

# 5. EQUIPMENT UNDER TEST

# 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE phone with BT,DTS/UNII a/b/g/n/ac, ANT+, NFC and MST.

# 5.2. MAXIMUM FIELD STRENGTH

The testing was performed at 3 meters. The transmitter maximum E-field at 30 meter distance was 13.77 dBuV/m, which was converted from the 3 meter data.

# 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes the loop antenna.

# 5.4. SOFTWARE AND FIRMWARE

The test utility software used during testing was A705GM.001.

# 5.5. WORST-CASE CONFIGURATION AND MODE

The fundamental of the EUT was investigated under three orthogonal orientations X (Flatbed), Y (Landscape), and Z (Portrait). The Z (Portrait) orientation was determined to be the worst-case orientation.

Although these tests were performed other than open filed site, adequate comparison measurements were confirmed against 30 m open filed site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788

**NOTE:** The EUT pre-scanned in three NFC type A, B & F. The worst type is A, and data rate of 106kbps was recorded to this report.

Page 7 of 33

# 5.6. DESCRIPTION OF TEST SETUP

#### SUPPORT EQUIPMENT

Support Equipment List					
Description	Manufacturer	Model	Serial Number	FCC ID	
AC Adapter	Samsung	EP-TA50EWE	DW3J719AS/A-E	N/A	
Earphone	Samsung	N/A	N/A	N/A	

### I/O CABLES (CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	RF	Shielded	0.2	To PSA
2	USB	1	USB	Un-shielded	1	EUT to AC Mains

### I/O CABLES (RADIATED AND CONDUCTED EMISSIONS)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	USB	1	USB	Shielded	1	N/A
2	earphone	1	3.5mm	Un-shielded	1	N/A

### TEST SETUP

The EUT is a stand alone. Test software exercised the radio card.

Page 8 of 33



# TEST SETUP

For radiated tests: EUT has support equipment. The test software exercises the radio.

Page 9 of 33

# 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST						
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal	
Antenna, Active Loop 9kHz- 30MHz	ETS-Lindgren	6502	T757	09/25/2019	09/25/2018	
Antenna, Passive Loop 30Hz – 1MHz	Electro-Metrics	EM-6871	PRE0179465	05/22/2019	05/22/2018	
Antenna, Passive Loop 100kHz – 30MHz	Electro_Metrics	EM-6872	PRE0179467	05/23/2019	05/23/2018	
EMI TEST RECEIVER	Rohde & Schwarz	ESW44	PRE0179375	05/08/2019	05/08/2018	
Temp Chamber	Thermotron Industries	SE-600-10-10	T80	05/01/2019	11/01/2018	
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T908	01/23/2020	01/23/2019	
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1450	01/24/2020	01/24/2019	
Amplifier, 9kHz to 1GHz, 32 dB	Sonoma Instrument	310	175953	12/13/2019	12/13/2018	
Hybrid Antenna, 30MHz to 3GHz	SunAR rf motion	JB3	PRE0184052	10/24/2019	10/24/2018	
	AC Line Co	onducted				
EMI Receiver	Rohde & Schwarz	ESR	T1436	02/14/2020	02/14/2019	
LISN for Conducted Emissions CISPR-16	FCC INC.	FCC LISN 50/250	T1310	06/15/2019	06/15/2018	
Test Software List						
Radiated Software	UL	UL E	MC	Ver 9.5, Ju	ne 22, 2018	
Antenna Port Software	UL	UL	RF	Ver 9.3.2, Jan. 07, 2019		
AC Line Conducted Software	UL	UL E	MC	Ver 9.5, Ma	ay 26, 2015	

# NOTES:

- 1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
- 2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Page 10 of 33

# 7. OCCUPIED BANDWIDTH

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 10kHz. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

Note: Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW

#### <u>RESULTS</u>

#### 99% and 20dB BW

#### Type A (CE Mode)

Mode Kbps	Frequency (MHz)	99% Bandwidth (KHz)	20dB Bandwidth (KHz)
424	13.56	21.738	24.98
212	13.56	22.279	24.85
106	13.56	24.707	25.39

#### TYPE B

Mode Kbps	Frequency (MHz)	99% Bandwidth (KHz)	20dB Bandwidth (KHz)
424	13.56	21.712	25.06
212	13.56	22.129	25.03
106	13.56	24.458	24.95

#### TYPE F

Mode Kbps	Frequency (MHz)	99% Bandwidth (KHz)	20dB Bandwidth (KHz)
424	13.56	21.160	24.95
212	13.56	21.225	24.96

Page 11 of 33

### <u>424Kbps</u>



#### 212Kbps



Page 12 of 33

#### 106Kbps



Page 13 of 33

# 7.2. Type B





#### 212Kbps



UL VERIFICATION SERVICES INC. 47173 Benicia Street, Fremont, CA 94538; USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 14 of 33

#### 106Kbps



Page 15 of 33

### <u>424Kbps</u>



### 212Kbps



Page 16 of 33

# 8. RADIATED EMISSION TEST RESULTS

# 8.1. LIMITS AND PROCEDURE

# <u>LIMIT</u>

# §15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator										
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)								
0.009 - 0.490	2400 / F (kHz)	300								
0.490 - 1.705	24000 / F (kHz)	30								
1.705 – 30.0	30	30								
30 - 88	100**	3								
88 - 216	150**	3								
216 - 960	200**	3								
Above 960	500	3								

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241. §15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the filed strength from uV/m to dBuV/m is: Limit (dBuV/m) = 20 log limit (uV/m)

Page 17 of 33

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

### TEST PROCEDURE

### ANSI C63.10, 2013

The EUT is an intentional radiator that incorporates a digital device, the highest fundamental frequency generated or used in the device is 13.56 MHz; therefore, the frequency range was investigated from 0.15 MHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater.

2D antenna use - For below 30MHz testing, investigation was done on three antenna orientations (parallel, perpendicular, and ground-parallel), parallel and perpendicular are the worst orientations, therefore testing was performed on these two orientations only.

### KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

# **RESULTS**

Page 18 of 33

# 8.2. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)

# TYPE A - 106Kbps (CE Mode)



# FUNDAMENTAL EMISSION MASK - (11.56 - 15.56 MHz)

NOTE: All data rate Field Strength was investigated and Type A, 106k found to have the highest Field Strength results and represents as the worst case data rate.

Page 19 of 33

# REPORT NO: 12726913-E7V1 FCC ID: A3LSMA705GM

#### Trace Markers

Marker	Frequency	Meter	Det	Loop Antenna	Cables (dB)	Dist Corr 30m	Corrected	FCC 15.225	PK Margin	Azimuth	Polarity
	(11112)	(dBuV)		(ubiii)			dB(uVolts/me	Linint	(ub)	(Degs)	
							ter)				
8	13.02823	16.82	Pk	10.7	.5	-40	-11.98	29.54	-41.52	0-360	Face-Off
1	13.02913	19.95	Pk	10.7	.5	-40	-8.85	29.54	-38.39	0-360	Face-On
2	13.345	26.57	Pk	10.7	.5	-40	-2.23	40.51	-42.74	0-360	Face-On
9	13.34658	24.58	Pk	10.7	.5	-40	-4.22	40.51	-44.73	0-360	Face-Off
10	13.44878	28.36	Pk	10.7	.5	-40	44	50.5	-50.94	0-360	Face-Off
3	13.45175	30.87	Pk	10.7	.5	-40	2.07	50.5	-48.43	0-360	Face-On
11	*13.55793	39.84	Pk	10.6	.5	-40	10.94	84	-73.06	0-360	Face-Off
4	*13.55963	42.67	Pk	10.6	.5	-40	13.77	84	-70.23	0-360	Face-On
12	13.6636	29.72	Pk	10.6	.5	-40	.82	50.5	-49.68	0-360	Face-Off
5	13.6675	31.81	Pk	10.6	.5	-40	2.91	50.5	-47.59	0-360	Face-On
13	13.7692	24.71	Pk	10.6	.5	-40	-4.19	40.51	-44.7	0-360	Face-Off
6	13.7715	27.18	Pk	10.6	.5	-40	-1.72	40.51	-42.23	0-360	Face-On
14	14.08643	18.14	Pk	10.6	.5	-40	-10.76	29.54	-40.3	0-360	Face-Off
7	14.0875	18.76	Pk	10.6	.5	-40	-10.14	29.54	-39.68	0-360	Face-On

\* - Indicates fundamental frequency

Pk - Peak detector

Page 20 of 33

# SPURIOUS EMISSIONS (0.09 – 30MHz)



# **Trace Markers**

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna (ACF)	Cables w/ PRE0186650	Dist Corr 300m	Corrected Reading (dBuVolts)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	.02748	21.14	Pk	58.2	-32.2	-80	-32.86	58.81	-91.67	38.81	-71.67		-		-	0-360
2	.2396	10.5	Pk	56.3	-32.1	-80	-45.3	-	-	-	-	40.03	-85.33	20.03	-65.33	0-360
4	.02729	21.02	Pk	58.2	-32.2	-80	-32.98	58.86	-91.84	38.86	-71.84	-	-	-	-	0-360
5	.26525	11.12	Pk	56.3	-32.1	-80	-44.68	-	-		-	39.14	-83.82	19.14	-63.82	0-360

#### Pk - Peak detector

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna (ACF)	Cables w/ PRE0186650	Dist Corr 30m (dB) 40Log	Corrected Reading (dBuVolts)	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
3	.81509	17.49	Pk	56.3	-32.1	-40	1.69	29.39	-27.7	0-360
6	.8151	17.27	Pk	56.3	-32.1	-40	1.47	29.39	-27.92	0-360
7	13.55998	40.52	Pk	34.3	-31.8	-40	3.02	29.5	-26.48	0-360
8	13.55998	40.4	Pk	34.3	-31.8	-40	2.9	29.5	-26.6	0-360

Pk - Peak detector

Note: Markers 7 and 8 are the 13.56MHz NFC Fundamental

Page 21 of 33

# 8.3. TX SPURIOUS EMISSION 30 TO 1000 MHz

# TYPE A - 106Kbps (CE Mode)





Page 22 of 33

## Trace Markers

Marker	Frequency	Meter	Det	AF PRE0184052	Amp/Cbl	Corrected	QPk Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		(dB/m)	(dB)	Reading	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)				(dBuV/m)					
1	42.4945	45.65	Pk	17.8	-31.4	32.05	40	-7.95	94	330	Н
	42.4725	40.24	Qp	17.8	-31.4	26.64	40	-13.36	94	330	Н
4	30.8077	29.08	Pk	26	-31.6	23.48	40	-16.52	0-360	199	Н
2	42.7904	50.14	Pk	17.5	-31.4	36.24	40	-3.76	198	146	V
	42.7554	45.7	Qp	17.6	-31.4	31.9	40	-8.1	198	146	V
3	30.5226	40.32	Pk	26.1	-31.6	34.82	40	-5.18	111	107	V
	30.6434	34.49	Qp	26.1	-31.6	28.99	40	-11.01	111	107	V
5	60.2678	40.14	Pk	13.4	-31.2	22.34	40	-17.66	0-360	100	V
6	81.3533	43.88	Pk	13.5	-31	26.38	40	-13.62	0-360	100	V

\* - indicates frequency in CFR47 Pt 15 Restricted Band

Pk - Peak detector

Qp - Quasi-Peak detector

Page 23 of 33

# 9. FREQUENCY STABILITY

### <u>LIMIT</u>

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### TEST PROCEDURE

ANSI C63.10-2013 Clause 6.8

### **RESULTS**

ID: 19497 AF Date: 4/4/2019	)
-----------------------------	---

No non-compliance noted.

Page 24 of 33

# TYPE A - 106Kbps (CE Mode)

106Kbps

			Refere	nce Frequency	: EUT Channe	el 13.56 MHz @	20ºC			
			Limit:	± 100 ppm =		1.356	kHz			
Power	Envir.									
Supply	Temp			Frequen	cy Deviation N	leasureed with	n Time Ela	apse		
		Startup	Delta	@ 2 mins	Delta	@ 5 mins	Delta	@ 10 mins	Delta	Limit
(Vdc)	(ºC)	(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(ppm)
3.80	50	13.5597065	7.227	13.5597019	7.570	13.5596975	7.894	13.5596955	8.040	± 100
3.80	40	13.5597620	3.134	13.5597435	4.497	13.5597270	5.717	13.5597116	6.852	± 100
3.80	30	13.5597934	0.817	13.5597915	0.957	13.5597889	1.153	13.5597882	1.201	± 100
3.80	20	13.5598045	0.000	13.5597986	0.437	13.5597966	0.585	13.5597960	0.632	± 100
3.80	10	13.5598449	-2.978	13.5598354	-2.274	13.5598241	-1.441	13.5598188	-1.051	± 100
3.80	0	13.5598445	-2.952	13.5598482	-3.223	13.5598464	-3.086	13.5598451	-2.991	± 100
3.80	-10	13.5597920	0.923	13.5598373	-2.415	13.5598469	-3.126	13.5598449	-2.978	± 100
3.23	20	13.5597960	0.625	13.5597957	0.651	13.5597953	0.680	13.5597942	0.761	± 100
4.37	20	13.5597943	0.755	13.5597941	0.770	13.5597939	0.782	13.5597934	0.817	± 100

Page 25 of 33

# **10. AC MAINS LINE CONDUCTED EMISSIONS**

### LIMITS

### §15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a  $50\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range	Limit	s (dBµV)
(MHz)	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Notes:

1. The lower limit shall apply at the transition frequencies

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### TEST PROCEDURE

ANSI C63.10:2013

### **RESULTS**

No non-compliance noted:

Page 26 of 33

### TYPE A - 106Kbps (CE Mode)

# 10.1.1. NORMAL OPERATION with ANTENNA

#### LINE 1 RESULTS



#### Worst Emission

Range	Range 1: Line-L1 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L1	LC Cables C1&C3	Limiter (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR) Margin (dB)	
1	.1635	35.45	Qp	.1	0	10.1	45.65	65.28	-19.63	-	-	
2	.16125	20.82	Ca	.1	0	10.1	31.02	-	-	55.4	-24.38	
3	.43575	26.55	Qp	0	0	10.1	36.65	57.14	-20.49	-	-	
4	.438	23.52	Ca	0	0	10.1	33.62	-	-	47.1	-13.48	
5	.96675	21.43	Qp	0	.1	10.1	31.63	56	-24.37	-	-	
6	.969	18.29	Ca	0	.1	10.1	28.49	-	-	46	-17.51	
7	3.18975	24.55	Qp	0	.1	10.1	34.75	56	-21.25	-	-	
8	3.192	16.97	Ca	0	.1	10.1	27.17	-	-	46	-18.83	
9	8.90475	42.77	Qp	0	.2	10.2	53.17	60	-6.83	-	-	
10	8.90925	32	Ca	0	.2	10.2	42.4	-	-	50	-7.6	
11	13.56	51.07	Qp	.1	.2	10.2	61.57	60	1.57	-	-	
12	13.56	47.23	Ca	.1	.2	10.2	57.73	-	-	50	7.73	
13	18.1365	20.37	Qp	.1	.3	10.3	31.07	60	-28.93	-	-	
14	18.1365	8.68	Ca	.1	.3	10.3	19.38	-	-	50	-30.62	
15	27.12075	22.81	Qp	.1	.4	10.5	33.81	60	-26.19	-	-	
16	27.12075	15.01	Ca	.1	.4	10.5	26.01	-	-	50	-23.99	

Qp - Quasi-Peak detector

Ca - CISPR average detection

Note: Markers 11 and 12 are the 13.56MHz NFC Fundamental

Page 27 of 33

#### REPORT NO: 12726913-E7V1 FCC ID: A3LSMA705GM LINE 2 RESULTS



#### **Worst Emission**

Range	Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency	Meter	Det	LISN L2	LC Cables	Limiter	Corrected	CFR 47	QP Margin	CFR 47	Av(CISPR)	
	(MHz)	Reading			C2&C3	(dB)	Reading	Part 15	(dB)	Part 15	Margin	
		(dBuV)					dBuV	Class B QP		Class B Avg	(dB)	
17	.1635	35.27	Qp	.1	0	10.1	45.47	65.28	-19.81	-	-	
18	.16125	18.48	Ca	.1	0	10.1	28.68	-	-	55.4	-26.72	
19	.438	24.84	Qp	0	0	10.1	34.94	57.1	-22.16	-	-	
20	.438	17.76	Ca	0	0	10.1	27.86	-	-	47.1	-19.24	
21	.97125	19.01	Qp	0	.1	10.1	29.21	56	-26.79	-	-	
22	.969	13.42	Ca	0	.1	10.1	23.62	-	-	46	-22.38	
23	3.15825	18.45	Qp	0	.1	10.1	28.65	56	-27.35	-	-	
24	3.15825	10.76	Ca	0	.1	10.1	20.96	-	-	46	-25.04	
25	9.0645	37.56	Qp	0	.2	10.2	47.96	60	-12.04	-	-	
26	9.0645	29.35	Ca	0	.2	10.2	39.75	-	-	50	-10.25	
27	13.56	48.25	Qp	.1	.2	10.2	58.75	60	-1.25	-	-	
28	13.56	44.31	Ca	.1	.2	10.2	54.81	-	-	50	4.81	
29	18.1365	15.47	Qp	.1	.3	10.3	26.17	60	-33.83	-	-	
30	18.1365	5.47	Ca	.1	.3	10.3	16.17	-	-	50	-33.83	
31	27.12075	23.35	Qp	.1	.4	10.5	34.35	60	-25.65	-	-	
32	27.12075	15.33	Ca	.1	.4	10.5	26.33	-	-	50	-23.67	

Qp - Quasi-Peak detector Ca - CISPR average detection Note: Markers 27 and 28 are the 13.56MHz NFC Fundamental

Page 28 of 33

# **10.1.2.** NORMAL OPERATION with ANTENNA TERMINATED



#### LINE 1 RESULTS

#### **Worst Emission**

Range	1: Line-L1 .	15 - 30MH	łz								
Marker	Frequency	Meter	Det	LISN L1	LC Cables	Limiter	Corrected	CFR 47	QP Margin	CFR 47	Av(CISPR)
	(MHz)	Reading			C1&C3	(dB)	Reading	Part 15	(dB)	Part 15	Margin
		(dBuV)					dBuV	Class B QP		Class B Avg	(dB)
1	.15225	33.3	Qp	.1	0	10.1	43.5	65.88	-22.38	-	-
2	.15225	20.44	Ca	.1	0	10.1	30.64	-	-	55.88	-25.24
3	.33225	27.69	Qp	0	0	10.1	37.79	59.39	-21.6	-	-
4	.3345	22.48	Ca	0	0	10.1	32.58	-	-	49.34	-16.76
5	.71925	22.28	Qp	0	0	10.1	32.38	56	-23.62	-	-
6	.7215	14.87	Ca	0	0	10.1	24.97	-	-	46	-21.03
7	3.975	25.36	Qp	0	.1	10.1	35.56	56	-20.44	-	-
8	3.9525	18.8	Ca	0	.1	10.1	29	-	-	46	-17
9	8.90025	41.06	Qp	0	.2	10.2	51.46	60	-8.54	-	-
10	8.90025	32.93	Ca	0	.2	10.2	43.33	-	-	50	-6.67
11	18.03975	18.49	Qp	.1	.3	10.3	29.19	60	-30.81	-	-
12	18.042	6.8	Ca	.1	.3	10.3	17.5	-	-	50	-32.5
13	28.14675	17.24	Qp	.1	.4	10.5	28.24	60	-31.76	-	-
14	28.16475	6.43	Ca	.1	.4	10.5	17.43	-	-	50	-32.57

Qp - Quasi-Peak detector

Ca - CISPR average detection

Page 29 of 33

#### REPORT NO: 12726913-E7V1 FCC ID: A3LSMA705GM LINE 2 RESULTS



#### **Worst Emission**

Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency	Meter	Det	LISN L2	LC Cables	Limiter	Corrected	CFR 47	QP Margin	CFR 47	Av(CISPR)
	(MHz)	Reading			C2&C3	(dB)	Reading	Part 15	(dB)	Part 15	Margin
		(dBuV)					dBuV	Class B QP		Class B Avg	(dB)
15	.15225	32.15	Qp	.1	0	10.1	42.35	65.88	-23.53	-	-
16	.15225	17.54	Ca	.1	0	10.1	27.74	-	-	55.88	-28.14
17	.35025	27.38	Qp	0	0	10.1	37.48	58.96	-21.48	-	-
18	.339	18.3	Ca	0	0	10.1	28.4	-	-	49.23	-20.83
19	.74625	19.49	Qp	0	0	10.1	29.59	56	-26.41	-	-
20	.74737	10.92	Ca	0	0	10.1	21.02	-	-	46	-24.98
21	3.93	22.02	Qp	0	.1	10.1	32.22	56	-23.78	-	-
22	3.92775	14.43	Ca	0	.1	10.1	24.63	-	-	46	-21.37
23	8.91825	38.33	Qp	0	.2	10.2	48.73	60	-11.27	-	-
24	8.90925	31.63	Ca	0	.2	10.2	42.03	-	-	50	-7.97
25	17.83725	13.23	Qp	.1	.3	10.3	23.93	60	-36.07	-	-
26	17.83725	6.93	Ca	.1	.3	10.3	17.63	-	-	50	-32.37
27	28.059	19.14	Qp	.1	.4	10.5	30.14	60	-29.86	-	-
28	28.06125	8.57	Ca	.1	.4	10.5	19.57	-	-	50	-30.43

**Qp** - Quasi-Peak detector

Ca - CISPR average detection