




PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctest.com



MEASUREMENT REPORT GSM/GPRS/EDGE/WCDMA

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:
10/5-11/8/2017
Test Site/Location:
PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
1M1710050266-02.A3L

FCC ID:	A3LSMA730F
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type: Certification

Model: SM-A730F/DS

Additional Model(s): SM-A730F

EUT Type: Portable Handset

FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)


FCC Rule Part(s): 22, 24, & 27

ISED Specification: RSS-132 Issue 3, RSS-133 Issue 6, RSS-139 Issue 3

Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President




FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 1 of 84	

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Cellular - Base Frequency Blocks	6
3.3	Cellular - Mobile Frequency Blocks	6
3.4	PCS - Base Frequency Blocks	6
3.5	PCS - Mobile Frequency Blocks	6
3.6	AWS - Base Frequency Blocks	7
3.7	AWS - Mobile Frequency Blocks	7
3.8	Radiated Measurements	7
4.0	MEASUREMENT UNCERTAINTY	9
5.0	TEST EQUIPMENT CALIBRATION DATA	10
6.0	SAMPLE CALCULATIONS	11
7.0	TEST RESULTS	12
7.1	Summary	12
7.2	Occupied Bandwidth	13
7.3	Spurious and Harmonic Emissions at Antenna Terminal	18
7.4	Band Edge Emissions at Antenna Terminal	44
7.5	Peak-Average Ratio	53
7.6	Radiated Power (ERP/EIRP)	56
7.7	Radiated Spurious Emissions Measurements	61
7.8	Frequency Stability / Temperature Variation	73
8.0	CONCLUSION	84

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 2 of 84	



MEASUREMENT REPORT

GSM / GPRS / EDGE / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
GPRS850	22H	824.2 - 848.8	0.719	28.57	1.180	30.72	243KGXW
EDGE850	22H	824.2 - 848.8	0.190	22.78	0.311	24.93	244KG7W
WCDMA850	22H	826.4 - 846.6	0.095	19.76	0.155	21.91	4M13F9W
WCDMA1700	27	1712.4 - 1752.6			0.354	25.50	4M17F9W
GPRS1900	24E	1850.2 - 1909.8			1.585	32.00	245KGXW
EDGE1900	24E	1850.2 - 1909.8			0.653	28.15	244KG7W
WCDMA1900	24E	1852.4 - 1907.6			0.273	24.36	4M16F9W

EUT Overview

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 3 of 84

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 4 of 84	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA730F**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

Test Device Serial No.: 29859, 21518, 29857, 29501, 29909, 24503

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-D-2010 and KDB 971168 D01 v03. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 5 of 84	

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-D-2010) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)


BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

3.5 PCS - Mobile Frequency Blocks


§24.229

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 6 of 84	




3.6 AWS - Base Frequency Blocks

§27.5(h)



3.7 AWS - Mobile Frequency Blocks

§27.5(h)



3.8 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a) §27.50(d)(10) §27.53(h)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 7 of 84

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-D-2010, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/ITA-603-D-2010.

FCC ID: A3LSMA730F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 8 of 84

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 9 of 84	

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX2	Licensed Transmitter Cable Set	5/3/2017	Annual	5/3/2018	LTX2
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/21/2017	Annual	6/21/2018	RE1
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/27/2017	Annual	3/27/2018	MY52350166
Agilent	N9038A	MXE EMI Receiver	4/26/2017	Annual	4/26/2018	MY51210133
Agilent	E5515C	Wireless Communications Test Set	1/29/2016	Biennial	1/29/2018	GB46310798
COM-Power	AL-130R	Active Loop Antenna	6/5/2017	Annual	6/5/2018	121085
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	6/21/2017	Annual	6/21/2018	441119
Com-Power	PAM-118A	Pre-Amplifier	6/21/2017	Annual	6/21/2018	551042
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
Espec	ESX-2CA	Environmental Chamber	4/11/2017	Annual	4/11/2018	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	12/5/2016	Biennial	12/5/2018	128338
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	5/19/2017	Annual	5/19/2018	251425001
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Mini-Circuits	PWR-SEN-4RMS	USB Power Sensor	3/24/2017	Annual	3/24/2018	11210140001
PCTEST	-	EMC Switch System	6/21/2017	Annual	6/21/2018	NM2
Rhode & Schwarz	CMU200	Base Station Simulator	N/A			107826
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102133
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102135
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	11/18/2015	Biennial	11/18/2017	91052522TX
Schwarzbeck	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Note:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 10 of 84	

6.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBC.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 11 of 84	

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA730F
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM / GPRS / EDGE / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Conducted Band Edge / Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	RSS-132(5.4) RSS-133(4.1) RSS-139(4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235 27.54	RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24, 27)		PASS	Section 7.8
22.913(a.2)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	RSS-133(6.4)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
27.50(d.4)	RSS-139(6.5)	Equivalent Isotropic Radiated Power	< 1 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a) 27.53(h)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Radiated Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 12 of 84

7.2 Occupied Bandwidth

§2.1049 RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 13 of 84	




Plot 7-1. Occupied Bandwidth Plot (Cellular GSM Mode)




Plot 7-2. Occupied Bandwidth Plot (EDGE850 Mode)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 14 of 84




Plot 7-3. Occupied Bandwidth Plot (PCS GSM Mode)




Plot 7-4. Occupied Bandwidth Plot (EDGE1900 Mode)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 15 of 84




Plot 7-5. Occupied Bandwidth Plot (Cellular WCDMA Mode)



Plot 7-6. Occupied Bandwidth Plot (AWS WCDMA Mode)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 16 of 84



Plot 7-7. Occupied Bandwidth Plot (PCS WCDMA Mode)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 17 of 84

7.3 Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §22.917(a) §24.238(a) §27.53(h) RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 18 of 84	

Cellular GSM Mode




Plot 7-8. Conducted Spurious Plot (Cellular GSM Mode - Low Channel)




Plot 7-9. Conducted Spurious Plot (Cellular GSM Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 19 of 84




Plot 7-10. Conducted Spurious Plot (Cellular GSM Mode - Low Channel)




Plot 7-11. Conducted Spurious Plot (Cellular GSM Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 20 of 84




Plot 7-12. Conducted Spurious Plot (Cellular GSM Mode - Mid Channel)




Plot 7-13. Conducted Spurious Plot (Cellular GSM Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 21 of 84




Plot 7-14. Conducted Spurious Plot (Cellular GSM Mode - High Channel)




Plot 7-15. Conducted Spurious Plot (Cellular GSM Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 22 of 84




Plot 7-16. Conducted Spurious Plot (Cellular GSM Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 23 of 84	




Plot 7-17. Conducted Spurious Plot (PCS GSM Mode - Low Channel)




Plot 7-18. Conducted Spurious Plot (PCS GSM Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 24 of 84




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode - Low Channel)




Plot 7-20. Conducted Spurious Plot (PCS GSM Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 25 of 84




Plot 7-21. Conducted Spurious Plot (PCS GSM Mode - Mid Channel)




Plot 7-22. Conducted Spurious Plot (PCS GSM Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 26 of 84




Plot 7-23. Conducted Spurious Plot (PCS GSM Mode - High Channel)



Plot 7-24. Conducted Spurious Plot (PCS GSM Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 27 of 84




Plot 7-25. Conducted Spurious Plot (PCS GSM Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 28 of 84

Cellular WCDMA Mode




Plot 7-26. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-27. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 29 of 84




Plot 7-28. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)



Plot 7-29. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 30 of 84




Plot 7-30. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-31. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 31 of 84




Plot 7-32. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-33. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 32 of 84




Plot 7-34. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 33 of 84

AWS WCDMA Mode




Plot 7-35. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)



Plot 7-36. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 34 of 84




Plot 7-37. Conducted Spurious Plot (AWS WCDMA Mode - Low Channel)




Plot 7-38. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 35 of 84




Plot 7-39. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)




Plot 7-40. Conducted Spurious Plot (AWS WCDMA Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 36 of 84




Plot 7-41. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)



Plot 7-42. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)


FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 37 of 84



Plot 7-43. Conducted Spurious Plot (AWS WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 38 of 84

PCS WCDMA Mode




Plot 7-44. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)



Plot 7-45. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 39 of 84




Plot 7-46. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-47. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 40 of 84




Plot 7-48. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)




Plot 7-49. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 41 of 84




Plot 7-50. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)



Plot 7-51. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 42 of 84



Plot 7-52. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 43 of 84

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(h) RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


Per 22.917(b) 24.238(b) 27.53(h)(3) and RSS-132(5.5) RSS-133(6.5) RSS-139(6.5) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 44 of 84

Cellular GSM Mode




Plot 7-53. Band Edge Plot (Cellular GSM Mode - Low Channel)




Plot 7-54. Band Edge Plot (Cellular GSM Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 45 of 84




Plot 7-55. Band Edge Plot (PCS GSM Mode - Low Channel)




Plot 7-56. 4MHz Span Plot (PCS GSM Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 46 of 84



Plot 7-57. Band Edge Plot (PCS GSM Mode - High Channel)



Plot 7-58. 4MHz Span Plot (PCS GSM Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 47 of 84

Cellular WCDMA Mode




Plot 7-59. Band Edge Plot (Cellular WCDMA Mode - Low Channel)



Plot 7-60. Band Edge Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 48 of 84

AWS WCDMA Mode



Plot 7-61. Band Edge Plot (AWS WCDMA Mode - Low Channel)



Plot 7-62. 4MHz Span Plot (AWS WCDMA Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 49 of 84




Plot 7-63. Band Edge Plot (AWS WCDMA Mode - High Channel)




Plot 7-64. 4MHz Span Plot (AWS WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 50 of 84

PCS WCDMA Mode



Plot 7-65. Band Edge Plot (PCS WCDMA Mode - Low Channel)



Plot 7-66. 4MHz Span Plot (PCS WCDMA Mode - Low Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 51 of 84



Plot 7-67. Band Edge Plot (PCS WCDMA Mode - High Channel)



Plot 7-68. 4MHz Span Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 52 of 84

7.5 Peak-Average Ratio

§24.232(d) RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v03 – Section 5.7.1

Test Settings

1. The signal analyzer’s CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 53 of 84	




Plot 7-69. Peak-Average Ratio Plot (PCS GSM Mode)




Plot 7-70. Peak-Average Ratio Plot (EDGE 1900 Mode)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 54 of 84



Plot 7-71. Peak-Average Ratio Plot (AWS WCDMA Mode)



Plot 7-72. Peak-Average Ratio Plot (PCS WCDMA Mode)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 55 of 84

7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) 27.50(d.4) RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 56 of 84	

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 57 of 84

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: A3LSMA730F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 58 of 84

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
824.20	GSM850	V	150	344	28.81	1.50	28.16	0.654	38.45	-10.30	30.31	1.073	40.61	-10.30
836.60	GSM850	V	150	349	29.05	1.50	28.40	0.692	38.45	-10.06	30.55	1.135	40.61	-10.06
848.80	GSM850	V	150	353	29.22	1.50	28.57	0.719	38.45	-9.89	30.72	1.180	40.61	-9.89
848.80	GSM850	H	150	10	27.85	1.50	27.20	0.525	38.45	-11.26	29.35	0.861	40.61	-11.26
848.80	EDGE850	V	150	353	23.43	1.50	22.78	0.190	38.45	-15.68	24.93	0.311	40.61	-15.68

Table 7-2. ERP/EIRP (Cellular GSM)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	150	359	20.41	1.50	19.76	0.095	38.45	-18.70	21.91	0.155	40.61	-18.70
836.60	WCDMA850	H	150	353	19.43	1.50	18.78	0.076	38.45	-19.68	20.93	0.124	40.61	-19.68
846.60	WCDMA850	H	150	356	18.73	1.50	18.08	0.064	38.45	-20.38	20.23	0.105	40.61	-20.38
826.40	WCDMA850	V	150	250	19.96	1.50	19.31	0.085	38.45	-19.15	21.46	0.140	40.61	-19.15

Table 7-3. ERP/EIRP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Positioner Azimuth [degree]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1712.40	WCDMA1700	H	10	352	19.95	5.55	25.50	0.354	30.00	-4.50
1732.60	WCDMA1700	H	18	350	19.47	5.41	24.88	0.307	30.00	-5.12
1752.60	WCDMA1700	H	339	1	19.78	5.27	25.05	0.320	30.00	-4.95
1712.40	WCDMA1700	V	272	292	17.18	5.63	22.81	0.191	30.00	-7.19

Table 7-4. EIRP (AWS WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	H	150	357	27.18	4.82	32.00	1.585	33.01	-1.01
1880.00	GPRS1900	H	150	358	26.40	4.74	31.14	1.301	33.01	-1.87
1909.80	GPRS1900	H	150	359	25.58	4.68	30.26	1.061	33.01	-2.75
1850.20	GPRS1900	V	150	213	23.51	4.79	28.30	0.677	33.01	-4.71
1850.20	EDGE1900	H	150	357	23.33	4.82	28.15	0.653	33.01	-4.86

Table 7-5. EIRP (PCS GSM)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 59 of 84	

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	V	118	9	15.39	8.97	24.36	0.273	33.01	-8.65
1880.00	WCDMA1900	V	100	33	14.80	8.99	23.79	0.239	33.01	-9.22
1907.60	WCDMA1900	V	106	10	14.51	8.99	23.50	0.224	33.01	-9.51
1852.40	WCDMA1900	H	100	26	13.25	8.99	22.24	0.167	33.01	-10.77

Table 7-6. EIRP (PCS WCDMA)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 60 of 84

7.7 Radiated Spurious Emissions Measurements
§2.1053 §22.917(a) 24.238(a) 27.53(h) RSS-132(5.5) RSS-133(5.5) RSS-139(6.6)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMA730F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 61 of 84

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 5) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 6) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 62 of 84	

Cellular GSM Mode

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm


Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1648.40	H	100	360	-60.20	8.84	-51.35	-38.4
2472.60	H	100	67	-65.59	9.66	-55.94	-42.9
3296.80	H	-	-	-64.28	9.51	-54.77	-41.8

Table 7-7. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	113	179	-69.27	8.85	-60.42	-47.4
2509.80	H	115	250	-77.77	9.17	-68.60	-55.6
3346.40	H	206	47	-76.63	9.36	-67.27	-54.3
4183.00	H	-	-	-81.29	10.19	-71.10	-58.1
5019.60	H	-	-	-80.57	11.09	-69.48	-56.5

Table 7-8. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 63 of 84

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1697.60	H	117	42	-64.42	8.85	-55.58	-42.6
2546.40	H	100	340	-66.51	9.75	-56.77	-43.8
3395.20	H	-	-	-66.68	9.83	-56.86	-43.9

Table 7-9. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 64 of 84

Cellular WCDMA Mode

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	-	-	-76.52	8.99	-67.53	-54.5
2479.20	H	198	335	-56.99	9.12	-47.87	-34.9
3305.60	H	-	-	-70.15	9.37	-60.78	-47.8
4132.00	H	-	-	-68.09	9.89	-58.21	-45.2
4958.40	H	-	-	-70.23	11.24	-58.99	-46.0

Table 7-10. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	-	-	-76.09	8.85	-67.24	-54.2
2509.80	H	198	335	-58.80	9.17	-49.64	-36.6
3346.40	H	-	-	-70.40	9.36	-61.04	-48.0
4183.00	H	123	350	-67.43	10.19	-57.24	-44.2
5019.60	H	-	-	-69.65	11.09	-58.56	-45.6

Table 7-11. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 65 of 84	

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	-	-	-76.05	8.70	-67.35	-54.4
2539.80	H	123	346	-57.09	9.26	-47.83	-34.8
3386.40	H	-	-	-69.17	9.44	-59.73	-46.7
4233.00	H	105	344	-67.04	10.43	-56.60	-43.6
5079.60	H	-	-	-69.30	10.90	-58.40	-45.4
5926.20	H	-	-	-67.14	11.24	-55.90	-42.9

Table 7-12. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 66 of 84

AWS WCDMA Mode

OPERATING FREQUENCY: 1712.40 MHz
 CHANNEL: 1312
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3424.80	H	178	241	-68.16	9.52	-58.64	-45.6
5137.20	H	-	-	-72.55	10.81	-61.74	-48.7
6849.60	H	-	-	-67.66	10.84	-56.82	-43.8

Table 7-13. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)

OPERATING FREQUENCY: 1732.60 MHz
 CHANNEL: 1413
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3465.20	H	178	245	-67.55	9.59	-57.96	-45.0
5197.80	H	-	-	-72.56	10.83	-61.72	-48.7
6930.40	H	-	-	-67.99	10.90	-57.09	-44.1

Table 7-14. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 67 of 84

OPERATING FREQUENCY: 1752.60 MHz
 CHANNEL: 1513
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3505.20	H	174	250	-68.18	9.67	-58.51	-45.5
5257.80	H	-	-	-72.58	10.97	-61.62	-48.6
7010.40	H	-	-	-68.37	11.00	-57.37	-44.4

Table 7-15. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1513)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 68 of 84	

PCS GSM Mode

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	V	202	26	-66.59	9.83	-56.76	-43.8
5550.60	V	146	43	-60.95	10.97	-49.97	-37.0
7400.80	V	178	338	-61.06	10.72	-50.34	-37.3
9251.00	V	146	335	-63.52	12.32	-51.20	-38.2
11101.20	V	-	-	-64.58	12.94	-51.64	-38.6

Table 7-16. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	V	178	40	-66.82	9.62	-57.20	-44.2
5640.00	V	135	35	-59.93	11.12	-48.81	-35.8
7520.00	V	158	11	-64.15	11.00	-53.15	-40.1
9400.00	V	-	-	-64.52	12.15	-52.37	-39.4
11280.00	V	-	-	-64.95	13.22	-51.73	-38.7

Table 7-17. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 69 of 84	

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	V	173	44	-64.45	9.23	-55.21	-42.2
5729.40	V	169	29	-63.21	11.29	-51.92	-38.9
7639.20	V	153	7	-65.05	11.29	-53.76	-40.8
9549.00	V	169	10	-63.60	12.22	-51.39	-38.4
11458.80	V	-	-	-64.67	13.24	-51.43	-38.4

Table 7-18. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 70 of 84	

PCS WCDMA Mode

OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	H	-	-	-72.95	9.72	-63.23	-50.2
5557.20	H	-	-	-71.83	10.99	-60.85	-47.8
7409.60	H	-	-	-67.14	10.79	-56.35	-43.4

Table 7-19. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	-	-	-72.91	9.50	-63.41	-50.4
5640.00	H	-	-	-72.01	11.16	-60.85	-47.9
7520.00	H	-	-	-67.79	11.03	-56.76	-43.8

Table 7-20. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 71 of 84

OPERATING FREQUENCY: 1907.60 MHz
 CHANNEL: 9538
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	H	-	-	-71.16	9.30	-61.86	-48.9
5722.80	H	-	-	-72.46	11.33	-61.13	-48.1
7630.40	H	-	-	-68.48	11.26	-57.22	-44.2

Table 7-21. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 72 of 84

7.8 Frequency Stability / Temperature Variation
§2.1055 §22.355 §24.235 §27.54 RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, RSS-132 and RSS-133, the frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency. For Part 24 Part 27 and RSS-139, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-D-2010

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMA730F	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 73 of 84

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 190
 REFERENCE VOLTAGE: 4.40 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.40	+ 20 (Ref)	836,599,743	-257	-0.0000307
100 %		- 30	836,600,021	21	0.0000025
100 %		- 20	836,600,033	33	0.0000039
100 %		- 10	836,599,806	-194	-0.0000232
100 %		0	836,600,451	451	0.0000539
100 %		+ 10	836,600,040	40	0.0000048
100 %		+ 20	836,600,080	80	0.0000096
100 %		+ 30	836,600,202	202	0.0000241
100 %		+ 40	836,600,020	20	0.0000024
100 %		+ 50	836,600,422	422	0.0000504
BATT. ENDPOINT	3.67	+ 20	836,599,969	-31	-0.0000037

Table 7-22. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 74 of 84

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)




Figure 7-8. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 75 of 84

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz
 CHANNEL: 4183
 REFERENCE VOLTAGE: 4.40 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.40	+ 20 (Ref)	836,599,891	-109	-0.0000130
100 %		- 30	836,599,908	-92	-0.0000110
100 %		- 20	836,600,152	152	0.0000182
100 %		- 10	836,600,143	143	0.0000171
100 %		0	836,599,968	-32	-0.0000038
100 %		+ 10	836,599,763	-237	-0.0000283
100 %		+ 20	836,600,193	193	0.0000231
100 %		+ 30	836,600,119	119	0.0000142
100 %		+ 40	836,599,926	-74	-0.0000088
100 %		+ 50	836,599,976	-24	-0.0000029
BATT. ENDPOINT	3.67	+ 20	836,600,008	8	0.0000010

Table 7-23. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 76 of 84

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)




Figure 7-9. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 77 of 84

Frequency Stability / Temperature Variation
§2.1055 §27.54 RSS-139(6.4)

OPERATING FREQUENCY: 1,732,600,000 Hz
 CHANNEL: 1413
 REFERENCE VOLTAGE: 4.40 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.40	+ 20 (Ref)	1,732,599,881	-119	-0.0000069
100 %		- 30	1,732,599,902	-98	-0.0000057
100 %		- 20	1,732,599,865	-135	-0.0000078
100 %		- 10	1,732,599,968	-32	-0.0000018
100 %		0	1,732,599,975	-25	-0.0000014
100 %		+ 10	1,732,599,999	-1	-0.0000001
100 %		+ 20	1,732,599,684	-316	-0.0000182
100 %		+ 30	1,732,600,089	89	0.0000051
100 %		+ 40	1,732,600,048	48	0.0000028
100 %		+ 50	1,732,600,084	84	0.0000048
BATT. ENDPOINT	3.67	+ 20	1,732,599,992	-8	-0.0000005

Table 7-24. Frequency Stability Data (AWS WCDMA Mode – Ch. 1413)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 78 of 84

Frequency Stability / Temperature Variation
§2.1055 §27.54 RSS-139(6.4)




Figure 7-10. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1413)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 79 of 84	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 4.40 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.40	+ 20 (Ref)	1,879,999,633	-367	-0.0000195
100 %		- 30	1,880,000,099	99	0.0000053
100 %		- 20	1,879,999,779	-221	-0.0000118
100 %		- 10	1,880,000,064	64	0.0000034
100 %		0	1,879,999,921	-79	-0.0000042
100 %		+ 10	1,880,000,371	371	0.0000197
100 %		+ 20	1,879,999,862	-138	-0.0000073
100 %		+ 30	1,880,000,266	266	0.0000141
100 %		+ 40	1,880,000,151	151	0.0000080
100 %		+ 50	1,879,999,973	-27	-0.0000014
BATT. ENDPOINT	3.67	+ 20	1,879,999,731	-269	-0.0000143

Table 7-25. Frequency Stability Data (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 80 of 84

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)




Figure 7-11. Frequency Stability Graph (PCS GSM Mode – Ch. 661)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 81 of 84	

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 9400
 REFERENCE VOLTAGE: 4.40 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.40	+ 20 (Ref)	1,880,000,179	179	0.0000095
100 %		- 30	1,880,000,335	335	0.0000178
100 %		- 20	1,879,999,989	-11	-0.0000006
100 %		- 10	1,880,000,119	119	0.0000063
100 %		0	1,880,000,076	76	0.0000040
100 %		+ 10	1,879,999,601	-399	-0.0000212
100 %		+ 20	1,879,999,784	-216	-0.0000115
100 %		+ 30	1,880,000,247	247	0.0000131
100 %		+ 40	1,880,000,141	141	0.0000075
100 %		+ 50	1,880,000,203	203	0.0000108
BATT. ENDPOINT	3.67	+ 20	1,880,000,063	63	0.0000034

Table 7-26. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset			Page 82 of 84

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)





Figure 7-12. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset		Page 83 of 84

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA730F** complies with all the requirements of Part 22, 24, & 27 of the FCC Rules and RSS-132, RSS-133, RSS-139 of the Industry Canada rules.

FCC ID: A3LSMA730F		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1710050266-02.A3L	Test Dates: 10/5-11/8/2017	EUT Type: Portable Handset	Page 84 of 84	